TaxaHFE: A machine learning approach to collapse microbiome datasets using

taxonomic structure

Authors: Andrew Oliver[1], Matthew Kay[2], Danielle G. Lemay [1,3,4]

Affiliations:

[1]USDA-ARS Western Human Nutrition Research Center, 430 West Health Sciences Dr.,

Davis, CA, 95616

[2]Independent Researcher

[3]Department of Nutrition, University of California, Davis, One Shields Ave., Davis, CA, 95616

[4]Genome Center, University of California, One Shields Ave., Davis, CA, 95616

*Corresponding author, 430 West Health Science Dr. Davis, CA 95616,

danielle.lemay@usda.gov, (530) 752-4748

ABSTRACT

Motivation: Biologists increasingly turn to machine learning models not just to predict, but

to explain. Feature reduction is a common approach to improve both performance and

interpretability of models. However, some biological data sets, such as microbiome data,

are inherently organized in a taxonomy, but these hierarchical relationships are not

leveraged during feature reduction. We sought to design a feature engineering algorithm to

exploit relationships in hierarchically organized biological data.

Results: We designed an algorithm, called TaxaHFE, to collapse information-poor features

into their higher taxonomic levels. We applied TaxaHFE to six previously published

datasets and found, on average, a 90% reduction in the number of features (s.d = 5.1%)

compared to using the most complete taxonomy. Using machine learning to compare the

most resolved taxonomic level (i.e., species) against TaxaHFE-preprocessed features,

models based on TaxaHFE features achieved an average increase of 3.47% in receiver

operator curve area under the curve (ROC- AUC). Compared to other hierarchical feature

engineering implementations, TaxaHFE introduces the novel ability to consider both

categorical and continuous response variables to inform the feature set collapse.

Importantly, we find TaxaHFE's ability to reduce hierarchically organized features to a more

information-rich subset increases the interpretability of models.

Availability and Implementation: TaxaHFE is available as a Docker image and as R code at

https://github.com/aoliver44/taxaHFE.

INTRODUCTION

With the cost of DNA sequencing continuing to drop faster than compute power

increases (Wetterstrand) the analysis of large data sets remains a bottleneck in biological

research. One method for analysis is machine learning (ML) (Choi *et al.*, 2022), which is a

blanket term that refers to computer algorithms designed to find patterns in data, iteratively

optimizing performance without human input. While ML methods represent a suite of

powerful and sensitive tools, they can suffer from a problem present in many human -omic

studies: many features (i.e., microbial taxa) describing relatively few samples.

Mathematician Richard Bellman referred to this problem as the "curse of dimensionality"

(Bellman, 2003). Practically speaking, too many features can result in "overfitting", leading

to poor generalizability of the model. For this reason, implementing methods to reduce

the size of data while retaining its important features can improve both the speed, the

generalizability, and interpretability of the data.

Feature engineering, or the set of preprocessing steps done to data prior to ML

model evaluation, can help address problems imposed by high-dimensional data. While

illustrating the totality of feature engineering is beyond the scope of this paper, some

general examples include scaling or normalizing features, removing low variance features,

collapsing highly correlated features, sophisticated methods for selecting subsets of

features, and collapsing features into principal coordinate space. The goal of several of

these methods is to reduce the feature space (dimensionality) and produce a highly

discriminatory set of variables with respect to a response of interest. However, in biology

models are not just used to make predictions, but to *explain*. This means that the reduced

feature set needs to also be interpretable, rather than alternate ordinations, such as

principal components.

Some biological data, such as microbiome and dietary data, can be represented using

hierarchical structures (Jacobs and Steffen, 2003; Johnson *et al.*, 2019; Choi *et al.*, 2022).

Taxonomic assignments have long been used to identify microorganisms. This taxonomy is

usually represented by a hierarchical classification scheme, whereby the ancestral level is the

most general group, followed by increasingly specific grouping rules. More recently,

researchers have begun to represent consumed foods in a similar taxonomic way (Johnson *et*

al., 2019). More than merely identifying information, taxonomy represents relatedness,

reflecting ecological patterns (for microorganisms) (Bevilacqua *et al.*, 2021) or complex

admixtures of similar chemicals and nutrients (for food) (Johnson *et al.*, 2019). While data with

hierarchical structure presents many different levels by which to analyze a trait or response,

researchers generally choose to collapse these data to a single level for ease of analysis

(i.e., analyzing microbiome data at the family-level) (Kleine Bardenhorst *et al.*, 2021). This

can be a useful strategy, especially if the trait/response of interest is known to be conserved

at a certain phylogenetic depth which can be approximated by a taxonomic level (Martiny *et al.*,

2015). Even without knowledge of a conserved phylogenetic depth *a priori*, tools exist to

identify the average phylogenetic depth of a trait/response; however, many of these tools

require a phylogenetic tree as input (Martiny *et al.*, 2012). Often there is not *a priori* information

available, and summarizing taxa to a specific level is weakly justified. Even more, if the data

was summarized at a taxonomic level, but the response to a treatment is conserved at a

different taxonomic level, it could lead to a false conclusion that, for example, the microbiome

does not respond to a treatment of interest. A systematic review of current practices for the

analysis of human microbiome data revealed a lack of consensus about which taxonomic level

to study (Kleine Bardenhorst *et al.*, 2021). Why not let information theory decide?

Here we introduce a method for hierarchical feature engineering (HFE) to

dynamically collapse hierarchical data purely based on taxonomic relationships and

information gain. Our algorithm, TaxaHFE, does not require the user to have knowledge *a*

priori regarding the taxonomic level of conservation for a given trait. Rather, it seeks to

maximize the information contained at various taxonomic levels while simultaneously

reducing redundancy in the feature space. As a proof of concept, we apply TaxaHFE to

microbiome data and compare it to an existing hierarchical feature engineering algorithm

(Oudah and Henschel, 2018), assessing feature reduction and downstream ML

performance. Additionally, we show that TaxaHFE's utility extends to other hierarchically

organized data by applying our algorithm to hierarchical food data represented by

taxonomic trees.

METHODS

TaxaHFE algorithm

The algorithm (Figure 1) can broadly be broken down into two main sections: 1) the

creation of a taxonomic tree representing the hierarchical data, and 2) the competitions of each

taxon in a post-order tree traversal. Within the competition section, four major steps occur: 1) a

feature abundance and prevalence filter, 2) a correlation competition between parent and child

taxa, 3) a machine learning step to determine information content of the taxa from the previous

step, and 4) one additional machine learning step on all the "winning" features. These steps are

graphically represented in Figure 1 and algorithmically outlined below.

1. Build tree

a. Generate a node x in the tree **T** for each taxon

b. Store the abundance values for the taxon on x, as well as calculating whether the

107   abundances meet minimum mean abundance and prevalence thresholds (Figure

108   1, Step 1)

109   c. To fill in any missing abundance data, traverse the tree **T** in post-order,

110   generating a missing abundance vector a_n for a node x_n as the vector sum of all

111   abundance vectors from the direct descendants $C_n = children(x_n)$, where a_c is

112   the abundance vector of child node c.

$$a_n = \sum_{c \in C_n} a_c$$

114 **2. Compete tree**

115   Traverse the tree **T** in post-order, considering every subtree $\mathbf{T}_n$ using the following steps.

116   a. If $root(\mathbf{T}_n)$ has not met the minimum mean abundance and prevalence

117   thresholds, this taxon will not be considered further (Figure 1, Step 1)

118   b. If $root(\mathbf{T}_n)$ is a leaf node, mark "winner" and proceed to the next subtree

119   i. Note: Being marked a "winner" is temporary, and any "winner" in a

120   particular subtree T_n at level l will be reconsidered at level $l - 1$ during

121   the traversal.

122   c. Traverse T_n, generating a set $\mathbf{N_0}$ of nodes previously marked as "winner". If a

123   node x is marked "winner", no descendent nodes are considered.

124   d. Generate a subset $\mathbf{N_{nc}} \in \mathbf{N_0}$, containing each node x in $\mathbf{N_0}$ whose abundance

125   vector a_x is not correlated with the abundance vector a_n of $root(\mathbf{T}_n)$, above the

126   specified threshold t (Figure 1, Step 2). For all nodes $\mathbf{N_0} - \mathbf{N_{nc}}$, remove the

127   "winner" designation:

$$\mathbf{N_{nc}} = \{x \mid x \in \mathbf{N_0}, corr(a_n, a_x) < t\}$$

128   e. Using the set of abundance vectors $\mathbf{A} = \{a_n, a_{nc1}, a_{nc2}, \dots\}$ (from $root(\mathbf{T}_n)$ and

129   the non-correlated nodes $\mathbf{N_{nc}}$) and response variables $\mathbf{M}$ (from the metadata

130   input), fit a random forest model to determine the taxa importances to $\mathbf{M}$

131   calculated using Gini impurity-corrected scores (Nembrini *et al.*, 2018) and

132   generating a vector of scores $\mathbf{S}$ (Figure 1, Step 3).

$$\mathbf{S} = RFgi(\mathbf{A}, \mathbf{M})$$

133   Any node x with a score s_x greater than $root(\mathbf{T}_n)$ score s_n is marked "winner"

$$\mathbf{N_w} = \{x \mid x \in N_0, s_x > s_n\}$$

134   Otherwise, if the score of $root(\mathbf{T}_n)$ is the highest value, only it is selected

$$\mathbf{N_w} = \{root(\mathbf{T}_n)\}$$

All other nodes $\mathbf{N_{nc}} - \mathbf{N_w}$ have the "winner" designation removed, as well as

$root(\mathbf{T}_n)$ if $root(\mathbf{T}_n) \notin \mathbf{N_w}$.

Traversal will be stopped at a level l, where $l \geq 2$, such that $level(root(\mathbf{T_n})) \geq$

l for all competed subtrees $\mathbf{T_c}$. This prevents $root(\mathbf{T_0})$ (that contains the sum of all

abundance vectors) from being included in the competition, and also allows for the

preservation of taxonomic information at a definable level. Because they have not

been traversed, any node x where $level(x) < l$ is not considered in the algorithm

and cannot be marked "winner".

The result of this is a set of distinct nodes $\mathbf{N_w}$, marked as "winner" across all

competed subtrees $\mathbf{T_c}$ having $root(\mathbf{T_0})$ (the root of the full tree) as the only

common ancestor. An optional final random forest model (Figure 1, Step 4) is then

fit using the set of abundance vectors $\mathbf{A_W}$ from $\mathbf{N_W}$, and the response variables $\mathbf{M}$.

$$\mathbf{S_W} = RFgi(\mathbf{A_W}, \mathbf{M})$$

149   The final feature set N_f is the set of nodes x with scores s_x greater than zero and

150   the average score Gini impurity-corrected scores of N_f:

$$N_f = \{x | x \in N_W, s_x > 0, s_x > mean(S_W)\}$$

Input data

The input data to TaxaHFE is (1) a flat file (comma- or tab-delimited) with a column

labeled "clade_name" containing the taxonomic features with subsequent columns as

samples containing numeric feature abundances and (2) a response variable flat file (Figure

1). The levels of the features within the input data should be delineated by a pipe symbol

("|"). For example, if the input data are microbiome features, the features should be

Kingdom|Phylum|Class|…|last level. The taxonomic features can contain any number of

levels present. The sample column names must be unique for each column in the input file

and match a column in the response variable file, which also must contain a column

encoding the response of interest (either categorical or continuous).

Implementation

A reference implementation of this algorithm was written in R as part of development.

The implementation uses the data.tree package (v1.0.0) (Glur *et al.*, 2020) to

represent the hierarchical structure of input taxa, as well as for the post-order traversal of

the data used in several places. Data.tree parses the input file column by using the pipe

symbol ("|") found in the input data, described above. Once imported into TaxaHFE, four

broad steps occur, as described in the algorithm above: 1) feature abundance and

prevalence filters, 2) a correlation competition between parent taxon and child taxa, 3) a

random forest competition selecting the most informative (relative to the response variable)

features from the previous step and 4) and an optional final "super filter" (SF) random forest

of all the taxa that have survived from steps 1-3 (Figure 1). TaxaHFE applies reasonable

defaults to these steps. For instance, by default, features are only considered if they have a

minimum mean feature abundance of 0.01% and a minimum feature prevalence of 1%. Both

filters can be set to zero or any other number, depending on the scale of the input data.

Additionally, if the user is predicting a rare class (i.e., class imbalance), if may be prudent to

keep rare features by setting these filters to zero. For the correlation competition, a child

taxon abundance must be correlated with the parent abundance at less than 0.95 Pearson

correlation to pass to step three. Finally, both step three and step four use random forests

(RF) to report back Gini impurity corrected scores per feature, indicating the feature's ability

to predict the user-supplied response variable. These RF models are built and rebuilt 40

times by default, averaging out the Gini impurity scores per feature. The RF model fitting is

done using the ranger package (v0.14.1) (Wright and Ziegler, 2017), including the ability to

distinguish between numeric and factor response variable types in the input metadata.

Randomness is seeded in the implementation using system time, but an allowance is made

for defining a specific random seed. This randomness influences the outcome of the RF

competitions run by the ranger package. For ease of use, the implementation has been

released on GitHub and additionally packaged into a Docker container, allowing it to be run

reliably in a variety of computing environments.

Output data

The outputs of TaxaHFE are individual files of summarized original abundances for each

hierarchical level and two files containing either the TaxaHFE or the TaxaHFE + SF selected

features alongside the response variable.

Downstream machine learning

The output of TaxaHFE is a reduced feature set, which may increase the performance

of predictive analyses such as machine learning. To test this, we analyzed hierarchical

datasets using a machine learning pipeline based around the Tidymodels package (v1.0.0)

(Kuhn and Wickham, 2020) in R. Input data was split using 70% data for training and

hyperparameter tuning, and 30% was used for testing. Inside the training split, 10-fold

repeated (3x) cross validation was used for Bayesian-search hyperparameter tuning. A gentle

correlation feature reduction step was also introduced within each cross-validation fold, yet at

0.95 Pearson (the same as TaxaHFE's internal correlation filter), it likely had minimal effect

on ML performance. The search space was limited to 80 different hyperparameter

combinations (optimizing mtry and minimum node size) or ten minutes of search time,

whichever finished first. Bayesian hyperparameter search was allowed to preemptively end if

the scoring metric was not improved after ten iterations. The metric optimized was balanced

accuracy for classification or mean absolute error for regression. The best model was fit to

the left-out test data and assessed using area under the receiver operator curve (ROC-AUC),

balanced accuracy, and Cohen's kappa (Kuhn *et al.*, 2023). For multi-class models, the Hand-

Till ROC-AUC (Hand and Till, 2001) and macro-averaged balanced accuracy was used. Each

ML model was run using ten different random seeds to reduce stochasticity introduced from

different train-test splits. To determine the importance of features, the package fastshap

(v0.0.7) (Greenwell, 2021; Štrumbelj and Kononenko, 2014) was used. Briefly, the best model

was fit to the entire input data, and Shapley values were calculated for each feature. The R

package ShapViz (v0.4.1) (Mayer and Stando, 2023) was used to plot these values.

Evaluation of TaxaHFE

Six previously published microbiome datasets (Lloyd-Price *et al.*, 2019; Mars *et al.*,

2020; Muller *et al.*, 2022; Wang *et al.*, 2020; Franzosa *et al.*, 2019; Erawijantari *et al.*, 2020;

Oliver *et al.*, 2022) and a dietary tree dataset (Kable *et al.*, 2022) were used to assess

TaxaHFE (Supplemental Table 1). For the microbiome datasets, TaxaHFE parameters were

set to minimum mean feature abundance of 0.01% and minimum feature prevalence of 1%.

The correlation threshold was set to 0.95, and nperm = 40 (defaults for TaxaHFE) and the

random seed was set to 42. For the food dataset, the abundance filter was changed to 0.

Each dataset was summarized at either the order, family, genus, or species level (using

TaxaHFE, which applies the prevalence and abundance filters prior to writing the summary

files). Additionally, the species summarized microbiome data was analyzed using a previously

published algorithm (hfe_algorithm.py (Oudah and Henschel, 2018)), using two correlation

cutoffs: the program's default 0.7 and 0.95 (matching TaxaHFE's default correlation filter).

These summarized and TaxaHFE-selected data were used in machine learning models to

predict response variables associated with each study (Supplemental Table 1), as described

above. To test whether ML performance was significantly different across different feature

reduction methods, we used a linear mixed-effects model (from the R package nlme v3.1- 157

(Pinheiro *et al.*, 2019)), with study*level as a fixed effect and the random seed as a random

effect. Quantile-quantile plots were investigated for normality of residuals. Study-specific

models were also built like the above model, without the study interaction term. Finally, we

performed estimated marginal means (EMMs) post-hoc tests using the emmeans package

(v1.8.8) (Lenth *et al.*, 2018) with Bonferroni adjusted p-values. We also analyzed the features

compositionally by measuring the variance explained by the features selected using

PERMANOVA models. To do so, we used the adonis(method = "bray", nperm = 999)

function from the vegan (v2.6-4) package (Oksanen *et al.*, 2019) in R. For comparative

purposes, Lefse (Segata *et al.*, 2011) was run on Galaxy (http://galaxy.biobakery.org/) using

default parameters, and Boruta was run using the Boruta package (v8.0.0) (Kursa and

Rudnicki, 2010) in R using default parameters.

Software and data availability

The code for TaxaHFE, along with installation instructions and example inputs, can be

found on GitHub (https://github.com/aoliver44/taxaHFE). TaxaHFE version 2.0 was used for all

analyses. The ML pipeline to assess the performance of TaxaHFE can also be found on

GitHub (https://github.com/aoliver44/nutrition_tools). Location of datasets used for comparisons

can be found in Supplemental Table 1. We downloaded five of the microbiome datasets from a

microbiome-metabolome dataset collection (Muller *et al.*, 2022).

RESULTS

TaxaHFE improves feature reduction compared to alternative taxonomically informed

methods.

We initially investigated how well TaxaHFE performs compared to summarizing

microbiome datasets to higher taxonomic levels (order (L4) to species (L7)), or when using a

previously published hierarchical feature engineering program (Oudah_70 and Oudah_95). In

all six previously published studies, the dimensional reduction produced by TaxaHFE (±

super filter, SF) selects features which, when used as input in machine learning models, result

in the higher mean ROC-AUC scores compared to data summarized at specific taxonomic

levels, or a previously published HFE algorithm (Figure 2A, Supplemental Figure 1,

Supplemental Table 2). The mean ROC-AUC for TaxaHFE (+SF) across all studies assessed

was 0.901 (s.d. = 0.071) followed by TaxaHFE (-SF) (0.897, s.d. = 0.071). Moreover,

TaxaHFE (+SF) produces the best models for 4/6 studies when assessed using balanced

accuracy (Figure 2B, Supplemental Table 2) and 4/6 studies using mean Cohen's kappa

(Figure 2C, Supplemental Table 2). In the other two cases, TaxaHFE preprocessed models

were not significantly different from the best models produced (Supplemental Figure 1).

In addition to performance improvements, TaxaHFE (+SF) utilizes less features than

comparable methods (Figure 2D). Models utilizing species-level features (after abundance

and prevalence filters, see methods) utilized 469 (s.d. = 97) species on average, compared

with the 45 (s.d. = 22) taxonomic features used by TaxaHFE (+SF) on average.

Additionally, TaxaHFE (+SF) selects 95 less features on average compared to a previously

published HFE algorithm by Oudah and Henschel (Oudah and Henschel, 2018). Importantly,

TaxaHFE's reduced feature set generally captures more variance in community composition

compared to existing hierarchical feature engineering methods or summarizing to a specific

taxonomic level (Figure 2E).

TaxaHFE can reduce features for both categorical and continuous predictions.

A previous effort towards hierarchical feature engineering produced an algorithm

which maximized a performance metric with respect to a categorical variable (Oudah and

Henschel, 2018). We designed TaxaHFE to handle both categorical and continuous

variables. To illustrate this, we used normalized antibiotic resistance gene abundance as a

continuous or categorical response variable for selecting taxa using previously published

data (Oliver *et al.*, 2022). Specifically, we only analyzed samples in the highest or lowest

ARG abundance quartile. Using categorical ARG abundance (low quartile vs high quartile),

TaxaHFE, with or without the default super-filter, selected 4 and 14 taxon features

respectively. Using these features as input to a random forest classification model

predicting categorical ARG abundance (high vs low) resulted in mean ROC-AUC values of

0.941 (+SF) and 0.952 (-SF) (Figure 3). Features summarized at the L4 level performed

slightly better in classification models than TaxaHFE+SF (L4 (order) ROC-AUC: 0.943). The

previously published HFE algorithm by Oudah and Henschel (Oudah and Henschel, 2018)

selected 134 features, a considerable increase from TaxaHFE (+SF) 4 features. Even with

far fewer features, TaxaHFE (+SF) achieved better performance metrics compared to

models built with Oudah engineered features (ROC-AUC: TaxaHFE+SF, 0.941; Oudah_70,

0.915).

When analyzing continuous ARG abundance, TaxaHFE, with or without the default

super-filter, selected 6 and 18 taxon features respectively. Using these features as input to a

random forest regression model predicting continuous ARG abundance resulted in mean R^2

(coefficient of determination) values of 0.644 (+SF) and 0.649 (-SF) (Figure 3C). Like the

categorical example, TaxaHFE+SF performed slightly behind the L4 model (by mean R^2

performance), which used L4 (order) summarized data (0.645), yet a post-hoc test showed

these differences were not significant, and the L4 model used far more features than

TaxaHFE+SF (36 versus 6). No data is shown for the Oudah and Henschel algorithm as that

algorithm does not support continuous outcome variables. In summary, TaxaHFE maximized

performance while minimizing features for both categorical and continuous outcomes.

Both the categorical and continuous example resulted in models utilizing similar

features (Figure 3D, E). Compared to a model built using Level 7 features (species), TaxaHFE

identified higher taxonomic levels to discriminate categorical ARG abundance. These higher

taxonomic levels, such as the class *Gammaproteobacteria* and family *Streptococcaceae,*

resulted in nearly   an order of magnitude higher SHAP values, suggesting TaxaHFE identified

features that were more influential to model predictions than models built using species level

data.

TaxaHFE also works on hierarchically organized diet data

Since TaxaHFE works with hierarchical features, we sought to examine its utility

beyond microbiome data. Dietary data represented as food trees could also be a useful

feature set to apply hierarchical feature engineering. To test this, we utilized a previously

published dietary food tree and tested TaxaHFE's ability to select features which explain

average fiber intake (Baldiviez *et al.*, 2017). After prevalence and abundance filters, 456

foods were assessed. TaxaHFE+SF selected 4 features as the most informative for

predicting average fiber intake, nearly a 99% reduction from the 456 features used as input.

When assessed using the concordance correlation coefficient, a measure of both correlation

and accuracy,   Bonferroni corrected EMM post-hoc test revealed that TaxaHFE+SF

performed significantly better than summarized features in a random forest ($p < 0.05$)

(Figure 4A). We next used Shapley values to determine which features were most important

to a model built with TaxaHFE+SF (Figure 4B) compared to a model built with Level 7

features (Figure 4C). The most important features identified by TaxaHFE+SF were "other

fruits" (Level 2), which include high fiber staples such as berries and avocados, and "dry

beans peas other legumes nuts and seeds" (Level 1) (Figure 4B). In contrast, the predictive

model performance is lower for Level 7 (Figure 4A) and the SHAP values, which indicate the

magnitude of importance, are also lower (Figure 4C) than those identified by TaxaHFE+SF

(Figure 4B). In summary, the use of TaxaHFE improved both model performance and

feature importance when used with dietary data arranged in food trees.

DISCUSSION

A common practice in microbiome analyses is the summarization of abundance

data at a single taxonomic level. In one review examining 419 microbiome studies, the

authors found that the genus level was the most commonly summarized taxonomic level,

followed by analysis at the phylum level (Kleine Bardenhorst *et al.*, 2021). However, the

discernable variation in microbial composition with respect to a trait or response is strongly

dependent on the taxonomic level analyzed (Martiny *et al.*, 2015). Thus, an analysis at a

single taxonomic level, especially at a level which is not optimized for the trait or response

of interest, could lead investigators to incorrectly conclude the absence of a relationship

between microbiome and response. Our results support this; to explain ARG abundance, a

model built using species level data would perform significantly worse than a model built

using order level or TaxaHFE preprocessed data (Figure 3).

Here we propose an algorithm for the feature engineering of hierarchically

organized data, particularly microbiome abundance data or dietary data represented using

food trees. Currently, few algorithms exist to reduce the high dimensionality found in

microbiome data with respect to the taxonomic structure inherent in microbial features.

Oudah and Henschel (Oudah and Henschel, 2018) provided an excellent implementation;

however, the Oudah algorithm is unable to handle: 1) a continuous response variable 2) non-

bacterial features and 3) abundances that are not relative abundances. At the core of

TaxaHFE is a random forest, which is a particularly capable ML algorithm for handling both

continuous and categorical response variables. Moreover, there is no need for specific

feature names; TaxaHFE bases its understanding of hierarchical levels purely based on the

use of a separator ("|") between levels. As such, any hierarchically organized data can be

used as input.

One important shared logic of both the Oudah algorithm and our algorithm is the

use of the parent taxon as the taxon to "beat" in the competitions. This decision was inspired

by an early implementation of hierarchical feature engineering (Ristoski and Paulheim,

2014), for which the goal of the algorithm was to choose the most valuable features from the

highest taxonomic levels possible. Indeed, when the goal is feature reduction, and the parent

taxon and child taxa contain redundant information relative to a response of interest,

choosing the parent taxon results in a feature that is likely representative of the child taxa in

some way. The reverse is not necessarily true.

Other feature reduction programs such as Lefse (based on linear discriminant

analysis) (Segata *et al.*, 2011) and Boruta (based on random forests) (Kursa and Rudnicki,

2010) are often used, particularly with microbiome data. However, when all taxonomic

levels are supplied to these programs, these programs often choose features that carry

redundant abundance information. For example, when using Lefse to select features based

the Erawijantari study, the output contained *Lactobacillales*, *Streptococcaceae*, and

Streptococcus (Supplemental Figure 2A), which are all directly related features that carry

nested but redundant feature abundance information (i.e., the abundance of *Streptococcus*

is contained within the abundance of *Streptococcaceae*). And while Boruta performs slightly

better than TaxaHFE in almost every case (Supplemental Figure 2B), it exhibits similar

behavior as Lefse, choosing features with redundant feature abundance information

(Supplemental Figure 2C). For some types of analyses this behavior is desirable. However,

for explicit feature reduction we suggest that TaxaHFE's method of removing overlapping

features is usually preferable to aid interpretation of biological data.

Importantly, TaxaHFE preprocessed data improves the performance of machine

learning models, especially compared to models produced using the lowest taxonomic

levels available (e.g., species). This is perhaps not altogether surprising; indeed, a

common observation across many microbiome studies is the highly personalized nature of

microbiomes (Oliver *et al.*, 2021). It stands to reason then, that while utilizing the most

resolved taxonomic data might best highlight differences person to person, it will often

mask more generalizable microbial responses within heterogeneous cohorts. Hierarchical

feature engineering allows for the capture of these more generalizable responses,

concomitantly increasing the accuracy of machine learning models in the process. We

note, however, that if the goal is a generalizable model, using feature engineering inside of

a cross-validation strategy is important to avoid data leakage (Aldehim and Wang, 2017).

We briefly examined the similarity of features selected across k = 3-fold partitions of the

data and found a high amount of dissimilarity (83%, data not shown) among the features

selected in each fold. One reason for this variability is the small number of samples in the

published studies we used to assess TaxaHFE (mean 262 samples). Like other feature

reduction tools, we expect the performance of TaxaHFE will suffer when samples are

limited.

Overall, perhaps the most important aspect of TaxaHFE is the gains in

interpretability. In the microbiome example of the status quo method of using the lowest level

taxa (Figure 3F), it is difficult to interpret the meaning of the ten species selected, each with a

very low SHAP value. But with TaxaHFE (Figure 3D and 3E), it is readily apparent that the

class *Gammaproteobacteria* and family *Streptococcaceae* are top predictors of antimicrobial

resistance in the human gut microbiome and their SHAP values are an order of magnitude

higher. The relationship between *Gammaproteobacteria* and antibiotic resistance has been

shown previously in a Hi-C study linking ARGs to their microbial hosts (Stalder *et al.*, 2019).

Moreover, when considered together TaxaHFE selected features also appear to explain more

compositional variance than using a single taxonomic level (Figure 2E). In the diet example

(Figure 4C), the model based on the lowest taxonomic level is again difficult to interpret, with

456 individual food items (e.g., apples, bananas, avocados, oranges, olive oil, salty corn snacks, flax seeds, etc.) predictive of fiber intake. TaxaHFE reports low intake of other_fruits (non- citrus), legumes/nuts/seeds, uncooked cereals, and vegetables of low fiber intake. The results from TaxaHFE suggest, for example, that it is the entire class of legumes/nuts/seeds that is predictive, not just flax seeds, which is more reasonable. For this reason, dietary data is traditionally summarized and reported at the highest taxonomic level (e.g., fruits, vegetables, dairy, meat, etc.). However, nuances like the association of low intake of uncooked cereals with low fiber intake will be missed with such standard summary variables.

One shortcoming of TaxaHFE is its speed. While it is not a memory intensive program, it does rely on relatively inefficient for-loops to iterate over each taxon in each taxonomic level. For example, in a microbiome dataset with 4640 features, TaxaHFE took 2 min 44 sec, whereas the Oudah algorithm took only 13 seconds on a 2.3 GHz Quad-Core Intel® Core i7 machine. Future iterations of TaxaHFE could utilize a more distributed parallelization implementation.

Another limitation of TaxaHFE is true of all machine learning algorithms in that large high-quality data sets are needed. Without sufficient information in the data (i.e., no relationship between the response variable and the features) all ML algorithms will suffer. However, what may not be obvious to users is that in the absence of information, machine learning algorithms will still report results, which often represent noise. Methods for avoiding pitfalls of machine learning have been described elsewhere (Whalen *et al.*, 2021), but we would be remiss to not echo them here. Specifically, we implore users to not merely trust models based on their accuracy alone, but to also investigate the features utilized for making predictions.

CONCLUSION

We demonstrate that TaxaHFE dramatically reduces the feature space of hierarchically organized data while generally increasing the performance of downstream

machine learning models and improving interpretability. While our examples come from

microbiology and nutrition research, TaxaHFE could be used with any data set that has

hierarchically related features. Moreover, TaxaHFE removes the prerequisite of choosing a

taxonomic level that captures the most information relative to a response of interest,

removing the need to ask, "At what taxonomic level should I analyze my data?". Overall, we

suggest that hierarchical feature engineering can lead to more accurate and interpretable

models.

ACKNOWLEDGEMENTS

We would like to acknowledge Elizabeth Chin for early TaxaHFE discussions and

Stephanie Wilson and Sarah Blecksmith for useful feedback provided while code testing.

We would like to thank Rachel Waymack and Jules Larke for thoughtful comments and

edits. A.O. was supported by an ORISE fellowship administered by Oak Ridge Associated

Universities through an interagency agreement between the U.S. Department of Energy

and the U.S. Department of Agriculture, Agricultural Research Service.

FUNDING INFORMATION

This work was supported by the U.S. Department of Agriculture (USDA)

Agricultural Research Service (ARS) grant 2032-51530-026-00D. A.O. was supported by

an appointment to the Research Participation Program at USDA ARS, administered by the

Oak Ridge Institute for Science and Education through an interagency agreement between

the U.S. Department of Energy and ARS. This research used resources provided by the

SCINet project of the USDA ARS project number 0500-00093-001-00-D. USDA is an equal

opportunity employer.

FIGURES

Figure 1: Overview of TaxaHFE

Figure 2: Comparisons made used summarized microbiome data (L4-L7, order through

species), a previously published hierarchical feature engineering program (Oudah)

457 employing two different internal correlation cutoffs (Pearson 0.7 and 0.95), and TaxaHFE with

458 and without the super-filter. Machine learning performance metrics (A-C) and number of

459 features used for model building (D). (E) Variance explained in PERMANOVA models by

460 the composition of the features relative to the response variable used.

461 **Figure 3:** Analysis of TaxaHFE on categorical and continuous data. Histogram of antibiotic

462 resistance gene abundance, showing just the top quartile and bottom quartile of the cohort

463 (A). These data were analyzed as a categorical factor (low vs high ARG abundance) or

464 continuous ARG abundance, and the (B, C) boxplots show the performance of machine

465 learning models utilizing summarized taxonomic data or taxonomic hierarchical feature

466 engineering. (D-F) Shapley values of the most informative features from a model built using

467 TaxaHFE+SF data as input for both categorical and continuous ARG abundance are

468 shown, as well as a model built only using L7 level data against the categorical ARG

469 outcome. Colored font levels share a common taxonomic group with TaxaHFE.

470 **Figure 4:** Testing TaxaHFE on hierarchically organized dietary data. Machine learning

471 performance metrics of models predicting average fiber intake using food tree data (A) and

472 number of features used for model building. Shapley values (B-C) of the most informative

473 features from a model built using TaxaHFE+SF data as input or L6 as input. Colored font

474 levels are those shared with TaxaHFE.

475 **SUPPLEMENTAL FIGURES**

476 **Supplemental Figure 1:** Study-specific ML performance scores of ROC-AUC (A),

477 balanced accuracy (B), and Cohen's Kappa (C) across different feature selection methods.

478 The green highlight represents the best model by averaging results from ten different

479 random seeds. (D) The number of features used at each summarized level or feature

480 engineering strategy per study.

481 **Supplemental Figure 2:** (A) Features selected by Lefse using Erawijantari dataset. (B)

482 Performance of the Boruta algorithm across the tested datasets and (C) the features

selected by the Boruta algorithm for the Oliver dataset.

SUPPLEMENTAL TABLES

Supplemental Table 1: List of studies used in comparisons

Supplemental Table 2: Performance of ML models and variance explained in

PERMANOVA models using summarized data and hierarchical feature engineering

algorithms.

REFERENCES

Aldehim,G. and Wang,W. (2017) Determining appropriate approaches for using data in feature

selection. *Int. J. Mach. Learn. Cybern.*, **8**, 915–928.

Baldiviez,L.M. *et al.* (2017) Design and implementation of a cross-sectional nutritional

phenotyping study in healthy US adults. *BMC Nutr.*, **3**, 1–13.

Bellman,R.E. (2003) Dynamic Programming Courier Corporation.

Bevilacqua,S. *et al.* (2021) The use of taxonomic relationships among species in applied

ecological research: Baseline, steps forward and future challenges.

Choi,Y. *et al.* (2022) A Guide to Dietary Pattern–Microbiome Data Integration. *J. Nutr.*, **152**,

1187–1199.

Erawijantari,P.P. *et al.* (2020) Influence of gastrectomy for gastric cancer treatment on faecal

microbiome and metabolome profiles. *Gut*, **69**, 1404–1415.

Franzosa,E.A. *et al.* (2019) Gut microbiome structure and metabolic activity in inflammatory

bowel disease. *Nat. Microbiol.*

Glur,C. *et al.* (2020) data.tree: General Purpose Hierarchical Data Structure.

Greenwell,B. (2021) fastshap: Fast Approximate Shapley Value.

Hand,D.J. and Till,R.J. (2001) A Simple Generalisation of the Area Under the ROC Curve for

Multiple Class Classification Problems. *Mach. Learn.*, **45**, 171–186.

Jacobs,D.R. and Steffen,L.M. (2003) Nutrients, foods, and dietary patterns as exposures in

research: a framework for food synergy. *Am. J. Clin. Nutr.*, **78**, 508S-513S.

Johnson,A.J. *et al.* (2019) Daily Sampling Reveals Personalized Diet-Microbiome Associations

in Humans. *Cell Host Microbe*, **25**, 789-802.e5.

Kable,M.E. *et al.* (2022) Tree-Based Analysis of Dietary Diversity Captures Associations

Between Fiber Intake and Gut Microbiota Composition in a Healthy US Adult Cohort. *J.*

Nutr., **152**, 779–788.

Kleine Bardenhorst,S. *et al.* (2021) Data Analysis Strategies for Microbiome Studies in Human

Populations—a Systematic Review of Current Practice. *mSystems*.

Kuhn,M. *et al.* (2023) yardstick: Tidy Characterizations of Model Performance.

Kuhn,M. and Wickham,H. (2020) Tidymodels: a collection of packages for modeling and

machine learning using tidyverse principles.

Kursa,M.B. and Rudnicki,W.R. (2010) Feature selection with the boruta package. *J. Stat. Softw.*

Lenth,R. *et al.* (2018) Emmeans. *R Packag. version 1.15-15*.

Lloyd-Price,J. *et al.* (2019) Multi-omics of the gut microbial ecosystem in inflammatory bowel

diseases. *Nature*.

Mars,R.A.T. *et al.* (2020) Longitudinal Multi-omics Reveals Subset-Specific Mechanisms

Underlying Irritable Bowel Syndrome. *Cell*.

Martiny,A.C. *et al.* (2012) Phylogenetic conservatism of functional traits in microorganisms.

ISME J. 2013 74, **7**, 830–838.

Martiny,J.B.H. *et al.* (2015) Microbiomes in light of traits: A phylogenetic perspective. *Science*

(80-.)., **350**.

Mayer,M. and Stando,A. (2023) shapviz: SHAP Visualizations.

Muller,E. *et al.* (2022) The gut microbiome-metabolome dataset collection: a curated resource

for integrative meta-analysis. *npj Biofilms Microbiomes*.

Nembrini,S. *et al.* (2018) The revival of the Gini importance? *Bioinformatics*, **34**, 3711–3718.

Oksanen,J. *et al.* (2019) vegan: Community Ecology Package. R package version 2.5-2. *Cran*

R.

Oliver,A. *et al.* (2022) Association of Diet and Antimicrobial Resistance in Healthy U.S. Adults.

MBio, **13**.

Oliver,A. *et al.* (2021) High-Fiber, Whole-Food Dietary Intervention Alters the Human Gut

Microbiome but Not Fecal Short-Chain Fatty Acids. *mSystems*, **6**.

Oudah,M. and Henschel,A. (2018) Taxonomy-aware feature engineering for microbiome

classification. *BMC Bioinformatics*, **19**, 1–13.

Pinheiro,J. *et al.* (2019) nlme: Linear and Nonlinear Mixed Effects Models.

Ristoski,P. and Paulheim,H. (2014) Feature Selection in Hierarchical Feature Spaces. In,

Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial

Intelligence and Lecture Notes in Bioinformatics)., pp. 288–300.

Segata,N. *et al.* (2011) Metagenomic biomarker discovery and explanation. *Genome Biol.*, **12**,

R60.

Stalder,T. *et al.* (2019) Linking the resistome and plasmidome to the microbiome. *ISME J. 2019*

1310, **13**, 2437–2446.

Štrumbelj,E. and Kononenko,I. (2014) Explaining prediction models and individual predictions

with feature contributions. *Knowl. Inf. Syst.*

Wang,X. *et al.* (2020) Aberrant gut microbiota alters host metabolome and impacts renal failure

in humans and rodents. *Gut.*

Wetterstrand.,K.A. DNA Sequencing Costs: Data from the NHGRI Genome Sequencing

Program (GSP).

Whalen,S. *et al.* (2021) Navigating the pitfalls of applying machine learning in genomics. *Nat.*

Rev. Genet. 2021 233, **23**, 169–181.

Wright,M.N. and Ziegler,A. (2017) ranger⬜: A Fast Implementation of Random Forests for High

Dimensional Data in C++ and R. *J. Stat. Softw.*, **77**.

Data Input

Samples

Features	S1	S2	S3	S4
F1	12	0	08	32
F2	0	0	05	01
F3	05	23	09	02

Samples	Metadata
S1	Healthy
S2	Healthy
S3	Disease

Abundance table   Metadata

Data QC Filter

Feature Prevalence: ≥ 1%*

Feature Abundance: ≥ 0.01%*

*defaults

Step 1

Machine Learning

Permute a random forest with metadata, parent, and descendants not dropped in correlation

IF: mean(Importance) of parent is most informative, drop descendants

ELSE: Keep descendants that beat parent based on mean importance

Step 3

Build Tree

Parse input features using pipe symbol ("|"), adding features as nodes to a tree.

A   *B*   *C*   *D*

Bacteria|Proteobacteria|Gammaproteobacteria|Enterobacterales

Fill in any missing levels by summing descendant abundances.

Traverse tree in post-order

Correlation

For any parent-descendant subset:

Prevotella
- *P. copri*
- *P. brevis*
- *P. bivia*
- *P. amnii*
- *P. oris*

Correlate abundances of parent and descendants

1. Drop highly correlated descendants above a threshold (default 0.95)

Step 2

Super Filter

Permute a random forest on all the selected features. Drop features below 0 mean importance & below the mean global importance

Step 4

Write Outputs

Samples

Features	S1	S2	S3	S4
F1	12	0	08	32
F2	0	0	05	01
F3	05	23	09	02

Summarized abundance table for downstream analysis

- - - - **Optional step**
——— **Algorithm path**