Autoencoder Model for Translating Omics Signatures

Nikolaos Meimetis[1], Krista M. Pullen[1], Daniel Y. Zhu[1], Avlant Nilsson[1,2], Trong Nghia Hoang[3], Sara

Magliacane[4,5] and Douglas A. Lauffenburger[1]*

1) Department of Biological Engineering, Massachusetts Institute of Technology, Cambridge, MA 02139, USA

2) Department of Biology and Biological Engineering, Chalmers University of Technology, Gothenburg, SE 41296,

Sweden

3) School of Electrical Engineering and Computer Science, Washington State University, Pullman, WA, 99164-4236,

USA

4) Institute of Informatics, University of Amsterdam, Amsterdam, The Netherlands

5) MIT-IBM Watson AI Lab, Cambridge, MA 02139, USA

* Corresponding author, lauffen@mit.edu

Abstract

The development of effective therapeutics and vaccines for human diseases requires a systematic

understanding of human biology. While animal and in vitro culture models have successfully elucidated

the molecular mechanisms of diseases in many studies, they yet fail to adequately recapitulate human

biology as evidenced by the predominant likelihood of failure in clinical trials. To address this broadly

important problem, we developed AutoTransOP, a neural network autoencoder framework to map

omics profiles from designated species or cellular contexts into a global latent space, from which

germane information can be mapped between different contexts. This approach performs as well or

better than extant machine learning methods and can identify animal/culture-specific molecular

features predictive of other contexts, without requiring homology matching. For an especially

challenging test case, we successfully apply our framework to a set of inter-species vaccine serology

studies, where no 1-1 mapping between human and non-human primate features exists.

Introduction

Animal and cellular models are essential tools for studying the underlying biology of human diseases, but these insights are not always clinically translatable, resulting in the failure of numerous therapeutics in clinical trials[1,2]. A common approach is to choose orthologous biomolecules, including genes, proteins, and cellular pathways, to perform direct functional comparisons across species. However, functional divergence and the absence of orthologous biomarkers can hinder these direct comparisons between species [3–5]. Furthermore, within the same species, the transcriptional response to chemical stimuli can be cell type-specific due to distinct genetic profiles, creating an additional barrier to understanding the mechanism of action of therapeutics[6–9]. Consequently, computational systems-based approaches are needed to gain a better understanding of the relationship between biological models and translate information gained from different model systems.

Advancements in sequencing technologies have enabled the generation of large-scale datasets from both animal and human species, facilitating more powerful analyses and comparisons of molecular features between different biological systems[2,3,10–13]. This has led to the development of numerous new statistical and machine learning models[3,13–17] for identifying similarities between species and experimental models. Notably, most existing approaches focus on direct correlations between analogous biomarkers or processes across species despite known species and model system differences. In an attempt to address this challenge, Brubaker et al. proposed a technique called "Translatable Components Regression"[18] (TransCompR), which maps human data into the principal component space of data from another species to identify translatable animal features that can predict human disease processes and phenotypes. Although this approach has been successfully applied to gain insights into some inflammatory pathologies[18,19], it depends on homologs or comparable molecular features between species. While TransCompR is well suited to identify omics signatures in one species that is most germane for understanding phenotype characteristics in another, it is not centrally designed to integrate

signatures across species. Moreover, this approach is by design only capable of deciphering linear

relationships, thus potentially excluding non-linear biological relationships.

With the advent of deep learning, particularly autoencoders, there is great potential to develop

approaches that can approximate the non-linear relationships underlying different biological systems

and species. Autoencoders are artificial neural networks (ANNs) that can embed raw input data into a

lower dimensional space from which the original data can be reconstructed [20]. Autoencoders have been

used in several tasks in biology including analyzing high dimensional data[21,22], denoising single-cell RNA

sequencing data[23–25], deciphering the hierarchical structure of transcriptomic profiles[26,27], and predicting

gene expression caused by various stimuli[28–30]. One such model, DeepCellState[31], focused on translating

cellular states, can predict the transcriptional profile of a cell type after drug treatment based on the

behavior of another cell type. However, similar to TransCompR, this approach depends on a 1-1

mapping of molecular features between cells to capture a global cell representation. Another recently

proposed framework, is the compositional perturbation autoencoder (CPA)[32]. It can construct a basal

latent space devoid of covariate and perturbation-specific signals, capturing only the basal cell state in

single-cell RNA sequence data. CPA can be used to generate *in-silico* transcriptional profiles at the single-

cell level for different perturbations, cells, and species, although it still requires mapping of orthologous

genes. To overcome such limitations, an approach similar to those used in language translation

autoencoder-based models, which create a global language representation[33,34], may be useful and could

aid biological inter-systems translation when 1-1 mappings between features do not exist.

In this study, we incorporate elements of the CPA approach with ideas from language translation

models[33,34] to develop an ANN framework hence referred to as AutoTransOP, Autoencoders for

Translating Omics Profiles, which utilizes separate autoencoders for each biological system, enabling the

mapping of samples into a global cross-model space, while providing feature importance estimates for

various phenotype-prediction tasks. The basic model is trained to simultaneously minimize the

reconstruction error of the input and the distance between samples coming from the same condition in

the global latent space. Our framework is benchmarked, using the latest version of the L1000 dataset[12],

against the established approaches of TransCompR[18], FIT[15] and the ANN approach of DeepCellState[31],

which all require 1-1 feature mapping. We demonstrate that our approach outperforms FIT and

DeepCellState, while there is no difference when comparing with TransCompR in cellular models.

Additionally, we present several variations of the model and we illustrate the adaptability of our

framework by applying it to data of varying omics type and sample size to answer different biological

questions of interest. Furthermore, we demonstrate its biological interpretability, an aspect that deep

learning models often struggle to attain, by using an integrated gradients approach [35]. To analyze the

performance of the model in inter-species translation we performed mouse[36] to human[37] translation of

single-cell transcriptomics of lung fibrosis, as well as non-human primate[38] to human translation[39] of

smaller-scale serology datasets to predict HIV vaccine efficacy in humans. The latter serves as a novel

case study of cross-species translation where no 1-1 mapping between features exists. After building the

model, we identified serological features in non-human primates that are predictive of protection

against HIV in humans, without analogous features necessarily being present in human data. These

findings demonstrate that features derived from this approach can be predictive of the phenotypic

profile of another biological model without requiring them to be homologs, allowing us to maximize the

amount of information we can capture from different model systems to advance our understanding of

complex human disease biology.

Results

A flexible framework for omics translation

We developed a flexible artificial neural network framework (see methods) for omics translation across

biological models. It consists of separate ANN encoders and decoders for each biological system, e.g. cell

line or species, that share a global latent space (Figure 1a), eliminating the need for a 1-1 mapping

between the features between systems. We implement two main variations of the global latent space

intending to remove the system-specific effect of perturbations. The first variation, which is also the

main model variation of this framework (model variation 1), consists of a single global latent space that

is created by maximizing the similarity of embeddings derived from the same condition/perturbation in

a different species or cell line. The second variation (model variation 2) is based on the recently

published compositional perturbation autoencoder (CPA)[32], where there are two separate latent spaces:

1) a global/basal latent space and 2) a composed latent space. The global latent space expands on the

first variation with an additional discriminator that attempts to remove the cell-line or species effect by

penalizing models where the classifier can detect from which encoder the latent representation

originates[32]. In the composed latent space, a cell/species classifier is simultaneously trained to ensure

there is a cell/species effect, which is either added through a trainable covariate vector[32] or added

through two intermediate ANNs, allowing for non-linearity. We utilize integrated gradients[35] to estimate

feature importance for various predictive tasks. Lastly, we also introduce a variation (model variation 3),

with one single global latent space, where a classifier is simultaneously trained on the global latent

space (see methods). This is a contradictory learning task where the framework attempts to

simultaneously remove the cell line or species effect globally but also hides cell or species information in

a few of the latent variables.

Benchmarking reconstruction and translation of gene expression profiles between two cell-lines

First, we compared our ANN framework with state-of-the-art techniques in the context of translating

homologous genes between in-vitro models within the same species. We use the L1000 transcriptomics

dataset[12] to benchmark different approaches to translate the effects of perturbations between different

human cell lines. The two main variations of our approach, as well as the variation where a classifier is

simultaneously trained on the global latent space, are compared with three previously published

approaches (DeepCellState[31], FIT[15], TransCompR[18]). As a baseline, the models are also compared to

"direct translation", i.e. directly using the gene expression profile in one cell line as a prediction for the

effect in another cell line. We evaluate the models both on the task of translating the gene expression

profile between cell lines, as well as the task of accurately reconstructing the gene expression for the

same cell line. We evaluate them using several different metrics: i) Pearson's correlation between

predicted gene expression and actual gene expression, ii) the per sample Spearman's rank correlation,

and iii) the accuracy in correctly predicting the sign of drug-induced gene expression.

When utilizing the 978 landmark genes measured in the L1000, all of our framework's variations provide

a statistically significant increase in performance compared to the direct translation across all metrics

(Figure 1b, Supplementary Tables 1-4 with p-values). When translating from the HT29 cell line to A375,

our main model variation outperformed FIT[15] and the basic DeepCellState[31] (DCS) methods. When

translating in the reverse direction, from A375 to HT29, our framework also outperforms the different

modifications of DCS (Figure 1b). It can be noted that the 2^{nd} modification of DCS that enforces

similarity in the latent space like our model, also outperforms the basic DCS, which may support the

importance of enforcing similarity in the global latent space via some distance metric. For reconstruction

of the input within a single cell line, the basic DCS approach outperforms the other approaches, at the

expense of its translation performance. On this metric, our approach performs well and comparably

with the other methods (Figure 1b). The alternative variations of our framework also perform

comparably well.

When using the L1000 dataset with computationally imputed expression of 10,086 genes, the

performance of all approaches drops, though still better than the baseline. There is generally no

statistically significant difference between our approach and the other state-of-the-art approaches

(Figure 1c). Interestingly, our approach performs better than direct translation also in the case of using

different genes as input for each cell line, e.g. using only the 978 landmark genes for the A375 cell line

and all the 10,086 genes for HT29 (Figure 1f). The performance is comparable to that using the same

genes for both cell lines, indicating the potential to later extend the method in cases where no 1-1

mapping exists.

Performance in using predicted gene expression to infer transcription factor activity

While the performance was worse in predicting the full set of 10,086 imputed genes, we reasoned that

these imputed transcriptomic profiles may still be useful as input into different aggregation methods,

e.g. to infer the activity of transcription factors (TFs). When we inferred transcription factor activity (see

methods), model performance increased relative to using all 10,086 genes and was comparable to that

in the case of the landmark genes (Figure 1b and 1d). Our model was not as successful at predicting

gene set enrichment (Supplementary Method 1, Supplementary Figure 3). Autoencoders have been

previously shown to be capable of capturing regulatory relationships between genes[26,31] but, to our

knowledge, not gene set enrichment, which might explain why we observed increased performance only

when inferring TF activity.

Creating cell-line-specific regions in the latent space enables robust cell classification

It is important to evaluate whether the cell line or species effect is successfully added to the composed

latent space and whether the framework can retrieve it. To establish the ability of the model to capture

cell-line-specific information we evaluated the performance in classifying the cell line when using all

10,086 genes (Figure 1e) and the landmark genes (Supplementary Table 11) of the L1000 dataset. The

performance of ANN classifiers trained directly on the L1000 gene expression data serves as the

baseline. Classifiers built with pre-trained embeddings, from DCS or our framework with one global

latent space, are expected to have lower performance than the baseline as these approaches generate

embeddings aiming to filter the cell-line effect as much as possible. Our framework seems to be better

at "forgetting" the cell line of origin in the global space than DCS, thus generating more global

embeddings (Figure 1e). Interestingly, when simultaneously training a classifier in the global latent space

we can outperform the baseline while the cell-line effect is still partially filtered in the higher dimensions

(Supplementary Figure 4). The CPA-based model in the composed latent space classifies cell lines with

100% accuracy, even though the similarity of input gene expression data between training and

validation sets, as well as the latent space embedding similarity, is generally low (Supplementary Figure

5). The CPA-based framework can create very well-separated cell-line-specific regions (Supplementary

Figure 6) in the composed latent space, indicating the framework's ability to shape the latent spaces

with robust cell-line-specific regions and explaining the observed accuracy.

Analysis of the framework's dependence on different aspects of the data

We further investigated how the performance of the framework was influenced by different factors,

focusing on the CPA-like approach. The framework has similar behavior and performance across cell-line

pairs (Figure 2a). For all cell lines, ~600 total training samples are sufficient to train a high-performance

model. Some cell-line pairs perform slightly worse, as the original correlation between the same

perturbations in the cell-line pair correlates with the model's performance (Figure 2b). Interestingly, the

amount of paired conditions, meaning similar perturbations across biological systems, required to

successfully facilitate translation can be as low as ~10-15% of the samples being paired (Figure 2c).

Finally, it seems the model is not affected by a moderate imbalance in the number of conditions coming

from each cell line (Figure 2d). Similar trends are observed when using 10,086 genes (Supplementary

Figure 7).

Evaluation of latent space embeddings

A global latent space is expected to have several properties to be suitable for translation. We evaluate

the embeddings produced from our framework based on three criteria (Figure 3a-3c): i) different cell

lines should not occupy different subspaces, so embeddings of pairs coming from the same cell line

should not be more similar to each other than embeddings from random pairs, ii) pairs of embeddings

coming from the same condition, regardless of cell line, should be similar, and iii) biological replicates

should give similar embeddings, so pairs of embeddings from biological duplicates should be similar to

each other. We evaluated these criteria using the cosine distance in latent space. No cell-line effect is

observed in the global latent space, both for training and validation embeddings (Figure 3a,

Supplementary Figure 8). Embeddings coming from the same condition are closer to each other than

embeddings coming from random pairs (Figure 3b), while biological duplicates are even closer (Figure

3c), validating that indeed we have successfully constructed a stimuli-specific global latent space. Similar

patterns can be observed in the global latent space when using the CPA-based approach (Figure 3d), but

with a cell-line effect visible in the composed latent space, as expected with this method. We use

Cohen's d to quantify the difference between the distributions of cosine distances across all folds in 10-

fold cross-validation (Figure 3e), proving that indeed there is a much higher cell-line effect in the latent

space than the effect in the global latent space.

Interpreting the biological information captured in the parameters

Deep learning models are often criticized for their lack of interpretability, so we investigate the

biological information captured by some of the model's parameters. Since only the cell-line effect is

minimized in the global latent space of the CPA-like framework, the trainable covariate (covariates such

as species, cell type etc.) vectors should only add a cell-specific effect. Intuitively, the global latent

embeddings are expected to capture a "zero"/basal cell state corresponding to expression of untreated

cells (controls), and thus the trained covariate which is added to that global representation should be

similar to the composed latent space vectors which now captures the cell line effect. To investigate this

we used control samples from the L1000 dataset not seen by the model during training, as well as

samples coming from untreated cell lines from the Cancer Cell Line Encyclopedia[40] (CCLE), using only the

genes included in the L1000 landmark genes. Additionally, for this investigation two models were

trained completely separately: the original benchmark model of A375/HT29 cell lines and another model

using the PC3 prostate cancer cell line and the HA1E normal epithelial cell line. The latter pair was

chosen because of high model performance (Figure 2a) and because these two cell lines are significantly

different in terms of biology. Each trained covariate, even though the models were trained separately, is

observed to be closer to its respective cell-line control signatures, both when using PCA for

dimensionality reduction (Figure 3f), where clearly defined cell-line specific regions are observed, as well

as when using t-SNE (Figure 3g). This demonstrates that some parts of the model are biologically

interpretable and capture specific information.

Identification of features that are important for translation and cell classification

The framework can be used to identify latent variables and genes that can be of biological importance.

As a case study, we selected the model of the PC3 and HA1E cell lines with a classifier trained

simultaneously to classify the cell lines from which the samples were derived (contradictory learning

tasks). To identify the importance of genes according to the model for a variety of tasks with respect to

their output, an integrated gradient-based approach[35] was utilized (Methods) that attributes an

importance score to each variable of interest. Since the same genes are used for both cell lines, it can be

interesting to identify which are important for the model to translate a gene expression profile from one

cell line to another cell line. Interestingly, the model attributes more importance to many genes other

than the gene of interest when translating to across cell lines for the same condition (Figure 4a). In the

case of the landmark genes, that phenomenon is slightly less prominent (Figure 4b). This is particularly

interesting since one of the selected cell lines is cancerous and the other is non-cancerous, suggesting

that the model may avert the fallacy of using the same gene as a proxy for its gene expression across

disparate biological systems. Additionally, the model does not just attribute importance to genes that

are highly expressed, based on Spearman's correlation between the absolute importance scores and the

absolute gene expression (Figure 4c).

The simultaneously trained classifier can also be used to identify subsets of latent variables in the global

latent space that are important for classifying samples by cell type. Although the cell line effect is

partially filtered and embeddings coming from the same condition are globally close to each other

(Supplementary Figure 4), there are still 11 latent variables that allow the classification of cell line

(Figure 4d) using a k-means-based approach (see Methods). These latent variables can separate the

samples based on cell line (Figure 4e), even though globally the cell line-specific effect in the latent

space is still filtered out. Genes considered important by the encoders to control these latent variables

should be either cell line-specific genes or a subset of genes that can easily distinguish between cell

lines. The importance scores of the genes for each cell line-specific encoder do not correlate at all and

are different between the two cell lines (Figure 4f). It is possible to even train a very simple generalized

linear model to classify cell lines based on gene expression, only using a subset of these important

genes, achieving high performance with only few genes from each cell line (Figure 4g).

Performance in inter-species translation for lung fibrosis

Animal models don't recapitulate human biology perfectly, so computational modeling can be used to

improve the translation between humans and animal models. We evaluate the ability of the framework

to perform inter-species translation. We utilize the raw gene counts coming from single-cell RNA-

sequencing of a mouse[36] and human[37] lung fibrosis dataset. Similar to the original CPA study[32], the

decoders predict a mean and a variance for every gene, derived from a negative binomial distribution.

Furthermore, both a trainable species vector and another trainable cell type vector are added to the

global space, in attempt to minimize both species and cell type effects. We evaluate the performance in

the reconstruction of gene expression profiles and the ability to translate between mouse and human

under 10-fold cross-validation in terms of R^2 of the predicted per gene means and variances, where we

would expect to observe a similar distribution in a successful translation, and thus mean and variance.

Our framework outperforms the other approaches in terms of R^2 of the means both in reconstruction

and translation (Figure 5a). When predicting the within-gene variance, there is not always a statistically

significant improvement, as all approaches have generally low performance (Figure 5b), which suggests

that the models fail to capture variation in gene expression. We do not find any significant difference in

performance between using all genes or just homologs (Figure 5a-5b). It is worth noting that based only

on the human lung fibrosis dataset, three of the top ten genes contributing to the top principal

components do not have homologs in mice (Supplementary Figure 11), meaning that irrespective of

performance, a method considering only homologs would exclude important genes for lung fibrosis.

We also evaluate the ability of each approach to classify fibrosis, species, and cell type and to classify

correctly a signature as a different species when that is translated in the composed latent space, by

adding a different species effect. In our framework, utilization of all genes outperforms the homolog

genes approaches in predicting fibrosis and species-translation, though the performance of all

approaches is high (Figure 5c). Similar to what was observed for the L1000 dataset, species and cell type

are perfectly predicted in our framework. Additionally, both the species and cell-type effects are filtered

(Figure 5e-5f, Supplementary Figures 9-10) in the global latent space compared to the composed latent

space, meaning the model succeeds in removing the cell type and species effect in the global latent

space and then retrieving it again in the composed latent space.

Generalization in other disease datasets

Models that are trained on a specific data set can often perform worse on external test sets, and it is,

therefore, useful to investigate to which extent the model can predict disease, species, and cell types in

other datasets, as well as different tissue and disease datasets. For this, we use an independent dataset

on mouse lung fibrosis[41] and a dataset on human liver cirrhosis[42]. In the mouse dataset, even though

different genes were measured than those in our model, the performance is still decent in disease

classification (Figure 5d). For the human dataset, which is an extreme case of fibrosis in a different

organ, the model has markedly lower performance although better than chance (Figure 5d).

Interestingly, in both cases, the model can still perfectly identify cell types and species (Figure 5d), once

again displaying the model's ability to capture the general characteristics of the system.

An inter-species model from serology data for predicting protection against HIV

As a final case study, we developed a model for cross-species translation of serology data, where there

are no 1-1 mapping of features, to predict vaccine-induced protection from HIV in humans. Previous

failed HIV vaccine trials have suggested that neutralizing antibody titers, the primary outcome for most

vaccine trials, do not consistently correlated with vaccine efficacy. Moreover, recent research suggests

that deeper characterization of the antibody response, including antibody subtype prevalence and Fc-

receptor binding affinity, may be necessary to predict the quality of the vaccine response. Notably, the

primary challenge in comparing pre-clinical animal models and human clinical trial data in this context is

that antibodies and Fc-receptors with similar names across species can be structurally and functionally

distinct and orthologous features might not exist. Our ANN approach has the potential to advance our

understanding of which preclinical features might best predict efficacy of a HIV vaccine. Here we utilize

serology data from non-human primate (NHP) and human datasets [38,39] following vaccination against

SHIV and HIV, respectively. In this case, we added a non-linear species effect using two small

intermediate fully-connected neural networks with non-linear activation functions (Figure 6a). In line

with other models constructed using this framework, the model was trained so that protected

individuals are close in the global latent space regardless of species. While two separate classifiers try to

predict vaccination status and protection in the global space (Figure 6a), a third classifier predicts

species in the composed latent space. For the human serology features, the model has high

performance when reconstructing each feature (Figure 6b, r = 0.89±0.01). In NHPs, while some features

are not predicted well and there is a big variation in performance between folds, the overall

performance is still good (Figure 6c, r = 0.71±0.04). Finally, the performance across all classification tasks

is exceptionally high (Figure 6d) including 100% accuracy in species classification and translation, which

is evaluated by how well the species classifier predicts species label when translating a signature to

another species in the latent space.

Using the model, we aimed to identify features from both species that are predictive of human

protection. For this, we performed the integrated gradient approach in parallel to likelihood ratio tests

(LRT) on each latent variable (see methods). Latent variables are denoted as important in predicting

human protection only if there is an agreement between the likelihood ratio test results and the

integrated gradients (Supplementary Figure 17). The human features identified indeed have a

statistically significant difference between protected and non-protected individuals (Figure 6e). Finally,

we identified NHP features that have a high gradient score when translating to human signatures,

meaning these NHP features are predictive of human features linked with viral protection (Figure 6f).

These features are not necessarily associated with NHP protection (Supplementary Figure 18) but they

could be predictive of human protection. Notably, while the top human features identified are generally

related to IgG titers, the top NHP features are mostly related to the Fcg-2A and Fcg-3A receptors.

Further analysis of feature importance could potentially identify a set of serological biomarkers in NHPs

that is highly predictive of human HIV vaccine efficacy.

Discussion

Here we develop AutoTransOP, an ANN framework that facilitates the translation of omics profiles

between different biological systems. The framework builds upon ideas of the CPA approach[32] and other

species and cellular translation methods[13,15,18,31], together with ideas from language translation

models[33]. The explicit goal is to align omics signatures between systems, rather than identifying what

information inherent in the signature of one system is most germane for understanding phenotype

characteristics in the other, which has been the objective in many previous studies[16–19]. The framework

performs as well as (or even better than) other state-of-the-art translation techniques, when using

homolog features between systems, and performs similarly also without a 1-1 mapping between

features. Notably, the framework constructs a truly global latent space with stimuli-specific regions, for

which classifiers can be jointly trained to make predictions for various tasks such as the diagnosis of

diseases.

Most current approaches to translating between systems require homolog features and utilize linear

transformations to facilitate translation[13–18], and are thus restricted to represent linear inter-species

relationships. Also, the non-linear ANN-based approach DeepCellState[31] requires homology of the

molecular features used to describe the biological systems. In contrast, our framework can represent

non-linear relationships between different biological systems, without requiring any kind of homology,

and achieves high performance using only a small percentage of paired conditions. This enabled us to

train a translation model on serology datasets for which a 1-1 mapping of the features between the two

biological models did not exist. Through interpretation of this model, relationships between very

different molecular profiles that correlate with specific phenotypes can be identified, e.g. protection

against infection.

Interpretability of deep learning models in biology remains a challenge. These models have been

criticized for providing a poor understanding of which biological relationships they capture [43,44]. On this

front, we demonstrate in our framework how integrated gradient approaches[35] can be used to estimate

the importance of features used by different parts of the framework for various tasks, enabling some

biological interpretation of the model. Based on this, we could propose serological features predictive of

human protection against HIV, including non-human primate-specific features that can be observed in

preclinical stages of vaccine development. Finally, elements of the framework can be used to interpret

and successfully retrieve the effects of species or cell types, filtered from the global latent space. This

can explain the ability of the framework to predict cell types and species with high performance also in

independent disease datasets, derived from different organs/tissues. However, there are still limitations

in the generalization of in the models to external datasets. In particular, the performance on such

datasets drops significantly as samples from different pathologies and tissues are considered. Even

within the same disease, the inclusion of different features can lead to reduced performance in

predicting disease diagnosis.

Despite our framework being trained successfully on datasets with relatively small sample sizes, the

model still contains many parameters, especially when using a larger number of features, which

inevitably leads to overfitting. Some of these shortcomings could likely be alleviated by applying our

framework to larger datasets, such as ARCHS4[10], which contains hundreds of thousands of publicly

available RNA-sequencing data from humans and mice. Training with more data and more diverse

unique conditions may enable higher generalization and higher granularity in modeling different

biological covariates. Additionally, with the advent of Natural Language Processing (NLP) models[45] and

attention-based models[46], our encoder modules could potentially be modified with NLP-like

representations. Recently, Geneformer[47], an attention-based model, was pre-trained on a corpus of 30

million single-cell transcriptomic profiles and was proven to be context-aware of the system it encodes.

Although it still requires some level of homology, it paves the way to utilize NLP approaches for transfer

learning in biology, and ultimately translation.

The flexibility of our framework allows the modeling of many different biological systems. This could

lead to the computational optimization of biological systems and assays aiming to model human

pathology. Using our framework, we can both explore potential transcriptional modifications to design

better disease models and identify features predictive of human biology without requiring homology

between systems, ultimately reducing resources spent during experimental modeling and potentially

expediting the translation of in-vitro and pre-clinical findings to human therapeutic advancement.

Methods

Pre-processing of *in-vitro* transcriptomics benchmark dataset

The L1000 CMap resource[12] contains bulk gene expression data from drug perturbations across different

cell lines and provides a benchmark dataset with diverse conditions and a large sample size (for a total

of 720,216 samples of drug perturbations of varying quality). Additionally, several equivalent

perturbations across different biological systems are available (406 *paired conditions* for the case of

A375 and HT29 cell lines after filtering and pre-processing, explained below) to evaluate the

performance in translating omics profiles. We selected high-quality drug perturbations from the latest

version of the L1000 dataset (accessed via clue.io). The level 5 z-score transformed and pre-processed

differential gene expression data of 978 landmark genes, measured with the L1000 assay, and

additionally, 9,196 computationally inferred genes in the CMap resource that were marked as well-

inferred, were considered in the subsequent analysis. We consider perturbations as high-quality if they

consist of signatures with more than three replicates, where at least half of them passed the standard

quality control protocols in the assay, as provided in the dataset, and were not identified as statistical

outliers (as considered by the L1000). Additionally, where multiple-signature perturbagens, i.e. technical

duplicates, only the signature with the highest transcriptional activity score (TAS) across these technical

duplicates was retained in the dataset, these signatures are labeled 'exemplars' by the CLUE platform

and are specifically designated for further analysis by the platform[48]. The TAS metric is provided along

with the L1000 dataset and quantifies signal strength and reproducibility. Finally, the ability to

distinguish between random signatures and true biological duplicates, meaning the same perturbagen

tested on the same cell line for the same duration and dosage, was evaluated for different parts of the

dataset, split using varying TAS thresholds (Supplementary Figure 19) and samples with a TAS≥0.3 were

retained. After filtering and 13,699 samples remained, with 1107 conditions available in total for the

HT29 cell line and 1213 for the A375 cell line. In the case of control signatures, we followed the same

procedure but without filtering based on TAS.

Pre-processing single-cell RNA sequencing interspecies datasets

For the human and mouse single-cell RNA-sequencing datasets, we first re-annotated manually each

annotated cell into one of the four classes: i) immune cells, ii) mesenchymal cells, iii) epithelial cells, iv)

endothelial cells, and iv) stem cells. These high-level labels were later used to remove cell effect from

the global latent space and were also used in the subsequent cell-type classification. Finally, while the

raw gene counts are used for reconstruction from the decoder in the loss function, the encoders take as

input the log-transformed counts ($x_{input} = \log_{10}(count + 1)$), which acts as an activation function in

the first layer of the encoder.

Pre-processing of the serology datasets

For all serology data, we aimed to construct a model using only antibody and receptor measurements.

The human data were retrieved from Chung, Kumar, Arnold et al.[39] upon request, the avidity molecular

features were dropped and the data were z-scored per feature. The non-human primates' data were

retrieved from Barouch, Tomaka, Wegmann, et al.[38] upon request, the samples taken in week 28 were

used, and antibody-dependent cellular function features and mass spectrometry data were dropped.

The data were log-transformed ($x = \log_{10}(MFI + 1)$), the median per feature from controls is

subtracted from each feature to standardize the data. Finally, the data are z-scored per feature.

The general framework and the training procedure

In this implementation, the framework always models pairs of systems for translation, species, or cell

lines. Each is modeled with separate encoders and decoders for each of the species or cell lines in the

pair attempting translation, while inside a latent module, the global latent space is shaped (Figure 1a).

Both the encoders and the decoders are multi-layered neural networks, with each layer consisting of,

sequentially: a fully-connected layer, a batch normalization layer[49], an ELU activation function[50], and a

dropout layer[51]. The final output layer of the encoder and the decoder consists of only one fully

connected layer without a trainable bias term.

For the construction of the global latent space several metrics are optimized: the distance ($\boldsymbol{L_{distance}}$)

between embeddings of profiles coming from different systems undergoing the same perturbation is

minimize and their cosine similarity ($\boldsymbol{L_{cosine}}$) and mutual information ($\boldsymbol{L_{MI}}$, see details below) is

maximized; and the divergence of the distribution of the latent variables from a random uniform

distribution is minimized ($\boldsymbol{L_{prior}}$). Both cosine similarity and Euclidean distance losses were added to

enforce the strongest possible filtering of species and cell type effect, while the cosine similarity also

enforces normalization of the latent embeddings. This is achieved using two different ANN

discriminators, as previously proposed in the MINE[52], Deep InfoMax[53] and InfoGraph[54] studies, where

the Jensen-Shannon Mutual Information between embeddings coming from the same perturbation is

estimated and the extra prior loss is calculated and added in the final loss, according to the following

equations with the implementation taken from the deepSNEM model[55].

• $L_{prior} = \frac{1}{N}\sum_{i=1}^{N}\left[\log(Discr_2(v_i)) + \log\left(1 - Discr_2\left(z_{g_i}\right)\right)\right]$, where v_i is a randomly

sampled embedding from a prior random uniform distribution ranging from 0 to 1 and z_{g_i} is a

global latent space embedding. N is the number of samples in a batch during training.

• $L_{MI} = -(MI^+ - MI^-),\ MI = \frac{1}{N1+N2}\sum_{i=1}^{N1}\sum_{j=1}^{N2} Discr_1\left(z_{g_i}, z_{g_j}\right)$, where MI⁺ and MI⁻ are

respectively the mutual information between pairs derived from the same conditions and pairs

coming from different conditions, averaged for every possible pair in a batch during training.

z_{g_i}, z_{g_j} are global latent space embeddings, whose mutual information is estimated by the

$Discr_1$ discriminator.

$Discr_1$ is the discriminator estimating the mutual information between two embeddings from the global

latent space. It takes as input two global latent space embeddings and passes them through the same 3

fully-connected layers, each of them followed by a ReLU activation function[50] and one fully-connected

skip connection. Then the product of the result of this non-linear transformation of the two embeddings

is used to approximate a lower bound of their Mutual Information, as proposed originally in MINE[52] and

Deep InfoMax[53]. $Discr_2$ is the second discriminator which takes as input an embedding vector and

calculates the probability a point in this embedding space is sampled from a specific distribution. This

way L_{prior} forces each feature of the learned embeddings to be sampled from a distribution close to the

random uniform distribution ranging from 0 to 1. It has three similar fully-connected layers and the final

scalar output is passed through a sigmoid activation function[50]. These regularization loss terms

$(L_{distance}, L_{cosine}, L_{MI})$ are calculated and averaged across every pair of global embeddings (z_{g_i}, z_{g_j})

that are coming from the same condition. The L_{prior} is calculated for every sample in the dataset,

meaning every global latent embedding and averaged across samples. For the case of the L1000 dataset,

we consider similar perturbations those that are coming from experiments of the same drug, tested on

the same cell line, with the same dose and time duration. For the lung fibrosis dataset, similar profiles

are considered those coming from samples that have the same diagnosis (fibrosis or not). For the

serology datasets, we train the framework so that embeddings coming from protected individuals

against HIV are close to each other regardless of species (and even vaccination status)

The basic task of this autoencoder framework is reconstruction, which is achieved by minimizing some

kind of reconstruction loss (L_{recon}). In the case of z-scored profiles from bulk data, this is done by

minimizing the mean sum of squared errors between the input of the encoders and the output of the

decoders. The sum of squares error is averaged across samples. For only the case of single-cell RNA-

sequencing data, based on the implementation proposed in the CPA manuscript[32] (found here

https://github.com/facebookresearch/CPA), the negative binomial negative log-likelihood is used to

optimize the reconstruction, by assuming that the data are derived from a negative-binomial

distribution characterized by a mean and variance that are both predicted. The negative binomial

negative log-likelihood loss is calculated for every sample and the average across all samples in the

batch is minimized.

Classifiers are used for different classification tasks. These consist of multiple fully connected layers and

a final SoftMax activation function before the output. The average entropy loss across samples for every

classification task in the latent space is minimized: $entropy_i =$

$\frac{1}{N}\sum_{j=1}^{N} CrossEntropy\big(Classifier_i(z_j), label_j\big)$, where $entropy_i$ is the average cross entropy between

every jth prediction of a classifier taking a latent vector as input and the true label for that sample.

L2-regularization of the weights and bias of the encoders ($L2_{encoder,i}$), decoders ($L2_{decoder,i}$), and

classifiers ($L2_{classifier,i}$) is also enforced by minimizing the sum of squares for the aforementioned

trainable parameters.

Taken together, for the basic variation the following loss function is optimized

$\boldsymbol{Loss_{basic}} = \lambda_{recon} * L_{recon} + \lambda_{distance} * L_{distance} + \lambda_{MI} * L_{MI} + \lambda_{prior} * L_{prior} + \sum_{i=1}^{2}\big(\lambda_{enc,i} *$

$L2_{encoder,i}\big) + \sum_{i=1}^{2}\big(\lambda_{dec,i} * L2_{decoder,i}\big) + \sum_{i=1}^{M}\big(\lambda_{L2class,i} * L2_{classifier,i}\big) + \sum_{i=1}^{M}\big(\lambda_{class,i} *$

$entropy_i\big) - \lambda_{cosine} * L_{cosine}$, where M is the number of classifiers and thus individual classification

tasks, and the rest of the terms, together with how they are calculated, have already been described in

the previous paragraphs of this section. For values for each of the λ used in the loss function see

Supplementary Table 5.

Variation of the global latent space with a simultaneously and competitively trained classifier

For the variation of the global latent space with a simultaneously and competitively trained classifier the

aim is to embed some species or cell line information in some of the latent variables. A simple classifier

for correctly predicting the cell line label is trained simultaneously on the global latent space with the

rest of the framework and an entropy loss is added to the original description of the framework. The

construction of a global latent space and the training of the classifier are competing tasks, where the

framework is trained to achieve a stable trade-off.

CPA-based variation of the framework

For the CPA-based framework, the global latent space is expanded by augmenting the loss function with

some additional terms.

An adverse classifier of species and cell types is added. As described in the original CPA manuscript[32],

during training we iterate between training the classifier (updating only its parameters) on the global

latent space, and training the rest of the framework with the addition of a penalty ($entropy_{adverse}$) if

the classifier correctly classifies species and cell types. To improve the robustness of the discriminator it

is initially pre-trained only with encoders and discriminators, without other classifiers and the decoders,

so that it can already distinguish cell types and species in the global space.

Furthermore, species and cell type effects are added to the latent space via trainable vectors. In the

newly composed latent space, from which the decoders are sampling embeddings, classifiers are jointly

trained to correctly classify cell types, and species (or even disease diagnosis). Additionally, the trainable

vectors are regularized by the L2 norm ($L2_{trained_{effect}}$). All the above can be summarized in this new

loss function:

511
$$Loss = Loss_{basic} - \lambda_{adverse} * entropy_{adverse} + \lambda_{trained_{effect}} * L2_{trained_{effect}}$$

512 Framework for the serology datasets

In the serology dataset we utilize the CPA-based framework but instead of adding the species effect with

trainable vectors, small artificial neural networks are utilized consisting of two fully-connected layers.

L2-regularization terms for these small ANNs are added to the training loss function.

Additionally, it is aimed to later identify features predictive of protection or vaccination status regardless

of species. For this purpose, we train two classifiers predicting vaccination and protection status in the

global latent space. We care more about protection and thus, as described previously, we aim to create

similar embeddings and minimize their distance in the global latent space just by looking at protection

status.

521 Framework's basic hyperparameters

Here we present the basic parameters used to train the model. No thorough hyperparameter tuning was

performed, and values were selected based on empirical values and tuned so that there is convergence

in the training loss and the training reconstruction performance (Pearson's r and/or R^2). Additionally,

these values were also tuned so that the performance in training (not validation) is sufficiently high,

meaning that the model is at least able to fit the given data. This empirical tuning was done only based

on the 1st training set in 10-fold cross-validation.

The latent space dimension was chosen to be as small as possible until the model's performance

dropped in both training and validation of only the 1st fold. Based on this latent dimension and the

original input dimension of the data the sizes of hidden layers of the encoders were chosen to be in-

between, gradually reducing the input dimension to that of the latent space. The actual size and number

were constrained by practical memory limits. The decoders had the same number and sizes of hidden

layers as those of the encoders, but now they increase the size of the embeddings from the latent

dimension to the original input dimension.

hyperparameter	L1000: 978 genes	L1000: 10,086 genes	Lung fibrosis	Serology
latent dimension	292	1025	512	32
hidden encoder layers dimensions	[640,384]	[4096,2048,1024,512]	[4096,2048]	[64]
hidden decoder layers dimensions	[384,640]	[512,1024,2048, 4096]	[2048, 4096]	[64]
cell type classifier hidden layer dimensions	[256,128,64]	[512,256,128]	[256,128,64,32]	-
species classifier hidden layer dimensions	-	-	[256,128,64,32]	[32,16,8]
fibrosis classifier hidden layer dimensions	-	-	[256,128,64,32]	-
serology phenotype classifiers classifier hidden layer dimensions	-	-	-	[32,16,8]
adverse classifiers hidden layers dimensions	[256,128,64]	[512,256,128]	[512,256,128,64]	[32,16,8]
intermediate ANN translators hidden layers dimensions	-	-	-	[32]
total batch size	512	512	1024	2000
number of epochs	1000	1000	200	50
learning rate	0.001	0.001	0.001	0.001

Evaluation procedure and metrics

The model performance was evaluated using 10-fold cross-validation. One fold of the data was hidden

during training and used to evaluate performance in unseen data, and 90% of the data from each system

(species or cell line in the case of L1000) were. For the L1000 dataset, for evaluating the translation of

the whole omics profile, we made sure that for the case of paired conditions, the perturbation in both

cell lines was hidden during training.

The classification tasks were evaluated by total accuracy and F1-score (or micro F1 for multiple

categories):

$$\text{Accuracy} = \frac{\sum_{i=1}^{K} TP_i + \sum_{i=1}^{K} TN_i}{\sum_{i=1}^{K} TP_i + \sum_{i=1}^{K} TN_i + \sum_{i=1}^{K} FP_i + \sum_{i=1}^{K} FN_i},$$

$$\text{F1}_{micro} = \frac{\sum_{i=1}^{K} TP_i}{\sum_{i=1}^{K} TP_i + \frac{1}{2} * \left(\sum_{i=1}^{K} FP_i + \sum_{i=1}^{K} FN_i\right)},$$

where K is the total number of classes in multi-class classification, TP and FP symbolize true and false

positives, and TN and FN symbolize true and false negatives. For the case of multiple classes, we define

as positives the samples belonging to that specific class while everything else is a negative sample. Using

this definition of positives and negatives we further calculate the TP, FP, TN and FN per class. In the case

of cell-type classification in lung fibrosis K=5.

For the cell line classification in L1000, species classification both in lung fibrosis and the serology

datasets, and vaccination and protection status in the serology dataset we use the F1 score and accuracy

for binary classification ($\text{Accuracy} = \frac{TP+TN}{TP+TN+FP+FN}$, $F1 = \frac{TP}{TP+\frac{1}{2}(FP+FN)}$).

To evaluate the validity of the predictions ($\hat{y}$) of whole signatures in translation and reconstruction,

compared to the ground truth (y), we utilized:

i.   the global Pearson's correlation $r(\hat{y}, y) = \frac{\sum(y_i - \bar{y})(\hat{y}_i - \bar{\hat{y}})}{\sqrt{\sum(y_i - \bar{y})^2 \sum(\hat{y}_i - \bar{\hat{y}})^2}}$, where $\hat{y}$ and y are flattened and the

i^{th} element is the i^{th} point in these flattened vectors.

ii.   the average per sample Spearman's correlation $r_s = \frac{\sum_{i=1}^{N} r(\text{Rank}(\hat{y}), \text{Rank}(y))_i}{N}$, where N is the

number of samples and Rank() means ranking the gene based on their differential gene

expression and using these ranks to calculate Spearman's correlation.

iii. the average per sample sign accuracy $= \frac{TP+TN+TrueZeros}{total\ predictions}$, where TP signifies the genes that

have a positive sign regulation both in the actual data and predictions, TN signifies the genes in

563   the sample that have a negative sign regulation both in the actual data and predictions, and

564   TrueZeros are the genes that have an absolute expression $\leq 10^{-6}$ both in the actual data and

565   predictions (a small tolerance rather than strictly zero was chosen for numerical reasons).

566 For the single-cell RNA-sequencing data where we predict the per gene mean and variance we calculate

567 the coefficient of determination (R^2) per gene mean and variance, similar to the original CPA

568 manuscript[32]. In general, R^2 is calculated as: $R^2 = 1 - \frac{RSS}{TSS}$, $where\ RSS = \sum(\hat{y}_i - y_i)^2\ and\ TSS =$

569 $\sum(y_i - \bar{y})^2$

570 Separation of latent space embeddings

571 To evaluate the similarity of embeddings for different signatures, and whether there is separation

572 based on cell, species, or conditions in the latent space, we utilize cosine distance, ranging from 0 (the

573 same) to 2 (completely) different: $cosine\ distance = 1 - cosine\ similarity = 1 - \frac{\sum_{i=1}^{d} z_{1,i}z_{2,i}}{\sqrt{\sum_{i=1}^{d} z_{1,i}^2}\sqrt{\sum_{i=1}^{d} z_{2,i}^2}}$,

574 where z_1 a and z_2 are two latent space vectors to be compared and d is the total number of elements in

575 the vector, i.e. the latent dimension.

576 To estimate if there is a cell, species, or condition effect, and compare it between the composed and

577 global latent space we utilize Cohen's d to estimate the effect size between the distributions of cosine

578 distances, derived from random pairs of embeddings and pairs coming from the same cell, species, or

579 condition. The effect size is thus calculated using the mean and standard deviations of two cosine

580 distance (cos) distributions as: $d = \frac{\overline{cos}_1 - \overline{cos}_2}{\sqrt{\frac{\left((n_1-1)s_1^2 + (n_2-1)s_2^2\right)}{n_1+n_2-2}}}$, where n_1, n_2 is the number of samples of each of

581 the two distance distributions, $\overline{cos}_1, \overline{cos}_2$ are the means of the cosine distance distributions and s_1,s_2 are

582 the standard deviations of the cosine distance distributions. A Cohen's d around 0.8 is a large effect size

583 (around 2 is considered a huge effect size) while around 0.5 is a medium effect size, and around 0.2 and

584 below is considered small or very small[56,57].

Feature importance using integrated gradients

To estimate the importance of features we utilize integrated gradients[35] from the Captum library[58].

$$InterGrad_i(x) = (x_i - x_i') \int_{a=0}^{1} \frac{dF(x' + a(x - x'))}{dx_i} da, x' = baseline = 0$$

The importance scores are calculated based on the gradient with respect to the input of the model, and

thus the higher the absolute integrated gradient the higher the importance of that input feature to

control the output. A negative score means the variable has a negative effect pushing the prediction to

the other class, while a positive score has a positive effect.

For example, if we want to identify important latent variables to classify a sample as one coming from a

particular cell line we calculate the integrated gradient of every latent variable to make the classification

and take the average across all samples. Similarly, if for example, we are aiming to calculate the

importance of genes to control latent variables in the global latent space we can calculate the integrated

gradient score of every gene for every variable in every sample, and then take the average across

samples.

K-means-based separation of important latent variables

Latent variables can be separated into important and unimportant ones using k-means, inspired by an

approach that was used to identify important connections between latent components and genes in

microbial organisms by using the weights derived from independent component analysis [59,60]. We

assume that only 2 main clusters of latent variables exist, one containing important variables and one

containing unimportant ones. On this front, the latent variables are clustered based on their absolute

gradient scores into 3 clusters, where 3rd cluster is assumed to be a very small cluster of outliers. The

midpoint between the variable with the highest score in the unimportant cluster and the variable with

the lowest score in the important cluster is used as a threshold to distinguish between significantly

important and unimportant latent variables. As a sanity check the important variables are also

compared with the top-ranked variables based on their score.

Likelihood ratio tests for the identification of important latent variables

To identify which latent embeddings correlate with viral protection after accounting for vaccination

status and species, a likelihood ratio test (LRT) was performed on each individual latent variable. Here,

the likelihood (L) of the alternative model (H_A): $latent\ variable_i\ embeddings \sim protection +$

$vaccination + species$ was compared to the likelihood of the nested model, or null hypothesis,

(H_0): $latent\ variable_i\ embeddings \sim vaccination + species$ in $LRT = -2\ln\left(\frac{L(H_0)}{L(H_A)}\right)$. We rejected

H_0 for $latent\ variable_i$ when the FDR-adjusted p-value of the chi-square test was less than 0.05,

concluding that the model including protection has a statistically significant better fit than the model

without protection. In the volcano plots, the $-\log(pvalue)$ is plotted against the t-value for the

protection term in the alternative model. This method assumes that the relationship between the latent

variable embeddings and protection is linear. R package *lmtest*[61] (version 0.9.40) was used to perform

these statistical tests. Finally, the intersection of these latent variables with significant latent variables

(average percentage importance score across folds ≥10%), based on their gradient score from the

trained protection classifier, is used for the final identification of robust latent variables associated with

viral protection. We keep latent variables that the sign of correlation with protection agrees in both

approaches.

Identification of protection-associated serological features

The importance of the serological features is calculated as previously described with the integrated

gradient score of every feature for every latent variable that was identified to be statistically significant

for predicting viral protection of humans, averaged across samples coming from the respective species.

Serological features with high scores (and at least ≥20%) can control latent variables in the global latent

space associated with human viral protection, and thus they are predictive of human protection. For

human features, we also validate that the univariate differences between protected and unprotected

individuals are indeed significant, by using a non-parametric Wilcoxon test, with Bonferroni correction

for multiple hypothesis testing.

Finally, we calculate the integrated gradient score for translating each non-human primate serological

profile to a human profile. The non-human features with high scores the human ones associated with

protection, can be considered serological non-human features predictive of human viral protection.

Inference of transcription factor activity

To infer the transcription factor activity, we utilized the VIPER algorithm[62] together with the Dorothea

Regulon[63]. The VIPER algorithm calculates the enrichment of gene expression signatures of regulons,

that are based on transcription regulatory networks. This way the activity of a transcription factor (TF) is

inferred based on the expression of downstream genes known to be regulated by this specific TF. The

Dorothea regulon contains known regulatory interactions, annotated based on the confidence that this

interaction exists. Here interactions are restricted to confidence levels A and B.

Hardware and software specifications

All models were expressed in and trained using the PyTorch framework[64] (version 1.12) in Python

(version 3.8.8). When using the 978 landmark genes and for the serology case study, the models were

trained in an NVIDIA GeForce RTX 3060 Laptop GPU with 6 GB of memory. The larger models (using

10,086 genes and the single-cell lung fibrosis data) were trained on the MIT Satori GPU cluster using

NVIDIA V100 32GB memory GPU cards. Pre-processing and statistical analysis of the results were done

in the R programming language (version 4.1.2). Visualization of results was done mainly using *ggplot2*[65].

More information about the versions of each library used can be found in the GitHub provided in the

Data and code availability section.

Data and code availability

The study did not produce new experimental data. All analyzed data that were used to train our models and produce all tables and figures, as well as all the code to generate those data, figures and tables are available at https://github.com/NickMeim/OmicTranslationBenchmark .

Acknowledgments

The authors would like to thank Brian Joughin for his valuable input on this work. We acknowledge funding from MIT-IBM Watson AI Lab, National Institutes of Health (NIH) IMPAcTB contract #75N93019C00071, NIH grant U01-AI67892, US Army Research Office Cooperative Agreement W911NF-19-2-0026, and the Swedish Research Council 06349 (AN).

Author contributions

NM and DAL conceived the study together with input from AN who run a pilot simulation. TNH and SM provided feedback on the methods and implementation of the approach. NM implemented the code and executed the simulations, preprocessed the data, trained the final models and analyzed their results. KP performed downstream analysis for the serology case study and interpreted the results. KP also wrote part of the respective results section. DYZ preprocessed and retrieved the data for the single-cell lung fibrosis case study and helped with result interpretation. NM wrote the manuscript and generated the figures. KP, DYZ, AN, TNH, SM and DAL edited the manuscript.

References

1. Mak, I. W., Evaniew, N. & Ghert, M. Lost in translation: animal models and clinical trials in cancer treatment. *Am J Transl Res* **6**, 114–118 (2014).

2. Brubaker, D. K. & Lauffenburger, D. A. Translating preclinical models to humans. *Science* **367**, 742–743 (2020).

3. Rhrissorrakrai, K. *et al.* Understanding the limits of animal models as predictors of human biology:

lessons learned from the sbv IMPROVER Species Translation Challenge. *Bioinformatics* **31**, 471–483

(2015).

4. Shay, T. *et al.* Conservation and divergence in the transcriptional programs of the human and mouse

immune systems. *Proceedings of the National Academy of Sciences* **110**, 2946–2951 (2013).

5. Gharib, W. H. & Robinson-Rechavi, M. When orthologs diverge between human and mouse. *Briefings*

in Bioinformatics **12**, 436–441 (2011).

6. Niepel, M. *et al.* Common and cell-type specific responses to anti-cancer drugs revealed by high

throughput transcript profiling. *Nat Commun* **8**, 1186 (2017).

7. Iorio, F. *et al.* Discovery of drug mode of action and drug repositioning from transcriptional

responses. *PNAS* **107**, 14621–14626 (2010).

8. Iwata, M., Sawada, R., Iwata, H., Kotera, M. & Yamanishi, Y. Elucidating the modes of action for

bioactive compounds in a cell-specific manner by large-scale chemically-induced transcriptomics. *Sci*

Rep **7**, 40164 (2017).

9. Fotis, C., Meimetis, N., Sardis, A. & G. Alexopoulos, L. DeepSIBA: chemical structure-based inference

of biological alterations using deep learning. *Molecular Omics* **17**, 108–120 (2021).

10.   Lachmann, A. *et al.* Massive mining of publicly available RNA-seq data from human and mouse.

Nat Commun **9**, 1366 (2018).

11.   Wilks, C. *et al.* recount3: summaries and queries for large-scale RNA-seq expression and splicing.

Genome Biology **22**, 323 (2021).

12.   Subramanian, A. *et al.* A Next Generation Connectivity Map: L1000 Platform and the First

1,000,000 Profiles. *Cell* **171**, 1437-1452.e17 (2017).

13.   Poussin, C. *et al.* The species translation challenge—A systems biology perspective on human

and rat bronchial epithelial cells. *Sci Data* **1**, 140009 (2014).

14.   Seok, J. Evidence-Based Translation for the Genomic Responses of Murine Models for the Study

of Human Immunity. *PLOS ONE* **10**, e0118017 (2015).

15.   Normand, R. *et al.* Found In Translation: a machine learning model for mouse-to-human

inference. *Nat Methods* **15**, 1067–1073 (2018).

16.   Brubaker, D. K., Proctor, E. A., Haigis, K. M. & Lauffenburger, D. A. Computational translation of

genomic responses from experimental model systems to humans. *PLOS Computational Biology* **15**,

e1006286 (2019).

17.   Brubaker, D. K. *et al.* Proteogenomic Network Analysis of Context-Specific KRAS Signaling in

Mouse-to-Human Cross-Species Translation. *Cell Systems* **9**, 258-270.e6 (2019).

18.   Brubaker, D. K. *et al.* An interspecies translation model implicates integrin signaling in infliximab-

resistant inflammatory bowel disease. *Science Signaling* **13**, eaay3258 (2020).

19.   Lee, M. J. *et al.* Computational Interspecies Translation Between Alzheimer's Disease Mouse

Models and Human Subjects Identifies Innate Immune Complement, TYROBP, and TAM Receptor

Agonist Signatures, Distinct From Influences of Aging. *Frontiers in Neuroscience* **15**, (2021).

20.   Schmidhuber, J. Deep Learning in Neural Networks: An Overview. *Neural Networks* **61**, 85–117

(2015).

21.   Tan, J., Hammond, J. H., Hogan, D. A. & Greene, C. S. ADAGE-Based Integration of Publicly

Available Pseudomonas aeruginosa Gene Expression Data with Denoising Autoencoders Illuminates

Microbe-Host Interactions. *mSystems* **1**, e00025-15 (2016).

22.   Wang, D. & Gu, J. VASC: Dimension Reduction and Visualization of Single-cell RNA-seq Data by

Deep Variational Autoencoder. *Genomics, Proteomics & Bioinformatics* **16**, 320–331 (2018).

23.   Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative modeling for single-

cell transcriptomics. *Nat Methods* **15**, 1053–1058 (2018).

24.   Eraslan, G., Simon, L. M., Mircea, M., Mueller, N. S. & Theis, F. J. Single-cell RNA-seq denoising

using a deep count autoencoder. *Nat Commun* **10**, 390 (2019).

25.   Lotfollahi, M., Wolf, F. A. & Theis, F. J. scGen predicts single-cell perturbation responses. *Nat*

Methods **16**, 715–721 (2019).

26.   Chen, L., Cai, C., Chen, V. & Lu, X. Learning a hierarchical representation of the yeast

transcriptomic machinery using an autoencoder model. *BMC Bioinformatics* **17**, S9 (2016).

27.   Lotfollahi, M. *et al.* Biologically informed deep learning to query gene programs in single-cell

atlases. *Nat Cell Biol* **25**, 337–350 (2023).

28.   Rampášek, L., Hidru, D., Smirnov, P., Haibe-Kains, B. & Goldenberg, A. Dr.VAE: improving drug

response prediction via modeling of drug perturbation effects. *Bioinformatics* **35**, 3743–3751 (2019).

29.   Way, G. P. & Greene, C. S. Extracting a biologically relevant latent space from cancer

transcriptomes with variational autoencoders. in *Biocomputing 2018* 80–91 (WORLD SCIENTIFIC,

2017). doi:10.1142/9789813235533_0008.

30.   Xie, R., Wen, J., Quitadamo, A., Cheng, J. & Shi, X. A deep auto-encoder model for gene

expression prediction. *BMC Genomics* **18**, 845 (2017).

31.   Umarov, R., Li, Y. & Arner, E. DeepCellState: An autoencoder-based framework for predicting

cell type specific transcriptional states induced by drug treatment. *PLOS Computational Biology* **17**,

e1009465 (2021).

32.   Lotfollahi, M. *et al.* Predicting cellular responses to complex perturbations in high-throughput

screens. *Molecular Systems Biology* **n/a**, e11517 (2023).

33.   Escolano, C., Costa-jussà, M. R. & Fonollosa, J. A. R. (Self-Attentive) Autoencoder-based

Universal Language Representation for Machine Translation. Preprint at

https://doi.org/10.48550/arXiv.1810.06351 (2018).

34.   Mohiuddin, T. & Joty, S. Unsupervised Word Translation with Adversarial Autoencoder.

Computational Linguistics **46**, 257–288 (2020).

35.   Sundararajan, M., Taly, A. & Yan, Q. Axiomatic Attribution for Deep Networks. in *Proceedings of*

the 34th International Conference on Machine Learning 3319–3328 (PMLR, 2017).

36.   Strunz, M. *et al.* Alveolar regeneration through a Krt8+ transitional stem cell state that persists

in human lung fibrosis. *Nat Commun* **11**, 3559 (2020).

37.   Habermann, A. C. *et al.* Single-cell RNA sequencing reveals profibrotic roles of distinct epithelial

and mesenchymal lineages in pulmonary fibrosis. *Science Advances* **6**, eaba1972 (2020).

38.   Barouch, D. H. *et al.* Evaluation of a mosaic HIV-1 vaccine in a multicentre, randomised, double-

blind, placebo-controlled, phase 1/2a clinical trial (APPROACH) and in rhesus monkeys (NHP 13-19).

The Lancet **392**, 232–243 (2018).

39.   Chung, A. W. *et al.* Dissecting Polyclonal Vaccine-Induced Humoral Immunity against HIV Using

Systems Serology. *Cell* **163**, 988–998 (2015).

40.   Barretina, J. *et al.* The Cancer Cell Line Encyclopedia enables predictive modelling of anticancer

drug sensitivity. *Nature* **483**, 603–607 (2012).

41.   Aran, D. *et al.* Reference-based analysis of lung single-cell sequencing reveals a transitional

profibrotic macrophage. *Nat Immunol* **20**, 163–172 (2019).

42.   Ramachandran, P. *et al.* Resolving the fibrotic niche of human liver cirrhosis at single-cell level.

Nature **575**, 512–518 (2019).

43.   Ching, T. *et al.* Opportunities and obstacles for deep learning in biology and medicine. *Journal of

The Royal Society Interface* **15**, 20170387 (2018).

44.   Wysocka, M., Wysocki, O., Zufferey, M., Landers, D. & Freitas, A. A systematic review of

biologically-informed deep learning models for cancer: fundamental trends for encoding and

interpreting oncology data. *BMC Bioinformatics* **24**, 198 (2023).

45.   Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep Bidirectional

Transformers for Language Understanding. *arXiv.org* https://arxiv.org/abs/1810.04805v2 (2018).

46.   Vaswani, A. *et al.* Attention is all you need. in *Advances in neural information processing systems*

5998–6008 (2017).

47.   Theodoris, C. V. *et al.* Transfer learning enables predictions in network biology. *Nature* 1–9

(2023) doi:10.1038/s41586-023-06139-9.

48.   [clue.io]. https://clue.io/.

49.   Ioffe, S. & Szegedy, C. Batch Normalization: Accelerating Deep Network Training by Reducing

Internal Covariate Shift. in *Proceedings of the 32nd International Conference on Machine Learning*

448–456 (PMLR, 2015).

50.   Rasamoelina, A. D., Adjailia, F. & Sinčák, P. A Review of Activation Function for Artificial Neural

Network. in *2020 IEEE 18th World Symposium on Applied Machine Intelligence and Informatics*

(SAMI) 281–286 (2020). doi:10.1109/SAMI48414.2020.9108717.

51.   Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I. & Salakhutdinov, R. Dropout: A Simple

Way to Prevent Neural Networks from Overfitting. *Journal of Machine Learning Research* **15**, 1929–

1958 (2014).

52.   Belghazi, M. I. *et al.* MINE: Mutual Information Neural Estimation. Preprint at

https://doi.org/10.48550/arXiv.1801.04062 (2021).

53.   Hjelm, R. D. *et al.* Learning deep representations by mutual information estimation and

maximization. Preprint at https://doi.org/10.48550/arXiv.1808.06670 (2019).

54.   Sun, F.-Y., Hoffmann, J., Verma, V. & Tang, J. InfoGraph: Unsupervised and Semi-supervised

Graph-Level Representation Learning via Mutual Information Maximization. Preprint at

https://doi.org/10.48550/arXiv.1908.01000 (2020).

55.   Fotis, C. *et al. DeepSNEM: Deep Signaling Network Embeddings for compound mechanism of*

action identification. 2021.11.29.470365

https://www.biorxiv.org/content/10.1101/2021.11.29.470365v1 (2021)

doi:10.1101/2021.11.29.470365.

56.   Sawilowsky, S. New Effect Size Rules of Thumb. *Journal of Modern Applied Statistical Methods* **8**,

(2009).

57.   Cohen, J. *Statistical Power Analysis for the Behavioral Sciences*. (Routledge, 2013).

58.   Kokhlikyan, N. *et al.* Captum: A unified and generic model interpretability library for PyTorch.

Preprint at https://doi.org/10.48550/arXiv.2009.07896 (2020).

59.   McConn, J. L., Lamoureux, C. R., Poudel, S., Palsson, B. O. & Sastry, A. V. Optimal dimensionality

selection for independent component analysis of transcriptomic data. *BMC Bioinformatics* **22**, 584

(2021).

60.   Sastry, A. V. *et al.* Mining all publicly available expression data to compute dynamic microbial

transcriptional regulatory networks. 2021.07.01.450581 Preprint at

https://doi.org/10.1101/2021.07.01.450581 (2021).

61.   Torsten Hothorn, A. Z. Diagnostic Checking in Regression Relationships. *R News* **2**, 7–10 (2002).

62.   Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using network-

based inference of protein activity. *Nat Genet* **48**, 838–847 (2016).

63.   Garcia-Alonso, L., Holland, C. H., Ibrahim, M. M., Turei, D. & Saez-Rodriguez, J. Benchmark and

integration of resources for the estimation of human transcription factor activities. *Genome Res.* **29**,

1363–1375 (2019).

64.   Paszke, A. *et al.* PyTorch: An Imperative Style, High-Performance Deep Learning Library. in

Advances in Neural Information Processing Systems vol. 32 (Curran Associates, Inc., 2019).

65.   Villanueva, R. A. M. & Chen, Z. J. ggplot2: Elegant Graphics for Data Analysis (2nd ed.).

Measurement: Interdisciplinary Research and Perspectives **17**, 160–167 (2019).

Figures

Figure 1: Model architecture and basic performance metrics. a) Framework architecture main
variations: I) **model variation 1:** One global space is constructed by mapping omic profiles in a space
where the distance between embeddings coming from the same perturbation is minimized. II) **model**
variation 2: CPA-based architecture where the latent space is separated into two, one global devoid of
species/cell effect and a composed latent space. **b)** Model performance in reconstructing and translating
gene expression profiles between the two cell lines with the most common perturbations in the L1000
dataset, A375 and HT29, by using only the 978 measured landmark genes. The **model variation 3** is the
one with a classifier simultaneously trained in one global latent space. For DCS modified v1-v2 see
Supplementary Methods 2.2-2.3. It is worth noting that DCS modified v2 has a distance term and a
direct translation term in its training loss. **c)** Model performance in reconstructing and translating gene
expression profiles between A375 and HT29 by using all 10,086 genes that are either measured or
belong to those that are well-inferred computationally. **d)** Performance in inferring transcription factors
activity by using the translated/predicted gene expression. **e)** Performance in correctly classifying cell
lines in different cases. **f)** Performance by using different inputs in the L1000.

Figure 2: Analysis of framework's performance and dependence on the data a) Performance in the
translation task of the CPA-based approach across different cell-line pairs and different sizes of training
data. **b)** Model performance in translation as a function of the initial similarity of 2 cell lines. **c)** Model
performance in translation for different percentages of paired conditions. **d)** Model performance in
translation for low-to-medium cell-line imbalance in the conditions of the training samples.

Figure 3: Properties of the latent space and model parameters interpretation. The two splits in 10-fold cross-validation present each time here are the ones where the maximum and minimum difference between the two distributions is observed. For every other split, the difference is between these two extreme cases. Additionally, panels a-c come from the first variation of the model with one global latent space while the rest come from the CPA-based approach **a)** Cosine distance between embeddings coming from random pairs of signatures and pairs coming from the same cell line. **b)** Cosine distance between embeddings coming from random pairs of signatures and pairs coming from the same condition tested on a different cell line **c)** Cosine distance between embeddings coming from random pairs of signatures and pairs being biological duplicates **d)** Distance between embeddings coming from random pairs of signatures and pairs coming from the same cell-line in the global and then the composed latent space in the CPA-based approach. **e)** Cohen's d between distributions of cosine distances between random pairs of embeddings and embeddings coming from the same cell distribution. **f-g)** 2D-Visualization of L1000 control conditions, untreated cell lines from the CCLE dataset, and the trainable vectors of the CPA-based framework containing the cell line basal effect added to perturbations.

Figure 4: Feature importance investigation **a-b)** Distribution of percentage rank in terms of the
importance of a gene to translate its expression to itself, using the 10,086 genes and the 978 landmark
genes respectively in the L1000 dataset. **c)** Per sample Spearman's correlation between absolute gene
importance scores and absolute gene expression. **d)** Important latent variable to classify a sample as PC3
or HA1E in the global latent space, when a classifier is simultaneously trained. **e)** Separation of cell lines
based on the top 2 most important latent variables according to the classifier. **f)** Average importance
scores of genes from PC3 to control cell-specific latent variables versus the importance scores from
HA1E, according to the individual encoders. **g)** Generalized Linear model classification performance by
using increasingly more important genes.

Figure 5: Evaluation of the framework in inter-species translation in fibrosis a-b) Performance (R^2) in predicting the per gene mean and variance of single-cell RNA-sequencing data for the tasks of reconstruction and species translation in the human-mouse lung fibrosis datasets. The comparison is done between the CPA-based framework using all genes or homologs and TransCompR **c)** Classification performance comparison in different tasks. **d)** Classification performance of the CPA-based framework using all genes in external disease datasets. **e)** Embeddings separation based on species in the global latent space versus the composed latent space. The effect size d is calculated as Cohen's d. **f)** Embeddings separation based on the cell type in the global latent space versus the composed latent space. The effect size d is calculated as Cohen's d.

Figure 6: Inter-species translation of serology data a) Framework architecture for inter-species
translation in the serology dataset. Instead of adding the species effect with a trained vector, it is adding
completely non-linear with 2 small intermediate neural networks. **b)** Per feature Pearson correlation
across in 10-fold cross-validation for human's features. **c)** Per feature Pearson correlation across in 10-
fold cross-validation for non-human primates' features. **d)** Classifiers' performance in various tasks. **e)**
Univariate differences between protected and non-protected individuals, for human serological features
related to viral protection, as found from the integrated gradient and LRT approach. **f)** Non-human
primate features predictive of human protection, by using importance score for translating them into
human features. Their quality is assigned based on the average reconstruction Pearson's r of these
features in 10-fold cross-validation: i) low quality = $0<r<0.25$, ii) medium quality = $0.25 \leq r<0.5$, iii) good
quality = $0.5 \leq r<0.75$, iv) high quality = $r \geq 0.75$