Autoencoder Model for Translating Omics Signatures

Nikolaos Meimetis[1], Krista M. Pullen[1], Daniel Y. Zhu[1], Trong Nghia Hoang[2], Sara Magliacane[3,4] and

Douglas A. Lauffenburger[1]*

1) Department of Biological Engineering, Massachusetts Institute of Technology, Cambridge, MA 02139, USA

2) School of Electrical Engineering and Computer Science, Washington State University, Pullman, WA, 99164-4236,

USA

3) Institute of Informatics, University of Amsterdam, Amsterdam, The Netherlands

4) MIT-IBM Watson AI Lab, Cambridge, MA 02139, USA

* Corresponding author, lauffen@mit.edu

Abstract

The development of effective therapeutics and vaccines for human diseases requires a systematic

understanding of human biology. While animal and in vitro culture models have successfully elucidated

the molecular mechanisms of diseases in many studies, they yet fail to adequately recapitulate human

biology as evidenced by the predominant likelihood of failure in clinical trials. To address this broadly

important problem, we developed a neural network autoencoder framework to map omics profiles from

designated species or cellular contexts into a global latent space, from which germane information can

be mapped between different contexts. This approach performs as well or better than extant machine

learning methods and can identify animal/culture-specific molecular features predictive of other

contexts, without requiring homology matching. For an especially challenging test case, we successfully

apply our framework to a set of inter-species vaccine serology studies, where no 1-1 mapping between

human and non-human primate features exists.

Introduction

Animal and cellular models are essential tools for studying and gaining insights into the underlying biology of human diseases, but these insights are not always clinically translatable, thus resulting in the failure of numerous therapeutics in clinical trials[1,2]. A common approach is to choose orthologous biomolecules, including genes, proteins, and cellular pathways, to perform direct functional comparisons across species. However, functional divergence and the absence of orthologous biomarkers can hinder these direct comparisons between species[3–5]. Furthermore, within the same species, comparing different cellular models reveals that the transcriptional response to chemical stimuli is cell type-specific due to distinct genetic profiles, creating an additional barrier to understanding the mechanism of action of various therapeutics[6–9]. Consequently, computational systems-based approaches are needed to gain a better understanding of the biological insights needed for inter-system translation.

Advancements in omics and sequencing technologies have enabled the generation of large-scale datasets from both animal and human species, facilitating more powerful analyses and comparison of molecular features between different biological systems[2,3,10–13]. Consequently, this has led to the development of numerous new statistical and machine learning models[3,13–17] for identifying similarities and differences between species and experimental models. Notably, most existing approaches focus on direct correlations between analogous biomarkers or processes across species despite known species and model system differences. To address this challenge, Brubaker et al. proposed a technique called "Translatable Components Regression"[18] (TransCompR), which can map human data into the principal component space of another species to identify translatable animal features that can predict human disease processes and phenotypes. Although this approach has been successfully applied to gain insights into a number of inflammatory pathologies[18,19], it requires the usage of homologs or at least comparable molecular features of the same dimensionality between species. Moreover, this linear approach is only capable of deciphering a part of inter-species relationships, which can be highly non-linear. We

emphasize, however, that TransCompR is not aimed centrally at aligning signatures between species but

rather at identifying what information inherent in a signature in one species is most germane for

understanding phenotype characteristics in the other – which is not the main goal of our new work here.

With the advent of large-scale datasets and deep learning approaches, autoencoders have the potential

to provide a deep learning framework that can approximate the non-linear relationships underlying

different biological systems and species. Autoencoders are artificial neural networks (ANNs), trained in

an unsupervised manner, that can embed raw input data into a lower dimensional space and

reconstruct the original data again[20]. Autoencoders have been successfully used in several tasks in

biology including analyzing high dimensional data[21,22], denoising single-cell RNA sequencing data[23–25],

deciphering the hierarchical structure of transcriptomic profiles[26,27], and predicting gene expression

caused by various stimuli[28–30].

Regarding cellular models Umarov, Li, and Arner developed DeepCellState[31], an autoencoder model

based on DeepFake technology[32], that can predict the transcriptional profile of a cell type after drug

perturbations based on the behavior of another cell type. However, this approach still requires a 1-1

mapping of molecular features, as perturbations from both models or species would need to pass

through the same part of the model. Also of note, the model captures a global cell representation based

on unsupervised learning of disentangled stimuli representations, which is an idea that has been

recently challenged[33]. Both of these limitations suggest that an approach, similar to those used in

language translation autoencoder-based models, which create a global language representation[34,35],

might improve biological inter-systems translation.

Relevant to the idea of building a global latent space for biological tasks, recently it was demonstrated in

an interpretable framework called compositional perturbation autoencoder (CPA)[36], how autoencoders

can be used to construct a basal latent space devoid of covariate and perturbational signals, capturing

only the basal cell state in single-cell RNA sequence data. CPA can be used to generate *in-silico*

transcriptional profiles at the single-cell level for different drug doses, cell types, time points, and

species when mapped to respective ortholog genes.

In this study we build upon ideas presented in the CPA approach, together with ideas from language

translation models[34,35] to develop an ANN framework that utilizes separate autoencoders for each

biological system, enabling the mapping of samples into a global cell or species space, while providing

feature importance estimates for various predictive tasks. The model in its basic form is trained to

simultaneously minimize the reconstruction error of the input omic profile and the distance between

samples coming from the same condition or perturbation in the global latent space. Our framework is

benchmarked, using the latest version of the L1000 dataset[12], against the established linear approaches

of TransCompR and FIT[15] (a linear regression model), as well as the neural network approach of

DeepCellState, which all require 1-1 feature mapping or input data of similar dimensions. We

demonstrate that our approach outperforms FIT and DeepCellState, while there is not a statistically

significant difference when comparing with TransCompR in cellular models where 1-1 mapping exists.

Additionally, we present several variations of the model and we illustrate the adaptability of our

framework by applying it to data of varying omics type and sample size. Furthermore, we demonstrate

its biological interpretability, an aspect that deep learning models often struggle to attain, by using an

integrated gradients approach[37]. To analyze the performance of the model in inter-species translation

we used a mouse[38] and a human[39] lung fibrosis single-cell RNA sequencing datasets, as well as two

small-scale serology datasets from humans and non-human primates vaccinated against HIV and SHIV,

respectively[40,41]. The latter serves as a novel case study of computational inter-species translation where

no 1-1 mapping between features exists. After building the model, we identified molecular features in

non-human primates that are predictive of protection against HIV in humans, without analogous

features necessarily being present in human data. These findings demonstrate that features derived

from this approach can be predictive of the phenotypic profile of another cellular or animal model

without requiring them to be homologs, allowing us to maximize the amount of information we can

capture from different model systems to advance both our understanding of complex human disease

biology and potentially develop more effective therapeutics and vaccines.

Results

A flexible Artificial Neural Network framework for omics translation

The framework is adaptive can be modified depending on the task at hand, however, it contains some

core elements and functionalities. The framework (see Methods for details) consists of two separate

ANN autoencoders for each biological system (e.g. cell line, species), while there are two main variations

of a latent space module which ensures that it removes the system-specific effect of perturbations and

constructs stimuli specific global latent space common for both autoencoders (Figure 1a). The

separation of the autoencoders allows for the utilization of molecular features without 1-1 mapping

between different systems. The first latent module consists of only one global latent space, created by

maximizing the similarity and Mutual Information (estimated via an ANN discriminator) of embeddings

coming from signatures that represent the same condition/perturbation in a different species or cell

line, while another prior discriminator forces the latent variables' distribution to be normal. The second

main latent module is based on the recently published compositional perturbation autoencoder (CPA)[36],

where there are two separated latent spaces: i) a global/basal latent space and ii) a composed latent

space. The global latent space is shaped the same way as in the first main module with the addition of

an extra discriminator/classifier which attempts to remove the cell-line or species effect by penalizing

the model when this classifier can distinguish between different cells or species, as in the original CPA.

In the composed latent space, a cell/species classifier is jointly trained to ensure there is a cell/species

effect, which is added through a trainable covariate vector or even completely non-linearly with two

intermediate ANNs. Finally, we introduced a novel functionality where feature importance can be

identified for various tasks based on integrated gradients[37] (Methods).

First, we compared our ANN framework with state-of-the-art techniques in the context of translating

homologous genes between in-vitro models within the same species. The L1000 dataset[12] provides an

ideal transcriptomics dataset for benchmarking different approaches for translating gene expression

profiles between different established human cell lines. The two main variations of our approach, as

well as a variation where a classifier is jointly trained on the global latent space to hide cell-line specific

information in a few latent variables (Methods), are compared with three previously published

approaches (DeepCellState[31], FIT[15], TransCompR[18]). Finally, the model is also compared to "direct

translation", where we directly use the gene expression profile in one cell line to predict an equivalent

perturbation in the other cell line. The models are evaluated both in the task of translating the gene

expression profile, as well as in the task of simply reconstructing the gene expression input, similar to

any autoencoder framework. The metrics used to evaluate the performance are: i) Pearson's correlation

between predicted gene expression and ground truth gene expression, ii) the per sample Spearman's

rank correlation, and iii) the accuracy in predicting correctly the sign of regulation of a gene. For

visualization purposes only statistically significant comparisons between our first main variation and

other techniques, in terms of Pearson's r, are shown (the p-values for all these comparisons across all

metrics are provided in Supplementary Tables 1-4) When utilizing the 978 landmark genes measured in

the L1000, all of our framework's variations provide a statistically significant increase in performance

compared to the direct translation across all metrics (Figure 1b). Our main method outperforms FIT[15]

and the basic DeepCellState[31] (DCS) method when translating from the HT29 cell line to A375, while

when translating in the reverse direction our framework outperforms even the variations of DCS (Figure

1b left). An interesting note is that the 2^{nd} variation of DCS also enforces a similarity in the latent space

when training the model, and since it outperforms the basic DCS, this indicates the importance of

enforcing similarity in the global latent space via some distance metric. The basic DCS approach while

taking a hit in the task of translation greatly outperforms the other approaches in terms of simple

reconstruction of the input within the same cell line. Nevertheless, our approach performs comparably

with other established methods in reconstruction (Figure 1b right). The other variations of our

framework perform comparably, even in the case of a global latent space where the cell line effect is not

completely removed (when training jointly a classifier). When using 10,086 genes (measured landmarks

and computationally well-inferred genes) all approaches take a significant hit in performance but still

perform better than the baseline while there is no statistically significant difference between our

approach and other state-of-the-art approaches (Figure 1c). Our approach only outperforms FIT in one

direction of translation. Finally, our approach performs better than direct translation also in the case of

using different genes as input for each cell-line (Figure 1f). The performance is comparable to that using

the same genes for both cell lines, indicating the potential to later extend the method in cases where no

1-1 mapping exists.

Performance in using predicted gene expression to infer transcription factor activity

In the case of using all ~10k genes, there is a decrease in performance (Figure 1b-1c), but it is possible

that the predicted values of these genes can still be summarized to infer the activity of transcription

factors (TFs) or other gene sets. Indeed by inferring transcription factor activity using the predicted gene

expression values with the VIPER algorithm[42] and the Dorothea regulon[43] (Methods) the model has

increased performance compared with using the ~10k genes and comparable to that in the case of the

landmark genes, while it still performs better than the baseline (Figure 1d). For the case of other gene

sets by performing Gene Set Enrichment Analysis (Supplementary Method 1, Supplementary Figure 3)

this is true only for small well-defined gene sets like KEGG pathways. The increased performance in

inferring only TFs activity might be a result of the previously shown ability of autoencoders to capture

regulatory relationships between genes[26,31].

Creating cell-line-specific regions in the latent space enables robust cell classification

To establish the ability of the model to retrieve cell-line-specific information in different variations we

evaluated the accuracy and F1 score in identifying the cell-line from which a sample is derived (Figure

1e). The performance of ANN classifiers trained on the original gene expression data and the PCA-

transformed data serves as the baseline. All classifiers are trained using the 10,086 genes of the L1000,

but the results in 978 landmark genes are similar (Supplementary Table 11). First, classifiers trained with

pre-trained embeddings from DCS or our framework with one global latent space are expected to have

lower performance, as embeddings coming from these approaches generate embeddings with the cell-

line effect being filtered as much as possible. Indeed, the performance is lower than the baseline and

our framework seems to generate more global embeddings than DCs making it more difficult to later

retrieve cell-line information. Interestingly when jointly training a classifier in the global latent space we

can outperform the baseline (Figure 1e) while the cell-line effect is still partially filtered in the higher

dimensions and embeddings coming from the same condition are close to each other regardless of

coming from different cells (Supplementary Figure 4). The CPA-based model in the composed latent

space perfectly classifies cell lines with, an even suspicious, 100% accuracy. The similarity of input gene

expression data in the validation sets, as well as the latent space embeddings similarity, is generally low

(Supplementary Figure 5) and no information leakage leads to this kind of performance. The CPA-based

framework can create very well-separated cell-line-specific regions (Supplementary Figure 6) in the

composed latent space, indicating the framework's ability to shape the latent spaces with robust cell-

line-specific regions and explaining the observed accuracy.

Framework's performance analysis

Due to the CPA-based approach's ability to shape the latent space and its classification performance, we

investigated the factors affecting the performance of this method, despite its slightly lower performance

in translation compared to that of a single global latent space. The framework has similar behavior and

performance for other cell-line pairs, as the original A375/HT29 pair used to initially benchmark the

approach against other models (Figure 2a). Some cell-line pairs perform slightly worse, as the original

correlation between the same perturbations in the cell-line pair correlates with the model's

performance and sets an upper bound in the model's performance (Figure 2b). Additionally, for all cell

lines, ~600 total training samples are enough to train a high-performance model (Figure 2a).

Interestingly, the amount of paired conditions required to train the framework can be low, as even with

~10-15% of the samples being paired is enough to shape a global latent space to facilitate translation

(Figure 2c). Finally, it seems the model is not affected by low to medium imbalance between conditions

coming from each cell line (Figure 2d). The same analysis for using all 10,086 genes shows similar trends

and results (Supplementary Figure 7).

Evaluation of latent space embeddings

The validity of the global latent embeddings (by using the 978 landmark genes) produced from our

framework is evaluated based on three main tasks (Figure 3a-3c): i) embeddings of pairs coming from

the same cell line should not be more similar to each other compared to embeddings from random

pairs, ii) embeddings of pairs coming from the same condition regardless of cell-line should be similar,

compared to embeddings from random pairs, and iii) embeddings of pairs that consist biological

duplicate signatures (meaning same drug tested on the same cell-line, with the same dose and duration)

should similar to each other compared to embeddings from random pairs. These tasks are evaluated

using cosine distance to quantify how close are embeddings coming from two gene expression

signatures. No cell-line effect is observed in the global latent space, both for training and validation

embeddings (Figure 3a, Supplementary Figure 8), proving that the framework succeeds in creating a

global cell-line space. Embeddings coming from the same condition are closer to each other than

embeddings coming from random pairs (Figure 3b), while biological duplicates are slightly even closer

(Figure 3c), validating that indeed we have constructed a stimuli-specific global latent space. Similar

patterns can be observed in the global latent space also when using the CPA-based approach (Figure

3d), while in the composed latent space where a cell-line effect should be visible, embeddings of pairs

coming from the same cell-line are closer in the latent space than random (Figure 3d). Cohen's d is used

to quantify the difference between the distributions of cosine distances across all folds (Figure 3e),

proving that indeed there is a much higher cell-line effect in the latent space than the effect in the global

latent space (not zero though).

Framework's trained parameters that capture biological information

To better interpret the framework, we investigate the biological information captured by some parts of

it. Since only the cell-line effect is filtered in the global latent space in the CPA-based framework then

the trainable covariate vectors should only add a basal cell-specific effect. Intuitively this would mean

that in the case of gene expression coming from untreated cells (control perturbations), the global latent

embeddings should capture a "zero"/basal cell state, and thus the trained covariate which is added to

that global representation should be similar to the composed latent space vectors which now capture

both the cell line effect. On this front, we used high-quality control samples from the L1000 dataset not

seen by the model during training, as well as samples coming from sequenced untreated cell lines from

the Cancer Cell Line Encyclopedia[44] (CCLE), pre-processed to use only genes present in the L1000

landmark genes and z-scored like the gene expression profiles used in the L1000 dataset. Additionally,

for this case study two models trained completely separately were trained: the original benchmark

model of A375/HT29 cell lines and another model using the PC3 prostate cancer cell line and the HA1E

normal epithelial cell line. The latter pair was chosen to be used in the subsequent analysis because of

both the comparably high performance of the model (Figure 2a) and a comparable amount of paired

conditions (330 in PC3/HA1E vs 406 in A375/HT29), while these two cell lines are significantly different

in terms of biology. Each trained covariate, even though the models were trained separately, is observed

to be closer to its respective cell-line control signatures, even those coming from an external dataset,

both when using PCA for dimensionality reduction (Figure 3f), where clearly defined cell-line specific

regions are observed, as well as when using t-SNE (Figure 3g).

Identification of important features that capture task-specific characteristics

The framework can identify both latent variables and genes, important for tasks of interest, enabling the

investigation of the framework's ability to identify important features that can be biologically

interesting. PC3 and HA1E cell lines were chosen, as described previously, to train a model with one

global latent space and one classifier trained jointly to classify the cell lines from which the samples

were derived (contradictory learning tasks). To identify the importance of input variables of different

parts of the model w.r.t their output, an integrated gradient-based approach[37] was utilized (see

Methods), attributing an importance score to each variable of interest. It is interesting since the same

genes are used for both cell lines, to identify what the model considers important to translate, in the

case of paired conditions, a gene expression profile from one cell line to the same set of genes in

another cell line. For approximately, 48% of the 10,086 genes, the model considers a different gene than

itself as important (important means in the top 20% genes based on their absolute importance score) to

be translated in the other cell line for the same condition (Figure 4a). For the case of landmarks genes,

this percentage slightly drops to 41% (Figure 4b). Since the cell lines chosen are one cancerous and one

non-cancerous this is an interesting result indicating that the model potentially avoids the fallacy of

using the same gene as a proxy for its gene expression across quite different biological systems.

Additionally, Spearman's correlation between the absolute importance scores and the absolute gene

expression across different samples is ~0.04 on average (Figure 4c), proving that the model doesn't

consider important just genes that are highly regulated. Subsequently, the jointly trained classifier can

identify a subset of important latent variables of the global latent space for classifying samples. Even

though the cell line effect is generally filtered and embeddings coming from the same condition are

close to each other globally (Supplementary Figure 4) the model can still identify 11 latent variables

(overlapping with the top-ranked variables based on absolute gradient score) that are important for

classifying a cell line (Figure 4d), by using a k-means based approach together with the calculated

importance scores (see Methods). These latent variables can greatly separate the latent vectors based

on the cell line (Figure 4e), even though globally the cell line-specific separation of embeddings is

minimized. Genes considered important by the encoders to control these latent variables should be

either cell line-specific genes or a subset of genes that can easily distinguish between cell lines. The

importance scores of the genes for each cell line-specific encoder do not correlate at all and are

different between the two cell lines (Figure 4f). It is possible to even train a very simple generalized

linear model to classify cell lines based on gene expression, only using a subset of these important

genes, achieving high performance and observing a saturation with only ~25-30 genes from each cell

line (Figure 4g).

Performance in inter-species translation for lung fibrosis

To evaluate the framework in inter-species translation, we utilize the raw gene counts coming from

single-cell RNA-sequencing of a mouse[38] and human[39] dataset with lung fibrosis. Based on the original

CPA manuscript [36], the decoders predict a mean and a variance for every gene, derived from a negative

binomial distribution. Furthermore, both a trainable species vector and another trainable cell type

vector are added to the global space, where it is attempted to filter both species and cell type effect. We

compare the CPA-based framework using all genes available in the dataset and using only the homologs,

as well as the best performing (in the L1000) variation of DCS and TransCompR. We evaluate the

performance in 10-fold cross-validation in terms of R^2 of the mean and variance in the reconstruction of

gene expression profiles, as well as in translating between mouse and human, where we would expect

to observe a similar distribution in a successful translation, and thus mean and variance. Our framework

outperforms the other approaches in terms of R^2 of the means both in reconstruction and translation

(Figure 5a). In predicting the variance there is not always a statistically significant improvement, while all

approaches have generally low performance (Figure 5b). Finally, there is not a significant difference

between using all genes or just homologs (Figure 5a-5b). Additionally, the CPA-based approaches and

TransCompR, when a classifier is trained, are compared in terms of classifying fibrosis, species, and cell

type. Cell type and species are also classified when a signature is translated into another species in the

composed latent space. Using all genes in our framework outperforms homolog genes approaches in the

fibrosis and species-translation tasks, while the performance of all approaches is high (Figure 5c). Similar

to what was observed in the L1000 dataset, species and cell type are predicted perfectly in our

framework. Additionally, both the species and cell-type effects are filtered (Figure 5e-5f, Supplementary

Figures 9-10) in the global latent space compared to the composed latent space. Finally, it is worth

noting that based only on the human lung fibrosis dataset, out of the top 10 genes contributing to the

top principal components, 3 of them are not homologs (Supplementary Figure 11). Regardless of

performance, a method considering only homologues would exclude important genes for lung fibrosis.

Generalization in other disease datasets

It is useful to investigate the extent to which the model can make predictions about disease, species,

and cell types in other datasets, used as external test sets, as well as different tissue and disease

datasets. On this front, an external mouse lung fibrosis[45] and human liver cirrhosis[46] dataset were used.

In the mouse dataset, even though different genes were measured than those in our model, the

performance is still decent in disease classification, and better than the random 50% (Figure 5d). In the

human dataset, which is an extreme case of fibrosis in a different organ, the model has significantly

lower performance but is still barely higher than random (Figure 5d). Interestingly, in both cases the

model can still perfectly identify cell types and species (Figure 5d), proving once again the ability of the

model to capture a very general species and cell type effect.

Building an inter-species model from serology data for predicting protection against HIV

We aimed to develop a framework for species translation that is still viable in the case where no 1-1

mapping between molecular features exist, a limitation of existing cross-species models. For this

purpose, we utilized non-human primate and human serology datasets[40,41] following vaccination against

SHIV and HIV, respectively. In this special case, the species effect was added completely non-linearly

during training, with 2 small intermediate neural networks (Figure 6a). This modification made no

significant difference in performance and in the properties of the global space, both in the case of the

L1000 and these serological datasets (Supplementary Figures 12-14). We reason that adding more non-

linear parts in the model is more appropriate for species translation in this setting, even if performance

is not increasing, due to few data points. The framework is trained so that protected individuals are

close in the global latent space regardless of species, while two separate classifiers try to predict

protection and vaccination outcomes (Figure 6a). In the composed latent space, a classifier predicts

species. The overall performance of the framework in 10-fold cross-validation in reconstructing the

input features is high (Figure 6b-6c). For the human serology features the performance is very high ($r =$

0.8932 ± 0.0115), while in non-human primates some features are not predicted well and there is a big

variation in performance between folds, the overall performance is still good ($r = 0.7107\pm0.0420$).

Finally, the performance across all classification tasks is exceptionally high (Figure 6d), with achieving

once again a perfect 100% accuracy in species classification and translation.

Non-human primates' serological features predictive of human protection against HIV

With our framework, we aimed to identify features predictive of human protection, even non-human

ones, by combining the integrated gradient approach (used in the L1000) with likelihood ratio tests (LRT)

performed on each latent variable (see Methods for more details). The likelihood of an alternative

model accounting for protection to derive the value of a latent variable is compared against a null model

not accounting for protection. Latent variables with an FDR-adjusted p-value<0.05 are considered

significant and the sign of the statistic signifies the directionality of the association with protection

(Supplementary Figure 16). For the integrated gradient approach, the integrated gradient of each latent

variable to predict protection was calculated for each human sample, according to the classifier in the

global latent space. Then the average score is used to signify importance. The intersection of latent

variables between the two approaches is used to identify the final latent variables contributing to

human protection (Supplementary Figure 17). Latent variables are denoted as important only if there is

an agreement between the likelihood ratio test results and the integrated gradients (and gradient

score≥10%).

To identify features that are important for predicting human protection, we utilize integrated gradient

scores derived by the respective encoder of each species to estimate the importance of a feature in

controlling a latent variable associated with protection. The human features identified indeed have a

statistically significant difference between protected and non-protected individuals (Figure 6e). Finally,

we identified non-human features that have a high gradient scores when translating to human

signatures, meaning these non-human primate features are predictive of human features linked with

viral protection (Figure 6f). These features are not necessarily associated with non-human primate viral

protection (Supplementary Figure 18) but they could be predictive of human protection.

Discussion

Here we developed an ANN framework that facilitates the translation of different omics profiles

between different biological systems, by building upon ideas introduced in the CPA approach[36] and

other species and cellular translation methods[13,15,18,31], together with ideas from language translation

models[34]. The explicit central goal here is to align omics signatures between species, rather than

identifying what information inherent in a signature in one species is most germane for understanding

phenotype characteristics in the other (which has been the objective in much of our recent work[16–19]).

The framework performs as well as (or even better in some cases) other state-of-the-art translation

techniques, when using homolog features, while it does not take a significant hit in performance when it

utilizes different features or non-homologs to represent two species or cell lines. Notably the framework

can construct a truly global latent space and manipulate it successfully to create stimuli-specific regions,

with high-performing classifiers trained jointly to make predictions for various tasks such as disease

diagnosis.

Current approaches[13–18] require homolog features and they utilize linear transformations to respectively

build their common latent space or translate signatures, thus being able to better approximate only the

linear inter-species relationships. Even the non-linear neural network approaches like DeepCellState[31]

require homology of the molecular features used to describe biological systems, without shaping the

latent space in some semi-supervised way. Additionally, approaches like FIT require a large number of

paired conditions to achieve high performance. Our framework could fill these gaps by non-linearly

modeling relationships between different biological systems, without requiring any kind of homology,

while it achieves high performance with only a small percentage of paired conditions used to construct

and tune the global latent space. This enables for the first time the training of a framework with

serology datasets where no 1-1 mapping of the features between the two biological models exists. This

way the identification of relationships between very different molecular profiles that correlate with

specific phenotypes, e.g. protection against infection, is possible, through the interpretation of the

framework.

Interpretability of deep learning models in biology remains a challenge and such models are often

criticized due to poor understanding of the biological relationships captured by the models[47,48]. On this

front, we demonstrate in our framework how integrated gradient approaches[37] can be used to estimate

the importance of features used by different parts of the framework for various tasks and decisions,

enabling to some extent the interpretation of the model. We were able to propose serological features

predictive of human protection against HIV, regardless of species. Furthermore, we explored the

biological information captured in the framework.

Different parts of the framework can capture and retrieve successfully the effect of species or cell types,

filtered from the global latent space, composing that way a new latent space that perfectly separates

species and cell types. This can explain the ability of the framework to predict, with very high

performance, general cell types (unfortunately not with high granularity regarding cell subtypes) and

species, even in external disease datasets, derived even from different organs/tissues, enabling this way

successful translation. However, there are still limitations in the generalization of the approach in

external datasets.

The performance in external disease datasets drops significantly as we move to more different

pathologies and tissues. Even for the same disease, different features measured can lead to reduced

performance regarding predictions made about disease diagnosis. The more features contained in the

molecular profile of a sample the more difficult is for the model to reconstruct this profile, while as

observed in the serology dataset not all features' predictions can be trusted. Even though our

framework can be trained even with fewer samples, still it contains a lot of parameters, especially when

using a larger number of molecular features, leading to overfitting, while training such large models is

not computationally trivial.

Some of these shortcomings can be alleviated by combining our framework with larger datasets, such as

ARCHS4[10], which contains the majority of publicly available RNA-sequencing data from humans and

mice. The Gene Expression Omnibus (GEO)[49] contains thousands of datasets, derived from different

types of molecular features, opening even the potential to utilize our framework for combining different

modalities. Training the framework with more data, more diverse unique conditions, and even training

to translate simultaneously between multiple systems and not just pairs, may enable higher

generalization and higher granularity in modeling different biological covariates, e.g. more specific cell

types.

Finally, the flexibility and adaptability of the framework allows it to be combined with other approaches,

to model many different biological systems. This could potentially lead to prior computational

optimization of biological systems and assays aiming to model human pathology. Features that are

informative and can explain or predict human biology, without requiring homology, can be identified

and optimized, while it is possible to use the framework to explore potential transcriptional

modifications to design better disease models, capturing the human phenotype in the clinic.

Methods

Pre-processing *in-vitro* transcriptomics benchmark dataset

The L1000 CMap resource[12] contains bulk gene expression data from drug perturbations across different

cell lines and provides a benchmark dataset with diverse conditions and a large sample size.

Additionally, a sufficient number of equivalent perturbations across different biological systems is

available (termed *paired conditions* for the rest of the manuscript) to evaluate the performance in

translating omics profiles. We selected high-quality drug perturbations from the latest version of the

L1000 dataset (accessed via clue.io). The level 5 z-score transformed and pre-processed differential gene

expression data of 978 landmark genes, measured with the L1000 assay, and additionally, 9,196

computationally well-inferred genes in the CMap resource, were considered in the subsequent analysis.

High-quality perturbations consist of signatures with more than three replicates, where at least half of

them passed standard quality control protocols in the assay, and were not identified as statistical

outliers. Additionally, for multiple-signature perturbagens (technical duplicates), only the signature with

the highest transcriptional activity score (TAS) across these technical duplicates was kept in the dataset.

These signatures are called exemplars and are specifically designated for further analysis in the CLUE

platform[50]. TAS is a metric inherent to the L1000 dataset that quantifies signal strength and

reproducibility and is calculated as the geometric mean of the number of differentially expressed

transcripts and the 75th quantile of pairwise replicate correlations. Finally, the ability to distinguish

between random signatures and true biological duplicates, meaning the same perturbagen tested on

the same cell line for the same duration and dosage, was evaluated for different parts of the dataset,

split using varying TAS thresholds (Supplementary Figure 19) and it was decided to keep samples with

TAS≥0.3. For the case of control signatures, we followed the same procedure without filtering based on

the TAS number.

Pre-processing single-cell RNA sequencing interspecies datasets

For the human and mouse single-cell RNA-sequencing datasets, first, each cell annotated was

summarized into one of the four many cell types: i) immune cells, ii) mesenchymal cells, iii) epithelial

cells, iv) endothelial cells, and iv) stem cells. These were used later to filter cell effect from the global

latent space and these are the categories used in subsequent cell-type classification. Finally, while the

raw gene counts are used for reconstruction from the decoder in the loss function, the encoders take as

input the log-transformed counts ($x_{input} = \log_{10}(count + 1)$).

Pre-processing serology dataset preprocessing

For all serology data, we aimed to build a model with just antibody and receptor measurements. From

the human serology data, avidity molecular features were first dropped and then the data were scaled

by z-scoring per feature. For the non-human primates' samples taken in week 28 were taken, while

antibody-dependent cellular function features and mass spectrometry data were dropped, so that we

utilize a similar modality of antibody and receptor measurements, as we did in humans. Then the data

are log-transformed ($x = \log_{10}(MFI + 1)$), since they consist of Median Fluorescence Intensity (MFI)

values and the median per feature from controls is subtracted from each feature to standardize the data

and create a differential expression effect. Finally, the data are again scaled by z-scoring per feature.

The general framework and the training procedure

Generally, the framework always consists of two independent encoders and two independent decoders

for each of the species or cell lines in the pair attempting translation, while inside some latent module, a

global latent space is shaped (Figure 1a). Both the encoders and the decoders are multi-layer fully

connected neural networks, with each layer consisting sequentially of a fully-connected layer, a batch

normalization layer, an ELU activation function, and a dropout layer. Only their final output layer

consists of only one fully-connected layer without a bias term.

For the construction of the global latent space, in every variation of the framework, the distance

($L_{distance}$) between embeddings of profiles coming from the same perturbation is minimized, their

cosine similarity (L_{cosine}) and mutual information (L_{MI}) is maximized, and finally the divergence of the

distribution of the latent variables from a normal distribution is also minimized (L_{prior}). Both cosine

similarity and Euclidean distance losses were added to enforce the strongest possible filtering of species

and cell type effect, while the cosine similarity also enforces normalization of the latent embeddings.

The last two tasks mentioned above are achieved via two different estimated ANN discriminators, based

on the Deep InfoMax and InfoGraph approaches[51,52], where the Jensen-Shannon Mutual Information

between embeddings coming from the same perturbation is estimated and the extra prior loss is added,

according to the following equation:

467
$$L = (L_{MI}) + (L_{prior}) = \left(-\frac{1}{N1 + N2} \sum_{i=1}^{N1} \sum_{j=1}^{N2} D_1(z_i, z_j) \right) + (D_2(Z||N))$$

Where Z denotes the global latent space embeddings, D_1 is the discriminator estimating the mutual

information between two embeddings and D_2 is the second discriminator which forces the distribution

of the features of each learned embedding to be close to the normal distribution N. D_1 consists of 3

fully-connected layers, each of them followed by a ReLU function and one fully-connected skip

connection. Likewise, D_2 has three similar fully-connected layers and the final scalar output is passed

through a sigmoid function. These regularization loss terms ($L_{distance}$, L_{cosine}, L_{MI}) are calculated and

averaged across every pair of global embeddings (z_i, z_j) that are coming from the same condition. The

L_{prior} is calculated for every sample in the dataset, meaning every global latent embedding and

averaged across samples.

For the case of the L1000 dataset, similar perturbations are considered the same drug, tested on the

same dose and time duration just on similar cell lines. For the lung fibrosis dataset, similar profiles are

considered those coming from samples that have the same diagnosis (fibrosis or not). For the serology

datasets, we train the framework so that embeddings coming from protected individuals against HIV are

close to each other regardless of species (and even vaccination status)

The basic task of this autoencoder framework is reconstruction, which is achieved by minimizing some

kind of reconstruction loss (L_{recon}). In the case of simple z-scored profiles coming from bulk data, this is

done by minimizing the mean sum of squared errors between the input of the encoders and the output

of the decoders. The sum or squares error is averaged across samples. For single-cell RNA-sequencing

data, based on the implementation proposed in the original CPA manuscript[36] (found here

https://github.com/facebookresearch/CPA), the negative binomial negative log-likelihood is used to

optimize the reconstruction, by assuming that the data are derived from a negative-binomial

distribution. In that case, the decoders are not just predicting one value per molecular feature, but a

mean and variance. The negative binomial negative log-likelihood loss is calculated for every sample and

the average across all samples in the batch is taken to be minimized.

Finally, classifiers, which also consist of multiple fully connected layers and a final SoftMax activation

function for the output, are used for different classification tasks. The average entropy loss across

samples for every classification task in the latent space (global or not) is minimized.

L2-regularization of the weights and bias of the encoders, decoders, and classifiers is also enforced. This

is implemented by calculating and minimizing the sum of squares for the aforementioned trainable

parameters.

All the above can be summarized in the following loss function, which consists of the basic loss used to

train the basic format of the framework (for the CPA-based approach see the corresponding section in

Methods, and for all other variations see Supplementary Method 2):

$Loss_{basic} = \lambda_{recon} * L_{recon} + \lambda_{distance} * L_{distance} + \lambda_{MI} * L_{MI} + \lambda_{prior} * L_{prior} + \sum_{i=1}^{2} \lambda_{enc,i} *$

$L2_{encoder,i} + \sum_{i=1}^{2} \lambda_{dec,i} * L2_{decoder,i} + \sum_{i=1}^{M} \lambda_{class,i} * entropy_i - \lambda_{cosine} * L_{cosine}$

Where M is the number of classifiers and thus individual classification tasks.

For values for each of the λ used in the loss function see Supplementary Table 12.

Translation of omics profiles

For translating an omics profile, we first encode it in the global latent space, using the encoder

representing the respective biological system (meaning species or cell line). Then the decoder of the

other biological system in the pair of the currently trained framework is using directly the embedding of

the global latent space to reconstruct the profile in the other system and thus translate the signature. In

the case of the CPA-based framework first, the species and cell type effect are added, via trained vectors

(Figure 1a) or intermediate small neural networks (Figure 6a), and then this composed latent signature is

passed through the decoder. During the evaluation of the model we utilize paired conditions, where the

same perturbation is present in both species/cell lines, and we know the ground truth expression profile

in both cases (more details in the Evaluation procedure and metrics section).

Global latent space with a jointly and competitively trained classifier

In this case, we aim to construct a generally global latent space, but also hide some species or cell line

information in some latent variables, we jointly train a simple classifier to correctly predict, in our case

study in the L1000, the cell line label. So just an entropy loss is added in the original description of the

framework. The construction of a global latent space and the training of the classifier is, in reality,

competing tasks, where the framework is trained to achieve some kind of stable trade-off.

CPA-based framework

For the CPA-based framework, we utilize the same tactics for building the global latent space and the

same basic loss function with some additions.

First of all, as described in the original CPA manuscript[36], during training we are iterating between

training classifier (updating only its parameters) in the global latent space, to predict cell type labels and

species labels, and training the rest of the framework with the extra addition of adding a penalty

($entropy_{adverse}$) if the classifier can correctly classify species and cell types. This way we are training to

update the parameters of the encoders, decoders, trainable vectors, and other classifiers so that the

entropy derived from this adverse classifier is maximized. This adverse classifier is initially pre-trained

only with encoders and discriminators so that it can already distinguish cell types and species in the

global space, making it more difficult to trick it, and thus trying harder to remove the species/cell effect.

Then the species and cell type effects are added via trainable vectors, to which is also applied L2-

regularization. This vector is trainable for the model to learn the unknown species and cell type effects

filtered from the global latent space. In the newly composed latent space, from which the decoders are

sampling embeddings, classifiers are jointly trained to correctly classify cell types, and species (or even

disease diagnosis).

All the above can be summarized in this new loss function:

$$Loss = Loss_{basic} - \lambda_{adverse} * entropy_{adverse} + \lambda_{trained_{effect}} * L2_{trained_{effect}}$$

Framework for the serology datasets

In the serology dataset we utilize the CPA-based framework but instead of adding the species effect with

trainable vectors, small artificial neural networks are utilized. These do not change the dimensionality of

the latent space and consist only of two fully-connected layers. This way they act as signal translators

adding species effect in a completely non-linear way. L2-regularization terms for these small ANNs are

added to the training loss function.

Additionally, it is aimed to later identify features predictive of protection or vaccination status regardless

of species. For this reason, we train two classifiers predicting vaccination and protection status in the

global latent space, which in other models would be trained in the composed latent space. We care

more about protection and thus, as described previously, we aim to create similar embeddings and

minimize their distance in the global latent space just by looking at protection status.

Framework's basic hyperparameters

Here we present the basic parameters used to train the model. For a more detailed overview of all

hyperparameters see Supplementary Table 13. No thorough hyperparameter tuning was performed,

and values were selected based on empirical values and tuned so that there is convergence in the

training loss and the training reconstruction performance (Pearson's r and/or R^2). Additionally, these

values were also tuned so that the performance in training (not validation) is sufficiently high, meaning

that the model is at least able to fit the given data. This empirical tuning was done only based on the 1st

training set in 10-fold cross-validation.

The latent space dimension was chosen to be as small as possible until the model's performance

dropped in both training and validation of only the 1st fold. Based on this latent dimension and the

original input dimension of the data the sizes of hidden layers of the encoders were chosen to be in-

between, gradually reducing the input dimension to that of the latent space. The actual size and number

were constrained by practical memory limits. The decoders had the same number and sizes of hidden

layers as those of the encoders, but now they increase the size of the embeddings from the latent

dimension to the original input dimension.

For using the L1000 978 landmark genes:

• Latent dimension = 292

• hidden encoder layers dimensions = [640,384]

• hidden decoder layers dimensions = [384,640]

• cell line classifier (also adverse for CPA) hidden layer dimensions = [256,128,64]

• total batch size = 512

• number of epochs = 1000

• learning rate = 0.001

For using the L1000 10,086 genes:

• Latent dimension = 1024

• hidden encoder layers dimensions = [4096,2048,1024,512]

• hidden decoder layers dimensions = [512,1024,2048, 4096]

• cell line classifier (also adverse for CPA) hidden layer dimensions = [512,256,128]

• total batch size = 512

• number of epochs = 1000

• learning rate = 0.001

For using the lung fibrosis datasets:

• Latent dimension = 512

• hidden encoder layers dimensions = [4096,2048]

• hidden decoder layers dimensions = [2048, 4096]

• cell type classifier hidden layer dimensions = [256,128,64,32]

• species classifier hidden layer dimensions = [256,128,64,32]

• fibrosis classifier hidden layer dimensions = [256,128,64,32]

• adverse classifiers hidden layers dimensions = [512,256,128,64]

• total batch size = 1024

• number of epochs = 200

• learning rate = 0.001

For using the serology datasets:

• Latent dimension = 32

• hidden encoder layers dimensions = [64]

• hidden human decoder layers dimensions = [64]

• hidden primate decoder layers dimensions = [128]

• all classifiers hidden layer dimensions = [32,16,8]

•   intermediate ANN translators hidden layers dimensions= [32]

•   total batch size = 50

•   number of epochs = 2000

•   learning rate = 0.001

Evaluation procedure and metrics

A part of the data was hidden during training and used to evaluate performance in unseen data, by using

10-fold cross-validation splits. For evaluating the translation of the whole omics profile, we made sure

that for the case of paired conditions, the perturbation in both species or cell lines was hidden during

training.

For the classification tasks simply, total accuracy and F1-score (micro F1 for multiple categories) were

used:

609
$$\text{Accuracy} = \frac{\sum_{i=1}^{K} TP_i + \sum_{i=1}^{K} TN_i}{\sum_{i=1}^{K} TP_i + \sum_{i=1}^{K} TN_i + \sum_{i=1}^{K} FP_i + \sum_{i=1}^{K} FN_i}$$

610
$$F1 - \text{micro} = \frac{\sum_{i=1}^{K} TP_i}{\sum_{i=1}^{K} TP_i + \frac{1}{2} * \left(\sum_{i=1}^{K} FP_i + \sum_{i=1}^{K} FN_i\right)}$$

Where K is the total number of classes.

To evaluate the validity of the predictions ($\hat{y}$) of whole signatures in translation and reconstruction,

compared to the ground truth (y), we utilized: i) the global Pearson's r, ii) per sample Spearman's

correlation (r_s), and iii) sign accuracy

$r(\hat{y}, y) = \frac{\sum (y_i - \bar{y})(\hat{y}_i - \bar{\hat{y}})}{\sqrt{\sum (y_i - \bar{y})^2 \sum (\hat{y}_i - \bar{\hat{y}})^2}}$, where $\hat{y}$ and y are flattened and the ith element is the ith point in these

flattened vectors

$r_s = \frac{\sum_{i=1}^{N} r(\text{Rank}(\hat{y}), \text{Rank}(y))_i}{N}$, where N is the number of samples

$\text{sign accuracy} = \frac{TP+TN+TrueZeros}{\text{total predictions}}$

For the single-cell RNA-sequencing data where we predict the per gene mean and variance we calculate

the R^2 of per gene mean and variance, similar to the original CPA manuscript[36]. In general, R^2 is

calculated as: $R^2 = 1 - \frac{RSS}{TSS}, where\ RSS = \sum(\hat{y}_i - y_i)^2\ and\ TSS = \sum(y_i - \bar{y})^2$

Separation of latent space embeddings

To evaluate how similar are embeddings of different signatures, and whether there is a separation

based on cell, species, or conditions in the latent space we utilize cosine distance, ranging from 0 (the

same) to 2 (completely) different: $cosine\ distance = 1 - cosine\ similarity = 1 - \frac{\sum_{i=1}^{d} z_{1,i} z_{2,i}}{\sqrt{\sum_{i=1}^{d} z_{1,i}^2} \sqrt{\sum_{i=1}^{d} z_{2,i}^2}}$,

where z_1 a and z_2 are two latent space vectors to be compared and d is the total number of elements in

the vector, meaning the latent dimension.

To estimate if there is a cell, species, or condition effect, and compare it between the composed and

global latent space we utilize Cohen's d to estimate the effect size between the distributions of cosine

distances, derived from random pairs of embeddings and pairs coming from the same cell, species, or

condition. The effect size is thus calculated using the mean and standard deviations of two cosine

distance (cos) distributions as: $d = \frac{\overline{cos}_1 - \overline{cos}_2}{\sqrt{\frac{((n_1-1)s_1^2 + (n_2-1)s_2^2)}{n_1+n_2-2}}}$.

A Cohen's d around 0.8 is a large effect size (around 2 is considered a huge effect size) while around 0.5

is a medium effect size, and around 0.2 and below is considered small or very small[53,54].

Feature importance using integrated gradients

To estimate the importance of features we utilize integrated gradients[37] from the Captum library[55].

$InterGrad_i(x) = (x_i - x_i') \int_{a=0}^{1} \frac{dF\left(x' + a(x - x')\right)}{dx_i} da, x' = baseline = 0$

The importance scores to make a prediction are calculated based on the gradient with respect to the

input of the model, and thus the higher the absolute integrated gradient the higher the importance of

that input feature to control the output. A negative score means the variable has a negative effect

pushing the prediction to the other class, while a positive score has a positive effect.

For example, if we want to identify important latent variables to classify a sample as one coming from a

particular cell line we calculate the integrated gradient of every latent variable to make the classification

and take the average across all samples. Similarly, if for example, we are aiming to calculate the

importance of genes to control latent variables in the global latent space we can calculate the integrated

gradient score of every gene for every variable in every sample, and then take the average across

samples.

K-means-based separation of important latent variables

Latent variables can be separated into important and unimportant ones using k-means, inspired by an

approach that was used to identify important connections between latent components and genes in

microbial organisms by using the weights derived from independent component analysis [56,57]. We

assume that only 2 main clusters of latent variables exist, one containing important variables and one

containing unimportant ones. On this front, the latent variables are clustered based on their absolute

gradient scores into 3 clusters, where 3rd cluster is assumed to be a very small cluster of outliers. The

midpoint between the variable with the highest score in the unimportant cluster and the variable with

the lowest score in the important cluster is used as a threshold to distinguish between significantly

important and unimportant latent variables. As a sanity check the important variables are also

compared with the top-ranked variables based on their score.

Likelihood ratio tests for the identification of important latent variables

To identify which latent embeddings correlate with viral protection after accounting for vaccination

status and species, a likelihood ratio test (LRT) was performed on each individual latent variable. Here,

the likelihood (L) of the alternative model (H_A): $latent\ variable_i\ embeddings \sim protection +$

$vaccination + species$ was compared to the likelihood of the nested model, or null hypothesis,

(H_0): $latent\ variable_i\ embeddings \sim vaccination + species$ in $LRT = -2\ln\left(\frac{L(H_0)}{L(H_A)}\right)$. We rejected

H_0 for $latent\ variable_i$ when the FDR-adjusted p-value of the chi-square test was less than 0.05,

concluding that the model including protection has a statistically significant better fit than the model

without protection. In the volcano plots, the $-\log(pvalue)$ is plotted against the t-value for the

protection term in the alternative model. This method assumes that the relationship between the latent

variable embeddings and protection is linear. R package *lmtest*[58] (version 0.9.40) was used to perform

these statistical tests. Finally, the intersection of these latent variables with significant latent variables

(average percentage importance score across folds ≥10%), based on their gradient score from the

trained protection classifier, is used for the final identification of robust latent variables associated with

viral protection. We keep latent variables that the sign of correlation with protection agrees in both

approaches.

Identification of protection-associated serological features

The importance of the serological features is calculated as previously described with the integrated

gradient score of every feature for every latent variable that was identified to be statistically significant

for predicting viral protection of humans, averaged across samples coming from the respective species.

Serological features with high scores (and at least ≥20%) can control latent variables in the global latent

space associated with human viral protection, and thus they are predictive of human protection. For

human features, we also validate that the univariate differences between protected and unprotected

individuals are indeed significant, by using a non-parametric Wilcoxon test, with Bonferroni correction

for multiple hypothesis testing.

Finally, we calculate the integrated gradient score for translating each non-human primate serological

profile to a human profile. The non-human features with high scores the human ones associated with

protection, can be considered serological non-human features predictive of human viral protection.

Transcription factor activity inference

To infer the transcription factor activity, we utilized the VIPER algorithm[42] together with the Dorothea

Regulon[43]. The VIPER algorithm is testing for regulon enrichment on gene expression signatures, based

on a prior knowledge transcription regulatory network. This way based on the expression of

downstream genes known to be regulated by a specific transcription factor, the activity of that TF is

inferred. The Dorothea regulon contains known regulatory interactions, annotated based on the

confidence that this interaction exists. We utilized only interactions of confidence levels A and B.

Hardware and software specifications

All deep learning models were trained using the PyTorch framework[59](version 1.12) in python version

3.8.8. When using the 978 landmark genes and for the serology case study, the models were trained in

an NVIDIA GeForce RTX 3060 Laptop GPU with 6 GB of memory. The larger models (using 10,086 genes

and the single-cell lung fibrosis data) were trained on the MIT Satori GPU cluster using NVIDIA V100

32GB memory GPU cards. Pre-processing and statistical analysis of the results were done in the R

programming language version 4.1.2. Visualization of results was done mainly using *ggplot2*[60]. More

information about the versions of each library used can be found in the GitHub provided in the Date and

code availability section.

Data and code availability

The study did not produce new experimental data. All analyzed data that were used to train our models

and produce all tables and figures, as well as all the code to generate those data, figures and tables are

available at https://github.com/NickMeim/OmicTranslationBenchmark .

Acknowledgements

The authors would like to thank Avlant Nilsson and Brian Joughin for their valuable input on this work.

We acknowledge funding from MIT-IBM Watson AI Lab, National Institutes of Health (NIH) IMPAcTB

contract #75N93019C00071, NIH grant U01-AI67892, US Army Research Office Cooperative Agreement

W911NF-19-2-0026.

References

1. Mak, I. W., Evaniew, N. & Ghert, M. Lost in translation: animal models and clinical trials in cancer

treatment. *Am J Transl Res* **6**, 114–118 (2014).

2. Brubaker, D. K. & Lauffenburger, D. A. Translating preclinical models to humans. *Science* **367**, 742–

743 (2020).

3. Rhrissorrakrai, K. *et al.* Understanding the limits of animal models as predictors of human biology:

lessons learned from the sbv IMPROVER Species Translation Challenge. *Bioinformatics* **31**, 471–483

(2015).

4. Shay, T. *et al.* Conservation and divergence in the transcriptional programs of the human and mouse

immune systems. *Proceedings of the National Academy of Sciences* **110**, 2946–2951 (2013).

5. Gharib, W. H. & Robinson-Rechavi, M. When orthologs diverge between human and mouse. *Briefings*

in Bioinformatics **12**, 436–441 (2011).

6. Niepel, M. *et al.* Common and cell-type specific responses to anti-cancer drugs revealed by high

throughput transcript profiling. *Nat Commun* **8**, 1186 (2017).

7. Iorio, F. *et al.* Discovery of drug mode of action and drug repositioning from transcriptional

responses. *PNAS* **107**, 14621–14626 (2010).

8. Iwata, M., Sawada, R., Iwata, H., Kotera, M. & Yamanishi, Y. Elucidating the modes of action for

bioactive compounds in a cell-specific manner by large-scale chemically-induced transcriptomics. *Sci*

Rep **7**, 40164 (2017).

9. Fotis, C., Meimetis, N., Sardis, A. & G. Alexopoulos, L. DeepSIBA: chemical structure-based inference

of biological alterations using deep learning. *Molecular Omics* **17**, 108–120 (2021).

10.   Lachmann, A. *et al.* Massive mining of publicly available RNA-seq data from human and mouse.

Nat Commun **9**, 1366 (2018).

11.   Wilks, C. *et al.* recount3: summaries and queries for large-scale RNA-seq expression and splicing.

Genome Biology **22**, 323 (2021).

12.   Subramanian, A. *et al.* A Next Generation Connectivity Map: L1000 Platform and the First

1,000,000 Profiles. *Cell* **171**, 1437-1452.e17 (2017).

13.   Poussin, C. *et al.* The species translation challenge—A systems biology perspective on human

and rat bronchial epithelial cells. *Sci Data* **1**, 140009 (2014).

14.   Seok, J. Evidence-Based Translation for the Genomic Responses of Murine Models for the Study

of Human Immunity. *PLOS ONE* **10**, e0118017 (2015).

15.   Normand, R. *et al.* Found In Translation: a machine learning model for mouse-to-human

inference. *Nat Methods* **15**, 1067–1073 (2018).

16.   Brubaker, D. K., Proctor, E. A., Haigis, K. M. & Lauffenburger, D. A. Computational translation of

genomic responses from experimental model systems to humans. *PLOS Computational Biology* **15**,

e1006286 (2019).

17.   Brubaker, D. K. *et al.* Proteogenomic Network Analysis of Context-Specific KRAS Signaling in

Mouse-to-Human Cross-Species Translation. *Cell Systems* **9**, 258-270.e6 (2019).

18.   Brubaker, D. K. *et al.* An interspecies translation model implicates integrin signaling in infliximab-

resistant inflammatory bowel disease. *Science Signaling* **13**, eaay3258 (2020).

19.   Lee, M. J. *et al.* Computational Interspecies Translation Between Alzheimer's Disease Mouse

Models and Human Subjects Identifies Innate Immune Complement, TYROBP, and TAM Receptor

Agonist Signatures, Distinct From Influences of Aging. *Frontiers in Neuroscience* **15**, (2021).

20.   Schmidhuber, J. Deep Learning in Neural Networks: An Overview. *Neural Networks* **61**, 85–117

(2015).

21.   Tan, J., Hammond, J. H., Hogan, D. A. & Greene, C. S. ADAGE-Based Integration of Publicly

758   Available Pseudomonas aeruginosa Gene Expression Data with Denoising Autoencoders Illuminates

759   Microbe-Host Interactions. *mSystems* **1**, e00025-15 (2016).

760   22.   Wang, D. & Gu, J. VASC: Dimension Reduction and Visualization of Single-cell RNA-seq Data by

761   Deep Variational Autoencoder. *Genomics, Proteomics & Bioinformatics* **16**, 320–331 (2018).

762   23.   Lopez, R., Regier, J., Cole, M. B., Jordan, M. I. & Yosef, N. Deep generative modeling for single-

763   cell transcriptomics. *Nat Methods* **15**, 1053–1058 (2018).

764   24.   Eraslan, G., Simon, L. M., Mircea, M., Mueller, N. S. & Theis, F. J. Single-cell RNA-seq denoising

765   using a deep count autoencoder. *Nat Commun* **10**, 390 (2019).

766   25.   Lotfollahi, M., Wolf, F. A. & Theis, F. J. scGen predicts single-cell perturbation responses. *Nat*

767   *Methods* **16**, 715–721 (2019).

768   26.   Chen, L., Cai, C., Chen, V. & Lu, X. Learning a hierarchical representation of the yeast

769   transcriptomic machinery using an autoencoder model. *BMC Bioinformatics* **17**, S9 (2016).

770   27.   Lotfollahi, M. *et al.* Biologically informed deep learning to query gene programs in single-cell

771   atlases. *Nat Cell Biol* **25**, 337–350 (2023).

772   28.   Rampášek, L., Hidru, D., Smirnov, P., Haibe-Kains, B. & Goldenberg, A. Dr.VAE: improving drug

773   response prediction via modeling of drug perturbation effects. *Bioinformatics* **35**, 3743–3751 (2019).

774   29.   Way, G. P. & Greene, C. S. Extracting a biologically relevant latent space from cancer

775   transcriptomes with variational autoencoders. in *Biocomputing 2018* 80–91 (WORLD SCIENTIFIC,

776   2017). doi:10.1142/9789813235533_0008.

777   30.   Xie, R., Wen, J., Quitadamo, A., Cheng, J. & Shi, X. A deep auto-encoder model for gene

778   expression prediction. *BMC Genomics* **18**, 845 (2017).

779   31.   Umarov, R., Li, Y. & Arner, E. DeepCellState: An autoencoder-based framework for predicting

780   cell type specific transcriptional states induced by drug treatment. *PLOS Computational Biology* **17**,

781   e1009465 (2021).

32.   Nguyen, T. T. *et al.* Deep learning for deepfakes creation and detection: A survey. *Computer*

Vision and Image Understanding **223**, 103525 (2022).

33.   Locatello, F. *et al.* Challenging Common Assumptions in the Unsupervised Learning of

Disentangled Representations. in *Proceedings of the 36th International Conference on Machine*

Learning 4114–4124 (PMLR, 2019).

34.   Escolano, C., Costa-jussà, M. R. & Fonollosa, J. A. R. (Self-Attentive) Autoencoder-based

Universal Language Representation for Machine Translation. Preprint at

https://doi.org/10.48550/arXiv.1810.06351 (2018).

35.   Mohiuddin, T. & Joty, S. Unsupervised Word Translation with Adversarial Autoencoder.

Computational Linguistics **46**, 257–288 (2020).

36.   Lotfollahi, M. *et al.* Predicting cellular responses to complex perturbations in high-throughput

screens. *Molecular Systems Biology* **n/a**, e11517 (2023).

37.   Sundararajan, M., Taly, A. & Yan, Q. Axiomatic Attribution for Deep Networks. in *Proceedings of*

the 34th International Conference on Machine Learning 3319–3328 (PMLR, 2017).

38.   Strunz, M. *et al.* Alveolar regeneration through a Krt8+ transitional stem cell state that persists

in human lung fibrosis. *Nat Commun* **11**, 3559 (2020).

39.   Habermann, A. C. *et al.* Single-cell RNA sequencing reveals profibrotic roles of distinct epithelial

and mesenchymal lineages in pulmonary fibrosis. *Science Advances* **6**, eaba1972 (2020).

40.   Chung, A. W. *et al.* Dissecting Polyclonal Vaccine-Induced Humoral Immunity against HIV Using

Systems Serology. *Cell* **163**, 988–998 (2015).

41.   Barouch, D. H. *et al.* Evaluation of a mosaic HIV-1 vaccine in a multicentre, randomised, double-

blind, placebo-controlled, phase 1/2a clinical trial (APPROACH) and in rhesus monkeys (NHP 13-19).

The Lancet **392**, 232–243 (2018).

42.   Alvarez, M. J. *et al.* Functional characterization of somatic mutations in cancer using network-

based inference of protein activity. *Nat Genet* **48**, 838–847 (2016).

43.   Garcia-Alonso, L., Holland, C. H., Ibrahim, M. M., Turei, D. & Saez-Rodriguez, J. Benchmark and

integration of resources for the estimation of human transcription factor activities. *Genome Res.* **29**,

1363–1375 (2019).

44.   Barretina, J. *et al.* The Cancer Cell Line Encyclopedia enables predictive modelling of anticancer

drug sensitivity. *Nature* **483**, 603–607 (2012).

45.   Aran, D. *et al.* Reference-based analysis of lung single-cell sequencing reveals a transitional

profibrotic macrophage. *Nat Immunol* **20**, 163–172 (2019).

46.   Ramachandran, P. *et al.* Resolving the fibrotic niche of human liver cirrhosis at single-cell level.

Nature **575**, 512–518 (2019).

47.   Ching, T. *et al.* Opportunities and obstacles for deep learning in biology and medicine. *Journal of*

The Royal Society Interface **15**, 20170387 (2018).

48.   Wysocka, M., Wysocki, O., Zufferey, M., Landers, D. & Freitas, A. A systematic review of

biologically-informed deep learning models for cancer: fundamental trends for encoding and

interpreting oncology data. *BMC Bioinformatics* **24**, 198 (2023).

49.   Edgar, R., Domrachev, M. & Lash, A. E. Gene Expression Omnibus: NCBI gene expression and

hybridization array data repository. *Nucleic Acids Research* **30**, 207–210 (2002).

50.   [clue.io]. https://clue.io/.

51.   Hjelm, R. D. *et al.* Learning deep representations by mutual information estimation and

maximization. Preprint at https://doi.org/10.48550/arXiv.1808.06670 (2019).

52.   Sun, F.-Y., Hoffmann, J., Verma, V. & Tang, J. InfoGraph: Unsupervised and Semi-supervised

Graph-Level Representation Learning via Mutual Information Maximization. Preprint at

https://doi.org/10.48550/arXiv.1908.01000 (2020).

53.   Sawilowsky, S. New Effect Size Rules of Thumb. *Journal of Modern Applied Statistical Methods* **8**,

(2009).

54.   Cohen, J. *Statistical Power Analysis for the Behavioral Sciences*. (Routledge, 2013).

55.   Kokhlikyan, N. *et al.* Captum: A unified and generic model interpretability library for PyTorch.

Preprint at https://doi.org/10.48550/arXiv.2009.07896 (2020).

56.   McConn, J. L., Lamoureux, C. R., Poudel, S., Palsson, B. O. & Sastry, A. V. Optimal dimensionality

selection for independent component analysis of transcriptomic data. *BMC Bioinformatics* **22**, 584

(2021).

57.   Sastry, A. V. *et al.* Mining all publicly available expression data to compute dynamic microbial

transcriptional regulatory networks. 2021.07.01.450581 Preprint at

https://doi.org/10.1101/2021.07.01.450581 (2021).

58.   Torsten Hothorn, A. Z. Diagnostic Checking in Regression Relationships. *R News* **2**, 7–10 (2002).

59.   Paszke, A. *et al.* PyTorch: An Imperative Style, High-Performance Deep Learning Library. in

Advances in Neural Information Processing Systems vol. 32 (Curran Associates, Inc., 2019).

60.   Villanueva, R. A. M. & Chen, Z. J. ggplot2: Elegant Graphics for Data Analysis (2nd ed.).

Measurement: Interdisciplinary Research and Perspectives **17**, 160–167 (2019).

Figures

Figure 1: a) Framework architecture main variations: I) One global space is constructed by mapping omic
profiles in a space where the distance between embeddings coming from the same perturbation is
minimized. II) CPA-based architecture where the latent space is separated into two, one global devoid of
species/cell effect and a composed latent space. **b)** Model performance in reconstructing and translating
gene expression profiles between the two cell lines with the most common perturbations in the L1000
dataset, A375 and HT29, by using only the 978 measured landmark genes. For DCS modified v1-v2 see
Supplementary Methods 2.2-2.3. It is worth noting that DCS modified v2 has a distance term and a
direct translation term in its training loss. **c)** Model performance in reconstructing and translating gene
expression profiles between A375 and HT29 by using all 10,086 genes that are either measured or
belong to those that are well-inferred computationally. **d)** Performance in inferring transcription factors
activity by using the translated/predicted gene expression. **e)** Performance in correctly classifying cell
lines in different cases. **f)** Performance by using different inputs in the L1000.

Figure 2: a) Performance in the translation task of the CPA-based approach across different cell-line
pairs and different sizes of training data. **b)** Model performance in translation as a function of the initial
similarity of 2 cell lines. **c)** Model performance in translation for different percentages of paired
conditions. **d)** Model performance in translation for low-to-medium cell-line imbalance in the
conditions of the training samples.

Figure 3: The two splits in 10-fold cross-validation that are shown each time here are the ones where the maximum and minimum difference between the two distributions is observed. For every other split, the difference is between these two extreme cases. Additionally, panels a-c come from the first variation of the model with one global latent space while the rest come from the CPA-based approach **a)** Cosine distance between embeddings coming from random pairs of signatures and pairs coming from the same cell line. **b)** Cosine distance between embeddings coming from random pairs of signatures and pairs coming from the same condition tested on a different cell-line **c)** Cosine distance between embeddings coming from random pairs of signatures and pairs being biological duplicates **d)** Cosine distance between embeddings coming from random pairs of signatures and pairs coming from the same cell-line in the global and then the composed latent space in the CPA-based approach. **e)** Cohen's d between distributions of cosine distances between random pairs of embeddings and embeddings coming from the same cell distribution. **f-g)** 2D-Visualization of L1000 control conditions, untreated cell lines from the CCLE dataset, and the trainable vectors of the CPA-based framework containing the cell line basal effect added to perturbations.

Figure 4: a-b) Distribution of percentage rank in terms of the importance of a gene to translate its expression to itself, using the 10,086 genes and the 978 landmark genes respectively in the L1000 dataset. **c)** Per sample Spearman's correlation between absolute gene importance scores and absolute gene expression. **d)** Important latent variable to classify a sample as PC3 or HA1E in the global latent space, when a classifier is jointly trained. **e)** Separation of cell lines based on the top 2 most important latent variables according to the classifier. **f)** Average importance scores of genes from PC3 to control cell-specific latent variables versus the importance scores from HA1E, according to the individual encoders. **g)** Generalized Linear model classification performance by using the number of important genes used is increased.

Figure 5: a-b) Performance (R^2) in predicting the per gene mean and variance of single-cell RNA-
sequencing data for the tasks of reconstruction and species translation in the human-mouse lung
fibrosis datasets. The comparison is done between the CPA-based framework using all genes or
homologs and TransCompR **c)** Classification performance comparison in different tasks. **d)** Classification
performance of the CPA-based framework using all genes in external disease datasets. **e)** Embeddings
separation based on species in the global latent space versus the composed latent space. The effect size
d is calculated as Cohen's d. **f)** Embeddings separation based on the cell type in the global latent space
versus the composed latent space. The effect size d is calculated as Cohen's d.

Figure 6: a) Framework architecture for inter-species translation in the serology dataset. Instead of adding the species effect with a trained vector, it is adding completely non-linear with 2 small intermediate neural networks. **b)** Per feature Pearson correlation across in 10-fold cross-validation for human's features. **c)** Per feature Pearson correlation across in 10-fold cross-validation for non-human primates' features. **d)** Classifiers' performance in various tasks. **e)** Univariate differences between protected and non-protected individuals, for human serological features related to viral protection. **f)** Non-human primate features predictive of human protection, by using importance score for translating them into human features. Their quality is assigned based on the average reconstruction Pearson's r of these features in 10-fold cross-validation: i) low quality = $0<r<0.25$, ii) medium quality = $0.25\leq r<0.5$, iii) good quality = $0.5\leq r<0.75$, iv) high quality = $r\geq0.75$