Title: The effects of data leakage on connectome-based machine learning models

Authors: Matthew Rosenblatt[1*], Link Tejavibulya[2], Rongtao Jiang[3], Stephanie Noble[3,4,5], Dustin Scheinost[1,2,3,6,7]

[1]Department of Biomedical Engineering, Yale University, New Haven, CT
[2]Interdepartmental Neuroscience Program, Yale University, New Haven, CT
[3]Department of Radiology & Biomedical Imaging, Yale School of Medicine, New Haven, CT
[4]Department of Bioengineering, Northeastern University, Boston, MA
[5]Department of Psychology, Northeastern University, Boston, MA
[6]Child Study Center, Yale School of Medicine, New Haven, CT
[7]Department of Statistics & Data Science, Yale University, New Haven, CT

Matthew Rosenblatt, Magnetic Resonance Research Center, 300 Cedar St, P.O. Box 208043, New Haven, CT, USA 06520-8043, USA. matthew.rosenblatt@yale.edu

Abstract

Predictive modeling has now become a central technique in neuroimaging to identify complex brain-behavior relationships and test their generalizability to unseen data. However, data leakage, which unintentionally breaches the separation between data used to train and test the model, undermines the validity of predictive models. Previous literature suggests that leakage is generally pervasive in machine learning, but few studies have empirically evaluated the effects of leakage in neuroimaging data. Although leakage is always an incorrect practice, understanding the effects of leakage on neuroimaging predictive models provides insight into the extent to which leakage may affect the literature. Here, we investigated the effects of leakage on machine learning models in two common neuroimaging modalities, functional and structural connectomes. Using over 400 different pipelines spanning four large datasets and three phenotypes, we evaluated five forms of leakage fitting into three broad categories: feature selection, covariate correction, and lack of independence between subjects. As expected, leakage via feature selection and repeated subjects drastically inflated prediction performance. Notably, other forms of leakage had only minor effects (e.g., leaky site correction) or even decreased prediction performance (e.g., leaky covariate regression). In some cases, leakage affected not only prediction performance, but also model coefficients, and thus neurobiological interpretations. Finally, we found that predictive models using small datasets were more sensitive to leakage. Overall, our results illustrate the variable effects of leakage on prediction pipelines and underscore the importance of avoiding data leakage to improve the validity and reproducibility of predictive modeling.

1. Introduction

Understanding individual differences in brain-behavior relationships is a central goal of neuroscience. As part of this goal, machine learning approaches using neuroimaging data, such

as functional connectivity, have grown increasingly popular in predicting numerous phenotypes
[1], including cognitive performance [2–6], age [7–10], and several clinically-relevant outcomes [11–13].
Compared to classic statistical inference, prediction offers advantages in replicability and
generalizability, as it evaluates models on participants unseen during model training [14,15].
Essentially, the data are split into training and test subsets, such as through k-fold cross-
validation or simple train/test splits, so that the model is strictly evaluated on unseen data.
Unfortunately, the boundaries between training and test data can be inadvertently violated by
data leakage. Data leakage is when information about the test data is introduced into the model
during training [16], nullifying the benefits of separating training and test data.
10
A recent meta-review of machine learning highlighted the prevalence of leakage across 17 fields
[17]. Three hundred twenty-nine papers were identified as containing leakage. This meta-review
described eight types of leakage: not having a separate test set, pre-processing on the training
and test sets, feature selection jointly on the training and test sets, duplicate data points,
illegitimate features, temporal leakage, non-independence between the training and test sets,
and sampling bias. Data leakage often led to inflated model performance and consequently
decreased reproducibility [17]. In another review specific to predictive neuroimaging, ten of the 57
studies may have leaked information by performing dimensionality reduction across the whole
dataset prior to train/test splitting [18]. Since leakage may dramatically change the reported
results, it contributes to the ongoing reproducibility crisis in neuroimaging [17,19–21]. Despite the
prevalence and concern of leakage, the severity of performance inflation due to leakage in
neuroimaging predictive models remains unknown.
23
In this work, we evaluate the effects of leakage on functional connectome-based predictive
models in four large datasets for the prediction of three phenotypes. Specifically, in over 400
pipelines, we test feature leakage, covariate-based leakage, and subject leakage. These
leakage types span five of the leakage types described by Kapoor and Narayanan [17] (Table S1).
We first show the effects of leakage on prediction performance by comparing two performance
metrics in various leaky and non-leaky pipelines. Then, we evaluate the effects of leakage on
model interpretation by comparing model coefficients. Furthermore, we resample the datasets at
four different sample sizes to illustrate how small sample sizes may be most susceptible to
leakage. Finally, we extend our analysis to structural connectomes in one public dataset.
Overall, our results elucidate the consequences, or in some cases lack thereof, of numerous
possible forms of leakage in neuroimaging datasets.
35
36   *2. Results*
37
Resting-state fMRI data were obtained in each of our four datasets: the Adolescent Brain
Cognitive Development (ABCD) Study[22] (N=7822-7969), the Healthy Brain Network (HBN)
Dataset[23] (N=1024-1201), the Human Connectome Project Development (HCPD) Dataset[24]
(N=424-605), and the Philadelphia Neurodevelopmental Cohort (PNC) Dataset[25,26] (N=1119-
1126). Throughout this work, we predicted age, attention problems, and matrix reasoning using
ridge regression [27] with 5-fold cross-validation, 5% feature selection, and a grid search for the
L2 regularization parameter. Specific measures for each dataset are described in the methods

section, but these three broad phenotypes were selected because they are available in all the
datasets in this study. In addition, these three phenotypes are appropriate for benchmarking
leakage because they span a wide range of effect sizes, with strong prediction performance for
age, moderate performance for matrix reasoning, and poor performance for attention problems.

We first evaluated the effects of leakage on prediction in HCPD (Sections *2.1-2.4*), and then, we
showed effects of leakage in the other three datasets (ABCD, HBN, PNC) (Section *2.6*).
Moreover, we compared model coefficients (Section *2.7*), varied the sample size (Section *2.8*),
and performed sensitivity analyses (Section *2.9*). The types of leakage used in this study are
summarized in Figure 1 and further detailed in the methods section.

10
11   **Figure 1.** Summary of the prediction pipelines used in this study. The various forms of leakage that may occur are
12   shown in orange. Feature leakage, leaky site correction, leaky covariate regression, and subject leakage may occur
13   prior to splitting the data into training and test sets. Family leakage may occur during the splitting of data.
14
15   *2.1 Performance of non-leaky pipelines*
16
We evaluated four non-leaky pipelines and found that different analysis choices led to different
prediction performance (Figure 2), as evaluated by Pearson's correlation r and cross-validation
R^2, also called q^2 [28]. Our gold standard model included covariate regression, site correction [29–31],
and feature selection within the cross-validation scheme, which was split accounting for family
structure. It exhibited no prediction performance for attention problems (median r=0.01, q^2=-
0.13), strong performance for age (r=0.80, q^2=0.63), and moderate performance for matrix
reasoning (r=0.30, q^2=0.08). Notably, q^2 may be negative when the model prediction gives a
higher mean-squared error than predicting the mean, as was the case for attention problems.
Performance when excluding site correction was nearly identical to the gold standard model
($|\Delta r|$<0.01, Δq^2<0.01). However, not regressing out covariates inflated r but had varying effects
on q^2 for all three phenotypes, including attention problems (Δr=0.05, Δq^2=-0.08), age (Δr=0.06,
Δq^2=0.11), and matrix reasoning (Δr=0.05, Δq^2=0.01). Though not the main focus of this paper,
these results highlight how prediction performance may change with different analysis choices,
especially regarding whether or not covariates are regressed from the data.
31

Figure 2. Prediction performance in HCPD of the non-leaky pipelines, including the gold standard, omitting covariate regression, omitting site correction, and omitting both covariate regression and site correction. Rows represent different non-leaky analysis choices, and columns show different phenotypes. The black bar represents the median performance of the gold standard models across random iterations, and the exact value of the bar is shown as the median r, r_{med}. The histograms show prediction performance across 100 iterations of 5-fold cross-validation. See also Figure S1.

2.2 Feature leakage

Features should be selected in the training data and then applied to the test data. Feature leakage occurs when selecting features in the combined training and test data. Feature leakage inflated prediction performance for each phenotype (Figure 3). The inflation was small for age (Δr=0.03, Δq^2=0.05), larger for matrix reasoning (Δr=0.17, Δq^2=0.13), and largest for attention problems (Δr=0.47, Δq^2=0.35). Notably, age had a strong baseline performance and was minimally affected by feature leakage, whereas attention problems had the worst baseline performance and was most affected by feature leakage. Furthermore, the attention problems prediction went from chance-level (r=0.01, q^2=-0.13) to moderate (r=0.48, q^2=0.22), which highlights the potential for feature leakage to hinder reproducibility efforts.

Figure 3. Prediction performance in HCPD of leaky feature selection, compared to the gold standard. Rows represent different leakage types, and columns show different phenotypes. The black bar represents the median performance of the gold standard models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation. See also Figure S1.

2.3 Covariate-related leakage

Covariate-related forms of leakage in this study included correcting for site differences and

performing covariate regression in the combined training and test data (i.e., outside of the cross-

validation folds) (Figure 4). Leaky site correction had little effect on performance (Δr=-0.01-0,

Δq^2=-0.01-0.01). Unlike the other forms of leakage in this study, leaky covariate regression

decreased performance for attention problems (Δr=-0.06, Δq^2=-0.17), age (Δr=-0.02, Δq^2=-

0.03), and matrix reasoning (Δr=-0.09, Δq^2=-0.08). These results illustrate that leakage can not

only hamper reproducibility by false inflation of performance, but also by underestimating the

true effect sizes.

12
Figure 4. Prediction performance in HCPD of covariate-related forms of leakage, including leaky site correction, and
leaky covariate regression. Rows represent different leakage types, and columns show different phenotypes. The
black bar represents the median performance of the gold standard models across random iterations, and the
histograms show prediction performance across 100 iterations of 5-fold cross-validation. See also Figure S1.

2.4 Subject-level leakage

Since families are often oversampled in neuroimaging datasets, leakage via family structure

may affect predictive models. Given the heritability of brain structure and function [32–34], leakage

may occur if one family member is in the training set and another in the test set. Family leakage

did not affect prediction performance of age or matrix reasoning (Δr=0.00, Δq^2=0.00) but did

slightly increase prediction performance of attention problems (Δr=0.02, Δq^2=0.00) (Figure 5).

Furthermore, subject-level leakage may occur when repeated measurements data (e.g.,

multiple tasks) are incorrectly treated as separate participants or when data are accidentally

duplicated. Here, we considered the latter case, where a certain percentage of the subjects in

the dataset were repeated (called "subject leakage"), at three different levels (5%, 10%, 20%)

(Figure 5). In all cases, subject leakage inflated prediction performance, with 20% subject

leakage having the greatest impact on attention problems (Δr=0.28, Δq^2=0.19), age (Δr=0.04,

Δq^2=0.07), and matrix reasoning (Δr=0.14, Δq^2=0.11). Similar to the trend seen in feature

leakage, the effects of subject leakage were more dramatic for models with weaker baseline

performance. Overall, these results suggest that family leakage may have little effect in certain

instances, but potential leakage via repeated measurements (i.e., subject leakage) can largely

inflate performance.

37
38

Figure 5. Prediction performance in HCPD of subject-level forms of leakage. These included family leakage and subject leakage at three different levels. Rows represent different leakage types, and columns show different phenotypes. The black bar represents the median performance of the gold standard models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation. See also Figure S1.

2.5 Additional family leakage analyses in ABCD

Since the two datasets in this study with family information contained mostly participants without any other family members in the dataset (HCPD: 471/605, ABCD: 5868/7969 participants did not have family members), we performed several additional experiments to determine the effects of family leakage with a larger proportion of families. We used ABCD instead of HCPD for these experiments because ABCD has more families with multiple members in the dataset.

First, ABCD was restricted to only twins (N=563 pairs of twins, 1126 participants total), after which we performed 100 iterations of 5-fold cross-validation for all three phenotypes and model types. In one case, family structure was accounted for in the cross-validation splits. In another, the family structure was ignored, constituting leakage. Leakage in the twin dataset exhibited minor to moderate increases in prediction performance (Figure 6), unlike when using the entire dataset. The inflation was *Δr*=0.04 for age and *Δr*=0.02 matrix reasoning and attention problems.

We included several additional phenotypes and models to compare how leakage may affect twin studies (Figure S2), which showed similar results. The phenotype similarity between the twin pairs did not have a strong relationship with changes in performance due to leakage (Figure S3). Furthermore, based on a simulation study, leakage effects increased with the percentage of participants belonging to a family with more than one individual (Figure S4).

2
3 **Figure 6.** Prediction performance in ABCD comparing the gold standard to twin/family leakage. The black bar
4 represents the median performance of the gold standard models across random iterations, and the histograms show
5 prediction performance across 100 iterations of 20-fold cross-validation. See also Figures S2-4.
6
7 *2.6 Evaluation of performance in additional datasets*
8
Compared to HCPD, we found similar trends in each of the 11 pipelines for ABCD, HBN, and
PNC (Figures S5-6). While excluding site correction had little to no effect in HCPD or HBN,
there was a small effect in ABCD (Δr=0.01-0.02, Δq^2=0.00-0.01). Furthermore, not performing
covariate regression generally inflated performance relative to the baseline for attention
problems (Δr=0.02-0.05, Δq^2=-0.08-0.04), age (Δr=-0.01-0.06, Δq^2=0.00-0.11), and matrix
reasoning (Δr=0.01-0.05, Δq^2=-0.02-0.01).
15
Across all datasets and phenotypes, leaky feature selection and subject leakage (20%) led to
the greatest performance inflation. Feature leakage had varying effects based on the dataset
and phenotype (Δr=0.03-0.52, Δq^2=0.01-0.47). The dataset with the largest sample size
(ABCD), was least affected by leaky feature selection, and weaker baseline models were more
affected by feature leakage. Subject leakage (20%) also inflated performance across all
datasets and phenotypes (Δr=0.06-0.29, Δq^2=0.03-0.24). Corroborating the results in HCPD,
leaky covariate regression was the only form of leakage that consistently deflated performance
(Δr=-0.09-0.00, Δq^2=-0.17-0.00). Family leakage (Δr=0.00-0.02, Δq^2=0.00) and leaky site
correction (Δr=-0.01-0.00, Δq^2=-0.01-0.01) had little to no effect.
25
26 The change in performance relative to the gold standard for each pipeline across all four
27 datasets and three phenotypes is summarized in Figure 7. Overall, only leaky feature selection
28 and subject leakage inflated prediction performance in this study.
29

Figure 7. Evaluation of performance differences between all pipelines and the gold standard pipeline across all datasets and phenotypes for Pearson's **a)** r and **b)** q^2. For each of r and q^2, the plots are ranked from the most inflated performance (top) to the most deflated performance (bottom). Boxplot elements were defined as follows: the center line is the median across all datasets, phenotypes, and iterations (100 per dataset/phenotype combination); box limits are the upper and lower quartiles; whiskers are 1.5x the interquartile range; points are outliers. See also Figure S5, Figure S6.

2.7 Comparing coefficients in leaky and non-leaky pipelines

Determining whether the performance of leaky and non-leaky pipelines is similar only tells part of the story, as two models could have similar prediction performance but learn entirely different brain-behavior relationships. As such, establishing how model coefficients may change for various forms of leakage is an equally important facet of understanding the possible effects of leakage. We first averaged the coefficients over the five folds of cross-validation and calculated the correlation between those coefficients and the coefficients of the gold standard model (Figure 8). Excluding site correction (median r_{coef}=0.75-0.99) led to minor coefficient changes. Meanwhile, excluding covariate regression (median r_{coef}=0.31-0.84) or excluding both covariate regression and site correction (median r_{coef}=0.32-0.81) resulted in moderate coefficient changes. Amongst the forms of leakage, leaky feature selection was, unsurprisingly, the most dissimilar to the gold standard coefficients (median r_{coef}=0.39-0.72). Other forms of leakage that notably affected the coefficients included family leakage (median r_{coef}=0.79-0.94) and 20% subject leakage (median r_{coef}=0.74-0.93). Otherwise, the coefficients between the leaky and gold standard pipelines were very similar. We also compared the coefficients for each pair of 11 analysis pipelines (Figure S7). Interestingly, although the coefficients for excluding covariate regression or performing leaky feature selection were relatively dissimilar to the gold standard coefficients (median r_{coef}=0.31-0.84), these coefficients were relatively similar to each other (median r_{coef}=0.68-0.92). This result could be explained by covariates contributing to brain-behavior associations in the entire dataset.

1
2 **Figure 8.** Similarity of coefficients between the gold standard and various forms of leakage. The boxes are colored by
3 the leakage family: orange (non-leaky analysis choices), blue (feature leakage), green (covariate-related leakage),
4 yellow (subject-level leakage). Boxplot elements were defined as follows: the center line is the median across 100
5 random iterations; box limits are the upper and lower quartiles; whiskers are 1.5x the interquartile range; points are
6 outliers. Missing values (i.e., no site information in PNC) are marked with "N/A." See also Figures S7-8.
7
In addition to correlating the coefficients at the edge level, we also considered the similarity of
feature selection across 10 canonical networks [35] (Figure S8). We calculated the number of
edges selected as features in each of the 55 subnetworks, which are defined as a connection
between a specific pair of the 10 canonical networks. We then adjusted for subnetwork size and
compared the rank correlation across different leakage types. Similar to the previous analysis,
not performing covariate regression changed the distribution of features across subnetworks
(median $r_{spearman,network}$=0.28-0.88). Amongst the forms of leakage, leaky feature selection
showed the greatest network differences compared to the gold standard model (median
$r_{spearman,network}$=0.25-0.85), while the other forms of leakage showed smaller differences (median
$r_{spearman,network}$=0.75-1.00).
18
19 *2.8 Effect of sample size*
20
All previously presented results investigated the four datasets at their full sample sizes (ABCD:
N=7822-7969, HBN: N=1024-1201, HCPD: N=424-605, PNC: N=1104-1126). Yet, although
these can lead to less reproducible results [21], smaller sample sizes are common in

neuroimaging studies. As such, consideration of how leakage may affect reported prediction
performance at various sample sizes is crucial. For leaky feature selection, leaky site correction,
leaky covariate regression, family leakage, and 20% subject leakage, we computed $\Delta r = r_{leaky} -$
r_{gold}, where r_{leaky} is the performance of the leaky pipeline and r_{gold} is the performance of the gold
standard non-leaky pipeline for a single seed of 5-fold cross-validation. For each combination of
leakage type, sample size (N=100, 200, 300, 400), and dataset, Δr was evaluated for 10
different resamples for 10 iterations of 5-fold cross-validation each (over 20,000 evaluations of
5-fold cross-validation in total) (Figure 9). In general, the variability of Δr was much greater for
the smallest sample size (N=100) compared to the largest sample size (N=400). For instance,
for matrix reasoning prediction in ABCD, Δr for family leakage ranged from -0.34 to 0.25 for
N=100 and from -0.12 to 0.13 for N=400. Another example is site correction in ABCD matrix
reasoning prediction, where Δr ranged from -0.13 to 0.06 for N=100 and from -0.11 to 0.03 for
N=400. While not every dataset and phenotype prediction had large variability in performance
for leaky pipelines at small sample sizes (e.g., HBN age prediction), the overall trends suggest
that leakage may be more unpredictable and thus dangerous in small samples compared to
large samples.
17
However, when taking the median performance across multiple k-fold splits for a given
subsample, the effects of most leakage types, except feature and subject leakage, decreased
(Figure S9). In general, the best practice is to perform at least 100 iterations of k-fold splits, but
due to the many analyses and pipelines in this study, we only performed 10 iterations. For
instance, for the ABCD prediction of matrix reasoning, taking the median across 10 iterations
resulted in a slightly smaller range of Δr values for all forms of leakage (N=400), including
feature leakage ($\Delta r_{multiple}$=0.17-0.67 for multiple iterations vs. Δr_{single}=0.10-0.71 for a single
iteration), leaky site correction ($\Delta r_{multiple}$=-0.11-0.03 vs. Δr_{single}=-0.06-0.01), leaky covariate
regression ($\Delta r_{multiple}$=-0.08 to -0.01 vs. Δr_{single}=-0.10-0.01), family leakage ($\Delta r_{multiple}$=-0.02-0.04 vs.
Δr_{single}=-0.12-0.13), and 20% subject leakage ($\Delta r_{multiple}$=0.21-0.33 vs. Δr_{single}=0.17-0.43). Overall,
performing multiple iterations of k-fold cross-validation reduced, but did not eliminate, the effects
of leakage. Leakage still led to large changes in performance in certain cases, particularly at
small sample sizes.

Figure 9. Difference between leaky and gold standard performance for various types of leakage and two sample sizes (N=100, 200, 300, 400). Rows represent the dataset, and columns show the phenotype. For each leakage type (x-axis), there are four results (N=100, 200, 300, 400). For each sample size, we repeated 10 random seeds of resampling for 10 iterations of 5-fold cross-validation. Boxplot elements were defined as follows: the center line is the median across all subsampling seeds and cross-validation iterations; box limits are the upper and lower quartiles; whiskers are 1.5x the interquartile range; points are outliers. See also Figure S9.

2.9 Sensitivity analyses

Two main sensitivity analyses were performed to support the robustness of our findings. First, we analyzed the effects of leakage in two other models (SVR, CPM). Second, we performed similar analyses using structural connectomes to demonstrate the effects of leakage beyond functional connectivity.

We repeated the analyses for support vector regression (SVR) (Figures S10, S12) and connectome-based predictive modeling (CPM) [2] (Figures S11, S13) and found similar trends in the effects of leakage. CPM generally had a slightly lower gold standard performance (age:

median r=0.16-0.61, q^2=0.02-0.37; attention problems: r=-0.04-0.11, q^2=-0.25-0.00; matrix

reasoning: r=0.18-0.27, q^2=0.02-0.05) than ridge regression (age: r=0.25-0.80, q^2=0.06-0.63;

attention problems: r=-0.01-0.13, q^2=-0.21-0.00; matrix reasoning: r=0.25-0.30, q^2=0.06-0.08)

and SVR (age: r=0.24-0.80, q^2=0.04-0.64; attention problems: r=0.00-0.12, q^2=-0.15 to -0.09;

matrix reasoning: r=0.25-0.34, q^2=0.05-0.10). Notably, CPM was less affected by leaky feature

selection (Δr=-0.04-0.39, Δq^2=0.00-0.38) compared to ridge regression (Δr=0.02-0.52,

Δq^2=0.02-0.47) and SVR (Δr=0.02-0.48, Δq^2=-0.01-0.38). In addition, subject leakage had the

largest effect on SVR (Δr=0.06-0.45, Δq^2=0.10-0.31), followed by ridge regression (Δr=0.04-

0.29, Δq^2=0.03-0.24) and CPM (Δr=0.00-0.17, Δq^2=0.00-0.16). Regardless of differences in the

size of the effects across models, the trends were generally similar.

In addition, we extended our leakage analyses from functional to structural connectomes with

635 participants from the HCPD dataset. Gold standard predictions of matrix reasoning,

attention problems, and age exhibited low to moderate performance in the HCPD structural

connectome data (Figure 10, S11) (matrix reasoning: median r=0.34, q^2=0.12; attention

problems: r=0.11, q^2=-0.07; age: r=0.73, q^2=0.53). The forms of leakage that most inflated the

performance were feature leakage (Δr=0.07-0.57, Δq^2=0.12-0.52) and subject leakage

(Δr=0.05-0.27, Δq^2=0.06-0.20). Compared to its effect on functional connectivity data, leaky

covariate regression in this particular instance showed milder reductions in performance (Δr=-

0.04-0.00, Δq^2=-0.04-0.00). Despite minor differences, these results in structural connectivity

data follow similar trends as the functional connectivity data.

Figure 10. Evaluation of leakage types for matrix reasoning, attention problems, and age prediction in structural connectomes using *r*. The rows show different leakage types, and the columns show different phenotypes. The black bar represents the median performance of the gold standard models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation. See also Figure S14.

3. Discussion

In this work, we demonstrated the effects of five possible forms of leakage on connectome-based predictive models in the ABCD, HBN, HCPD, and PNC datasets. In some cases, leakage led to severe inflation of prediction (e.g., leaky feature selection). In others, there was little to no difference (e.g., leaky site correction). The overall effects of leaky pipelines showed similar trends across the different phenotypes, models, and connectomes investigated in this work.

Furthermore, subsampling to smaller sizes--typical in the neuroimaging literature--led to an
increased effect of leakage. Leakage is never the correct practice, but quantifying its effects in
neuroimaging is still important to understand exactly how much leakage may impede
reproducibility in neuroimaging. Given the variable effects of leakage found in this work, the
strict splitting of testing and training samples is particularly important in neuroimaging to
accurately estimate the performance of a predictive model.
7
Feature leakage is widely accepted as a bad practice, and as expected, it severely inflated
prediction performance. Although feature leakage is likely rare in the literature, it can
dramatically increase model performance and thus hinder reproducibility. For instance, a recent
work [36] demonstrated that a high-profile article "predicting" suicidal ideation in youth had no
predictive power after removing feature selection leakage. The original paper, which has now
been retracted, received 254 citations since its publication in 2017 according to Google Scholar.
As such, it is essential to re-emphasize the importance of avoiding feature leakage. Though
avoiding feature leakage may appear obvious, it can occur in more subtle ways. For example,
one may investigate which networks significantly differ between two groups in the whole dataset
and then create a predictive model using those networks. Notably, the effects of feature leakage
were smaller in ABCD due to its large sample size. In other words, when using thousands of
samples, the selected features are likely robust across different folds of training data. This result
is consistent with recent findings regarding association studies [21]. In general, feature leakage
can be reduced by sharing code on public repositories. Although it requires additional work, we
strongly urge authors to share their analysis code in all cases and preprocessed data when
appropriate. Then, the community can quickly and easily reproduce results and look for potential
leakage in the code.
25
Similarly, subject leakage led to inflated effects. It is more likely in datasets with multiple runs of
fMRI, time points, or tasks. For example, a high-profile preprint used deep learning to predict
pneumonia from chest X-rays, and the authors did not account for patients having multiple
scans, causing leakage across the training and test sets. Fortunately, this leakage was
identified by a community member and quickly corrected in a subsequent version of the preprint
[37], which illustrates the importance of writing detailed methods and sharing code. Extra care
should be taken for prediction when using multiple scans per individual, such as when collecting
multiple task scans or longitudinal data.
34
We typically associate leakage with inflated prediction performance. However, leaky covariate
regression deflated prediction performance. Our results corroborate previous works, suggesting
that covariate regression must be performed within the cross-validation loop to avoid false
deflation of effect sizes [38–40]. Interestingly, performing covariate regression itself may lead to
leakage [41] and is another consideration when deciding whether and how to implement covariate
regression.
41
42 Aside from feature and subject leakage, no other leakage significantly increased prediction
43 performance when using large sample sizes. Notably, leaky site correction did not affect
44 prediction performance. Family leakage had little to no effect when using the entire dataset due

to the small percentage of participants belonging to families with more than one individual. Still, a twin subset and various simulations demonstrated that the effects of family leakage are more pronounced when datasets have a larger proportion of multi-member families. Large, public datasets, like ABCD and the broader HCP lifespan datasets, are increasingly multi-site with complex nested dependency between participants (i.e., twins) [42]. These factors facilitate larger sample sizes for better statistical power and more representative samples, which can minimize model bias [1,43–45]. However, accounting for these factors can rapidly increase the complexity of a prediction pipeline. Thus, these results are reassuring for the broader field. Overall, they likely mean that results with these forms of leakage remain valid, at least in these datasets and phenotypes. Although, there is no guarantee that any of these forms of leakage will not inflate performance. Thus, avoiding data leakage is still necessary to ensure valid results.

Among the phenotypes in this work, age, which had the best prediction performance, was the least affected by leakage. This result suggests that leakage may moreso affect phenotypes with a weaker brain-behavior association. When there is a strong brain-behavior relationship, a model may capture the relevant pattern regardless of leakage. However, when there is a weak brain-behavior relationship, the model may predominantly rely on patterns arising from leakage, thus possibly leading to the larger effects of leakage in behaviors with weak effect sizes. In other words, when the effects are very weak (e.g., attention problems in this study), leakage appears to "overtake" the true effect. Because effect sizes in brain-behavior association studies are often weak, attention to leakage is particularly important. Yet, it is important to note that the effects of leakage were tested in three phenotypes in this study, and do not comprehensively test across all effect sizes.

Crucially, leakage exhibited more variable effects in smaller datasets. As such, accounting for leakage is even more crucial with small samples. All researchers should avoid leakage, but those using small clinical samples or patient groups should be particularly careful. Taking the median performance of the models over multiple iterations of k-fold cross-validation (i.e., different random seeds) mitigated the inflation. This example underscores the benefits of performing many (>=100) iterations of k-fold cross-validation [28,46]. Though k-fold cross-validation is the most common form of evaluation in neuroimaging, train/test splits are not uncommon. Given that train/test splits are often only performed for one random seed, leakage with small sample sizes may be a greater issue when using train/test splits.

Along with its effects on performance, we found that leakage also affected model interpretation, and therefore neurobiological interpretation. Coefficients for feature leakage were unsurprisingly dissimilar to the gold standard because the leaky feature selection relies on one feature subset, whereas the gold standard pipeline selects a different subset of features for each fold of cross-validation. Otherwise, the most notable differences in coefficients arose from omitting covariate regression. This result highlights that, in addition to avoiding leakage, researchers should consider how various analysis choices may affect results [47,48].

The results presented in this work focus on neuroimaging, specifically functional and structural connectivity prediction studies. However, the lessons from this work may be valuable to any

field using scientific machine learning. Since we expect that leakage will be prevalent across
many fields for the foreseeable future, quantifying the effects of leakage may provide valuable
field-specific insight into the validity of published results. Thus, we encourage researchers in
other fields to use their domain-specific knowledge to identify possible forms of leakage and
subsequently evaluate their effects. Although quantifying the effects is essential due to the
pervasiveness of leakage, researchers should pay careful attention to avoiding leakage.
7
Numerous strategies can help prevent leakage in neuroimaging and other machine-learning
applications. These strategies include carefully developing and sharing code, alternative
validation strategies, model information sheets [17], skepticism about one's own results, and
cross-disciplinary collaborations. Writing and maintaining code should incorporate several facets
to reduce the likelihood of leakage, including establishing an analysis plan prior to writing code,
using well-maintained packages, and sharing code. One's analysis plan should be set ahead of
time, either informally or, if appropriate, formally through pre-registration. As one tries more
pipelines, especially if searching for a significant result (i.e., "p-hacking"), leakage is more likely
to occur. A predefined plan could minimize the likelihood of leakage by detailing how features
will be selected, which models will be trained, and how possible covariates and nested
structures will be handled. Another suggestion for reducing the likelihood of leakage is using
well-maintained packages. For example, Scikit-learn has a k-fold cross-validation package [27]
that has been thoroughly tested, whereas developing k-fold cross-validation code from scratch
may lead to accidental leakage. Among many other benefits, sharing code, particularly well-
documented code, could decrease the effects of leakage by allowing external reviewers to
investigate published pipelines for leakage. Relatedly, although not always possible, distributing
preprocessed data can make the reproduction of results much easier and less time-consuming
for reviewers or those who want to verify the validity of a predictive model.
26
Moreover, most neuroimaging papers are evaluated with train/test splits or k-fold cross-
validation. However, alternative validation strategies, such as a lockbox [49] or external
validation, may reduce the likelihood of leakage. Both these strategies help to maintain a clearer
separation between training and test data, where a lock box entails leaving out a subset of the
data until a final evaluation [49] and external validation consists of applying a model to a different
dataset. Another strategy to decrease the prevalence of leakage is using model information
sheets, such as the one proposed by Kapoor and Narayanan [17]. Model information sheets allow
for the authors, reviewers, and public to reflect upon the work and identify possible leakage.
However, it may be difficult to verify the accuracy of model information sheets when data cannot
be shared [17]. This limitation is especially true for neuroimaging datasets, which often require
applications to access the data. As a result, we also recommend healthy skepticism of one's
results. For instance, if a machine learning pipeline leads to a surprising result, the code should
be scrutinized by asking a collaborator to view one's code or repeat the analyses on synthetic
data. Finally, collaborations across disciplines to incorporate domain and machine learning
experts will help prevent leakage [17]. Domain experts can bring knowledge of the nuances of
datasets (e.g., the prevalence of family structures in neuroimaging datasets). In contrast,
machine learning experts can help domain experts train models to avoid leakage.
44
While this study investigated several datasets, modalities, phenotypes, and models, several
limitations still exist. In many instances in this work, leakage had little to no effect on the
prediction results, yet this finding does not mean that leakage is acceptable in any case.
Another limitation is that this study cannot possibly cover all forms of leakage for all datasets
and phenotypes. Other possible forms of leakage, like leakage via hyperparameter selection [49],
were not considered in this study, as detailed in the methods section. Furthermore, we studied

child, adolescent, and young adult cohorts in well-harmonized datasets in this work, but differences in populations and dataset quality could alter the effects of leakage. For example, we showed that family leakage had greater effects in twin studies. As another example, in the case of site correction, if a patient group was scanned at Site A and the healthy control group at Site B, then site leakage would likely have a large impact. Alternative methods may be more appropriate for accounting for possible covariates or site differences in a prediction setting, such as comparing neuroimaging data models to models built only using covariates or leave-one-site-out prediction [50]. Nevertheless, we still included covariate regression and site correction in our analysis because they are common in the field and may still be well-suited for using prediction to explain the generalizability of brain-behavior relationships. Also, differences in scan lengths between datasets may drive differences in performance across datasets. However, it should not affect the main conclusions of this paper regarding leakage in machine learning models. In addition, we used the types of models most common in functional connectivity brain-phenotype studies [51]. Yet, complex models like neural networks are likely more susceptible to leakage due to their ability to memorize data [52,53]. Relatedly, many other evaluation metrics exist, such as mean squared error and mean absolute error; we focused primarily on r and secondarily on q^2 because r is the most common performance metric in neuroimaging trait prediction studies [51].

Another limitation is that leakage is not always as well-defined as in this paper. Some examples are universally leakage, such as ignoring family structure, accidentally duplicating data, and selecting features in the combined training and test data. In other cases, whether training and test data are independent may depend on the goal. For example, one may wish to develop a model that will be applied to data from a new site, in which case leave-one-site-out prediction would be necessary. Here, leakage would be present if data from the test site were included when training the model. However, other applications, such as those presented in this paper, may not require data to be separated by site and can instead apply site correction methods. Similarly, if one wishes to demonstrate that a model generalizes across diagnostic groups, the model should be built on one group and tested on another. The application-dependent nature of leakage highlights the importance of attention to detail and thoughtful experimentation in avoiding leakage.

Concerns about reproducibility in machine learning [17] can be partially attributed to leakage. As expected, feature and subject leakage inflated prediction performance. Positively, many forms of leakage did not exhibit inflated results. Additionally, larger samples and running multiple train and test splits mitigated inflated results. Since the effects of leakage are wide-varying and not known beforehand, the best practice remains to be vigilant and avoid data leakage altogether.

4. Methods

4.1 Preprocessing

In all datasets, data were motion corrected. Additional preprocessing steps were performed using BioImage Suite [54]. This included regression of covariates of no interest from the functional data, including linear and quadratic drifts, mean cerebrospinal fluid signal, mean white matter

signal, and mean global signal. Additional motion control was applied by regressing a 24-
parameter motion model, which included six rigid body motion parameters, six temporal
derivatives, and the square of these terms, from the data. Subsequently, we applied temporal
smoothing with a Gaussian filter (approximate cutoff frequency=0.12 Hz) and gray matter
masking, as defined in common space. Then, the Shen 268-node atlas [55] was applied to
parcellate the denoised data into 268 nodes. Finally, we generated functional connectivity
matrices by correlating each pair of node time series data and applying the Fisher transform.
8
9   Data were excluded for poor data quality, missing nodes due to lack of full brain coverage, high
10   motion (>0.2mm mean frame-wise motion), or missing behavioral/phenotypic data, which is
11   detailed further for each specific dataset below.
12
13   *4.2 Adolescent Brain Cognitive Development (ABCD) Data*
14
In this work, we used the first and second releases of the first year of the ABCD dataset. This
consists of 9-10-year-olds imaged across 21 sites in the United States. 7970 participants with
resting-state connectomes (up to 10 minutes of resting-state data) remained in this dataset after
excluding scans for poor quality or high motion (>0.2mm mean frame-wise displacement [FD]).
Family information was not available for one participant, leaving 7969 participants, with 6903
unique families. Among these participants, the mean age was 9.94 (s.d. 0.62) years, with a
range of 9-10.92 years, and 49.71% self-reported their sex as female.
22
23   For the attention problems measure, we used the Child Behavior Checklist (CBCL) [56] Attention
24   Problems Raw Score. One participant was missing the attention problems score in ABCD. Of
25   the participants with an attention problems score, the mean was 2.80 (s.d. 3.40), with a range of
26   0-20.
27
28   For the matrix reasoning measure, we used the Wechsler Intelligence Scale for Children (WISC-
29   V) [57] Matrix Reasoning Total Raw Score. WISC-V measurements were missing from 147
30   participants (N=7822). The mean matrix reasoning score in ABCD was 18.25 (s.d. 3.69), with a
31   range of 0-30.
32
33   *4.3 Healthy Brain Network (HBN) Data*
34
35   The HBN dataset consists of participants from approximately 5-22 years old. The data were
36   collected from four sites near the New York greater metropolitan area. 1201 participants with
37   resting-state connectomes (10 minute scans) remained after applying the exclusion criteria.
38   39.80% were female, and the average age was 11.65 (s.d. 3.42) years, with a range of 5.58-
39   21.90. Family information is not available in this dataset.
40
41   For the attention problems measure, we used the CBCL Attention Problems Raw Score [56]. 51
42   participants were missing the attention problems score, but the mean score of the remaining
43   participants was 7.41 (s.d. 4.54), with a range of 0-19.
44

For the matrix reasoning measure, we also used the WISC-V [57] Matrix Reasoning Total Raw
Score. 177 participants were excluded for missing this measure. The mean score was 18.36
(s.d. 4.46), with a range of 2-31.

4.4 Human Connectome Project Development (HCPD) Data

The HCPD dataset includes healthy participants ages 8-22, with imaging data acquired at four
sites across the United States (Harvard, UCLA, University of Minnesota, Washington University
in St. Louis). 605 participants with resting-state connectomes (up to 26 minutes of resting-state
data) remained after excluding low-quality or high-motion data. Among these 605 participants,
the average age was 14.61 (s.d. 3.90) years, ranging from 8.08-21.92 years. 53.72% of
participants self-reported their sex as female, and there were 536 unique families.

For the attention problems measure, we used the Child Behavior Checklist (CBCL) [56] Attention
Problems Raw Score. 462 participants had this measure available, and the mean was 2.03 (s.d.
2.56), with a range of 0-18.

For the matrix reasoning measure, we used the WISC-V [57] Matrix Reasoning Total Raw Score.
424 participants remained in this analysis, with a mean of 21.08 (s.d. 3.96) and a range of 11-
31.

4.5 Philadelphia Neurodevelopmental Cohort (PNC) Data

The PNC dataset consists of 8-21 year-olds in the Philadelphia area who received care at the
Children's Hospital of Philadelphia. 1126 participants with resting-state scans (six minute scans)
passed our exclusion criteria. The average age was 14.80 (s.d. 3.29) years, with a range of 8-
21. The percentage of self-reported female participants was 54.62%.

For the attention problems measure, we used the Structured Interview for Prodromal Symptoms
[58]: Trouble with Focus and Attention Severity Scale (SIP001, accession code:
phv00194672.v2.p2). 1104 participants had this measure available, and the mean was 1.03
(s.d. 1.19), with a range of 0-6.

For the matrix reasoning measure, we used the Penn Matrix Reasoning [59,60] Total Raw Score
(PMAT_CR, accession code: phv00194834.v2.p2).1119 participants remained in this analysis,
with a mean of 11.99 (s.d. 4.09) and a range of 0-24.

4.6 Baseline Models

For the primary analyses, we trained a ridge regression model using 5-fold cross-validation [27].
For HBN, HCPD, and PNC, five nested folds were used for hyperparameter selection, while only
two nested folds were used in ABCD to reduce computation time. Within the folds, the top 5% of
features most significantly correlated with the phenotypic variable were selected. Furthermore,

we performed a grid search over the L2 regularization parameter α ($\alpha=10^{\{-3,-2,-1,0,1,2,3\}}$), with the
chosen model being the one with the highest Pearson's correlation value r in the nested folds.
3
For our baseline gold standard model (Figures 2-5: labeled "Gold standard"), the data were split
accounting for family structure, where applicable (ABCD and HCPD only), such that all
members of a single family were included in the same test split. In addition, we performed
cross-validated covariate regression, where several covariates were regressed from the
functional connectivity data within the cross-validation scheme [38,40]. Covariates were first
regressed from the training data, and then those parameters were applied to regress covariates
from the test data. The covariates included mean head motion (FD), sex, and age, though age
was not regressed from the data for models predicting age. Furthermore, where applicable
(ABCD, HBN, and HCPD), site differences were corrected within the cross-validation scheme
using ComBat [29–31]. ComBat was performed separately from covariate regression because
ComBat is designed for batch effects, not continuous variables [61]. In addition to the baseline
gold standard model, we evaluated numerous forms of leakage, as described in the following
sections (see also Figure 1).
17
18 *4.7 Selection of forms of leakage*
19
Due to the myriad forms of leakage, investigating every type of leakage is not feasible. In this
work, we focused on three broad categories of leakage, including feature selection leakage,
covariate-related leakage (leakage via site correction or covariate regression), and subject-level
leakage (leakage via family structure or repeated subjects). We chose these particular forms of
leakage because we expect that they are the most common and/or impactful errors in
neuroimaging prediction studies. In our experience, feature selection leakage is an important
consideration because it may manifest in subtle ways. For example, one may perform an
explanatory analysis, such as determining the most significantly different brain networks
between two groups, and then use these predetermined networks as predictive features, which
constitutes leakage. As for covariate-related leakage, we have noticed that site correction and
covariate regression are often performed on the combined training and test data in
neuroimaging studies. Finally, for subject-level leakage, family structure is often ignored in
neuroimaging datasets, unless it is being explicitly studied. Thus, understanding how prediction
performance may be altered by these forms of leakage remains an important question.
34
Some forms of leakage were not considered in this work, including temporal leakage, the
selection of model hyperparameters in the combined training/test data, unsupervised
dimensionality reduction in the combined training/test data, standardization of the phenotype,
and illegitimate features. Temporal leakage, where a model makes a prediction about the future
but uses test data from a time point prior to the training data [17], is not relevant for cross-
sectional studies using static functional and structural connectivity, but it could be relevant for
prediction studies using longitudinal data or brain dynamics. While evaluating models in the test
dataset to select the best model hyperparameters is a form of leakage, it has been previously
studied in neuroimaging [49] and therefore was not included in this study. Various forms of
unsupervised dimensionality reduction, such as independent component analysis [62,63], are

popular in neuroimaging and constitute leakage if performed in the combined training and test
datasets prior to performing prediction. Leakage via unsupervised dimensionality reduction
should be avoided, but we felt that leakage via feature selection is a dimensionality reduction
technique that is both more common and more impactful, due to its involvement of the target
variable. Moreover, phenotypes are sometimes standardized (i.e., z-scored) outside of the
cross-validation folds, but this form of leakage was not investigated in this work because it is
insensitive to the most common evaluation metrics in prediction using neuroimaging connectivity
(Pearson's r, q^2). Finally, leakage via illegitimate features entails the model having access to
features which it should not, such as a predictor that is a proxy for the outcome variable [17].
Studies using both imaging and clinical or phenotypic measures to predict other outcomes
should be cautious of leakage via illegitimate features, but it is less relevant for studies
predicting strictly from structural or functional connectivity data.
13
14   *4.8 Feature leakage*
15
Feature selection is a common step in many connectome-based machine learning pipelines.
Often, it consists of determining which features are the most relevant to the phenotype of
interest, such as by selecting the edge features most correlated with this phenotype. A possible
mistake is selecting features in the entire dataset, then training models and evaluating
performance with k-fold cross-validation or a train/test split. Whelan and Garavan [64] previously
demonstrated inflated performance via non-nested feature selection using random data, though
we think it is also useful to demonstrate this with neuroimaging data. To do so, we selected the
top 5% of features in the entire dataset, and then evaluated the performance using 5-fold cross-
validation.
25
26   *4.9 Covariate-related leakage*
27
A common example of leakage is correcting for site effects, such as with ComBat [29–31], in the
whole dataset prior to splitting data into training and test sets. To avoid leakage, one should
apply ComBat to the training data within each fold of cross-validation, and then use those
ComBat parameters to correct for the site of the test data, as described in a recent work by
Spisak [61]. Here, we evaluated the effect of leakage via performing ComBat on the entire dataset
and compared this to the gold standard of applying ComBat within cross-validation folds. As
described in several previous works [29–31], ComBat performs the correction based on the
following equation for feature v of the data X, with site i and scan j [29–31]:

$$x_{i,j,v}^{adjusted} = \frac{x_{i,j,v} - \widehat{\alpha_v} - \gamma_{i,v}^*}{\delta_{i,v}^*} + \widehat{\alpha_v}$$

where α_v is the overall measure for that edge, $\gamma_{i,v}$ is the additive site effects for site i and feature
v, and $\delta_{i,v}$ is the multiplicative site effects for site i and feature v [30]. However, unless performed
in a cross-validated manner, leakage occurs when estimating α_v, $\gamma_{i,v}$, and $\delta_{i,v}$ on the combined
training and test data. In practice, these parameters should be estimated only in the training
data, and then applied to correct for site in both the training and test data. Crucially, we are
performing site correction within individual datasets, where the imaging parameters are

generally harmonized across sites. As such, we may underestimate the effects of site in other
scenarios, such as when combining small datasets into one large study.
3
4   Another common form of leakage is covariate regression. For example, regressing the
5   covariates/confounds out of the whole dataset in a non-cross-validated manner has been shown
6   to negatively affect prediction performance [40]. The following equations describe regressing
7   covariates out of the whole dataset for feature X of size [N x p], covariates C of size [N x (k+1)],
8   which includes an intercept term, and the OLS solution $\hat{\beta}$ [38]:

$$\hat{\beta} = (C^T C)^{-1} C^T X$$

$$X_{adjusted} = X - C\hat{\beta}$$

11 Leakage occurs above by finding the OLS solution $\hat{\beta}$ using both training and test data.
12 Performing covariate regression within the cross-validation folds is the recommended solution to
13 avoid leakage [38,40]:

$$\hat{\beta}_{train} = (C_{train}^T C_{train})^{-1} C_{train}^T X_{train}$$

$$X_{train,adjusted} = X_{train} - C_{train}\hat{\beta}_{train}$$

$$X_{test,adjusted} = X_{test} - C_{test}\hat{\beta}_{train}$$

17 The above equations avoid leakage by finding the OLS solution $\hat{\beta}$ only in the training data, and
18 subsequently applying it to the test data. Cross-validated and non-cross-validated covariate
19 regression have been compared in several previous studies [38,40], and we build upon those
20 previous works here by evaluating them in three phenotypes and four datasets through the view
21 of leakage.
22
23 *4.10 Subject-level leakage*
24
Neuroimaging datasets, such as ABCD and HCPD, are often oversampled for twins or siblings.
Given the heritability of brain structure and function [32–34], family structure should be specifically
accounted for in analysis pipelines, such as in permutation tests [65]. In the context of this work,
having one family member in the training set and another in the test split is a form of leakage.
For instance, in a hypothetical case of predicting a highly heritable phenotype from a highly
heritable brain network, the model could "memorize" the data from one family member in the
training set and strongly predict the phenotype of another family member in the test set.
However, splitting the data into cross-validation folds by family instead of on the individual
subject level prevents leakage. If a dataset contains 1000 participants from 500 unique families,
5-fold cross-validation should include training data belonging to 400 randomly selected *families*,
and test data belonging to the other 100 randomly selected *families.*
36
Another possible case of leakage is where various scans from the same participant are treated
as separate samples, which we call "Subject leakage." This could include, for instance, treating
longitudinal data as cross-sectional or including various runs (or tasks) of fMRI acquisition for
the same participant as separate data points. To evaluate an extreme version of subject
leakage, we considered the case when a certain percentage of the subjects in the dataset were
repeated. For example, in a hypothetical dataset with 1000 participants, 20% subject leakage
would include an additional 200 repeats of random participants in the dataset, for a total dataset

size of 1200. Then, in this larger sample, we repeated nested cross-validation and compared
the prediction performance results to the original sample. In this form, subject leakage is not
directly comparable to longitudinal or repeated measurements studies, since we are instead
duplicating the exact same scan. Yet, we can use repeated subjects to demonstrate the concept
of leakage. Notably, we did not account for family structure in subject leakage, otherwise the
leaked subjects would always be in the same training or test split.
7
8 *4.11 Evaluation metrics*
9
10 Our main evaluation metric is Pearson's correlation *r* between the true and predicted phenotype.
11 This evaluation metric does not necessarily reflect predictive power but is commonly used to
12 establish brain-behavior relationships [28]. In addition, we reported cross-validation R^2, also called
13 q^2, as defined below [28]:

14
$$q^2 = 1 - \frac{\Sigma\ (y - y_{pred})^2}{\Sigma\ (y - \bar{y})^2}$$

15 where *y* and *y_{pred}* are the observed and predicted behavior, respectively, and $\bar{y}$ is the mean of
16 the observed behavior. Performance metrics were calculated by concatenating predictions
17 across folds, and then these metrics were calculated for 100 random seeds of cross-validation.
18 Importantly, q^2 is sometimes substantially negative when the model prediction gives a higher
19 mean-squared error than predicting the mean.
20
21 *4.12 Sample size*
22
To evaluate the interaction between sample size and leakage, we randomly sampled without
replacement N=100, 200, 300, and 400 participants from ABCD, HBN, HCPD, and HBN. The
ABCD data was only resampled from the four largest sites (total N=2436) to avoid issues with
ComBat where only one data point was present from a particular site after resampling. In
addition, for the two datasets with family structure (ABCD and HCPD), data were resampled by
family, not by individual, to keep approximately the same proportion of related participants in our
subsample. We repeated the resampling procedure 10 times for each dataset and sample size,
and for each resampled dataset we evaluated the gold standard and leaky prediction
performance across 10 repeats of 5-fold nested cross-validation.
32
33 *4.13 Structural connectome analysis*
34
35 Our structural connectome analyses included 635 participants from the HCPD dataset. We
36 started with the diffusion tensor data of the 635 participants. Then, we corrected for
37 susceptibility artifacts and applied DSI-studio to reconstruct the diffusion data using generalized
38 q-sampling imaging. Finally, we created structural connectomes using automatic fiber tracking
39 for the Shen 268-node atlas [55].
40
41
42
43

1 *4.14 Additional models*
2
We evaluated the effects of leakage in two additional models: support vector regression (SVR)
[27] and connectome-based predictive modeling (CPM) [2]. In both cases, we performed 5% feature
selection, as described above. For SVR, the radial basis function was used, and we performed
a grid search for the L2 regularization parameter ($C=10^{\{-3,-2,-1,0,1,2,3\}}$), where C is inversely
proportional to regularization strength. For CPM, the positive and negative features were
combined into a single number, and a univariate linear regression model was then fitted.
9
10 *Data availability*
11
12 Data are available through the Adolescent Brain Cognitive Development Study (22), the Healthy
13 Brain Network Dataset (23), the Human Connectome Project Development Dataset (24), and
14 the Philadelphia Neurodevelopmental Cohort Dataset (25, 26). Source data (i.e., prediction
15 performance values) that can be used for creating the plots are provided with this work and also
16 available at https://github.com/mattrosenblatt7/leakage_neuroimaging.
17
18 *Code availability*
19
20 Code for the analyses and plots is available at:
21 https://github.com/mattrosenblatt7/leakage_neuroimaging.
22
23 *Acknowledgements*
24

This study was supported by the National Institute of Mental Health grant R01MH121095
(obtained by D.S.). M.R. was supported by the National Science Foundation Graduate
Research Fellowship under grant DGE2139841. L.T. was supported by the Gruber Science
Fellowship. S.N. was supported by the National Institute of Mental Health under grant
K00MH122372. Any opinions, findings, and conclusions or recommendations expressed in this
material are those of the authors and do not necessarily reflect those of the funding agencies.
31
The Human Connectome Project Development data was supported by the National Institute Of
Mental Health of the National Institutes of Health under Award Number U01MH109589 and by
funds provided by the McDonnell Center for Systems Neuroscience at Washington University in
St. Louis. The HCP-Development 2.0 Release data used in this report came from DOI:
10.15154/1520708. Additional data used in the preparation of this article were obtained from the
Adolescent Brain Cognitive DevelopmentSM (ABCD) Study (https://abcdstudy.org), held in the
NIMH Data Archive (NDA). This is a multisite, longitudinal study designed to recruit more than
10,000 children age 9-10 and follow them over 10 years into early adulthood. The ABCD
Study® is supported by the National Institutes of Health and additional federal partners under
award numbers U01DA041048, U01DA050989, U01DA051016, U01DA041022, U01DA051018,
U01DA051037, U01DA050987, U01DA041174, U01DA041106, U01DA041117, U01DA041028,
U01DA041134, U01DA050988, U01DA051039, U01DA041156, U01DA041025, U01DA041120,
U01DA051038, U01DA041148, U01DA041093, U01DA041089, U24DA041123, U24DA041147.
A full list of supporters is available at https://abcdstudy.org/federal-partners.html. A listing of
participating sites and a complete listing of the study investigators can be found at

https://abcdstudy.org/consortium_members/. ABCD consortium investigators designed and
implemented the study and/or provided data but did not necessarily participate in the analysis or
writing of this report. This manuscript reflects the views of the authors and may not reflect the
opinions or views of the NIH or ABCD consortium investigators. The Healthy Brain Network
(http://www.healthybrainnetwork.org) and its initiatives are supported by philanthropic
contributions from the following individuals, foundations and organizations: Margaret Bilotti;
Brooklyn Nets; Agapi and Bruce Burkard; James Chang; Phyllis Green and Randolph Cōwen;
Grieve Family Fund; Susan Miller and Byron Grote; Sarah and Geoff Gund; George Hall;
Jonathan M. Harris Family Foundation; Joseph P. Healey; The Hearst Foundations; Eve and
Ross Jaffe; Howard & Irene Levine Family Foundation; Rachael and Marshall Levine; George
and Nitzia Logothetis; Christine and Richard Mack; Julie Minskoff; Valerie Mnuchin; Morgan
Stanley Foundation; Amy and John Phelan; Roberts Family Foundation; Jim and Linda
Robinson Foundation, Inc.; The Schaps Family; Zibby Schwarzman; Abigail Pogrebin and David
Shapiro; Stavros Niarchos Foundation; Preethi Krishna and Ram Sundaram; Amy and John
Weinberg; Donors to the 2013 Child Advocacy Award Dinner Auction; Donors to the 2012 Brant
Art Auction. Additional data were provided by the PNC (principal investigators Hakon
Hakonarson and Raquel Gur; phs000607.v1.p1). Support for the collection of these datasets
was provided by grant RC2MH089983 awarded to Raquel Gur and RC2MH089924 awarded to
Hakon Hakonarson
20
21   *Author contributions*
22
23   M.R. and D.S. conceptualized the study. L.T. and D.S curated the data. M.R. performed the
24   formal analysis. M.R. and D.S. drafted the manuscript. L.T., R.J., S.N., and D.S. reviewed and
25   edited the manuscript. M.R., R.J., S.N., and D.S. contributed to the visualizations. D.S.
26   supervised the project.
27
28   *Competing interests*
29
30   The authors declare no competing interests.
31
32   *Inclusion and ethics*
33
34   Data collection was approved by the relevant ethics review board for each of the four datasets.
35   Informed consent was obtained by the relevant data collection teams in the four public datasets.
36   Additionally, we have local human research approval for using these datasets.
37
References

1.   Tejavibulya, L. *et al.* Predicting the future of neuroimaging predictive models in mental

health. *Mol. Psychiatry* **27**, 3129–3137 (2022).

2.   Shen, X. *et al.* Using connectome-based predictive modeling to predict individual behavior

from brain connectivity. *Nat. Protoc.* **12**, 506–518 (2017).

3. Sui, J., Jiang, R., Bustillo, J. & Calhoun, V. Neuroimaging-based Individualized Prediction

of Cognition and Behavior for Mental Disorders and Health: Methods and Promises. *Biol.*

Psychiatry **88**, 818–828 (2020).

4. Barron, D. S. *et al.* Transdiagnostic, Connectome-Based Prediction of Memory Constructs

Across Psychiatric Disorders. *Cereb. Cortex* **31**, 2523–2533 (2020).

5. Song, H. & Rosenberg, M. D. Predicting attention across time and contexts with functional

brain connectivity. *Current Opinion in Behavioral Sciences* **40**, 33–44 (2021).

6. Boyle, R. *et al.* Connectome-based predictive modelling of cognitive reserve using task-

based functional connectivity. *Eur. J. Neurosci.* **57**, 490–510 (2023).

7. Tetereva, A. & Pat, N. The (Limited?) Utility of Brain Age as a Biomarker for Capturing

Cognitive Decline. *bioRxiv* 2022.12.31.522374 (2023) doi:10.1101/2022.12.31.522374.

8. Lund, M. J. *et al.* Brain age prediction using fMRI network coupling in youths and

associations with psychiatric symptoms. *Neuroimage Clin* **33**, 102921 (2022).

9. Kardan, O. *et al.* Resting-state functional connectivity identifies individuals and predicts age

in 8-to-26-month-olds. *Dev. Cogn. Neurosci.* **56**, 101123 (2022).

10. Zhai, J. & Li, K. Predicting Brain Age Based on Spatial and Temporal Features of Human

Brain Functional Networks. *Front. Hum. Neurosci.* **13**, 62 (2019).

11. Gao, M. *et al.* Multimodal brain connectome-based prediction of suicide risk in people with

late-life depression. *Nature Mental Health* **1**, 100–113 (2023).

12. Wu, X. *et al.* Connectome-based predictive modeling of compulsion in obsessive–

compulsive disorder. *Cereb. Cortex* **33**, 1412–1425 (2022).

13. Garrison, K. A. *et al.* Transdiagnostic Connectome-Based Prediction of Craving. *Am. J.*

Psychiatry **180**, 445–453 (2023).

14. Spisak, T., Bingel, U. & Wager, T. D. Multivariate BWAS can be replicable with moderate

sample sizes. *Nature* vol. 615 E4–E7 (2023).

15. Bzdok, D., Varoquaux, G. & Steyerberg, E. W. Prediction, Not Association, Paves the Road to Precision Medicine. *JAMA Psychiatry* **78**, 127–128 (2021).

16. Kaufman, S., Rosset, S., Perlich, C. & Stitelman, O. Leakage in data mining: Formulation, detection, and avoidance. *ACM Trans. Knowl. Discov. Data* **6**, 1–21 (2012).

17. Kapoor, S. & Narayanan, A. Leakage and the reproducibility crisis in machine-learning-based science. *Patterns* **4**, 100804 (2023).

18. Poldrack, R. A., Huckins, G. & Varoquaux, G. Establishment of Best Practices for Evidence for Prediction: A Review. *JAMA Psychiatry* **77**, 534–540 (2020).

19. Poldrack, R. A. *et al.* Scanning the horizon: towards transparent and reproducible neuroimaging research. *Nat. Rev. Neurosci.* **18**, 115–126 (2017).

20. Botvinik-Nezer, R. & Wager, T. D. Reproducibility in Neuroimaging Analysis: Challenges and Solutions. *Biol Psychiatry Cogn Neurosci Neuroimaging* (2022) doi:10.1016/j.bpsc.2022.12.006.

21. Marek, S. *et al.* Reproducible brain-wide association studies require thousands of individuals. *Nature* **605**, E11 (2022).

22. Casey, B. J. *et al.* The Adolescent Brain Cognitive Development (ABCD) study: Imaging acquisition across 21 sites. *Dev. Cogn. Neurosci.* **32**, 43–54 (2018).

23. Alexander, L. M. *et al.* An open resource for transdiagnostic research in pediatric mental health and learning disorders. *Sci Data* **4**, 170181 (2017).

24. Somerville, L. H. *et al.* The Lifespan Human Connectome Project in Development: A large-scale study of brain connectivity development in 5-21 year olds. *Neuroimage* **183**, 456–468 (2018).

25. Satterthwaite, T. D. *et al.* Neuroimaging of the Philadelphia neurodevelopmental cohort. *Neuroimage* **86**, 544–553 (2014).

26. Satterthwaite, T. D. *et al.* The Philadelphia Neurodevelopmental Cohort: A publicly available resource for the study of normal and abnormal brain development in youth.

Neuroimage **124**, 1115–1119 (2016).

27. Pedregosa, F. *et al.* Scikit-learn: Machine learning in Python. *The Journal of machine Learning research* **12**, 2825–2830 (2011).

28. Scheinost, D. *et al.* Ten simple rules for predictive modeling of individual differences in neuroimaging. *Neuroimage* **193**, 35–45 (2019).

29. Johnson, W. E., Li, C. & Rabinovic, A. Adjusting batch effects in microarray expression data using empirical Bayes methods. *Biostatistics* **8**, 118–127 (2007).

30. Fortin, J.-P. *et al.* Harmonization of multi-site diffusion tensor imaging data. *Neuroimage* **161**, 149–170 (2017).

31. Fortin, J.-P. *et al.* Harmonization of cortical thickness measurements across scanners and sites. *Neuroimage* **167**, 104–120 (2018).

32. Koten, J. W., Jr *et al.* Genetic contribution to variation in cognitive function: an FMRI study in twins. *Science* **323**, 1737–1740 (2009).

33. Adhikari, B. M. *et al.* Heritability estimates on resting state fMRI data using ENIGMA analysis pipeline. *Pac. Symp. Biocomput.* **23**, 307–318 (2018).

34. Zhao, B. *et al.* Heritability of Regional Brain Volumes in Large-Scale Neuroimaging and Genetic Studies. *Cereb. Cortex* **29**, 2904–2914 (2019).

35. Noble, S., Mejia, A. F., Zalesky, A. & Scheinost, D. Improving power in functional magnetic resonance imaging by moving beyond cluster-level inference. *Proc. Natl. Acad. Sci.* **119**, e2203020119 (2022).

36. Verstynen, T. & Kording, K. P. Overfitting to 'predict'suicidal ideation. *Nature Human Behaviour* 1–2 (2023).

37. Rajpurkar, P. *et al.* CheXNet: Radiologist-Level Pneumonia Detection on Chest X-Rays with Deep Learning. *arXiv [cs.CV]* (2017).

38. Snoek, L., Miletić, S. & Scholte, H. S. How to control for confounds in decoding analyses of neuroimaging data. *Neuroimage* **184**, 741–760 (2019).

39. More, S., Eickhoff, S. B., Caspers, J. & Patil, K. R. Confound Removal and Normalization in Practice: A Neuroimaging Based Sex Prediction Case Study. in *Machine Learning and Knowledge Discovery in Databases. Applied Data Science and Demo Track* 3–18 (Springer International Publishing, 2021). doi:10.1007/978-3-030-67670-4_1.

40. Chyzhyk, D., Varoquaux, G., Milham, M. & Thirion, B. How to remove or control confounds in predictive models, with applications to brain biomarkers. *Gigascience* **11**, (2022).

41. Hamdan, S. *et al.* Confound-leakage: Confound Removal in Machine Learning Leads to Leakage. *arXiv [cs.LG]* (2022).

42. Horien, C. *et al.* A hitchhiker's guide to working with large, open-source neuroimaging datasets. *Nat Hum Behav* **5**, 185–193 (2021).

43. Li, J. *et al.* Cross-ethnicity/race generalization failure of behavioral prediction from resting-state functional connectivity. *Sci Adv* **8**, eabj1812 (2022).

44. Chen, Z. *et al.* Evaluation of Risk of Bias in Neuroimaging-Based Artificial Intelligence Models for Psychiatric Diagnosis: A Systematic Review. *JAMA Netw Open* **6**, e231671 (2023).

45. Wang, R., Chaudhari, P. & Davatzikos, C. Bias in machine learning models can be significantly mitigated by careful training: Evidence from neuroimaging studies. *Proc. Natl. Acad. Sci. U. S. A.* **120**, e2211613120 (2023).

46. Varoquaux, G. *et al.* Assessing and tuning brain decoders: Cross-validation, caveats, and guidelines. *Neuroimage* **145**, 166–179 (2017).

47. Botvinik-Nezer, R. *et al.* Variability in the analysis of a single neuroimaging dataset by many teams. *Nature* **582**, 84–88 (2020).

48. Dafflon, J. *et al.* A guided multiverse study of neuroimaging analyses. *Nat. Commun.* **13**, 3758 (2022).

49. Hosseini, M. *et al.* I tried a bunch of things: The dangers of unexpected overfitting in classification of brain data. *Neurosci. Biobehav. Rev.* **119**, 456–467 (2020).

50. Dockès, J., Varoquaux, G. & Poline, J.-B. Preventing dataset shift from breaking machine-

learning biomarkers. *Gigascience* **10**, (2021).

51. Yeung, A. W. K., More, S., Wu, J. & Eickhoff, S. B. Reporting details of neuroimaging

studies on individual traits prediction: A literature survey. *Neuroimage* **256**, 119275 (2022).

52. Carlini, N., Liu, C., Erlingsson, Ú., Kos, J. & Song, D. The Secret Sharer: Evaluating and

Testing Unintended Memorization in Neural Networks. in *USENIX Security Symposium* vol.

267 (2019).

53. Feldman, V. Does learning require memorization? a short tale about a long tail. in

Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing 954–

959 (Association for Computing Machinery, 2020). doi:10.1145/3357713.3384290.

54. Papademetris, X. *et al.* BioImage Suite: An integrated medical image analysis suite: An

update. *Insight J.* **2006**, 209 (2006).

55. Shen, X., Tokoglu, F., Papademetris, X. & Constable, R. T. Groupwise whole-brain

parcellation from resting-state fMRI data for network node identification. *Neuroimage* **82**,

403–415 (2013).

56. Achenbach, T. M. & Ruffle, T. M. The Child Behavior Checklist and related forms for

assessing behavioral/emotional problems and competencies. *Pediatr. Rev.* **21**, 265–271

(2000).

57. Wechsler, D. *WISC-V: Technical and interpretive manual.* (NCS Pearson, Incorporated,

2014).

58. Miller, T. J. *et al.* Prodromal assessment with the structured interview for prodromal

syndromes and the scale of prodromal symptoms: predictive validity, interrater reliability,

and training to reliability. *Schizophr. Bull.* **29**, 703–715 (2003).

59. Bilker, W. B. *et al.* Development of abbreviated nine-item forms of the Raven's standard

progressive matrices test. *Assessment* **19**, 354–369 (2012).

60. Moore, T. M., Reise, S. P., Gur, R. E., Hakonarson, H. & Gur, R. C. Psychometric

properties of the Penn Computerized Neurocognitive Battery. *Neuropsychology* **29**, 235–246 (2015).

61. Spisak, T. Statistical quantification of confounding bias in machine learning models. *Gigascience* **11**, (2022).

62. McKeown, M. J. *et al.* Analysis of fMRI data by blind separation into independent spatial components. *Hum. Brain Mapp.* **6**, 160–188 (1998).

63. Chen, S. *et al.* Group independent component analysis reveals consistent resting-state networks across multiple sessions. *Brain Res.* **1239**, 141–151 (2008).

64. Whelan, R. & Garavan, H. When optimism hurts: inflated predictions in psychiatric neuroimaging. *Biol. Psychiatry* **75**, 746–748 (2014).

65. Winkler, A. M., Webster, M. A., Vidaurre, D., Nichols, T. E. & Smith, S. M. Multi-level block permutation. *Neuroimage* **123**, 253–268 (2015).

1   **Supplementary Materials for:**

2   The effects of data leakage on connectome-based machine learning models

4   *S1. Summary of the leakage types in this study*

Leakage type	Why is it leakage?	Relation to Kapoor and Narayanan [17]
Leaky feature selection	If the test data contributes to the feature selection process, there is no assessment of generalizability of the feature selection from training to test data.	Feature selection jointly on the training and test sets
Leaky site correction	If sites are controlled for in the training/test data simultaneously, then the test data indirectly leaks information back into the model training via the site correction parameters.	Pre-processing on the training and test sets
Leaky covariate regression	If covariates are regressed in the training/test data simultaneously, then the test data indirectly leaks information back into the model training via the covariate regression parameters.	Pre-processing on the training and test sets
Family leakage	Having one family member in the training dataset and another in the test dataset breaches the independence between training/test data. This could be particularly relevant for heritable behaviors.	Non-independence between the training and test sets; Sampling bias
Subject leakage	Similar to family leakage, if subjects are repeated across the training and test sample, then the model training is directly affected by a subject that can also be in the test dataset.	Duplicate data points

6   **Table S1.** Summary of the leakage types used in this study and their mapping to those used by Kapoor and

7   Narayanan [17].

1   *S2. Evaluation of leakage with q^2 in the main dataset (HCPD)*

2
3   **Figure S1.** Evaluation of leakage in HCPD with a metric of q^2, related to Figures 2-5. Rows represent different
4   leakage types, and columns show different phenotypes. The black bar represents the median performance of the
5   "gold standard" models across random iterations, and the histograms show prediction performance across 100
6   iterations of 5-fold cross-validation.

1 *S3. Family leakage analysis*
2
Beyond the three original phenotypes and models in this study, we considered several
additional phenotypes from the Child Behavioral Checklist (CBCL) [56], as well as one additional
model (Random Forest). The phenotypes were the Anxiety and Depression CBCL Syndrome
Scale Raw Score (Anx/Dep), Aggressive CBCL Syndrome Scale Raw Score (Aggression),
Internal CBCL Syndrome Scale Raw Score (Internal), and the External CBCL Syndrome Scale
Raw Score (External). The Random Forest was considered in case the other models (ridge
regression, SVR, CPM) had too low of a memorization capacity that would limit the effects of
leakage. For the Random Forest [27], 10 estimators were used, and a grid search was performed
varying the maximum depth (3, 5, 7, 9).
12
13 We found that, across all models and phenotypes, the median performance of twin leakage was
14 greater than the median gold standard performance (Figure S2). The effects of leakage were
15 greater for ridge regression and SVR compared to CPM and the Random Forest. Although not
16 tested, family leakage may become increasingly impactful for complex models, such as neural
17 networks, that are trained with larger datasets and more participants per family.
18
19

20
Figure S2. Comparison of prediction performance between the gold standard and twin leakage in the ABCD twin
subset, related to Figure 6. Boxplot elements were defined as follows: the center line is the median across 100
random iterations; box limits are the upper and lower quartiles; whiskers are 1.5x the interquartile range; points are
outliers. Four models (ridge regression, SVR, CPM, Random Forest) and seven phenotypes were included. In all
cases, the median performance was higher for twin leakage compared to the gold standard. AP: Attention CBCL
Syndrome Scale Raw Score; MR: WISC-V Matrix Reasoning Total Raw Score; Anx/Dep: Anxiety and Depression
CBCL Syndrome Scale Raw Score; Aggression: Aggressive CBCL Syndrome Scale Raw Score; Internal: Internal
CBCL Syndrome Scale Raw Score; External: External CBCL Syndrome Scale Raw Score.
29
We compared the similarity of each phenotype between twins and the corresponding increase in
prediction performance in a leaky vs. non-leaky pipeline. As a metric of similarity, we took the
ratio of the mean absolute error of the phenotype between each twin pair to the mean absolute
error between the participant and all non-twin participants, and this ratio was averaged across
all participants. The MAE ratio for participant *p* is defined as:

$$MAE\ Ratio\ = \frac{MAE(y_p, y_{p,twin})}{MAE(y_p, y_{p,non-twin})}$$

Thus, a value closer to 0 reflects greater similarity of that phenotype between twins. We chose
to use phenotype similarity instead of literature estimates of heritability because a phenotype
such as age is not necessarily "heritable," but it is identical (or nearly identical due to different
interview dates) for twins. Similarly, the CBCL measures were determined by a parent
questionnaire and thus may reflect the tendencies of a parent in answering questions rather
than explicit heritability of a trait.
42

1 The most similar phenotypes did not necessarily show greater leakage effects (Figure S3). This
2 result could point toward the limited memorization capacity of the model, given the study design.
3 For example, if there were many members per family, the model may more easily "memorize"
4 the signature of family members, and the effects of leakage may be greater.

5
6 **Figure S3.** Comparison of prediction performance with twin leakage (*y*-axis) and the gold standard (*x*-axis) colored by
7 phenotype similarity, related to Figure 6. An MAE Ratio closer to zero entails greater similarity between twins. The
8 shape of each point indicates the phenotype.
9
10
11 Furthermore, we performed a simulation that altered the percentage of one-individual families in
12 the dataset. To do this, we started with only families with multiple individuals, and then we
13 added in random fractions of the participants without family members. In general, the effects of
14 leakage increased as the fraction of participants coming from families with multiple members
15 increased (Figure S4). However, the effects were still relatively small.
16

1
2 **Figure S4.** Simulation varying the percentage of participants with family members in the ABCD datasets, related to
3 Figure 6. Ridge regression was performed for 100 random iterations with the datasets subsample consisting of 30,
4 40, 50, 60, 70, 80, 90, and 100% multi-participant families (100% is restricted to only participants with other family
5 members). The error bars reflect the 2.5th and 97.5th percentiles of the 100 random iterations. AP: Attention
6 Problems, MR: Matrix Reasoning.

1   *S4. Leakage for additional datasets and models*
2

3
4   **Figure S5.** Summary of leakage types in additional three datasets (ABCD, HBN, PNC), related to Figure 7. The rows
5   show different leakage types, and, within each dataset, the columns show different phenotypes. The black bar
6   represents the median performance of the "gold standard" models across random iterations, and the
7   histograms show prediction performance across 100 iterations of 5-fold cross-validation.
8

Figure S6. Evaluation of leakage in ABCD, HBN, and PNC with a metric of q^2, related to Figure 7. Rows represent different leakage types, and columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.

1
2 **Figure S7.** Similarity of coefficients across all pipelines, averaged over 100 random seeds, related to Figure 8. For
3 each pair of the 13 pipelines, we computed the correlation between their coefficients. Missing values (i.e., no site
4 information in PNC) are shown in black.

1
Figure S8. Subnetwork-level rank correlations for number of selected features, related to Figure 8. The boxes are
colored by the leakage family: black (gold standard), orange (non-leaky analysis choices), blue (feature leakage),
green (covariate-related leakage), yellow (subject-level leakage). To compare the gold standard features to features
from the other pipelines, we calculated the rank correlation between the number of features in each subnetwork
(adjusted for subnetwork size). Boxplot elements were defined as follows: the center line is the median of the rank
correlation across 100 random iterations; box limits are the upper and lower quartiles; whiskers are 1.5x the
interquartile range; points are outliers.

1
2 **Figure S9.** Difference in median performances across 10 random seeds of 5-fold cross-validation, related to Figure 9.
3 Rows represent the dataset, and columns show the phenotype. For each leakage type (x-axis), there are four results
4 (N=100, 200, 300, 400). For each sample size, we repeated 10 random seeds of resampling for 10 iterations of 5-fold
5 cross-validation. Boxplot elements were defined as follows: the center line is the median across 10 iterations; box
6 limits are the upper and lower quartiles; whiskers are 1.5x the interquartile range; points are outliers.
7
8

Figure S10. Evaluation of leakage types with *r* and SVR. The rows show different leakage types, and, within each dataset, the columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.

Figure S11. Evaluation of leakage types with *r* and CPM. The rows show different leakage types, and, within each dataset, the columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.

Figure S12. Evaluation of leakage types with q^2 and SVR. The rows show different leakage types, and, within each dataset, the columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.

Figure S13. Evaluation of leakage types with q^2 and CPM. The rows show different leakage types, and, within each dataset, the columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.

Figure S14. Evaluation of leakage types for matrix reasoning, attention problems, and age prediction in structural connectomes using q^2, related to Figure 10. The rows show different leakage types, and the columns show different phenotypes. The black bar represents the median performance of the "gold standard" models across random iterations, and the histograms show prediction performance across 100 iterations of 5-fold cross-validation.