Pitch is Not a Helix: Probing the Structure of Musical Pitch Across Tasks and Experience

Raja Marjieh[1], Thomas L. Griffiths[1,2,†], and Nori Jacoby[3,4,†]

[1]Department of Psychology, Princeton University, USA

[3]Department of Computer Science, Princeton University, USA

[3]Max Planck Institute for Empirical Aesthetics, Germany

[4]Department of Psychology, Cornell University, USA

[†]Equal Contribution.

Author Note

Corresponding author: Raja Marjieh. E-mail: `raja.marjieh@princeton.edu`.

Data and code: https://osf.io/nx586/?view_only=a0f74c9269a4448f821aadccf76ba175

Abstract

Pitch perception is at the core of our experience of both speech and music, and understanding the appropriate representation of musical pitch has intrigued scholars for centuries. The pitch helix, which jointly represents logarithmic scaling of the periodicity of tones and the heightened similarity between tones separated by an octave has been widely assumed to be the underlying representation of pitch. Despite becoming default textbook material, the empirical basis of the pitch helix is highly limited due to small sample sizes and inadequate experimental designs. Drawing inspiration from representational similarity analysis in neuroscience, we revisit this problem through a series of nine experiments, involving participants with varied levels of musical expertise ($N = 592$), and paradigms covering both perception and production. We show that, depending on task and musical experience, the best geometrical approximation to the representation of pitch can exhibit an array of structures ranging from linear to double-helical structures, providing strong evidence that a simple helical representation cannot explain the data. Surprisingly, we also find that octave equivalence is strongest in the singing task despite being the most challenging due to production noise. These results suggest a new, broader understanding of how we perceive pitch.

Keywords: pitch perception, representations, octave equivalence, singing

Pitch is Not a Helix: Probing the Structure of Musical Pitch

Across Tasks and Experience

Pitch is one of the most extensively studied psychological phenomena due to its crucial role in both music and speech perception (Attneave & Olson, 1971; Koelsch & Siebel, 2005; Peretz & Zatorre, 2005; Levitin, 2006; Plack et al., 2006; Zatorre et al., 2007; McDermott & Oxenham, 2008; Patel, 2010; Wong et al., 2012; McPherson & McDermott, 2018; Oxenham, 2018; Jacoby et al., 2019). Research on pitch typically focuses on two major, complementary questions. The first question concerns the computational and neural processes underlying the local transformation from a given sound sensation to pitch perception (Plack et al., 2006; McDermott & Oxenham, 2008; Oxenham, 2018). In this area, researchers have explored the integration of both spatial and temporal cues (Von Békésy, 1960; Rose et al., 1967; Patterson, 1976; Shamma, 1985; Cedolin & Delgutte, 2010; Bentsen et al., 2011), including resolved and unresolved harmonics (Plomp, 1967; Shackleton & Carlyon, 1994; Lau et al., 2017). Moreover, empirical studies have investigated the neural correlates of pitch processing (Schulze et al., 2002; Bendor & Wang, 2005; Schnupp et al., 2011; Norman-Haignere et al., 2013; Feng & Wang, 2017), while computational modeling has provided insights into the biological mechanisms involved in this transformation (de Cheveigné, 2010).

The second major question concerns how individual pitches are combined to form larger perceptual structures, such as pitch contours in speech perception, which convey prosodic information, or lexical distinctions in tone languages. In music, individual pitches are organized into scales that reference tonal centers (Krumhansl & Kessler, 1982; Fogel et al., 2015), ultimately creating melodies (Cuddy et al., 1981; Dowling, 1990; Temperley, 2008; Anglada-Tort et al., 2023) and complete musical compositions (Zatorre et al., 1994; Cheung et al., 2019; Zatorre, 2024). Key to this question is understanding the underlying global representations that enable the formation of larger perceptual units from individual

Figure 1

The pitch helix and its underlying components, the pitch height line and the chroma circle.

Numbers indicate semitonal pitch values relative to a generic base labeled as 0.

pitches (Shepard, 1982a, 1982b). These global representations, which organize the relationships between different pitch percepts, are crucial for both the neuroscience and psychology of music (Patel, 2003).

Perhaps the most well-known of these structures is the pitch helix (Figure 1). This model, proposed by Shepard (Shepard, 1978, 1982a, 1982b; though see also Ruckmick, 1929) accounts for two key features of pitch in Western music. First, pitch is organized linearly on a logarithmic scale: tones with slower periodicity are perceived as "low", while those with faster periodicity are perceived as "high" (ANSI, 1960; Jacoby et al., 2019). Additionally, Western music uses octave equivalence, where tones with periodicities differing by an octave (a 2:1 ratio) share the same note name, or chroma, and are treated as musically similar (Shepard, 1964; Deutsch, 1973; Kallman, 1982; Shepard, 1982a; Demany & Armand, 1984; Hoeschele et al., 2012; Hoeschele et al., 2013; Jacoby et al., 2019). The combination of these features—pitch height and octave equivalence—led to the hypothesis that musical pitch representations could be approximated by a helix (Shepard, 1982a). Since then, the pitch helix and its sub-components have become a standard topic

in many perception and music textbooks (e.g., Krumhansl, 2001; Plack et al., 2006; Tymoczko, 2006; Wolfe et al., 2006; Goldstein, 2008; Plack, 2018), as well as modern research and review articles (e.g., Trainor and Unrau, 2011; Hoeschele et al., 2012; Milne and Holland, 2016; Jacoby et al., 2019; Marjieh, Sucholutsky, et al., 2024).

What evidence supports the concept of a helical pitch representation? Most research since Shepard's original work tends to focus on pitch height and octave equivalence separately (though see Regev et al., 2019). Research has uncovered several findings that support the idea of pitch organization from low to high. The ear itself performs frequency decomposition, with high frequencies processed closer to the base of the cochlea (Von Békésy, 1960; Schnupp et al., 2011). This tonotopic organization is maintained in both the midbrain and primary auditory cortex (Winter et al., 2001; Patterson et al., 2002; Hall & Plack, 2009). Even non-experts are capable of making low-high judgments with considerable accuracy (Plack & Oxenham, 2005), and pitch perception follows a roughly logarithmic scale across a broad frequency range (Attneave & Olson, 1971; Moore, 1973; Jacoby et al., 2019). However, this mapping is not entirely straightforward, as pitch perception is influenced by both spatial and temporal cues (Schnupp et al., 2011). Additionally, tonotopic regions including the auditory cortex do not respond robustly in the same way to tones of the same pitch with different timbres (Winter et al., 2001; Schulze et al., 2002; Hall & Plack, 2009) which indicates that they reflect lower-level, frequency-related aspects of tones rather than a fully invariant pitch representation (Nelken, 2011).

The findings on octave equivalence are varied. Octave equivalence is fundamental to Western music theory (d'Arezzo, 1955; Drabkin, 2001; Aldwell et al., 2018), and octaves are common across songs from various cultures (Kuroyanagi et al., 2019; Mehr et al., 2019). However, debate persists in the literature regarding its dependence on biological mechanisms and its prevalence among individuals with or without musical training (Humphreys, 1939; Shepard, 1964; Deutsch, 1973; Idson & Massaro, 1978; Kallman &

Massaro, 1979; Kallman, 1982). Kallman (1982) used a similarity rating method testing three musicians, finding that only one of the three demonstrated a significant increase in perceived similarity for tones separated by an octave. Later, Demany and Armand (1984) used a melodic similarity paradigm, finding octave equivalence in children but noting a weaker effect in adults. More recently, Jacoby et al. (2019) used a singing paradigm, showing that octave equivalence is culturally contingent (absent among the Tsimane', an indigenous Bolivian population) and varies within Western participants based on musical expertise. This aligns with Regev et al. (2019), who used EEG signals for deviance detection, indicating that octave equivalence was not automatically detected, even by expert musicians. Finally, Hoeschele and colleagues (Hoeschele et al., 2012; Hoeschele et al., 2013) used an operant conditioning test with humans and chickadees, finding that only humans exhibited octave equivalence (see also Wagner et al., 2022; Wagner et al., 2023; Wagner et al., 2024). However, the degree to which octave equivalence is based on biological mechanisms remains highly debated (Pressnitzer & Demany, 2019), with consensus proving difficult due to the diverse range of paradigms, participant groups, and analytical methods used across studies.

Based on the above evidence, it is now natural to ask: Is the pitch helix a psychological reality? Alternatively, does the derived structure merely reflect diverse factors that vary with task, expertise, and culture? In this alternative view, pitch perception involves reweighting various features with differing levels of salience to meet specific task demands. This question is important because it determines whether we can realistically expect to find robust neural correlates. If the pitch helix is not genuinely represented in the mind, then attempting to locate it would be futile.

It is surprising that the psychological research that directly addresses the question of the pitch helix, and global pitch representations more broadly, has largely relied on limited data and experimental designs. For instance, some studies that collected direct similarity judgments between tone pairs relied on small musician groups and yielded

conflicting results (e.g., Kallman (1982) found evidence for octave equivalence in only one out of the three musicians tested, whereas Allen (1967) detected octave equivalence in data from ten musicians). Some relied exclusively on participants with significant musical experience (Krumhansl, 1979) which limits generalizability in light of evidence that auditory and pitch perception may depend on individual experience (Koelsch et al., 1999; Kishon-Rabin et al., 2001; Gaser & Schlaug, 2003; Fujioka et al., 2004; Peretz & Zatorre, 2005; Micheyl et al., 2006; Wong et al., 2007; Zatorre et al., 2007; Trainor & Corrigall, 2010; Dellacherie et al., 2011; François et al., 2013; Jacoby & Ahissar, 2013; Merzenich et al., 2013; Weiss et al., 2014; Liu et al., 2023). Additionally, studies using Shepard tones display octave equivalence by design as Shepard tones are physically identical for pitches separated by an octave, making it hard to draw inferences about the structure of the underlying helical representation (Shepard, 1978, 1982a). Notably, multiple studies confounded pitch perception with tonality. This is problematic as it is less surprising to see expertise differences in tasks involving tonality, a more complex musical feature, compared to pitch. For example, Shepard's foundational work (Shepard, 1982a, 1982b) used probe tone ratings from Krumhansl and Shepard (1979) of how well a tone completes a scale and interpreted them as symmetric similarity scores between two pitch values. Similarly, Krumhansl's seminal research on pitch similarity (Krumhansl, 1979) employed specific musical sequences before the comparison tones, like a diatonic C major scale, potentially priming participants to the initial sequence tones, as noted by Shepard (1982b). Later studies relied on a similar priming approach, and further conflated similarity with melodic consonance by asking participants to rate the "pleasantness" and "harmony" of the tone combinations (Amano, 1993).

In summary, although the pitch helix has become a widely accepted concept in many perception textbooks, handbooks, and articles (e.g., Krumhansl, 2001; Plack et al., 2006; Wolfe et al., 2006; Goldstein, 2008; Trainor and Unrau, 2011; Plack, 2018), it is based on weak experimental evidence. Recent research on pitch perception following the

classic studies of Shepard (1982a) and Krumhansl (1979) largely studied in isolation the components of octave equivalence and pitch height representations, and did not address the question of global representations directly. In addition, the question of the degree that octave equivalence is contributing to pitch representations continues to be a source of heated debates. Finally, classic and more recent studies that directly probe the global structure of pitch representations often rely on unsuitable paradigms (conflating for example tonality) and separately addressing the issues of expertise and task dependency.

Our study addresses these limitations by revisiting the foundational question of the psychological reality of the pitch helix across tasks and experience groups. We do so by applying new methodologies from large-scale online experiments (Anglada-Tort et al., 2023; Marjieh, Jacoby, et al., 2024), enabling a fresh look at the global representation of musical pitch. Our approach, inspired by representational similarity analysis (RSA; Kriegeskorte et al., 2008), covers both production-based and evaluative paradigms. If the pitch helix truly serves as the fundamental representation of pitch, then we would expect it to be detectable across the various tasks and experience groups. Contrary to that, our findings reveal that the best geometrical approximations for the representation of pitch differ substantially across the different conditions, challenging the idea of a uniform pitch helix representation. Instead, they suggest that distinct perceptual factors influence task performance, which we identify and show that they explain the majority of the global structure in pitch similarity. These results help in shaping future computational models of pitch processing in the brain, and provide a more holistic view of how we represent pitch.

Results

To cover the different ways in which people process musical pitch, we considered three prominent behavioral paradigms (Figures 2A-C) that provide complementary forms of task engagement and applied them to both musician and non-musician participants. Crucially, we selected paradigms that allow for a similarity-based analysis as with MDS and RSA (Shepard, 1980; Kriegeskorte et al., 2008). In these approaches, behavioral data

Figure 2

*Probing pitch similarity across tasks and musical experience. Left panel: Schematics of the three paradigms **A.** similarity judgments over pairs of melodies that differ by a transposition, **B.** free imitation of two-note melodies through singing, and **C.** similarity judgments over pairs of isolated tones. Right panel (**D-F**): Corresponding normalized similarity profiles as a function of interval separations for the three behavioral paradigms and different participant groups (no musical experience, some musical experience, and musicians; see Methods). Shaded area, here and everywhere else, represents 95% confidence intervals bootstrapped over participants with 1,000 repetitions.*

such as direct similarity judgments, response distributions (e.g., confusion probabilities), or patterns of neural activation (Shepard, 1980; Kriegeskorte et al., 2008; Sucholutsky et al., 2023) are translated into similarity matrices that can be used to study the global organization of a representation of interest. Accordingly, our experiments covered tones that spanned multiple octaves which allowed us to elicit similarity matrices across a broad range. Our goal here is to deploy the similarity-based approach to characterize the global structure of musical pitch representations and to test to what extent the helical representation of pitch provides a consistent and unified account across tasks and experience groups. Participants were recruited online (see Participants) from two pools, Amazon Mechanical Turk (AMT) and an internal pool of professional musicians through the Max Planck Institute for Empirical Aesthetics (see Methods). Throughout, we divide the AMT participants into two categories based on their reported years of musical experience: those who reported zero years of musical experience ('No Musical Experience') and those who reported non-zero years of musical experience ('Some Musical Experience'), in addition to the professional musicians category ('Musicians'). All demographic information is provided in Supplementary Table A1.

In the first paradigm, we wanted to probe pitch representations in the context of melody perception, which is one of the most prominent contexts that involve musical pitch perception across cultures (Savage et al., 2015; Mehr et al., 2019). To that end, we expanded the version of the Demany and Armand (1984) task used by Jacoby et al. (2019) whereby people listened to pairs of randomly generated three-note melodies and rated their similarity on a Likert scale (Figure 2A; see Methods). Crucially, we generated the second melody from the first by applying a fixed transposition t to the second and third tones across a wide two-octave range. Since these melodies were randomized across trials, we expected the average rating to be able to track the interplay between pitch height (how separated are the tones on a log-scale) and chroma (whether tone chroma is identical in both melodies, i.e., at octave transpositions). Figure 2D shows substantial group

differences in the average profile as a function of the transposition interval (see Participants and Table A1 for all demographic and experience information). Participants with no musical experience ($N = 102$; "No Musical Experience" in Figure 2), exhibited a predominantly linear profile (linear model explains 93.8% of the variance of the average profile, CI: $[91.8, 95.8]$) with a small but significant bump at the first octave (12 semitones, CI of the mean rating difference between 12 and the average rating of 11 and 13 semitones is $[0.030, 0.084]$ which does not include zero), and musicians ($N = 41$) exhibiting a highly non-linear profile (linear model explains only 17.4% of the variance, CI: $[7.98, 26.9]$) that is more flattened with significant spikes at octave transpositions (12 and 24 semitones; CIs for mean rating difference for 12 and the average of 11 and 13, and 24 and 23 semitones were $[0.293, 0.406]$ and $[0.307, 0.440]$, respectively) suggesting octave equivalence and chroma sensitivity. Participants with some musical experience ($N = 92$; "Some Musical Experience"), on the other hand, exhibited a profile that is somewhere between those of the other two groups. Quantitatively, a linear model explained 86.0% of the variance of the average profile (CI: $[80.7, 91.3]$) and the CI of the mean difference in rating between 12 and the average of 11 and 13 semitones, and between 24 and 23 semitones were $[0.061, 0.131]$ and $[0.016, 0.088]$, respectively.

In order to provide a complementary perspective on pitch representations, we considered the paradigm of Jacoby et al. (2019) whereby people were asked to sing back two-note melodies that extended outside their singing range (Figure 2B; see Methods). This task provides an ecologically-valid form of musical engagement with pitch as singing is present in virtually every human culture (Savage et al., 2015; Mehr et al., 2019), and recent methodological advances enable it to be conducted online and at scale (Anglada-Tort et al., 2023). Moreover, singing also involves pitch production and as such complements the perceptual-evaluative task of melodic similarity presented above. Participants heard two-note melodies, with the first tone sampled from a frequency range of $45.5 - 105.5$ MIDI note corresponding to $113.2 - 3623.1$ Hz, and were asked to reproduce them by singing (the

participants' singing range is approximately $80 - 1000$ Hz). We specifically focused on how people approximated tones outside their singing range and constructed similarity scores between pitch values based on how similar their response distributions were (see Methods). This approach is consistent with prior multi-dimensional scaling analysis techniques whereby behavioral response distributions (e.g., confusion probabilities; Shepard, 1987) are used to construct similarity measures with the idea being that two stimuli are similar in so far as they produce the same behavioral response. This also enables us to analyze the production-based singing data using the same methodologies that we apply for the perceptual-evaluative similarity judgment paradigms. We estimated similarity scores between different target pitch values by computing the Jensen-Shannon distance (JSD) between their response distributions. This was done by first applying a two-dimensional kernel density estimation to target-response pitch pairs and then applying JSD between slices pertaining to pitch values of interest (see Methods; raw target-response distributions are provided in Supplementary Figure A1). Figure 2E shows the resulting average similarity profiles. Similar to the first paradigm, different experience groups exhibited qualitatively different profiles, with participants with no reported musical experience ($N = 50$; see Table A1 for full demographics) showing a linear similarity trend with weak residual periodicity at the octave (linear model explains 89.0% of the variance with CI $[78.6, 99.4]$, and a sinusoidal model with 12-semitone periodicity explains 7.4% of the variance with CI $[0.6, 14.3]$) and musicians ($N = 41$) exhibiting a highly periodic pattern with strong peaks at integer multiples of the octave (linear model explains 1.2% of the variance with CI $[0, 3.3]$ and a sinusoidal model with 12-semitone periodicity explains 92.7% of the variance with CI $[89.8, 95.6]$). Participant with some musical experience ($N = 49$) yielded a pattern that is in between the two other profiles (linear model explains 28.5% of the variance with CI $[0.2, 56.8]$ and a sinusoidal model with 12-semitone periodicity explains 61.0% of the variance with CI $[32.8, 89.3]$).

Finally, we returned to the classic approach of Shepard (1980) and asked

participants to directly rate the similarity between pairs of isolated tones with as little as possible additional context (Figure 2C; see Methods). We generated a high-powered similarity matrix by asking participants to rate pairs of harmonic complex tones taken from a two-octave range from C4 to C6. Figure 2F shows the average similarity rating as a function of the interval between the two tones. In this case, participants with zero reported years of musical experience ($N = 94$; additional details in Table A1) exhibited a nearly perfectly flat profile (linear model explains 90.8% of the variance with CI $[89.1, 92.6]$) with no significant peak at the octave: CI of the mean rating difference between 12 and the average rating of 11 and 13 semitones is $[-0.02, 0.042]$), and musicians ($N = 30$) on the other hand exhibiting a highly non-linear pattern (linear model explains 18.2% of the variance with CI $[1.4, 35.0]$) with spikes at the octaves (12 and 24 semitones; CIs of the mean difference in rating between 12 and average of 11 and 13 semitones, and between 24 and 23 semitones were $[0.421, 0.580]$ and $[0.240, 0.780]$, respectively) and sharp dips at the tritones (6 and 18 semitones; CIs of the mean difference in rating between 6 and average of 5 and 7 semitones, and between 18 and average of 17 and 19 semitones were $[-0.315, -0.155]$ and $[-0.276, -0.130]$, respectively) indicating strong octave equivalence but also strong tritone aversion and enhanced similarity at perfect intervals around it (i.e., 5, 7, 17 and 19 semitones). Participants with some musical experience ($N = 92$) capture the onset of the transition between the prior two groups (linear model explains 89.5% of the variance with CI $[85.6, 93.4]$) and a small but significant peak at the first octave (CI of mean difference between 12 and the average of 11 and 13 semitones was $[0.047, 0.148]$) and an onset of a dip at the first tritone (CI of mean difference between 6 and the average of 5 and 7 semitones was $[-0.058, -0.006]$), but not around 18 semitones (CI of mean difference between 18 and the average of 17 and 19 semitones was $[-0.063, 0.021]$).

The observed similarity marginals suggest strong task and experience dependencies. To see what representations could underlie those marginals and whether they are consistent with a unified pitch helix, we subjected them to three-dimensional MDS analysis (we

Figure 3

Multidimensional scaling solutions in three dimensions for the various similarity data
shown in Figure 2. Left to right: similarity judgments over melodies that differ by a
*transposition (**A-C**), free imitation of two-note melodies via singing (**D-F**), and similarity*
*judgments over pairs of isolated tones (**G-I**). Numbers and colors indicate pitch values in*
MIDI scale. Interactive 3D versions are available in the Supplementary Materials for all
MDS solutions shown in the present work.

selected three dimensions based on a stress curve analysis; see Supplementary Figure A2). This corresponds to averaging the raw similarity matrices over their diagonals (i.e., over equal semitonal separations; see Supplementary Figures A3-A4) and applying MDS (see Methods). The resulting MDS solutions, shown in Figure 3, exhibit a rich array of geometries, with the traditional helical representation appearing in only three out of the nine conditions considered (Figure 3D-F) and pertaining to the singing task (we confirmed in a simulation analysis that this is not an artifact of the singing paradigm and that it is perfectly capable of capturing other structures, see Supplementary Figure A5). In addition, MDS solutions for the raw unprocessed similarity matrices exhibit similar qualitative differences, though they are naturally noisier (Supplementary Figure A6). As with Figure 2, we see that with increased musical experience the derived representations become increasingly non-linear. In the melodic similarity case, participants with no musical experience yield a largely linear solution (Figure 3A), whereas musicians yield a solution characterized by octave-equivalent tone units (Figure 3C). Participants with some musical experience yield an intermediate non-linear solution (Figure 3B). As for the singing paradigm (Figure 3D-F), while all groups yield helical solutions, those solutions get increasingly tighter with experience, possibly reflecting an increasingly diminished pitch height dimension. Finally, for the isolated tone similarity paradigm, we also observe a structural transition as a function of experience whereby the linear approximation observed in the lower experience groups (Figure 3G-H) factorizes into a double helix in musicians (Figure 3I) to account for tritone aversion and heightened similarity at perfect intervals. Curiously, this recovers the 'double-helix wound around a line' structure hypothesized by Shepard (1982a, 1982b) as a candidate approximation for the structure of musical pitch. It differs, however, from the four dimensional double helix solution derived by using the probe tone data of Krumhansl and Shepard (1979) which is wound around a torus (the direct sum of the chroma circle and the circle of fifths; Figures 3 and 5 in Shepard, 1982a). Viewed together, these results provide clear evidence that a simple unified helical representation is

inadequate for capturing musical pitch perception across tasks and experience.

Computational Modeling

To tease apart the relative contributions of the perceptual factors underlying the similarity patterns observed above, we used a computational modeling approach inspired by an analysis initially proposed by Shepard (1982b) and adapted here to capture the different possible sources of variance observed in our data. Specifically, we determined which combination of factors best explained the empirical similarity matrices across the different conditions (see Methods). We did that by introducing a basis of geometric components $d_{ij}^{(c)}$ and estimating how the behavioral similarity s_{ij} loaded on these components by fitting a metric solution of the form $1 - s_{ij} = b + \sum_c a_c d_{ij}^{(c)}$ via linear regression where $b, a_c \geq 0$ are non-negative coefficients (Figure 4; see also Methods and Supplementary Figures A3 and A7). Based on the marginal analysis of Figure 2, we selected four component: a linear pitch height scale d_{ij}^l and three additional components that represent the identification of particular intervals, namely, a component d_{ij}^o that identifies octaves, a component d_{ij}^p that identifies perfect intervals (fourth and fifth), and a component d_{ij}^t that captures aversion to tritones. The octave component had an additional width hyperparameter σ_o that interpolated between sharp octave recognition and smoother chroma matching (see Methods for explicit formulae). Despite the simplicity of this model it provided excellent fit to the observed data with mean Pearson correlation of $r = .94$ (r values ranged between $.80 - .99$ depending on the experiment and were corrected for attenuation; see Methods for details regarding model evaluation; full list of correlations and other evaluation metrics is provided in Supplementary Table A3).

The resulting component weights for each of the paradigms considered are summarized in Figure 4 (the numerical values for all parameters can be found in Supplementary Table A2; enlarged insets are provided in Supplementary Figures A3 and A7). We see that these weights vary widely depending on experience and task. Starting from the melodic similarity paradigm (Figure 4A-C) we observe that most of the variability

Figure 4

Geometric component analysis of similarity. Fitted geometric coefficients to data from different musical experience groups and their associated raw (top) and model (bottom) similarity matrices shown as insets (enlarged insets are shown in Supplementary Figures A3 and A7; numerical values are provided in Supplementary Table A2). Error bars indicate 95% confidence intervals bootstrapped over participants with 1,000 repetitions.

is driven by the linear and octave components for all participant groups (Musicians: $r = .98$, 95% CI: [.98, .98]; Some Musical Experience: $r = .98$, 95% CI: [.97, .98]; No Experience: $r = .98$, 95% CI: [.98, .98]), however the octave component was significantly more dominant for musicians (Figure 4C; octave coefficient CI $[0.38, 0.48]$) compared with the lower experience groups (Figure 4A-B; octave coefficient CI $[0.13, 0.19]$, and $[0.06, 0.10]$ for participants with some musical experience, and no musical experience, respectively). Moreover, the relatively diminished linear component in musicians (Figure 4C; compare linear coefficient CI $[0.14, 0.28]$ vs. octave coefficient CI $[0.38, 0.48]$) as well as the narrow octave width ($\sigma_o = 0.51$) are suggestive of sharp octave recognition, whereby participants recognize the interval of an octave specifically as more similar without this enhanced similarity influencing other neighboring intervals (consistent with the flattened profile in Figure 2D).

Turning next to the singing paradigm (Figure 4D-F), we see an analogous pattern where the data is largely explained by the linear and octave components (Musicians: $r = .98$, 95% CI: [.98, .99]; Some Musical Experience: $r = .84$, 95% CI: [.80, .88]; No Musical Experience: $r = .80$, 95% CI: [.77, .83]). In particular, we see that the linear component in musicians is nearly absent relative to that of the octave (compare linear component CI $[0.01, 0.05]$ vs. octave component CI $[0.43, 0.53]$) which is suggestive of chroma matching. Unlike the previous paradigm, however, here we see that the optimal octave component width is much larger ($\sigma_o = 1.97$). Possible reasons for this result could be a perceptually broad representation (as a result of the higher task demands), and production noise. Interestingly, the reversal in the dominance of the linear and octave components in musicians relative to the participant group with no reported musical experience (Figure 4D) seems to happen also for the intermediate group with some musical experience (Figure 4E; linear component CI $[0.05, 0.11]$ vs. octave coefficient CI $[0.12, 0.24]$) which is not the case for the melodic similarity paradigm (Figure 4B; linear component CI $[0.50, 0.64]$ vs. octave component CI $[0.13, 0.19]$), suggesting that for

non-musicians pitch chroma is more salient in the singing task than in the melodic similarity task (even though the singing task is perfectly capable of detecting a linear representation; see simulation results in Supplementary Figure A5).

Finally, for the similarity over isolated tones paradigm (Figure 4G-I) we see a distinct pattern in which the lower experience groups (Figure 4G-H; No Musical Experience: $r = .96$, 95% CI: $[.96, .96]$; Some Musical Experience: $r = .97$, 95% CI: $[.96, .97]$) load almost exclusively on the linear component, while musicians ($r = .93$, 95% CI: $[.89, .97]$), on the other hand, exhibit a complex pattern in which all components contribute, in particular, tritone aversion (coefficient CI: $[0.11, 0.21]$) and enhanced similarity at perfect intervals (coefficient CI: $[0.01, 0.13]$), in addition to relatively balanced linear and octave components (linear coefficient CI: $[0.27, 0.53]$, octave coefficient CI: $[0.38, 0.54]$).

Discussion

Our results provide strong evidence for the conclusion that musical pitch perception cannot be adequately captured by a simple helical representation as is often depicted, exaggerating on the one hand the effect of octave equivalence in non-musicians, and missing, on the other, the implications of alternative sources of variance in the judgments of musicians, in particular, those pertaining to tritone aversion and preference towards perfect intervals. Moreover, our work highlights that the most suitable geometrical approximation may in fact be task dependent, reflecting a representation that is shaped by different psychological factors with variable degrees of salience. Surprisingly, we also found that octave equivalence was most salient across experience groups in the singing task, despite being the most demanding and prone to production noise.

Musical Pitch Perception is Composite and Task Dependent

Across all experiments, we found that four components explained most of the meaningful variance in pitch similarity (an average raw R^2 of .79 across datasets, and an average corrected Pearson correlation of $r = .94$). However, their relative importance

varied greatly between populations and tasks. Finding population and task dependency in pitch perception supports the idea that pitch is processed in higher-order brain areas (Nelken, 2011; Schnupp et al., 2011).

We found that a simple linear component dominated the responses of non-musicians, and also contributed to the responses of musicians (Figure 4). This is in line with the widely adopted definition of pitch by the American National Standards Institute (ANSI, 1960; "pitch is the auditory attribute of sound that allows sounds to be ordered on a scale from low to high") which emphasizes the linear nature of pitch. This is also consistent with Jacoby et al. (2019) who showed evidence that linear pitch perception is present in participants across cultures.

The other leading component we found was octave equivalence. Our findings support the idea that octave equivalence varies across participants and that the extent to which it is manifested is shaped by its salience in the task, supporting Jacoby et al. (2019), Pressnitzer and Demany (2019), and Regev et al. (2019). More specifically, we show quantitatively how the strength of octave equivalence varies with musical experience within the same task (Figure 4). Moreover, we found that the strength of the octave component relative to the linear component was particularly salient in the singing task. This is surprising as one would expect the singing task to yield noisy response patterns being a production-based task and more challenging. While we did find that participant responses were noisy (Supplementary Figure A1), they nevertheless showed the most clear octave equivalence compared with other tasks, even though the singing task is capable of capturing a linear representation (Supplementary Figure A5A-B). This underscores the importance of naturalistic paradigms when evaluating pitch perception.

Beyond these two components our results showed that musicians in the similarity judgment task over tones also relied on two other components, specifically "aversion" to tritones and preference for perfect intervals. What can explain this behavior? One idea is that musicians can identify musical intervals based on their ear training, and then report

what they think they are expected to report based on their explicit knowledge of Western music theory (Aldwell et al., 2018), or reflecting their internalized known distribution of melodic intervals in musical corpora (Vos & Troost, 1989; Zivic et al., 2013; Anglada-Tort et al., 2023). However, the fact that we observed task dependencies for all three experience groups, including groups with zero years of musical experience, suggest that the results could not be fully attributed to participants "rationalizing" about their expected responses. Another possibility is that other aspects of music perception may influence musicians' responses. For example, the phenomenon of melodic consonance, or the perceived pleasantness of tone sequences. Recent research suggests that Western participants (Anglada-Tort et al., 2023) exhibit a hierarchy of preferences when evaluating the pleasantness of two-tone melodies, with tones separated by an octave and perfect intervals being particularly pleasant, and those separated by a tritone being particularly unpleasant. This pattern overlaps to a certain extent also with that of harmonic consonance (the pleasantness of simultaneous tones; Trainor and Heinmiller, 1998; McDermott et al., 2010; Harrison and Pearce, 2020; Lahdelma and Eerola, 2020; Marjieh, Harrison, et al., 2024). Regardless of what strategy underlies the musicians' responses, our results undermines the validity of the unified pitch helix as a model of human behavior.

There are several ways in which our work is novel with respect to previous research. First, we provide a holistic test for the idea of the helical representation of pitch which is taken as a default model but in fact is based on weak empirical evidence. Second, our study explicitly introduces the dimension of task dependency by testing consistency across multiple tasks alongside multiple levels of expertise. This design extends previous research, which typically examined each of these dimensions (task dependency and expertise) in isolation. Third, we provide additional insights into the ongoing debate over octave equivalence and its prominence in pitch perception. Beyond the finding in Jacoby et al. (2019) which suggests that musical experience modulates perception of octave equivalence, we innovate in that we try to characterize the global perceptual structure underlying the

singing imitation task and comparing it to other paradigms.

Implications

If the pitch helix does not constitute a "psychological reality", an alternative possibility is that distinct elements such as octave equivalence and logarithmic frequency scaling are perceived and processed separately by the brain. When individuals make judgments—such as assessing the similarity between two tones—they weigh these different features in a task-specific manner. When performing another task, such as singing to reproduce a tone, they may adjust their weighting of available cues or features differently. Previous research shows that local pitch perception is task-dependent, and has leveraged this dependency to uncover distinct mechanisms for processing sounds into pitch. Indeed, by analogy to those psychoacoustic studies (Demany & Ramos, 2005; McPherson & McDermott, 2018), one may expect that the relative salience of different musical dimensions underlying the global organization of pitch percepts would be heavily modulated in different tasks, which is what we indeed found.

Our results carry implications for studying the neural correlates of pitch. Instead of a single representation in localized areas, we now expect pitch cues to be processed separately in lower and mid-level regions (Schulze et al., 2002; Bendor & Wang, 2005; Schnupp et al., 2011; Norman-Haignere et al., 2013; Feng & Wang, 2017), with integration only occurring at later stages of auditory processing (Nelken, 2011), akin to phoneme processing in speech (Mesgarani et al., 2014). Furthermore, our findings underscore the roles of statistical learning (Loui et al., 2010; Loui, 2012; Pearce, 2018), as the salience of these components strongly depends on musical expertise (Schön & François, 2011; Jacoby & Ahissar, 2013). Our results also highlight the capacity of brain plasticity to strongly modulate auditory perception, consistent with a large body of work that shows differences between musicians and non-musicians in auditory perception and production, as well as their neural correlates (Shepard, 1982a; Koelsch et al., 1999; Gaser & Schlaug, 2003; Zatorre et al., 2007; Dellacherie et al., 2011; François et al., 2013; Jacoby & Ahissar, 2013;

Merzenich et al., 2013).

Beyond neuroscience, our results are valuable for computational models of pitch perception. Predictive models of human behavior should consider both task dependency and expertise, as these are crucial for accurately capturing the nuances of pitch perception as demonstrated in the present work. Computational models that rely on mechanisms that cannot capture task and expertise dependencies should therefore be revised or excluded.

Limitations and Future Work

We end by discussing limitations which point to important directions for future research. First, our participant cohort is largely Western, particularly from the United States and Germany. This limits the generalizability of the present findings as elements of pitch perception such as octave equivalence and melodic preferences vary cross-culturally (Jacoby et al., 2019). A natural follow-up, therefore, could look at the way representations vary across cultures by applying the same methods deployed in this work which by design are suitable for cross-cultural research (similar to McDermott et al., 2016; Lahdelma and Eerola, 2020; McPherson et al., 2020; Jakubowski et al., 2022; Jacoby et al., 2024; Ozaki et al., 2024).

Second, in the present work we exclusively focused on population level analysis of representations, however, since musical experience is very subjective one might expect to see individual differences (McDermott et al., 2010) and use that to inform the relation between components beyond group differences. Since we sought to derive dense similarity matrices that spanned multiple octave ranges (which necessitate hundreds of judgments to cover once; e.g. covering all pairs in the octave range C4-C6 requires at least $25 \times 24/2 = 300$ without repetition) while ensuring that the online studies are not too long to maintain high data quality, we were unable to collect enough data per participant to enable individual-level geometric component analysis. Multi-session in-lab studies using the same paradigms of the present work may be a suitable follow up. This is particularly important, since splitting the data by musical expertise does show significant differences

even within the same paradigm, this indicates that individual variation is likely to play a significant role in the structure of pitch representations (Figures 2-4)

Third, previous work suggests that tonality may also be a shaping force in pitch perception (Krumhansl, 1979; Krumhansl & Shepard, 1979; Fogel et al., 2015). While our method tried to minimize carry-on effects of tonality from previous trials (by shifting tones randomly from trial to trial), it is possible that some sense of tonality can be induced even within a single trial, at least when it comes to expert musicians (Figure 4I).

Finally, there are other established paradigms for studying pitch representations that exist in the literature which we did not consider (e.g., Hoeschele et al., 2012) as they were not compatible with representational similarity analysis. Future work could explore alternative analytical approaches to examine these cases and assess if similar patterns emerge. We intend to pursue these directions in upcoming research.

To conclude, while pitch perception provides the fundamental backbone underlying both speech and music perception, it is neither simple nor static. Instead of a unified helical representation, our results reveal a highly complex and dynamical phenomenon that is likely to depend on multiple independent factors. More broadly, our work showcases how combining large-scale behavioral studies with diverse behavioral paradigms and computational modeling can provide new answers to fundamental questions in auditory research. We believe that scaling up psychological research in tandem with concurrent computational approaches will continue to provide exciting new hypotheses concerning the nature of human cognition.

Methods

Software Implementation

The behavioral paradigms were designed and deployed using PsyNet[1] (Harrison et al., 2020), a modern framework for complex experiment design which builds on the

―――――

[1] https://www.psynet.dev

Dallinger[2] platform for online experiment hosting and participant recruitment. Participants interact with the experiment in the browser using a front-end interface which, in turn, communicates with a back-end Python cluster that organizes the experiment timeline. All experiment and analysis code are available in the Supporting Information provided with this manuscript (see Code and Data Availability below).

Stimuli

We defined absolute pitch using the Musical Instrument Digital Interface (MIDI) semitonal scale which is based on a logarithmic pitch representation. This was motivated by previous research which showed that participants across cultures use approximately logarithmic pitch representations (Jacoby et al., 2019). Specifically, the MIDI scale was defined as follows: $f = 440 \times 2^{(p-69)/12}$ where f is frequency in Hertz and p is the corresponding pitch value. This means that a Concert A (A4 or 440 Hz) corresponds to a value of 69 on this scale. All experiments involved additively synthesized harmonic complex tones $s(t) = \sum_{i=0}^{n_H-1} w_i \sin(2\pi f_i t)$ with $n_H = 10$ harmonics, where $f_i = f_0 \times (i+1)$ for some fundamental frequency f_0, $w_i = 10^{-\omega_i/20}$, $\omega_i = \rho \log_2(i+1)$ and a roll-off parameter, ρ, which parametrically represents the timbre of the sound by controlling the prominence of high harmonics. The tones were synthesized using Tone.js[3], a Javascript library for audio synthesis in the browser. Each tone had a temporal envelope comprising of a linear attack portion, an exponential decay portion to some sustain amplitude, and a final exponential release portion. These were specified based on the constraints of each paradigm (see below).

Similarity Paradigms. The similarity judgment paradigms used a roll-off parameter ρ of 3 dB/octave. In the similarity between tones paradigm, the envelope comprised a 200 ms linear attack segment reaching an amplitude of 1, followed by a short 100 ms exponential decay to an amplitude of 0.8, and finally an exponential release segment lasting for 1 second. The two tones within a given pair were separated by 300 ms

---

[2] https://dallinger.readthedocs.io/en/latest/

[3] https://tonejs.github.io/

of silence. In the case of melodies, the individual tones within melodies similarly had an envelope comprising of 200 ms linear attack followed by a short 100 ms decay to an amplitude of 0.8, and then an exponential release portion with the same decay rate as before. The release portion was played up to an inter-onset-interval of 650 ms in the first two tones (i.e. for 350 ms), and for 1 second in the last tone, followed by 200 ms of silence. This choice of parameters was intended to ensure that the presentation of melodies was brief and well-separated (so as not to interact with memory and to allow participants to experience a range of melodic pairs within a single experiment).

In the similarity judgment paradigm over melodies, random melodies were synthesized by first uniformly sampling a starting tone in the MIDI range 76-80, and then generating the second and third tones by subtracting a uniformly sampled integer interval in the range $5 - 7$ and $9 - 11$ semitones, respectively. This means that the resulting melodies could have a variety of melodic intervals per transposition so that pre-existing musical expectations would not prime the perception of the transposition interval. Transpositions were then generated by subtracting a fixed integer interval in the range $0 - 24$ semitones from the second and third tones. As for the similarity judgment paradigm over tones, tones covered the MIDI range $60 - 84$ corresponding to the notes C4-C6.

Singing Paradigm. In the singing task, the pitch range, timbre, and temporal envelope of the tones, can all influence the difficulty of singing back melodies. We thus adapted sound parameters that were extensively tested in a previous online singing study (Anglada-Tort et al., 2023) and used the following values: a roll-off parameter ρ of 14 dB/octave, a 10 ms attack, a 50 ms decay to an amplitude of 0.6, followed by a 550 ms release portion and 190 ms of silence (i.e., 800 ms inter-onset-interval between tones). Two-note melodies were produced based on the design of Jacoby et al. (2019) (Experiment 4) by sampling the first tone from the range of $45.5 - 105.5$, and then creating the second tone by adding one of the intervals 0, ±1, ±2, or ±3 semitones. To further assist singers in their responses we applied a method proposed in Jacoby et al., 2019, where each

experiment consisted of a series of "blocks" presented in random order, each of which presented stimuli within a single frequency register (i.e., by sampling the first tone uniformly from the range $[p_0 - 6, p_0 + 6]$ where $p_0 = 51.5, 63.5, 75.5, 87.5, 99.5$).

Participants

Participants were recruited online from two participant pools: Amazon Mechanical Turk (AMT), and an internal pool of professional musicians through the Max Planck Institute for Empirical Aesthetics. To cover different experience levels, we divided the AMT participants into two subcategories based on whether they reported zero years of musical experience ('No Musical Experience') or some years of musical experience ('Some Musical Experience'), in addition to the musicians ('Musicians'). The division of the AMT population also aligns with a median-split based on reported years of musical experience. Participants reported years of musical experience by responding to the query: 'Have you ever played a musical instrument? If yes, for how many years did you play?'. Demographic information for all participant groups is summarized in Supplementary Table A1. Additional recruitment details are provided below.

AMT Participants. Participants on AMT were subject to the following recruitment criteria designed to ensure data quality: 1) participants must be 18 years of age or more, 2) they must reside in the United States, 3) they have a 99% approval rate or higher on prior AMT tasks, and 4) have successfully completed 5,000 tasks on AMT (a common threshold in large scale AMT studies; e.g., Hardy et al., 2023). These participants provided informed consent under a Princeton University Institutional Review Board (IRB) protocol (application 10859) in the similarity tasks and a Max Planck Ethics Council protocol (application 2021_42) in the singing task, and were paid a fair wage of 12 USD per hour.

Musicians. The musician cohort was recruited through an internal online participant pool at the Max Planck Institute for Empirical Aesthetics (MPIEA). Participants were recruited to this pool by researchers and research assistants at MPIEA

by sending emails to local and international music conservatories, as well as handing flyers at local music conservatories in Germany. The pool is diverse and comprises the following countries: Germany, Spain, Italy, Malaysia, France, Hungary, United Kingdom, Switzerland, Australia, Peru, Indonesia, Argentina, Croatia, Hong Kong, Lebanon, Chile, and Serbia. In order to participate, musicians were required to be at least 18 years of age and to have at least 10 years of active musical training. Participants provided consent under a Max Planck Ethics Council protocol (application 2021_42) and were paid at a rate of 15 USD per hour. Participant took the experiment remotely, and the web-interface was identical to the one used by the AMT participants. We excluded three participants in melodic similarity, two in singing, and two in tone similarity who reported less than 10 years of musical experience. We also note that the number of musicians varied between the similarity paradigms due to the nature of online recruitment whereby participants had the freedom to select which experiments they wanted to complete from a list of available studies.

Pre-screening

  Similarity Paradigms. To enhance online data quality, in the similarity tasks participants were required to complete a headphone prescreening test (Woods et al., 2017) to ensure that they were wearing headphones. In each trial of this test, participants heard a series of three tones and were asked to judge which of these was the quietest. The tones were designed to induce a phase cancellation effect when played on speakers which would lead participants without headphones to answer incorrectly. Participants who failed the headphone test were not allowed to proceed to the main experiment but were nevertheless fully compensated for the time taken to perform the pre-screening test.

  Singing Paradigm. As with the similarity tasks, participants in the singing paradigm first completed a headphone prescreening test. This was then followed by an additional recording test which was adapted from Anglada-Tort et al. (2023) and proceeded as follows. First, participants performed a microphone check to ensure that their

audio was detectable. Specifically, a pop up window was triggered asking participants to allow audio recording in the browser. Participants could not proceed without enabling their microphone. Once allowed, participants were instructed to freely sing into their microphone and check that an audio meter (provided on the page) indicated an appropriate sound level (volume). Next, participants were asked to sing two notes of their choice to the syllable 'TA' which were then played back to the participant so that they can double check that their microphone is appropriately set up. At this point, participants completed two practice trials in which they were instructed to imitate two two-note melodies ('In this task, we want to measure how well you can imitate a melody. In the next few trials you can practice performing the task, before we measure your performance in the main experiment. You will hear a melody with 2 notes, and after it ends, you'll be asked to sing these two notes back as accurately as possible. Note: Use the syllable TA to sing each note and leave a silent gap between notes. We will provide feedback after each trial'). After each trial participants were informed of the number of notes that were detected (see Singing Transcription Technology below). Importantly, this step did not provide feedback on the singing pitch to avoid biasing the participants. Finally, participants proceeded to a test phase where they had to complete 10 additional singing imitation trials without feedback ('We will now test your singing performance in a total of 10 trials. Like before, your goal is to listen to each melody, and after it ends, sing these two notes back as accurately as possible. Note: Use the syllable TA to sing each note and leave a silent gap between notes'). Participants recruited through AMT were allowed to proceed only if they were able to satisfy the following three criteria on at least 5 of the 10 trials: (i) They sung exactly two notes, (ii) the absolute interval error between the target and sung melodies was no larger than 3 semitones, and (iii) the direction of the target and sung melodies was the same (i.e. ascending vs. descending). These criteria were adapted from Anglada-Tort et al. (2023) and intended to ensure that AMT participants were making an honest effort to imitate the melodies. Musicians also performed this pre-screener, however, we set their

passing threshold to 0 (meaning that everyone passed) as their recruitment was more controlled. Nonetheless, in a post-hoc analysis we confirmed that only one musician marginally failed the test (by achieving a score of 4) whom we excluded. Finally, we note that the two-note melodies were taken from the same set as that devised by Anglada-Tort et al. (2023), and comprised the melodic intervals -2.6, -1.3, 0.0, 1.3, and 2.6, played at two registers (i.e. bass tones), 49 semitones (low) and 61 semitones (high), with uniform roving width of 2.5 semitones. The fractional intervals and roving were applied so that no specific sense of tonality is induced (Jacoby et al., 2019).

Performance Incentives

To motivate online participants to provide honest responses for the otherwise subjective tasks, participants in the similarity paradigms were informed that they could receive a performance bonus depending on the quality of their responses. Specifically, they received the following instructions: "The quality of your responses will be automatically monitored, and you will receive a bonus at the end of the experiment in proportion to your quality score. The best way to achieve a high score is to concentrate and give each trial your best attempt". While the tasks are subjective in nature, we used self-consistency as a measure of performance quality. This was done by repeating 5 random trials at the end of the experiment and then computing Spearman correlation between the original and repeated answers. The resulting score s was then used to compute a small bonus of up to 10 cents using the formula $\min(\max(0, 0.1s), 0.1)$.

Procedure

Similarity Paradigms. In the similarity over melodies task, the experiment proceeded as follows: upon completing the consent form participants received the following instructions: "In this experiment we are studying how people perceive melodies. In each round you will be presented with two three-note melodies and your task will be to simply judge how similar they are. You will have seven response options, ranging from 0 ('Completely Dissimilar') to 6 ('Completely Similar'). Choose the one you think is most

appropriate. You will also have access to a replay button that will allow you to replay the sounds if needed. Note: no prior expertise is required to complete this task, just choose what you intuitively think is the right answer". Participants then completed two practice trials and then proceeded to the main experiment. The procedure for the similarity over isolated tones task was identical, except that we replaced "melodies" in the instructions with "sounds". Participants completed up to 80 trials.

Singing Paradigm. After providing informed consent and completing the pre-screening trials (see Pre-screening) participants received the following instructions: 'In this final part of the experiment, we will ask you to do exactly the same as in the previous part. 1. You will hear a 2 note melody. 2. You will have to sing back the 2 notes. That means, in total you will sing 2 notes. The difference is that this time there will be a total of 38 trials. For all notes, use the syllable TA to sing the note and leave a silent gap between notes. Note: some of the tones you'll hear will be high, and well above your singing range. You should, however, sing them within your comfortable singing range.' The latter note was intended to ensure that participants were not surprised by the high tones (consistent with Jacoby et al. (2019); see Session Structure in that paper), as well as to ensure that they imitated the melodies within their natural singing range for compatibility with the pitch transcription technology of Anglada-Tort et al. (2023) that we employed (see Singing Transcription Technology below). Participants then completed the trials which corresponded to the randomized trial blocks (see Stimuli) in addition to three repeat trials (i.e. repeating three random trials from the original 35). The trials were presented in one continuous stream without any additional indications. In a given trial, participants received the following instructions: "This melody has 2 notes. Sing back the melody. Use the syllable TA". The recording interface comprised of a temporal meter (see Supplementary Figure A9) indicating the three recording stages. The initial portion, indicated in orange, signaled the listening portion ("Listen to the melody..."). Then, a second portion, indicated in red, signaled that the recording was in progress ("Recording...SING THE MELODY!").

This portion lasted for the duration of the original melody plus one second. Finally, a third portion, highlighted in green, indicated that recording was complete ("Done!"), and lasted for 500 ms. The next trial then started automatically, and so on.

Singing Transcription Technology

We relied on the singing transcription technology[4] of Anglada-Tort et al. (2023) for extracting the fundamental frequencies (f_0) of the participants' sung notes. This technology has been extensively tested and was shown to provide reliable f_0 estimates in online settings (Anglada-Tort et al., 2023). The automated process comprises four steps: i) Cleaning the recorded audio from artifacts. This included removing the first 100 ms of a recording, applying a 150 ms linear fade-in, and applying a band-pass filter with cut-off frequencies 80-6000 Hz to remove any non-singing spectral components. ii) Applying a pitch estimation method based on auto-correlation (Boersma et al., 1993) for extracting f_0 from sung segments, implemented using parselmouth (Jadoul et al., 2018). We used the recommended parameters (Anglada-Tort et al., 2023) of 65 Hz (36 semitones, C2) for pitch floor and 622 Hz for pitch ceiling (75 semitones, D#5). iii) Segmenting the continuous f_0 signal into individual isolated tones. This was done by extracting the envelope of the audio signal (by computing the maximum of the squared amplitude within non-overlapping 40 ms windows and then taking the square root) and applying a peak detection algorithm (Duarte & Watanabe, 2015) to find areas of vocal activity that are separated by silences (defined as envelope values that are less than -30 dB relative to the first peak within a segment and extending for at least 30 ms). iv) Filtering the list of audio segments using a set of heuristics to remove any spurious audio segments. This included removing segments that are shorter than 40 ms, removing segments with large deviations from the median f_0, i.e., segments that deviate from the median by at least 8 semitones for more than 35% of the duration the segment which could happen when the singer's voice "cracks", as well as removing any segments with median f_0 that falls outside the 65 - 622 Hz range of the

---

[4] https://gitlab.com/computational-audition/sing4me

auto-correlation step). Finally, the remaining segments were summarized into single pitch values by computing the median f_0 (full details of the approach can be found in Anglada-Tort et al. (2023) under Method Details).

To ensure that the parameters of the singing transcription technology did not bias or constrain the response distributions, we compared our results to the in-lab data of Jacoby et al. (2019). The data are reproduced in Supplementary Figure A10 alongside ours. We see that the online and in-lab data are highly consistent, both in terms of the response range (95% CI of response pitch values for the in-lab data was $[44, 76]$ semitones for non-musicians, and $[45, 72]$ semitones for musicians, both of which are highly overlapping with our design range of $[36, 75]$ semitones), as well as the resulting similarity matrices shown in Supplementary Figure A11 ($r = .93$, $p < 0.001$ for non-musicians, and $r = .95$, $p < 0.001$ for musicians; see Data Analysis for details regarding computing the similarity matrices).

Data Analysis

Constructing Similarity Matrices. To generate an aggregate similarity matrix from the direct similarity judgment paradigms, we applied the following procedures. In the case of similarity over isolated tone pairs, we simply computed the average Likert score per pair of items and divided by a constant of 6 so that similarity scores would be normalized between 0 and 1 (rather than 0 and 6). As for similarity over melodies, since the data is one-dimensional in that case (a pitch transposition t between random melodies) we constructed a two-dimensional matrix a_{ij} from the one-dimensional data s_t using the formula $a_{ij} = s_{|p_i - p_j|}$ where p_i and p_j are pitch values of interest. We again divided by a factor of 6 so that similarity scores would be normalized between 0 and 1. As for the singing data, the procedure is slightly more complicated and is described below. To produce the smoothed raw matrices we averaged the similarity matrices over their diagonal values, i.e. $s_{ij}^{smooth} = \bar{s}_{|i-j|}$ where $\bar{s}_{|i-j|}$ is the average over the $|i - j|$-th off-diagonal of s_{ij} (0 being the main diagonal).

Singing Response Distributions. To construct similarity matrices based on the response distributions of human singers, we first applied a 2D Gaussian kernel density estimate (KDE) $\rho(p_t, p_r)$ to the target-response pitch pairs (p_t, p_r) (we used the first tone in each target melody as the second tone is not independent) using the `KernelDensity` method of the `scikit-learn`[5] Python package with a bandwidth parameter of $\sigma = 1.1$ semitones and a resolution of 500×500 bins. We used this bandwidth as it provided a good tradeoff between reliability and resolution as determined by a five-fold cross validation analysis using the `GridSearchCV` method of `scikit-learn`. Dissimilarity between two target pitches p_{t_1} and p_{t_2} was then computed by applying the Jensen-Shannon distance `jensenshannon` from the `scipy`[6] package to the KDE marginals $\rho(p_r|p_{t_1})$ and $\rho(p_r|p_{t_2})$. To ensure that this approach is sufficiently flexible to capture different meaningful structures we applied it to different simulated response distributions that capture various modes of behavior. Specifically, we used a similar target pitch distribution as in the online experiments and simulated different response pitch values including (i) a noisy linear response, (ii) a noisy linear response with register saturation, (iii) a mixture of linear response with some probability of singing an octave above or below the target pitch, (iv) a mixture of linear response with some chance of singing one or more fifths above or below the target pitch, and (v) chroma matching within a given register. We then applied an identical processing procedure as in the behavioral experiments to produce similarity matrices which we then subjected to MDS. The results are shown in Supplementary Figure A5 and we found that the approach is indeed able to capture a variety of qualitatively different structures. Simulation code and 3D visualizations of the simulated solutions are provided in the OSF repository.

Multi-dimensional Scaling. We constructed MDS embeddings using the `MDS` method of `scikit-learn`. This was done in two steps, first we applied a metric MDS to

---

[5] https://scikit-learn.org/stable/

[6] https://scipy.org/

find an initial embedding which was then fed as an initialization into a non-metric MDS. We used three components, a maximum iteration value of 10,000, and a tolerance parameter of 1e-100. We chose three dimensional embeddings based on a stress curve analysis (Supplementary Figure A2) and selected the smallest number of dimensions for which all stress values across all conditions dropped below 0.15 (MDS fit is deemed poor above this threshold; Kruskal, 1964). This ensured that all structures are represented adequately within the same unified presentation (since lower dimensional structures can always be represented in higher dimensions but not vice versa). Finally, we note that all MDS solutions presented in this work are also available as 3D interactive HTML visualizations available through the OSF repository and the supplementary materials (see Code and Data Availability).

Geometric Components. The explicit formulae for the different geometric components were: a linear pitch scale $d_{ij}^{(l)} \propto |p_i - p_j|$, two positive interval recognition components $d_{ij}^{(c)} = 1 - \exp\left(-(\chi(p_i, p_j) - c)^2/2\sigma_c^2\right)$ where $\chi(p_i, p_j) = \min\{\psi_{ij}, 6 - \psi_{ij}\}$ and $\psi_{ij} = |p_i - p_j| \mod 12$ to capture chroma distance (i.e., intervallic distance irrespective of register) and $c = 0, 5$ for octave $(d_{ij}^{(o)})$ and perfect intervals (fourth and fifth; $d_{ij}^{(p)}$), respectively, and one negative recognition component $d_{ij}^{(c)} = \exp\left(-(\chi(p_i, p_j) - c)^2/2\sigma_c^2\right)$ with $c = 6$ to capture tritone aversion $(d_{ij}^{(t)})$. We fixed $\sigma_c = 0.25$ semitones for the tritone and perfect intervals as a narrow interval recognition threshold and optimized the octave width σ_o as a hyperparameter since different values of σ_o efficiently interpolate between sharp octave recognition and smooth distance on the chroma circle (since $c = 0$). As a sanity check for the chosen width parameter values, we refitted the model in the musician tone similarity condition (Figure 4F, the only condition in which the tritone and perfect intervals had substantial contributions) but this time allowing all width parameters to vary. We found that the optimal width parameters did not differ much from our chosen values $(\sigma_o = 0.39, \sigma_t = 0.17$ and $\sigma_p = 0.57)$. In addition, to ensure that the coefficients are properly normalized (i.e., each geometric component varied between 0 to 1), we rescaled the

linear component such that its largest separation on a given range of interest equals to one (e.g. if pitch differences varied between 0 and 24 semitones, we defined $d_{ij}^{(l)} = |p_i - p_j|/24$).

Model Fitting and Evaluation. We fitted geometric components to the data using the `LinearRegression` method of `scikit-learn`. This was done by first flattening the upper triangular part of each component's distance matrix $d_{ij}^{(c)}$ into a feature vector $v_i^{(c)}$ and then fitting a linear regression of the form $1 - s_i = b + \sum_c a_c v_i^{(c)}$ where $b, a_c \geq 0$ are non-negative coefficients and s_i is the flattened upper-triangular matrix of the behavioral similarity data. We repeated this fitting process 1,000 times by bootstrapping over participants in a split-half fashion (i.e., generating random half-splits of the data based on participants and then fitting the model to one half and testing on the other). The optimal octave width hyperparameter σ_o was fine-tuned using the blackbox optimizer `scipy.optimize.minimize` over the bootstrapped linear regression procedure described above. To quantify model performance, we computed three Pearson correlation coefficients for each of the 1,000 split-halves as follows: r_{dd} the correlation between the corresponding human similarity matrices of each split, r_{dm} the correlation between the model fit on one half with the human similarity of the other (there are two ways to compute this so we took the mean), and r_{mm} the correlation between the fitted models on each half. We then used these values to compute the corrected correlation for attenuation $r = r_{md}/\sqrt{r_{dd}r_{mm}}$.

Code and Data Availability. Data and code used in this work can be accessed via the link: https://osf.io/nx586/?view_only=a0f74c9269a4448f821aadccf76ba175.

Author Contributions. All authors contributed to the design of the experiments. Author RM implemented the experiments, analyzed the results, and drafted the initial manuscript. All authors collaborated on editing and revising the manuscript.

Competing Interests. The authors declare no competing interests.

Acknowledgements. This work was supported by grant 61454 from the John Templeton Foundation.

References

Ruckmick, C. (1929). A new classification of tonal qualities. *Psychological Review*, *36*(2), 172.

Humphreys, L. G. (1939). Generalization as a function of method of reinforcement. *Journal of Experimental Psychology*, *25*(4), 361.

d'Arezzo, G. (1955). Micrologus. ed. *Joseph Smits van Waesberghe. Rome: American Institute of Musicology.*

ANSI. (1960). Acoustical terminology si. *1-1960, American Standards Association.*

Von Békésy, G. (1960). Experiments in hearing.

Kruskal, J. B. (1964). Multidimensional scaling by optimizing goodness of fit to a nonmetric hypothesis. *Psychometrika*, *29*(1), 1–27.

Shepard, R. (1964). Circularity in judgments of relative pitch. *The journal of the acoustical society of America*, *36*(12), 2346–2353.

Allen, D. (1967). Octave discriminability of musical and non-musical subjects. *Psychonomic Science*, *7*(12), 421–422.

Plomp, R. (1967). Pitch of complex tones. *The Journal of the Acoustical Society of America*, *41*(6), 1526–1533.

Rose, J. E., Brugge, J. F., Anderson, D. J., & Hind, J. E. (1967). Phase-locked response to low-frequency tones in single auditory nerve fibers of the squirrel monkey. *Journal of neurophysiology*, *30*(4), 769–793.

Attneave, F., & Olson, R. K. (1971). Pitch as a medium: A new approach to psychophysical scaling. *The American journal of psychology*, 147–166.

Deutsch, D. (1973). Octave generalization of specific interference effects in memory for tonal pitch. *Perception & Psychophysics*, *13*(2), 271–275.

Moore, B. C. (1973). Frequency difference limens for short-duration tones. *The Journal of the Acoustical Society of America*, *54*(3), 610–619.

Patterson, R. D. (1976). Auditory filter shapes derived with noise stimuli. *The Journal of the Acoustical Society of America*, *59*(3), 640–654.

Idson, W. L., & Massaro, D. W. (1978). A bidimensional model of pitch in the recognition of melodies. *Perception & Psychophysics*, *24*(6), 551–565.

Shepard, R. (1978). The circumplex and related topological manifolds in the study of perception. *Theory construction and data analysis in the behavioral sciences*, 29–80.

Kallman, H. J., & Massaro, D. W. (1979). Tone chroma is functional in melody recognition. *Perception & Psychophysics*, *26*, 32–36.

Krumhansl, C. L. (1979). The psychological representation of musical pitch in a tonal context. *Cognitive psychology*, *11*(3), 346–374.

Krumhansl, C. L., & Shepard, R. (1979). Quantification of the hierarchy of tonal functions within a diatonic context. *Journal of experimental psychology: Human Perception and Performance*, *5*(4), 579.

Shepard, R. (1980). Multidimensional scaling, tree-fitting, and clustering. *Science*, *210*(4468), 390–398.

Cuddy, L. L., Cohen, A. J., & Mewhort, D. (1981). Perception of structure in short melodic sequences. *Journal of Experimental Psychology: Human Perception and Performance*, *7*(4), 869.

Kallman, H. J. (1982). Octave equivalence as measured by similarity ratings. *Perception & Psychophysics*, *32*(1), 37–49.

Krumhansl, C. L., & Kessler, E. J. (1982). Tracing the dynamic changes in perceived tonal organization in a spatial representation of musical keys. *Psychological review*, *89*(4), 334.

Shepard, R. (1982a). Geometrical approximations to the structure of musical pitch. *Psychological review*, *89*(4), 305.

Shepard, R. (1982b). Structural representations of musical pitch. In D. Deutsch (Ed.), *Psychology of music* (pp. 343–390). Academic Press.

Demany, L., & Armand, F. (1984). The perceptual reality of tone chroma in early infancy. *The journal of the Acoustical Society of America*, *76*(1), 57–66.

Shamma, S. A. (1985). Speech processing in the auditory system ii: Lateral inhibition and the central processing of speech evoked activity in the auditory nerve. *The Journal of the Acoustical Society of America*, *78*(5), 1622–1632.

Shepard, R. (1987). Toward a universal law of generalization for psychological science. *Science*, *237*(4820), 1317–1323.

Vos, P. G., & Troost, J. M. (1989). Ascending and descending melodic intervals: Statistical findings and their perceptual relevance. *Music Perception*, *6*(4), 383–396.

Dowling, W. J. (1990). Expectancy and attention in melody perception. *Psychomusicology: A Journal of Research in Music Cognition*, *9*(2), 148.

Amano, S. (1993). Perception of tonal and microtonal structure over octaves. *Japanese Psychological Research*, *34*(3), 89–95.

Boersma, P., et al. (1993). Accurate short-term analysis of the fundamental frequency and the harmonics-to-noise ratio of a sampled sound. *Proceedings of the institute of phonetic sciences*, *17*(1193), 97–110.

Shackleton, T. M., & Carlyon, R. P. (1994). The role of resolved and unresolved harmonics in pitch perception and frequency modulation discrimination. *The Journal of the Acoustical Society of America*, *95*(6), 3529–3540.

Zatorre, R. J., Evans, A. C., & Meyer, E. (1994). Neural mechanisms underlying melodic perception and memory for pitch. *Journal of neuroscience*, *14*(4), 1908–1919.

Trainor, L. J., & Heinmiller, B. M. (1998). The development of evaluative responses to music:: Infants prefer to listen to consonance over dissonance. *Infant Behavior and Development*, *21*(1), 77–88.

Koelsch, S., Schröger, E., & Tervaniemi, M. (1999). Superior pre-attentive auditory processing in musicians. *Neuroreport*, *10*(6), 1309–1313.

Drabkin, W. (2001). Octave (i). https://doi.org/10.1093/gmo/9781561592630.article.50054

Kishon-Rabin, L., Amir, O., Vexler, Y., & Zaltz, Y. (2001). Pitch discrimination: Are professional musicians better than non-musicians? *Journal of basic and clinical physiology and pharmacology, 12*(2), 125–144.

Krumhansl, C. L. (2001). *Cognitive foundations of musical pitch* (Vol. 17). Oxford University Press.

Winter, I. M., Wiegrebe, L., & Patterson, R. D. (2001). The temporal representation of the delay of iterated rippled noise in the ventral cochlear nucleus of the guinea-pig. *The Journal of physiology, 537*(Pt 2), 553.

Patterson, R. D., Uppenkamp, S., Johnsrude, I. S., & Griffiths, T. D. (2002). The processing of temporal pitch and melody information in auditory cortex. *Neuron, 36*(4), 767–776.

Schulze, H., Neubauer, H., Ohl, F. W., Hess, A., & Scheich, H. (2002). Representation of stimulus periodicity and its learning induced plasticity in the auditory cortex: Recent findings and new perspectives. *Acta Acustica united with Acustica, 88*(3), 399–407.

Gaser, C., & Schlaug, G. (2003). Brain structures differ between musicians and non-musicians. *Journal of neuroscience, 23*(27), 9240–9245.

Patel, A. D. (2003). Language, music, syntax and the brain. *Nature neuroscience, 6*(7), 674–681.

Fujioka, T., Trainor, L. J., Ross, B., Kakigi, R., & Pantev, C. (2004). Musical training enhances automatic encoding of melodic contour and interval structure. *Journal of cognitive neuroscience, 16*(6), 1010–1021.

Bendor, D., & Wang, X. (2005). The neuronal representation of pitch in primate auditory cortex. *Nature, 436*(7054), 1161–1165.

Demany, L., & Ramos, C. (2005). On the binding of successive sounds: Perceiving shifts in nonperceived pitches. *The Journal of the Acoustical Society of America, 117*(2), 833–841.

Koelsch, S., & Siebel, W. A. (2005). Towards a neural basis of music perception. *Trends in cognitive sciences*, *9*(12), 578–584.

Peretz, I., & Zatorre, R. J. (2005). Brain organization for music processing. *Annu. Rev. Psychol.*, *56*, 89–114.

Plack, C. J., & Oxenham, A. J. (2005). The psychophysics of pitch. In *Pitch: Neural coding and perception* (pp. 7–55). Springer.

Levitin, D. J. (2006). *This is your brain on music: The science of a human obsession.* Penguin.

Micheyl, C., Delhommeau, K., Perrot, X., & Oxenham, A. J. (2006). Influence of musical and psychoacoustical training on pitch discrimination. *Hearing research*, *219*(1-2), 36–47.

Plack, C. J., Oxenham, A. J., & Fay, R. R. (2006). *Pitch: Neural coding and perception* (Vol. 24). Springer Science & Business Media.

Tymoczko, D. (2006). The geometry of musical chords. *Science*, *313*(5783), 72–74.

Wolfe, J. M., Kluender, K. R., Levi, D. M., Bartoshuk, L. M., Herz, R. S., Klatzky, R. L., Lederman, S. J., & Merfeld, D. M. (2006). *Sensation & perception.* Sinauer Sunderland, MA.

Wong, P. C., Skoe, E., Russo, N. M., Dees, T., & Kraus, N. (2007). Musical experience shapes human brainstem encoding of linguistic pitch patterns. *Nature neuroscience*, *10*(4), 420–422.

Zatorre, R. J., Chen, J. L., & Penhune, V. B. (2007). When the brain plays music: Auditory–motor interactions in music perception and production. *Nature reviews neuroscience*, *8*(7), 547–558.

Goldstein, E. B. (2008). *Blackwell handbook of sensation and perception.* John Wiley & Sons.

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, *2*, 249.

McDermott, J. H., & Oxenham, A. J. (2008). Music perception, pitch, and the auditory system. *Current opinion in neurobiology*, *18*(4), 452–463.

Temperley, D. (2008). A probabilistic model of melody perception. *Cognitive Science*, *32*(2), 418–444.

Hall, D. A., & Plack, C. J. (2009). Pitch processing sites in the human auditory brain. *Cerebral cortex*, *19*(3), 576–585.

Cedolin, L., & Delgutte, B. (2010). Spatiotemporal representation of the pitch of harmonic complex tones in the auditory nerve. *Journal of Neuroscience*, *30*(38), 12712–12724.

de Cheveigné, A. (2010). Pitch perception alain de cheveigné. *The oxford handbook of auditory science: Hearing*, *3*, 71.

Loui, P., Wessel, D. L., & Kam, C. L. H. (2010). Humans rapidly learn grammatical structure in a new musical scale. *Music perception*, *27*(5), 377–388.

McDermott, J. H., Lehr, A. J., & Oxenham, A. J. (2010). Individual differences reveal the basis of consonance. *Current Biology*, *20*(11), 1035–1041.

Patel, A. D. (2010). *Music, language, and the brain.* Oxford university press.

Trainor, L. J., & Corrigall, K. A. (2010). Music acquisition and effects of musical experience. *Music perception*, 89–127.

Bentsen, T., Harte, J. M., & Dau, T. (2011). Human cochlear tuning estimates from stimulus-frequency otoacoustic emissions. *The Journal of the Acoustical Society of America*, *129*(6), 3797–3807.

Dellacherie, D., Roy, M., Hugueville, L., Peretz, I., & Samson, S. (2011). The effect of musical experience on emotional self-reports and psychophysiological responses to dissonance. *Psychophysiology*, *48*(3), 337–349.

Nelken, I. (2011). Music and the auditory brain: Where is the connection? *Frontiers in Human Neuroscience*, *5*, 106.

Schnupp, J., Nelken, I., & King, A. (2011). *Auditory neuroscience: Making sense of sound.* MIT press.

Schön, D., & François, C. (2011). Musical expertise and statistical learning of musical and linguistic structures. *Frontiers in psychology*, *2*, 167.

Trainor, L. J., & Unrau, A. (2011). Development of pitch and music perception. In *Human auditory development* (pp. 223–254). Springer.

Hoeschele, M., Weisman, R. G., & Sturdy, C. B. (2012). Pitch chroma discrimination, generalization, and transfer tests of octave equivalence in humans. *Attention, Perception, & Psychophysics*, *74*, 1742–1760.

Loui, P. (2012). Learning and liking of melody and harmony: Further studies in artificial grammar learning. *Topics in Cognitive Science*, *4*(4), 554–567.

Wong, P. C., Ciocca, V., Chan, A. H., Ha, L. Y., Tan, L.-H., & Peretz, I. (2012). Effects of culture on musical pitch perception. *PloS one*, *7*(4), e33424.

François, C., Chobert, J., Besson, M., & Schön, D. (2013). Music training for the development of speech segmentation. *Cerebral Cortex*, *23*(9), 2038–2043.

Hoeschele, M., Weisman, R. G., Guillette, L. M., Hahn, A. H., & Sturdy, C. B. (2013). Chickadees fail standardized operant tests for octave equivalence. *Animal cognition*, *16*, 599–609.

Jacoby, N., & Ahissar, M. (2013). What does it take to show that a cognitive training procedure is useful?: A critical evaluation. *Progress in brain research*, *207*, 121–140.

Merzenich, M., Nahum, M., & van Vleet, T. (2013). *Changing brains: Applying brain plasticity to advance and recover human ability.* Elsevier.

Norman-Haignere, S., Kanwisher, N., & McDermott, J. H. (2013). Cortical pitch regions in humans respond primarily to resolved harmonics and are located in specific

tonotopic regions of anterior auditory cortex. *Journal of Neuroscience*, *33*(50), 19451–19469.

Zivic, P. H. R., Shifres, F., & Cecchi, G. A. (2013). Perceptual basis of evolving western musical styles. *Proceedings of the National Academy of Sciences*, *110*(24), 10034–10038. https://doi.org/10.1073/pnas.1222336110

Mesgarani, N., Cheung, C., Johnson, K., & Chang, E. F. (2014). Phonetic feature encoding in human superior temporal gyrus. *Science*, *343*(6174), 1006–1010.

Weiss, A. H., Granot, R. Y., & Ahissar, M. (2014). The enigma of dyslexic musicians. *Neuropsychologia*, *54*, 28–40.

Duarte, M., & Watanabe, R. (2015). Notes on scientific computing for biomechanics and motor control (version v0. 0.2). zenodo.

Fogel, A. R., Rosenberg, J. C., Lehman, F. M., Kuperberg, G. R., & Patel, A. D. (2015). Studying musical and linguistic prediction in comparable ways: The melodic cloze probability method. *Frontiers in psychology*, *6*, 1718.

Savage, P. E., Brown, S., Sakai, E., & Currie, T. E. (2015). Statistical universals reveal the structures and functions of human music. *Proceedings of the National Academy of Sciences*, *112*(29), 8987–8992.

McDermott, J. H., Schultz, A. F., Undurraga, E. A., & Godoy, R. A. (2016). Indifference to dissonance in native amazonians reveals cultural variation in music perception. *Nature*, *535*(7613), 547–550.

Milne, A. J., & Holland, S. (2016). Empirically testing tonnetz, voice-leading, and spectral models of perceived triadic distance. *Journal of Mathematics and Music*, *10*(1), 59–85.

Feng, L., & Wang, X. (2017). Harmonic template neurons in primate auditory cortex underlying complex sound processing. *Proceedings of the National Academy of Sciences*, *114*(5), E840–E848.

Lau, B. K., Mehta, A. H., & Oxenham, A. J. (2017). Superoptimal perceptual integration suggests a place-based representation of pitch at high frequencies. *Journal of Neuroscience*, *37*(37), 9013–9021.

Woods, K. J., Siegel, M. H., Traer, J., & McDermott, J. H. (2017). Headphone screening to facilitate web-based auditory experiments. *Attention, Perception, & Psychophysics*, *79*(7), 2064–2072.

Aldwell, E., Schachter, C., & Cadwallader, A. (2018). *Harmony and voice leading*. Cengage Learning.

Jadoul, Y., Thompson, B., & De Boer, B. (2018). Introducing parselmouth: A python interface to praat. *Journal of Phonetics*, *71*, 1–15.

McPherson, M. J., & McDermott, J. H. (2018). Diversity in pitch perception revealed by task dependence. *Nature human behaviour*, *2*(1), 52–66.

Oxenham, A. J. (2018). How we hear: The perception and neural coding of sound. *Annual review of psychology*, *69*(1), 27–50.

Pearce, M. T. (2018). Statistical learning and probabilistic prediction in music cognition: Mechanisms of stylistic enculturation. *Annals of the New York Academy of Sciences*, *1423*(1), 378–395.

Plack, C. J. (2018). *The sense of hearing*. Routledge.

Cheung, V. K., Harrison, P. M., Meyer, L., Pearce, M. T., Haynes, J.-D., & Koelsch, S. (2019). Uncertainty and surprise jointly predict musical pleasure and amygdala, hippocampus, and auditory cortex activity. *Current Biology*, *29*(23), 4084–4092.

Jacoby, N., Undurraga, E. A., McPherson, M. J., Valdés, J., Ossandón, T., & McDermott, J. H. (2019). Universal and non-universal features of musical pitch perception revealed by singing. *Current Biology*, *29*(19), 3229–3243.

Kuroyanagi, J., Sato, S., Ho, M.-J., Chiba, G., Six, J., Pfordresher, P., Tierney, A., Fujii, S., & Savage, P. E. (2019). Automatic comparison of human music, speech, and bird song suggests uniqueness of human scales.

Mehr, S. A., Singh, M., Knox, D., Ketter, D. M., Pickens-Jones, D., Atwood, S., Lucas, C.,
Jacoby, N., Egner, A. A., Hopkins, E. J., et al. (2019). Universality and diversity in
human song. *Science*, *366*(6468), eaax0868.

Pressnitzer, D., & Demany, L. (2019). Auditory perception: Relative universals for musical
pitch. *Current Biology*, *29*(19), R927–R929.

Regev, T. I., Nelken, I., & Deouell, L. Y. (2019). Evidence for linear but not helical
automatic representation of pitch in the human auditory system. *Journal of
cognitive neuroscience*, *31*(5), 669–685.

Harrison, P., Marjieh, R., Adolfi, F., van Rijn, P., Anglada-Tort, M., Tchernichovski, O.,
Larrouy-Maestri, P., & Jacoby, N. (2020). Gibbs sampling with people. *Advances in
Neural Information Processing Systems*, *33*, 10659–10671.

Harrison, P., & Pearce, M. T. (2020). Simultaneous consonance in music perception and
composition. *Psychological Review*, *127*(2), 216.

Lahdelma, I., & Eerola, T. (2020). Cultural familiarity and musical expertise impact the
pleasantness of consonance/dissonance but not its perceived tension. *Scientific
reports*, *10*(1), 8693.

McPherson, M. J., Dolan, S. E., Durango, A., Ossandon, T., Valdés, J., Undurraga, E. A.,
Jacoby, N., Godoy, R. A., & McDermott, J. H. (2020). Perceptual fusion of musical
notes by native amazonians suggests universal representations of musical intervals.
Nature communications, *11*(1), 2786.

Jakubowski, K., Polak, R., Rocamora, M., Jure, L., & Jacoby, N. (2022). Aesthetics of
musical timing: Culture and expertise affect preferences for isochrony but not
synchrony. *Cognition*, *227*, 105205.

Wagner, B., Sturdy, C. B., Weisman, R. G., & Hoeschele, M. (2022). Pitch chroma
information is processed in addition to pitch height information with more than two
pitch-range categories. *Attention, Perception, & Psychophysics*, *84*(5), 1757–1771.

Anglada-Tort, M., Harrison, P. M., Lee, H., & Jacoby, N. (2023). Large-scale iterated
        singing experiments reveal oral transmission mechanisms underlying music
        evolution. *Current Biology.*

Hardy, M. D., Thompson, B. D., Krafft, P., & Griffiths, T. L. (2023). Resampling reduces
        bias amplification in experimental social networks. *Nature Human Behaviour*, *7*(12),
        2084–2098.

Liu, J., Hilton, C. B., Bergelson, E., & Mehr, S. A. (2023). Language experience predicts
        music processing in a half-million speakers of fifty-four languages. *Current Biology*,
        33(10), 1916–1925.

Sucholutsky, I., Muttenthaler, L., Weller, A., Peng, A., Bobu, A., Kim, B., Love, B. C.,
        Grant, E., Groen, I., Achterberg, J., et al. (2023). Getting aligned on
        representational alignment. *arXiv preprint arXiv:2310.13018.*

Wagner, B., Šlipogor, V., Oh, J., Varga, M., & Hoeschele, M. (2023). A comparison
        between common marmosets (callithrix jacchus) and human infants sheds light on
        traits proposed to be at the root of human octave equivalence. *Developmental
        Science*, *26*(5), e13395.

Jacoby, N., Polak, R., Grahn, J. A., Cameron, D. J., Lee, K. M., Godoy, R.,
        Undurraga, E. A., Huanca, T., Thalwitzer, T., Doumbia, N., et al. (2024).
        Commonality and variation in mental representations of music revealed by a
        cross-cultural comparison of rhythm priors in 15 countries. *Nature Human
        Behaviour*, 1–32.

Marjieh, R., Harrison, P. M., Lee, H., Deligiannaki, F., & Jacoby, N. (2024). Timbral
        effects on consonance disentangle psychoacoustic mechanisms and suggest
        perceptual origins for musical scales. *Nature Communications*, *15*(1), 1482.

Marjieh, R., Jacoby, N., Peterson, J. C., & Griffiths, T. L. (2024). The universal law of
        generalization holds for naturalistic stimuli. *Journal of Experimental Psychology:
        General*, *153*(3), 573.

Marjieh, R., Sucholutsky, I., van Rijn, P., Jacoby, N., & Griffiths, T. L. (2024). Large language models predict human sensory judgments across six modalities. *Scientific Reports*, *14*(1), 21445.

Ozaki, Y., Tierney, A., Pfordresher, P. Q., McBride, J. M., Benetos, E., Proutskova, P., Chiba, G., Liu, F., Jacoby, N., Purdy, S. C., et al. (2024). Globally, songs and instrumental melodies are slower and higher and use more stable pitches than speech: A registered report. *Science advances*, *10*(20), eadm9797.

Wagner, B., Toro, J. M., Mayayo, F., & Hoeschele, M. (2024). Do rats (rattus norvegicus) perceive octave equivalence, a critical human cross-cultural aspect of pitch perception? *Royal Society Open Science*, *11*(5), 221181.

Zatorre, R. J. (2024). *From perception to pleasure: The neuroscience of music and why we love it*. Oxford University Press.

Appendix

Supporting Information

Table A1

Demographics of the lower and upper experience non-musician subgroups, as well as the musician groups.

Task	Group	N	N_m	N_f	N_o	M_{age}	SD_{age}	M_{yme}	SD_{yme}	*Range*
Similarity (Mel.)	No Exp.	102	66	36	0	39.8	11.6	0	0	$0-0$
Similarity (Mel.)	Some Exp.	92	54	37	1	41.0	12.8	7.3	8.9	$0.5-53$
Similarity (Mel.)	Musicians	41	19	15	7	30.0	8.3	19.9	7.9	$11-41$
Singing	No Exp.	50	30	20	0	42.5	11.0	0	0	$0-0$
Singing	Some Exp.	49	30	19	0	43.8	11.3	7.6	9.8	$0.5-55$
Singing	Musicians	42	15	26	1	31.9	10.3	21.2	9.4	$12-46$
Similarity (Ton.)	No Exp.	94	57	37	0	40.9	10.4	0	0	$0-0$
Similarity (Ton.)	Some Exp.	92	52	39	1	39.5	10.1	5.7	6.0	$1-34$
Similarity (Ton.)	Musicians	30	14	10	6	32.4	10.6	22.2	9.6	$12-46$

Note: The measures are: N total number of participants. N_m, N_f, N_o number of participants that self-identified as male, female, and other, respectively. M_{age}, SD_{age} mean and standard deviation of age. M_{yme}, SD_{yme}, *Range* mean, standard deviation and range of reported years of musical experience. 'Similarity (Mel.)' and 'Similarity (Ton.)' correspond to similarity over melodies and isolated tones, respectively.

Figure A1

Pitch imitation through singing. Target vs. response pitch distributions for musicians and non-musicians (using a Guassian kernel with $\sigma = 1.1$ semitones determined through 5-fold cross validation; density normalized relative to a uniform distribution).

Figure A2

Normalized stress curves as a function of embedding dimensions as applied to the different

similarity matrices in Supplementary Figure A4. Dashed red line indicates the 0.15

threshold above which MDS fit is deemed poor (Kruskal, 1964). Based on this analysis, we

selected three-dimensional MDS for presenting the results in the paper.

Figure A3

Raw similarity matrices for the different behavioral paradigms considered in the paper.

Figure A4

Smoothed similarity matrices by averaging the raw matrices in Figure A3 over their diagonals for the different behavioral paradigms considered in the paper.

Figure A5

Simulated singing responses and their corresponding similarity matrices and MDS solutions.
A. Noisy linear response. B. Noisy linear response with register saturation. C. Singing an
octave above or below a tone. D. Imitating along the circle of fifths. E. Chroma matching.

Figure A6

Three-dimensional multidimensional scaling solutions for the raw unprocessed behavioral similarity matrices in Supplementary Figure A3. Left to right: similarity judgments over melodies that differ by a transposition, free imitation of two-note melodies via singing, and similarity judgments over pairs of isolated tones.

Figure A7

Fitted model similarity matrices for the different behavioral paradigms considered.

Table A2

Full list of model parameter values and their 95% confidence intervals.

Task	Group	Intercept	Linear	Octave	Tritone	Perfect	σ_o
Similarity (Mel.)	No Exp.	0.12 ± 0.03	0.69 ± 0.06	0.08 ± 0.02	0.01 ± 0.01	0.01 ± 0.01	0.63
Similarity (Mel.)	Some Exp.	0.12 ± 0.03	0.57 ± 0.07	0.16 ± 0.03	0.02 ± 0.02	0.01 ± 0.01	0.64
Similarity (Mel.)	Musicians	0.07 ± 0.05	0.21 ± 0.07	0.43 ± 0.05	0.00 ± 0.00	0.03 ± 0.02	0.51
Singing	No Exp.	0.16 ± 0.02	0.17 ± 0.05	0.08 ± 0.04	0.00 ± 0.00	0.00 ± 0.00	2.33
Singing	Some Exp.	0.17 ± 0.02	0.08 ± 0.03	0.18 ± 0.06	0.00 ± 0.00	0.00 ± 0.00	2.21
Singing	Musicians	0.19 ± 0.01	0.03 ± 0.02	0.48 ± 0.05	0.01 ± 0.00	0.00 ± 0.00	1.97
Similarity (Ton.)	No Exp.	0.12 ± 0.03	1.04 ± 0.05	0.00 ± 0.00	0.00 ± 0.00	0.01 ± 0.01	0.25
Similarity (Ton.)	Some Exp.	0.10 ± 0.05	0.96 ± 0.06	0.04 ± 0.04	0.00 ± 0.01	0.03 ± 0.02	0.21
Similarity (Ton.)	Musicians	-0.04 ± 0.11	0.40 ± 0.13	0.46 ± 0.08	0.16 ± 0.05	0.07 ± 0.06	0.37

Table A3

Full list of evaluation metrics and their 95% confidence intervals using split-half bootstrap over participants with 1,000 repetitions.

Task	Group	R^2	r_{dd}	r_{mm}	r_{dm}	r
Similarity (Mel.)	No Exp.	$.95 \pm .01$	$.99 \pm .00$	$.99 \pm .00$	$.97 \pm .00$	$.98 \pm .00$
Similarity (Mel.)	Some Exp.	$.95 \pm .02$	$.99 \pm .01$	$.99 \pm .01$	$.97 \pm .01$	$.98 \pm .00$
Similarity (Mel.)	Musicians	$.94 \pm .02$	$.97 \pm .03$	$.99 \pm .02$	$.96 \pm .02$	$.98 \pm .00$
Singing	No Exp.	$.54 \pm .12$	$.83 \pm .07$	$.98 \pm .05$	$.72 \pm .04$	$.80 \pm .03$
Singing	Some Exp.	$.53 \pm .13$	$.73 \pm .11$	$.96 \pm .10$	$.70 \pm .07$	$.84 \pm .04$
Singing	Musicians	$.92 \pm .03$	$.95 \pm .02$	$.99 \pm .00$	$.96 \pm .01$	$.99 \pm .00$
Similarity (Ton.)	No Exp.	$.89 \pm .01$	$0.96 \pm .01$	$1.00 \pm .00$	$.94 \pm .00$	$.96 \pm .00$
Similarity (Ton.)	Some Exp.	$.88 \pm .02$	$.94 \pm .01$	$.99 \pm .00$	$.93 \pm .00$	$.97 \pm .00$
Similarity (Ton.)	Musicians	$.48 \pm .10$	$.53 \pm .08$	$.96 \pm .07$	$.66 \pm .05$	$.93 \pm .04$

Note: The measures are: R^2 coefficient of determination, r_{dd} data-data Pearson correlation, r_{mm} model-model, Pearson correlation, r_{dm} data-model Pearson correlation, and r data-model correlation corrected for attenuation (see Methods for full details).

Figure A8

Three-dimensional multidimensional scaling solutions for the fitted model similarity matrices. Left to right: similarity judgments over melodies that differ by a transposition, free imitation of two-note melodies via singing, and similarity judgments over pairs of isolated tones.

Figure A9

Recording interface for the online singing paradigm.

Figure A10

Comparing our online response pitch distributions to the in-lab response distributions of Jacoby et al. (2019) (using a Guassian kernel with $\sigma = 1.1$; density normalized relative to a uniform distribution).

Figure A11

Comparison between resulting similarity matrices based on our online data and the in-lab

data of Jacoby et al. (2019) shown in Supplementary Figure A10. The results show high

consistency of the similarity matrices between our online data and the in-lab data (r = .93,

p < 0.001 for non-musicians, and r = .95, p < 0.001 for musicians)