Pitch is Not (Always) a Helix: Probing the Structure of Musical Pitch Across Tasks and Experience

Raja Marjieh[1], Thomas L. Griffiths[1,2,†], and Nori Jacoby[3,4,†]

[1]Department of Psychology, Princeton University, USA

[3]Department of Computer Science, Princeton University, USA

[3]Max Planck Institute for Empirical Aesthetics, Germany

[4]Department of Psychology, Cornell University, USA

[†]Equal Contribution.

Author Note

Corresponding author: Raja Marjieh. E-mail: `raja.marjieh@princeton.edu`.

Abstract

Pitch perception is at the core of our experience of both speech and music, and understanding the appropriate representation of musical pitch has intrigued scholars for centuries. The pitch helix, which jointly represents the logarithmic scaling of the periodicity of tones and the heightened similarity between tones separated by an octave, or octave equivalence, is often presented in textbooks as the underlying representation of pitch. However, prior research suggests that the representation of pitch is influenced by task context and musical expertise, although the evidence derives from disparate studies that are small-scale and sometimes contradictory. Here we systematically investigate how the representation of pitch varies across musical expertise levels and task demands. Drawing inspiration from representational similarity analysis in neuroscience, we revisit this problem through a series of nine experiments involving participants with varied levels of musical expertise ($N = 592$) and paradigms covering both perception and production. We show that, depending on task and musical experience, the best geometrical approximation to the representation of pitch can exhibit an array of structures ranging from linear to double-helical structures, providing strong evidence that a simple helical representation cannot explain the data. Surprisingly, we also found that octave equivalence was strongest in the singing task despite being the most challenging due to production noise. These results suggest a broader, more nuanced understanding of how we perceive pitch.

Keywords: pitch perception, representations, octave equivalence, singing

Pitch is Not (Always) a Helix: Probing the Structure of Musical Pitch

Across Tasks and Experience

Pitch is one of the most extensively studied psychological phenomena due to its crucial role in both music and speech perception (Attneave & Olson, 1971; Koelsch & Siebel, 2005; Peretz & Zatorre, 2005; Levitin, 2006; Plack et al., 2006; Zatorre et al., 2007; McDermott & Oxenham, 2008; Patel, 2010; Wong et al., 2012; McPherson & McDermott, 2018; Oxenham, 2018; Jacoby et al., 2019). Research on pitch typically focuses on two complementary major questions. The first major question concerns the computational and neural processes underlying the local transformation from a given sound sensation to pitch perception (Plack et al., 2006; McDermott & Oxenham, 2008; Oxenham, 2018). In this area, researchers have explored the integration of various cues (Von Békésy, 1960; Rose et al., 1967; Patterson, 1976; Shamma, 1985; Cedolin & Delgutte, 2010; Bentsen et al., 2011), including resolved and unresolved harmonics (Plomp, 1967; Shackleton & Carlyon, 1994; Lau et al., 2017). Moreover, empirical studies have investigated the neural correlates of pitch processing (Schulze et al., 2002; Bendor & Wang, 2005; Schnupp et al., 2011; Norman-Haignere et al., 2013; Feng & Wang, 2017), while computational modeling has provided insights into the biological mechanisms involved in this transformation (de Cheveigné, 2010).

The second major question concerns how individual pitches are combined to form larger perceptual structures, such as pitch contours in speech perception, which convey prosodic information, or lexical distinctions in tone languages. In music, individual pitches are organized into scales that reference tonal centers (Krumhansl & Kessler, 1982; Fogel et al., 2015), ultimately creating melodies (Cuddy et al., 1981; Dowling, 1990; Temperley, 2008; Anglada-Tort et al., 2023) and complete musical compositions (Zatorre et al., 1994; Cheung et al., 2019; Zatorre, 2024). Key to this question is understanding the underlying global representations that enable the formation of larger perceptual units from individual

Figure 1

The pitch helix and its underlying components, the pitch height line and the chroma circle. Numbers indicate semitonal pitch values relative to a generic base labeled as 0.

pitches (Shepard, 1982a, 1982b). These global representations, which organize the relationships between different pitch percepts, are crucial for both the neuroscience and psychology of music (Patel, 2003).

Perhaps the most well-known of these structures is the pitch helix (Figure 1; see also Supplementary Figure A12). This model, proposed by Shepard (Shepard, 1978, 1982a, 1982b; though see also Ruckmick, 1929) accounts for two key features of pitch in Western music. First, pitch is organized uniformly on a logarithmic scale (i.e., a log-linear line; Jacoby et al., 2019). Tones with slower periodicity are perceived as "low", while those with faster periodicity are perceived as "high" (ANSI, 1960). Additionally, Western music uses octave equivalence, where tones with periodicities differing by an octave (a 2:1 ratio) share the same note name, or chroma, and are treated as musically similar (Shepard, 1964; Deutsch, 1973; Kallman, 1982; Shepard, 1982a; Demany & Armand, 1984; Hoeschele et al., 2012; Hoeschele et al., 2013; Jacoby et al., 2019). The combination of these features—pitch height and octave equivalence—led to the hypothesis that musical pitch representations could be approximated by a helix (Shepard, 1982a). Since then, the pitch helix and its

sub-components have become a standard topic in many perception and music textbooks

(e.g., Krumhansl, 2001; Plack et al., 2006; Tymoczko, 2006; Wolfe et al., 2006; Goldstein,

2008; Plack, 2018), as well as modern research and review articles (e.g., Trainor and Unrau,

2011; Hoeschele et al., 2012; Milne and Holland, 2016; Jacoby et al., 2019; Marjieh,

Sucholutsky, et al., 2024).

Research has uncovered several findings that support the idea of pitch organization

from low to high. The ear itself performs frequency decomposition, with high frequencies

processed closer to the base of the cochlea (Von Békésy, 1960; Schnupp et al., 2011). This

tonotopic organization is maintained in both the midbrain and primary auditory cortex

(Winter et al., 2001; Patterson et al., 2002; Hall & Plack, 2009). Even non-experts are

capable of making low-high judgments with considerable accuracy (Plack & Oxenham,

2005), and pitch perception follows a roughly logarithmic scale across a broad frequency

range (Attneave & Olson, 1971; Moore, 1973; Jacoby et al., 2019). However, this mapping

is not entirely straightforward, as pitch perception is influenced by multiple cues (Schnupp

et al., 2011). Additionally, tonotopic regions including the auditory cortex do not respond

robustly in the same way to tones of the same pitch with different timbres (Winter et al.,

2001; Schulze et al., 2002; Hall & Plack, 2009) which indicates that they reflect lower-level,

frequency-related aspects of tones rather than a fully invariant pitch representation

(Nelken, 2011).

The findings on octave equivalence are more varied. Octave equivalence is

fundamental to Western music theory (d'Arezzo, 1955; Drabkin, 2001; Aldwell et al., 2018),

and octaves are common across songs from various cultures (Kuroyanagi et al., 2019; Mehr

et al., 2019). However, the literature yields a complex picture with respect to its

dependence on biological mechanisms, its prevalence among individuals with or without

musical training, and its dependence on tasks (Humphreys, 1939; Shepard, 1964; Deutsch,

1973; Idson & Massaro, 1978; Kallman & Massaro, 1979; Kallman, 1982). Deutsch (1972)

used a recognition paradigm to show that participants were able to reliably identify a

famous tune when transposed into any of three given octave registers. However, when each note in the tune was independently sampled from a different octave register, recognition was severely diminished suggesting that octave equivalence cues were weaker than contour cues. Kallman (1982) used a similarity rating method testing three musicians, finding that only one of the three demonstrated a significant increase in perceived similarity for tones separated by an octave. Later, Demany and Armand (1984) used a melodic similarity paradigm, finding octave equivalence in children but noting a weaker effect in adults. More recently, Jacoby et al. (2019) used a singing paradigm, showing that octave equivalence is culturally contingent (absent among the Tsimane', an indigenous Bolivian population) and varies within Western participants based on musical expertise. In contrast, Hoeschele and colleagues (Hoeschele et al., 2012; Hoeschele et al., 2013) used an operant conditioning test with humans and chickadees, finding that only humans exhibited octave equivalence (see also Wagner et al., 2022; Wagner et al., 2023; Wagner et al., 2024). However, the degree to which octave equivalence is based on biological mechanisms remains highly debated (Pressnitzer & Demany, 2019), with consensus proving difficult due to the diverse range of paradigms, participant groups, and analytical methods used across studies.

Research on the neural basis of octave equivalence yields a nuanced picture as well. For instance, Warren et al. (2003) used fMRI to suggest distinct representations for chroma (anterior to the primary auditory cortex) and pitch height (posterior to the primary auditory cortex). In contrast, Briley et al. (2013), using EEG, found that chroma representation emerges only for complex tones, while pure tones primarily evoke representations of pitch height. More recently, Regev et al. (2019) reached a similar conclusion using EEG signal for deviance detection, showing that octave equivalence was not automatically detected with pure tones, even by expert musicians.

As for the the psychological research that directly addresses the question of the pitch helix, and global pitch representations more broadly, it is surprising that it has largely relied on limited data and experimental designs. For instance, some studies that

collected direct similarity judgments between tone pairs relied on small musician groups and yielded conflicting results (e.g., Kallman (1982) found evidence for octave equivalence in only one out of the three musicians tested, whereas Allen (1967) detected octave equivalence in data from ten musicians). Some relied exclusively on participants with significant musical experience (Krumhansl, 1979) which limits generalizability in light of evidence that auditory and pitch perception may depend on individual experience (Koelsch et al., 1999; Kishon-Rabin et al., 2001; Gaser & Schlaug, 2003; Fujioka et al., 2004; Peretz & Zatorre, 2005; Micheyl et al., 2006; Wong et al., 2007; Zatorre et al., 2007; Trainor & Corrigall, 2010; Dellacherie et al., 2011; François et al., 2013; Jacoby & Ahissar, 2013; Merzenich et al., 2013; Weiss et al., 2014; Liu et al., 2023). Additionally, studies using Shepard tones display octave equivalence by design as Shepard tones are physically identical for pitches separated by an octave, making it hard to draw inferences about the structure of the underlying helical representation (Shepard, 1978, 1982a). Notably, multiple studies confounded pitch perception with tonality. This is problematic as it is less surprising to see expertise differences in tasks involving tonality, a more complex musical feature, compared to pitch. For example, Shepard's foundational work (Shepard, 1982a, 1982b) used probe tone ratings from Krumhansl and Shepard (1979) of how well a tone completes a scale and interpreted them as symmetric similarity scores between two pitch values. Similarly, Krumhansl's seminal research on pitch similarity (Krumhansl, 1979) employed specific musical sequences before the comparison tones, like a diatonic C major scale, potentially priming participants to the initial sequence tones, as noted by Shepard (1982b). Later studies relied on a similar priming approach, and further conflated similarity with melodic consonance by asking participants to rate the "pleasantness" and "harmony" of the tone combinations (Amano, 1993).

In summary, many perception textbooks, handbooks, and articles (e.g., Krumhansl, 2001; Plack et al., 2006; Wolfe et al., 2006; Goldstein, 2008; Trainor and Unrau, 2011; Plack, 2018), use the pitch helix for describing aspects of pitch perception. However,

evidence from multiple disparate studies suggests that pitch representations may be influenced by musical experience and task demands, which imply a more nuanced representation. In addition, previous psychological research that directly addresses the problem of the pitch helix suffers from various methodological limitations, including studying expertise and task separately, small sample sizes, and unsuitable paradigms that conflate factors such as tonality and consonance. These limitations provide a fragmented view of pitch representations.

Our study addresses these gaps by jointly assessing the representation of pitch across tasks and experience groups. In addition, we address previous methodological limitation by applying new techniques from large-scale online experiments (Anglada-Tort et al., 2023; Marjieh, Jacoby, et al., 2024), enabling a fresh look at the global representation of musical pitch. Our approach, inspired by representational similarity analysis (RSA; Kriegeskorte et al., 2008), covers both production-based and evaluative paradigms. If the pitch helix serves as a fundamental representation of pitch, then we would expect it to be detectable across the various tasks and experience groups. Contrary to that, our findings reveal that the best geometrical approximations for the representation of pitch differ substantially across the different conditions, challenging the idea of a uniform pitch helix representation. Instead, they suggest that distinct perceptual factors influence task performance, which we identify and show that they explain the majority of the global structure in pitch similarity. This is important because it further informs whether we can realistically expect to find robust neural correlates. It also helps in shaping future computational models of pitch processing, and provides a more holistic view of how we represent pitch that may nuance future depictions of pitch representations in scholarly resources.

Results

To cover the different ways in which people process musical pitch, we considered three prominent behavioral paradigms (Figures 2A-C) that provide complementary forms of task engagement and applied them to both musician and non-musician participants.

Figure 2

*Probing pitch similarity across tasks and musical experience. Left panel: Schematics of the three paradigms **A.** similarity judgments over pairs of melodies that differ by a transposition, **B.** free imitation of two-note melodies through singing, and **C.** similarity judgments over pairs of isolated tones. Right panel (**D-F**): Corresponding normalized similarity profiles as a function of interval separations for the three behavioral paradigms and different participant groups (no musical experience, some musical experience, and musicians; see Methods). Shaded area, here and everywhere else, represents 95% confidence intervals bootstrapped over participants with 1,000 repetitions.*

Crucially, we selected paradigms that allow for a similarity-based analysis as with MDS

and RSA (Shepard, 1980; Kriegeskorte et al., 2008). In these approaches, behavioral data

such as direct similarity judgments, response distributions (e.g., confusion probabilities), or

patterns of neural activation (Shepard, 1980; Kriegeskorte et al., 2008; Sucholutsky et al.,

2023) are translated into similarity matrices that can be used to study the global

organization of a representation of interest. Accordingly, our experiments covered tones

that spanned multiple octaves which allowed us to elicit similarity matrices across a broad

range. Our goal here is to deploy the similarity-based approach to characterize the global

structure of musical pitch representations and to test to what extent the helical

representation of pitch provides a consistent and unified account across tasks and

experience groups. Participants were recruited online (see Participants) from two pools,

Amazon Mechanical Turk (AMT) and an internal pool of professional musicians through

the Max Planck Institute for Empirical Aesthetics (see Methods). Throughout, we divide

the AMT participants into two categories based on their reported years of musical

experience: those who reported zero years of musical experience ('No Musical Experience')

and those who reported non-zero years of musical experience ('Some Musical Experience'),

in addition to the professional musicians category ('Musicians'). All demographic

information is provided in Supplementary Table A1.

In the first paradigm, we wanted to probe pitch representations in the context of

melody perception, which is one of the most prominent contexts that involve musical pitch

perception across cultures (Savage et al., 2015; Mehr et al., 2019). To that end, we

expanded the version of the Demany and Armand (1984) task used by Jacoby et al. (2019)

whereby people listened to pairs of randomly generated three-note melodies and rated their

similarity on a Likert scale (Figure 2A; see Methods). Crucially, we generated the second

melody from the first by applying a fixed transposition t to the second and third tones

across a wide two-octave range. Since these melodies were randomized across trials, we

expected the average rating to be able to track the interplay between pitch height (how

separated are the tones on a log-scale) and chroma (whether tone chroma is identical in

both melodies, i.e., at octave transpositions). Figure 2D shows substantial group

differences in the average profile as a function of the transposition interval (see Participants

and Table A1 for all demographic and experience information). Participants with no

musical experience ($N = 102$; "No Musical Experience" in Figure 2), exhibited a

predominantly linear profile (linear model explains 93.8% of the variance of the average

profile, CI: $[91.8, 95.8]$) with a small but significant bump at the first octave (12 semitones,

CI of the mean rating difference between 12 and the average rating of 11 and 13 semitones

is $[0.030, 0.084]$ which does not include zero), and musicians ($N = 41$) exhibiting a highly

non-linear profile (linear model explains only 17.4% of the variance, CI: $[7.98, 26.9]$) that is

more flattened with significant spikes at octave transpositions (12 and 24 semitones; CIs for

mean rating difference for 12 and the average of 11 and 13, and 24 and 23 semitones were

$[0.293, 0.406]$ and $[0.307, 0.440]$, respectively) suggesting octave equivalence and chroma

sensitivity. Participants with some musical experience ($N = 92$; "Some Musical

Experience"), on the other hand, exhibited a profile that is somewhere between those of

the other two groups. Quantitatively, a linear model explained 86.0% of the variance of the

average profile (CI: $[80.7, 91.3]$) and the CI of the mean difference in rating between 12 and

the average of 11 and 13 semitones, and between 24 and 23 semitones were $[0.061, 0.131]$

and $[0.016, 0.088]$, respectively.

In order to provide a complementary perspective on pitch representations, we

considered the paradigm of Jacoby et al. (2019) whereby people were asked to sing back

two-note melodies that extended outside their singing range (Figure 2B; see Methods).

This task provides an ecologically-valid form of musical engagement with pitch as singing is

present in virtually every human culture (Savage et al., 2015; Mehr et al., 2019), and recent

methodological advances enable it to be conducted online and at scale (Anglada-Tort et al.,

2023). Moreover, singing also involves pitch production and as such complements the

perceptual-evaluative task of melodic similarity presented above. Participants heard

two-note melodies, with the first tone sampled from a frequency range of $45.5 - 105.5$ MIDI note corresponding to $113.2 - 3623.1$ Hz, and were asked to reproduce them by singing (the participants' singing range is approximately $80 - 1000$ Hz). We specifically focused on how people approximated tones outside their singing range and constructed similarity scores between pitch values based on how similar their response distributions were (see Methods). This approach is consistent with prior multi-dimensional scaling analysis techniques whereby behavioral response distributions (e.g., confusion probabilities; Shepard, 1987) are used to construct similarity measures with the idea being that two stimuli are similar in so far as they produce the same behavioral response. This also enables us to analyze the production-based singing data using the same methodologies that we apply for the perceptual-evaluative similarity judgment paradigms. We estimated similarity scores between different target pitch values by computing the Jensen-Shannon distance (JSD) between their response distributions. This was done by first applying a two-dimensional kernel density estimation to target-response pitch pairs and then applying JSD between slices pertaining to pitch values of interest (see Methods; raw target-response distributions are provided in Supplementary Figure A1). Figure 2E shows the resulting average similarity profiles. Similar to the first paradigm, different experience groups exhibited qualitatively different profiles, with participants with no reported musical experience ($N = 50$; see Table A1 for full demographics) showing a linear similarity trend with weak residual periodicity at the octave (linear model explains 89.0% of the variance with CI $[78.6, 99.4]$, and a sinusoidal model with 12-semitone periodicity explains 7.4% of the variance with CI $[0.6, 14.3]$) and musicians ($N = 41$) exhibiting a highly periodic pattern with strong peaks at integer multiples of the octave (linear model explains 1.2% of the variance with CI $[0, 3.3]$ and a sinusoidal model with 12-semitone periodicity explains 92.7% of the variance with CI $[89.8, 95.6]$). Participants with some musical experience ($N = 49$) yielded a pattern that is in between the two other profiles (linear model explains 28.5% of the variance with CI $[0.2, 56.8]$ and a sinusoidal model with 12-semitone

periodicity explains 61.0% of the variance with CI [32.8, 89.3]).

Finally, we returned to the classic approach of Shepard (1980) and asked

participants to directly rate the similarity between pairs of isolated tones with as little as

possible additional context (Figure 2C; see Methods). We generated a high-powered

similarity matrix by asking participants to rate pairs of harmonic complex tones taken

from a two-octave range from C4 to C6. Figure 2F shows the average similarity rating as a

function of the interval between the two tones. In this case, participants with zero reported

years of musical experience ($N = 94$; additional details in Table A1) exhibited a nearly

perfectly flat profile (linear model explains 90.8% of the variance with CI [89.1, 92.6]) with

no significant peak at the octave: CI of the mean rating difference between 12 and the

average rating of 11 and 13 semitones is [−0.02, 0.042]), and musicians ($N = 30$) on the

other hand exhibiting a highly non-linear pattern (linear model explains 18.2% of the

variance with CI [1.4, 35.0]) with spikes at the octaves (12 and 24 semitones; CIs of the

mean difference in rating between 12 and average of 11 and 13 semitones, and between 24

and 23 semitones were [0.421, 0.580] and [0.240, 0.780], respectively) and sharp dips at the

tritones (6 and 18 semitones; CIs of the mean difference in rating between 6 and average of

5 and 7 semitones, and between 18 and average of 17 and 19 semitones were

[−0.315, −0.155] and [−0.276, −0.130], respectively) indicating strong octave equivalence

but also strong tritone aversion and enhanced similarity at perfect intervals around it (i.e.,

5, 7, 17 and 19 semitones). Participants with some musical experience ($N = 92$) capture

the onset of the transition between the prior two groups (linear model explains 89.5% of

the variance with CI [85.6, 93.4]) and a small but significant peak at the first octave (CI of

mean difference between 12 and the average of 11 and 13 semitones was [0.047, 0.148]) and

an onset of a dip at the first tritone (CI of mean difference between 6 and the average of 5

and 7 semitones was [−0.058, −0.006]), but not around 18 semitones (CI of mean difference

between 18 and the average of 17 and 19 semitones was [−0.063, 0.021]).

Figure 3

*Multidimensional scaling solutions in three dimensions for the various similarity data shown in Figure 2. Left to right: similarity judgments over melodies that differ by a transposition (**A-C**), free imitation of two-note melodies via singing (**D-F**), and similarity judgments over pairs of isolated tones (**G-I**). Numbers and colors indicate pitch values in MIDI scale. Interactive 3D versions are available in the Supplementary Materials for all MDS solutions shown in the present work.*

The observed similarity marginals suggest strong task and experience dependencies. To see what representations could underlie those marginals and whether they are consistent with a unified pitch helix, we subjected them to three-dimensional MDS analysis (we selected three dimensions based on a stress curve analysis; see Supplementary Figure A2). This corresponds to averaging the raw similarity matrices over their diagonals (i.e., over equal semitonal separations; see Supplementary Figures A3-A4) and applying MDS (see Methods). The resulting MDS solutions, shown in Figure 3, exhibit a rich array of geometries, with the traditional helical representation appearing in only three out of the nine conditions considered (Figure 3D-F) and pertaining to the singing task (we confirmed in a simulation analysis that this is not an artifact of the singing paradigm and that it is perfectly capable of capturing other structures, see Supplementary Figure A5). In addition, MDS solutions for the raw unprocessed similarity matrices exhibit similar qualitative differences, though they are naturally noisier (Supplementary Figure A6). As with Figure 2, we see that with increased musical experience the derived representations become increasingly non-linear. In the melodic similarity case, participants with no musical experience yield a largely linear solution (Figure 3A), whereas musicians yield a solution characterized by octave-equivalent tone units (Figure 3C). Participants with some musical experience yield an intermediate non-linear solution (Figure 3B). As for the singing paradigm (Figure 3D-F), while all groups yield helical solutions, those solutions get increasingly tighter with experience, possibly reflecting an increasingly diminished pitch height dimension. Finally, for the isolated tone similarity paradigm, we also observe a structural transition as a function of experience whereby the linear approximation observed in the lower experience groups (Figure 3G-H) factorizes into a double helix in musicians (Figure 3I) to account for tritone aversion and heightened similarity at perfect intervals. Curiously, this recovers the 'double-helix wound around a line' structure hypothesized by Shepard (1982a, 1982b) as a candidate approximation for the structure of musical pitch (Supplementary Figure A12B). It differs, however, from the four dimensional double helix

316 solution derived by using the probe tone data of Krumhansl and Shepard (1979) which is

317 wound around a torus (the direct sum of the chroma circle and the circle of fifths; Figures

318 3 and 5 in Shepard, 1982a; see also Supplementary Figure A12C). Viewed together, these

319 results provide clear evidence that a simple unified helical representation is inadequate for

320 capturing musical pitch perception across tasks and experience.

Computational Modeling

To tease apart the relative contributions of the perceptual factors underlying the

similarity patterns observed above, we used a computational modeling approach inspired

by an analysis initially proposed by Shepard (1982b) and adapted here to capture the

different possible sources of variance observed in our data. Specifically, we determined

which combination of factors best explained the empirical similarity matrices across the

different conditions (see Methods). We did that by introducing a basis of geometric

components $d_{ij}^{(c)}$ and estimating how the behavioral similarity s_{ij} loaded on these

components by fitting a metric solution of the form $1 - s_{ij} = b + \sum_c a_c d_{ij}^{(c)}$ via linear

regression where $b, a_c \geq 0$ are non-negative coefficients (Figure 4; see also Methods and

Supplementary Figures A3 and A7). Based on the marginal analysis of Figure 2, we

selected four component: a linear pitch height scale d_{ij}^l and three additional components

that represent the identification of particular intervals, namely, a component d_{ij}^o that

identifies octaves, a component d_{ij}^p that identifies perfect intervals (fourth and fifth), and a

component d_{ij}^t that captures aversion to tritones. The octave component had an additional

width hyperparameter σ_o that interpolated between sharp octave recognition and smoother

chroma matching (see Methods for explicit formulae). Despite the simplicity of this model

it provided excellent fit to the observed data with mean Pearson correlation of $r = .94$ (r

values ranged between $.80 - .99$ depending on the experiment and were corrected for

attenuation; see Methods for details regarding model evaluation; full list of correlations and

other evaluation metrics is provided in Supplementary Table A3).

The resulting component weights for each of the paradigms considered are

Figure 4

Geometric component analysis of similarity. Fitted geometric coefficients to data from different musical experience groups and their associated raw (top) and model (bottom) similarity matrices shown as insets (enlarged insets are shown in Supplementary Figures A3 and A7; numerical values are provided in Supplementary Table A2). Error bars indicate 95% confidence intervals bootstrapped over participants with 1,000 repetitions.

summarized in Figure 4 (the numerical values for all parameters can be found in

Supplementary Table A2; enlarged insets are provided in Supplementary Figures A3 and

A7). We see that these weights vary widely depending on experience and task. Starting

from the melodic similarity paradigm (Figure 4A-C) we observe that most of the variability

is driven by the linear and octave components for all participant groups (Musicians:

$r = .98$, 95% CI: [.98, .98]; Some Musical Experience: $r = .98$, 95% CI: [.97, .98]; No

Experience: $r = .98$, 95% CI: [.98, .98]), however the octave component was significantly

more dominant for musicians (Figure 4C; octave coefficient CI $[0.38, 0.48]$) compared with

the lower experience groups (Figure 4A-B; octave coefficient CI $[0.13, 0.19]$, and $[0.06, 0.10]$

for participants with some musical experience, and no musical experience, respectively).

Moreover, the relatively diminished linear component in musicians (Figure 4C; compare

linear coefficient CI $[0.14, 0.28]$ vs. octave coefficient CI $[0.38, 0.48]$) as well as the narrow

octave width ($\sigma_o = 0.51$) are suggestive of sharp octave recognition, whereby participants

recognize the interval of an octave specifically as more similar without this enhanced

similarity influencing other neighboring intervals (consistent with the flattened profile in

Figure 2D).

Turning next to the singing paradigm (Figure 4D-F), we see an analogous pattern

where the data are largely explained by the linear and octave components (Musicians:

$r = .98$, 95% CI: [.98, .99]; Some Musical Experience: $r = .84$, 95% CI: [.80, .88]; No

Musical Experience: $r = .80$, 95% CI: [.77, .83]). In particular, we see that the linear

component in musicians is nearly absent relative to that of the octave (compare linear

component CI $[0.01, 0.05]$ vs. octave component CI $[0.43, 0.53]$) which is suggestive of

chroma matching. Unlike the previous paradigm, however, here we see that the optimal

octave component width is much larger ($\sigma_o = 1.97$). Possible reasons for this result could

be a perceptually broad representation (as a result of the higher task demands), and

production noise. Interestingly, the reversal in the dominance of the linear and octave

components in musicians relative to the participant group with no reported musical

experience (Figure 4D) seems to happen also for the intermediate group with some musical experience (Figure 4E; linear component CI $[0.05, 0.11]$ vs. octave coefficient CI $[0.12, 0.24]$) which is not the case for the melodic similarity paradigm (Figure 4B; linear component CI $[0.50, 0.64]$ vs. octave component CI $[0.13, 0.19]$), suggesting that for non-musicians pitch chroma is more salient in the singing task than in the melodic similarity task (even though the singing task is perfectly capable of detecting a linear representation; see simulation results in Supplementary Figure A5).

Finally, for the similarity over isolated tones paradigm (Figure 4G-I) we see a distinct pattern in which the lower experience groups (Figure 4G-H; No Musical Experience: $r = .96$, 95% CI: $[.96, .96]$; Some Musical Experience: $r = .97$, 95% CI: $[.96, .97]$) load almost exclusively on the linear component, while musicians ($r = .93$, 95% CI: $[.89, .97]$), on the other hand, exhibit a complex pattern in which all components contribute, in particular, tritone aversion (coefficient CI: $[0.11, 0.21]$) and enhanced similarity at perfect intervals (coefficient CI: $[0.01, 0.13]$), in addition to relatively balanced linear and octave components (linear coefficient CI: $[0.27, 0.53]$, octave coefficient CI: $[0.38, 0.54]$).

Discussion

Our results provide strong evidence for the conclusion that musical pitch perception cannot be adequately captured by a simple helical representation as is often depicted, exaggerating on the one hand the effect of octave equivalence in non-musicians, and missing, on the other, the implications of alternative sources of variance in the judgments of musicians, in particular, those pertaining to tritone aversion and preference towards perfect intervals. Moreover, our work highlights that the most suitable geometrical approximation may in fact be task dependent, reflecting a representation that is shaped by different psychological factors with variable degrees of salience. Surprisingly, we also found that octave equivalence was most salient across experience groups in the singing task, despite being the most demanding and prone to production noise.

Musical Pitch Perception is Composite and Task Dependent

Across all experiments, we found that four components explained most of the meaningful variance in pitch similarity (an average raw R^2 of .79 across datasets, and an average corrected Pearson correlation of $r = .94$). However, their relative importance varied greatly between populations and tasks. Finding population and task dependency in pitch perception supports the idea that pitch is processed in higher-order brain areas (Nelken, 2011; Schnupp et al., 2011).

We found that a simple linear component dominated the responses of non-musicians, and also contributed to the responses of musicians (Figure 4). This is in line with the widely adopted definition of pitch by the American National Standards Institute (ANSI, 1960; "pitch is the auditory attribute of sound that allows sounds to be ordered on a scale from low to high") which emphasizes the linear nature of pitch. This is also consistent with Jacoby et al. (2019) who showed evidence that log-linear pitch perception is present in participants across cultures.

The other leading component we found was octave equivalence. Our findings support the idea that octave equivalence varies across participants and that the extent to which it is manifested is shaped by its salience in the task, supporting Jacoby et al. (2019), Pressnitzer and Demany (2019), and Regev et al. (2019). More specifically, we show quantitatively how the strength of octave equivalence varies with musical experience within the same task (Figure 4). Moreover, we found that the strength of the octave component relative to the linear component was particularly salient in the singing task. This is surprising as one would expect the singing task to yield noisy response patterns being a production-based task and more challenging. While we did find that participant responses were noisy (Supplementary Figure A1), they nevertheless showed the most clear octave equivalence compared with other tasks, even though the singing task is capable of capturing a linear representation (Supplementary Figure A5A-B). This underscores the importance of naturalistic paradigms when evaluating pitch perception. Beyond these two

components our results showed that musicians in the similarity judgment task over tones also relied on two other components, specifically "aversion" to tritones and preference for perfect intervals.

What can explain the behavioral differences across groups? One idea is that musicians can identify musical intervals based on their ear training, and then report what they think they are expected to report based on their explicit knowledge of Western music theory (Aldwell et al., 2018), or reflecting their internalized known distribution of melodic intervals in musical corpora (Vos & Troost, 1989; Zivic et al., 2013; Anglada-Tort et al., 2023). However, the fact that we observed task dependencies for all three experience groups, including groups with zero years of musical experience, suggest that the results could not be fully attributed to participants "rationalizing" about their expected responses. Another possibility is that other aspects of music perception may influence musicians' responses. For example, the phenomenon of melodic consonance, or the perceived pleasantness of tone sequences. Recent research suggests that Western participants (Anglada-Tort et al., 2023) exhibit a hierarchy of preferences when evaluating the pleasantness of two-tone melodies, with tones separated by an octave and perfect intervals being particularly pleasant, and those separated by a tritone being particularly unpleasant. This pattern overlaps to a certain extent also with that of harmonic consonance (the pleasantness of simultaneous tones; Trainor and Heinmiller, 1998; McDermott et al., 2010; Harrison and Pearce, 2020; Lahdelma and Eerola, 2020; Marjieh, Harrison, et al., 2024). Regardless of what strategy underlies the musicians' responses, our results undermine the validity of the pitch helix as an adequate unified model.

Overall, our results align with findings from previous smaller-scale, disparate studies and consolidate them within a single, unified large-scale study. Furthermore, our paper explicitly introduces the dimensions of task and expertise dependency (which are often studied separately) by evaluating multiple tasks in parallel across multiple levels of expertise, and verifying their joint influence on pitch perception.

Implications

One possible implication of our findings is that distinct elements such as octave equivalence and logarithmic frequency scaling are perceived and processed separately by the brain. When individuals make judgments—such as assessing the similarity between two tones—they weigh these different features in a task-specific manner. When performing another task, such as singing to reproduce a tone, they may adjust their weighting of available cues or features differently. Previous research shows that local pitch perception is task-dependent, and has leveraged this dependency to uncover distinct mechanisms for processing sounds into pitch. Indeed, by analogy to those psychoacoustic studies (Demany & Ramos, 2005; McPherson & McDermott, 2018), one may expect that the relative salience of different musical dimensions underlying the global organization of pitch percepts would be heavily modulated in different tasks, which is what we indeed found.

Our results carry implications for studying the neural correlates of pitch. Instead of a single representation in localized areas, we now expect pitch cues to be processed separately in lower and mid-level regions (Schulze et al., 2002; Bendor & Wang, 2005; Schnupp et al., 2011; Norman-Haignere et al., 2013; Feng & Wang, 2017), with integration only occurring at later stages of auditory processing (Nelken, 2011), akin to phoneme processing in speech (Mesgarani et al., 2014). Furthermore, our findings underscore the roles of statistical learning (Loui et al., 2010; Loui, 2012; Pearce, 2018), as the salience of these components strongly depends on musical expertise (Schön & François, 2011; Jacoby & Ahissar, 2013). Our results also highlight the capacity of brain plasticity to strongly modulate auditory perception, consistent with a large body of work that shows differences between musicians and non-musicians in auditory perception and production, as well as their neural correlates (Shepard, 1982a; Koelsch et al., 1999; Gaser & Schlaug, 2003; Zatorre et al., 2007; Dellacherie et al., 2011; François et al., 2013; Jacoby & Ahissar, 2013; Merzenich et al., 2013).

Beyond neuroscience, our results are valuable for computational models of pitch

perception. Predictive models of human behavior should consider both task dependency

and expertise, as these are crucial for accurately capturing the nuances of pitch perception

as demonstrated in the present work. Computational models that rely on mechanisms that

cannot capture task and expertise dependencies should therefore be revised or excluded.

Likewise, future pedagogical resources (e.g., textbooks) depicting pitch representations

should acknowledge that the pitch helix is only one instance of a broader class of

geometrical approximations of pitch representations, some of which may be more suitable

depending on the task and expertise considered.

Limitations and Future Work

We end by discussing limitations which point to important directions for future

research. First, our participant cohort is largely Western, particularly from the United

States and Germany. This limits the generalizability of the present findings as elements of

pitch perception such as octave equivalence and melodic preferences vary cross-culturally

(Jacoby et al., 2019). A natural follow-up, therefore, could look at the way representations

vary across cultures by applying the same methods deployed in this work which by design

are suitable for cross-cultural research (similar to McDermott et al., 2016; Lahdelma and

Eerola, 2020; McPherson et al., 2020; Jakubowski et al., 2022; Jacoby et al., 2024; Ozaki

et al., 2024).

Second, in the present work we exclusively focused on population-level analysis of

representations, however, since musical experience is very subjective one might expect to

see individual differences (McDermott et al., 2010) and use that to inform the relation

between components beyond group differences. Since we sought to derive dense similarity

matrices that spanned multiple octave ranges (which necessitate hundreds of judgments to

cover once; e.g. covering all pairs in the octave range C4-C6 requires at least

$25 \times 24/2 = 300$ without repetition) while ensuring that the online studies are not too long

to maintain high data quality, we were unable to collect enough data per participant to

enable individual-level geometric component analysis. Multi-session in-lab studies using the

same paradigms of the present work may be a suitable follow up. This is particularly important, since splitting the data by musical expertise does show significant differences even within the same paradigm, this indicates that individual variation is likely to play a significant role in the structure of pitch representations (Figures 2-4)

Third, previous work suggests that tonality may also be a shaping force in pitch perception (Krumhansl, 1979; Krumhansl & Shepard, 1979; Fogel et al., 2015). While our method tried to minimize carry-on effects of tonality from previous trials (by shifting tones randomly from trial to trial), it is possible that some sense of tonality can be induced even within a single trial, at least when it comes to expert musicians (Figure 4I).

Finally, there are other established paradigms for studying pitch representations that exist in the literature which we did not consider (e.g., Hoeschele et al., 2012) as they were not compatible with representational similarity analysis. Future work could explore alternative analytical approaches to examine these cases and assess if similar patterns emerge. We intend to pursue these directions in upcoming research.

To conclude, while pitch perception provides the fundamental backbone underlying both speech and music perception, it is neither simple nor static. Instead of a unified helical representation, our results reveal a highly complex and dynamical phenomenon that is likely to depend on multiple independent factors. More broadly, our work showcases how combining large-scale behavioral studies with diverse behavioral paradigms and computational modeling can provide new answers to fundamental questions in auditory research. We believe that scaling up psychological research in tandem with concurrent computational approaches will continue to provide exciting new hypotheses concerning the nature of human cognition.

Methods

Software Implementation

The behavioral paradigms were designed and deployed using PsyNet[1] (Harrison et al., 2020), a modern framework for complex experiment design which builds on the Dallinger[2] platform for online experiment hosting and participant recruitment. Participants interact with the experiment in the browser using a front-end interface which, in turn, communicates with a back-end Python cluster that organizes the experiment timeline. All experiment and analysis code are available in the Supporting Information provided with this manuscript (see Code and Data Availability below).

Stimuli

We defined absolute pitch using the Musical Instrument Digital Interface (MIDI) semitonal scale which is based on a logarithmic pitch representation. This was motivated by previous research which showed that participants across cultures use approximately logarithmic pitch representations (Jacoby et al., 2019). Specifically, the MIDI scale was defined as follows: $f = 440 \times 2^{(p-69)/12}$ where f is frequency in Hertz and p is the corresponding pitch value. This means that a Concert A (A4 or 440 Hz) corresponds to a value of 69 on this scale. All experiments involved additively synthesized harmonic complex tones $s(t) = \sum_{i=0}^{n_H-1} w_i \sin(2\pi f_i t)$ with $n_H = 10$ harmonics, where $f_i = f_0 \times (i+1)$ for some fundamental frequency f_0, $w_i = 10^{-\omega_i/20}$, $\omega_i = \rho \log_2(i+1)$ and a roll-off parameter, ρ, which parametrically represents the timbre of the sound by controlling the prominence of high harmonics. The tones were synthesized using Tone.js[3], a Javascript library for audio synthesis in the browser. Each tone had a temporal envelope comprising of a linear attack portion, an exponential decay portion to some sustain amplitude, and a final exponential release portion. These were specified based on the constraints of each paradigm (see below).

───────

[1] https://www.psynet.dev

[2] https://dallinger.readthedocs.io/en/latest/

[3] https://tonejs.github.io/

⁵⁵²   **Similarity Paradigms.** The similarity judgment paradigms used a roll-off

⁵⁵³ parameter ρ of 3 dB/octave. In the similarity between tones paradigm, the envelope

⁵⁵⁴ comprised a 200 ms linear attack segment reaching an amplitude of 1, followed by a short

⁵⁵⁵ 100 ms exponential decay to an amplitude of 0.8, and finally an exponential release

⁵⁵⁶ segment lasting for 1 second. The two tones within a given pair were separated by 300 ms

⁵⁵⁷ of silence. In the case of melodies, the individual tones within melodies similarly had an

⁵⁵⁸ envelope comprising of 200 ms linear attack followed by a short 100 ms decay to an

⁵⁵⁹ amplitude of 0.8, and then an exponential release portion with the same decay rate as

⁵⁶⁰ before. The release portion was played up to an inter-onset-interval of 650 ms in the first

⁵⁶¹ two tones (i.e. for 350 ms), and for 1 second in the last tone, followed by 200 ms of silence.

⁵⁶² This choice of parameters was intended to ensure that the presentation of melodies was

⁵⁶³ brief and well-separated (so as not to interact with memory and to allow participants to

⁵⁶⁴ experience a range of melodic pairs within a single experiment).

⁵⁶⁵   In the similarity judgment paradigm over melodies, random melodies were

⁵⁶⁶ synthesized by first uniformly sampling a starting tone in the MIDI range 76-80, and then

⁵⁶⁷ generating the second and third tones by subtracting a uniformly sampled integer interval

⁵⁶⁸ in the range $5 - 7$ and $9 - 11$ semitones, respectively. This means that the resulting

⁵⁶⁹ melodies could have a variety of melodic intervals per transposition so that pre-existing

⁵⁷⁰ musical expectations would not prime the perception of the transposition interval.

⁵⁷¹ Transpositions were then generated by subtracting a fixed integer interval in the range

⁵⁷² $0 - 24$ semitones from the second and third tones. As for the similarity judgment paradigm

⁵⁷³ over tones, tones covered the MIDI range $60 - 84$ corresponding to the notes C4-C6.

⁵⁷⁴   **Singing Paradigm.** In the singing task, the pitch range, timbre, and temporal

⁵⁷⁵ envelope of the tones, can all influence the difficulty of singing back melodies. We thus

⁵⁷⁶ adapted sound parameters that were extensively tested in a previous online singing study

⁵⁷⁷ (Anglada-Tort et al., 2023) and used the following values: a roll-off parameter ρ of 14

⁵⁷⁸ dB/octave, a 10 ms attack, a 50 ms decay to an amplitude of 0.6, followed by a 550 ms

release portion and 190 ms of silence (i.e., 800 ms inter-onset-interval between tones).

Two-note melodies were produced based on the design of Jacoby et al. (2019) (Experiment 4) by sampling the first tone from the range of $45.5 - 105.5$, and then creating the second tone by adding one of the intervals $0, \pm1, \pm2,$ or ±3 semitones. To further assist singers in their responses we applied a method proposed in Jacoby et al. (2019), where each experiment consisted of a series of "blocks" presented in random order, each of which presented stimuli within a single frequency register (i.e., by sampling the first tone uniformly from the range $[p_0 - 6, p_0 + 6]$ where $p_0 = 51.5, 63.5, 75.5, 87.5, 99.5$).

Participants

Participants were recruited online from two participant pools: Amazon Mechanical Turk (AMT), and an internal pool of professional musicians through the Max Planck Institute for Empirical Aesthetics. To cover different experience levels, we divided the AMT participants into two subcategories based on whether they reported zero years of musical experience ('No Musical Experience') or some years of musical experience ('Some Musical Experience'), in addition to the musicians ('Musicians'). The division of the AMT population also aligns with a median-split based on reported years of musical experience. Participants reported years of musical experience by responding to the query: 'Have you ever played a musical instrument? If yes, for how many years did you play?'. Demographic information for all participant groups is summarized in Supplementary Table A1. Additional recruitment details are provided below.

AMT Participants. Participants on AMT were subject to the following recruitment criteria designed to ensure data quality: 1) participants must be 18 years of age or more, 2) they must reside in the United States, 3) they have a 99% approval rate or higher on prior AMT tasks, and 4) have successfully completed 5,000 tasks on AMT (a common threshold in large scale AMT studies; e.g., Hardy et al., 2023). These participants provided informed consent under a Princeton University Institutional Review Board (IRB) protocol (application 10859) in the similarity tasks and a Max Planck Ethics Council

protocol (application 2021_42) in the singing task, and were paid a fair wage of 12 USD
per hour.

Musicians. The musician cohort was recruited through an internal online
participant pool at the Max Planck Institute for Empirical Aesthetics (MPIEA).
Participants were recruited to this pool by researchers and research assistants at MPIEA
by sending emails to local and international music conservatories, as well as handing flyers
at local music conservatories in Germany. The pool is diverse and comprises the following
countries: Germany, Spain, Italy, Malaysia, France, Hungary, United Kingdom,
Switzerland, Australia, Peru, Indonesia, Argentina, Croatia, Hong Kong, Lebanon, Chile,
and Serbia. In order to participate, musicians were required to be at least 18 years of age
and to have at least 10 years of active musical training. Participants provided consent
under a Max Planck Ethics Council protocol (application 2021_42) and were paid at a rate
of 15 USD per hour. Participant took the experiment remotely, and the web-interface was
identical to the one used by the AMT participants. We excluded three participants in
melodic similarity, two in singing, and two in tone similarity who reported less than 10
years of musical experience. We also note that the number of musicians varied between the
similarity paradigms due to the nature of online recruitment whereby participants had the
freedom to select which experiments they wanted to complete from a list of available
studies.

Pre-screening

Similarity Paradigms. To enhance online data quality, in the similarity tasks
participants were required to complete a headphone prescreening test (Woods et al., 2017)
to ensure that they were wearing headphones. In each trial of this test, participants heard
a series of three tones and were asked to judge which of these was the quietest. The tones
were designed to induce a phase cancellation effect when played on speakers which would
lead participants without headphones to answer incorrectly. Participants who failed the
headphone test were not allowed to proceed to the main experiment but were nevertheless

fully compensated for the time taken to perform the pre-screening test.

Singing Paradigm. As with the similarity tasks, participants in the singing paradigm first completed a headphone prescreening test. This was then followed by an additional recording test which was adapted from Anglada-Tort et al. (2023) and proceeded as follows. First, participants performed a microphone check to ensure that their audio was detectable. Specifically, a pop up window was triggered asking participants to allow audio recording in the browser. Participants could not proceed without enabling their microphone. Once allowed, participants were instructed to freely sing into their microphone and check that an audio meter (provided on the page) indicated an appropriate sound level (volume). Next, participants were asked to sing two notes of their choice to the syllable 'TA' which were then played back to the participant so that they can double check that their microphone is appropriately set up. At this point, participants completed two practice trials in which they were instructed to imitate two two-note melodies ('In this task, we want to measure how well you can imitate a melody. In the next few trials you can practice performing the task, before we measure your performance in the main experiment. You will hear a melody with 2 notes, and after it ends, you'll be asked to sing these two notes back as accurately as possible. Note: Use the syllable TA to sing each note and leave a silent gap between notes. We will provide feedback after each trial'). After each trial participants were informed of the number of notes that were detected (see Singing Transcription Technology below). Importantly, this step did not provide feedback on the singing pitch to avoid biasing the participants. Finally, participants proceeded to a test phase where they had to complete 10 additional singing imitation trials without feedback ('We will now test your singing performance in a total of 10 trials. Like before, your goal is to listen to each melody, and after it ends, sing these two notes back as accurately as possible. Note: Use the syllable TA to sing each note and leave a silent gap between notes'). Participants recruited through AMT were allowed to proceed only if they were able to satisfy the following three criteria on at least 5 of the 10 trials: (i) They sung

exactly two notes, (ii) the absolute interval error between the target and sung melodies was no larger than 3 semitones, and (iii) the direction of the target and sung melodies was the same (i.e. ascending vs. descending). These criteria were adapted from Anglada-Tort et al. (2023) and intended to ensure that AMT participants were making an honest effort to imitate the melodies. Musicians also performed this pre-screener, however, we set their passing threshold to 0 (meaning that everyone passed) as their recruitment was more controlled. Nonetheless, in a post-hoc analysis we confirmed that only one musician marginally failed the test (by achieving a score of 4) whom we excluded. Finally, we note that the two-note melodies were taken from the same set as that devised by Anglada-Tort et al. (2023), and comprised the melodic intervals -2.6, -1.3, 0.0, 1.3, and 2.6, played at two registers (i.e. bass tones), 49 semitones (low) and 61 semitones (high), with uniform roving width of 2.5 semitones. The fractional intervals and roving were applied so that no specific sense of tonality is induced (Jacoby et al., 2019).

Performance Incentives

To motivate online participants to provide honest responses for the otherwise subjective tasks, participants in the similarity paradigms were informed that they could receive a performance bonus depending on the quality of their responses. Specifically, they received the following instructions: "The quality of your responses will be automatically monitored, and you will receive a bonus at the end of the experiment in proportion to your quality score. The best way to achieve a high score is to concentrate and give each trial your best attempt". While the tasks are subjective in nature, we used self-consistency as a measure of performance quality. This was done by repeating 5 random trials at the end of the experiment and then computing Spearman correlation between the original and repeated answers. The resulting score s was then used to compute a small bonus of up to 10 cents using the formula $\min(\max(0, 0.1s), 0.1)$.

Procedure

Similarity Paradigms. In the similarity over melodies task, the experiment proceeded as follows: upon completing the consent form participants received the following instructions: "In this experiment we are studying how people perceive melodies. In each round you will be presented with two three-note melodies and your task will be to simply judge how similar they are. You will have seven response options, ranging from 0 ('Completely Dissimilar') to 6 ('Completely Similar'). Choose the one you think is most appropriate. You will also have access to a replay button that will allow you to replay the sounds if needed. Note: no prior expertise is required to complete this task, just choose what you intuitively think is the right answer". Participants then completed two practice trials and then proceeded to the main experiment. The procedure for the similarity over isolated tones task was identical, except that we replaced "melodies" in the instructions with "sounds". Participants completed up to 80 trials.

Singing Paradigm. After providing informed consent and completing the pre-screening trials (see Pre-screening) participants received the following instructions: 'In this final part of the experiment, we will ask you to do exactly the same as in the previous part. 1. You will hear a 2 note melody. 2. You will have to sing back the 2 notes. That means, in total you will sing 2 notes. The difference is that this time there will be a total of 38 trials. For all notes, use the syllable TA to sing the note and leave a silent gap between notes. Note: some of the tones you'll hear will be high, and well above your singing range. You should, however, sing them within your comfortable singing range.' The latter note was intended to ensure that participants were not surprised by the high tones (consistent with Jacoby et al. (2019); see Session Structure in that paper), as well as to ensure that they imitated the melodies within their natural singing range for compatibility with the pitch transcription technology of Anglada-Tort et al. (2023) that we employed (see Singing Transcription Technology below). Participants then completed the trials which corresponded to the randomized trial blocks (see Stimuli) in addition to three repeat trials

(i.e. repeating three random trials from the original 35). The trials were presented in one

continuous stream without any additional indications. In a given trial, participants received

the following instructions: "This melody has 2 notes. Sing back the melody. Use the

syllable TA". The recording interface comprised of a temporal meter (see Supplementary

Figure A9) indicating the three recording stages. The initial portion, indicated in orange,

signaled the listening portion ("Listen to the melody..."). Then, a second portion, indicated

in red, signaled that the recording was in progress ("Recording...SING THE MELODY!").

This portion lasted for the duration of the original melody plus one second. Finally, a third

portion, highlighted in green, indicated that recording was complete ("Done!"), and lasted

for 500 ms. The next trial then started automatically, and so on.

Singing Transcription Technology

We relied on the singing transcription technology[4] of Anglada-Tort et al. (2023) for

extracting the fundamental frequencies (f_0) of the participants' sung notes. This

technology has been extensively tested and was shown to provide reliable f_0 estimates in

online settings (Anglada-Tort et al., 2023). The automated process comprises four steps: i)

Cleaning the recorded audio from artifacts. This included removing the first 100 ms of a

recording, applying a 150 ms linear fade-in, and applying a band-pass filter with cut-off

frequencies 80-6000 Hz to remove any non-singing spectral components. ii) Applying a

pitch estimation method based on auto-correlation (Boersma et al., 1993) for extracting f_0

from sung segments, implemented using parselmouth (Jadoul et al., 2018). We used the

recommended parameters (Anglada-Tort et al., 2023) of 65 Hz (36 semitones, C2) for pitch

floor and 622 Hz for pitch ceiling (75 semitones, D#5). iii) Segmenting the continuous f_0

signal into individual isolated tones. This was done by extracting the envelope of the audio

signal (by computing the maximum of the squared amplitude within non-overlapping 40

ms windows and then taking the square root) and applying a peak detection algorithm

(Duarte & Watanabe, 2015) to find areas of vocal activity that are separated by silences

---

[4] https://gitlab.com/computational-audition/sing4me

(defined as envelope values that are less than -30 dB relative to the first peak within a

segment and extending for at least 30 ms). iv) Filtering the list of audio segments using a

set of heuristics to remove any spurious audio segments. This included removing segments

that are shorter than 40 ms, removing segments with large deviations from the median f_0,

i.e., segments that deviate from the median by at least 8 semitones for more than 35% of

the duration the segment which could happen when the singer's voice "cracks", as well as

removing any segments with median f_0 that falls outside the 65 - 622 Hz range of the

auto-correlation step). Finally, the remaining segments were summarized into single pitch

values by computing the median f_0 (full details of the approach can be found in

Anglada-Tort et al. (2023) under Method Details).

To ensure that the parameters of the singing transcription technology did not bias

or constrain the response distributions, we compared our results to the in-lab data of

Jacoby et al. (2019). The data are reproduced in Supplementary Figure A10 alongside

ours. We see that the online and in-lab data are highly consistent, both in terms of the

response range (95% CI of response pitch values for the in-lab data was $[44, 76]$ semitones

for non-musicians, and $[45, 72]$ semitones for musicians, both of which are highly

overlapping with our design range of $[36, 75]$ semitones), as well as the resulting similarity

matrices shown in Supplementary Figure A11 ($r = .93$, $p < 0.001$ for non-musicians, and

$r = .95$, $p < 0.001$ for musicians; see Data Analysis for details regarding computing the

similarity matrices).

Data Analysis

Constructing Similarity Matrices. To generate an aggregate similarity matrix

from the direct similarity judgment paradigms, we applied the following procedures. In the

case of similarity over isolated tone pairs, we simply computed the average Likert score per

pair of items and divided by a constant of 6 so that similarity scores would be normalized

between 0 and 1 (rather than 0 and 6). As for similarity over melodies, since the data is

one-dimensional in that case (a pitch transposition t between random melodies) we

constructed a two-dimensional matrix a_{ij} from the one-dimensional data s_t using the

formula $a_{ij} = s_{|p_i - p_j|}$ where p_i and p_j are pitch values of interest. We again divided by a

factor of 6 so that similarity scores would be normalized between 0 and 1. As for the

singing data, the procedure is slightly more complicated and is described below. To

produce the smoothed raw matrices we averaged the similarity matrices over their diagonal

values, i.e. $s_{ij}^{smooth} = \bar{s}_{|i-j|}$ where $\bar{s}_{|i-j|}$ is the average over the $|i - j|$-th off-diagonal of s_{ij} (0

being the main diagonal).

Singing Response Distributions. To construct similarity matrices based on the

response distributions of human singers, we first applied a 2D Gaussian kernel density

estimate (KDE) $\rho(p_t, p_r)$ to the target-response pitch pairs (p_t, p_r) (we used the first tone

in each target melody as the second tone is not independent) using the `KernelDensity`

method of the `scikit-learn`[5] Python package with a bandwidth parameter of $\sigma = 1.1$

semitones and a resolution of 500×500 bins. We used this bandwidth as it provided a

good tradeoff between reliability and resolution as determined by a five-fold cross

validation analysis using the `GridSearchCV` method of `scikit-learn`. Dissimilarity

between two target pitches p_{t_1} and p_{t_2} was then computed by applying the Jensen-Shannon

distance `jensenshannon` from the `scipy`[6] package to the KDE marginals $\rho(p_r|p_{t_1})$ and

$\rho(p_r|p_{t_2})$. To ensure that this approach is sufficiently flexible to capture different

meaningful structures we applied it to different simulated response distributions that

capture various modes of behavior. Specifically, we used a similar target pitch distribution

as in the online experiments and simulated different response pitch values including (i) a

noisy linear response, (ii) a noisy linear response with register saturation, (iii) a mixture of

linear response with some probability of singing an octave above or below the target pitch,

(iv) a mixture of linear response with some chance of singing one or more fifths above or

below the target pitch, and (v) chroma matching within a given register. We then applied

---

[5] https://scikit-learn.org/stable/

[6] https://scipy.org/

an identical processing procedure as in the behavioral experiments to produce similarity

matrices which we then subjected to MDS. The results are shown in Supplementary

Figure A5 and we found that the approach is indeed able to capture a variety of

qualitatively different structures. Simulation code and 3D visualizations of the simulated

solutions are provided in the OSF repository.

Multi-dimensional Scaling. We constructed MDS embeddings using the `MDS`

method of `scikit-learn`. This was done in two steps, first we applied a metric MDS to

find an initial embedding which was then fed as an initialization into a non-metric MDS.

We used three components, a maximum iteration value of 10,000, and a tolerance

parameter of 1e-100. We chose three dimensional embeddings based on a stress curve

analysis (Supplementary Figure A2) and selected the smallest number of dimensions for

which all stress values across all conditions dropped below 0.15 (MDS fit is deemed poor

above this threshold; Kruskal, 1964). This ensured that all structures are represented

adequately within the same unified presentation (since lower dimensional structures can

always be represented in higher dimensions but not vice versa). Finally, we note that all

MDS solutions presented in this work are also available as 3D interactive HTML

visualizations available through the OSF repository (see Code and Data Availability).

Geometric Components. The explicit formulae for the different geometric

components were: a linear pitch scale $d_{ij}^{(l)} \propto |p_i - p_j|$, two positive interval recognition

components $d_{ij}^{(c)} = 1 - \exp\left(-(\chi(p_i, p_j) - c)^2/2\sigma_c^2\right)$ where $\chi(p_i, p_j) = \min\{\psi_{ij}, 6 - \psi_{ij}\}$ and

$\psi_{ij} = |p_i - p_j| \mod 12$ to capture chroma distance (i.e., intervallic distance irrespective of

register) and $c = 0, 5$ for octave ($d_{ij}^{(o)}$) and perfect intervals (fourth and fifth; $d_{ij}^{(p)}$),

respectively, and one negative recognition component $d_{ij}^{(c)} = \exp\left(-(\chi(p_i, p_j) - c)^2/2\sigma_c^2\right)$

with $c = 6$ to capture tritone aversion ($d_{ij}^{(t)}$). We fixed $\sigma_c = 0.25$ semitones for the tritone

and perfect intervals as a narrow interval recognition threshold and optimized the octave

width σ_o as a hyperparameter since different values of σ_o efficiently interpolate between

sharp octave recognition and smooth distance on the chroma circle (since $c = 0$). As a

sanity check for the chosen width parameter values, we refitted the model in the musician

tone similarity condition (Figure 4F, the only condition in which the tritone and perfect

intervals had substantial contributions) but this time allowing all width parameters to vary.

We found that the optimal width parameters did not differ much from our chosen values

($\sigma_o = 0.39$, $\sigma_t = 0.17$ and $\sigma_p = 0.57$). In addition, to ensure that the coefficients are

properly normalized (i.e., each geometric component varied between 0 to 1), we rescaled the

linear component such that its largest separation on a given range of interest equals to one

(e.g. if pitch differences varied between 0 and 24 semitones, we defined $d_{ij}^{(l)} = |p_i - p_j|/24$).

Model Fitting and Evaluation. We fitted geometric components to the data

using the `LinearRegression` method of `scikit-learn`. This was done by first flattening

the upper triangular part of each component's distance matrix $d_{ij}^{(c)}$ into a feature vector $v_i^{(c)}$

and then fitting a linear regression of the form $1 - s_i = b + \sum_c a_c v_i^{(c)}$ where $b, a_c \geq 0$ are

non-negative coefficients and s_i is the flattened upper-triangular matrix of the behavioral

similarity data. We repeated this fitting process 1,000 times by bootstrapping over

participants in a split-half fashion (i.e., generating random half-splits of the data based on

participants and then fitting the model to one half and testing on the other). The optimal

octave width hyperparameter σ_o was fine-tuned using the blackbox optimizer

`scipy.optimize.minimize` over the bootstrapped linear regression procedure described

above. To quantify model performance, we computed three Pearson correlation coefficients

for each of the 1,000 split-halves as follows: r_{dd} the correlation between the corresponding

human similarity matrices of each split, r_{dm} the correlation between the model fit on one

half with the human similarity of the other (there are two ways to compute this so we took

the mean), and r_{mm} the correlation between the fitted models on each half. We then used

these values to compute the corrected correlation for attenuation $r = r_{md}/\sqrt{r_{dd}r_{mm}}$.

Code and Data Availability. Data and code used in this work can be accessed

via the link: https://osf.io/nx586/?view_only=a0f74c9269a4448f821aadccf76ba175.

Author Contributions. All authors contributed to the design of the experiments.

Author RM implemented the experiments, analyzed the results, and drafted the initial

manuscript. All authors collaborated on editing and revising the manuscript.

Competing Interests. The authors declare no competing interests.

Acknowledgements. This work was supported by grant 61454 from the John

Templeton Foundation.

References

Ruckmick, C. (1929). A new classification of tonal qualities. *Psychological Review, 36*(2), 172.

Humphreys, L. G. (1939). Generalization as a function of method of reinforcement. *Journal of Experimental Psychology, 25*(4), 361.

d'Arezzo, G. (1955). Micrologus. ed. *Joseph Smits van Waesberghe. Rome: American Institute of Musicology.*

ANSI. (1960). Acoustical terminology si. *1-1960, American Standards Association.*

Von Békésy, G. (1960). Experiments in hearing.

Kruskal, J. B. (1964). Multidimensional scaling by optimizing goodness of fit to a nonmetric hypothesis. *Psychometrika, 29*(1), 1–27.

Shepard, R. (1964). Circularity in judgments of relative pitch. *The journal of the acoustical society of America, 36*(12), 2346–2353.

Allen, D. (1967). Octave discriminability of musical and non-musical subjects. *Psychonomic Science, 7*(12), 421–422.

Plomp, R. (1967). Pitch of complex tones. *The Journal of the Acoustical Society of America, 41*(6), 1526–1533.

Rose, J. E., Brugge, J. F., Anderson, D. J., & Hind, J. E. (1967). Phase-locked response to low-frequency tones in single auditory nerve fibers of the squirrel monkey. *Journal of neurophysiology, 30*(4), 769–793.

Attneave, F., & Olson, R. K. (1971). Pitch as a medium: A new approach to psychophysical scaling. *The American journal of psychology*, 147–166.

Deutsch, D. (1972). Octave generalization and tune recognition. *Perception & Psychophysics, 11*(6), 411–412.

Deutsch, D. (1973). Octave generalization of specific interference effects in memory for tonal pitch. *Perception & Psychophysics, 13*(2), 271–275.

Moore, B. C. (1973). Frequency difference limens for short-duration tones. *The Journal of the Acoustical Society of America*, *54*(3), 610–619.

Patterson, R. D. (1976). Auditory filter shapes derived with noise stimuli. *The Journal of the Acoustical Society of America*, *59*(3), 640–654.

Idson, W. L., & Massaro, D. W. (1978). A bidimensional model of pitch in the recognition of melodies. *Perception & Psychophysics*, *24*(6), 551–565.

Shepard, R. (1978). The circumplex and related topological manifolds in the study of perception. *Theory construction and data analysis in the behavioral sciences*, 29–80.

Kallman, H. J., & Massaro, D. W. (1979). Tone chroma is functional in melody recognition. *Perception & Psychophysics*, *26*, 32–36.

Krumhansl, C. L. (1979). The psychological representation of musical pitch in a tonal context. *Cognitive psychology*, *11*(3), 346–374.

Krumhansl, C. L., & Shepard, R. (1979). Quantification of the hierarchy of tonal functions within a diatonic context. *Journal of experimental psychology: Human Perception and Performance*, *5*(4), 579.

Shepard, R. (1980). Multidimensional scaling, tree-fitting, and clustering. *Science*, *210*(4468), 390–398.

Cuddy, L. L., Cohen, A. J., & Mewhort, D. (1981). Perception of structure in short melodic sequences. *Journal of Experimental Psychology: Human Perception and Performance*, *7*(4), 869.

Kallman, H. J. (1982). Octave equivalence as measured by similarity ratings. *Perception & Psychophysics*, *32*(1), 37–49.

Krumhansl, C. L., & Kessler, E. J. (1982). Tracing the dynamic changes in perceived tonal organization in a spatial representation of musical keys. *Psychological review*, *89*(4), 334.

Shepard, R. (1982a). Geometrical approximations to the structure of musical pitch. *Psychological review*, *89*(4), 305.

Shepard, R. (1982b). Structural representations of musical pitch. In D. Deutsch (Ed.), *Psychology of music* (pp. 343–390). Academic Press.

Demany, L., & Armand, F. (1984). The perceptual reality of tone chroma in early infancy. *The journal of the Acoustical Society of America*, *76*(1), 57–66.

Shamma, S. A. (1985). Speech processing in the auditory system ii: Lateral inhibition and the central processing of speech evoked activity in the auditory nerve. *The Journal of the Acoustical Society of America*, *78*(5), 1622–1632.

Shepard, R. (1987). Toward a universal law of generalization for psychological science. *Science*, *237*(4820), 1317–1323.

Vos, P. G., & Troost, J. M. (1989). Ascending and descending melodic intervals: Statistical findings and their perceptual relevance. *Music Perception*, *6*(4), 383–396.

Dowling, W. J. (1990). Expectancy and attention in melody perception. *Psychomusicology: A Journal of Research in Music Cognition*, *9*(2), 148.

Amano, S. (1993). Perception of tonal and microtonal structure over octaves. *Japanese Psychological Research*, *34*(3), 89–95.

Boersma, P., et al. (1993). Accurate short-term analysis of the fundamental frequency and the harmonics-to-noise ratio of a sampled sound. *Proceedings of the institute of phonetic sciences*, *17*(1193), 97–110.

Shackleton, T. M., & Carlyon, R. P. (1994). The role of resolved and unresolved harmonics in pitch perception and frequency modulation discrimination. *The Journal of the Acoustical Society of America*, *95*(6), 3529–3540.

Zatorre, R. J., Evans, A. C., & Meyer, E. (1994). Neural mechanisms underlying melodic perception and memory for pitch. *Journal of neuroscience*, *14*(4), 1908–1919.

Trainor, L. J., & Heinmiller, B. M. (1998). The development of evaluative responses to music:: Infants prefer to listen to consonance over dissonance. *Infant Behavior and Development*, *21*(1), 77–88.

Koelsch, S., Schröger, E., & Tervaniemi, M. (1999). Superior pre-attentive auditory processing in musicians. *Neuroreport*, *10*(6), 1309–1313.

Drabkin, W. (2001). Octave (i). https://doi.org/10.1093/gmo/9781561592630.article.50054

Kishon-Rabin, L., Amir, O., Vexler, Y., & Zaltz, Y. (2001). Pitch discrimination: Are professional musicians better than non-musicians? *Journal of basic and clinical physiology and pharmacology*, *12*(2), 125–144.

Krumhansl, C. L. (2001). *Cognitive foundations of musical pitch* (Vol. 17). Oxford University Press.

Winter, I. M., Wiegrebe, L., & Patterson, R. D. (2001). The temporal representation of the delay of iterated rippled noise in the ventral cochlear nucleus of the guinea-pig. *The Journal of physiology*, *537*(Pt 2), 553.

Patterson, R. D., Uppenkamp, S., Johnsrude, I. S., & Griffiths, T. D. (2002). The processing of temporal pitch and melody information in auditory cortex. *Neuron*, *36*(4), 767–776.

Schulze, H., Neubauer, H., Ohl, F. W., Hess, A., & Scheich, H. (2002). Representation of stimulus periodicity and its learning induced plasticity in the auditory cortex: Recent findings and new perspectives. *Acta Acustica united with Acustica*, *88*(3), 399–407.

Gaser, C., & Schlaug, G. (2003). Brain structures differ between musicians and non-musicians. *Journal of neuroscience*, *23*(27), 9240–9245.

Patel, A. D. (2003). Language, music, syntax and the brain. *Nature neuroscience*, *6*(7), 674–681.

Warren, J. D., Uppenkamp, S., Patterson, R. D., & Griffiths, T. D. (2003). Separating pitch chroma and pitch height in the human brain. *Proceedings of the National Academy of Sciences*, *100*(17), 10038–10042.

Fujioka, T., Trainor, L. J., Ross, B., Kakigi, R., & Pantev, C. (2004). Musical training enhances automatic encoding of melodic contour and interval structure. *Journal of cognitive neuroscience*, *16*(6), 1010–1021.

Bendor, D., & Wang, X. (2005). The neuronal representation of pitch in primate auditory cortex. *Nature*, *436*(7054), 1161–1165.

Demany, L., & Ramos, C. (2005). On the binding of successive sounds: Perceiving shifts in nonperceived pitches. *The Journal of the Acoustical Society of America*, *117*(2), 833–841.

Koelsch, S., & Siebel, W. A. (2005). Towards a neural basis of music perception. *Trends in cognitive sciences*, *9*(12), 578–584.

Peretz, I., & Zatorre, R. J. (2005). Brain organization for music processing. *Annu. Rev. Psychol.*, *56*, 89–114.

Plack, C. J., & Oxenham, A. J. (2005). The psychophysics of pitch. In *Pitch: Neural coding and perception* (pp. 7–55). Springer.

Levitin, D. J. (2006). *This is your brain on music: The science of a human obsession.* Penguin.

Micheyl, C., Delhommeau, K., Perrot, X., & Oxenham, A. J. (2006). Influence of musical and psychoacoustical training on pitch discrimination. *Hearing research*, *219*(1-2), 36–47.

Plack, C. J., Oxenham, A. J., & Fay, R. R. (2006). *Pitch: Neural coding and perception* (Vol. 24). Springer Science & Business Media.

Tymoczko, D. (2006). The geometry of musical chords. *Science*, *313*(5783), 72–74.

Wolfe, J. M., Kluender, K. R., Levi, D. M., Bartoshuk, L. M., Herz, R. S., Klatzky, R. L., Lederman, S. J., & Merfeld, D. M. (2006). *Sensation & perception.* Sinauer Sunderland, MA.

Wong, P. C., Skoe, E., Russo, N. M., Dees, T., & Kraus, N. (2007). Musical experience shapes human brainstem encoding of linguistic pitch patterns. *Nature neuroscience*, *10*(4), 420–422.

Zatorre, R. J., Chen, J. L., & Penhune, V. B. (2007). When the brain plays music: Auditory–motor interactions in music perception and production. *Nature reviews neuroscience*, *8*(7), 547–558.

Goldstein, E. B. (2008). *Blackwell handbook of sensation and perception.* John Wiley & Sons.

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, *2*, 249.

McDermott, J. H., & Oxenham, A. J. (2008). Music perception, pitch, and the auditory system. *Current opinion in neurobiology*, *18*(4), 452–463.

Temperley, D. (2008). A probabilistic model of melody perception. *Cognitive Science*, *32*(2), 418–444.

Hall, D. A., & Plack, C. J. (2009). Pitch processing sites in the human auditory brain. *Cerebral cortex*, *19*(3), 576–585.

Cedolin, L., & Delgutte, B. (2010). Spatiotemporal representation of the pitch of harmonic complex tones in the auditory nerve. *Journal of Neuroscience*, *30*(38), 12712–12724.

de Cheveigné, A. (2010). Pitch perception alain de cheveigné. *The oxford handbook of auditory science: Hearing*, *3*, 71.

Loui, P., Wessel, D. L., & Kam, C. L. H. (2010). Humans rapidly learn grammatical structure in a new musical scale. *Music perception*, *27*(5), 377–388.

McDermott, J. H., Lehr, A. J., & Oxenham, A. J. (2010). Individual differences reveal the basis of consonance. *Current Biology*, *20*(11), 1035–1041.

Patel, A. D. (2010). *Music, language, and the brain.* Oxford university press.

Trainor, L. J., & Corrigall, K. A. (2010). Music acquisition and effects of musical experience. *Music perception*, 89–127.

Bentsen, T., Harte, J. M., & Dau, T. (2011). Human cochlear tuning estimates from stimulus-frequency otoacoustic emissions. *The Journal of the Acoustical Society of America*, *129*(6), 3797–3807.

Dellacherie, D., Roy, M., Hugueville, L., Peretz, I., & Samson, S. (2011). The effect of musical experience on emotional self-reports and psychophysiological responses to dissonance. *Psychophysiology*, *48*(3), 337–349.

Nelken, I. (2011). Music and the auditory brain: Where is the connection? *Frontiers in Human Neuroscience*, *5*, 106.

Schnupp, J., Nelken, I., & King, A. (2011). *Auditory neuroscience: Making sense of sound.* MIT press.

Schön, D., & François, C. (2011). Musical expertise and statistical learning of musical and linguistic structures. *Frontiers in psychology*, *2*, 167.

Trainor, L. J., & Unrau, A. (2011). Development of pitch and music perception. In *Human auditory development* (pp. 223–254). Springer.

Hoeschele, M., Weisman, R. G., & Sturdy, C. B. (2012). Pitch chroma discrimination, generalization, and transfer tests of octave equivalence in humans. *Attention, Perception, & Psychophysics*, *74*, 1742–1760.

Loui, P. (2012). Learning and liking of melody and harmony: Further studies in artificial grammar learning. *Topics in Cognitive Science*, *4*(4), 554–567.

Wong, P. C., Ciocca, V., Chan, A. H., Ha, L. Y., Tan, L.-H., & Peretz, I. (2012). Effects of culture on musical pitch perception. *PloS one*, *7*(4), e33424.

Briley, P. M., Breakey, C., & Krumbholz, K. (2013). Evidence for pitch chroma mapping in human auditory cortex. *Cerebral Cortex*, *23*(11), 2601–2610.

François, C., Chobert, J., Besson, M., & Schön, D. (2013). Music training for the development of speech segmentation. *Cerebral Cortex*, *23*(9), 2038–2043.

Hoeschele, M., Weisman, R. G., Guillette, L. M., Hahn, A. H., & Sturdy, C. B. (2013). Chickadees fail standardized operant tests for octave equivalence. *Animal cognition*, *16*, 599–609.

Jacoby, N., & Ahissar, M. (2013). What does it take to show that a cognitive training procedure is useful?: A critical evaluation. *Progress in brain research*, *207*, 121–140.

Merzenich, M., Nahum, M., & van Vleet, T. (2013). *Changing brains: Applying brain plasticity to advance and recover human ability*. Elsevier.

Norman-Haignere, S., Kanwisher, N., & McDermott, J. H. (2013). Cortical pitch regions in humans respond primarily to resolved harmonics and are located in specific tonotopic regions of anterior auditory cortex. *Journal of Neuroscience*, *33*(50), 19451–19469.

Zivic, P. H. R., Shifres, F., & Cecchi, G. A. (2013). Perceptual basis of evolving western musical styles. *Proceedings of the National Academy of Sciences*, *110*(24), 10034–10038. https://doi.org/10.1073/pnas.1222336110

Mesgarani, N., Cheung, C., Johnson, K., & Chang, E. F. (2014). Phonetic feature encoding in human superior temporal gyrus. *Science*, *343*(6174), 1006–1010.

Weiss, A. H., Granot, R. Y., & Ahissar, M. (2014). The enigma of dyslexic musicians. *Neuropsychologia*, *54*, 28–40.

Duarte, M., & Watanabe, R. (2015). Notes on scientific computing for biomechanics and motor control (version v0. 0.2). zenodo.

Fogel, A. R., Rosenberg, J. C., Lehman, F. M., Kuperberg, G. R., & Patel, A. D. (2015). Studying musical and linguistic prediction in comparable ways: The melodic cloze probability method. *Frontiers in psychology*, *6*, 1718.

Savage, P. E., Brown, S., Sakai, E., & Currie, T. E. (2015). Statistical universals reveal the structures and functions of human music. *Proceedings of the National Academy of Sciences*, *112*(29), 8987–8992.

McDermott, J. H., Schultz, A. F., Undurraga, E. A., & Godoy, R. A. (2016). Indifference to dissonance in native amazonians reveals cultural variation in music perception. *Nature, 535*(7613), 547–550.

Milne, A. J., & Holland, S. (2016). Empirically testing tonnetz, voice-leading, and spectral models of perceived triadic distance. *Journal of Mathematics and Music, 10*(1), 59–85.

Feng, L., & Wang, X. (2017). Harmonic template neurons in primate auditory cortex underlying complex sound processing. *Proceedings of the National Academy of Sciences, 114*(5), E840–E848.

Lau, B. K., Mehta, A. H., & Oxenham, A. J. (2017). Superoptimal perceptual integration suggests a place-based representation of pitch at high frequencies. *Journal of Neuroscience, 37*(37), 9013–9021.

Woods, K. J., Siegel, M. H., Traer, J., & McDermott, J. H. (2017). Headphone screening to facilitate web-based auditory experiments. *Attention, Perception, & Psychophysics, 79*(7), 2064–2072.

Aldwell, E., Schachter, C., & Cadwallader, A. (2018). *Harmony and voice leading.* Cengage Learning.

Jadoul, Y., Thompson, B., & De Boer, B. (2018). Introducing parselmouth: A python interface to praat. *Journal of Phonetics, 71*, 1–15.

McPherson, M. J., & McDermott, J. H. (2018). Diversity in pitch perception revealed by task dependence. *Nature human behaviour, 2*(1), 52–66.

Oxenham, A. J. (2018). How we hear: The perception and neural coding of sound. *Annual review of psychology, 69*(1), 27–50.

Pearce, M. T. (2018). Statistical learning and probabilistic prediction in music cognition: Mechanisms of stylistic enculturation. *Annals of the New York Academy of Sciences, 1423*(1), 378–395.

Plack, C. J. (2018). *The sense of hearing.* Routledge.

Cheung, V. K., Harrison, P. M., Meyer, L., Pearce, M. T., Haynes, J.-D., & Koelsch, S. (2019). Uncertainty and surprise jointly predict musical pleasure and amygdala, hippocampus, and auditory cortex activity. *Current Biology*, *29*(23), 4084–4092.

Jacoby, N., Undurraga, E. A., McPherson, M. J., Valdés, J., Ossandón, T., & McDermott, J. H. (2019). Universal and non-universal features of musical pitch perception revealed by singing. *Current Biology*, *29*(19), 3229–3243.

Kuroyanagi, J., Sato, S., Ho, M.-J., Chiba, G., Six, J., Pfordresher, P., Tierney, A., Fujii, S., & Savage, P. E. (2019). Automatic comparison of human music, speech, and bird song suggests uniqueness of human scales.

Mehr, S. A., Singh, M., Knox, D., Ketter, D. M., Pickens-Jones, D., Atwood, S., Lucas, C., Jacoby, N., Egner, A. A., Hopkins, E. J., et al. (2019). Universality and diversity in human song. *Science*, *366*(6468), eaax0868.

Pressnitzer, D., & Demany, L. (2019). Auditory perception: Relative universals for musical pitch. *Current Biology*, *29*(19), R927–R929.

Regev, T. I., Nelken, I., & Deouell, L. Y. (2019). Evidence for linear but not helical automatic representation of pitch in the human auditory system. *Journal of cognitive neuroscience*, *31*(5), 669–685.

Harrison, P., Marjieh, R., Adolfi, F., van Rijn, P., Anglada-Tort, M., Tchernichovski, O., Larrouy-Maestri, P., & Jacoby, N. (2020). Gibbs sampling with people. *Advances in Neural Information Processing Systems*, *33*, 10659–10671.

Harrison, P., & Pearce, M. T. (2020). Simultaneous consonance in music perception and composition. *Psychological Review*, *127*(2), 216.

Lahdelma, I., & Eerola, T. (2020). Cultural familiarity and musical expertise impact the pleasantness of consonance/dissonance but not its perceived tension. *Scientific reports*, *10*(1), 8693.

McPherson, M. J., Dolan, S. E., Durango, A., Ossandon, T., Valdés, J., Undurraga, E. A., Jacoby, N., Godoy, R. A., & McDermott, J. H. (2020). Perceptual fusion of musical

notes by native amazonians suggests universal representations of musical intervals. *Nature communications*, *11*(1), 2786.

Jakubowski, K., Polak, R., Rocamora, M., Jure, L., & Jacoby, N. (2022). Aesthetics of musical timing: Culture and expertise affect preferences for isochrony but not synchrony. *Cognition*, *227*, 105205.

Wagner, B., Sturdy, C. B., Weisman, R. G., & Hoeschele, M. (2022). Pitch chroma information is processed in addition to pitch height information with more than two pitch-range categories. *Attention, Perception, & Psychophysics*, *84*(5), 1757–1771.

Anglada-Tort, M., Harrison, P. M., Lee, H., & Jacoby, N. (2023). Large-scale iterated singing experiments reveal oral transmission mechanisms underlying music evolution. *Current Biology*.

Hardy, M. D., Thompson, B. D., Krafft, P., & Griffiths, T. L. (2023). Resampling reduces bias amplification in experimental social networks. *Nature Human Behaviour*, *7*(12), 2084–2098.

Liu, J., Hilton, C. B., Bergelson, E., & Mehr, S. A. (2023). Language experience predicts music processing in a half-million speakers of fifty-four languages. *Current Biology*, *33*(10), 1916–1925.

Sucholutsky, I., Muttenthaler, L., Weller, A., Peng, A., Bobu, A., Kim, B., Love, B. C., Grant, E., Groen, I., Achterberg, J., et al. (2023). Getting aligned on representational alignment. *arXiv preprint arXiv:2310.13018*.

Wagner, B., Šlipogor, V., Oh, J., Varga, M., & Hoeschele, M. (2023). A comparison between common marmosets (callithrix jacchus) and human infants sheds light on traits proposed to be at the root of human octave equivalence. *Developmental Science*, *26*(5), e13395.

Jacoby, N., Polak, R., Grahn, J. A., Cameron, D. J., Lee, K. M., Godoy, R., Undurraga, E. A., Huanca, T., Thalwitzer, T., Doumbia, N., et al. (2024). Commonality and variation in mental representations of music revealed by a

cross-cultural comparison of rhythm priors in 15 countries. *Nature Human Behaviour*, 1–32.

Marjieh, R., Harrison, P. M., Lee, H., Deligiannaki, F., & Jacoby, N. (2024). Timbral effects on consonance disentangle psychoacoustic mechanisms and suggest perceptual origins for musical scales. *Nature Communications*, *15*(1), 1482.

Marjieh, R., Jacoby, N., Peterson, J. C., & Griffiths, T. L. (2024). The universal law of generalization holds for naturalistic stimuli. *Journal of Experimental Psychology: General*, *153*(3), 573.

Marjieh, R., Sucholutsky, I., van Rijn, P., Jacoby, N., & Griffiths, T. L. (2024). Large language models predict human sensory judgments across six modalities. *Scientific Reports*, *14*(1), 21445.

Ozaki, Y., Tierney, A., Pfordresher, P. Q., McBride, J. M., Benetos, E., Proutskova, P., Chiba, G., Liu, F., Jacoby, N., Purdy, S. C., et al. (2024). Globally, songs and instrumental melodies are slower and higher and use more stable pitches than speech: A registered report. *Science advances*, *10*(20), eadm9797.

Wagner, B., Toro, J. M., Mayayo, F., & Hoeschele, M. (2024). Do rats (rattus norvegicus) perceive octave equivalence, a critical human cross-cultural aspect of pitch perception? *Royal Society Open Science*, *11*(5), 221181.

Zatorre, R. J. (2024). *From perception to pleasure: The neuroscience of music and why we love it*. Oxford University Press.

Appendix

Supporting Information

Table A1

Demographics of the lower and upper experience non-musician subgroups, as well as the musician groups.

Task	Group	N	N_m	N_f	N_o	M_{age}	SD_{age}	M_{yme}	SD_{yme}	$Range$
Similarity (Mel.)	No Exp.	102	66	36	0	39.8	11.6	0	0	$0-0$
Similarity (Mel.)	Some Exp.	92	54	37	1	41.0	12.8	7.3	8.9	$0.5-53$
Similarity (Mel.)	Musicians	41	19	15	7	30.0	8.3	19.9	7.9	$11-41$
Singing	No Exp.	50	30	20	0	42.5	11.0	0	0	$0-0$
Singing	Some Exp.	49	30	19	0	43.8	11.3	7.6	9.8	$0.5-55$
Singing	Musicians	42	15	26	1	31.9	10.3	21.2	9.4	$12-46$
Similarity (Ton.)	No Exp.	94	57	37	0	40.9	10.4	0	0	$0-0$
Similarity (Ton.)	Some Exp.	92	52	39	1	39.5	10.1	5.7	6.0	$1-34$
Similarity (Ton.)	Musicians	30	14	10	6	32.4	10.6	22.2	9.6	$12-46$

Note: The measures are: N total number of participants. N_m, N_f, N_o number of participants that self-identified as male, female, and other, respectively. M_{age}, SD_{age} mean and standard deviation of age. M_{yme}, SD_{yme}, $Range$ mean, standard deviation and range of reported years of musical experience. 'Similarity (Mel.)' and 'Similarity (Ton.)' correspond to similarity over melodies and isolated tones, respectively.

Figure A1

Pitch imitation through singing. Target vs. response pitch distributions for musicians and non-musicians (using a Guassian kernel with $\sigma = 1.1$ semitones determined through 5-fold cross validation; density normalized relative to a uniform distribution).

Figure A2

Normalized stress curves as a function of embedding dimensions as applied to the different similarity matrices in Supplementary Figure A4. Dashed red line indicates the 0.15 threshold above which MDS fit is deemed poor (Kruskal, 1964). Based on this analysis, we selected three-dimensional MDS for presenting the results in the paper.

Figure A3

Raw similarity matrices for the different behavioral paradigms considered in the paper.

Figure A4

Smoothed similarity matrices by averaging the raw matrices in Figure A3 over their diagonals for the different behavioral paradigms considered in the paper.

Figure A5

Simulated singing responses and their corresponding similarity matrices and MDS solutions.

A. Noisy linear response. B. Noisy linear response with register saturation. C. Singing an octave above or below a tone. D. Imitating along the circle of fifths. E. Chroma matching.

Figure A6

Three-dimensional multidimensional scaling solutions for the raw unprocessed behavioral similarity matrices in Supplementary Figure A3. Left to right: similarity judgments over melodies that differ by a transposition, free imitation of two-note melodies via singing, and similarity judgments over pairs of isolated tones.

Figure A7

Fitted model similarity matrices for the different behavioral paradigms considered.

Table A2

Full list of model parameter values and their 95% confidence intervals.

Task	Group	Intercept	Linear	Octave	Tritone	Perfect	σ_o
Similarity (Mel.)	No Exp.	0.12 ± 0.03	0.69 ± 0.06	0.08 ± 0.02	0.01 ± 0.01	0.01 ± 0.01	0.63
Similarity (Mel.)	Some Exp.	0.12 ± 0.03	0.57 ± 0.07	0.16 ± 0.03	0.02 ± 0.02	0.01 ± 0.01	0.64
Similarity (Mel.)	Musicians	0.07 ± 0.05	0.21 ± 0.07	0.43 ± 0.05	0.00 ± 0.00	0.03 ± 0.02	0.51
Singing	No Exp.	0.16 ± 0.02	0.17 ± 0.05	0.08 ± 0.04	0.00 ± 0.00	0.00 ± 0.00	2.33
Singing	Some Exp.	0.17 ± 0.02	0.08 ± 0.03	0.18 ± 0.06	0.00 ± 0.00	0.00 ± 0.00	2.21
Singing	Musicians	0.19 ± 0.01	0.03 ± 0.02	0.48 ± 0.05	0.01 ± 0.00	0.00 ± 0.00	1.97
Similarity (Ton.)	No Exp.	0.12 ± 0.03	1.04 ± 0.05	0.00 ± 0.00	0.00 ± 0.00	0.01 ± 0.01	0.25
Similarity (Ton.)	Some Exp.	0.10 ± 0.05	0.96 ± 0.06	0.04 ± 0.04	0.00 ± 0.01	0.03 ± 0.02	0.21
Similarity (Ton.)	Musicians	-0.04 ± 0.11	0.40 ± 0.13	0.46 ± 0.08	0.16 ± 0.05	0.07 ± 0.06	0.37

Table A3

Full list of evaluation metrics and their 95% confidence intervals using split-half bootstrap over participants with 1,000 repetitions.

Task	Group	R^2	r_{dd}	r_{mm}	r_{dm}	r
Similarity (Mel.)	No Exp.	$.95 \pm .01$	$.99 \pm .00$	$.99 \pm .00$	$.97 \pm .00$	$.98 \pm .00$
Similarity (Mel.)	Some Exp.	$.95 \pm .02$	$.99 \pm .01$	$.99 \pm .01$	$.97 \pm .01$	$.98 \pm .00$
Similarity (Mel.)	Musicians	$.94 \pm .02$	$.97 \pm .03$	$.99 \pm .02$	$.96 \pm .02$	$.98 \pm .00$
Singing	No Exp.	$.54 \pm .12$	$.83 \pm .07$	$.98 \pm .05$	$.72 \pm .04$	$.80 \pm .03$
Singing	Some Exp.	$.53 \pm .13$	$.73 \pm .11$	$.96 \pm .10$	$.70 \pm .07$	$.84 \pm .04$
Singing	Musicians	$.92 \pm .03$	$.95 \pm .02$	$.99 \pm .00$	$.96 \pm .01$	$.99 \pm .00$
Similarity (Ton.)	No Exp.	$.89 \pm .01$	$0.96 \pm .01$	$1.00 \pm .00$	$.94 \pm .00$	$.96 \pm .00$
Similarity (Ton.)	Some Exp.	$.88 \pm .02$	$.94 \pm .01$	$.99 \pm .00$	$.93 \pm .00$	$.97 \pm .00$
Similarity (Ton.)	Musicians	$.48 \pm .10$	$.53 \pm .08$	$.96 \pm .07$	$.66 \pm .05$	$.93 \pm .04$

Note: The measures are: R^2 coefficient of determination, r_{dd} data-data Pearson correlation, r_{mm} model-model, Pearson correlation, r_{dm} data-model Pearson correlation, and r data-model correlation corrected for attenuation (see Methods for full details).

Figure A8

Three-dimensional multidimensional scaling solutions for the fitted model similarity matrices. Left to right: similarity judgments over melodies that differ by a transposition, free imitation of two-note melodies via singing, and similarity judgments over pairs of isolated tones.

Figure A9

Recording interface for the online singing paradigm.

Figure A10

Comparing our online response pitch distributions to the in-lab response distributions of Jacoby et al. (2019) (using a Guassian kernel with $\sigma = 1.1$; density normalized relative to a uniform distribution).

Figure A11

Comparison between resulting similarity matrices based on our online data and the in-lab data of Jacoby et al. (2019) shown in Supplementary Figure A10. The results show high consistency of the similarity matrices between our online data and the in-lab data (r = .93, p < 0.001 for non-musicians, and r = .95, p < 0.001 for musicians)

Figure A12

*Different geometrical representations for the structure of musical pitch as proposed by Roger Shepard. Illustrations are redrawn based on the original designs shown in Shepard (1982a). **A.** A simple helix. **B.** A double helix. **C.** A double helix wound around a torus. Musical note values as well as the chroma circle and circle of fifths are indicated.*