Predicting visual search from neural similarity

Predicting cued and oddball visual search performance from neural representational similarity

Lu-Chun Yeh[1,2,*], Sushrut Thorat[2,3], Marius V. Peelen[2]

[1]Mathematical Institute, Department of Mathematics and Computer Science, Physics, Geography, Justus-Liebig-University Gießen, 35392 Gießen, Germany
[2]Donders Institute for Brain, Cognition and Behaviour, Radboud University, 6525 GD Nijmegen, The Netherlands
[3]Institute of Cognitive Science, University of Osnabrück, 49090 Osnabrück, Germany

*Corresponding author:
Lu-Chun Yeh
Email: luchun.yeh@gmail.com
Mathematical Institute
Justus Liebig University Gießen
Arndtstraße 2
35392 Gießen, Germany

Conflict of interest statement:
The authors declare no competing financial interests.

Acknowledgements:
This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No. 725970).

Abstract

Capacity limitations in visual tasks can be observed when the number of task-related objects increases. An influential idea is that such capacity limitations are determined by competition at the neural level: two objects that are encoded by shared neural populations interfere more in behavior (e.g., visual search) than two objects encoded by separate neural populations. However, the neural representational similarity of objects varies across brain regions and across time, raising the question of where and when competition determines task performance. Furthermore, it is unclear whether the association between neural representational similarity and task performance is common or unique across tasks. Here, we used neural representational similarity derived from fMRI, MEG, and deep neural networks (DNN) to predict performance on two visual search tasks involving the same objects and requiring the same responses but differing in instructions: cued visual search and oddball visual search. Separate groups of participants viewed the individual objects in neuroimaging experiments to establish the neural representational similarity between those objects. Results showed that performance on both search tasks could be predicted by neural representational similarity throughout the visual system (fMRI), from 80 msec after onset (MEG), and in all DNN layers. Stepwise regression analysis, however, revealed task-specific associations, with unique variability in oddball visual search performance predicted by early/posterior neural similarity, and unique variability in cued visual search task performance predicted by late/anterior neural similarity. These results reveal that capacity limitations in superficially similar visual search tasks may reflect competition at different stages of visual processing.

Keywords: Visual search, representational similarity analysis, fMRI, MEG, DNN

Significance Statement

Visual search for target objects is slowed down by the presence of distractors, but not all distractors are equally distracting – the more similar a distractor is to the target, the more it slows down search. Here, we used fMRI, MEG, and a deep neural network to reveal where, when, and how neural similarity between targets and distractors predicts visual search performance across two search tasks: oddball visual search (locating the different-looking object) and cued visual search (locating the cued object). Results also revealed brain regions, time points, and feature levels that predicted task-unique performance. These results provide a neural basis for similarity theories of visual search and show that this neural basis differs across visual search tasks.

Introduction

Our daily-life environments contain multiple objects that are impossible to process all at once. According to the biased competition model of attention (Desimone & Duncan, 1995), this limitation is reflected in competition for neural representation in visual cortex, with attention being the mechanism that resolves this competition. A central tenet of the biased competition model is that competitive interactions are strongest between stimuli that activate neurons in nearby regions of visual cortex (Desimone, 1998). While most early studies focused on competition in visuotopically organized areas (e.g., Reynolds et al., 1999), more recent work has provided evidence that this principle extends to the representational space of objects in ventral temporal cortex (VTC; Reddy & Kanwisher, 2007; Kliger & Yovel, 2020; Bao & Tsao, 2020).

If the level of competition between objects is determined by their representational similarity in visual cortex, we would expect this to be reflected in behavior as well. Indeed, several studies have linked neural representational similarity in visual cortex to visual search efficiency (e.g., Sripati et al., 2010; Proklova et al., 2016), providing a link between neural similarity and stimulus similarity, as postulated in theories of visual search (Duncan & Humphreys, 1989). A more general link to behavior was demonstrated by a series of functional magnetic resonance imaging (fMRI) studies that related neural representational similarity to performance on multiple visual tasks (visual search, visual categorization, visual working memory, visual awareness; Cohen et al., 2014; 2015; 2017). In these studies, objects that evoked relatively similar fMRI activity patterns, when presented in isolation, were found to interfere more in these visual tasks. For example, participants were faster to search for a car among faces (relatively low neural similarity) than for a car among phones (relatively high neural similarity). For all tasks, this relationship was most strongly observed in ventral and lateral occipitotemporal cortex. Integrating the findings across studies, the authors concluded that the representational similarity of objects in visual cortex reflects "a stable architecture of object representation that is a primary bottleneck for many visual behaviors" (Cohen et al., 2017).

One interpretation of these findings is that different kinds of visual judgments involving the same set of objects would be limited by the objects' representational similarity in the same parts of visual cortex. Alternatively, the relationship between neural representational similarity and visual task performance may differ across tasks. For example, tasks that rely more on low-level features could be constrained by the

objects' representational similarity in low-level visual cortex, whereas tasks relying on matching visual input to memory templates may be constrained by representational similarity in high-level visual cortex (Cohen et al., 2017). In the present study, we aimed to reveal the common and unique representational stages that constrain two superficially similar visual search tasks: cued visual search (Wolfe, 2020) and oddball visual search (Arun, 2012). As an example of these tasks, consider a fruit basket containing an apple and three oranges; on one occasion we may search for the apple (*cued visual search*), while on another occasion, we may search for the different-looking object (*oddball visual search*). These tasks involve the same visual input and require the same response. However, previous research has shown that only performance on the cued visual search task is influenced by the categorical similarity of the objects (Belke et al., 2008, Moores et al., 2003; Telling et al., 2010; Yeh & Peelen, 2022). This raises the question of how performance on these tasks relates to the objects' neural representational similarity in visual cortex, both spatially (fMRI) and temporally (magnetoencephalography; MEG).

Here, using the approach of Cohen et al. (2017), we related performance on cued and oddball visual search tasks to neural representational similarity using fMRI, MEG, and a deep neural network (DNN). This design allowed us to test where and when neural representational similarity predicts task performance that is common and/or unique to cued and oddball visual search, thereby informing theories of visual search.

Figure 1. Stimuli and tasks. (A) All stimuli used in the experiments. (B) In the behavioral experiments, stimuli were paired based on categorical and perceptual similarity (Yeh & Peelen, 2022), for a total of 32 pairs. (C) Task procedure of the cued visual search task. Participants were asked to search for a predefined target (in Chinese, the cue in English was not shown in the real experiment) and press the button corresponding to the target location. (ITI: intertrial interval) (D) Task procedure of the oddball visual search task. Participants were asked to search for an odd stimulus and press the button corresponding to the target location. (E) Task procedure of the same/different task. Participants were asked to judge whether the two objects were the same or different.

Materials and Methods

Visual tasks

We examined competition at the behavioral level in three visual tasks involving the same object set (Figure 1A): cued visual search, oddball visual search, and a same/different task. Reaction time (RT) data were taken from previous studies, each involving a different group of participants (cued visual search task (N=16) and same/different task (N=24): Yeh & Peelen, 2022; oddball visual search task (N=16): Proklova et al., 2016). For all analyses, we took the reciprocal of RT (1/RT) as a measure of dissimilarity (i.e., faster responses indicate higher dissimilarity), following previous recommendations (Arun, 2012).

In the cued visual search task (Figure 1C), participants indicated the location of the object that was cued on that trial. In the oddball visual search task (Figure 1D), participants indicated the location of the oddball object. Finally, in the same/different task (Figure 1E), participants indicated whether the two objects were the same or different. We added the same/different task based on previous research showing that variations in RT across object pairs in the same/different task are highly correlated with variations in RT in the oddball task (Jacob & Arun, 2020). While the oddball visual search task shared the "search" aspect with the cued visual search task, the same/different task shared the stimulus displays with the cued visual search task. The three tasks had different procedures but shared the same stimuli (Figure 1A). Eight animate and eight inanimate objects were used as stimuli, and each object had four exemplars (64 stimuli in total). All stimuli were grayscaled and were presented on a gray background. For more details, see the methods of Experiment 1 and 2 in Yeh & Peelen (2022) and Experiment 1 in Proklova et al. (2016).

Neural measurements and representational dissimilarity

Neural responses evoked by each individual object were recorded with fMRI and MEG. These data were taken from previous studies (fMRI (N=18): Proklova et al., 2016; MEG (N=29): Proklova et al., 2019). During those recordings, only one object was presented at a time and no search task was performed.

The representational dissimilarity of the fMRI data was computed using the approach of Proklova et al. (2016), restricted to the 32 pairs used in the behavioral experiments (Figure 1B). Briefly, following Proklova et al. (2016), we constructed the spherical searchlight neighborhood for every voxel in the brain (100 voxels) and

computed the correlation between the beta values of the objects in each pair across the voxels, in each of the searchlight spheres. Then, the representational similarity values were transformed into dissimilarity values by subtracting the correlation values from 1.

The representational dissimilarity of the MEG data was computed using pairwise decoding analyses for each time point (10 msec) for each participant, following Proklova et al. (2019). Neural dissimilarity is reflected by the decoding accuracy: the higher the decoding accuracy, the greater the neural dissimilarity. Detailed information on this decoding analysis can be found in Proklova et al. (2019). We used the 32 pairs of neural dissimilarity results of magnetometers (Proklova et al. (2019) reported similar results for magnetometers and gradiometers). We combined data across the two experiments reported in Proklova et al. (2019).

Finally, we established the representational dissimilarity of the object set in AlexNet (Krizhevsky et al., 2017), a feedforward DNN for object classification. We first obtained activations elicited by the stimuli (individual objects) at each layer of AlexNet. For each relevant pair of stimuli, at each layer, the similarity between the activation patterns was computed using correlation. Then, the representational similarity values were transformed into dissimilarity values by subtracting the correlation values from 1. The schematic of the analysis approach is illustrated in Figure 2.

Figure 2. Schematic of analysis approach. Neural activity to individual objects was measured with fMRI, MEG, and DNN. These activity measures were used to compute the neural representational dissimilarity for 32 pairs of stimuli that were presented in the visual tasks. Finally, neural representational dissimilarity was used to predict task performance using regression analysis. This analysis can show where, when, and in which layer neural representational dissimilarity predicts task performance.

Relating neural representational dissimilarity to task performance

We used linear regression analysis to relate pairwise neural representational dissimilarity to pairwise task performance. We used the *z*-transformed neural dissimilarity to predict the *z*-transformed task performance (1/RT). For fMRI and MEG analyses, we used the dissimilarity values of 32 pairs from each participant to predict the group-average task performance, while for DNN analyses, we used the dissimilarity values obtained from AlexNet to predict task performance for each participant in the behavioral tasks. This resulted in beta maps (fMRI), beta timelines (MEG), and betas for each layer (DNN), reflecting the associations between neural representational dissimilarity and performance on each of the three tasks (Figure 2).

Predicting visual search from neural similarity

Furthermore, to explore unique associations between representational dissimilarity and task performance, we ran two-step regression analyses to (1) compare the cued visual search task with the oddball visual search task and (2) compare the cued visual search task with the same/different task. To calculate betas reflecting task-unique associations, we first ran a linear regression analysis using one task performance (e.g., cued visual search) to predict the other task performance (e.g., oddball visual search). Then, we ran another linear regression analysis using the *z*-transformed neural dissimilarity values to predict the *z*-transformed *residual* of the first regression analysis. Overall, we obtained four beta maps (fMRI), beta timelines (MEG), and betas for each layer (DNN) for three tasks. Two are for the cued visual search task when removing the effect of the oddball visual search task and the same/different task, one is for the oddball visual search task when removing the effect of the cued visual search task, and one is for the same/different task when removing the effect of the cued visual search task.

Statistical tests

To test the significance of the beta values, we used one-sample t-tests against zero and controlled the type I error for multiple comparisons. For the fMRI analyses, we used a voxel-level threshold of *p* < .001 (uncorrected) and a cluster-level threshold of *p* < .05 (FWE corrected) to control type I error. Only the values within visual cortex (including Brodmann areas 17, 18, 19, 20, 37) were included in the statistical tests. Clusters were only reported when the cluster size was larger than 50 voxels. For fMRI MNI y-coordinate, MEG, and DNN analyses, the statistical significance of correlations was tested using cluster-based nonparametric permutation one-sample *t*-tests against zero to determine the window of significant correlation, controlling for multiple comparisons (Maris & Oostenveld, 2007). The permutation test was with null distribution created from 1000 Monte Carlo random partitions using a cluster correction for type I error (p <.05, one-tailed).

Results

Correlations between visual tasks

Before examining the associations between neural representational similarity and task performance, we computed the correlations between performance on the three tasks using a split-half analysis (across participants), to test how these tasks are related. That is, we tested whether pairs that were easy in one task were also easy in another task. We first randomly assigned participants into two groups and then computed the correlation between the means of the two datasets both within and between tasks. We repeated this procedure 100 times and computed the average of the outputs. As expected based on previous findings (Jacob & Arun, 2020), performance on the oddball visual search task was closely related to performance on the same/different task, with the between-task correlation (r = 0.85) being close to the within-task correlations (same/different: r = 0.90; oddball: r = 0.97). This confirms that the same/different task and the oddball visual search task provided similar measures of pairwise task performance. The correlations between performance on these two tasks and performance on the cued visual search task were lower (oddball-cued: r = 0.71, same/different-cued: r = 0.76), also relative to the within-task correlation (cued: r = 0.94). This raises the possibility that oddball and cued visual search tasks are uniquely associated with neural representational similarity. At the same time, the overall high cross-task correlations also suggest that there is a substantial shared component driving performance in these tasks.

fMRI: Spatial associations between neural representational dissimilarity and task performance

To test for brain regions in which neural representational dissimilarity predicted task performance, we performed single regression analyses using a searchlight approach (see Materials and Methods). For each sphere, neural representational dissimilarity (based on responses evoked by objects presented in isolation) was used to predict pairwise task performance (Figure 2), separately for the three tasks. Results showed that performance on all three tasks was predicted by representational dissimilarity in both low- and high-level visual cortex (Figure 3A; Table 1), in line with previous reports (Proklova et al., 2016; Cohen et al., 2017). This was confirmed by an analysis that averaged beta values across x- and z-coordinates, with significantly positive beta values in both posterior and anterior visual cortex regions (Figure 5, solid

lines). These results thus reveal considerable overlap in the brain regions that predicted performance on each task.

Next, we tested for task-specific associations between neural representational dissimilarity and task performance by first regressing out performance on the oddball visual search task from performance on the cued visual search task (and vice versa). The same analysis was repeated for the same/different task and the cued visual search task. Results revealed several brain regions in which neural representational dissimilarity predicted variability in task performance that was unique to one of the tasks (Figure 3B; Table 1). Specifically, unique variability in cued visual search performance was predicted by relatively anterior regions in visual cortex, overlapping the fusiform gyrus, while unique variability in oddball visual search performance was predicted by more posterior regions. This result was replicated when including the same/different task instead of the oddball task (Figure 3C; Table 1), showing that these unique associations did not simply reflect differences in the displays of cued and oddball visual search tasks (Figure 1). The posterior-anterior difference was also clearly observed in the y-coordinate analysis (Figure 4), with the unique prediction of the cued visual search task strongest at y=-60 and the unique prediction of the oddball visual search task strongest at the most posterior parts of visual cortex (y=-100). These results thus reveal that performance on two highly similar visual search tasks are uniquely predicted by neural representational dissimilarity in different brain regions.

Associations	Side	p-value (FWE Corrected)	cluster size (voxels)	peak coordinate(x,y,z)	peak T-value
Cued visual search	Right	<.001	1227	42,-58,-16	10.51
		<.001	115	14,-84,-8	5.7
	Left	<.001	1506	-32,-48,-18	10.11
Oddball visual search	Right	<.001	825	44,-60,-12	9.24
	Left	<.001	2611	-38,-48,-22	9.14
Same/different task	Right	<.001†	4637	42,-58,-20	11.05
	Left			-42,-62,-14	10.12
Unique associations (Cued vs. Oddball)	Side	p-value (FWE Corrected)	cluster size (voxels)	peak coordinate(x,y,z)	peak T-value
Cued visual search	Right	<.001	258	40,-50,-14	7.81
		=.005	69	46,-80,-2	8.72
	Left	<.001	338	-32,-48,-18	11.41
		=.002	80	-46,-82,-2	6.04
Oddball visual search	Left	<.001	390	-20,-88,-14	7.30
Unique associations (Cued vs. S/D)	Side	p-value (FWE Corrected)	cluster size (voxels)	peak coordinate(x,y,z)	peak T-value
Cued visual search	Right	<.001	180	40,-66,-14	6.17
		<.001	114	46,-78,-2	7.91
	Left	<.001	271	-32,-48,-18	9.69
		=.001	92	-46,-80,-18	5.39
Same/different task	Right	<.001	356	26,-96,8	7.77
	Left	<.001	762	-20,-90,-6	7.02

Table 1. Significant clusters in the fMRI analyses. Peak coordinates are in MNI space. †The significant cluster for same/different task includes both right and left hemispheres.

Figure 3. fMRI searchlight maps relating neural representational dissimilarity to task performance. A) Clusters in which neural representational dissimilarity predicted task performance, separately for each task. B) Clusters in which neural representational dissimilarity predicted performance unique to the cued visual search task (red) and the oddball visual search task (blue). C) Clusters in which neural representational dissimilarity predicted performance unique to the cued visual search task (red) and the same/different task (green).

Figure 4. fMRI results across the visual hierarchy. Graphs show the average beta estimate along the y-coordinate axis for left (top panel) and right (bottom panel) hemispheres. The means were computed for every 5 mm in the MNI y-coordinate (averaging across the x and z coordinates). Solid lines show results from analyses relating neural representational dissimilarity to performance on each task separately. Dashed lines show results from analyses relating neural representational dissimilarity to performance on one task, after regressing out performance on another task (stated after the "-" symbol). Significant clusters (cluster-based permutation tests, $p < .05$, one-tailed) are highlighted in bold.

MEG: Temporal associations between neural representational dissimilarity and task performance

Recent MEG studies have shown that patterns of activity across MEG sensors can be used to decode object properties in a time-sensitive manner (Grootswagers et al., 2017; Robinson et al., 2023), revealing the representational dynamics of visual processing (Carlson et al., 2013; Cichy et al., 2014). Using this approach, we tested *when* neural representational dissimilarity predicts visual search performance. The regression analysis linking neural representational dissimilarity to task performance was otherwise identical to that performed on the fMRI data (Figure 2). Results showed that

performance on all three tasks was predicted by neural representational dissimilarity from 80 msec after stimulus onset (cluster-based $p < .001$; Figure 5). The analyses testing for task-specific associations revealed unique associations between neural representational dissimilarity and task performance of the oddball visual search task (cluster-based $p < .001$) and the same/different task (cluster-based $p < .001$) starting from around 80 ms after stimulus onset (Figure 6). Unlike the fMRI results, no unique association was found between neural representational dissimilarity and cued visual search task performance. These results provide a clear temporal association between neural representational dissimilarity and task performance, and show that the unique association between neural representational dissimilarity and cued visual search task performance that we observed in fMRI was not captured by MEG activity patterns.

Figure 5. MEG results showing temporal associations between neural representational dissimilarity and task performance. MEG results of the regression analyses using neural representational dissimilarity to predict cued visual search task performance (left panel), oddball visual search performance (middle panel), and same/different task performance (right panel). Solid lines show results from analyses relating neural representational dissimilarity to performance on each task separately. Dashed lines show results from analyses relating neural representational dissimilarity to performance on one task, after regressing out performance on another task (stated after the "-" symbol). Significant clusters (cluster-based permutation tests, $p < .05$, one-tailed) are highlighted in bold.

DNN: Layer-wise associations between representational dissimilarity and task performance

Finally, we used a feedforward DNN model (AlexNet) to explore which layers of the hierarchical network predicted task performance. We followed the regression approach we used in the fMRI/MEG analysis but now using the representational dissimilarity

computed from the patterns of activation in DNN layers (Figure 2). Results showed that performance on all three tasks was predicted by the representational dissimilarity of all ten selected layers (cluster-based p <.001; Figure 6): the Input layer, the five convolutional layers (Conv1, Conv2, Conv3, Conv4, and Conv5), the three fully-connected layers (FC6, FC7, FC8), and the softmax layer on the readout (SM). Here, we also found task-specific associations. The cued visual search task performance was predicted by representational dissimilarity in the deeper layers, including FC6, FC7, FC8, and SM (cluster-based p =.005) after regressing out oddball visual search performance, and was predicted by representational dissimilarity in FC7, FC8, and SM (cluster-based p =.0036) after regressing out same/different task performance (Figure 6). By contrast, oddball visual search and same/different task performance were predicted by all layers after regressing out cued visual search performance, and contrary to the cued visual search, most strongly with the earlier layers (cluster-based p <.001).

Figure 6. DNN results showing associations between representational dissimilarity and task performance. DNN results of the regression analyses using representational dissimilarity to predict the cued visual search performance (left panel), oddball visual search performance (middle panel), and same/different task performance (right panel). Solid lines show results from analyses relating representational dissimilarity to performance on each task separately. Dashed lines show results from analyses relating neural representational dissimilarity to performance on one task, after regressing out performance on another task (stated after the "-" symbol). Significant clusters (cluster-based permutation tests, p < .05, one-tailed) are highlighted in bold.

Discussion

In this study, we tested whether, where, and when the pairwise neural representational similarity of objects predicts visual search performance (RT) involving these object

pairs. By using fMRI, MEG, and a DNN we established a detailed spatiotemporal association between neural representational similarity and visual search performance. Results showed that visual search performance was predicted by neural representational similarity in both high- and low-level regions of the visual cortex (fMRI), from 80 msec after onset (MEG), and in all DNN layers. When analyzed separately, similar brain-behavior associations were observed for a cued visual search task and an oddball visual search task. This shared component is in line with previous results showing that performance on different tasks can be predicted by the same stable neural similarity structure (Cohen et al., 2014; 2015; 2017).

Importantly, however, the pairwise variability of performance in the two visual search tasks was not identical, such that search for some pairs was relatively more difficult in one task than the other. Using stepwise regression analysis, we could relate these task-unique components of performance to neural representational similarity as well. Results showed that neural representational similarity in regions of high-level visual cortex (fMRI) and the late layers of a DNN predicted the unique component of the cued visual search task. By contrast, neural representational similarity in regions of low-level visual cortex (fMRI) and the early layers of a DNN predicted the unique component of the oddball visual search task. These results provide evidence that performance on superficially similar visual search tasks, involving the same stimuli and response, is nonetheless constrained by neural similarity at different stages of visual processing.

The finding that search performance is predicted by neural similarity in visual cortex is in line with theories that explain visual search efficiency in terms of stimulus similarity (Duncan & Humphreys, 1989). Specifically, search performance has been proposed to be determined by a combination of target-distractor and distractor-distractor similarity (the pairwise approach in the current study only considers target-distractor similarity). The similarity theory of visual search used the term similarity to refer to similarity along multiple dimensions, with the relevant dimension depending on the experimental stimuli (e.g., color, shape). For example, in an experiment where color was the only manipulated dimension, color similarity would determine search efficiency (Duncan & Humphreys, 1989). In the current experiment, we investigated search for familiar real-world objects that differed along multiple feature dimensions (e.g., texture, shape). Interestingly, the association between neural similarity and visual search was observed throughout the visual cortex (fMRI), across a long time window

(MEG), and at different hierarchical levels of visual feature representation (DNN). These findings therefore suggest that the similarity that predicts visual search performance for familiar objects is multidimensional, likely consisting of a combination of low- and high-level features.

At the same time, our results show that the similarity dimension that determines search performance depends on the type of search task, even for identical stimuli. Specifically, similarity at higher levels of visual cortex and in later layers of a neural network predicted the unique component of cued visual search. These unique associations may reflect features that are diagnostic of the category (animate/inanimate) of the objects, in line with previous behavioral and EEG studies that found that cued visual search is influenced by categorical similarity (Belke et al., 2008, Moores et al., 2003; Telling et al., 2010; Yeh & Peelen, 2022). Furthermore, in a previous fMRI study (Proklova et al., 2016), we showed that the categorical similarity of the object set was represented in high-level visual cortex regions that overlap with the regions that predicted the unique cued visual search performance in the current study. Finally, the representational similarity in later layers of AlexNet have been shown to follow a categorical organization (Khaligh-Razavi & Kriegeskorte, 2014).

One possibility is that the high-level component observed for the cued visual search task reflects an additional template-matching stage, comparing visual input to a target template held in working memory (Cohen et al., 2017; Wolfe, 2021; Eimer, 2014). In this scenario, the cued visual search task could be equivalent to the oddball visual search task plus an additional template-matching stage. Interestingly, however, our results also revealed unique brain-behavior associations for the oddball task, particularly in earlier stages of visual processing. These results suggest that different stimulus dimensions can be flexibly emphasized to support different visual search tasks on the same stimulus set. This is in line with a growing literature demonstrating the flexible adjustment of top-down attentional templates, for example based on expected distractor characteristics (Lee & Geng, 2020; Lerebourg et al., 2022, Boettcher et al., 2020).

The current MEG results showed that representational similarity from 80 ms after stimulus onset reliably predicted visual search performance. Surprisingly, however, the unique component of cued visual search performance was not reflected in the representational structure of MEG at any time point, even though unique associations were observed in comparable fMRI and DNN analyses. These results indicate that

while MEG sensor patterns are highly sensitive to the low-/mid-level object features that predict visual search performance in general, they are not sensitive to the high-level (e.g., categorical) features that predict the unique aspect of cued visual search performance. This finding nonetheless matches a previous study in which MEG patterns could not discriminate between perceptually matched object categories, unlike fMRI patterns (Proklova et al., 2019). Of note, we have also performed the current analysis on an EEG dataset and similarly observed no significant association between EEG representational similarity and the unique aspect of cued visual search performance (data not shown). The lack of sensitivity of M/EEG to high-level object features means that it remains an open question when during visual processing neural representational similarity predicts the unique aspect of cued visual search.

Our approach has several limitations. First, our analyses were done across different groups of participants, focusing on commonalities across groups. This approach prevents analyses that link representational structure to behavioral performance at the individual-subject level (Charest et al., 2014). Second, we used a stimulus set in which half the object pairs were matched for outline shape and that included a clear categorical distinction. Higher-level dimensions may become particularly relevant in visual search for objects that are perceptually similar (Yeh & Peelen, 2022). Therefore, future studies would need to replicate our results with a larger and more diverse stimulus set. Third, our search tasks were highly simplified, involving only one distractor object, fixed presentation locations, and no scene context. By contrast, real-world search typically includes many distractors, variable locations, and meaningful context. Finally, the approach of associating stable neural architecture to visual search performance is, by definition, indirect, such that a positive association between neural similarity and task performance in a particular brain region (or time point) does not prove that that brain region causally determines task performance.

Conclusion. In summary, our results reveal a strong association between neural representational similarity and visual search performance: when the neural representation of a target object was relatively dissimilar to the neural representation of a distractor object, visual search was relatively fast. The finding that unique performance on two superficially similar visual search tasks was predicted by neural similarity in different visual cortex regions and in different DNN layers shows that neural constraints on visual task performance are, to some extent, task specific.

Capacity limitations in superficially similar visual search tasks may thus reflect competition at different stages of visual processing.

References

Arun, S. P. (2012). Turning visual search time on its head. *Vision Research, 74*(1), 86-92.

Bao, P., & Tsao, D. Y. (2018). Representation of multiple objects in macaque category-selective areas. *Nature communications, 9*(1), 1-16.

Belke, E., Humphreys, G. W., Watson, D. G., Meyer, A. S., & Telling, A. L. (2008). Top-down effects of semantic knowledge in visual search are modulated by cognitive but not perceptual load. *Perception & Psychophysics, 70*(8), 1444-1458.

Boettcher, S. E., van Ede, F., & Nobre, A. C. (2020). Functional biases in attentional templates from associative memory. *Journal of Vision, 20*(13), 7.1-10.

Carlson, T., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of object vision: the first 1000 ms. *Journal of vision, 13*(10), 1.1-19.

Charest, I., Kievit, R. A., Schmitz, T. W., Deca, D., & Kriegeskorte, N. (2014). Unique semantic space in the brain of each beholder predicts perceived similarity. *Proceedings of the National Academy of Sciences, 111*(40), 14565-14570.

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space and time. *Nature neuroscience, 17*(3), 455-462.

Cohen, M. A., Alvarez, G. A., Nakayama, K., & Konkle, T. (2017). Visual search for object categories is predicted by the representational architecture of high-level visual cortex. *Journal of Neurophysiology, 117*(1), 388-402.

Cohen, M. A., Konkle, T., Rhee, J. Y., Nakayama, K., & Alvarez, G. A. (2014). Processing multiple visual objects is limited by overlap in neural channels. *Proceedings of the National Academy of Sciences of the United States of America, 111*(24), 8955-8960.

Cohen, M. A., Nakayama, K., Konkle, T., Stantić, M., & Alvarez, G. A. (2015). Visual awareness is limited by the representational architecture of the visual system. *Journal of Cognitive Neuroscience, 27*(11), 2240-2252.

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention. *Annual Review of Neuroscience, 33*(18), 193-222.

Desimone, R. (1998). Visual attention mediated by biased competition in extrastriate visual cortex. *Philosophical Transactions of the Royal Society of London. Series B: Biological Sciences, 353*(1373), 1245-1255.

Duncan, J., & Humphreys, G. W. (1989). Visual search and stimulus similarity. *Psychological review, 96*(3), 433-458.

Duncan, J., Humphreys, G., & Ward, R. (1997). Competitive brain activity in visual attention. *Current opinion in neurobiology, 7*(2), 255-261.

Eimer, M. (2014). The neural basis of attentional control in visual search. *Trends in cognitive sciences, 18*(10), 526-535.

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding dynamic brain patterns from evoked responses: A tutorial on multivariate pattern analysis applied to time series neuroimaging data. *Journal of cognitive neuroscience, 29*(4), 677-697.

Jacob, G., & Arun, S. P. (2020). How the forest interacts with the trees: Multiscale shape integration explains global and local processing. *Journal of Vision, 20*(10), 20.1-21.

Kliger, L., & Yovel, G. (2020). The functional organization of high-level visual cortex determines the representation of complex visual stimuli. *Journal of Neuroscience*, 40(39), 7545-7558.

Khaligh-Razavi, S. M., & Kriegeskorte, N. (2014). Deep supervised, but not unsupervised, models may explain IT cortical representation. *PLoS computational biology, 10*(11), e1003915.

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2017). ImageNet Classification with Deep Convolutional Neural Networks. *Communications of the ACM, 60*(6), 84-90.

Lee, J., & Geng, J. J. (2020). Flexible weighting of target features based on distractor context. *Attention, Perception, & Psychophysics, 82*, 739-751.

Lerebourg, M., de Lange, F. P., & Peelen, M. V. (2022). Expected Distractor Context biases the Attentional Template for Target Shapes. *bioRxiv*, 2022-10. https://doi.org/10.1101/2022.10.18.512686

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG-and MEG-data. *Journal of neuroscience methods, 164*(1), 177-190.

Moores, E., Laiti, L., & Chelazzi, L. (2003). Associative knowledge controls deployment of visual selective attention. *Nature neuroscience, 6*(2), 182-189.

Proklova, D., Kaiser, D., & Peelen, M. V. (2016). Disentangling representations of object shape and object category in human visual cortex: The animate–inanimate distinction. *Journal of cognitive neuroscience, 28*(5), 680-692.

Proklova, D., Kaiser, D., & Peelen, M. V. (2019). MEG sensor patterns reflect perceptual but not categorical similarity of animate and inanimate objects. *Neuroimage, 193*, 167-177.

Robinson, A. K., Quek, G. L., & Carlson, T. A. (2023). Visual Representations: Insights from Neural Decoding. *Annual Review of Vision Science, 9*,2.1-2.23.

Reddy, L., & Kanwisher, N. (2007). Category selectivity in the ventral visual pathway confers robustness to clutter and diverted attention. *Current Biology, 17*(23), 2067-2072.

Reynolds, J. H., Chelazzi, L., & Desimone, R. (1999). Competitive mechanisms subserve attention in macaque areas V2 and V4. *Journal of Neuroscience, 19*(5), 1736-1753.

Sripati, A. P., & Olson, C. R. (2010). Global image dissimilarity in macaque inferotemporal cortex predicts human visual search efficiency. *Journal of Neuroscience, 30*(4), 1258-1269.

Telling, A. L., Kumar, S., Meyer, A. S., & Humphreys, G. W. (2010). Electrophysiological Evidence of Semantic Interference in Visual Search. *Journal of Cognitive Neuroscience, 22*(10), 2212-2225.

Wolfe, J. M. (2020). Visual search: How do we find what we are looking for?. *Annual review of vision science, 6*, 539-562.

Wolfe, J. M. (2021). Guided Search 6.0: An updated model of visual search. *Psychonomic Bulletin & Review, 28*(4), 1060-1092.

Yeh, L.-C., & Peelen, M. V. (2022). The time course of categorical and perceptual similarity effects in visual search. *Journal of Experimental Psychology: Human Perception and Performance, 48*(10), 1069-1082.