Rethinking simultaneous suppression in visual cortex via compressive spatiotemporal population receptive fields

Authors

Eline R Kupers[1*], Insub Kim[1], Kalanit Grill-Spector[1,2]

Affiliations

[1] Department of Psychology, Stanford University, CA, USA
[2] Wu Tsai Neurosciences Institute, Stanford University, CA, USA
* Corresponding author. Email to: ekupers@stanford.edu

Acknowledgements
We thank Brian Wandell for fruitful discussions. This research was supported by the US NIH NEI R01 EY023915 (KGS). Funders had no role in study design, data collection and analysis, or decision to submit the manuscript.

Author contributions
E.R.K and K.G.S. designed the experiment. K.G.S. provided funding. E.R.K. and I.K. collected data and wrote computational framework. E.R.K. analyzed the data. K.G.S. oversaw computational framework and data analysis. E.R.K and K.G.S. wrote the manuscript. I.K. provided feedback on manuscript.

1 Abstract

When multiple visual stimuli are presented simultaneously in the receptive field, the neural response is suppressed compared to presenting the same stimuli sequentially. The prevailing hypothesis suggests that this suppression is due to competition among multiple stimuli for limited resources within receptive fields, governed by task demands. However, it is unknown how stimulus-driven computations may give rise to simultaneous suppression. Using fMRI, we find simultaneous suppression in single voxels, which varies with both stimulus size and timing, and progressively increases up the visual hierarchy. Using population receptive field (pRF) models, we find that compressive spatiotemporal summation rather than compressive spatial summation predicts simultaneous suppression, and that increased simultaneous suppression is linked to larger pRF sizes and stronger compressive nonlinearities. These results necessitate a rethinking of simultaneous suppression as the outcome of stimulus-driven compressive spatiotemporal computations within pRFs, and open new opportunities to study visual processing capacity across space and time.

2 Introduction

The human visual system has limited processing capacity. We are worse at processing multiple stimuli presented at once than when the identical stimuli are shown one after the other in the same location. This drop in performance has been observed in a variety of visual tasks, such as searching for a target among distractors[1,2], recognizing an object when surrounded by flankers[3], or keeping multiple items in short-term visual working memory[4].

A neural phenomenon attributed to limited visual capacity is simultaneous suppression: A reduced response when multiple visual stimuli are presented at once than when the identical stimuli are shown one after the other in sequence[5-12]. Simultaneous suppression is prevalent and robust: it is observed across visual cortex, from the level of single-neuron spiking[5-7], all the way to the level of entire visual areas using fMRI[8-12], with large effect sizes: up to 2-fold amplitude differences between sequential and simultaneous presentations of otherwise identical stimuli[8,9,12].

A prevailing explanation linking simultaneous suppression to visual capacity is based on the influential theory of biased competition[7,8,13]. This theory argues that visual processing capacity is determined by the computational resources afforded by receptive fields, where the visual system prioritizes inputs that are behaviorally relevant for further processing. When a visual stimulus is presented alone in the receptive field, the item can be fully processed with the limited neural resources. However, when multiple stimuli are presented at once in the receptive field, the stimuli compete for neural resources, resulting in a reduced neural response. This explanation of stimuli competing for neural resources is linked to visual attention, as it has been suggested that competition can be governed by task or behavioral demands[13]. As such, a large body of research has examined how simultaneous suppression is modulated by visual attention[7,8,14-16] and stimulus context[10,11]. However, it is unknown how stimulus-driven computations within receptive fields may give rise to simultaneous suppression in the first place. Thus, the goal of the present study is to operationalize and elucidate the computational mechanisms underlying simultaneous suppression in human visual cortex.

A key prediction stemming from the biased competition theory is that simultaneous suppression will only occur in neurons whose receptive fields are large enough to encompass several stimuli[9,12]. It is well documented that the size of receptive fields[17] and population receptive fields (pRFs, aggregate receptive field of the neuronal population in an fMRI voxel[18,19]) progressively increase from earlier to higher areas up the visual hierarchy. Consistent with this idea, several studies reported that simultaneous suppression systematically increases up the visual hierarchy and is absent in V1[7-9,12], suggesting that the lack of suppression in V1 is because its receptive fields are too

small to encompass multiple visual stimuli. However, there is an assumption in prior work, which is

that neurons sum inputs linearly over the duration of the stimulus[7,9,12,20]. This assumption has

emphasized research on how the spatial overlap between stimuli and the receptive field may affect

simultaneous suppression[8,9,12] and less on how stimulus timing may affect simultaneous suppression.

As stimuli have identical duration, size, and location across simultaneous and sequential

conditions, neurons summing linearly over visual space and linearly over stimulus duration are

predicted to respond identically in these conditions. Therefore, the lower responses for simultaneous

than sequential presentations suggest nonlinear, and in particular, subadditive summation. Although

linear summation within receptive fields is observed in some cases[21-23], violations of response

linearity in the human visual system have been extensively reported. Spatially, responses to bigger

stimuli are typically less than the sum of responses to smaller stimuli[22,24-27]. Temporally, responses

to longer stimuli are typically smaller than the sum of responses to shorter stimuli[28-44]. While both

hemodynamic[45-47] and neural[27,35,39-42,48-51] mechanisms may contribute to observations made with

fMRI, empirical and computational modeling studies suggest that the observed subadditivity is driven

by compressive summation of visual inputs within neurons' receptive fields across space[27,50] and

across time[33,36,38,40-44]. Therefore, rather than considering how context or task demands affect

simultaneous suppression, we asked: to what extent is simultaneous suppression a consequence of

compressive computations within receptive fields in visual cortex? Here, we consider two possible

classes of compressive neural mechanisms that may generate simultaneous suppression:

compressive spatial summation and compressive spatiotemporal summation.

Compressive spatial summation within the receptive field predicts that the response to

multiple stimuli presented together within the pRF (as in simultaneous conditions) will be lower than

the sum of responses to the individual stimuli shown alone (as in sequential conditions). As the

duration of stimuli are matched between the simultaneous and sequential conditions, the spatial

summation hypothesis predicts that the level of simultaneous suppression will depend only on the

spatial overlap between the stimuli and the pRF. As both average receptive field size and

compressive nonlinearities increase up the visual hierarchy[27,50], compressive spatial summation also

predicts that the level of simultaneous suppression will increase from earlier to later visual areas.

Compressive spatiotemporal summation within the receptive field predicts that simultaneous

suppression will not only depend on the spatial overlap between stimuli and the receptive field, but

also the timing of stimuli. This prediction is based on the empirical observation that neuronal

responses to visual stimuli vary over time, typically showing an initial strong transient response at

stimulus onset (lasting for 100-200 ms), followed by a weaker sustained response lasting for the

duration of the stimulus[32,42,44,52-55], and often a transient response at stimulus offset[42,44,54]. These

nonlinear temporal dynamics suggest that presenting all stimuli at once in the pRF (as in

simultaneous conditions) results in two transients (at stimulus onset and offset). This response will

be lower than the accumulated response induced by multiple visual transients when presenting

multiple stimuli one-by-one in rapid fashion (as in sequential conditions). Thus, the spatiotemporal

hypothesis predicts that the level of simultaneous suppression will depend on both the spatial overlap

between the stimuli and the pRF, and the difference in the number of visual transients between

simultaneous and sequential conditions. Similar to compressive spatial nonlinearities, compressive

temporal nonlinearities also increase up the visual hierarchy[39-42,44,51], predicting an increase in the

level of suppression as pRF size and spatiotemporal compression increase.

Here, we used fMRI and a computational pRF framework to distinguish between these

hypotheses. We conducted two fMRI experiments. In the first (SEQ-SIM, **Fig 1A**), we measured

responses to sequentially or simultaneously presented stimuli and examined how stimulus size and

timing affect the level of simultaneous suppression in each voxel of the visual system (**Fig 1B**). In

the second experiment (retinotopy, **Fig 1D**), we estimated each voxel's spatial pRF parameters and

used estimated parameters in a pRF modeling framework to predict the BOLD time series for each

voxel in the SEQ-SIM experiment. We then implemented several pRF models in our modeling

framework to computationally test our hypotheses. To test the compressive spatial summation

hypothesis, we used a compressive spatial summation (CSS) pRF model[27] as it successfully predicts

subadditive responses to stimuli of different sizes in pRFs across the visual hierarchy. To test the

compressive spatiotemporal summation hypothesis, we used a novel compressive spatiotemporal

(CST) summation pRF model[51], which captures pRF responses to a large range of spatial and

temporal stimulus conditions by modeling neural responses in units of visual degrees and

milliseconds.

3 Results

To investigate what factors affect simultaneous suppression, we designed an fMRI experiment in which participants viewed colorful patterned square stimuli in upper and lower quadrants while performing a 1-back RSVP letter task at fixation. Squares could either be presented sequentially (one after the other, in random order) or simultaneously (all at once) (**Fig 1A**). For each pair of sequential and simultaneous conditions, individual square presentation is identical in size and duration within an 8-s block such that linear summation of visual inputs in space and time will generate identical responses for both sequence types. To distinguish between spatial and spatiotemporal mechanisms of simultaneous suppression, we varied square size and timing (**Fig 1B,C**). Additionally, participants completed an independent retinotopy experiment[56] to delineate visual areas and estimate spatial pRF parameters in each voxel (**Fig 1D**).

In each visual area, we measured BOLD responses in voxels which pRF centers overlapped the quadrants with SEQ-SIM stimuli. We then determined how spatial and temporal stimulus properties affect simultaneous suppression for each pRF across visual areas spanning ventral, lateral, and dorsal processing streams. We predict that if simultaneous suppression is of spatial origin, there will be greater suppression in higher-level than early visual areas because those higher-level areas contain larger pRFs that will overlap multiple squares and also show greater spatial compression[27]. Additionally, we predict that varying square size but not timing will affect simultaneous suppression. If simultaneous suppression is of spatiotemporal origin, in addition to observing greater suppression for larger pRFs in higher-level areas, we also predict stronger suppression for long (1 s) than short (0.2 s) presentations because the former has longer sustained stimulus periods, resulting in four times fewer visual transients in the 8-s stimulus blocks than the latter (**Fig 1B**).

To give a gist of the data, we first show results from example voxels in early (V1) and higher-level (VO1/2) areas of the ventral stream. These visual areas differ in overall pRF size and spatial compression: V1 pRFs are small and typically overlap only one square, and VO1/2 pRFs are large and overlap multiple squares.

A *SEQ-SIM experiment*

B *SEQ-SIM conditions*

C *SEQ-SIM single stimulus run*

D *Retinotopy experiment*

Figure 1. Overview of fMRI experiments. (A) SEQ-SIM experiment. Example trial sequences for small and short stimuli. Four colorful squares were presented in the upper left and lower right quadrants, presented either sequentially in random order (left) or simultaneously (right) interspersed by blank periods to match the trial duration. Observers performed a 1-back RSVP letter task at fixation. Letter is enlarged for visibility. **(B) Stimulus conditions.** Square stimuli were shown in one of two presentation timings (0.2 s or 1 s) and in one of two sizes (4 deg^2 or 16 deg^2). Number of trials per block was adjusted to create a 4:1 ratio in number of transients (stimulus onsets or offsets) for short vs long durations. The number of transients indicated is based on a pRF overlapping all four squares, e.g., for 1-s sequentially-presented squares there are 16 transients per block: 4 stimulus frames x 2 on/offsets x 2 trials. If a pRF overlaps only a single square (time course not shown), the number of transients will be identical for SEQ and SIM pairs. For each SEQ-SIM pairing, individual squares were shown for the same duration within a single trial (red bracket). Trials were repeated within an 8-s block (black bracket), where square content was updated for each trial. **(C) Example of SEQ-SIM stimulus run.** A single 332-s SEQ-SIM run contained 16 8-s pseudo-randomized stimulus blocks, interspersed with 12-s blank periods. Data are analyzed in 23-s time windows containing pre-stimulus baseline period, one stimulus block, and subsequent blank period (zoom). **(D) Retinotopy experiment.** Observers viewed bars containing cropped cartoon stimuli traversing the visual field (left, Toonotopy[56]) while fixating and performing a color change detection task at fixation[56]. Data were used to define visual areas and select pRFs with centers overlapping stimulus quadrants in the main experiment (right). Fixation dot is enlarged for visibility.

3.1   V1 voxels with small pRFs show modest to no simultaneous suppression

For a single V1 voxel with a small pRF overlapping only a single square, we find similar responses

for simultaneous vs sequential presentations for the two stimulus sizes and presentation timings (**Fig

2A) as the stimulus within the pRF is identical across the two types of presentation sequences. In
other words, this voxel shows no simultaneous suppression. Additionally, we observe that for this V1
voxel responses are larger for short presentations (many visual transients) vs long presentations
(few visual transients) even though the total duration of stimulation across the blocks is identical.
However, there is no difference in the response amplitude for small vs big squares of the same
duration (left vs right panels).

158
Figure 2. V1 voxels show no to little simultaneous suppression. (A) Example V1 voxel with small pRF
overlapping a single square. The example voxel's pRF (yellow circle) is superimposed on square locations
(black). Gray time courses show the example voxel's average BOLD time series ± SEM across block repeats
for each stimulus condition. Above each time series is an example stimulus sequence for each condition in an
8-s block. *Gray sequence:* time course including all square stimuli. *Black sequence:* time course for small pRF
overlapping one square. **(B) Relation between BOLD amplitude (% signal) for simultaneous vs sequential**
blocks, for each size/duration condition. Data include all V1 voxels from participant S3 with pRFs
overlapping square stimuli, averaged across a 9-s time window centered on the peak response. Each dot is a
voxel, colored by effective pRF size from the retinotopy model fit ($\sigma/\sqrt{CSS_n}$). *Dashed line:* No suppression.
Solid black line: Linear mixed model (LMM) line fit for this participant's V1 data. Slope (±SE) across voxels are
indicated in each panel.

To assess simultaneous suppression, we compare single voxel response amplitudes for
simultaneous vs sequential presentations for a given stimulus condition. No suppression will result
on voxels falling on the identity line, whereas simultaneous suppression will result in voxels below
the diagonal. In V1, we find that many voxels fall closely or just below the identity line (**Fig 2B**,
example participant; **Supplementary Fig 1,** all participants) even as response levels were higher for
short vs long stimulus presentation timings. To quantify this relationship, we fit a linear mixed model
(LMM) relating the simultaneous amplitude to the sequential amplitude across V1 voxels using a
fixed interaction effect for conditions, and a random effect for participants (i.e., intercepts and slopes
vary per participant and condition, **Equation 10**). LMM slopes of 1 indicate no suppression, slopes
less than 1 indicate simultaneous suppression, where smaller slopes correspond to stronger
suppression levels.

Across participants, the LMM captures 86% of the variance in V1, with the following average
(± SEM) suppression levels: small and long squares: 0.81 ± 0.069 ($CI_{95\%}=0.56–1.06$), small and short
squares: 0.85 ± 0.058 ($CI_{95\%}=0.73–0.96$), big and long squares: 0.85 ± 0.090 ($CI_{95\%}=0.56–1.4$), and big
and short squares: 0.84 ± 0.081 ($CI_{95\%}=0.57–1.1$). Thus, V1 voxels with relatively small pRFs show
modest to no simultaneous suppression.

3.2   Strong simultaneous suppression for large pRFs in higher-level visual areas

For a single VO voxel with a large pRF overlapping all four large squares, we find lower responses
for simultaneous than sequential presentations for both square sizes and presentation timings (**Fig
3A**). In other words, this voxel shows simultaneous suppression across all experimental conditions.
Additionally, we observe that the overall response amplitudes of this voxel are larger for the big
squares and short presentations compared to the small squares and long presentations.

We observe this pattern of results across VO voxels. Plotting the average amplitude for
simultaneous vs sequential presentations, we find a linear relationship between responses to
simultaneous and sequential pairings, where voxels show simultaneous suppression and the level of
suppression varies across experimental conditions (**Fig 3B**, example participant; **Supplementary
Fig 1,** all participants). This relationship is not a given, as simultaneous suppression could have
tapered off with response level. Instead, our data suggests that suppression can be summarized with
a single slope per visual area and experimental condition.

Quantitative analyses using a LMM ($R^2=97\%$) revealed significant simultaneous suppression
varying with stimulus size and timing, with the following suppression levels: small and long squares:
0.40 ± 0.075 ($CI_{95\%}=0.15–0.65$), small and short squares: 0.65 ± 0.052 ($CI_{95\%}=0.55–0.75$), big and long

squares: 0.62±0.11 (CI$_{95\%}$=0.31–0.93), and big and short squares: 0.70±0.033 (CI$_{95\%}$=0.54–0.87).
Notably, for stimuli of the same duration, there is larger suppression (smaller slopes) for the small vs big squares. However, for the same square size, there is larger suppression for long vs short presentation timings. This suggests that in VO1/2, in addition to the stimulus' spatial overlap with the pRF, timing also contributes to simultaneous suppression.

Figure 3. Individual VO1/2 voxels with large pRFs show strong simultaneous suppression effects. Same layout as Fig 2, but for higher-level visual area VO1/2. Data are from participant S3. **(A) Example time series of a VO1 voxel.** Voxel has a large pRF that covers all the four squares of both sizes (yellow circle). **(B) Simultaneous vs. sequential BOLD amplitude for all voxels in VO1/2.** *Dashed line:* No suppression; *Solid black line:* LMM line fit for this participant's VO1/2 data. Slope (±SE) across voxels are indicated in each panel.

3.3 Simultaneous suppression increases up the visual hierarchy and depends on stimulus size and presentation timing

We next quantified the relationship between responses in simultaneous vs sequential presentations across the visual hierarchy. Our data show four findings. First, in each visual area and stimulus condition, we find a linear relationship between voxels' responses to simultaneous and sequential

stimuli (**Fig 4A**, big and short stimuli; **Supplementary Fig 1**, all conditions). Second, when
quantifying this linear relationship by its slope, we find that simultaneous suppression is prevalent at
the voxel level in almost every visual area across participants. Third, across all stimulus conditions,
we find that suppression levels progressively increase from early visual areas (V1 to V2 to V3) to
intermediate areas (hV4, LO1/2, V3A/B), with the strongest simultaneous suppression in TO1/2 (**Fig
4B** and **Supplementary Table 1**). Fourth, up the visual hierarchy, simultaneous suppression levels
depend on stimulus condition. In particular, higher-level visual areas show stronger suppression for
long vs short presentation timings, and stronger suppression for small vs big square sizes. A two-
way repeated measures ANOVA revealed significant effects of visual area ($F(8)=23$, $p=7.3 \times 10^{-27}$)
and stimulus condition ($F(3)=27$, $p=2.3 \times 10^{-15}$) on suppression slopes. There was no significant
interaction between stimulus condition and visual area (**Supplementary Table 2;** post-hoc
Bonferroni-corrected t-tests).

Figure 4. Simultaneous suppression increases up the visual hierarchy. (A) Average sequential vs simultaneous BOLD amplitude of individual voxels for small and short stimulus condition. Each point is a voxel, colored by effective pRF size estimated from the retinotopy data. Each panel shows data of all 10 participants. *Black solid line:* LMM fit (average across participants). *Dashed line*: identity line. *Shaded area:* $CI_{95\%}$ across participants. *Yellow circles:* illustration of average effective pRF size per area, ranging from 1° in V1 to 7.8° in TO1/2. **(B) Suppression levels for each stimulus condition and visual area.** Slopes are derived from LMM fit to simultaneous vs sequential average BOLD amplitude data from all 10 participants, for each visual area. A slope of 1 indicates no suppression. Smaller slopes indicate larger suppression. *Large colored dots:* Group average of a visual area. *Error bars*: SEM across participants. *Light gray dots:* Individual participant slopes (random effects). Early visual areas are in blue colors (V1: indigo. V2: dark blue. V3: light blue), ventral visual areas in green colors (hV4: dark green. VO1/2: light green), dorsal visual areas are in purple colors (V3A/B: purple. IPS0/1: pink), and lateral visual areas are in warm colors (LO1/2: red. TO1/2: yellow).

The increasing suppression levels across the visual hierarchy are in line with our prediction that simultaneous suppression will be stronger in visual areas that have larger pRF sizes. This

relationship is evident at the level of entire visual areas (**Fig 4B**), but not across voxels within an area

(**Fig 4A**). Within an area, we find similar suppression levels for voxels with pRFs that drastically vary

in size (e.g., VO1/2), yet their level of suppression is predicted by a single line. Thus, while pRF size

is an important predictor of simultaneous suppression at the level of an entire visual area, our data

suggest that by itself, summation within pRFs that vary in size is insufficient to explain different

suppression levels observed across stimulus conditions. Together, these results reveal robust

simultaneous suppression at the individual voxel level that depends both on pRF size alongside

stimulus size and timing parameters.

To understand how much of the observed suppression in higher-level visual areas is

accumulated from earlier visual areas, we compare suppression slopes between pairs of consecutive

visual areas within a processing stream. One possibility is that suppression monotonically

accumulates up the visual hierarchy irrespective of stimulus condition (e.g., a consistent difference

in slopes between consecutive areas). Alternatively, suppression may increase until a certain

processing stage and then plateau (e.g., when the average pRF size within a visual area is large

enough to encompass all square stimuli). Contrary to these predictions, we find that the difference in

suppression levels between consecutive visual areas varies by stimulus condition, and suppression

levels do not increase consistently across the visual hierarchy nor plateau (**Supplementary Fig 2A**).

Additionally, observed differences in suppression levels between consecutive visual areas do not

show a clear relationship with differences in pRF size (**Supplementary Fig 2B)** or differences in

spatiotemporal compression within pRFs (**Supplementary Fig 2C**). These results suggest that there

is some accumulation of simultaneous suppression up the visual hierarchy, but that accumulation

alone cannot fully explain the observed simultaneous suppression levels in higher visual areas.

3.4   A spatiotemporal pRF modeling framework to predict simultaneous suppression at the
269   single voxel level

To gain insight into the stimulus-driven computations that give rise to different levels of simultaneous

suppression at the voxel level, we developed a computational framework that predicts the neural

population response in each voxel from its pRF given the frame-by-frame stimulus sequence of the

SEQ-SIM experiment (**Fig 5**). To capture the brief nature of the stimuli and the neural response, both

stimulus sequence and predicted pRF responses have millisecond resolution. This neural pRF

response is then convolved with the hemodynamic response function (HRF) to predict the voxel's

BOLD response and downsampled to 1 s resolution to match the fMRI acquisition (**Fig 5A**). Crucially,

for each voxel, we use a single pRF model and the stimulus sequence of the entire SEQ-SIM

experiment to predict its time series across all stimulus conditions at once. For all tested pRF models,

spatial parameters of each voxel's pRF are identical and estimated from the independent retinotopy
experiment (**Fig 1D**).

We test three pRF models. First, a compressive spatiotemporal pRF model (CST[51]) (**Fig 5B**)
to quantitatively examine if compressive spatiotemporal summation within pRFs can predict
simultaneous suppression across all stimulus manipulations. The CST pRF model contains three
spatiotemporal channels that have the same spatial pRF (2D Gaussian) but different neural temporal
impulse response functions (IRFs): a sustained, on-transient, and off-transient channel that captures
stimulus duration, onsets, and offsets; neural IRFs use default temporal pRF parameters from
Stigliani *et al.*[41]. These spatiotemporal filter outputs are rectified and subjected to a compressive
static nonlinearity, which produces subadditive spatiotemporal summation for both sustained and
transient channels.

290
Figure 5. Computational modeling framework. (A) Model overview. *From left to right:* Given a binarized
stimulus sequence and pRF model, the neural response is predicted at millisecond time resolution. This neural
response is convolved with hemodynamic response function (HRF) to predict the BOLD response. After the
convolution with the HRF, data are downsampled to 1-s temporal resolution (TR in SEQ-SIM experiment). **(B-
D) Tested pRF models.** For each voxel, spatial pRF parameters are identical for all models and estimated
from the retinotopy experiment (Fig 1D). Both CSS and LSS models sum linearly over time. For simulated pRF
model predictions, see Supplementary Fig 3. **(B) Compressive Spatiotemporal summation (CST)**[51].
Temporal pRF parameters are default parameters from Stigliani *et al.*[41]. Static power-law exponent parameter

(<1) is the same for all three spatiotemporal channels and fitted to each voxel's SEQ-SIM data. The overall
predicted BOLD response by the CST model is the weighted sum of the sustained and combined transient
channel. **(C) Compressive spatial summation (CSS)**[27]. 2D Gaussian followed by a static compressive
nonlinearity (exponent <1, estimated from retinotopy data). **(D) Linear spatial summation (LSS)**[18]. LSS pRFs
sum linearly across space and time by computing the dot product between the binarized stimulus frame and
the 2D Gaussian pRF.

Second, we implement a compressive spatial summation pRF model (CSS[27]) (**Fig 5C**) to

quantitatively test if subadditive spatial summation alone can explain simultaneous suppression. The

CSS model has a 2D Gaussian followed by a compressive static nonlinearity and is successful in

predicting spatial subadditivity in voxels with larger pRFs beyond V1.

Third, we implement a linear spatial summation pRF model (LSS[18]) (**Fig 5D**) to quantitatively

test if small voxels that show little to no simultaneous suppression, such as those in V1, can be

predicted by linear summation in space and time. The LSS pRF contains a 2D Gaussian for each

voxel and sums stimulus input linearly over time and space. This model was also used to validate

our experimental design as it predicts that, irrespective of pRF size, linear summation of stimuli in

paired SEQ-SIM conditions should result in the same response, i.e., no simultaneous suppression.

We test these pRF models for four main reasons. First, they describe a neural mechanism

with a receptive field restricted to part of the visual field; this restriction is needed to test the impact

of stimulus location and size. Second, the identical spatial pRF across models and similar static

nonlinearity implementation for compressive models (CST and CSS) allow for informative

comparisons between models. Third, both compressive models have the potential to predict

simultaneous suppression within this stimulus regime. Fourth, CST and CSS models have been

successful in providing a comprehensive explanation for subadditive visually-driven responses

across visual cortex[27,51].

3.5 Comparing pRF model performance in predicting observed SEQ-SIM data

For each voxel, we generate three predicted BOLD responses, one for each tested pRF model (CST,

CSS, LSS; see **Supplementary Fig 3** for example pRF model predictions). We fit each model using

split-half cross-validation and quantified the cross-validated variance explained (cv-R^2) for each

voxel. This provides a principled and unbiased way to test the hypotheses.

For our example, small V1 pRF, both spatial models (LSS and CSS) predict the same BOLD

response for sequential and simultaneous pairs (**Fig 6A**, bottom and middle rows). This is because

the pRF covers only one small square, and consequently, spatial summation is identical across SIM

and SEQ presentations. Comparing predictions to data, both LSS and CSS models capture the

voxel's response to long stimulus conditions, but underpredict the voxel's response for short stimulus

conditions, resulting in the same cv-R^2 of 43% for this V1 voxel. In comparison, the CST pRF model

best captures the response pattern across all stimulus conditions (cv-R^2=52%), predicting no

suppression and larger BOLD amplitudes for short than long stimulus conditions (**Fig 6A**, top row).

336
Figure 6. Comparison of pRF model performance. (A) V1 example voxel. *Gray shaded area:* Average ±
SEM voxel time series. Data are from the same voxel as in Fig 2A repeated for each row. PRF model fits are
shown in dashed lines. Split-half cross-validated variance explained (cv-R^2) is computed by fitting the predicted
time series to the average of odd runs and applying the modelfit to the average of even runs and vice versa.
Blue: Compressive spatiotemporal summation model (CST, top row). *Orange:* Compressive spatial summation
model (CSS, middle row). *Black:* Linear spatial summation model (LSS, bottom row). **(B) VO1/2 example**
voxel. Data are from the same voxel as in Fig 3A repeated for each row. Same color scheme as panel A. **(C)**
Distribution of voxel-level cross-validated variance explained for each pRF model, all 10 participants.
Triangle: median. *Dotted line:* noise ceiling computed from max split-half reliability across participants. *Blue:*

CST. *Orange*: CSS. *Gray:* LSS. Since number of voxels vary per participant and visual area, we assure equal
contribution of each participant by resampling data 1000x of each participant's visual area. **(D) Pairwise model**
comparison for each visual area. *Bars:* Average across participants of the voxelwise difference in cv-R^2
between two pRF models. *Error bars:* SEM across participants. *Individual dots:* Average difference for each
participant. *Blue-gray:* CST vs LSS. *Blue-orange:* CST vs CSS. *Orange-gray:* CSS vs LSS.

When pRFs are large and cover multiple stimuli, like the example VO1/2 voxel, the LSS pRF

model predicts larger responses for big than small squares, slightly higher responses for long than

short presentations, and identical responses for sequential and simultaneous pairs. As such, it fails

to predict the observed simultaneous suppression in all conditions (**Fig 6B**, bottom row). On the other

hand, the CSS pRF model predicts simultaneous suppression because of spatial subadditivity, as

well as a modest increase in response with stimulus size (**Fig 6B**, middle row). Like the LSS model,

the CSS model predicts slightly larger responses for the long than short presentations of a given

sequence type (SIM/SEQ). Consequently, the CSS model predicts simultaneous suppression well

for the long presentations across stimulus sizes, but overpredicts simultaneous suppression for short

presentations. In contrast, the CST pRF model best predicts all stimulus conditions for this example

voxel: it shows simultaneous suppression, slightly larger responses for big vs small stimulus sizes,

and larger responses for short vs long presentation timings (**Fig 6B**, top row).

Across all voxels and visual areas, we find that the CST pRF model best predicts our data

(**Fig 6C,D**). The CST model explains more cv-R^2 than LSS and CSS pRF models and approaches

the noise ceiling in V3 and higher-level visual areas (**Fig 6C**, dotted line). A two-way repeated

measures ANOVA revealed significant effects of pRF model ($F(2)=2.6 \times 10^3$, $p<10^{-209}$) and region of

interest (ROI) ($F(8)=3.4 \times 10^3$, $p<10^{-209}$) on cv-R^2, as well as a significant interaction between pRF

model and ROI ($F(2,8)=65$, $p=2.8 \times 10^{-209}$) (post-hoc Bonferroni-corrected t-tests are reported in

Supplementary Table 3). On average, the increase in cv-R^2 for the CST model compared to the

other models ranges from ~5% in V1 to ~12% in VO1/2 (**Fig 6D**). Beyond early visual cortex, the

CSS model outperforms LSS, but in V1 the LSS model slightly (+1.4%) and significantly ($p=2.7 \times 10^{-8}$)

explains more cv-R^2 than the CSS model. These results suggest that V1 voxels largely sum linearly

in space, but nonlinearly in time. However, across the visual hierarchy, compressive spatiotemporal

summation provides a more comprehensive explanation of the empirical data.

3.6   To what extent do pRF models predict simultaneous suppression across visual cortex
376   and across stimulus conditions?

377   To understand the underlying neural computations that generate simultaneous suppression, we use

378   pRF models to predict the level of simultaneous suppression in each voxel and condition of the SEQ-

379 SIM experiment. Then, we compare the model-based simultaneous suppression against the

380 observed suppression (**Fig 7**, shaded gray bars).

381
Figure 7. Model-based prediction of simultaneous suppression vs observed simultaneous suppresion.
Shaded gray bars: Observed suppression levels in data, mean ± SEM across participants (same as Fig 4B).
Black open circles: Linear spatial summation (LSS) pRF model; *Orange filled circles:* Compressive spatial
summation (CSS) pRF model; *Blue filled circles:* Compressive spatiotemporal (CST) summation. Model-based
points and errorbars show average and SEM across all 10 participants.

The CST model best captures simultaneous suppression across visual areas and stimulus

conditions as its predictions are largely within the range of data variability (**Fig 7**, compare blue circles

to shaded gray bars). Specifically, the CST model predicts (i) progressively increasing simultaneous

suppression across visual hierarchy, (ii) stronger suppression for longer than shorter presentation

timings for squares of the same size, and (iii) weaker suppression for bigger than smaller squares of

the same timing. The CST model performs similarly with pRF parameters that are optimized using

the independent spatiotemporal retinotopy experiment[51] (**Supplementary Figs 8-9**).

The CSS model captures the progressively stronger simultaneous suppression across visual

hierarchy and the observed simultaneous suppression for the long stimuli in a few visual areas

(V3A/B, IPS0/1, and TO1/2), but fails to predict suppression for short stimuli and generally
overpredicts the level of suppression (**Fig 7,** orange circles). In other words, the CSS model predicts
much stronger simultaneous suppression levels than observed, as model predictions are consistently
below the data. This overprediction is largest for short presentation timings in early (V1-V3) and
ventral visual areas (hV4 and VO1). One reason for this mismodeling error is that the CSS model
does not encode visual transients: it predicts stronger simultaneous suppression for small than big
sizes but predicts similar simultaneous suppression for long and short presentations of the same
square size.

Finally, and as expected, the LSS model does not predict simultaneous suppression
altogether. This is because the LSS model sums visual inputs linearly in space and time, and we
designed our experiment such that each square is shown for the same duration and location in
sequential and simultaneous conditions. Therefore, the LSS model predicts the same responses for
sequential and simultaneous stimulus pairings and consequently no suppression (**Fig 7**, black open
circles). For the big and long squares, the LSS model predicts slightly higher responses for
simultaneous vs sequential presentations. We attribute this to our experimental design, which has
different inter-stimulus-intervals of individual squares between sequential and simultaneous blocks,
see *Methods – LSS pRF model*).

Thus far, we primarily focused on two compressive pRF models (CST and CSS) and find that
CST pRFs best predict simultaneous suppression. However, this does not rule out the possibility that
other types of subadditive mechanisms within pRFs can account for simultaneous suppression. One
such mechanism is center-surround suppression, which is most prevalent in early stages of visual
processing (retina[57], LGN[24], and V1[58]). To test this possibility, we simulated Difference of Gaussians
(DoG) pRFs for voxels in V1 through hV4. In these visual areas, DoG pRFs have a positive center
that encompasses one or few squares while the larger, negative surround covers more squares,
which may suppress the overall response in simultaneous conditions (**Supplementary Fig 7A**). Yet,
we find that DoG pRFs predict no simultaneous suppression in V1 through hV4 for our stimuli
(**Supplementary Fig 7B**). Instead, like the LSS model, DoG pRFs sum linearly over the spatial and
temporal extent of the stimulus, resulting in similar responses across SIM and SEQ conditions.

A second potential subadditive mechanism is delayed normalization[42,44]. To test this
mechanism, we implement a delayed normalization spatiotemporal (DN-ST) pRF model for 7
participants who completed a separate spatiotemporal pRF retinotopy experiment[51]. Like the CST
model, the DN-ST model captures the increase in simultaneous suppression across the visual
hierarchy, as well as differences in suppression levels with stimulus size and timing (**Supplementary**

Fig 8A). A two-way repeated measures ANOVA reveals significant effects of pRF model
($F(2)=1.1\times10^2$, $p=6.3\times10^{-47}$) and ROI ($F(7)=1.3\times10^3$, $p<10^{-47}$) on cv-R^2 (**Supplementary Fig 8B**),
where the DN-ST model with optimized parameters predict overall less cv-R^2 than either CST model:
3.9% less cv-R^2 than CST pRFs with fixed temporal parameters and 1.5% less cv-R^2 than CST pRFs
with optimized parameters. In particular, DN-ST pRFs tend to underpredict the level of simultaneous
suppression for short stimulus timings (0.2 s) (**Supplementary Fig 9A**). The ANOVA also indicates
a significant interaction between pRF model and ROI ($F(2,7)=5.0$, $p=1.6\times10^{-9}$), where both CST
models perform significantly better than the DN-ST model in almost all visual areas, and the main
CST pRF model explains slightly but significantly more cv-R^2 than the optimized CST pRF model in
visual areas V1, hV4, V3A/B, LO1/2, and TO1/2 (**Supplementary Table 4**, post-hoc Bonferroni-
corrected t-tests).

Together, these model comparisons suggest that accounting for spatiotemporal nonlinearities
rather than just spatial nonlinearities is necessary for predicting simultaneous suppression across a
variety of spatial and temporal stimulus conditions.

3.7　What intrinsic pRF components drive the observed simultaneous suppression?

To elucidate what pRFs components predict the varying levels of simultaneous suppression across
the visual system, we examine the relationship between the average suppression level and CST pRF
model parameters. We find that simultaneous suppression increases with pRF size, spatiotemporal
compression (CST_n), and necessitates contributions from both sustained and transient temporal
channels (**Fig 8**). Visual areas with larger pRF sizes tend to show stronger simultaneous suppression
levels (smaller slopes, Pearson's correlation $r=-0.72$, CI$_{95\%}=-0.81$–0.59, $p<0.0001$) (**Fig 8A**).
Likewise, visual areas with stronger spatiotemporal compression within pRFs (smaller exponents)
are linked to stronger simultaneous suppression levels (Pearson's $r=0.65$, CI$_{95\%}=0.50$–0.76,
$p<0.0001$) (**Fig 8B**).

Lastly, we find that across visual areas, both sustained and transient channels contribute to
predicting single voxel BOLD responses, as their β-weights are similar (no significant difference in β-
weights across channels) (**Fig 8C**). These results indicate that both sustained and transient channels
are needed to predict simultaneous suppression across different stimulus size and timing conditions.

Figure 8. Simultaneous suppression depends on pRF size, compressive exponent, and contributions from both sustained and transient channels. In all panels: *dots/bars* show average across 10 participants. *Error bars:* SEM across 10 participants. **(A) Simultaneous suppression level vs median pRF size. (B) Simultaneous suppression level vs median CST pRF exponent.** For effective size and exponent pRF parameters, we first computed the median across pRFs of a visual area for each participant, as compressive exponent values in V1 and V2 voxels are not normally distributed (see Supplementary Fig 4), then we calculated the average median value across participants. Pearson's correlation (*r*) is computed using individual participant data. Significant *p*-values are indicated with * (*p*<0.0001). **(C) Average β-weights of sustained and transient channels in CST pRF model.** Beta weights are averaged first within a participant's visual area, to then average across participants per visual area. *Colored bars:* Sustained channel. *White bars:* Combined transient channel. Differences between sustained and transient channels are not significant. **(D) Median exponent pRF parameters for CSS vs CST model.** Dashed line indicates equality line.

Examining the relationship between simultaneous suppression and optimized CST model parameters underscores our findings that larger pRF sizes, stronger compressive nonlinearity (i.e., smaller exponents), and contributions of both sustained and transient channels are important for predicting the level of simultaneous suppression across the visual hierarchy, whereas time constant parameters do not systematically co-vary with observed suppression levels (**Supplementary Fig 9B-D**). The DN-ST model shows similar a relationship as the CST model, where increased levels of simultaneous suppression are predicted by larger pRF sizes and stronger spatiotemporal compression within the pRF via larger semi-saturation constants in the denominator, smaller exponents, and increased exponential decay time constants (**Supplementary Fig 9F-I**). These results suggest that simultaneous suppression can be predicted by more than one implementation of a compressive spatiotemporal mechanism (static nonlinearity vs delayed divisive normalization).

Because the static nonlinearity in CST pRFs is applied to the output of spatiotemporal channels, the compressive nonlinearity is of spatiotemporal nature and cannot be separated into spatial and temporal dimensions. Nevertheless, we can gain insight into the different contributions of spatial versus spatiotemporal compression by comparing the exponent across the main CST and CSS pRF models. We find that across all visual areas, CSS pRFs have smaller exponents (resulting in more compression) than CST pRFs with a fixed time constant (**Fig 8D**). This overly strong compression by the CSS model likely explains its mismodeling of the short stimuli, where it predicts too much

488 suppression (**Fig 7**). Interestingly, while CST pRFs with optimized spatiotemporal parameters have
489 similarly small exponents like CSS pRFs, the CST pRFs are more accurate than CSS pRFs in
490 predicting simultaneous suppression across stimulus conditions (**Supplementary Fig 9C**).
491   Overall, these results suggests that both spatial and temporal nonlinearities within pRFs are
492 necessary to account for the observed simultaneous suppression, and ultimately interact.

4 Discussion

Simultaneous suppression is a decades-old, yet perplexing neurophysiological phenomenon: Why is
the response to multiple stimuli presented simultaneously substantially lower compared to the
response to the same stimuli presented sequentially? Here, we combined a new experimental
design, varying stimulus size and presentation timing, with an innovative spatiotemporal pRF
modeling framework to elucidate the stimulus-driven computations that may give rise to simultaneous
suppression in individual voxels. Our results show that the level of simultaneous suppression
depends not only on the spatial overlap between stimuli and the pRF, but also on the timing of stimuli
and the number of visual transients. Furthermore, we find that compressive (subadditive)
spatiotemporal computations by pRFs predict simultaneous suppression in each voxel across the
visual hierarchy, and across various experimental conditions. These findings suggest that a stimulus-
driven compressive spatiotemporal computation by pRFs generates simultaneous suppression and
necessitate a rethinking of the neural mechanisms involved in simultaneous suppression.

4.1 Rethinking the neural mechanisms of simultaneous suppression

By investigating simultaneous suppression under a computational lens, measuring and predicting
each voxel's pRF response independently, we provide a mechanistic explanation on how the spatial
overlap between the stimulus and pRF drives simultaneous suppression at the single voxel level.
This confirms the longstanding hypothesis that the overlap between the receptive field and stimuli
matters[8,9,12]. Additionally, we show that increasing simultaneous suppression up the visual hierarchy
is predicted by both the progressive increase in pRF size and strength of spatiotemporal
compression.
Crucially, we are able to explain a wide range of simultaneous suppression levels by stimulus-
driven computations within pRFs alone, which necessitates a rethinking of the neural processing
underlying simultaneous suppression. Thus, we propose a new idea that simultaneous suppression
is a consequence of simple, stimulus-driven spatiotemporal computations rather than a result of
stimuli competing for limited neural resources within receptive fields, and prioritized by task demands.

As our computational framework uses a stimulus-referred encoding model, it has predictive power.

This allows future research to make new predictions about suppression levels for any stimulus

sequence. The framework is also modular and can be expanded to computationally operationalize

the effects of stimulus content, context, and task demands on simultaneous suppression.

4.2　Simultaneous suppression increases up the visual processing hierarchy, and depends on
stimulus size and timing

Consistent with previous work[7-9,12], our data show that simultaneous suppression increases up the

visual hierarchy and is particularly strong in ventral visual areas (hV4 and VO1/2). Notably, we find

that not only stimulus size and location, but also stimulus timing and number of visual transients

affect the level of simultaneous suppression: for stimuli of the same size, longer timings (1 s) with

fewer transients generated stronger suppression levels than shorter timings (0.2 s) with more

transients.

Contrary to prior studies[8-12], we find moderate levels of suppression in already in V1, despite its

small receptive fields. This may be because of multiple differences between studies. First, differences

in the level of analysis: we quantify simultaneous suppression at the voxel level vs ROI level in prior

fMRI studies[8-12]. Second, differences in which pRFs are analyzed: we include all pRFs that overlap

the stimuli, including small pRFs that partially overlap multiple squares, but electrophysiology studies

used stimuli that completely overlap with neurons' receptive fields[5-7]. Third, differences in stimulus

timing: prior studies used a single stimulus timing (0.25 s per stimulus)[8-12], which is similar to our

short stimuli, for which we find weaker levels of simultaneous suppression.

4.3　Compressive spatiotemporal computations within pRFs can explain simultaneous
suppression across visual cortex

To test whether compressive spatial summation or compressive spatiotemporal summation can

predict simultaneous suppression across experimental conditions, we compared multiple pRF

models. Overall, the CST pRF model provides a comprehensive explanation for simultaneous

suppression across voxels spanning the ventral, dorsal, and lateral visual processing streams, as

well as stimuli varying in size and presentation timing. This high performance of the CST model

across all visual areas is not a given, as different models could have better predicted certain visual

areas or processing streams.

Spatial pRF models captured some, but not all aspects of the observed simultaneous

suppression. For instance, CSS pRFs are able to predict simultaneous suppression for long (1 s) but

not shorter stimulus timings in several visual areas. As LSS, DoG, and CSS pRF models were

developed for stimulus durations and intervals that evoke BOLD responses that approximately sum

linearly in time, these models are limited because they do not account for visual transients. This

assumption of temporal linearity is not only a limitation of the spatial pRF models we tested, but of

any other pRF model that sums linearly over the stimulus duration, such as linear spatiotemporal

pRF models[49] or other center-surround pRFs[50].

Likewise, we show that other mathematical forms of subadditive spatiotemporal summation, a

delayed normalization spatiotemporal pRF model (DN-ST), can predict simultaneous suppression

across stimulus conditions, as well as across visual areas. When inspecting pRF parameters of the

tested spatiotemporal pRF models (CST and DN-ST), we find that pRF size and compressive

nonlinearities that incorporate visual transients at the neural level are crucial for predicting

simultaneous suppression.

While our spatiotemporal pRF models outperform spatial pRF models in predicting

simultaneous suppression across stimuli size and timing, CST and DN-ST pRF models did not

capture all spatiotemporal nonlinearities. For instance, for long stimuli, both CST and DN-ST models

tend to overpredict suppression in early visual areas. Future research may improve CST and DN-ST

model performance by optimizing parameters of both neural and hemodynamic temporal impulse

response functions (IRFs) in each voxel[51]. Additionally, the estimation of some pRF model

parameters is more sensitive to the experimental design and HRF variability (e.g., time constant)

than others (e.g., pRF position)[51]. Therefore, we stress that it is important to consider how the

experimental design may affect pRF parameter estimates and subsequent model performance.

We are not the first to consider temporal aspects of BOLD responses in models of the human

visual system. Prior studies have suggested other hemodynamic[45-47] and neural[35,39-42,48-50] IRFs to

capture BOLD temporal nonlinearities (see review[59]). Notwithstanding the success of these models,

only the recent development of a compressive spatiotemporal pRF model[51] with neural IRFs in units

of visual degrees and milliseconds provided us with the opportunity to examine what subadditive

spatiotemporal computations contribute to simultaneous suppression for the following reasons. First,

a successful model needs to account for neural nonlinearities. We believe that the observed

nonlinearities are of neural rather than hemodynamic origin, as electrocorticography and single unit

recordings show that neural responses to brief visual stimuli evoke strong visual transients and are

nonlinear[42]. In a recent study, we have shown that implementing such neural nonlinearities in a

computational model rather than optimizing hemodynamic responses is necessary to predict BOLD

temporal nonlinearities to brief stimuli as in the present study[51]. Second, to capture visual transients

in rapid succession, the model requires neural IRFs with millisecond precision and a 50-200 ms

response window rather than a 1-4s window as afforded by hemodynamic models[47,49]. Third, the

model also requires a spatial pRF. While prior studies have modeled neural IRFs with millisecond

time resolution[35,39-42], without a spatial component these models are unable to predict differences in

responses to one vs multiple stimuli covering a pRF.

4.4 Compressive spatiotemporal summation as a general computational mechanism in the
visual system

A key insight from our study is that both increasing pRF size and stronger spatiotemporal

compression contribute to increasing levels of simultaneous suppression up the visual processing

hierarchy. This insight complements prior work[8,9] which proposed that the progressive increase in

receptive field size causes stronger simultaneous suppression in higher-level areas.

Increasing receptive field size and compression from early to higher-level visual areas have

been interpreted as increasing summation windows that enhance invariance both in space[22,27,50,60,61]

and time[28,32,33,37,39,40,44]. This aligns with the idea that spatial and temporal compression of visual

information share a similar processing strategy[40] and suggests that compressive spatiotemporal

summation may be a general computational principle in visual cortex. Moreover, our findings show

that spatiotemporal receptive field models can be leveraged to gain insights about neural responses

beyond processing of visual motion and dynamic information, such as predicting responses to rapidly

presented stimuli varying in spatial locations, as in the present study. In addition to predicting the

level of simultaneous suppression, the compressive spatiotemporal pRF model showed that ventral

visual areas are highly sensitive to temporal properties of the visual input. These findings are in line

with prior work showing that dynamic visual inputs affect not only motion-sensitive neurons in V1 and

MT but also drive ventral visual stream areas V2, V3, hV4, and VO[36,62-68].

What may be the role of compressive spatiotemporal summation? Little is known regarding to

the role of compressive spatiotemporal summation outside of motion processing[69-72]. One possibility

is that increasing compressive spatiotemporal summation generates representations that encode

complex shape and motion information that unfolds over time[73]. This may be useful for binding

different views of novel objects during unsupervised learning (associated with ventral stream

functions[74,75]) or for perceiving complex visual dynamics, actions, and social interactions (associated

with lateral stream functions[76-78]). Another possibility is that spatiotemporal compression within pRFs

may enable neurons to prioritize novel visual information[13,79]. This may be beneficial for visual

search[1,2] or short-term visual working memory by converting redundant visual information into a more

efficient representation[80]. However, spatiotemporal compression may also limit visual processing

capacity, affecting downstream cognitive processes such as worse memory for simultaneously vs

sequentially presented items[81]. Thus, an important future direction is characterizing and

computationally linking the neural phenomenon of simultaneous suppression to behaviors such as

visual capacity, and testing what computational mechanisms generalize across scenarios and tasks.

In sum, our empirical data and voxel-wise pRF modeling approach call for a rethinking of the

neural mechanisms that drive simultaneous suppression and suggest that suppression is a byproduct

of compressive spatiotemporal computations. These findings provide exciting new opportunities to

computationally understand how stimulus content, context, and task demands affect simultaneous

suppression and visual processing capacity more broadly.

5 Methods

5.1 Participants

Ten participants (6 self-identified as female, 4 self-identified as male, ages 22-53 years, M = 30.1 years, SD = 8.7 years) with normal or corrected-to-normal vision participated in a retinotopy and SEQ-SIM fMRI experiment. Participants gave written informed consent, were compensated for their time, and all procedures were approved by the Stanford Internal Review Board on Human Subjects Research.

5.2 Stimuli & experimental design

Stimuli were generated using MATLAB R2017b (MathWorks, MA, USA) and PsychToolbox[82] on an Apple MacBook Pro laptop. Images were presented using an Eiki LC-WUL100L projector (Eiki International, Inc., CA, USA) on a rear-projection screen via two large mirrors placed at the back of the MRI scanner bed. The projected image had a resolution of 1920x1080 pixels, resulting in a field-of-view of ~38x24°, and refresh rate of 60 Hz. The display was calibrated using a linearized lookup table.

      Retinotopy experiment. Participants completed four 3.4-minute runs, where bar stimuli cropped from colorful cartoons traversed across a 24x24° circular aperture (Toonotopy[56]). Cartoon images inside the bar changed randomly at 8 Hz. The bar swept in 12 discrete steps, 2-s per bar position, for 4 orientations (0°, 45°, 90°, 135°) and 2 motion directions for each orientation. Observers fixated on a central dot (diameter = 0.12°) and pressed a button every time the fixation dot changed color (semi-random intervals, 6–36 s). Due to a coding error, button presses were only recorded for 3 participants, who performed at ceiling (M = 98.7% correct, SD = 1.2%).

      SEQ-SIM experiment. Participants completed eight ~5.5-minute runs (except for participant S5, completing six runs), where 8 squares were presented sequentially or simultaneously while fixating: 4 squares in the lower right quadrant and 4 squares in the upper left quadrant. Both sequential and simultaneous conditions used two presentation timings (short: 0.2 s and long: 1 s) and two sizes (small: 2x2° and big: 4x4°), resulting in eight conditions. We did not consider sex and/or gender in this study design.

      Stimuli: Squares were randomly cropped from colorful cartoons and placed on a mean luminance gray background. To ensure square stimuli would elicit responses in visual cortex, squares with little to no contrast were excluded (normalized root mean square contrast across pixels < 10%). The content of individual squares differed for each trial and quadrant, and never repeated within a run. Within a quadrant, squares had a 2-by-2 layout with a 0.82° gap between them, centered at

~7.1° eccentricity ([x,y] = [5°,5°]). Both sizes used identical gap and eccentricity, such that 4 small

squares extended horizontally and vertically from 2.59° to 7.41°, and big squares extended from

0.59° to 9.41°. The lower right and upper left quadrant had the same square locations but mirrored

horizontally and vertically.

Experimental Design: Stimuli were shown in ~8 s blocks, interspersed by 12-s blank periods.

Each run started with a 6-s countdown and 12-s blank and ended with a 12-s blank. Each condition

was repeated four times in a pseudo-randomized order across two runs. The block order, as well as

individual square presentation within a block, differed across runs. Each participant was assigned a

unique pair of runs, which were repeated four times (three for participant S5) within the experiment

with different square content (see example: https://osf.io/7rqf4).

Sequential and simultaneous conditions had 8 trials per block for short stimuli and 2 trials per

block for long stimuli. We used different trial-per-block ratios such that short and long conditions had

a similar total block duration while the number of visual transients quadrupled (16 vs 64)—matching

the increase between small and big square sizes (4 vs 16 deg^2). In a sequential trial, the four squares

in each quadrant appeared one at a time, in random order, with a 33-ms inter-stimulus-interval (ISI)

between squares. In a simultaneous trial, all four squares in a quadrant appeared at once for the

same duration and location followed by a mean luminance gray display to match duration of a

sequential trial.

Block onsets and stimulus conditions were identical across quadrants, but timing and order

of individual square appearances were independently determined per quadrant. In simultaneous

blocks with long stimulus presentations, stimuli in the first trial were presented at block onset to match

sequential blocks. Stimuli of the second trial were presented 4 s later to avoid 7-s gaps between

stimuli within a block. In simultaneous blocks with short presentations, stimuli in the first trial were

also locked to block onset, but onset of stimuli in the following 7 trials was randomized within a trial.

Task & Behavioral performance: Participants performed a 1-back letter RSVP task at fixation

and pressed a button when a letter repeated (1/9 probability). The letters (diameter of ~0.5°) updated

at 1.5 Hz, alternating between black and white colors, and randomly drawn from a predefined list ('A',

'S', 'D', 'F', 'G', 'H', 'J', 'K', 'B', 'P'). Participants had a 0.83-s response window after a letter appeared

and performance was displayed after every run. Outside the scanner, participants did 1-minute

practice runs until they reached at least 70% correct before starting the experiment. In the scanner,

participants performed the task well (M = 88% correct, SD = 8.2%), ranging from 68–95%, and

average false alarm rate of 2%. These behavioral data are confirmed by steady fixation in eye

movement data (**Supplementary Fig 5**) and indicate that participants were fixating throughout
experimental runs.

5.3   MRI data acquisition

Participant's structural and functional data were collected using a 3T GE Signa MR750 scanner
located in the Center for Cognitive and Neurobiological Imaging at Stanford University. Whole brain
T1-weighted anatomy data were acquired using a BRAVO pulse sequence (1 mm^3 isotropic,
inversion time=450 ms, TE=2.912 ms, FA=12°), using a Nova 32-channel head coil. Functional data
were collected using a Nova 16-channel coil, using a T2*-sensitive gradient echo planar imaging
sequence (2.4 mm^3 isotropic, FoV=192 mm, TE=30 ms, FA=62°). EPI slice prescriptions were
oblique, roughly perpendicular to the calcarine sulcus. Retinotopy experiment used a TR of 2000 ms
and 28 slices. SEQ-SIM experiment used a TR of 1000 ms and 14 slices. A T1-weighted inplane
image (0.75x0.75x2.4 mm) was collected with the same coil and slice prescription as the functional
scans to align functional and anatomical scans.
Left eye gaze data of 9 participants were continuously recorded in each SEQ-SIM run at 1000
Hz using an EyeLink 1000 (SR Research Ltd., Osgoode, ON, Canada). Eye position calibration and
validation was conducted before the first run, using a 5-point grid. We could not collect eye gaze data
in one participant due to constraints in the mirror setup. Four participants were excluded prior to
analysis due to excessive measurement noise. Analysis details for eye gaze data are in the
Supplementary Material above **Supplementary Fig 5**.

5.4   MRI data analysis

5.4.1 Data availability
Data are provided with this paper and publicly available at https://osf.io/rpuhs/.

5.4.2 Code availability
Analyses were conducted in MATLAB (R2020b) and FreeSurfer's auto-segmentation[83] (v6.0;
http://surfer.nmr.mgh.harvard.edu/).   Analysis   code   is   publicly   available   on   GitHub:
https://github.com/VPNL/simseqPRF and https://github.com/VPNL/spatiotemporalPRFs.

5.4.3 Preprocessing
Whole-brain   T1-weighted   scans   were   aligned   to   the   AC-PC   line   using   SPM12
(https://github.com/spm/spm12)   and   auto-segmented   with   FreeSurfer's   *recon-all*   algorithm.
Functional data were slice-time corrected, motion corrected, drift corrected, converted to percent

signal change using the *Vistasoft* toolbox (https://github.com/vistalab/vistasoft). Participants'

functional scans were aligned with the inplane to their whole brain anatomy scan, using a coarse,

followed by a fine 3D rigid body alignment (6 DoF) using the *alignvolumedata_auto* toolbox

(https://github.com/cvnlab/alignvolumedata). The first 8 (SEQ-SIM) or 6 (Retinotopy) volumes of

each functional scan were removed to avoid data with unstable magnetization.

Retinotopy analysis. Retinotopy runs were averaged and analyzed with Vistasoft's

compressive spatial summation pRF model (CSS)[27] using a 2-stage optimization (coarse grid-fit,

followed by fine search-fit). For each voxel, this resulted in 2D Gaussian pRF with center coordinates

(x_0, y_0) in degrees, pRF standard deviation (σ) in degrees and pRF static nonlinearity exponent

(CSS$_n$) ranging from 0.01 to 1. To avoid pRFs that are not visually responsive, we selected pRFs

with R^2 ≥20% in the retinotopy experiment, similar to previous pRF publications[56,84].

Defining visual areas. Spatial pRF parameters were converted to polar angle and

eccentricity maps and projected to participant's native cortical surface using nearest neighbor

interpolation. Visual field maps were used to define the following visual areas: V1, V2, and V3[85], hV4

and VO1/2[86], LO1/2 and TO1/2[87], and V3A/B and IPS0/1[88].

Defining ROIs and selecting voxels. For each visual area, we selected voxels with pRFs

centers within the circumference of the big squares in the SEQ-SIM experiment, that is, within an

8.82x8.82° square located 0.59° to 9.41° from display center in both x- and y-dimensions in each

quadrant. From these voxels, we used those with corresponding data from the SEQ-SIM experiment.

Overall, we obtained data in most participants' visual areas, except 6 participants who had insufficient

coverage of IPS0/1 and 2 participants who had insufficient coverage of TO1/2, due to fewer slices in

the SEQ-SIM than retinotopy experiment.

SEQ-SIM analysis. We excluded voxels with a split-half reliability <10% to filter out those

voxels with little to no visual response. Excluded voxels were mostly from V1 and V2, with small

pRFs that fell in between stimuli or on the border of stimuli. The two unique SEQ-SIM runs were

concatenated for each repeat. When applying split-half cross-validation for model fitting, the 4

concatenated runs were split into two odd and two even runs, and averaged within each half.

5.5   pRF modeling framework

Our modeling framework contained three main pRF models: (i) LSS, to test linear spatial

summation[18], (ii) CSS, to test compressive spatial summation[27], and (iii) CST, to test compressive

spatiotemporal summation[51]. Both LSS and CSS models linearly sum over the temporal duration of

the stimulus.

751   Each model's input is a 3D binarized stimulus sequence, pixels by pixels (in visual degrees) by
752 time (milliseconds). Each pRF is applied to each frame of the stimulus sequence to predict the neural
753 pRF response. For each model, this neural response is then convolved with a canonical
754 hemodynamic response function (HRF) (double-gamma SPM default) and downsampled to the fMRI
755 acquisition TR. This results in a predicted BOLD response for the entire stimulus sequence. For each
756 pRF that overlapped stimuli in SEQ-SIM experiment, predictions were computed for each unique 5.5-
757 min run, and then concatenated for the two unique runs. Importantly, concatenated runs contained
758 all 8 stimulus conditions, requiring each model to predict all conditions simultaneously.

759   We model spatial pRF parameters in each voxel using independent retinotopy data and then
760 test which type of spatial and/or spatiotemporal pRF computations predict simultaneous suppression
761 in each voxel in the main experiment.

762   **LSS pRF model.** The LSS model has a circular 2D Gaussian pRF with an area summing to
763 1. The pRF computes the dot product between the 2D Gaussian and stimulus sequence at each time
764 point to predict the response of the neural population within a voxel:

765  $$\text{Neural response}_{LSS}(t) = \int S(x, y, t) \cdot G(x, y)\, dx dy \quad (1)$$

766  $$G(x, y) = e^{\frac{(x-x_0)^2 + (y-y_0)^2}{2\sigma^2}} \quad (2)$$

767   where t is time in ms, S is the stimulus sequence with visual field positions *(x, y)* in visual
768 degrees by time in ms, and G is a circular 2D Gaussian centered at visual field positions *(x₀, y₀)* with
769 size σ in visual degrees.

770   This model sums inputs linearly in visual space and time, and typically predicts the same
771 BOLD response for sequential and simultaneous trials that are matched in stimulus size, location,
772 and duration. For longer stimulus durations, the LSS model occasionally predicts larger responses
773 for simultaneous than sequential conditions, due to a difference in ISI between the two conditions.
774 Specifically, the randomized square onset causes sequential ISIs to range from 1–7s, which by
775 chance can be longer than the fixed 4-s simultaneous ISI—especially for small pRFs that overlap a
776 single square. For these scenarios, the LSS model predicts the BOLD responses accumulate less in
777 the sequential than simultaneous block.

778   **CSS pRF model.** The CSS model has the same spatial pRF model as the LSS model,
779 followed by a static power-law nonlinearity:

780  $$\text{Neural response}_{CSS}(t) = \left[\int S(x, y, t) \cdot G(x, y)\, dx dy\right]^{CSS_n} \quad (3)$$

781   where t is time in ms, the power-law exponent (CSS_n) is bound between 0.01–1 and therefore
782 results in compressive (subadditive) summation.

783   **CST pRF model.** The CST model contains three spatiotemporal channels for each voxel.
784   Each channel has the same spatial pRF as the LSS model, which is combined with a sustained, on-
785   transient, or off-transient neural temporal impulse response function (IRF).

786   For the main analysis, the sustained, on-transient, and off-transient IRFs are identical across
787   voxels, where neural IRFs are based on the following gamma function:

788
$$IRF\ (t) = \frac{\left(\frac{t}{\kappa\tau}\right)^{(n-1)} e^{-\left(\frac{t}{\kappa\tau}\right)}}{\kappa\tau(n-1)!} \qquad (4)$$

where t is time in ms, κ is the time constant ratio parameter, τ (tau) is the time constant
parameter in ms, and n is an exponent parameter.

The sustained IRF is a monophasic gamma function as in (4) with $\kappa = 1$, $\tau = 49.3$ ms and $n =$
9, resulting in a peak response between 40-50 ms. The on-transient IRF is the difference of two
gamma functions: the sustained IRF and a second gamma function as in (4) with parameters: $\tau =$
4.93 ms, $\kappa = 1.33$, $n = 10$, resulting in a biphasic function that generates a brief response at stimulus
onset. These IRF parameters are default V1 parameters from Stigliani *et al.*[39,41], which are based on
human psychophysics[89]. The off-transient IRF is identical to the on-transient IRF but with opposite
sign, generating a response at stimulus offset. The area under the sustained IRF sums to 1, and area
under each transient IRF sums to 0.

For each channel, we compute the spatiotemporal pRF response to a stimulus sequence by
first applying the dot product between the spatial pRF and the stimulus sequence at each time point
(millisecond resolution). This spatial pRF output is then convolved with the channel's neural temporal
IRFs. The resulting spatiotemporal response is then rectified to remove negative values in the
transient channels as we reasoned that either on- or off-transient responses will increase BOLD
responses (sustained responses are always positive). The rectified sustained, on-transient, and off-
transient channel responses are then subject to the same static power-law nonlinearity, controlled
by the exponent parameter (CST_n), resulting in the following neural response for each channel:

807
$$\text{Neural response}_{CST_i}(t) = [\,|IRF_i(t)\ *\ [\int S(x,y,t) \cdot G(x,y)\,dxdy]|\,]^{CST_n} \qquad (5)$$

where $i = [1,2,3]$ indicating the sustained, on-transient, or off-transient channel, t is time in
ms, $*$ indicates convolution, and the power-law exponent (CST_n) is bound between 0.1–1,
compressing the spatiotemporal channel responses. We use a compressive nonlinearity as we
reasoned that simultaneous suppression is due to subadditive summation.

After predicting neural responses for each channel, we sum on- and off-transient channels.
The sustained channel and combined transient channels are then convolved with the HRF and

downsampled to 1 s to predict fMRI data. The voxel's response is the weighted sum of the two (β_S,

β_T) time series. More details about the CST model can be found in Kim *et al.*[51].

Alternative pRF models: In addition to the main pRF models, we tested two alternative

spatiotemporal pRF models—CST$_{opt}$ and DN-ST—for 7 of our participants who took part in a

separate spatiotemporal retinotopy experiment[51], and a Difference of Gaussians (DoG) pRF model[48].

We used CST$_{opt}$ and DN-ST pRF model parameters that were optimized with a default HRF to match

the main CST pRF model.

CST$_{opt}$: The same model like the above-mentioned CST model, but using optimized spatial

and temporal pRF parameters for each voxel, estimated from the separate Kim *et al.* experiment[51],

to understand the impact of using mostly fixed pRF parameters in the CST model. When describing

CST$_{opt}$ model performance, we refer to the main CST model as CST$_{fix}$, because most its pRF

parameters are fixed (spatial parameters from the Toonotopy experiment, a fixed time constant from

Stigliani *et al.*[39,41]), except for the exponent (CST_n), which is estimated from the SEQ-SIM data.

DN-ST: A divisive normalization spatiotemporal pRF model, to test if compressive

spatiotemporal summation within the pRF with a different mathematical form can equally well predict

the SEQ-SIM data. The DN-ST model implements subadditive summation using divisive

normalization and an exponential decay function[40,42,44]. As for the CST$_{opt}$, DN-ST model parameters

are optimized for each voxel from a separate spatiotemporal retinotopy experiment by Kim *et al.*[51].

DN-ST pRF model. The DN-ST model has a 2D circular Gaussian spatial pRF combined with

a temporal IRF that contains a divisive normalization and an exponential decay function as

implemented in Kim *et al.*[51]:

$$\text{Neural response}_{DN\text{-}ST}(t) = \frac{|r(t)|^n}{\sigma_{DN}{}^n + [|r(t)| * IRF_{DN2}(t)]^n} \qquad (6)$$

where t is time in ms, σ_{DN} is a semi-saturation constant, n is the exponent, and $r(t)$ is the

linear component of the neural response (computed as the convolution between the neural temporal

impulse response function IRF_{DN1} and the spatial pRF response to the stimulus sequence (same as

equation 1):

$$r(t) = IRF_{DN1}(t) * [S(x, y, t) \cdot G(x, y)] \qquad (7)$$

where IRF_{DN1} is a gamma function with time t in ms and first time constant τ_1 in ms:

$$IRF_{DN1}(t) = te^{-t/\tau_1} \qquad (8)$$

The second temporal IRF in the denominator of the neural response acts as a low-pass filter using

an exponential decay function:

$$IRF_{DN2}(t) = e^{-t/\tau_2} \qquad (9)$$

where t is time in ms and τ_2 is the second time constant parameter in ms. More details about

the DN-ST model, spatiotemporal retinotopy experiment, and optimization procedure can be found

in Kim *et al.*[51].

Difference of Gaussians (DoG) pRF model. To test whether center-surround DoG pRFs

predict simultaneous suppression, we simulate each voxel's pRF as two 2D Gaussians, a center

from which a larger surround is subtracted[48,50]. We simulate DoG pRFs only for V1 to hV4 for three

reasons. First, the surround pRF needs to encompass more visual input than the center pRF to

predict simultaneous suppression. These visual areas have pRFs where the smaller pRF center

would encompass a subset of square stimuli and the larger suppressive surround pRF would

encompass more squares than the center. Second, the surround pRF of voxels in visual areas

beyond hV4 would likely extend far beyond the visual display, unlikely to make a significant

contribution to the response. Third, the effects of surround suppression are most prominent at early

processing stages, including LGN[24] and early visual cortex (V1-V3[48,50]).

The center Gaussian is identical to the LSS pRF, estimated from the retinotopy session

(equation 1). The surround Gaussian has the same center position with a larger size, where the scale

factor was based on the average center/surround size ratio from Aqil *et al.*[50]; V1: 7.4, V2: 6.8, V3:

7.3, and hV4: 5.8 times the center size. We used a constant scaling for all voxels within the same

visual area, because directly estimating DoG pRFs from the independent retinotopy data using the

approach by Zuiderbaan *et al.*[48] resulted in unstable model fits. This instability is likely due to the

relatively few and short blank periods in our retinotopy experiment compared to Zuiderbaan *et al.*,

which has 4 x 30s-blank periods for each 5.5-min run.

Fixed and optimized pRF parameters. Spatial pRF parameters were independently

estimated from each participant's retinotopy experiment using the CSS pRF model, resulting in a

pRF center (x_0, y_0), standard deviation (σ) and exponent (CSS_n) parameter for each voxel. The

standard deviation and exponent parameter trade-off in the CSS model (see Kay *et al.*[27]), where

$\frac{\sigma}{\sqrt{CSS_n}}$ approximates the effective pRF size: the standard deviation (σ) estimated with a linear pRF

model (LSS, no spatial compression). Therefore, to reconstruct CSS pRFs, we use each voxel's

estimated CSS parameters ($x_0, y_0, \sigma,$ and CSS_n). To reconstruct LSS and CST pRFs, we use the

same estimated pRF center (x_0, y_0), but for the standard deviation (σ) we use the effective pRF size

($\frac{\sigma}{\sqrt{CSS_n}}$).

The time constant parameter (τ) for the temporal IRF in the main CST model is fixed (from

Stigliani *et al.*[39,41]) and we only optimized the exponent (CST_n) using a grid-fit approach for each

voxel. The best fitting CST_n was determined by systematically evaluating goodness-of-fit of predicted
time series with CST_n between 0.1–1 (0.05 steps) and selecting the CST_n resulting in the highest
cross-validated R^2. We used a grid-fit instead of a search-fit optimization approach to avoid estimates
getting stuck in a local minimum.

We use a fixed temporal IRF for the following reasons. First, we predicted that the main driver
of the suppression effect will be the compressive static nonlinearity (power-law exponent). Second,
by using the same spatial parameters for all pRF models estimated from the independent retinotopy
experiment, the model comparison will be more informative as differences in model performance are
due to differences in nonlinear computations, not spatial position. Third, to estimate all CST
parameters we need a separate spatiotemporal pRF retinotopy experiment[51]. We have such data for
7 out of 10 participants, which we used for comparing CST_{fix}, CST_{opt}, and DN-ST spatiotemporal
models. For this comparison, we restricted our analysis to voxels whose pRF centers overlap the
square stimuli in the SEQ-SIM experiment, as well as voxels whose variance explained by the
spatiotemporal pRF model was 20% or higher, and whose split-half reliability in the SEQ-SIM
experiment was 10% or higher. As in the spatiotemporal pRF retinotopy experiment, we excluded
voxels with CST time constants (tau) larger than 1000 ms. This sub-selection of voxels results in a
substantially smaller number of voxels per visual area (~60%) than we used to compare the main
pRF models and resulted in the removal IPS0/1 results as only two participants contributed to this
visual area.

5.6   Model fitting

We fitted each voxel's pRF model prediction separately to data, using a split-half cross-validation
procedure. The maximum height of predicted BOLD time series was normalized to 1 and we added
a column of 1's to capture response offset. This resulted in two regressors (β_0, β_1) for LSS and CSS
models, and three regressors (β_0, β_S, β_T) for CST. We used linear regression (ordinary least squares)
to fit these regressors to the voxel's observed time series, separately for odd and even splits. To
determine model goodness-of-fit (variance explained), we computed the cross-validated coefficient
of determination (cv-R^2) by using the scaled predicted time series of one split to predict observed
time series from the other split and vice versa (i.e., β-weights are fixed and not refitted). Cv-R^2 values
and β-weights were averaged across split halves for each voxel. Split-half reliability across runs was
used as the noise ceiling.

To check whether CST model performance could be inflated by the extra regressor, we also
computed cross-validated adjusted-R^2, which penalizes goodness-of-fit for the number of time points

and explanatory variables. The adjusted-R^2 values were almost numerically identical to R^2 and did
not significantly affect our results nor statistical comparisons.

5.7   Linear mixed model

To quantify simultaneous suppression, we fitted a linear mixed model (LMM) to all participant's voxels
within a visual area with MATLAB's *fitlme.m,* using the maximum likelihood fitting method. This LMM
predicted the average simultaneous BOLD response of each voxel as a function of the average
sequential BOLD response, for each stimulus condition (fixed interaction effect), allowing for a
random intercept and slope per participant and stimulus condition (random interaction effect):

$$SIM\ ampl \sim 1 + SEQ\ ampl \times Condition + (1 + SEQ\ ampl \times Condition\ |\ Participant) \qquad (10)$$

where *SIM ampl* and *SEQ ampl* are a matrix (nr voxels x 4) with continuous values, *Condition*
is a categorial vector (1 x 4), and *Participant* is the group level for the random effects (10 participants
for main pRF models, 7 participants for DN-ST and CST$_{opt}$ models).

This LMM captured our data well (mean R^2 = 90%, SD = 6.6%), with V1: 86%, V2: 94%, V3:
94%, hV4: 92%, VO1/2: 97%, V3A/B: 95%, IPS0/1: 88%, LO1/2: 85%, and TO1/2: 76% variance
explained. We tested this LMM to three alternative LMMs: (i) mean sequential amplitude as a fixed
factor (no condition interaction effect) with one random intercept per participant, (ii) a fixed interaction
effect with a single intercept per participant, identical for each stimulus condition, and (iii) a fixed
interaction effect with a random participant intercept for each condition. Despite having more degrees
of freedom (45) than the alternative LMMs (4, 10, and 19), the main LMM was a better fit to the data
as it had a significantly higher log-likelihood than alternative LMMs, and lower AIC and BIC for each
visual area (F-test *p*<0.00001) (**Supplementary Fig 6**).

5.8   Summarizing results

BOLD time series. Both observed and predicted run time series were averaged across split-halves
and segmented into 23-TR time windows. These time windows spanned from 4 s pre-block onset, 8
s stimulus block, to 11 s post-block. For each voxel, we took the average time window and standard
error of the mean (SEM) across 4 repeats.

Seq vs Sim BOLD amplitude. The average data and model time windows were summarized
into 8 values per voxel (one per condition), by averaging the BOLD response within a 9-TR window
centered on the peak, spanning from either 4–12s or 5–13s after stimulus block onset. These values
were used in LMMs and scatter plots. We used a variable start per condition and visual area because
the BOLD accumulation rate differed. The start was determined by averaging (data or model) time

windows across voxels within a visual area and condition, into a "grand mean" time window and
finding the first TR after block onset where the BOLD response exceeded 10% of the total cumulative
sum. This averaging window was applied to all voxels within a visual area.

Simultaneous suppression effects. We summarized LMM results for each condition and
visual area as line fits with 95%-confidence intervals ($CI_{95\%}$) using the slope and intercept of the
individual participants (**Fig 2B** and **3B**) or average across participants (**Fig 4A**). For **Fig 4B**, we
summarized the simultaneous suppression level using the average slope and SEM across
participants. For **Fig 8**, we first averaged slopes across conditions within a participant, and then
average slopes across participants (± SEM). For **Supplementary Fig 2A,** we assessed differences
in suppression levels between consecutive visual areas (suppression deltas). We computed
suppression deltas separately for each participant by subtracting each participant's regression slopes
of the earlier visual area from the later visual area. Visual area pairs are chosen based on a
feedforward visual hierarchy for each visual processing stream[76-78]. We then calculated the average
deltas across 10 participants (± SEM) for each visual area pair and each stimulus condition. For
Supplementary Fig 2B, we first calculated the average slopes across stimulus conditions within a
participant, then computed the delta suppression slopes between pairs of visual areas within
participants, and then computed the average delta suppression across participants (± SEM).

PRF parameters. We resampled pRF size, exponents (CSS_n, CST_n, DN-ST n), time
constants (CST_{opt} tau, DN-ST tau_1 and tau_2), DN-ST semi-saturation constants, and CST β_S and β_T
1000x with replacement within a participant's visual area, because the number of voxels varied
across areas and participants. For pRF size, exponent, time constant, and semi-saturation constant,
we report the median resampled parameter for each participant and visual area because the V1 and
V2 CST_n were not normally distributed (see **Supplementary Fig 4**). CST β_S and β_T were normally
distributed; hence, we report the average resampled beta weights per participant and visual area.
For group results, we report the average (± SEM) across participants' mean or median resampled
parameter value, for each visual area. For **Supplementary Figs 2B and 2C**, we first compute the
difference in median pRF size (or CST exponent) for each visual area pair within participants, and
then average delta pRF size (or CST exponent) values across participants (± SEM).

5.9　Statistical analyses

To quantify differences in LMM regression slopes, we ran a two-way repeated measures ANOVA
with factors visual area and stimulus conditions across participants. To quantify differences in pRF
model cv-R^2, we ran a two-way repeated measures ANOVA with factors pRF model and visual area

(ROI) across voxels of all participants and visual areas. For both ANOVA results, if there was a main

effect ($p<0.05$), we used Bonferroni-corrected post-hoc multiple comparison t-tests (two-sided) to

evaluate differences between pRF models, or visual area and stimulus condition. We used Pearson's

correlation (*r*) to quantify the relationship between participant slopes averaged across conditions and

effective pRF size, exponents (*CST$_n$* or DN-ST *n*), time constants (CST$_{opt}$ tau, DN-ST tau$_1$ and tau$_2$),

or DN-ST semi-saturation constants across visual areas.

6 References

1. Duncan, J. The locus of interference in the perception of simultaneous stimuli. *Psychol Rev* **87**, 272-300 (1980).
2. Scharff, A., Palmer, J. & Moore, C. M. Evidence of fixed capacity in visual object categorization. *Psychon Bull Rev* **18**, 713-721 (2011). https://doi.org:10.3758/s13423-011-0101-1
3. Pelli, D. G., Palomares, M. & Majaj, N. J. Crowding is unlike ordinary masking: distinguishing feature integration from detection. *J Vis* **4**, 1136-1169 (2004). https://doi.org:10.1167/4.12.12
4. Luck, S. J. & Vogel, E. K. The capacity of visual working memory for features and conjunctions. *Nature* **390**, 279-281 (1997). https://doi.org:10.1038/36846
5. Miller, E. K., Gochin, P. M. & Gross, C. G. Suppression of visual responses of neurons in inferior temporal cortex of the awake macaque by addition of a second stimulus. *Brain Res* **616**, 25-29 (1993). https://doi.org:10.1016/0006-8993(93)90187-r
6. Recanzone, G. H., Wurtz, R. H. & Schwarz, U. Responses of MT and MST neurons to one and two moving objects in the receptive field. *Journal of neurophysiology* **78**, 2904-2915 (1997). https://doi.org:10.1152/jn.1997.78.6.2904
7. Reynolds, J. H., Chelazzi, L. & Desimone, R. Competitive mechanisms subserve attention in macaque areas V2 and V4. *J Neurosci* **19**, 1736-1753 (1999). https://doi.org:10.1523/JNEUROSCI.19-05-01736.1999
8. Kastner, S., de Weerd, P., Desimone, R. & Ungerleider, L. G. Mechanisms of Directed Attention in the Human Extrastriate Cortex as Revealed by Functional MRI. *Science* **282**, 108-111 (1998). https://doi.org:10.1126/science.282.5386.108
9. Kastner, S. *et al.* Modulation of sensory suppression: implications for receptive field sizes in the human visual cortex. *Journal of neurophysiology* **86**, 1398-1411 (2001). https://doi.org:10.1152/jn.2001.86.3.1398
10. Beck, D. M. & Kastner, S. Stimulus context modulates competition in human extrastriate cortex. *Nat Neurosci* **8**, 1110-1116 (2005). https://doi.org:10.1038/nn1501
11. McMains, S. A. & Kastner, S. Interactions of top-down and bottom-up mechanisms in human visual cortex. *J Neurosci* **31**, 587-597 (2011). https://doi.org:10.1523/JNEUROSCI.3766-10.2011
12. Kim, N. Y., Pinsk, M. A. & Kastner, S. Neural Basis of Biased Competition in Development: Sensory Competition in Visual Cortex of School-Aged Children. *Cerebral cortex* **31**, 3107-3121 (2021). https://doi.org:10.1093/cercor/bhab009
13. Desimone, R. & Duncan, J. Neural mechanisms of selective visual attention. *Annu Rev Neurosci* **18**, 193-222 (1995).
14. Usher, M. & Niebur, E. Modeling the Temporal Dynamics of IT Neurons in Visual Search: A Mechanism for Top-Down Selective Attention. *J Cogn Neurosci* **8**, 311-327 (1996). https://doi.org:10.1162/jocn.1996.8.4.311
15. Deco, G. & Rolls, E. T. Neurodynamics of biased competition and cooperation for attention: a model with spiking neurons. *Journal of neurophysiology* **94**, 295-313 (2005). https://doi.org:10.1152/jn.01095.2004
16. Scalf, P. E. & Beck, D. M. Competition in visual cortex impedes attention to multiple items. *J Neurosci* **30**, 161-169 (2010). https://doi.org:10.1523/JNEUROSCI.4207-09.2010
17. Maunsell, J. H. & Newsome, W. T. Visual processing in monkey extrastriate cortex. *Annu Rev Neurosci* **10**, 363-401 (1987). https://doi.org:10.1146/annurev.ne.10.030187.002051
18. Dumoulin, S. O. & Wandell, B. A. Population receptive field estimates in human visual cortex. *NeuroImage* **39**, 647-660 (2008). https://doi.org:10.1016/j.neuroimage.2007.09.034
19. Wandell, B. A. & Winawer, J. Computational neuroimaging and population receptive fields. *Trends Cogn Sci* **19**, 349-357 (2015). https://doi.org:10.1016/j.tics.2015.03.009
20. Reynolds, J. H. & Heeger, D. J. The normalization model of attention. *Neuron* **61**, 168-185 (2009). https://doi.org:10.1016/j.neuron.2009.01.002
21. Albrecht, D. G. & Hamilton, D. B. Striate cortex of monkey and cat: contrast response function. *Journal of neurophysiology* **48**, 217-237 (1982). https://doi.org:10.1152/jn.1982.48.1.217

| 1031 | 22 | Press, W. A., Brewer, A. A., Dougherty, R. F., Wade, A. R. & Wandell, B. A. Visual areas and spatial summation in human visual cortex. *Vision Res* **41**, 1321-1332 (2001). https://doi.org:10.1016/s0042-6989(01)00074-8 |

22 Press, W. A., Brewer, A. A., Dougherty, R. F., Wade, A. R. & Wandell, B. A. Visual areas and spatial
summation in human visual cortex. *Vision Res* **41**, 1321-1332 (2001). https://doi.org:10.1016/s0042-
6989(01)00074-8

23 Hansen, K. A., David, S. V. & Gallant, J. L. Parametric reverse correlation reveals spatial linearity of
retinotopic human V1 BOLD response. *NeuroImage* **23**, 233-241 (2004).
https://doi.org:10.1016/j.neuroimage.2004.05.012

24 Solomon, S. G., White, A. J. & Martin, P. R. Extraclassical receptive field properties of parvocellular,
magnocellular, and koniocellular cells in the primate lateral geniculate nucleus. *J Neurosci* **22**, 338-
349 (2002). https://doi.org:10.1523/JNEUROSCI.22-01-00338.2002

25 Pihlaja, M., Henriksson, L., James, A. C. & Vanni, S. Quantitative multifocal fMRI shows active
suppression in human V1. *Hum Brain Mapp* **29**, 1001-1014 (2008).
https://doi.org:10.1002/hbm.20442

26 Vanni, S. & Rosenstrom, T. Local non-linear interactions in the visual cortex may reflect global
decorrelation. *J Comput Neurosci* **30**, 109-124 (2011). https://doi.org:10.1007/s10827-010-0239-2

27 Kay, K. N., Winawer, J., Mezer, A. & Wandell, B. A. Compressive spatial summation in human visual
cortex. *Journal of neurophysiology* **110**, 481-494 (2013). https://doi.org:10.1152/jn.00105.2013

28 Tolhurst, D. J., Walker, N. S., Thompson, I. D. & Dean, A. F. Non-linearities of temporal summation
in neurones in area 17 of the cat. *Exp Brain Res* **38**, 431-435 (1980).
https://doi.org:10.1007/BF00237523

29 Boynton, G. M., Engel, S. A., Glover, G. H. & Heeger, D. J. Linear systems analysis of functional
magnetic resonance imaging in human V1. *J Neurosci* **16**, 4207-4221 (1996).
https://doi.org:10.1523/JNEUROSCI.16-13-04207.1996

30 Birn, R. M., Saad, Z. S. & Bandettini, P. A. Spatial heterogeneity of the nonlinear dynamics in the
FMRI BOLD response. *NeuroImage* **14**, 817-826 (2001). https://doi.org:10.1006/nimg.2001.0873

31 Miller, K. L. *et al.* Nonlinear temporal dynamics of the cerebral blood flow response. *Hum Brain Mapp*
13, 1-12 (2001).

32 Motter, B. C. Modulation of transient and sustained response components of V4 neurons by temporal
crowding in flashed stimulus sequences. *J Neurosci* **26**, 9683-9694 (2006).
https://doi.org:10.1523/JNEUROSCI.5495-05.2006

33 Hasson, U., Yang, E., Vallines, I., Heeger, D. J. & Rubin, N. A hierarchy of temporal receptive
windows in human cortex. *J Neurosci* **28**, 2539-2550 (2008).
https://doi.org:10.1523/JNEUROSCI.5487-07.2008

34 Yesilyurt, B., Ugurbil, K. & Uludag, K. Dynamics and nonlinearities of the BOLD response at very
short stimulus durations. *Magn Reson Imaging* **26**, 853-862 (2008).
https://doi.org:10.1016/j.mri.2008.01.008

35 Horiguchi, H., Nakadomari, S., Misaki, M. & Wandell, B. A. Two temporal channels in human V1
identified using fMRI. *NeuroImage* **47**, 273-280 (2009).
https://doi.org:10.1016/j.neuroimage.2009.03.078

36 Nishimoto, S. & Gallant, J. L. A three-dimensional spatiotemporal receptive field model explains
responses of area MT neurons to naturalistic movies. *J Neurosci* **31**, 14551-14564 (2011).
https://doi.org:10.1523/JNEUROSCI.6801-10.2011

37 Honey, C. J. *et al.* Slow cortical dynamics and the accumulation of information over long timescales.
Neuron **76**, 423-434 (2012). https://doi.org:10.1016/j.neuron.2012.08.011

38 Mattar, M. G., Kahn, D. A., Thompson-Schill, S. L. & Aguirre, G. K. Varying Timescales of Stimulus
Integration Unite Neural Adaptation and Prototype Formation. *Current biology : CB* **26**, 1669-1676
(2016). https://doi.org:10.1016/j.cub.2016.04.065

39 Stigliani, A., Jeska, B. & Grill-Spector, K. Encoding model of temporal processing in human visual
cortex. *Proc Natl Acad Sci U S A* **114**, E11047-E11056 (2017).
https://doi.org:10.1073/pnas.1704877114

40 Zhou, J., Benson, N. C., Kay, K. N. & Winawer, J. Compressive Temporal Summation in Human
Visual Cortex. *J Neurosci* **38**, 691-709 (2018). https://doi.org:10.1523/JNEUROSCI.1724-17.2017

41 Stigliani, A., Jeska, B. & Grill-Spector, K. Differential sustained and transient temporal processing
across visual streams. *PLoS computational biology* **15**, e1007011 (2019).
https://doi.org:10.1371/journal.pcbi.1007011

42 Zhou, J., Benson, N. C., Kay, K. & Winawer, J. Predicting neuronal dynamics with a delayed gain
control model. *PLoS computational biology* **15**, e1007484 (2019).
https://doi.org/10.1371/journal.pcbi.1007484
43 Hendrikx, E., Paul, J. M., van Ackooij, M., van der Stoep, N. & Harvey, B. M. Visual timing-tuned
responses in human association cortices and response dynamics in early visual cortex. *Nat Commun*
13, 3952 (2022). https://doi.org/10.1038/s41467-022-31675-9
44 Groen, I. I. A. *et al.* Temporal dynamics of neural responses in human visual cortex. *J Neurosci* **42**,
7562-7580 (2022). https://doi.org/10.1523/JNEUROSCI.1812-21.2022
45 Friston, K. J., Mechelli, A., Turner, R. & Price, C. J. Nonlinear responses in fMRI: the Balloon model,
Volterra kernels, and other hemodynamics. *NeuroImage* **12**, 466-477 (2000).
https://doi.org/10.1006/nimg.2000.0630
46 Henson, R. N., Price, C. J., Rugg, M. D., Turner, R. & Friston, K. J. Detecting latency differences in
event-related BOLD responses: application to words versus nonwords and initial versus repeated
face presentations. *NeuroImage* **15**, 83-97 (2002). https://doi.org/10.1006/nimg.2001.0940
47 Lewis, L. D., Setsompop, K., Rosen, B. R. & Polimeni, J. R. Fast fMRI can detect oscillatory neural
activity in humans. *Proc Natl Acad Sci U S A* **113**, E6679-E6685 (2016).
https://doi.org/10.1073/pnas.1608117113
48 Zuiderbaan, W., Harvey, B. M. & Dumoulin, S. O. Modeling center-surround configurations in
population receptive fields using fMRI. *J Vis* **12**, 10 (2012). https://doi.org/10.1167/12.3.10
49 DeSimone, K. & Schneider, K. A. Distinguishing Hemodynamics from Function in the Human LGN
Using a Temporal Response Model. *Vision (Basel)* **3** (2019). https://doi.org/10.3390/vision3020027
50 Aqil, M., Knapen, T. & Dumoulin, S. O. Divisive normalization unifies disparate response signatures
throughout the human visual hierarchy. *Proc Natl Acad Sci U S A* **118** (2021).
https://doi.org/10.1073/pnas.2108713118
51 Kim, I., Kupers, E. R., Lerma-Usabiaga, G. & Grill-Spector, K. Characterizing spatiotemporal
population receptive fields in human visual cortex with fMRI. *J Neurosci* **44**, e0803232023 (2024).
https://doi.org/10.1523/JNEUROSCI.0803-23.2023
52 Maunsell, J. H., Nealey, T. A. & DePriest, D. D. Magnocellular and parvocellular contributions to
responses in the middle temporal visual area (MT) of the macaque monkey. *J Neurosci* **10**, 3323-
3334 (1990). https://doi.org/10.1523/JNEUROSCI.10-10-03323.1990
53 De Valois, R. L. & Cottaris, N. P. Inputs to directionally selective simple cells in macaque striate
cortex. *Proc Natl Acad Sci U S A* **95**, 14488-14493 (1998). https://doi.org/10.1073/pnas.95.24.14488
54 Ray, S. & Maunsell, J. H. Different origins of gamma rhythm and high-gamma activity in macaque
visual cortex. *PLoS biology* **9**, e1000610 (2011). https://doi.org/10.1371/journal.pbio.1000610
55 Jacques, C. *et al.* Corresponding ECoG and fMRI category-selective signals in human ventral
temporal cortex. *Neuropsychologia* **83**, 14-28 (2016).
https://doi.org/10.1016/j.neuropsychologia.2015.07.024
56 Finzi, D. *et al.* Differential spatial computations in ventral and lateral face-selective regions are
scaffolded by structural connections. *Nat Commun* **12**, 2278 (2021). https://doi.org/10.1038/s41467-
021-22524-2
57 Croner, L. J. & Kaplan, E. Receptive fields of P and M ganglion cells across the primate retina. *Vision*
Res **35**, 7-24 (1995). https://doi.org/10.1016/0042-6989(94)E0066-T
58 Henry, C. A., Jazayeri, M., Shapley, R. M. & Hawken, M. J. Distinct spatiotemporal mechanisms
underlie extra-classical receptive field modulation in macaque V1 microcircuits. *Elife* **9** (2020).
https://doi.org/10.7554/eLife.54264
59 Polimeni, J. R. & Lewis, L. D. Imaging faster neural dynamics with fast fMRI: A need for updated
models of the hemodynamic response. *Prog Neurobiol* **207**, 102174 (2021).
https://doi.org/10.1016/j.pneurobio.2021.102174
60 Macevoy, S. P. & Epstein, R. A. Decoding the representation of multiple simultaneous objects in
human occipitotemporal cortex. *Current biology : CB* **19**, 943-947 (2009).
https://doi.org/10.1016/j.cub.2009.04.020
61 Rust, N. C. & Dicarlo, J. J. Selectivity and tolerance ("invariance") both increase as visual information
propagates from cortical area V4 to IT. *J Neurosci* **30**, 12978-12995 (2010).
https://doi.org/10.1523/JNEUROSCI.0179-10.2010

62   Cheng, K., Hasegawa, T., Saleem, K. S. & Tanaka, K. Comparison of neuronal selectivity for
stimulus speed, length, and contrast in the prestriate visual cortical areas V4 and MT of the macaque
monkey. *Journal of neurophysiology* **71**, 2269-2280 (1994). https://doi.org:10.1152/jn.1994.71.6.2269
63   Tootell, R. B. *et al.* Functional analysis of human MT and related visual cortical areas using magnetic
resonance imaging. *J Neurosci* **15**, 3215-3230 (1995). https://doi.org:10.1523/JNEUROSCI.15-04-
03215.1995
64   Smith, A. T., Greenlee, M. W., Singh, K. D., Kraemer, F. M. & Hennig, J. The processing of first- and
second-order motion in human visual cortex assessed by functional magnetic resonance imaging
(fMRI). *J Neurosci* **18**, 3816-3830 (1998). https://doi.org:10.1523/JNEUROSCI.18-10-03816.1998
65   Vanduffel, W. *et al.* Visual motion processing investigated using contrast agent-enhanced fMRI in
awake behaving monkeys. *Neuron* **32**, 565-577 (2001). https://doi.org:10.1016/s0896-
6273(01)00502-5
66   An, X. *et al.* Distinct functional organizations for processing different motion signals in V1, V2, and V4
of macaque. *J Neurosci* **32**, 13363-13379 (2012). https://doi.org:10.1523/JNEUROSCI.1900-12.2012
67   Nandy, A. S., Mitchell, J. F., Jadi, M. P. & Reynolds, J. H. Neurons in Macaque Area V4 Are Tuned
for Complex Spatio-Temporal Patterns. *Neuron* **91**, 920-930 (2016).
https://doi.org:10.1016/j.neuron.2016.07.026
68   Mikellidou, K. *et al.* Cortical BOLD responses to moderate- and high-speed motion in the human
visual cortex. *Sci Rep* **8**, 8357 (2018). https://doi.org:10.1038/s41598-018-26507-0
69   Adelson, E. H. & Bergen, J. R. Spatiotemporal energy models for the perception of motion. *J Opt Soc*
Am A **2**, 284-299 (1985). https://doi.org:10.1364/josaa.2.000284
70   Watson, A. B. & Ahumada, A. J., Jr. Model of human visual-motion sensing. *J Opt Soc Am A* **2**, 322-
341 (1985). https://doi.org:10.1364/josaa.2.000322
71   Heeger, D. J. Modeling simple-cell direction selectivity with normalized, half-squared, linear
operators. *Journal of neurophysiology* **70**, 1885-1898 (1993).
https://doi.org:10.1152/jn.1993.70.5.1885
72   Simoncelli, E. P. & Heeger, D. J. A model of neuronal responses in visual area MT. *Vision Res* **38**,
743-761 (1998). https://doi.org:10.1016/s0042-6989(97)00183-1
73   Russ, B. E., Koyano, K. W., Day-Cooney, J., Perwez, N. & Leopold, D. A. Temporal continuity
shapes visual responses of macaque face patch neurons. *Neuron* **111**, 903-914 e903 (2023).
https://doi.org:10.1016/j.neuron.2022.12.021
74   Wallis, G. & Bulthoff, H. Learning to recognize objects. *Trends Cogn Sci* **3**, 22-31 (1999).
https://doi.org:10.1016/s1364-6613(98)01261-3
75   Zhuang, C. *et al.* Unsupervised neural network models of the ventral visual stream. *Proc Natl Acad*
Sci U S A **118** (2021). https://doi.org:10.1073/pnas.2014196118
76   Weiner, K. S. & Grill-Spector, K. Neural representations of faces and limbs neighbor in human high-
level visual cortex: evidence for a new organization principle. *Psychol Res* **77**, 74-97 (2013).
https://doi.org:10.1007/s00426-011-0392-x
77   Pitcher, D. & Ungerleider, L. G. Evidence for a Third Visual Pathway Specialized for Social
Perception. *Trends Cogn Sci* **25**, 100-110 (2021). https://doi.org:10.1016/j.tics.2020.11.006
78   Wurm, M. F. & Caramazza, A. Two 'what' pathways for action and object recognition. *Trends Cogn*
Sci **26**, 103-116 (2022). https://doi.org:10.1016/j.tics.2021.10.003
79   Mruczek, R. E. & Sheinberg, D. L. Context familiarity enhances target processing by inferior temporal
cortex neurons. *J Neurosci* **27**, 8533-8545 (2007). https://doi.org:10.1523/JNEUROSCI.2106-
07.2007
80   Brady, T. F., Konkle, T. & Alvarez, G. A. Compression in visual working memory: using statistical
regularities to form more efficient memory representations. *J Exp Psychol Gen* **138**, 487-502 (2009).
https://doi.org:10.1037/a0016797
81   Ihssen, N., Linden, D. E. & Shapiro, K. L. Improving visual short-term memory by sequencing the
stimulus array. *Psychon Bull Rev* **17**, 680-686 (2010). https://doi.org:10.3758/PBR.17.5.680
82   Brainard, D. H. The Psychophysics Toolbox. *Spat Vis* **10**, 433-436 (1997).
83   Dale, A. M., Fischl, B. & Sereno, M. I. Cortical surface-based analysis. I. Segmentation and surface
reconstruction. *NeuroImage* **9**, 179-194 (1999). https://doi.org:10.1006/nimg.1998.0395

84   Poltoratski, S., Kay, K., Finzi, D. & Grill-Spector, K. Holistic face recognition is an emergent
phenomenon of spatial processing in face-selective regions. *Nat Commun* **12**, 4745 (2021).
https://doi.org:10.1038/s41467-021-24806-1
85   Smith, A. T., Singh, K. D., Williams, A. L. & Greenlee, M. W. Estimating receptive field size from fMRI
data in human striate and extrastriate visual cortex. *Cerebral cortex* **11**, 1182-1190 (2001).
https://doi.org:10.1093/cercor/11.12.1182
86   Witthoft, N. *et al.* Where is human V4? Predicting the location of hV4 and VO1 from cortical folding.
Cerebral cortex **24**, 2401-2408 (2014). https://doi.org:10.1093/cercor/bht092
87   Amano, K., Wandell, B. A. & Dumoulin, S. O. Visual field maps, population receptive field sizes, and
visual field coverage in the human MT+ complex. *Journal of neurophysiology* **102**, 2704-2718 (2009).
https://doi.org:10.1152/jn.00102.2009
88   Swisher, J. D., Halko, M. A., Merabet, L. B., McMains, S. A. & Somers, D. C. Visual topography of
human intraparietal sulcus. *J Neurosci* **27**, 5326-5337 (2007).
https://doi.org:10.1523/JNEUROSCI.0991-07.2007
89   Watson, A. B. in *Handbook of Perception and Human Performance*   (eds K. Boff, L. Kaufman, & J.
Thomas) Ch. 6, 1-43 (Wiley, 1986).

1208

Supplementary Figure 1.
Average sequential vs simultaneous BOLD amplitude of individual voxels for all stimulus condition. Each point is a voxel are colored by effective pRF size estimated from retinotopy data in six 2º non-overlapping bins. Each panel shows data of all 10 participants. *Black solid line:* Average LMM slope across participants. *Shaded area:* 95%-confidence interval across participants. *Dashed line:* Identity line, no suppression.

1222
Supplementary Figure 2. Accumulation of simultaneous suppression up the visual hierarchy. (A)
Difference in suppression levels between two visual areas in the hierarchy, for each stimulus condition.
Delta suppression values are derived by first subtracting participants' regression slopes of the earlier visual
area from the subsequent later visual area (e.g., V2–V1). *Large colored dots:* Group average of 10 participant's
delta suppression values for each area pair. Zero indicates no difference in suppression. Negative values
indicate relatively more suppression in the later than earlier visual area. Positive values indicate relatively more
suppression in the earlier than later visual area. We find that the difference in simultaneous suppression levels
across consecutive visual areas varies by stimulus condition and that there is neither a monotonic increase nor
plateauing of suppression across visual processing hierarchies. For example, for long duration stimuli, we
observe a "sawtooth" pattern where suppression increases more from V1 to V2 than V2 to V3, and more from
V3 to hV4 than hV4 to VO1/2 in the ventral stream. This suggests no monotonic increase in suppression from
mid-level area hV4 to higher-level visual areas VO1/2. *Light gray dots:* Individual participant delta suppression.
Dark blue: V2–V1. *Light blue:* V3–V2, *Dark green:* hV4–V3. *Light green:* VO1/2–-hV4. *Purple:* V3A/B–V3. *Pink:*
IPS0/1 –V3A/B. *Red:* LO1/2–V3. *Yellow:* TO1/2–LO1/2. *Error bars:* SEM across 10 participants. **(B) Difference**
in suppression levels vs median pRF size. (C) Difference in suppression levels vs median CST pRF
exponent. In panel B and C, delta suppression values are averaged across stimulus conditions within a
participant, before computing the difference in suppression between visual areas. Delta pRF size and pRF
exponent are derived by first subtracting median pRF size (or CST exponent) of the earlier visual area from
the later visual area within participants, then averaging differences values across 10 participants for each area
pair (dots). Overall, we find no clear relation between differences in suppression levels with the difference in
pRF size (B) or spatiotemporal compression (C) between paired visual areas. *Error bars*: SEM across
participants. *Dashed line:* No difference in suppression slopes.

1245
Supplementary Figure 3. Simulated pRF model predictions for a single sequential trial followed by a
simultaneous trial. Each model simulation uses a large pRF (see inset in A) that overlaps four small squares
presented for 0.2 s (short square timing). **(A) Stimulus time course.** The stimulus' visual extent is represented
as the total contrast area in a binarized stimulus frame, where pixels are summed across space for each time
point and normalized to set the maximum contrast area to 1. Because each trial has 4 squares per quadrant,
the contrast area for each square in the sequential trial (SEQ) is a fourth of the area when all squares are
shown simultaneously (SIM). **(B-D) PRF model predictions.** *Black lines & left y-axis:* predicted neural
response. *Colored lines & right y-axis:* predicted BOLD response. **(B) Linear spatial summation (LSS) pRF**
prediction (dashed gray). The LSS model sums stimulus input linearly over time and space. This linearity,
combined with individual squares in simultaneous and sequential trials being matched in duration and location
relative to the pRF, results in the LSS model predicting no simultaneous suppression. **(C) Compressive spatial**
summation (CSS) pRF prediction (dashed orange). Due to the compressive static nonlinearity, the CSS
model predicts simultaneous suppression when multiple squares (simultaneously) overlap with the pRF than
when a single square (sequentially) overlaps the pRF. The CSS pRF model sums linearly in time and as the
overall stimulus duration is similar in our experiment between the blocks of short and long conditions, it will not
predict differences in response amplitude for short vs long stimulus presentation timings (not shown in this
simulation). **(D) Compressive spatiotemporal summation (CST) pRF prediction (blue)**. *Blue dot-dashed:*
sustained spatiotemporal channel. *Blue dashed:* combined on- and off-transient spatiotemporal channel. By
explicitly encoding neural temporal transients in milliseconds, the CST model predicts larger BOLD responses
for many visual transients (SEQ) vs a few transients (SIM). The static nonlinearity produces additional
subadditive spatiotemporal summation for both sustained and transient channels, including spatial subadditivity
when multiple squares overlap the pRF. Consequently, both CST channels generate larger responses for
sequential than simultaneous presentations, and predict different responses for the short and long conditions
(not shown in simulation), which vary by a factor of 4 in number of transients (Fig 1B).

Supplementary Figure 4. Average CST pRF exponent parameter distributions. Distributions are computed by first resampling participants' data 1000x per visual area, then averaging distributions across participants. Both group average (line) and SEM (shaded area) of each visual area distribution are then upsampled 2x. *Asterisks:* median CST exponent value.

Eye movement analysis. Raw horizontal and vertical gaze position (deg) and velocity (deg/s) time
series of 5 participants during SEQ-SIM fMRI experiment were preprocessed as follows. First, we
removed time points occurring within -100 to 100 ms of blinks. Second, given large amounts of spatial
noise, we used the Identification by Two-Means Clustering algorithm[1] to label robust fixation periods
and their visual field location. If gaze locations jumped between two means due to noise, we
recentered data to a single mean. Third, we removed time points (and surrounding 2 ms) if they had
(i) a velocity larger than a typical saccade up to 8º (400 deg/s)[2], (ii) an absolute gaze location that
extended beyond the stimulus display (radius = 10º), or (iii) a gaze position SD 2.5x larger than SD
across horizontal and vertical time series. We excluded 7 runs with < 20% data, resulting in 32 runs
total. We visualized participant's median and kernel density of gaze location across runs in visual
space.
1286

1287

Supplementary Figure 5. Eye fixation locations during SEQ-SIM experiment. Normalized fixation density
is shown for 5 participants (S1, S2, S3, S4, S9) and across all participants (N=5). *Red cross:* Median gaze
location across runs. *Contour lines*: Density at 1st, 10th, 50th, 100th percentile, correspond to magenta, dark
blue, green, and yellow sections. *Light gray squares:* Outlined location of large squares closest to fixation
([x,y]=[0,0]). *Dark gray squares:* Outlined location of small squares closest to fixation.

1. Hessels, R.S., *et al.*, Noise-robust fixation detection in eye movement data: Identification by two-
means clustering (I2MC). *Behav Res Methods* **49**(5), 1802-1823 (2017).
2. Smeets, J.B. and Hooge, I.T. Nature of variability in saccades. *J Neurophysiol* **90**(1), 12-20 (2003).

Supplementary Figure 6. Comparison of linear mixed models (LMMs). For each model comparison metric, we computed the difference between main LMM and alternative LMM. The main LMM fits the data better than all alternative LMMs, for each visual area, on each metric. *Right:* Difference in LMM log likelihood. *Middle:* Difference in LMM AIC. *Left:* Difference in LMM BIC. The main LMM uses a fixed intercept and slope for mean sequential (SEQ) amplitude as a function of stimulus condition and allowing for random participant intercept and slope per stimulus condition. *Black bar:* Alternative LMM 1, using a fixed intercept and slope for mean sequential (SEQ) amplitude and allowing one random slope per participant. *White bar:* Alternative LMM 2, using a fixed intercept and slope for mean sequential (SEQ) amplitude as a function of stimulus condition and allowing one random slope per participant. *Yellow bar:* Alternative LMM 3, using a fixed intercept and slope for mean sequential (SEQ) amplitude as a function of stimulus condition and allowing a random slope per participant, per condition.

1296

1308 **Supplementary Table 1.**

1309 ***Summary of suppression slopes for 9 visual areas and 4 stimulus conditions.*** *Data are scale factors and*

1310 *have arbitrary units. Data are from 10 participants, except for IPS0/1 (4 participants) and TO1/2 (8 participants).*

1311 *M: mean. SE: standard error.*

Visual area	Stimulus condition							
	Small & Short		Small & Long		Big & Short		Big & Long	
	M	*SE*	*M*	*SE*	*M*	*SE*	*M*	*SE*
V1	.85	.057	.81	.023	.84	.070	.85	.036
V2	.75	.028	.63	.023	.78	.037	.78	.055
V3	.67	.040	.59	.054	.74	.039	.70	.076
hV4	.64	.037	.40	.029	.66	.040	.62	.080
VO1/2	.65	.051	.40	.034	.70	.042	.62	.070
V3A/B	.66	.051	.39	.043	.67	.035	.65	.059
IPS0/1	.63	.061	.41	.054	.67	.10	.56	.056
LO1/2	.56	.057	0.27	0.041	.61	.051	.59	.064
TO1/2	.43	.057	0.24	0.043	0.47	0.019	.47	.11

1312

Supplementary Table 2.
1314 ***Post-hoc comparisons of suppression slopes, for each visual area and stimulus condition.*** Mean
1315 condition difference (C1 – C2), standard error (SE) and 95%-confidence intervals are have arbitray units
1316 (slope). P-values are Bonferroni-corrected for multiple comparisons. * $p<0.05$, ** $p<0.01$, *** $p<0.001$.

Visual area	Condition 1	Condition 2	C1 – C2	SE	$CI_{95\%}$ Lower	$CI_{95\%}$ Upper
V1	Short & big	Long & big	-.013	.076	-.21	.19
	Short & big	Short & small	-.0071	.076	-.21	.19
	Short & big	Long & small	.030	.076	-.17	.23
	Long & big	Short & small	.0054	.076	-.20	.22
	Long & big	Long & small	.042	.076	-.19	.24
	Short & small	Long & small	.037	.076	-.16	.24
V2	Short & big	Long & big	.047	.076	-.15	.25
	Short & big	Short & small	.032	.076	-.17	.23
	Short & big	Long & small	.15	.076	-.049	.35
	Long & big	Short & small	-.016	.076	-.22	.18
	Long & big	Long & small	.12	.076	-.096	.31
	Short & small	Long & small	.12	.076	-.080	.32
V3	Short & big	Long & big	.034	.076	-.17	.23
	Short & big	Short & small	.051	.076	-.15	.25
	Short & big	Long & small	.14	.076	-.057	.34
	Long & big	Short & small	.017	.076	-.18	.22
	Long & big	Long & small	.11	.076	-.091	.31
	Short & small	Long & small	.093	.076	-.11	.29
hV4	Short & big	Long & big	.043	.076	-.16	.24
	Short & big	Short & small	.025	.076	-.18	.23
	Short & big	Long & small	.27**	.076	.066	.47
	Long & big	Short & small	-.018	.076	-.22	.18
	Long & big	Long & small	.22*	.076	.022	.42
	Short & small	Long & small	.24**	.076	.040	.44
VO1/2	Short & big	Long & big	.086	.076	-.11	.29
	Short & big	Short & small	.056	.076	-.14	.26
	Short & big	Long & small	.30***	.076	.10	.50
	Long & big	Short & small	-.030	.076	-.23	.17
	Long & big	Long & small	.22*	.076	.016	.42
	Short & small	Long & small	.25**	.076	.046	.45
V3A/B	Short & big	Long & big	.033	.076	-.17	.23
	Short & big	Short & small	.027	.076	-.17	.23
	Short & big	Long & small	.30***	.076	.099	.50
	Long & big	Short & small	-.0061	.076	-.21	.19
	Long & big	Long & small	.27**	.076	.066	.47
	Short & small	Long & small	.27**	.076	.072	.47
IPS0/1	Short & big	Long & big	.12	.12	-.21	.42
	Short & big	Short & small	.042	.12	-.27	.36
	Short & big	Long & small	.26	.12	-.056	.58
	Long & big	Short & small	-.064	.12	-.38	.25
	Long & big	Long & small	.16	.12	-.16	.47
	Short & small	Long & small	.22	.12	-.098	.54
LO1/2	Short & big	Long & big	.027	.076	-.17	.23
	Short & big	Short & small	.058	.076	-.14	.26
	Short & big	Long & small	.35***	.076	.15	.55
	Long & big	Short & small	.030	.076	-.17	.23
	Long & big	Long & small	.32***	.076	.12	.52
	Short & small	Long & small	.29***	.076	.091	.49
TO1/2	Short & big	Long & big	.14	.084	-.086	.36
	Short & big	Short & small	.040	.084	-.18	.26
	Short & big	Long & small	.24*	.084	.013	.46
	Long & big	Short & small	-.098	.084	-.32	.13
	Long & big	Long & small	.10	.084	-.12	.32
	Short & small	Long & small	.20	.084	-.027	0.42

1317 **Supplementary Table 3.**
1318 *Post-hoc comparisons of pRF model performance.* Mean model difference (M1 – M2), standard error and
1319 95%-confidence intervals are in units of percent cross-validated variance explained (cv-R^2) and correspond to
1320 violin plots in Fig 6C. P-values are Bonferroni-corrected for multiple comparisons. Significant differences are
1321 indicated with * $p<0.05$, ** $p<0.01$, or *** $p<0.001$.

Visual area	Model 1	Model 2	M1 – M2	SE	CI$_{95\%}$ Lower	CI$_{95\%}$ Upper
V1	CSS	LSS	-1.38***	0.24	-1.95	-0.804
	CST	CSS	6.54***	0.24	5.97	7.12
	CST	LSS	5.17***	0.24	4.59	5.74
V2	CSS	LSS	-0.41	0.24	-0.98	0.164
	CST	CSS	9.33***	0.24	8.76	9.90
	CST	LSS	8.92***	0.24	8.35	9.49
V3	CSS	LSS	0.25	0.24	-0.32	0.819
	CST	CSS	10.42***	0.24	9.85	11.0
	CST	LSS	10.67***	0.24	10.10	11.2
hV4	CSS	LSS	3.21***	0.32	2.45	3.97
	CST	CSS	8.02***	0.32	7.26	8.77
	CST	LSS	11.23***	0.32	10.47	12.0
VO1/2	CSS	LSS	4.92***	0.38	4.02	5.82
	CST	CSS	8.88***	0.38	7.98	9.78
	CST	LSS	13.80***	0.38	12.90	14.7
V3A/B	CSS	LSS	1.02***	0.26	0.39	1.65
	CST	CSS	8.63***	0.26	8.00	9.26
	CST	LSS	9.65***	0.26	9.02	10.3
IPS0/1	CSS	LSS	2.77**	0.78	0.91	4.63
	CST	CSS	6.77***	0.78	4.91	8.62
	CST	LSS	9.53***	0.78	7.68	11.4
LO1/2	CSS	LSS	1.16***	0.23	0.61	1.71
	CST	CSS	4.44***	0.23	3.89	5.00
	CST	LSS	5.60***	0.23	5.05	6.15
TO1/2	CSS	LSS	3.95***	0.56	2.60	5.30
	CST	CSS	3.34***	0.56	1.99	4.69
	CST	LSS	7.29***	0.56	5.95	8.64

1322
Supplementary Figure 7. Simulated Difference of Gaussians pRF model performs similarly to the LSS
pRF model. (A) V1 example voxel. *Gray shaded area:* Average ± SEM voxel time series, repeated for each
row. PRF model fits are shown in dashed lines. *Dark Blue:* Compressive spatiotemporal summation model with
fixed voxel parameters (CST, first row). *Orange:* Compressive spatial summation model (CSS, second row).
Black: Linear spatal summation model (LSS, third row). *Purple:* Difference of Gaussians model (DoG, fourth
row). DoG pRF surround size is based on each visual area's average pRF center/surround ratio reported by
Aqil *et al.* (2021)[50]. **(B) Distribution of voxel-level cross-validated variance explained for each pRF model.**
Triangle: median. *Dotted line:* noise ceiling computed from voxel's maximum split-half reliability across
participants. CST (blue), CSS (orange), and LSS (gray) violin plots are the same as in Fig 6C. *Purple*: DoG.
Each participant's data is resampled 1000x for each visual area. **(C) Model-based prediction of**
simultaneous suppression vs observed simultaneous suppresion. Panel shows the same observed and
predicted CST, CSS, and LSS suppression levels as Fig 7, with the addition of predicted suppression levels
by the simulated DoG pRFs (semi-saturated filled purple circles) Model-based points and errorbars show
average and SEM across 10 participants.

1337
Supplementary Figure 8. Comparison of fixed vs optimized CST and DN-ST pRF model performance.
(A) VO1/2 example voxel. *Gray shaded area:* Average ± SEM voxel time series. CST_fix data are from the same
voxel as in Fig 6B. CST_opt and DN-ST example voxels show corresponding time series to CST_fix time series
from the same participant (S3), but have different pRF parameters from Kim *et al.* (2024)[51]. PRF model fits are
shown in dashed lines. *Dark Blue:* Compressive spatiotemporal summation model with fixed voxel parameters
(CST_fix, top row). *Cyan:* Compressive spatiotemporal summation model with optimized voxel parameters
(CST_opt, middle row). *Pink:* Divisive normalization spatiotemporal summation model with optimized voxel
parameters (DN-ST, bottom row). **(B) Distribution of voxel-level cross-validated variance explained for**
each pRF model. Each violin plot contains data from the 7 overlapping participants with Kim *et al.* (2024).
Triangle: Median. *Dotted line:* Noise ceiling computed from voxel's maximum split-half reliability across

participants. *Blue:* CST_{fix}. *Cyan*: CST_{opt}. *Pink:* DN-ST. Each participant's data is resampled 1000x for each visual area. A two-way repeated measures ANOVA revealed significant effects of pRF model ($F(2)=1.1\times10^2$, $p=6.3\times10^{-47}$) and ROI ($F(7)=1.3\times10^3$, $p<10^{-47}$) on cv-R^2, with CST models outperforming DN-ST on average by about 3%, as well as a significant interaction between pRF model and ROI ($F(2,7)=5.0$, $p=1.6\times10^{-9}$). Post-hoc Bonferroni-corrected t-tests revealed that both CST models significantly explain more cv-R^2 than the DN-ST model in all visual areas, except for CST_{opt} in TO1/2. In addition, the CST_{fix} model explains significantly more cv-R^2 than the CST_{opt} in several visual areas (V1, hV4, V3A/B, LO1/2, and TO1/2). **(C) Pairwise model comparison for each visual area.** *Bars:* Group average voxelwise difference in cv-R^2 between two pRF models. *Error bars:* SEM across participants. *Individual dots:* Average difference for each participant. *Dark blue–cyan:* CST_{fix} vs CST_{opt}. *Dark blue–pink:* CST_{fix} vs DN-ST. *Cyan–pink:* CST_{opt} vs DN-ST.

Supplementary Table 4.
Post-hoc comparisons of spatiotemporal pRF model performance. Mean model difference (M1 – M2), standard error, and 95%-confidence intervals are in units of percent cross-validated variance explained (cv-R^2) and correspond to violin plots in Supplementary Fig 8B. Data are from 7 overlapping participants with Kim *et al.* (2024)[51]. IPS0/1 results are removed as only two participants contributed data for these visual areas. P-values are Bonferroni-corrected for multiple comparisons. Significant differences are indicated with * $p<0.05$, ** $p<0.01$, or *** $p<0.001$.

Visual area	Model 1	Model 2	M1 – M2	SE	CI$_{95\%}$ Lower	CI$_{95\%}$ Upper
V1	CST_{fix}	CST_{opt}	2.35***	0.55	1.03	3.67
	CST_{fix}	DN-ST	2.89***	0.55	1.58	4.21
	CST_{opt}	DN-ST	0.54	0.55	-0.77	1.86
V2	CST_{fix}	CST_{opt}	-0.16	0.43	-1.18	0.870
	CST_{fix}	DN-ST	1.24*	0.43	0.21	2.26
	CST_{opt}	DN-ST	1.39**	0.43	0.36	2.42
V3	CST_{fix}	CST_{opt}	0.95	0.44	-0.10	1.99
	CST_{fix}	DN-ST	3.00***	0.44	1.96	4.05
	CST_{opt}	DN-ST	2.06***	0.44	1.01	3.10
hV4	CST_{fix}	CST_{opt}	1.79*	0.64	0.27	3.31
	CST_{fix}	DN-ST	5.08***	0.64	3.56	6.60
	CST_{opt}	DN-ST	3.23***	0.64	1.76	4.81
VO1/2	CST_{fix}	CST_{opt}	0.92	0.63	-0.58	2.43
	CST_{fix}	DN-ST	4.56***	0.63	3.05	6.07
	CST_{opt}	DN-ST	3.63***	0.63	2.12	5.15
V3A/B	CST_{fix}	CST_{opt}	3.34***	0.51	2.12	4.56
	CST_{fix}	DN-ST	4.58***	0.51	3.36	5.80
	CST_{opt}	DN-ST	1.24*	0.51	0.017	2.46
LO1/2	CST_{fix}	CST_{opt}	1.35*	0.53	0.088	2.61
	CST_{fix}	DN-ST	2.88***	0.53	1.62	4.14
	CST_{opt}	DN-ST	1.53*	0.53	0.27	2.79
TO1/2	CST_{fix}	CST_{opt}	4.40*	1.56	0.65	8.14
	CST_{fix}	DN-ST	6.61***	1.56	2.86	10.4
	CST_{opt}	DN-ST	2.21	1.57	-1.55	5.98

Supplementary Figure 9. Comparison of compressive spatiotemporal pRF models. Suppression levels and pRF parameters are from voxels overlapping SEQ-SIM squares for the 7 participants overlapping with Kim

et al. (2024)[51]. In all panels: *dots/bars* show average across 7 participants. *Error bars:* SEM across 7
participants. IPS0/1 results are removed as only two participants contributed data for these visual areas. **(A)**
CST$_{fix}$, CST$_{opt}$, and DN-ST pRF model-based predictions of simultaneous suppression. Shaded *dark blue*
bars: Average ± SEM observed suppression levels in voxels with CST$_{fix}$ pRFs. *Shaded cyan bars:* Average ±
SEM observed suppression levels in voxels with CST$_{opt}$ pRFs. *Shaded pink bars:* Average ± SEM observed
suppression levels in voxels with DN-ST pRFs. *Dark blue circles*: Average ± SEM predicted simultaneous
suppression by CST$_{fix}$ pRFs. *Cyan filled circles:* Average ± SEM predicted simultaneous suppression by CST$_{opt}$
pRFs. *Pink filled circles:* Average ± SEM predicted simultaneous suppression by DN-ST pRFs. The DN-ST
pRFs tends to underpredict simultaneous suppression levels for short stimulus durations, which may be due to
less accurate temporal parameter recovery for the DN-ST compared to the CST model[51] and/or to the DN-ST
model being more sensitive to prolonged stimulus durations than visual transients[40,42] whereas the SEQ-SIM
experiment is dominated by latter. **(B-D). Simultaneous suppression levels vs CST$_{opt}$ and CST$_{fix}$ pRF**
parameters. For panels B-D (effective size, exponent, and tau pRF parameters), we first computed the median
across pRFs of a visual area for each participant (similar to Fig 8), then we calculated the average of this
median value across 7 participants. Pearson's correlation (*r*) is computed using individual participant data.
Filled colored circles: CST$_{opt}$ pRF parameters. *White circles with colored outline:* CST$_{fix}$ pRF parameters. (B)
Simultaneous suppression level vs median CST$_{opt}$ pRF effective size. (C) Simultaneous suppression level vs
CST$_{opt}$ exponent (static nonlinearity). (D) Simultaneous suppression level vs time constant τ (tau). We find that
the range of estimated spatiotemporal compression (exponent) in the CST$_{opt}$ pRF model in the Kim *et al.* (2024)
experiment is smaller, and compression is overall stronger than the spatiotemporal compression in the CST$_{fix}$
pRF model, which was optimized to the SEQ-SIM data. **(E) Average β-weights of sustained and transient**
channels for CST$_{opt}$ pRF model. Beta weights are averaged first within a participant's visual area, then
averaged across participants per visual area. *Colored bars:* Sustained channel. *White bars:* Combined transient
channel. Channels do not differ significantly from one another across visual areas. **(F-I) Simultaneous**
suppression levels vs DN-ST pRF parameters. For all panels, we first computed the median across pRFs
of a visual area for each participant (similar to Fig 8), then we calculated the average median value across
participants. Pearson's correlation (*r*) is computed using individual participant data. (F) Simultaneous
suppression level vs median DN-ST pRF effective size. (G) Simultaneous suppression level vs exponent (DN-
ST *n*). (H) Simultaneous suppression level vs time constants. *Filled colored circles*: τ_1 parameter, time
constants of the IRF. A smaller tau$_1$ results in an IRF that peaks earlier. *White circles with colored outline:* τ_2
parameter, time constant of the exponential decay. A smaller τ_2 results in quicker decay and stronger
compression. (I) Simultaneous suppression level vs semi-saturation constant (σ_{DN}). A smaller semi-saturation
results in stronger compression within the pRF. Significant effects are indicated with * *p*<0.05, ** *p*<0.01 or ***
p<0.001; *ns*: not significant.