BeeBDC: An R package and globally synthesised and flagged bee occurrence dataset

Authors

James B. Dorey[1], Erica E. Fischer[2], Paige R. Chesshire[3], Angela Nava-Bolaños[4], Robert L. O'Reilly[1], Silas Bossert[5,6], Shannon M. Collins[7], Elinor M. Lichtenberg[7], Erika M. Tucker[8], Allan Smith-Pardo[9], Armando Falcon-Brindis[10], Diego A. Guevara[11], Bruno Ribeiro[12], Diego de Pedro[13], John Pickering[14], Keng-Lou James Hung[15], Katherine A. Parys[16], Lindsie M. McCabe[17], Matthew S. Rogan[18,19], Robert L. Minckley[20], Santiago J.E. Velazco[21], Terry Griswold[17], Tracy A. Zarrillo[22], Walter Jetz[18,19], Yanina V. Sica[18,19], Michael C. Orr[23,24†], Laura Melissa Guzman[25†], John S. Ascher[26†], Alice C. Hughes[27†], Neil S. Cobb[8†]

[†]These authors jointly supervised this work

Affiliations

1. College of Science and Engineering, Flinders University, Sturt Rd, Bedford Park, 5042, SA, Australia
2. Centre for the History of Science, Technology, and Medicine, Department of History, King's College London, Strand, WC2R 2LS, London, United Kingdom
3. Department of Biological Sciences, Northern Arizona University, S Beaver St, Flagstaff, 86011, AZ, USA
4. Unidad Multidisciplinaria de Docencia e Investigación, Facultad de Ciencias, Campus Juriquilla, Universidad Nacional Autónoma de México, Boulevard Juriquilla, Jurica La Mesa, Juriquilla, 76230, Querétaro, México
5. Department of Entomology, Washington State University, Dairy Rd, Pullman, 99164-6382, WA, USA
6. Department of Entomology, National Museum of Natural History,
Smithsonian Institution, 10th and Constitution Avenue, Washington, 20560, DC, USA
7. Department of Biological Sciences and Advanced Environmental Research Institute, University of North Texas, W Mulberry St, Denton, 76201, TX, USA
8. Biodiversity Outreach Network, W Silver Spruce Ave, Flagstaff, 86001, AZ, USA
9. Animal Plant Health Inspection Service (APHIS); Plant Protection and Quarantine (PPQ); Science and Technology (S&T); Pest Identification Technology laboratory (PITL) United States Department of Agriculture (USDA), St. Suite, Sacramento, CA. 95814, USA
10. Department of Entomology, Research and Education Center, University of Kentucky, University Dr, Princeton, KY 42445
11. Departamento de Biología, Universidad Nacionalde Colombia, Bogotá, Cra 45 #268-5, D.C., Colombia
12. Programa de Pós-graduação em Ecologia e Evolução, Universidade Federal de Goiás, Goiânia, Av. Esperança, 74690-900, GO, Brazil
13. Ensenada Center for Scientific Research and Higher Education, Carr. Tijuana-Ensenada, Zona Playitas, 22860, Ensenada, Baja California, Mexico
14. Discover Life, Blue Heron Drive, Athens, GA 30605
15. Oklahoma Biological Survey, University of Oklahoma, Chesapeake St, Norman, 73019, OK, USA
16. USDA ARS Pollinator Health in Southern Crop Ecosystems Research Unit, Experiment Station Rd, Stoneville, 38776, MS, USA
17. USDA-ARS Pollinating Insects-Research Unit, Old Main Hill, Logan, 84322, UT, USA
18. Center for Biodiversity and Global Change, Yale University, Prospect St, New Haven, 06511, CT, USA
19. Department of Ecology & Evolutionary Biology, Yale University, Prospect St, New Haven, 06511, CT, USA

20. Department of Biology, University of Rochester, Rochester, 14620, NY, USA

21. Instituto de Biología Subtropical, Consejo Nacional de Investigaciones Científicas y
Técnicas, Universidad Nacional de Misiones, Puerto Iguazú, Misiones, Argentina.

22. The Connecticut Agricultural Experiment Station, Huntington St, New Haven, 06511, CT,
USA

23. Entomologie, Staatliches Museum für Naturkunde Stuttgart, Rosenstein, Stuttgart, 70191,
Baden-Württemberg, Germany

24. Key Laboratory of Zoological Systematics and Evolution, Institute of Zoology, Chinese
Academy of Sciences, Beichen West Road, Beijing, 100101, China

25. Marine and Environmental Biology, Department of Biological Sciences, University of
Southern California, Trousdale Pkwy, Los Angeles, 90089-0371, CA, USA

26. Department of Biological Sciences, National University of Singapore, Science Dr, 117558,
Singapore

27. School of Biological Sciences, University of Hong Kong, Pok Fu Lam Rd, Lung Fu Shan, Hong
Kong

corresponding author: James Dorey (jbdorey@me.com)

Abstract

Species occurrence data are foundational for research, conservation, and science communication, but the limited availability and accessibility of reliable data represents a major obstacle, particularly for insects, which face mounting pressures. We present *BeeBDC*, a new *R* package, and a global bee occurrence dataset to address this issue. We combined >18.2 million bee occurrence records from multiple public repositories (GBIF, SCAN, iDigBio, USGS, ALA) and smaller datasets, then standardised, flagged, deduplicated, and cleaned the data using the reproducible *BeeBDC R*-workflow. Specifically, we harmonised species names (following established global taxonomy), country names, and collection dates and we added record-level flags for a series of potential quality issues. These data are provided in two formats, "cleaned" and "flagged-but-uncleaned". The *BeeBDC* package with online documentation provides end users the ability to modify filtering parameters to address their research questions. By publishing reproducible *R* workflows and globally cleaned datasets, we can increase the accessibility and reliability of downstream analyses. This workflow can be implemented for other taxa to support research and conservation.

Background & Summary

Occurrence datasets are increasingly critical for scientific research, conservation, and communication worldwide. From foundational systematic[1,2], life-history[3], and conservation studies[4,5], to continental or global macroecological[6,7] or macroevolutionary analyses[8], occurrence data are used to understand the natural world and form the basis of research, policy, and management. Spatiotemporal occurrence records (e.g., from specimens, images, or observations) are being delivered to, and produced by, community scientists in quantities that were unthinkable just a decade ago, with ever-increasing identification support by professional experts[9]. However, community-generated records can be biased towards larger and more charismatic taxa[10]. Online repositories, such as the Global Biodiversity Information Facility (GBIF) and Symbiota Collection of Arthropod Network (SCAN), are invaluable data aggregators and tools in supporting the mobilisation of arthropod occurrence data to help both researchers and general audiences understand biodiversity. Concurrently and complementarily, initiatives like iNaturalist and QuestaGame (Australia) enable community and professional scientists to generate occurrence data for research, science communication, and more[9]. Occurrence data are being generated daily, making new analyses possible for previously data-poor taxa. These data are key to developing National Strategic Biodiversity and Action plans, upon which the monitoring framework of the Post-2020 Global Biodiversity Framework will depend[11]. Therefore, developing methods to aggregate and standardise such data is essential.

Despite the great utility of occurrence data, many issues can inhibit their successful use. Firstly, whilst "open data" is now mandated in many journals, data standards are inconsistently implemented. This means that these data are increasingly fragmented and thus still inaccessible. Occurrence records can be rendered partially or critically incomplete at many different phases between the initial point of data collection and point of data publication and sharing[12]. For example, poor data collection practices at the point of production (in the field) can make downstream recovery efforts impossible. Data can often be omitted or altered during transcription, digitisation, or geo-referencing, making occurrences unusable or misleading. For example, only 2.7 out of 31 million (9%) Brazilian plant occurrences were considered high-quality following data cleaning and validation by Ribeiro, et al. [13]. Misidentification can also be a major issue; for example, 58% of African gingers from 40 herbaria across 21 countries bear an incorrect name[14], highlighting the importance of accessible museum and herbarium specimens[15]. Secondly, data can be of excellent quality, digitised, and used in publications, but they may not be made available in accessible repositories. Whatever the reason, such data are effectively unavailable for — or, in the case

123   of misleading data, detrimental to — further research, conservation, and management[16].
124   Funding institutions to curate and digitise collections might fill in some of the major data gaps
125   revealed in recent global analyses of public data[6].
126
Mobilising massive datasets with numerous potential issues represents a major roadblock for
researchers and other users. A careful balance between discarding too much data and
accepting too many problematic records must be maintained. Ideally, problematic records can
instead be flagged (allowing users the choice of treatment) or fixed using a combination of
automated pipelines and expert validation[17]. The barriers are such that the data cleaning
process is often built from scratch or nearly so for each new project (re-inventing the wheel)[6,7].
Constantly rebuilding the data cleaning process can result in haphazard application of cleaning
and data quality and is a major hurdle for many researchers and conservation practitioners
that might preclude them from undertaking robust and reproducible analyses. This represents
a major accessibility problem that stalls research, management, and conservation —
particularly for research groups that lack sufficient support, expertise, facilities, or time to
develop or implement cleaning workflows — that could otherwise produce excellent research.
This results in major knowledge gaps of species distributions and ecological niches, especially
in developing economies and over extended timescales[18]. Until now, very few major efforts
have been made to combine, clean/flag, and make accessible the world's occurrence datasets;
this is particularly true for diverse and ecologically important arthropods[7,19,20]. We tackle this
issue of data cleaning and reproducibility using a major group that is taxonomically extensive
(>20,000 valid species), ecologically and economically important, and for which research is
booming globally: bees.
146
Bees (Hymenoptera: Anthophila) are a keystone taxon of terrestrial ecosystems across the
globe and the most significant group of pollinating animals in both agricultural and natural
settings[21,22]. As such, great efforts are made to understand their spatial distributions[6] and it is
critical for research on this flagship invertebrate taxon to be robust and correctly analysed.
Despite the urgent need for quality occurrence data, there are many barriers to their use,
particularly accessibility and reliability. Removing these hurdles will encourage new research
and enable best practices at greatly reduced effort and financial cost. At the time of download
and to our knowledge, there are ~18.1 million bee occurrence records that are publicly
available in major public repositories and more that are private or otherwise inaccessible. Here
we collate and process several bee datasets for open-use by all interested parties. We also
produce a machine-readable version of the global bee taxonomy and country-level checklist
available on the Discover Life website[23]. Specifically, we curated multiple raw datasets,
combined curated records, taxonomically harmonized species names, and annotated
potentially problematic records. Herein, we combined public and private datasets to provide
(i) a cleaned and standardized dataset (6.8 million occurrences), (ii) a flagged-but-uncleaned
dataset (for users to filter based on our flagging columns; 18.2 million occurrences), (iii) all R-
scripts and input files needed to produce both datasets (Fig. 1), and (iv) summary figures and
tables highlighting the state of global bee data. All data and scripts are accessible,
documented, and open access. Importantly, we plan to periodically update and publish new
versions of the *BeeBDC* occurrence data cleaning package[24] and bee data. This will leave room
for improved versions and functionality, especially because new occurrence data are
consistently being added to online databases. Despite being developed specifically for bee
datasets, many of our functions are generic and can be applied to various taxa for which similar
issues exist.
171

Methods
Data sources

We sourced data from publicly available online data repositories
(https://doi.org/10.25451/flinders.21709757; ExtraTables/MajorRepoAttributes_2023-09-
01.xlsx) as well as select non-public, private, or otherwise publicly inaccessible sources that
were willing to share their data for this study. We use the term "data source" in the
manuscript, but recognise that these sources can be very distinct in function. For example,
aggregators serve data that is created and curated by multiple distinct data providers. The
primary repositories that we sourced data from were (i) GBIF, (ii) SCAN, (iii) Integrated
Digitized Biocollections (iDigBio), (iv) the United States Geological Survey (USGS), and (v) the
Atlas of Living Australia (ALA). Additionally, we have sought out and incorporated smaller
public or private data sources from (i) Allan Smith-Pardo (ASP), (ii) Robert Minckley (BMin),
(iii) Elle Pollination Ecology Lab (EPEL[25]), (iv) *Bombus* Montana (Bmont; Casey Delphia[26]), (v)
Ecdysis (Ecd[27]), (vi) Gaiarsa, et al. [28] (Gai), (vii) the Connecticut Agricultural Experiment Station
(CAES[29,30]), (viii), USDA ARS South-eastern USA (Parys), (ix) Eastern Colorado (Arathi Seshadri),
(xi) Florida State Collection of Arthropods (FSCA), (xi) Armando Falcon-Brindis (Arm), and (xii)
four more publicly available bee datasets from the literature (SMC, Bal, Lic, Dor)[3,4,31-37]. These
datasets were collated by directly engaging and collaborating with their owners, particularly
where data gaps were perceived, but with a particular emphasis on the Americas.

Global Biodiversity Information Facility data were downloaded via the online portal on the 14th
of August 2023[38-44] on a per-family basis. SCAN data were downloaded between the 14th and
20th of August 2023[45-51] on a per-family basis and by subsets of collections if the one million
record limit was surpassed (the maximum capacity for a single download). Integrated Digitized
Biocollections data were downloaded on the 1st of September 2023[52-58] by selecting all
Apoidea records and filtering to the seven bee families (Andrenidae, Apidae, Colletidae,
Halictidae, Megachilidae, Melittidae, and Stenotritidae). United States Geological Survey data
were provided directly by Sam Droege on the 19th of November 2022[59]. Finally, ALA data were
downloaded on the 1st of September 2023[60] using a *BeeBDC* wrapper function,
atlasDownloader, which uses their *R*-package, *galah*[61].

We sourced taxonomic name and checklist data from information hosted on the Discover Life
website[23]. Our bee taxonomy is current as of the 20th of August 2023 and the bee country
checklist as of the 21st of August 2023. Both of these datasets are maintained by Ascher and
Pickering [23] and are critical sources to ensure occurrence quality. We also added small updates
to both datasets based on those published in Orr, et al. [6] and to reflect orthographic variants
that were identified during manual data and error checks. We undertook manual checks of
over 4,500 flagged interactive bee species maps (mostly in the Americas) to highlight and
correct potential errors in these datasets and our functions.

Data-cleaning workflow

Analyses were undertaken in *R* version 4.3.1[62] and *R-Studio* "Beagle Scouts" Release. The
BeeBDC package and script relied heavily on several *R*-packages. Much of the workflow script
used and built upon the *bdc* (biodiversity data cleaner) package[13], tidyverse packages —
particularly *dplyr*[63], *magrittr*[64], *tibble*[65], *stringr*[66], *tidyselect*[67], *ggplot2*[68], *tidyr*[69], *rlang*[70], *xml2*[71],
readr[72], and *lubridate*[73], — and *CoordinateCleaner*[74]. Additionally, we used *R.utils*[75], *galah*[61],
emld[76], openxlsx[77], *rnaturalearth*[78], *rnaturalearthdata*[79], *countrycode*[80], *hexbin*[81], *cowplot*[82],
ggspatial[83], *renv*[84], *chorddiag*[85], *igraph*[86], *sf*[87], and *terra*[88]. In some cases we have modified or
rebuilt *bdc* functions into *BeeBDC* to better work with other parts of our package or to produce
different results. Functions that relate strongly to *bdc* are prefixed with "jbd_" to indicate to
users that an alternate function exists and to compare package documentation (e.g., by
running "?*jbd_coordinates_precision*" in *R*) for each. Our script was both built and run on a
2019 MacBook Pro with a 2.4 GHz 8-core Intel i9 with 64GB 2667 MHz DDR4 RAM. Hence,

while it can be run on personal computers — and this accessibility is intentional — we are
aware that memory (RAM) and physical storage could inhibit some devices from processing
the full dataset (i.e., 18.2 million occurrences and ~131 columns).

The core workflow, *R* vignette, and functions are freely available on GitHub
(https://jbdorey.github.io/BeeBDC/index.html). The workflow is clearly numbered and
labelled using the *R-Studio* document outline to allow quick navigation of the script. For clarity
and continuity, we list the sections below according to our script, including (0.x) script
preparation, (1.x) data merge, (2.x) data preparation, (3.x) initial flags, (4.x) taxonomy, (5.x)
space, (6.x) time, (7.x) de-duplication, (8.x) data filtering, (9.x) summary figures and tables,
and (10.x) package data. Additionally, most of our functions attempt to provide extensive and
informative user-outputs for quality assurance. We provide a reference table of the
occurrence-cleaning functions that are available between *BeeBDC*, *bdc*, and
CoordinateCleaner (Table 1). Our script focuses on the specifics of bee data; however, it
provides the templates needed to integrate the specifics of other taxon groups and input data.

Most functions in our script aim to identify and flag potentially problematic occurrence records
based on specific tests and user-provided thresholds (flagging functions). However, several
functions modify the occurrence records themselves when errors are identified (carpentry
functions). We also provide summary and filtering functions that allow users to explore data
issues and export useable datasets. While most functions can be implemented anywhere in
the workflow, a subset relies on columns produced from earlier functions and these are
highlighted in the package documentation and website. Below, we explain the sections and
functions found in our script and the logic behind their implementation. We do not explain the
optional steps documented in the script as they were not implemented in our dataset, but see
the *BeeBDC* documentation for further clarification.

0. Script preparation

To ensure accessibility and ease of use, we ask users to set the root file path in which the script
should look for or create certain datasets or functions. Our *dirMaker* function should locate
and, if missing, create the file structure sought by the rest of the script and the *bdc* package.
Packages are then installed and loaded. Here the script initialises and stores the *renv* files. The
renv package files keep information about package versions to encourage further
reproducibility of scripts and ease of publishing for users.

1. Data merge

The data merge section of the script reads very large datasets from the major data repositories
— GBIF, iDigBio, USGS, SCAN, and ALA. It then (i) unifies the data (selecting certain columns
set by the *ColTypeR* function) to Darwin Core format[89], (ii) merges them into a single dataset,
and (iii) creates a metadata file that both accompanies the *R*-object and is saved locally
(https://doi.org/10.25451/flinders.21709757; ExtraTables/MajorRepoAttributes_2023-09-
01.xlsx). These functions were built to accommodate the entirety of the large repositories
above; however, they can be slow on computers with limited RAM.

2. Data preparation

Here, we provide users with two options to re-import the data saved during *1. Data merge*.
For general applications, the *bdc* package provides excellent import functionality but would
require manual work initially (2.1a in script). For users who want to run data from the above
major repositories, we provide seamless functionality to read those data (2.1b in script). For

users aiming to update the bee datasets from online repositories, they may incorporate the
documented manual data edits (2.2 in script) and re-incorporate several privately curated
datasets (2.2–2.5 in script). Once a dataset is standardised to Darwin Core format and contains
the necessary columns, users can begin flagging or cleaning each occurrence record for data
integrity. Our total dataset comprised 18,239,522 uncleaned bee occurrence records (Fig. 1).

3. Initial flags

To perform initial data-quality flags and checks, we used a combination of *BeeBDC* and *bdc*
functions, which we will list below. These include data flagging and carpentry functions, with
the latter supporting the former.

3.1 Scientific name flags. We used the *bdc* function, *bdc_scientificName_empty,* to flag
records with no scientific name provided (i.e., an empty *scientificName* cell). This step flagged
183,341 (1%) occurrences.

3.2 Missing Coordinates. We used the *bdc* function, *bdc_coordinates_empty,* to flag
records with no coordinates provided (empty *decimalLatitude* or *decimalLongitude* columns).
This step flagged 2,967,777 (16%) occurrences.

3.3 Coordinates out of range. We used the *bdc* function,
bdc_coordinates_outOfRange, to flag records that were not on the map (i.e., not between -90
and 90 for latitude or not between -180 and 180 for longitude). This step flagged 2,071 (<1%)
occurrences.

3.4 Poor record source. We used the *bdc* function, *bdc_basisOfRecords_notStandard,*
to flag occurrences that did not meet our criteria regarding their basis of records. Broadly, we
kept all event, human observation, living specimen, material/preserved specimen, occurrence,
and literature data. For this step, we were relatively liberal in what we allowed to remain in
the dataset and only excluded fossil specimens; however, some users might prefer to also
remove human observations. This step flagged 34,078 (<1%) occurrences.

3.5 Country name. We used our function, *countryNameCleanR*, to match GBIF ISO2
country codes to country names from a static Wikipedia ISO2 to country name table within
the function. Users can also input a data frame of problem names and fixed names to replace
them in the dataset. We then created a modified version of the *bdc* function
bdc_country_from_coordinates into a chunking function, *jbd_CfC_chunker* (to work on smaller
portions of the dataset at a time), where the user can specify chunk-sizes to best manage this
RAM-intensive function. This function also can be run in parallel (multiple threads). However,
for all parallel-ready functions users must be aware of their available RAM; ten cores seemed
reasonable on a 64 GB machine (mc.cores = 10) for this function, but for the remaining
functions we used between two and six. The *jbd_CfC_chunker* function assigns country names
to those occurrences that were missing them but that have valid coordinates that correspond
to a country. This step assigned country names to 283,517 (2%) occurrences.

3.6 Standardise country names. We used the *bdc* function, *bdc_country_standardized,*
to attempt to further standardise country names for consistency. This step standardised
country names for 4,509,729 (25%) occurrences.

3.7 Transposed coordinates. We used a parallel-ready (mc.cores = 4) chunking
function, *jbd_Ctrans_chunker*, (as *jbd_CfC_chunker* above) that wraps a custom version of the
bdc function, *bdc_coordinates_transposed* (*jbd_coordinates_transposed*), which flags and

corrects coordinates for which the latitude and longitude are transposed. This step corrected
transposed coordinates for 2,267 (<1%) occurrences.

3.8 Coordinates and country inconsistent. Here, we created a similar, but parallel-
ready (mc.cores = 4), function to *bdc*'s called *jbd_coordCountryInconsistent*. We re-built the
bdc version for memory efficiency and to accommodate the processing of our dataset, which
is much larger than the *bdc* test dataset. Our function flags occurrences for which the
coordinates and country do not match while allowing for a user input map buffer (in decimal
degrees). This step flagged 3,636 (<1%) occurrences.

3.9 Georeference issue. We ran the *bdc* function, *bdc_coordinates_from_locality,*
which highlights occurrences for which there is no latitude or longitude directly associated
with the data, but for which sufficient locality data may be used to extrapolate relatively
accurate geological coordinates. This step flagged 2,387,891 (13%) occurrences.

3.10 Absent records. We provide a function, *flagAbsent*, to flag occurrence records
that are marked as "ABSENT". Users may not be aware that many thousands of records are
often provided as absent. These records might occur, for example, due to repeated sampling
programmes not finding a certain species on a particular date or at a particular site. This step
flagged 154,202 (1%) occurrences.

3.11 Restricted licenses. We provide a function, *flagLicense*, that aims to flag records
that are not licensed for use. While such records should not be on public data repositories,
some few are. Therefore, users should be aware not to use these protected data points. This
step flagged 657 (<1%) occurrences.

3.12 GBIF issues. We provide a function, *GBIFissues*, to flag occurrences already
flagged for user-specified GBIF issues. For example, we flagged GBIF occurrences marked as
"COORDINATE_INVALID" and "ZERO_COORDINATE". This step flagged 14 (<1%) occurrences.

At the end of the initial flags section, we provide the *flagRecorder* function to save the flags
for all occurrences as a separate file. Users may then use *bdc* functions to create summaries,
reports, and some figures.

4. Taxonomic cleaning

While *bdc* provides great functionality for taxonomic cleaning of some groups, it does not
provide access to the most-current bee taxonomy. Hence, we used the online global bee
taxonomy available through Discover Life[23], which lists approximately 21,000 valid names and
31,000 synonyms or orthographic variants. Discover Life is the leading source of bee names
and is peer-reviewed by global experts on an ongoing basis. We flagged this list for ambiguous
names (homonyms) that, to varying degrees, could not be matched due to their complicated
taxonomic histories. Records with ambiguous names were either processed differently or
excluded from the below function and hence the final occurrence dataset. We also made some
manual corrections as taxonomic issues (mostly orthographic variants) were identified
(https://doi.org/10.25451/flinders.21709757;   ExtraTables/AddedTaxonomyVariants.xlsx).
The final taxonomy is available in the *BeeBDC* package as *beesTaxonomy*.

We first cleaned our species names using the *bdc* function *bdc_clean_names,* which attempts
to clean names and unify writing-styles (e.g., capitalization and punctuation). It also removes
family names, qualifiers (this is flagged), infraspecific terms, separates authors, dates, and
annotations. This function also adds a taxonomic uncertainty flag, *.uncer_terms*, which flagged

3,334 (<1%) records. We then used our parallel-ready (mc.cores = 4) *harmoniseR* function to
harmonise occurrence names with our combined Discover Life taxonomy. This function takes
steps to (i) compare occurrence names directly with valid names (genus species authority), (ii)
combine the *bdc*-cleaned name and occurrence authority to match against the valid name, (iii)
match species names with canonical flagged names (i.e., scientific names with flags from
Discover Life), (iv) directly compare scientific names, (v) combine the occurrence scientific
name and occurrence authority to match against the valid name, (vi) match occurrence's
scientific name with the taxonomy's valid name with subgenus removed from both, and (vii)
as above but using canonical names. Between each step, the function filters out already-
matched names. These steps are first taken for the non-ambiguous names (according to our
taxonomy) and then applied again for the ambiguous names but also matching the authority
("author year", all lowercase and with no punctuation). If a name cannot be unambiguously
matched at any level (homonyms), then they will fail this function and an accepted name will
not be applied. The function then moves the provided name to *the verbatimScientificName*
column and updates the scientificName, species, family, subfamily, genus, subgenus,
specificEpithet, infraspecificEpithet, and scientificNameAuthorship columns where better
matches are found. This is only done for occurrences with a successful match; unmatched
occurrences are not altered. Occurrence records that do not match the taxonomies are flagged
accordingly with the *.invalidName* column. The data produced from each step are merged and
an updated object is output. The minimum requirement for this function is a data frame with
a column containing species names — this is intended to allow quick checking and updating of
simple species lists. This step matched valid names to 16,566,207 (91%) and flagged 1,673,315
(9%) occurrences, respectively.

5. Space flagging

We further flagged our data for spatial issues using a combination of functions from *BeeBDC,*
bdc, and *CoordinateCleaner*. We outline these steps below.

5.1 Coordinate precision. We used our function, *jbd_coordinates_precision*, to flag
occurrence records with latitude and longitudes below a threshold of two decimal places (~1.1
km at the equator). This step differs from the *bdc* function *bdc_coordinates_precision* by only
flagging occurrences where both latitude *and* longitude were rounded. This step flagged
3,608,776 (20%) occurrences.

5.2 Common spatial issues. We then used the *CoordinateCleaner* function,
clean_coordinates, which runs several tests to flag potentially erroneous data. We flagged
records that were within (i) 1 km of capital cities, (ii) 500 m of province or country centroids,
(iii) 1 km of GBIF headquarters in Copenhagen, Denmark, or (iv) 100 m of biodiversity
institutions; or that have (v) equal latitude and longitude coordinates, or (vi) zero as latitude
and longitude. For example, these issues can arise when occurrences were labelled only with
the city, province, country, institution, or repository are georeferenced to those exact
locations. The latter two could arise from copy errors or incomplete data. We did not flag
points in the ocean as they are flagged with a small buffer by *5.5 Country Checklist* (below).
This step flagged (i) 15,653; (ii) 16,979; (iii) 11; (iv) 80,558; (v) 10,568; and (vi) 10,417 (each
<1%) occurrences, respective to the above criteria.

5.3 Fill-down errors and gridded datasets. We provide the parallel-ready (mc.cores =
4) *diagonAlley* function that uses a sliding window to flag potential fill-down errors in the
latitude and longitude columns. The function removes any empty values and then groups data
by event date and collector. It then arranges latitude and longitude, removes identical values,
and flags sequences of latitudes or longitudes where the differences between records are

exactly equal. The user defines a minimum number of repeats required for a flag (minRepeats
= 6) and a minimum number of decimal places required to consider an occurrence (using 5.1
jbd_coordinates_precision; ndec = 3). Secondly, we then implemented the *cd_round* function
from *CoordinateCleaner* to identify datasets (using the *datasetName* column) that have their
latitudes or longitudes potentially gridded, using the default values. This step flagged 390,206
(2%) and 113,617 (<1%) occurrences for fill-down and gridded datasets, respectively.

5.4 Coordinate uncertainty. We provide the *coordUncerFlagR* function that flags
records by a user-defined threshold for coordinate uncertainty — usually provided in the
Darwin Core *coordinateUncertaintyInMeters* column. We used a threshold of 1 km. This step
flagged 2,778,159 (15%) occurrences.

5.5 Country Checklist. We provide the parallel-ready (mc.cores = 4) *countryOutlieRs*
function that uses the country-level checklist available on the Discover Life website
(beesTaxonomy). While vagrants are only a minor issue, Discover Life excludes port vagrants
and clear misidentifications; however, "natural" and established vagrants are generally
included as valid. For example, the Fiji checklist includes eight relatively recent, but
established, introductions[23,90]. The function checks all of the harmonised species names
against the checklist and the country in which the occurrence falls (using overlap with
rnaturalearth). Points that don't align with *rnaturalearth* (e.g., they are on the coast) can be
buffered by a user-specified amount, in degrees, to attempt a match. In our case, we used 0.05
degrees (~5.6 km). It is worth noting that changing the *rnaturalearth* resolution could lead to
slight variations in results and that the higher resolutions (scale = 50 or "large") might be
optimal for most regions; especially for discontinuous island groups. The function produces
three columns. The first column, *countryMatch*, summarises the occurrence-level result:
where the species is not known to occur in that country (noMatch), it is known from a
bordering country (neighbour), or it is known to occur in that country (exact). The second
column's output depends on user input. If the user wants to keep occurrences that are either
exact matches or in adjacent (bordering) countries to those in the checklist
(keepAdjacentCountry = TRUE) then the filtering column *.countryOutlier* will be TRUE for these
cases and FALSE only for those with noMatch. A keepAdjacentCountry = FALSE argument will
only flag exact country checklist matches as TRUE. For our dataset, we chose the former. The
third column, *.sea*, flags the points which don't align with *rnaturalearth* or its buffer — they
are identified as being in the ocean. The *countryOutlier* column flagged 1,788,481 (10%)
occurrences and the *.sea* column flagged 202,371 (1%).

Users may then produce maps, reports, and figures using the *bdc* package. They can also
append the saved flag file using the *flagRecorder* function.

6. Time flagging

The next major sequence of functions aims to recover or filter occurrence records with date-
related issues. We outline the steps taken below.

6.1 Recover missing event date. We provide the *dateFindR* function that seeks to
recover occurrence records that would otherwise be removed due to missing event date. The
function first removes unreasonable dates based on a user-defined year-range (we removed
dates prior to 1700 and after the present year). The function then seeks to harmonize date
formats in a step-wise manner by first (i) combining dates from the year, month, and day
columns into the *eventDate* column, then (ii) taking just the year column where it is provided
without event date. Subsequently, the function looks for dates in the *verbatimEventDate*,
fieldNotes, and *locationRemarks* columns by looking in sequence for unambiguous date strings

in the following formats: (iii) year-month-day, (iv) day-month-year (where day is identifiable
— i.e., days >12; or months are identifiable — in written or Roman-numeral formats), (v)
month-day-year (where days or months are identifiable as above), and (vi) month-year (where
month is identifiable as written or Roman-numeral formats). The function then finds
ambiguous date strings in the *verbatimEventDate*, *fieldNotes*, and *locationRemarks* columns
and keeps only the year value. All date values are then returned in the standardised year-
month-day-hours-minutes-seconds format. Users should consider this threshold critically in
relation to their own hypotheses and potentially run *dateFindR* over the Flagged-but-
uncleaned dataset with their own threshold if required. This step rescued dates for 1,331,377
(7%) occurrences.

6.2 Missing event date. We then used the *bdc* function, *bdc_eventDate_empty*, to flag
records that do not have date in the *eventDate* column. This step flagged 1,452,980 (8%)
occurrences.

6.3 Old records. We used the *bdc* function, *bdc_year_outOfRange*, to flag occurrence
records that are likely too old for use in species distribution modelling. Here, we flagged
occurrences from before 1950. Users may want to consider changing this value or disregarding
this flag as it applies, or does not, to the question(s) that they want to ask. This step flagged
1,543,768 (8%) occurrences.

Users may then create reports and figures on the time filters using the *bdc* package. They can
also append the saved flag file using the *flagRecorder* function.

7. Duplicate records

Duplicate records frequently arise between or within repositories. These records can be
difficult to discern particularly where single specimens have been assigned multiple, or worse,
no unique identifiers, or where the same locality has been georeferenced independently by
multiple institutions. We provide a custom function called *dupeSummary*, that iteratively
searches occurrences for duplication using multiple column-sets. Users can choose to identify
duplicates based on identifier columns, collection information, or both. They may also define
any number of custom column sets by which to identify duplicates.

Some identifier columns might contain codes that are too simple. The function allows users to
set thresholds to ignore those occurrences when checking the relevant columns for duplicates.
For example, the *catalogNumber* might be "145" or "174a", which could result in over-
matching of duplicates. Users may set a characterThreshold and numberThreshold which
would ignore codes which don't pass both. Users may also set a numberOnlyThreshold, which
will check codes above that threshold, irrespective of the characterThreshold. We use the
defaults of two, three, and five, respectively. Hence, minimum passing codes could include
"AG194" and "390174". This can be entirely turned off by setting all values to zero or ignored
for selected column sets using CustomComparisonsRAW.

The function identifies duplicates based on collection information where it iteratively
compares user-defined sets of columns. The function first compares custom column sets and
can then compare generic, but customisable, column sets. For our bee data, we used several
steps to identify duplicates. Firstly, we compared (i) *catalogNumber* and *institutionCode* using
CustomComparisonsRAW. Secondly, we identified duplicates based on the *scientificName*
with the (ii) *catalogNumber* and *institutionCode*, (iii) *gbifID*, (iv) *occurrenceID*, (v) *recordId*, and

(vi) *id* columns using CustomComparisons. Finally, we identified duplicates using the generic
column sets of *decimalLatitude*, *decimalLongitude*, *scientificName*, *eventDate*, and *recordedBy*
columns at the same time as the (vii) *catalogNumber* and (viii) *otherCatalogNumbers* columns.

Using the *scientificName* column with the identifier columns allows different species with the
same identifier to be maintained. This is important where an event identifier (multiple
specimens from one collection event) has been placed in the wrong column. For the
occurrences where the taxonomy did not match (e.g., because of an ambiguous or incomplete
identification) duplicates won't be identified; in these cases they will be removed by
harmoniseR (or another flag). At the same time, occurrences where species identifications
have been updated in only some datasets will not be identified as duplicates. Users may
choose their own input parameters while weighing the costs and benefits.

The function arranges the data by (i) a user-defined list of input sources (where the first data
sources are preferred over later ones; i.e., GBIF > SCAN > iDigBio, etc.), then, (ii) completeness
by user-defined columns, and (iii) by the summary column (to keep clean occurrences). For
point three above, duplicate occurrences with more of these completeness columns will be
preferred over those with fewer; i.e., the most-complete record is chosen. Where public and
private data were duplicated, we gave preference to private data providers over the public
data aggregators under the assumption that data providers have the most recent information.
We also preferred manually cleaned occurrence records from Chesshire, et al. [91] over those
sourced directly from data aggregators. All pairwise duplicates were clustered where they
overlapped and a single best occurrence was kept using the above arrangement. This step
flagged 7,558,747 (41%) occurrences. Most of these duplicates arose between data sources;
however, within-source duplicates were quite prominent in SCAN (Fig. 2).

8. Final filter

We first used the function *manualOutlierFindeR* function to flag occurrences identified as
misidentifications or outliers by experts who reviewed interactive point maps. (from
interactiveMapR below). There were 181 records from Chesshire, et al. [91] and 2,203 records
identified by expert review of interactive species maps (see Technical validation). However,
these were revised following the addition of new occurrence data. For each outlier identified,
the function uses the output from *dupeSummary* to identify its duplicate records and flags
those for removal. This function flagged 2,160 (<1%) records.

The "flagged-but-uncleaned" dataset was produced with the *summaryFun* which updated the
.summary column. The *.summary* column is updated to include any records that are flagged in
at least one flagging column, with user-defined exceptions. We excluded several filtering
columns that we decided were not critical to data integrity. These were the diagonal and grid
flags (*.sequential*, *.gridSummary*, *.lonFlag*, and *.latFlag*) and the taxonomic uncertainty flag
(*.uncer_terms*). We also excluded high coordinate uncertainty (*.uncertaintyThreshold*) and
records out of range (*.year_outOfRange*) because this filtering level might be too strict for
general analysis and can remove ~1 million otherwise clean records at the 1 km level. Users
may download our flagged dataset and begin at this step to choose the flags that are important
for their hypotheses to remove or customise with different thresholds
(https://doi.org/10.25451/flinders.21709757; OutputData/05_unCleaned_database.csv). For
our "completely cleaned" dataset we followed used the above parameters in *summaryFun* but
also chose to filter to only clean records and then remove all filtering columns
(https://doi.org/10.25451/flinders.21709757; OutputData/05_cleaned_database.csv). This
step removed 11,408,998 (63%) occurrences and left 6,830,524 (37%) cleaned occurrences.

9. Summary figures, tables, and outputs

Beyond the figures produced throughout the cleaning process by the *bdc* package, we also provide several unique custom figure functions.

9.1 Duplicate chordDiagrams. We provide a function, *chordDiagramR*, that wraps the *circlize*[92], *ComplexHeatmap*[93,94], and *paletteer*[95] packages to build a chord diagram that visualises the linkages between duplicated occurrence data sources (Fig. 2).

9.2 Duplicate histogram. We provide a function, *dupePlotR*, to visualise duplicates by source, breaking them down into (i) discarded duplicates, (ii) kept duplicates (as chosen in *7.x Duplicate records*), and (iii) unique records (Fig. 3). This is displayed as both a total number of records and the proportion within each data source.

9.3 Flags by source. We provide the *plotFlagSummary* function that produces a compound bar plot that, for each data source, indicates the proportion of records that pass or fail, or cannot be assessed for each flag (Fig. 4). We built additional functionality into this function that allows users to provide a species name (and the column in which that name is found) and (i) save the occurrence data, (ii) produce a map coloured by a filtering column of choice, and (iii) the compound bar plot for that specific species. This can be an excellent function to quickly examine potential issues. Additionally, users can choose to output the table used to make the figure using saveTable = TRUE.

9.4 Maps. We provide a function, *summaryMaps*, that uses the cleaned data to show the number of species and number of occurrences per country (Fig. 5). For the latter function, we broke up these values using classes and "fisher" intervals[96]; however, any style from the *classInt*[97] package can be entered. Additionally, we provide a function, *interactiveMapR*, that iteratively makes and saves interactive html maps for any number of species. These interactive maps colour occurrences if they pass or fail any flags, if they are country outliers, or if they are expert outliers. Collection and flag information are provided in pop-ups for each point.

9.5 Data providers. We provide a function, *dataProvTables*, that produces a table of data providers with the number of cleaned occurrences and species for each. The function also attempts to identify the data provider using other columns when it is omitted from the *institutionCode* column, providing an updated institution code and name. This function is thus far customised to bee datasets. We provide both the top 14 rows (for datasets with >100,000 clean occurrences; Table 2) and the full table (https://doi.org/10.25451/flinders.21709757; OutputData/Reports/dataProviders.xlsx).

9.6 Flag summary. We built a function, *flagSummaryTable*, that will produce a summary table of the total number of failed occurrences per flag and per species (or any other categorical column of interest).

9.7 Taxonomic and country checklist queries. Users may be interested in querying *BeeBDC* for species names, validities, and in which countries a species can be found. Our function, *BeeBDCQuery*, allows users to enter one or more species name as a character vector and it will report on (i) the validity of the name, (ii) all synonyms, and (iii) the countries in which it is found. This information will be returned as a list of tables.

10. Package data

10.1 Bee taxonomy and checklist. We provide a modified version of the global bee
taxonomy and country-level checklist produced by John Ascher and John Pickering and hosted
on Discover Life[23] as part of *BeeBDC*. These datasets are downloadable directly from the
FigShare using the functions *beesTaxonomy* and *beesChecklist*, respectively.

10.2 Test datasets. We further provide three test datasets with BeeBDC. The dataset
bees3sp includes 105 flagged points from three haphazardly chosen species; *beesFlagged*
contains 100 randomly chosen flagged occurrence records; and *beesRaw* contains 100
randomly chosen unflagged occurrence records.

Data Records
Our dataset and the data used in our analyses are available for download in our repository
(https://doi.org/10.25451/flinders.21709757).   See   Data   Sources   above   for   further
information. Occurrence datasets are provided in standard DarwinCore format and saved as
.csv files. The additional materials are organised into the following folders:
590   1.   Figures. Contains primary figures and additional *bdc* figures.
591   2.   OutputData. Contains the "cleaned" (05_cleaned_database.csv) and "flagged-
592   but-uncleaned" (unCleaned_database.csv) datasets, reports, and the *R* console
593   outputs from the script (RunNotes_BeeBDC_1Sep23.txt).
594   3.   InputData. Contains   the   major   repository   downloads,   additional   input
595   datasets, and custom Chesshire, et al. [91] data files.
596   4.   ExtraTables.   Contains   metadata   for   the   major   repository   downloads
597   (MajorRepoAttributes_2023-09-01.xlsx) and the added taxonomy variants
598   (AddedTaxonomyVariants.xlsx).
599   5.   The beesTaxonomy.Rda and beesChecklist.Rda datasets that are downloaded
600   using BeeBDC (see 10. Package data above).
601

Technical Validation
For our current data version, we outline the data quality according to our flags. We provide
summaries of the deduplication process, including the duplication linkages within and
between datasets (Fig. 2), and the number and proportion of duplicates, kept duplicates, and
unique occurrences per dataset (Fig. 3). Importantly, we provide a figure summary of the
proportion of records flagged for all data sources (Fig. 4). This figure indicates data quality
across the entire dataset and where each data source might focus their cleaning efforts. We
demonstrate the country-level patterns of both species and occurrences on a global map (Fig.
5). Finally, all *BeeBDC* and *bdc* summary and data quality figures and maps are provided in the
Additional Figures folder (https://doi.org/10.25451/flinders.21709757).
612
We assessed our figures and interactive maps in a lengthy and iterative error-checking
process. Throughout the development of the package, functions and results were scrutinised
by the authors, particularly JBD, EEF, AN-B, RLO'R, SB, DAG, DdP, K-LJH, LMM, TG, TAZ, MCO,
LMG, JSA, ACH, and NSC. Functions were tested throughout development and as a part of our
CRAN submission process to ensure robustness and consistency of results with expectations.
Occurrence records were examined frequently in this process and, several times, interactive
maps of 100 randomly chosen species were produced and manually checked. In addition to
this, interactive maps for all species with sufficient data between Colombia and Canada (4,221
spp.) were produced and manually checked (in some cases for multiple versions) as part of an
additional effort to build species distribution models of the bees in that region led by AN-B
and NSC.
624

We found that data quality was highly variable between sources (Fig. 4). Data duplication was often the most prominent flag, comprising 41% of the total uncleaned dataset. There was substantial duplication between and even within both major and minor data repositories (Figs. 2 and 3). Importantly, the assumption that all data make their way to GBIF is incorrect (at least at the time of downloading); we found that each repository holds unique data (Fig. 3). However, it is also likely that poor data quality might preclude successful duplicate matching. Regardless, this highlights the importance of sourcing occurrence data from a variety of repositories. However, in terms of actual input data quality and completeness, many occurrences (i) lacked coordinates, (ii) did not have a scientific name or that name did not match known taxonomy, (iii) had low-resolution coordinates, (iv) had high coordinate uncertainty (where this was estimated), (v) did not match the country checklist on the Discover Life website, (vi) lacked collection date, and/or (vii) were collected prior to 1950 (Fig. 4). These quality issues might preclude data use in downstream works and require further efforts to repair. In worst case scenarios, unfit data might pass flagging steps and cause misleading results. The presented workflow enables researchers to prepare data that can support robust analyses. To the best of our knowledge, this is now the most thoroughly curated global occurrence dataset for bees and is potentially leading for any terrestrial invertebrate group of this size.

The mismatch between bee species richness according to occurrence data and country checklists has already been highlighted by Orr, et al. [6]. We also highlight the geographical, taxonomic, and collection biases in the global bee data (Fig. 5). We show that the number of cleaned species occurrences in most of Africa and large parts of Asia are in the lowest class counts, where classes are defined using a Fisher-Jenks algorithm[96] (Fig. 5a). We also show that the number of occurrences in Africa, Asia, and even South America are often in the lowest class counts and to a greater degree than species counts (Fig. 5b). Some countries in Africa (Equatorial Guinea, Djibouti, and parts of Western Sahara) do not have a single cleaned occurrence record (Fig. 5). There are also large mismatches between the number of species and number of occurrence records. These disparities are hugely concerning and highlight ongoing inequalities in taxonomic, sampling, and digitisation efforts. While we integrate new datasets from Central and South America (with more expected to be released in future versions) we note that there are likely many more data available in grey literature for the under-sampled regions of the world and museum specimens that are yet to be digitised. We hope that this contribution provides a foundation for a more formal recognition and prioritization of important taxonomic, sampling, and digitisation efforts.

Usage Notes

All of our occurrence datasets are cleaned for (i) taxonomic information according to the Discover Life website, (ii) country name (country_suggested) and ISO2 code, and (iii) recoverable event dates from other columns. When using our data or parts of our workflow users should also cite the data sources where they are relevant. Our occurrence data are provided in two ways:

Cleaned. We provide a dataset that is completely cleaned of records that failed any of our filtering steps with the exception of: (i) *.gridSummary,* (ii) *.lonFlag*, (iii) *.latFlag*, (iv) *.uncertaintyThreshold*, (v) *.sequential*, and (vi) *.year_outOfRange*. All filtering columns are also removed from this dataset to reduce file size.

Flagged-but-uncleaned. We provide a dataset that includes all of the above filters as flags, in addition to the otherwise unfiltered flags above. This dataset is provided with a column for each of these flags where occurrences that failed for a filtering step are flagged as "FALSE" and those that passed as "TRUE". This convention is used to maintain continuity with

functions from the *bdc* and *coordinateCleaner* packages. Users are able to use our script to
read in and filter their data or manually filter these data in a way that is appropriate for their
use. Our filtering script should also provide users with the necessary template to reduce or
modify their data into their desired size and structure. In particular, users may use the
dontFilterThese argument in the *summaryFun* function to exclude certain filters that do not
relate to their research question.

Users may incorporate our data pulls or conduct their own. However, we do note that ALA,
through the *galah* package, is the only major data provider with a convenient download
protocol for large datasets. Other Application Programming Interfaces (APIs) and even web
protocols make downloading a limiting and lengthy process; for example, the *rgbif* package
has a limit of 100,000 occurrences. Making similar API methods available for other major data
repositories would greatly increase their accessibility. Usage of the *BeeBDC* package and
workflow should be accessible to most users with basic *R* knowledge. Once the datasets and
folder structure are determined the script should require minimal user input. We highlight
again that this workflow was tested on a machine with 64 GB of RAM and that users with less
RAM might have prolonged run times and need to reduce chunk sizes for some functions. In
the end, this work is aimed to facilitate open source data for both scientific and applied usage.

Code Availability

We provide a full website with vignettes (including a complete and a basic workflow) that
demonstrates the functionality of our script with the input data
(https://jbdorey.github.io/BeeBDC/index.html). Our "basic workflow" is for users that simply
wish to download our flagged but unfiltered dataset and apply (i) manual filters based on our
filtering columns or further filter to only include certain (ii) countries, (iii) date ranges, or (iv)
uncertainty levels. Secondly, we provide these annotated *R*-scripts run from start to finish on
our GitHub (https://github.com/jbdorey/BeeBDC/tree/main/inst). Our scripts, related files,
and downloaded instructions can be found on our GitHub page
(https://github.com/jbdorey/BeeBDC).

Acknowledgements

We acknowledge the wonderful data providers such as ALA, GBIF, SCAN, and iDigBio, who
maintain and make available datasets for public use. We also sincerely thank Sam Droege for
organising and contributing the substantial USGS bee dataset. We additionally acknowledge
and thank individuals and organisations that do the same, including those individually used
here produced by: Elizabeth Elle, Casey Delphia, Ecdysis, Gaiarsa et al., Arathi Seshadri, and
the Florida State Collection of Arthropods. A special thanks also goes to Elizabeth Murray for
her excellent suggestion that led to the naming of our R package, BeeBDC. Mention of trade
names or commercial products in this publication is solely for the purpose of providing specific
information and does not imply recommendation or endorsement by the U.S. Department of
Agriculture. USDA is an equal opportunity provider and employer. JB Dorey was partly funded
by the Biodiversity Outreach Network and at the earliest stages of the paper's conception was
partly funded by Burt's Bees. EE Fischer was supported by the Hans Rausing Scholarship in the
History of Science. A Nava-Bolaños is grateful to Consejo Nacional de Ciencia y Tecnología for
the postdoctoral fellow for the project "Polinizadores: actores clave en la seguridad
alimentaria". S Bossert was funded under NSF grant, DEB-2127744. EM Lichtenberg and SM
Collins were partially funded through the Texas State Wildlife Grants program grant CA-
0002506 in cooperation with the U.S. Fish and Wildlife Service, Wildlife and Sport Fish
Restoration Program. MS Rogan, YV Sica, and W Jetz were partly funded by Burt's Bees. TA
Zarrillo was additionally funded by Hatch funds from the Connecticut Agricultural Experiment
Station and the Connecticut Department of Energy and Environmental Protection Wildlife

Division and the federal State Wildlife Grants Program. Additional partial funding was provided
by the iDigBees TCN NSF award #2216927.
729

730 Author contributions

The project was **conceptualised** by JB Dorey and KLJ Hung. The project design was guided by
JB Dorey, EE Fischer, MS Rogan, YV Sica, MC Orr, LM Guzman, JS Ascher, AC Hughes, and NS
Cobb. **Data were provided and/or curated** by JB Dorey, PR Chesshire, A Nava-Bolaños, SM
Collins, EM Lichtenberg, EM Tucker, A Smith-Pardo, A Falcon-Brindis, DE de Pedro, KA Parys,
RL Minckley, T Griswold, T Zarillo, JA Ascher, AC Hughes, and NS Cobb. The **code was drafted**
by JB Dorey, tested by JB Dorey and EE Fischer, and input was provided by RL O'Reilly, S
Bossert, and SM Collins. *R* Markdown was generated by JB Dorey and R O'Reilly. Figures were
created by JB Dorey and S Bossert. The **manuscript was drafted** by JB Dorey and all authors
provided critical feedback and reviewed the final manuscript. First and senior authors are
ordered by relative contribution and alphabetically in between these groups.
741

742 Competing interests

743 The authors declare no conflicts of interest.
744

Tables

Table 1. The occurrence data filtering steps, functions, packages (*BeeBDC*[24], *bdc*[13], and *CoordinateCleaner*[74]), descriptions, and function references required to undertake each step of filtering. The function steps include script and data preparation, flagging (adding function result column), carpentry (altering the data itself), and filtering (removing occurrences based on data flags). The packages *BeeBDC* and bdc also have a selection of functions that are useful for data visualisation and table production which are critical for error-checking the results. Parentheses under descriptions often indicate the flagging columns produced by that function. Asterisks next to function names indicate that they are parallel-ready (can be run across multiple threads).

Step	Function	Package	Brief description	Reference
0. Script preparation	*dirMaker*	*BeeBDC*	Builds the directory architecture in a given location for the *BeeBDC* and *bdc* packages	(Dorey et al. 2023)
1. Data merge	*atlasDownloader*	*BeeBDC*	Downloads occurrence data from the Atlas of Living Australia (or other Atlas' with reduced functionality)	(Dorey et al. 2023)
	repoMerge, importOccurrences, USGS_formatter, formattedCombiner, and dataSaver	*BeeBDC*	Imports and merges occurrence data from (i) GBIF, SCAN, iDigBio, and ALA; (ii) loads data from (i); (iii) loads USGS bee lab dataset, (iv) adds USGS data to the larger dataset, and (v) saves these data and metadata	(Dorey et al. 2023)
2. Data preparation	*idMatchR**	*BeeBDC*	Tries to match results from previous runs to the current download in order to maintain consistency in the *database_id* column (*idContinuity*)	(Dorey et al. 2023)
	PaigeIntegrater	*BeeBDC*	Integrates manually modified occurrences from Chesshire, et al. [91]	(Dorey et al. 2023)
	readr_BeeBDC	*BeeBDC*	A series of functions to format specific datasets into Darwin Core format	(Dorey et al. 2023)
	bdc_standardize_datasets	*bdc*	A method to convert and read custom datasets to Darwin Core format	(Ribeiro et al. 2022)
3. Pre-filtering	*jbd_Ctrans_chunker*, jbd_coordinates_transposed*, & bdc_coordinates_transposed*	*BeeBDC & bdc*	Flags occurrences where latitude and longitude appear to be transposed (*coordinates_transposed*)	(Dorey et al. 2023; Ribeiro et al. 2022)
	flagAbsent	*BeeBDC*	Flags occurrences that are marked as "absent" under occurrenceStatus (*.occurrenceAbsent*)	(Dorey et al. 2023)

flagLicense	*BeeBDC*	Flags occurrences that are restricted by usage licences (*.unLicensed*)	(Dorey et al. 2023)
GBIFissues	*BeeBDC*	Flags occurrences based on user-defined GBIF flags (*.GBIFflags*)	(Dorey et al. 2023)
jbd_CfC_chunker & *bdc_country_from_coordinates*	*BeeBDC & bdc*	Get country name using coordinates (where no country name is provided)	(Dorey et al. 2023; Ribeiro et al. 2022)
jbd_coordCountryInconsistent & *bdc_coordinates_country_inconsistent*	*BeeBDC & bdc*	Flag occurrences where the country name does not match the coordinates. Both functions are very similar with slightly different implementations (*.coordinates_country_inconsistent*)	(Ribeiro et al. 2022; Dorey et al. 2023)
bdc_country_standardized	*bdc*	Standardises country names and adds ISO2 codes, if needed	(Ribeiro et al. 2022)
bdc_coordinates_from_locality	*bdc*	Extracts occurrences with locality information that might allow geolocation (to fill gaps)	(Ribeiro et al. 2022)
bdc_scientificName_empty	*bdc*	Flag occurrences without a scientific name (*.scientificName_empty*)	(Ribeiro et al. 2022)
bdc_coordinates_empty	*bdc*	Flag occurrences without latitude or longitude (*.coordinates_empty*)	(Ribeiro et al. 2022)
bdc_coordinates_outOfRange	*bdc*	Flag occurrences that don't map on Earth (*.coordinates_outOfRange*)	(Ribeiro et al. 2022)
bdc_basisOfRecords_notStandard	*bdc*	Flag occurrences based on "*basisOfRecord*" (*.basisOfRecords_notStandard*)	(Ribeiro et al. 2022)
clean_fossils	*CoordinateCleaner*	Flags species that occur in common fossil databases	(Zizka et al. 2019)
4. Taxonomy	*harmoniseR**	*BeeBDC*	Harmonizes taxonomy based on custom synonym lists (updated bee taxonomy provided; *.invalidName*)	(Dorey et al. 2023)

	bdc_clean_names	*bdc*	Cleans scientific names (e.g., removes prepended family names, removes qualifiers, etc.) and flags occurrences with name qualifiers (*.uncer_terms, verbatim_scientificName, & names_clean*)	(Ribeiro et al. 2022)
	bdc_query_names_taxadb	*bdc*	Harmonizes taxonomy based on the *taxadb* package	(Ribeiro et al. 2022)
5. Space	*diagonAlley**	*BeeBDC*	Flags records for fill-down errors in coordinates within dataset (*.sequential*)	(Dorey et al. 2023)
	coordUncerFlagR	*BeeBDC*	Flags occurrences that do not pass a threshold of "*coordinateUncertaintyInMeters*" (*.uncertaintyThreshold*)	(Dorey et al. 2023)
	countryOutlieRs*	*BeeBDC*	Flags occurrences that do not match exact or adjacent country based on a custom checklist (bee country checklist is provided; *.countryOutlier & countryMatch*)	BeeBDC
	manualOutlierFindeR	*BeeBDC*	Flags occurrences (and their duplicates) based on expert identification (*.expertOutlier*)	BeeBDC
	jbd_coordinates_precision & bdc_coordinates_precision	*BeeBDC & bdc*	Flags occurrences based on coordinate precision (number of decimal places). The *bdc* function flags occurrences if either latitude or longitude are imprecise. The *BeeBDC* function only flags occurrences where both latitude and longitude are imprecise (*.rou*)	(Ribeiro et al. 2022; Dorey et al. 2023)
	clean_coordinates	*CoordinateCleaner*	Flags occurrences based on proximity to the centroids of capitals, countries, provinces, GBIF, and institutions; zeros for coordinates; points in seas; statistical outliers; urban areas; and coordinate validity (*.val, . cen, .inst, .equ, .sea, .zer, .otl, .cap, & .gbf*)	(Zizka et al. 2019)
	cd_ddmm	*CoordinateCleaner*	Flags occurrences where a significant fraction of records have been subjected to a common 'degree minute' to 'decimal degree' conversion error, where the degree sign is recognized as decimal delimiter	(Zizka et al. 2019)

	cd_round	*CoordinateCleaner*	Flags occurrences that might be from gridded datasets (*.lonFlag*, *.latFlag*, & *.gridSummary*)	(Zizka et al. 2019)
6. Time	*dateFindR*	*BeeBDC*	Attempts to find and rescue dates hidden in other columns	(Dorey et al. 2023)
	bdc_eventDate_empty	*bdc*	Flags occurrences without a date (*.eventDate_empty*)	(Ribeiro et al. 2022)
	bdc_year_outOfRange	*bdc*	Flags occurrences created prior to a user-specified year cut-off (*.year_outOfRange*)	(Ribeiro et al. 2022)
7. Duplicates	*dupeSummary*	*BeeBDC*	Iteratively searches out duplicates based on user-specified inputs. Duplicate clusters are merged and one occurrence is kept (based on user input) while the rest are flagged (*.duplicates*)	(Dorey et al. 2023)
	cc_dupl	*CoordinateCleaner*	Flags duplicates based on matching coordinates and species names (*.dpl*)	(Zizka et al. 2019)
8. Filtering	*summaryFun*	*BeeBDC*	Filters occurrences based on flag columns and has additional inputs including: choosing filters to examine, only updating the ".summary" flag column, and removing the flag columns (*.summary*)	(Dorey et al. 2023)
	bdc_filter_out_flags	*bdc*	Filters occurrences using all present flag columns (starting with ".")	(Ribeiro et al. 2022)
	bdc_filter_out_names	*bdc*	Filters occurrences based only on the accepted status of taxonomy	(Ribeiro et al. 2022)
9. Figures & tables	*chordDiagramR*	*BeeBDC*	Creates a chord diagram that shows the direction and strength of duplicate linkages between data sources	(Dorey et al. 2023)
	dupePlotR	*BeeBDC*	Creates two stacked bar graphs showing the total number and proportion of duplicates, kept duplicates, and unique records per data source	(Dorey et al. 2023)
	plotFlagSummary	*BeeBDC*	Visualise the results of all flag columns for all data sources	(Dorey et al. 2023)

summaryMaps	*BeeBDC*	Visualise a country-level, global, and classed heat map of occurrences and species per country	(Dorey et al. 2023)
interactiveMapR	*BeeBDC*	Create interactive html maps for any number of species that show collection and flag data	(Dorey et al. 2023)
jbd_create_figures & *bdc_create_figures*	*BeeBDC* & *bdc*	Create figures reporting the results of the *BeeBDC* or *bdc* packages	(Ribeiro et al. 2022; Dorey et al. 2023)
bdc_quickmap	*bdc*	Create a quick point map	(Ribeiro et al. 2022)
dataProvTables	*BeeBDC*	Build a table that shows the number of occurrences and species attributable to each data provider	(Dorey et al. 2023)
flagSummaryTable	*BeeBDC*	Produces a summary table of failures for each flag per species (or any other user-defined categorical column).	(Dorey et al. 2023)
bdc_create_report	*bdc*	Create a report summarizing the results of data quality tests	(Ribeiro et al. 2022)
10. Data sets	*beesTaxonomy* & *beesChecklist*	*BeeBDC*	Modified and machine-readable versions of the Discover Life[23] bee taxonomy and country-level checklist that can be downloaded from FigShare using these functions	(Dorey et al. 2023)
	beesRaw, beesFlagged, & *bees3sp*	*BeeBDC*	Three test datasets with (i) 100 randomly chosen unflagged occurrences, (ii) 100 randomly chosen flagged occurrences, and (iii) 105 occurrences for three haphazardly chosen bee species.[23]	(Dorey et al. 2023)
Auxiliary	*fileFinder*	*BeeBDC*	Recursively searches a directory for the most-recent version of a file that matches a text string and returns the path[23]	(Dorey et al. 2023)
	ColTypeR	*BeeBDC*	Provides arguments to define column types in *tibble* data frames. Users may provide any number of additional columns and column types	(Dorey et al. 2023)
	repoFinder	*BeeBDC*	Returns paths for all GBIF, SCAN, iDigBio, and ALA occurrence datasets within a specified directory	(Dorey et al. 2023)

751
752

753 **Table 2**. The institution code, institution name, number of clean bee occurrences, and number of unique bee species for the datasets with >100,000 clean bee
754 occurrences in our dataset.

Institution code	Institution name	Occurrence count	Species count
iNaturalist	iNaturalist	823,679	2,954
USDA-ARS	USDA Agricultural Research Service	450,540	4,264
Observation.org	Observation.org	421,262	690
SLU Artdatabanken	SLU Artdatabanken	353,869	284
Natuurpunt	Natuurpunt	268,470	303
USGS	United States Geological Survey Bee Lab	251,123	1,238
CSCF	Swiss National Biodiversity Data and Information Centres	246,684	578
AMNH	American Museum of Natural History	242,953	5,152
KU	Kansas University Entomology collection	215,411	5,786
Biological Records Centre	Biological Records Centre	191,773	258
Bumblebee Conservation Trust	Bumblebee Conservation Trust	147,833	271
AMU	Adam Mickiewicz University in Poznań	144,805	191
naturgucker	naturgucker	139,953	411
FinBIF	Finnish Biodiversity Information Facility	135,871	315

755
756

Figures

758
759   Figure 1.
760

Duplicated record sources

761
762   Figure 2.
763

764
765 Figure 3.

766
767 Figure 4.

(a)

(b)

768
769   Figure 5.
770

Figure Legends

772   **Figure 1.** Visual summary of our BeeBDC[24] workflow for compiling, cleaning, flagging, and
773   summarizing the most extensive, publicly available data set of native bee occurrences. Asterisk
774   indicates that the number of records flagged in (5) Space Flagging includes all steps.
775

Figure 2. A chord diagram showing duplications between major data sources. The major data
repositories, the Global Biodiversity Information Facility (GBIF), Integrated Digitized
Biocollections (iDigBio), and Symbiota Collections of Arthropods Network (SCAN) are indicated
on the diagram's outer ring with bee families indicated on the associated inner ring. Smaller
collections are indicated under 'Other' on the outer ring and the associated inner ring indicates
individual datasets. The 'Other' collections are the Atlas of Living Australia (ALA), Allan Smith-
Pardo (ASP), Bob Minckley (BMin), *Bombus* Montana (BMont), The Connecticut Agricultural
Experiment Station (CAES[29,30]), Ecdysis (Ecd[27]), Gaiarsia (Gai[28]), Elinor Lichtenberg (Lic[36]), and
the United States Geological Survey (USGS) data. The size of each ring and inner linkage (chord)
is relative to the number of occurrences. The chords link occurrences are that are duplicated
between data sources[85].
787

Figure 3. Duplicate occurrence summary. Two bar plots showing (a) the total number of
records and (b) the proportion of records in each dataset that were duplicates (sand), kept

duplicates (light green), and unique (dark green). Duplicates are occurrences that were
identified to have a match in another or the same dataset and that were thus flagged or
discarded. Kept duplicates are the same as duplicates, except they are the version of the
occurrence records that were kept. Unique occurrences are those that were not matched to
any other occurrences and were also kept. The included datasets are the Global Biodiversity
Information Facility (GBIF), Symbiota Collections of Arthropods Network (SCAN), Integrated
Digitized Biocollections (iDigBio), the United States Geological Survey (USGS), the Atlas of
Living Australia (ALA), Elle Pollination Ecology Lab (EPEL[25]), the Connecticut Agricultural
Experiment Station (CAES[29,30]), Ecdysis (Ecd[27]), Allan Smith-Pardo (ASP), Gaiarsia (Gai[**28**]),
Bombus Montana (BMont[26]), Ballare, et al. [35] (Bal), Armando (Arm), Bob Minckley (BMin),
Elinor Lichtenberg (Lic[36]), Eastern Colarado (EaCO), Texas literature data (SMC), and Dorey
literature data (Dor)[3,4,37].

Figure 4. Flag summary. A compound bar plot showing the proportion of all occurrences within
each data source (x-axis) that were flagged for each filtering step (y-axis). Green indicates the
proportion of occurrences that passed a filter, red indicates the proportion that failed a filter,
and grey indicates those that could not be assessed. Each x-axis tick indicates intervals of 25%.
The summary row indicates the total proportion of passed or failed occurrences for each
dataset based on those that were chosen to be filtered. In this instance, (i) taxonomic qualifier,
(ii) gridded longitudes, (iii) gridded latitudes, and (iv) gridded latitude and longitude were not
included in the summary row. The included datasets are the Global Biodiversity Information
Facility (GBIF), Symbiota Collections of Arthropods Network (SCAN), Integrated Digitized
Biocollections (iDigBio), the United States Geological Survey (USGS), the Atlas of Living
Australia (ALA), Allan Smith-Pardo (ASP), the Connecticut Agricultural Experiment Station
(CAES[29,30]), *Bombus* Montana (BMont[26]), Bob Minckley (BMin), Ecdysis (Ecd[27]), Gaiarsia (Gai[**28**]),
Elle Pollination Ecology Lab (EPEL[25]), Armando (Arm), Ballare, et al. [35] (Bal), Eastern Colarado
(EaCO), Elinor Lichtenberg (Lic[36]), Texas literature data (SMC), and Dorey literature data
(Dor)[3,4,37].

Figure 5. Occurrence-country summary maps created using the cleaned data indicating the (a)
number of species per country and (b) number of occurrences per country from the filtered
data. Colours indicate the number of (a) species or (b) occurrences where dark colours are low
and yellow colours are high. Class intervals were defined using a "fisher" method.

References
1   Tu, D. V. *et al.* Taxonomy notes and new occurrence data of four species of atyid
shrimp (Crustacea: Decapoda: *Atyidae*) in Vietnam, all described from China.
Biodivers. Data J. **9,** e70289 (2021).
2   Dar, G. H., Khuroo, A. A., Reddy, C. S. & Malik, A. H. Impediment to taxonomy and its
impact on biodiversity science: an Indian perspective. *Proc. Natl. Acad. Sci. India Sect.*
B Biol. Sci. **82,** 235-240 (2012).
3   Dorey, J. B., Fagan-Jeffries, E. P., Stevens, M. I. & Schwarz, M. P. Morphometric
comparisons and novel observations of diurnal and low-light-foraging bees. *J.*
Hymenoptera Res. **79,** 117–144 (2020).
4   Dorey, J. B. Missing for almost 100 years: the rare and potentially threatened bee
Pharohylaeus lactiferus (Hymenoptera, Colltidae). *J. Hymenoptera Res.* **81,** 165-180
(2021).
5   Dorey, J. B. *et al.* Continental risk assessment for understudied taxa post catastrophic
wildfire indicates severe impacts on the Australian bee fauna. *Global Change Biol.* **27,**
6551-6567 (2021).

6 Orr, M. C. *et al.* Global patterns and drivers of bee distribution. *Curr. Biol.* **31,** 451-
458.e454 (2021).
7 Kass, J. M. *et al.* The global distribution of known and undiscovered ant biodiversity.
Science Advances **8,** eabp9908 (2022).
8 Murray, E. A. *et al.* Phylogeny, phenology, and foraging breadth of *Ashmeadiella*
(Hymenoptera: Megachilidae). *Insect. Syst. Divers.* **5** (2021).
9 Callaghan, C. T. *et al.* The benefits of contributing to the citizen science platform
iNaturalist as an identifier. *PLoS Biol.* **20,** e3001843 (2022).
10 Deacon, C., Govender, S. & Samways, M. J. Overcoming biases and identifying
opportunities for citizen science to contribute more to global macroinvertebrate
conservation. *Biodivers. Conserv.* **32,** 1789-1806 (2023).
11 Convention on Biological Diversity. *First draft of the post-2020 global biodiversity*
framework. (United Nations Environment Programme, 2021).
12 Chapman, A. *Principles of Data Quality*. (Global Biodiversity Information Facility,
Copenhagen, 2005).
13 Ribeiro, B. R. *et al. bdc*: a toolkit for standardizing, integrating and cleaning biodiversity
data. *Methods Ecol. Evol.* **13,** 1421-1428 (2022).
14 Goodwin, Z. A., Harris, D. J., Filer, D., Wood, J. R. I. & Scotland, R. W. Widespread
mistaken identity in tropical plant collections. *Curr. Biol.* **25,** R1066-R1067 (2015).
15 Maldonado, C. *et al.* Estimating species diversity and distribution in the era of Big Data:
to what extent can we trust public databases? *Global Ecol. Biogeogr.* **24,** 973-984
(2015).
16 Peterson, A. T., Asase, A., Canhos, D. A. L., de Souza, S. & Wieczorek, J. Data leakage
and loss in biodiversity informatics. *Biodivers. Data J.* **6,** e26826 (2018).
17 Chapman, A. *Principles and Methods of Data Cleaning: Primary Species and Species-*
Occurrence Data version 1.0. (Global Biodiversity Information Facility, Copenhagen,
2005).
18 Boakes, E. H. *et al.* Distorted views of biodiversity: spatial and temporal bias in species
occurrence data. *PLoS Biol.* **8,** e1000385 (2010).
19 Pinkert, S., Barve, V., Guralnick, R. & Jetz, W. Global geographical and latitudinal
variation in butterfly species richness captured through a comprehensive country-
level occurrence database. *Global Ecol. Biogeogr.* **31,** 830-839 (2022).
20 Guénard, B., Weiser, M. D., Gómez, K., Narula, N. & Economo, E. P. The Global Ant
Biodiversity Informatics (GABI) database: synthesizing data on the geographic
distribution of ant species (Hymenoptera: Formicidae). *Myrmecol. News* **24,** 83–89
(2017).
21 Ollerton, J. Pollinator diversity: distribution, ecological function, and conservation.
Annu. Rev. Ecol., Evol. Syst. **48** (2017).
22 Danforth, B. N., Minckley, R. L., Neff, J. L. & Fawcett, F. *The Solitary Bees: Biology,*
Evolution, Conservation. (Princeton University Press, 2019).
23 Ascher, J. S. & Pickering, J. *Discover Life bee species guide and world checklist*
(Hymenoptera: Apoidea: Anthophila).
http://www.discoverlife.org/mp/20q?guide=Apoidea_species, 2020).
24 Dorey, J. B., O'Reilly, R. L., Bossert, S. & Fischer, E. E. BeeBDC: an occurrence data
cleaning   package.   v.   R   package   version   1.0.0
https://jbdorey.github.io/BeeBDC/index.html (2023).
25 Guzman, L. M., Kelly, T. & Elle, E. A data set for pollinator diversity and their
interactions with plants in the Pacific Northwest. *Ecology*, e3927 (2022).
26 Delphia,   C.   M.   Bumble   bees   of   Montana.
https://www.mtent.org/projects/Bumble_Bees/bombus_species.html. (2022)
27 Ecdysis.   *Ecdysis: a   portal   for   live-data   arthropod   collections*,
<https://serv.biokic.asu.edu/ecdysis/index.php> (2022).

28 Gaiarsa, M. P., Kremen, C. & Ponisio, L. C. Pollinator interaction flexibility across scales
affects patch colonization and occupancy. *Nat. Ecol. Evol.* **5,** 787-793 (2021).
29 Zarrillo, T. A., Stoner, K. A. & Ascher, J. S. Biodiversity of bees (Hymenoptera: Apoidea:
Anthophila) in Connecticut (USA). *Zootaxa* (Accepted).
30 Ecdysis. Occurrence dataset (ID: 16fca9c2-f622-4cb1-aef0-3635a7be5aeb).
https://ecdysis.org/content/dwca/CAES-CAES_DwC-A.zip. (2023)
31 Auerbach, E. S., Johnson, W. P., Smith, J. R. & McIntyre, N. E. Wildlife refuges support
high bee diversity on the Southern Great Plains. *Environ. Entomol.* **48,** 968-976 (2019).
32 Angela, B., Lisa, M. O., Loren, M. S. & Scott, T. M. A survey of the insects of the
Southern High Plains (Llano Estacado) of Texas, with particular reference to pollinators
and other anthophiles. *J. Kans. Entomol. Soc.* **91,** 255-309 (2019).
33 Cate, C. A. *Monitoring, assessing and evaluating the pollinator species (Hymenoptera:*
Apoidea) found on a native brush site, a revegetated site and an urban garden Doctoral
dissertation thesis, Texas A&M University, (2007).
34 Cusser, S., Neff, J. L. & Jha, S. Land-use history drives contemporary pollinator
community similarity. *Landscape Ecol.* **33,** 1335-1351 (2018).
35 Ballare, K. M., Neff, J. L., Ruppel, R. & Jha, S. Multi-scalar drivers of biodiversity: local
management mediates wild bee community response to regional urbanization. *Ecol.*
Appl. **29,** e01869 (2019).
36 Lichtenberg, E. M., Milosavljević, I., Campbell, A. J. & Crowder, D. W. Differential
effects of soil conservation practices on arthropods and crop yield. *bioRxiv*,
https://doi.org/10.1101/2021.1112.1106.471474 (2022).
37 Dorey, J. B., Schwarz, M. P. & Stevens, M. I. Review of the bee genus *Homalictus*
Cockerell (Hymenoptera: Halictidae) from Fiji with description of nine new species.
Zootaxa **4674,** 1–46 (2019).
38 GBIF.org. GBIF occurrence download, Stenotritidae.
https://doi.org/10.15468/dl.qw4nrx. (2023)
39 GBIF.org. GBIF occurrence download, Apidae. https://doi.org/10.15468/dl.z47pxw.
(2023)
40 GBIF.org. GBIF occurrence download, Megachilidae.
https://doi.org/10.15468/dl.fehn9f. (2023)
41 GBIF.org. GBIF occurrence download, Colletidae. https://doi.org/10.15468/dl.v7ua7j.
(2023)
42 GBIF.org. GBIF occurrence download, Halictidae.
https://doi.org/10.15468/dl.mndybx. (2023)
43 GBIF.org. GBIF occurrence download, Andrenidae.
https://doi.org/10.15468/dl.9hpbc2. (2023)
44 GBIF.org. GBIF occurrence download, Melittidae.
https://doi.org/10.15468/dl.hvc4tm. (2023)
45 SCAN. SCAN-Bugs occurrence download, Andrenidae (uuid: 4aa93d4a-14c1-46cf-
962b-91b511b37a61). (2023).
46 SCAN. SCAN-Bugs occurrence download, Colletidae (uuid: 51f8ff61-ef61-4442-b4fc-
633363bd3a72). (2023).
47 SCAN. SCAN-Bugs occurrence download, Megachilidae (uuid: 22c06aa6-5de7-481b-
8f3c-19a38e5d781b). (2023).
48 SCAN. SCAN-Bugs occurrence download, Melittidae (uuid: 2ef4b935-6955-4755-baad-
3ab29dacb39e). (2023).
49 SCAN. SCAN-Bugs occurrence download, Halictidae (uuids: b43390c4-1e3f-43c9-bf20-
d47d08790ba6; 7a557a82-ee7c-43d7-9482-aa92962e7822). (2023).
50 SCAN. SCAN-Bugs occurrence download, Stenotritidae (uuid: ba089776-099d-4d66-
8ff0-3b5cfe31f9c8). (2023).

944	51	SCAN. SCAN-Bugs occurrence download, Apidae (uuids: 2b932582; dedc-4c2d-8562-
945		0b55234ac34a; 55eef3f1-a4db-40ab-a1d2-ecb87ca1ea27; 708bbd8f-e396-4790-
946		8c09-9fa93c1b7b37; 02eb74a8-dc4e-416e-84ed-2743473bfd3f). (2023).
947	52	iDigBio.org. iDigBio occurrence download, Halictidae. http://s.idigbio.org/idigbio-downloads/0dcb19ee-20d5-4f31-9378-ace17d4e648f.zip. (2023)
949	53	iDigBio.org. iDigBio occurrence download, Andrenidae. http://s.idigbio.org/idigbio-downloads/1628cae7-9c45-4c6f-8030-4b85e55fd8a3.zip. (2023)
951	54	iDigBio.org. iDigBio occurrence download, Colletidae. http://s.idigbio.org/idigbio-downloads/33d3eb54-aa6f-48bd-ab3e-0edd199ce87c.zip. (2023)
953	55	iDigBio.org. iDigBio occurrence download, Stenotritidae. http://s.idigbio.org/idigbio-downloads/5aa5abe1-62e0-4d8c-bebf-4ac13bd9e56f.zip. (2023)
955	56	iDigBio.org. iDigBio occurrence download, Melittidae. http://s.idigbio.org/idigbio-downloads/a1f9d87e-b68d-4152-b2bc-f5b22fa861b4.zip. (2023)
957	57	iDigBio.org. iDigBio occurrence download, Megachilidae. http://s.idigbio.org/idigbio-downloads/b9105de9-40e2-45db-ab94-50f0bd532eb1.zip. (2023)
959	58	iDigBio.org. iDigBio occurrence download, Apidea. http://s.idigbio.org/idigbio-downloads/cb6ec734-00b1-47d7-811e-90ec9ce9ebb7.zip. (2023)
961	59	Droege, S., Irwin, E., Malpass, J. & Mawdsley, J. *The bee lab*. Report No. 2023-3023, 2 (Reston, VA, 2023).
963	60	ALA.org.au. ALA occurrence download. https://doi.org/10.26197/ala.cdb5a16c-5f19-4dee-b584-5f2f40196bd9. (2023)
965	61	Stevenson, M., Westgate, M. & Newman, P. *galah*: Atlas of Living Australia (ALA) data and resources in *R*. v. *R* package version 1.5.3 https://cran.r-project.org/web/packages/galah/index.html (2022).
968	62	R Development Core Team. R: a language and environment for statistical computing. v. R version 4.3.1 http://www.R-project.org (Vienna, Austria, 2019).
970	63	Wickham, H., François, R., Henry, L. & Müller, K. *dplyr*: a grammar of data manipulation. v. *R* package version 1.1.3 https://cran.r-project.org/web/packages/dplyr/index.html (2022).
973	64	Bache, S. M. & Wickham, H. *magrittr*: a forward-pipe operator for *R*. v. *R* package version 2.0.3 https://cran.r-project.org/web/packages/magrittr/index.html (2022).
975	65	Müller, K. & Wickham, H. *tibble*: simple data frames. v. *R* package version 3.2.1 https://cran.r-project.org/web/packages/tibble/index.html (2022).
977	66	Wickham, H. *stringr*: simple, consistent wrappers for common string operations. v. *R* package version 1.5.0 https://CRAN.R-project.org/package=stringr (2019).
979	67	Henry, L. & Wickham, H. *tidyselect*: select from a set of strings. v. R package version 1.2.0 https://CRAN.R-project.org/package=tidyselect (2022).
981	68	Wickham, H. *ggplot2: Elegant graphics for data analysis*. (Springer-Verlag, 2016).
982	69	Wickham, H. & Girlich, M. *tidyr*: tidy messy data. v. *R* package version 1.2.0 https://CRAN.R-project.org/package=tidyr (2022).
984	70	Henry, L. & Wickham, H. *rlang*: functions for base types and core *R* and '*tidyverse*' features. v. *R* package version 1.1.1 https://CRAN.R-project.org/package=rlang (2022).
986	71	Wickham, H., Hester, J. & Ooms, J. *xml2*: parse XML. v. *R* package version 1.3.5 https://CRAN.R-project.org/package=xml2 (2021).
988	72	Wickham, H., Hester, J. & Bryan, J. *readr*: read rectangular text data. v. *R* package version 2.1.4 https://CRAN.R-project.org/package=readr (2022).
990	73	Grolemund, G. & Wickham, H. Dates and times made easy with *lubridate*. *J. Stat. Softw.* **40,** 1–25 (2011).
992	74	Zizka, A. *et al. CoordinateCleaner*: Standardized cleaning of occurrence records from biological collection databases. *Methods Ecol. Evol.* **10,** 744-751 (2019).
994	75	Bengtsson, H. *R.utils*: various programming utilities. v. R package version 2.12.2 https://CRAN.R-project.org/package=R.utils (2022).

76 Boettiger, C. Ecological metadata as linked data. *J. Open Source Softw.* **4,** 1276 (2019).

77 Schauberger, P. & Walker, A. *openxlsx*: read, write and edit xlsx files*. R package version*
4.2.5.2. v. R package version 4.2.5.2 https://CRAN.R-project.org/package=openxlsx
(2023).

78 South, A. *rnaturalearth*: world map data from Natural Earth. v. *R* package version 0.3.4
https://CRAN.R-project.org/package=rnaturalearth (2017).

79 South, A. *rnaturalearthdata*: world vector map data from Natural Earth used in
'*rnaturalearth*'. v. *R* package version 0.1.0 https://CRAN.R-
project.org/package=rnaturalearthdata (2017).

80 Arel-Bundock, V., Enevoldsen, N. & Yetman, C. *countrycode*: An *R* package to convert
country names and country codes. *J. Open Source Softw.* **3,** 848 (2018).

81 Carr, D., Lewin-Koh, N., Maechler, M. & Sarkar, D. *hexbin*: hexagonal binning routines.
v. *R* package version 1.28.3 https://CRAN.R-project.org/package=hexbin (2021).

82 Wilke, C. O. *cowplot*: streamlined plot theme and plot annotations for 'ggplot2'. v. R
package version 1.1.1 https://CRAN.R-project.org/package=cowplot (2019).

83 Dunnington, D. ggspatial: spatial data framework for ggplot2. v. R package version
1.1.9 https://CRAN.R-project.org/package=ggspatial (2021).

84 Ushey, K. *renv*: project environments. v. *R* package version 1.0.2 https://CRAN.R-
project.org/package=renv (2022).

85 Flor, M. *chorddiag*: interactive chord diagrams. v. *R* package version 0.1.3
https://github.com/mattflor/chorddiag/ (2022).

86 Csardi, G. & Nepusz, T. The *igraph* software package for complex network research.
InterJournal, 1695 (2006).

87 Pebesma, E. Simple features for *R*: standardized support for spatial vector data. *R J.*
10, 439–446 (2018).

88 Hijmans, R. J. *terra*: spatial data analysis. v. *R* package version 1.5-21 https://CRAN.R-
project.org/package=terra (2022).

89 Wieczorek, J. *et al.* Darwin Core: an evolving community-developed biodiversity data
standard. *PLOS ONE* **7,** e29715 (2012).

90 Naaz, Z. T., Bibi, R. & Dorey, J. B. Current status of bees in Fiji; geographical distribution
and role in pollination of crop plants. *Orient. Insects* **56,** 1-27 (2022).

91 Chesshire, P. R. *et al.* Completeness analysis for over 3000 United States bee species
identifies persistent data gaps. *Ecography* **2023,** e06584 (2023).

92 Gu, Z., Gu, L., Eils, R., Schlesner, M. & Brors, B. *circlize* Implements and enhances
circular visualization in *R*. *Bioinformatics* **30,** 2811-2812 (2014).

93 Gu, Z., Eils, R. & Schlesner, M. Complex heatmaps reveal patterns and correlations in
multidimensional genomic data. *Bioinformatics* **32,** 2847–2849 (2016).

94 Gu, Z. Complex heatmap visualization. *iMeta* **1,** e43 (2022).

95 Hvitfeldt, E. *paletteer*: comprehensive collection of color palettes. v. R package
version. 1.5.0 https://github.com/EmilHvitfeldt/paletteer (2021).

96 Fisher, W. D. On grouping for maximum homogeneity. *J. Am. Stat. Assoc.* **53,** 789–798
(1958).

97 Bivand, R. *classInt*: choose univariate class intervals. v. R package version. 0.4–9
https://CRAN.R-project.org/package=classInt (2022).

1040