Speech prosody enhances the neural processing of syntax

AUTHORS

Giulio Degano[1], Peter W. Donhauser[4], Laura Gwilliams[5], Paola Merlo[6,7], Narly Golestani[1,2,3].

1. Department of Psychology, Faculty of Psychology and Educational Sciences, University of Geneva, Geneva, Switzerland.
2. Brain and Language Lab, Cognitive Science Hub, University of Vienna.
3. Dept of Behavioral and Cognitive Biology, Faculty of Life Sciences, University of Vienna.
4. Ernst Strüngmann Institute for Neuroscience in Cooperation with Max Planck Society, Frankfurt am Main, Germany.
5. Department of Psychology, Stanford University, California, USA
6. Department of Linguistics, University of Geneva, Geneva, Switzerland.
7. University Centre for Informatics, University of Geneva, Geneva, Switzerland.

Abstract

Human language relies on the correct processing of syntactic information, as it is essential for

successful communication between speakers. As an abstract level of language, syntax has

often been studied separately from the physical form of the speech signal, thus often masking

the interactions that can promote better syntactic processing in the human brain. We analyzed

a MEG dataset to investigate how acoustic cues, specifically prosody, interact with syntactic

representations. We examined whether prosody enhances the cortical encoding of syntactic

representations. We decoded syntactic phrase boundaries directly from brain activity, and

evaluated possible modulations of the decoding by the presence of prosodic boundaries. Our

findings demonstrate that the presence of a prosodic boundary improves the representation of

phrase boundaries, indicating the facilitative role of prosodic cues in processing abstract

linguistic features. This study gives neurobiological evidence for the boosting of syntactic

processing via interactions with prosody.

Introduction

One of the main properties of human languages is its structured, and not purely linear, nature. Syntactic rules define syntactic structure, which can give rise to an infinite number of utterances. This structure has an important role in speech comprehension, as it groups words into coherent syntactic and semantic units and supports efficient communication. Thus, the correct processing of syntactic information is critical for successful communication across speakers. Beside syntactic rules, different abstract sources of information can change the way these utterances are processed (i.e. semantic content, context, predictions based on statistics, etc), but research in the last twenty years has shown that syntax can be also tightly linked to a more physical aspect of speech: prosodic information [1,2].

The suprasegmental information carried by prosody has multiple acoustic markers that can be used to orient the processing of sentence structure, and the semantic interpretation of sentences. These acoustic markers can include variation in pitch or in the energy of the speech signal as well as lengthening of syllables or the insertion of long pauses. For example, the sentence "Johnny the little boy is playing" has two different meanings that give rise to two different syntactic representations and are expressed by two different locations of the acoustic cues. The lengthening of the syllable *boy* and the placement of an additional pause after it can differentiate between two syntactic structures: one where the sentence is directed at someone called 'Johnny' (i.e., "Jonny, the little boy is playing"), and one where 'Johnny' is the subject of the verb phrase (i.e. "Johnny, the little boy, is playing") and the noun phrase 'the little boy', is an apposition. This example shows how prosodic boundaries can dramatically change how words need to be grouped together in order to successfully communicate concepts. This particular feature of prosodic boundaries can be seen as one of the most evident connections between prosody and syntax as it highlights, for example, a close correspondence with grammatical phrase boundaries[1,2]. The alignment between these two linguistic representations might be key for facilitating the mapping of the incoming speech signal onto a syntactic

56 structure, and disambiguating between the two alternative tree representations that
57 correspond to the two different interpretations.

58   The link between prosody and syntax has also extensively been explored in the context
of developmental studies, where it has been proposed that prosody assists the acquisition of
the first language; this phenomenon is known as prosodic bootstrapping [3,4]. This theoretical
framework proposes that infants use prosodic information in the speech signal to help them
infer syntactic rules and structures, and thus acquire their first language [4]. Indeed, prosody
has been shown to help infants learn syntactic constituency [5], interpret syntactic adjacency [6],
and segment continuous speech [7]. Importantly, prosodic bootstrapping has also been shown
to occur in different languages, such as English, French, and Italian [8] and in bilingual infants
[9]. The significant role of prosody in ontogeny is consistent with its posited role as a precursor
of language [10], coming from work showing that newborn babies can already distinguish
languages coming from the same rhythmic class as their environmental language from those
coming from different rhythmic classes [10,11]. In turn, such a developmentally early sensitivity to
prosody likely arises from prenatal processing and learning [12,13], thanks to an auditory system
that is established and functional in the last 4-6 weeks of gestation [14–16]. Indeed, prenatal
exposure to speech and other acoustic signals is more faithful to slower-changing acoustic
information such as that contained in prosody, due to low low-pass filtering of sound by the
amniotic fluid [17–20].

75   Although the results in children show that syntactic learning becomes less reliant on
prosody later in life [21,22], there is evidence of a continuous interaction between these two
features even in adults. This is likely due to the fact that prosodic signals can be a reliable
acoustic and perceptual scaffold for the online processing of syntactic features [23]. Indeed, it
has been shown that prosodic cues such as pitch variation and syllable duration can assist
syntax learning more than transitional probabilities [24]. Prosody also helps the initial parsing of
sentences [25,26], morphosyntactic dependency learning [7], and speech segmentation [7], in adults.

82   Biological evidence for a prosody-syntax interaction further supports the importance of
prosody for more reliable syntactic parsing. Brain imaging research using

electroencephalography (EEG) has shown that changes in pause, pitch, loudness, or duration

that mark boundaries between phrases, known as prosodic boundaries [7], affect neural markers

of syntactic disambiguation. For example, it has been found that manipulation of the placement

of prosodic boundary modulates the evoked responses to the stimuli such as to assist syntactic

disambiguation [27,28] and processing of garden path sentences [29–31]. Conversely, research has

also shown the influence of syntactic predictions on prosodic processing. For instance, it has

been shown that a neural marker of prosodic processing - the closure positive shift [32] – can be

elicited by biases generated from initial syntactic parsing preferences, even in the absence of

explicit acoustic cues [33]. It is thus possible to hypothesize that the regular interaction between

and co-occurrence of these two linguistic features has driven the brain into expecting syntactic

and prosodic representations to be coherent even if one of the two is not explicitly present, or

when they do not co-occur. In line with this, a recent study has demonstrated that the cortical

tracking of naturalistic speech is enhanced when overt and covert prosodic boundaries are

aligned with the syntactic structure compared to when they are misaligned [34].

Very few fMRI studies have been done on the interaction between prosody and other,

more abstract levels of linguistic information. Seminal studies on the processing of linguistic

prosody per se involved comparing different types of filtered speech. These studies showed

mixed results in terms of hemispheric lateralization, with some having identified right [35,36] but

also some left [37] hemispheric involvement of temporal and frontal-opercular regions in relation

to the modulation of pitch (i.e. intonation) during speech processing. The lateralization likely

depends on which information is being extracted from the signal or on the control condition [38–

41]. The processing of higher-level linguistic features such as syntax is known to be more left-

lateralized involving regions such as the inferior frontal gyrus (IFG), and middle temporal gyrus

[42–44]. The few studies that have focused on the question of prosody-syntax *interactions* using

fMRI showed, for example, that in tonal languages (here: Mandarin), there are shared

activations in the left but not right inferior frontal gyrus IFG between intonational (question vs.

answer) and phonologically relevant tonal (word category) processing [45]. Another investigation

similarly reported a role of the left IFG in processing linguistically relevant intonational cues;

this region's activation was modulated when those cues played a crucial role in sentence comprehension [41].

Although research has shown neural evidence for prosody-syntax interactions, more work is needed to fill the knowledge gap regarding how the brain processes these two linguistic features jointly in more *naturalistic* processing contexts. Most of the studies to date, especially those using EEG, have exploited neural signals or activity emerging from the violation or disambiguation of prosodic or syntactic signals. In the context of EEG studies, this has allowed us to assess the neural markers of time-locked analyses [46], but has limited implications regarding the neural processing of syntactic and prosodic information during naturalistic speech perception. Moreover, controlled studies that make use of expectations or violations can be highly affected by error detection or other processes that are not central to syntactic judgments, again making it difficult to draw conclusions regarding the processing of prosody-syntax interactions per se [30].

In contrast to what can be assessed with well-controlled experimental paradigms, human communication is based on a very complex, multidimensional signal. The use of tightly controlled experiments and reductionist, task-based paradigms fall short of an ecological characterization of the neural processes underlying naturalistic language processing [47]. The importance of the generalization of neuroscience research has gained attention in recent years, and the last decade has seen increased use of narratives in experimental designs, to simulate natural speech perception. For this, brain activity is measured during passive listening, to closely simulate the way that speech is processed in day-to-day contexts. In such studies, control over the effect(s) of interest can be applied *after* data collection, at the data analysis stage, thus increasing the flexibility and ecological validity of the experiment [48]. A driving force underlying this paradigm change is the increasingly flexible and powerful computational tools that are now becoming available to model human speech. Indeed, the use of machine learning techniques to statistically assess (and control for) different linguistic features has led to a new line of research that has the aim of modeling complex cognitive and neural functions in ecologically valid settings[49]. Importantly, such model-based encoding and

decoding approaches allow results to be interpretable in light of proposed underlying cognitive

and/or neural mechanisms [50] . Recent studies have already shown promising results in using

linearized modeling approaches for pinpointing the neural signatures underlying the

processing of semantics [51–53], syntax [54–56], phonetics [57,58] and acoustics [59–61]. These

computational models of the different levels of linguistic representation have however often

been investigated in isolation, and very few studies have looked at their possible interactions

[52].

In the present study, we made use of naturalistic stimuli together with brain decoding

[49] to fill a knowledge gap in how the cortical representation of syntax can be modulated by

prosody to facilitate speech processing . We used machine learning techniques to compute,

on the one hand, the syntactic phrase boundaries, and, on the other hand, the prosodic

boundaries of a speech corpus (TED talks).

Here, we first tested whether the strength of the prosodic boundaries present in the

speech data was modulated as a function of closing phrase boundaries when producing

natural speech (4 separate TED talks)[57]. Thus, while not explicitly marking intonational units,

we employed prosodic boundary strength since it is a metric that's been shown to positively

correlate with intonational units. Then, in an existing magnetoencephalography (MEG) dataset

of participants listening to the same TED talks[57], we investigated whether the neural encoding

mirrors the prosodic-syntactic interaction we identified in the speech signal. Such a finding

would provide biological evidence for 'prosodic boosting' of syntactic encoding in the adult

brain, reflecting a neural mechanism that allows prosodic cues to increase the robustness of

syntactic representations, and thus of successful speech comprehension.

Results

Stimulus spectrogram analysis

We first analyzed the four TED talks spectrograms, to understand if the speakers used different prosodic cues in correspondence with the syntactic closing phrase boundaries of their utterances. Since the prosodic boundary strength is characterized by positive values and by a skewed distribution, we used a gamma mixture to model the strength distribution. The gamma-mixture model was fitted to the prosodic boundary strength distributions across all four TED talks. This analysis revealed two latent gamma distributions: γ_1 with shape of 1.1 and rate of 2.8 and γ_2 with shape of 14 and rate of 10.7. The gamma-mixture analysis resulted in a boundary between γ_1 and γ_2 at 1.01 prosodic boundary strength (dimensionless quantity), thus dividing the words of the TEDLium corpora into content items with high and low prosodic boundary strength (left panel, Fig. 1).

This binarization of the dataset allowed us to uncover the distribution of words with versus without closing phrase boundaries within these two latent prosody distributions. We found that in the presence of weak prosodic boundary strength, the percentage of words without a closing phrase boundary (56%) was greater than the one with a closing phrase boundary (44%), whereas when the speakers used a strong prosodic boundary strength this pattern was reversed (28%for words without a closing phrase boundary y and 72%for words with a closing phrase boundary) (right panel, Fig. 1). We then tested for differences in the proportion of word tokens with and without closing phrase boundaries across the two categories of prosodic boundary strength. First, we ran a GLM with a binomial link function between the two levels of prosodic boundary and the presence or not of a closing phrase boundary. This resulted in a significant positive relationship across the syntactic representation and the prosodic boundary (z-value = 16.52, $p < 0.001$). Second, to further validate these results, we also ran a linear model using the continuous values of the prosodic boundary strength. To do this we changed the link function to a gamma function (family = Gamma() of

the dplyr package in R) and ran the model as done previously. This analysis further confirmed

that words with a closing phrase boundary have greater prosodic boundary strength compared

to words without a closing phrase boundary (t-value = 16.36, p < 0.001).

Based on these results, we created three different groups of word tokens (with

resampling) that could be evaluated in the brain decoding. The first group comprised words

with a weak prosody boundary, called here 'neutral', where a closing phrase boundary could

equally be present or absent. A second group included words without a closing phrase

boundary and a weak prosodic boundary, as well as words with a closing phrase boundary

and a strong prosodic boundary, called here 'coherent', since this group included the most

statistically probable combination based on the stimuli analysis. The third group was

composed of words with a closing phrase boundary and a weak prosodic boundary and

words without closing phrase boundary and a strong prosodic boundary. This last

combination was called 'incoherent', since it had the least probable association of prosody

and syntax, given our analysis of the speech data. Based on these three sets we assess

(1) the contribution of prosodic boundary strength in the encoding syntactic representation

in the brain and (2) if the interaction between syntax and prosody that was seen in the

stimuli was also mirrored within the cortical representation of the participants (see neural

analysis).

Figure 1. Results of the stimulus analysis. The left panel shows the two-Gamma Mixture Model that was used to binarize the words according to high or low prosodic boundary strength. The beige line indicates the probability distribution of words with a weak PB, while the yellow line represents the probability distribution of words with a strong prosodic boundary. The right panel shows the frequencies and count of words with and without a closing phrase boundary in the two prosody clusters.

Neural analysis

Our analysis of brain activity involved the multivariate decoding of syntactic information from brain activity using a combination of the mne-Python software and custom code. The MEG data was divided into smaller trials based on word offsets, and a logistic classifier was trained to map brain activity to the presence or absence of **closing phrase boundaries**. Two types of classifications were performed: one using a classical multivariate pattern analysis (MVPA) thus concatenating MEG data across time and channels (Fig. 2), and another performing a temporal classification over the epoched data (Fig. 3). Importantly, the decoder was trained only on neutral combinations to evaluate the neural processing of syntactic information within a weak prosodic context, thus avoiding any inherent bias that was present in the stimuli. By generalizing the performance of the model across the neutral, coherent, and incoherent conditions, it was then possible to quantify and assess differences in the strength of syntactic representations in the brain under various prosodic conditions.

MVPA decoding

First, we tested whether the neural encoding of **closing phrase boundaries** was modulated by prosodic strength, in line with our stimulus analysis. Specifically, we test the hypothesis that syntactic classification performance is highest in the "coherent" condition, where the presence of closing phrase boundaries is coupled with strong prosodic cues. In the MVPA analysis of the pre-offset time windows (Fig. 2), we found that the classification performance of coherent and neutral, but not of incoherent trials was greater than chance level (Coherent: Mean AUC = 0.52, $p < 0.001$, Incoherent: Mean AUC = 0.5, $p = 0.134$, Neutral: Mean AUC = 0.51, $p < 0.001$). The decoding of the coherent condition was found to be better than that of the neutral and incoherent conditions (Coherent>Incoherent: $p=0.004$; Coherent>Neutral: $p=0.014$). Similar results were obtained in the post offset time window, where all three condition performed better than chance (Coherent: Mean AUC = 0.53, $p < 0.001$, Incoherent: Mean AUC

234 = 0.51, p = 0.032, Neutral: Mean AUC = 0.52, p = 0.001) but at different levels, since the

235 decoding of the coherent condition was again better than that of the neutral and incoherent

236 conditions (Coherent>Incoherent: p=0.002; Coherent>Neutral: p=0.004).

Figure 2 Results of the MVPA. We decoded the presence of closing phrase boundaries using the MEG activity within 400 ms time windows before and after stimulus offset, for the three generalizations sets (coherent in red, incoherent in blue and neutral in orange). The left panel corresponds to the decoding in the pre-stimulus offset time windowIn both pre- and post-offset data, the different test sets were also compared to one another; in both cases, the coherent condition was found to be the set with the highest decodability. (*) p<0.05; (**) p<0.01; (***) p<0.001.

Temporal decoding

The results of the temporal decoding analysis showed significant encoding of syntactic

information in the coherent and neutral test sets (Fig. 3, upper row). The permutation test in

the coherent condition revealed two immediately adjacent clusters that together started just

before word offsets, and peaked within a 0 - 200ms post word-offset time window (Cluster 1:

[-0.085, 0.418]s, p = 0.001; Cluster 2: [0.438, 0.578]s, p = 0.013). In the incoherent condition

we did not find any significant effect of decoding, while the neutral condition showed a similar

but weaker trend compared to the coherent one, with the three significant clusters mostly

spanning the post-offset period (Cluster 1: [-0.024, 0.043]s, p = 0.021; Cluster 2: [0.136,

0.223]s, p = 0.011; Cluster 3: [0.237, 0.311]s, p = 0.010).

In both contrasts comparing tests sets, we found that the presence of prosodic content boosted

the strength of the syntactic classification (lower row, Fig. 3). The cluster permutation test

comparing the coherent with incoherent trials showed significant clusters in the post-offset

period (Cluster 1: [-0.024, 0.063]s, p = 0.012; Cluster 2: [0.076, 0.163]s, p = 0.008; Cluster 3:

[0.230, 0.277]s, p = 0.033; Cluster 4: [0.290, 0.337]s, p = 0.031; Cluster 5: [0.478, 0.599]s, p

= 0.004; Cluster 6: [0.726, 0.759]s, p = 0.043), as did the test comparing the coherent with the

neutral condition (Cluster 1: [0.029, 0.110]s, p = 0.004; Cluster 2: [0.123, 0.163]s, p = 0.048).

This demonstrates a consistency between the patterns observed in the neural encoding of the

syntax-prosody interaction and in those detected in the speech stimuli themselves.

Figure 3 Results of decoding presence/absence of closing phrase boundary, as a word unfolds. The upper panel (A-C) shows the temporal classification accuracy in the coherent (red – A), Incoherent (blue – B) and neutral (yellow – C) sets. Coherent and neutral sets performed performed above chance, but both decoding accuracy and the significant time windows differed across these sets. The performance of test sets was then directly compared (D and E), to identify the time windows during which the coherent set performed better than the incoherent and neutral ones. We found that in the post-stimulus time window of the first 200 ms, the decoding of closing phrase boundaries in coherent condition (i.e. containing trials that had a combination of prosodic and syntactic features that was consistent with the pattern that was most frequently detected in the stimuli) was

significantly stronger than for closing phrase boundaries with weak or mismatched prosodic boundary strength.\ Horizontal red lines represent significant results under cluster-based permutation tests.

Discussion

The purpose of this study was to shed light on the interaction between the representation of

prosody and phrase boundaries in the adult brain. We aimed to uncover their relation within

utterances produced by different TED talk speakers and within the neural representation of

closing phrase boundaries. We tested the hypothesis that the brain represents closing phrase

boundaries differently depending on the prosodic structure of the sentences; this would lend

support to the idea that prosodic information is used by the brain to facilitate the representation

of syntactic relationships during speech processing.

In our stimulus analysis, we showed that speakers modulate their speech output

depending on the intended syntactic structure. More specifically, we showed that stronger

prosodic boundaries were more likely to be placed on words that had a closing phrase

boundary. Conversely, the speech utterances had a relatively weaker if not absent prosodic

boundary for words that did not terminate a larger syntactic unit. These results are in line with

known linguistic relationships between prosody and syntax in speech, based on evidence that

the placement of stress or boundaries in intonational phrases can reflect the syntactic structure

of the sentence[1,2]. Our findings support the presence of an interaction between syntactic units

and prosodic cues, likely reflecting a mechanism whereby speakers, whether consciously or

not, modulate their speech output to help the listener focus on the more salient syntactic

relationships between words in order to facilitate comprehension.

Previous such evidence for prosody-syntax relationships has, however, not been

investigated in speech corpora using fully automated, large-scale language models for the

extraction of prosodic and syntactic features like the ones adopted here [62,63]. Instead, most of

the research exploiting these powerful language parsers has been used for the extraction of

prosodic and syntactic regularities from large amounts of data to produce better text-to-speech

generators [64,65] or to improve the quality of syntactic parsing [66]. Deep learning approaches can

indeed be useful as they indirectly demonstrate a statistical relationship between prosody and

syntax, but only a few of these studies have shown links that are linguistically interpretable [67].

Here, we used a data-driven model of language to automatically extract well-characterized

linguistic features from a continuous, naturalistic speech signal, and as such our work

contributes to a more focused and quantitative analysis of the interface between prosody and

syntax than has been demonstrated to date.

In the MEG data analysis, we tested whether the neural processing of syntactic

information is modulated by prosody while healthy individuals listened to TED talks. We first

trained a decoding model that was free of prosodic biases to learn the mapping of the syntactic

information in the neural data. Then, during generalization testing, we contrasted the decoding

performance across words belonging to different combinations of prosodic and syntactic

information. Two decoding methods were used to assess the relationship. Using MVPA, we

tested time windows before and after the offset of each word to see if the neural processing of

syntactic information may have differed across different prosody-syntax combinations. The

second method made use of temporal decoding, to give us a finer-grained and continuous

view of the dynamics of potential phrase boundary and prosodic boundary interactions. Both

the MVPA and the temporal decoding analyses revealed that prosodic boundary strength was

associated with better classification of the presence or absence of closing phrase boundaries,

suggesting that the presence of prosodic cues leads to enhanced syntactic processing.

Critically, we found this enhancement to underlie coherent rather than incoherent conditions.

We interpret this improved decoding as reflecting that strong prosodic cues serve to enhance

the cortical representation of closing phrase boundaries, suggesting a dynamic interaction

between prosodic and syntactic sources of information during processing. This in turn supports

the importance of bottom-up, acoustic information (e.g. prosody) in shaping higher-level,

linguistic representations. On the other hand, the decoder's poor performance on the

incoherent condition may be due to conflicting sources of information; in the case where they

mismatch,– the prosodic cues serve to weaken the syntactic representation of closing phrase

boundaries, which leads to poorer decoding accuracy. To further validate the specificity of this

effect, we additionally analyzed the temporal decoding within the four classes separately (see

Supplementary materials, Fig.3). Results confirmed that the high decoding accuracy of the

coherent condition is driven by words having high prosodic boundary strength, accompanied

by the presence of closing phrase boundaries.

Our finding aligns with previous work showing the relevance of prosody in the

modulating brain markers of sentence structures and syntactic operations [27,29–31,33,68], but our

work further shows that prosody results in a syntactic representational gain in the neural signal.

Moreover, our findings suggest that the temporal co-occurrence or alignment of prosodic cues,

grounded in the acoustic signal, and of higher-level, abstract linguistic features can enhance,

or boost the neural processing of higher-level linguistic representations. This finding is relevant

for evolutionary theories of language, as it could suggest that prosodic cues might have either

co-evolved with or even preceded the evolution of syntax, to assist the structuring of human

speech. In this context, theorists have already proposed that, as early forms of communication

gradually transformed from protolanguages to complex hierarchical structures, prosody likely

served as a foundational element in influencing the evolution of complex grammatical systems

[69,70].

Our temporal decoding analysis as well as the MVPA revealed interesting qualitative

patterns before and after word offsets. For coherent and neutral conditions decoding

performance was above chance even before word offsets. This suggests the presence of

predictive mechanisms, whereby the brain is anticipating the creation of syntactic units before

the words are completely heard. Unfortunately, even if the prosodic content is controlled in

one of the two conditions that show a predictive effect we cannot shed light on the nature of

this prediction (i.e. acoustic, purely syntactic or a combination of both). In the coherent

condition, significant decoding lasts up to 600ms *after* word offsets, suggesting an additive

contribution of acoustic cues (i.e. presence of prosodic boundary strength) to the higher order

processing underlying speech comprehension following the representation of a closing phrase

boundary [68]. In other words, the presence of prosodic information appears to promote longer-

lasting neural processing of syntax, possibly arising from reverberating top-down and bottom-

up processing during comprehension.

Our decoding analysis of MEG data limits our ability to localize brain regions involved

in the prosody-syntax interface. Previous studies looking at the brain networks modulated by

linguistic prosody per se have shown the involvement of regions within the ventral and dorsal

pathways spanning the superior temporal lobe and sulcus, premotor cortex, posterior temporal

lobe and IFG, often biased towards the right hemisphere [38,71] but found also in the left, or

bilaterally [72–74]. Interestingly, two of these areas – the posterior temporal lobe and IFG – have

historically been considered to also play a crucial role as hubs for syntactic processing [75–77]. It

can be thus hypothesized that the posterior temporal lobe and the inferior frontal gyrus (IFG)

may be possible loci for the interface between prosody and syntax. Indeed, recent findings

seem to indicate the involvement of the left IFG in cases where intonation is used to establish

sentence structure [41,78]. Further investigation on the role of linguistic prosody, especially in

interaction with syntax, remains to be conducted. This work could for example employ

functional connectivity analyses, to shed light on how the respective networks interact to

support synergistic interaction between different levels of (para-)linguistic processing. This

research ought ideally to also integrate more complex models that can disentangle the amount

of information conveyed by prosody and its potential to benefit the structuring of human

speech. For example, extending our computational approach to data with higher spatial

resolution, such as fMRI, could uncover the neural architecture that exploits prosodic

information to enhance the cortical representation of syntactic structures.

Methods
359

MEG data acquisition and preprocessing
360

We made use of an existing MEG dataset obtained from 11 participants in previously

published work (20-34 years; 5 female) [57]. The MEG signals were recorded using a 275-

channel VSM/CTF system, with a sampling rate of 2400 Hz and low-pass filtered at 660 Hz.

Eye movements and blinks were recorded using 2 bipolar electro-oculographic (EOG)

channels.

Independent component analysis was used to remove artifacts due to eye movement

and heartbeats. The MEG signal from each channel was subsequently visually inspected to

remove those containing excessive broadband power spectra. For the coregistration between

anatomical data and the MEG channels, the head shape of each participant was digitized

using Polhemus Isotrak (Polhemus Inc., USA), based on T1-weighted structural MRI data (1.5

T, 240 x 240 mm field of view, 1 mm isotropic, sagittal orientation).

Forward modeling was computed on the MEG data using the overlapping-sphere

model [79]. Noise normalized minimum norm operator was used to estimate the inverse solution

[80]. Further, singular value decomposition was performed on the resolution matrices defining

the source space. For each session and subject, this operation produced a set of M singular

vectors reflecting an orthogonal space on which the coregistered data was projected. By taking

the 99% cut-off of the singular value spectrum, we defined a low-dimensional space X_c over

which the decoding analysis was computed. For further details regarding the data preparation,

see [57].

Speech stimuli

The speech stimuli used during the MEG acquisition consisted of 4 different talks

(Daniel Kahneman, James Cameron, Jane McGonigal, and Tom Wujec), extracted from the

TEDLium corpus [81]. Seven audio files were created by splitting three TED talks into two parts,

while one was kept intact. Audio files lasted 509 secs on average, and only one was played

during each block of MEG acquisition. There were 7 blocks in total, with an average length of

8.49 min [+/- sd of 1.24 mins] (see supplementary material for more information).

The speech stimuli were forced-aligned to the TED talk text, extracted from the online

transcripts using the Montreal forced aligner (MFA, [82]. The automatic alignment was

implemented with the LibriSpeech corpora [83], available as an MFA model. The output of the

alignment was examined, and corrected manually using the Praat software [84].

392   Further stimulus adjustments were done to optimize the following MEG analysis (see

393  Decoding section). First, out-of-dictionary tokens were labeled as <unk> and removed from

394  the set. Second, to avoid positional confounds due to end-of-sentence effects, the last word

395  of each sentence was also removed.

396   The complete preprocessing of the TED talks produced a stimulus set consisting of

397  1723 unique words that were subsequently used in the stimulus and MEG data analysis.

Figure 4. Pipeline for the extraction of the syntactic and prosodic features from the stimuli. Top right corner shows that we first extracted the constituency trees from the text annotation using Spacy. We then marked each word in the text based on the presence (filled dot) or absence (empty dot) of closing phrase boundaries. Bottom left corner shows that we computed a wavelet analysis of the stimulus acoustics to extract the prosodic boundaries (PB – white lines). Prosodic boundaries varied in their strength, depending on the local spectral characteristics of the speech stimuli (thickness of the lines reflects stronger boundaries). Finally, using gamma mixtures models we binarized the prosodic boundaries in two groups, to allow investigation of the prosody – syntax interaction.

Prosodic and syntactic features in the speech stimuli

401   Two sets of features were extracted from the text and audio signal to characterize the

402  syntactic and prosodic components, respectively (Fig. 4). The sentences obtained from the

403  online transcriptions of the selected TED talks were tokenized, tagged with their Part-of-

Speech label, and finally annotated with an automatic parser. The complete annotation was

performed using the pre-trained Spacy pipeline (en_core_web_trf, version 3.2.4,

https://spacy.io/, Berkeley Neural Parser), with the RoBERTa transformer [63]. After the parsing

was computed, we assumed a bottom-up traversal of the tree and counted the number of

closing nodes for each word in the dataset. We assume this bottom-up traversal of the tree as

previous neurophysiological evidence has highlighted a cortical implementation of a bottom-

up parser of the incoming language stream using high-precision intracranial recordings[85] .

Based on this traversal, we assigned each word from the stimulus set to two different classes.

One class represented the group of words that closed more than one node, and were thus

associated with a closing phrase boundary, the other represented the group of words that did

not close any phrase or nodes (Fig.4).

In the second step, we computed a spectro-temporal analysis of the audio files to

extract the word duration, the energy, and the f_0 information. The time courses of these three

features were then combined and analyzed via wavelet transform. The spectrogram obtained

after this last step was used to evaluate the maps of minimal power around word offsets to

assess the prosodic boundary strength associated with each word. This unsupervised

modeling of prosodic information was computed using the Wavelet Prosodic Toolkit to extract

the prosodic boundary strength (https://github.com/asuni/wavelet_prosody_toolkit). While we

have not manually marked intonational units, we employed prosodic boundary strength as a

metric for these units since it has been shown to positively correlate with human annotations[62].

Words that were automatically tagged with prosodic boundary strength equal to 0 were

discarded from further analysis as they did not contain meaningful spectral content. The

prosodic distribution of the data was subsequently modeled using a two-Gamma Mixture

model to cluster the complete stimulus set into two latent distributions. This step allowed us to

classify the prosodic content of each word within the binary categories of weak and strong

prosodic boundary strength. The final feature matrix Y describing our stimuli was thus

comprised of a syntactic feature characterizing the words as having or not having a closing

phrase boundary, and of a prosodic feature characterizing the words as having a weak or strong prosodic boundary strength (Fig. 4).

Assessing the prosody-syntax interaction in the stimuli

To assess the interaction between prosodic and syntactic information in the stimuli, we first separated all the words present in the dataset based on the weak or strong prosodic boundary strength content. We then compared these two groups regarding their percentage of words that did or did not have a closing phrase boundary. This allowed us to examine whether or not prosodic boundary strength was modulated in relation to syntactic structure during the production of the selected TED talks.

Model-based decoding of syntax in the MEG data

The multivariate decoding of syntactic information from brain activity was implemented using a combination of the mne-Python software (version 1.0, https://github.com/mne-tools/mne-python) and custom code. The low-dimensional MEG data X_c was separated into smaller trials by extracting the brain activity before and after each word offset. Trials with an inter-trial offset interval of less than 100 ms were discarded. Following that, a logistic classifier was trained to learn a linear mapping between the brain activity and the presence or absence of closing phrase boundaries. Two different types of classifications were computed. First, MEG data was concatenated across time and channels in the time windows pre-word and post-word offset to assess the general prosodic boosting, with the prediction that syntactic decoding performance would be modulated by prosodic boundary strength in a way that is coherent with the pattern obtained in the stimuli themselves. Second, a refined decoding analysis of each time point between 400ms pre-offset and 800ms post-offset was done, to assess finer temporal modulation patterns of the cortical representation of closing phrase boundaries.

Training and test data sets

The data to be used for training versus testing was selected based on the data-driven modeling computed on the word stimuli. Following the analysis of the stimuli (see 'Stimulus analysis' subsection of the Results), the training set was created by selecting only words having a weak prosodic boundary strength, including an equal number of words with and without closing phrase boundaries. This allowed us to obtain a classifier that was not influenced by the different levels of prosodic content, and that was syntactically balanced.

The model was assessed using three different test sets, each containing the same number of words from each syntactic category (i.e. with and without closing phrase boundaries) that were not overlapping across sets or repeating from the training sample. The first test set, similar to the training dataset, contained only words that had low prosodic boundary strength (*neutral*). The second set contained words having a closing phrase boundary and strong prosodic boundary strength, and words without a closing phrase boundary and weak prosodic boundary strength (*coherent*). The final set contained words having a closing phrase boundary but weak prosodic boundary strength, and words without a closing phrase boundary but with strong prosodic boundary strength (*incoherent*). The final training set was composed of 3740 words and the three testing sets were composed of 654 words each. These three different sets aim to characterize syntactic distributions (i.e. presence or absence of closing phrase boundaries) within different combinations of high and low prosodic boundary strength content. Importantly, we expected the three test sets to generate separate brain features or states that could or could not improve the classification accuracies of the classifiers based on the interaction between prosody and syntax. This analysis allowed us to hypothesize stronger syntactic decoding in the test set that was coherent with the results shown in the stimulus analysis (i.e. in the high separability set). Moreover, this procedure allowed us to quantify differences in the strength of syntactic encoding across the conditions, given that they were balanced such that each include the same number of stimuli with versus without phrase boundaries.

MVPA of pre and post-word offset

We used a logistic classifier (regularization parameter C = 1) to predict the presence of words

with or without closing phrase boundaries. This linear mapping was tested by pooling all the

brain activity time point x channel in two separate time windows: a 400 ms window before word

offset and a 400 ms one after word offset. We hypothesized that the MVPA approach would

also show that the encoding of closing phrase boundaries is modulated by the presence of

prosodic information, i.e. that we'll find evidence for prosodic boosting of syntactic processing.

MVPA statistics

We evaluated the performance of the model by assessing the area under the curve (AUC) of

the classification against chance (50%) on the test sets. The training and testing were repeated

by performing 10-fold randomized cross-validation. The differences across the three

conditions and against chance level were assessed in a second-level analysis via paired

permutation testing with 2046 permutations (permutation_test of mlxtend package). Further

prevalence analysis of the within-participant AUC scores can be found in the Supplementary

material.

Temporal decoding

A single regularized logistic classifier was trained for each time point, and optimized via nested

5-fold cross-validation. The regularization parameter C was selected during nested cross-

validation via a log-spaced grid search between 10^{-5} and 10^{5}.

The best temporal model obtained after the grid search was then tested by estimating

the AUC of the classification (sklearn.metric.roc_auc_score) across each of the different

conditions described above: neutral, incoherent and coherent.

The AUC results across these three test sets were used for two different contrasts to

assess the effects of prosodic boundaries on the decodability of syntactic phrase boundaries

from brain activity. In the first contrast, the coherent condition was tested against the neutral

condition, while in the second we compared coherent against incoherent separability.

Critically, while the first contrast allowed us to understand the effect of prosodic content on closing phrase boundaries, the second verified that the prosodic boosting is specific to words with closing phrase boundaries. This strategy allowed us to show that the potential improvement in decoding was not due to a purely acoustic effect, but to an interaction between syntax and prosody

Temporal decoding statistics

Similarly to the MVPA analysis, the temporal decoding results were evaluated using a cluster-based permutation test. The temporal decoding of the three test sets as well as of the two contrasts were extracted for each participant, and tested against chance (50%) in a second-level analysis. To do this we ran a non-parametric cluster-level paired t-test with 2046 permutations ($2^{\#ofSubjects}$) on the AUC time series obtained from each participant (mne.stats.permutation_cluster_1samp_test).

Funding

This research was funded by the NCCR Evolving Language, Swiss National Science Foundation Agreement #51NF40_180888.

Acknowledgements

We thank Sylvain Baillet for sharing the MEG data, and John Hale and Donald Dunagan for useful exchanges regarding syntax.

Data availability

The decoding data files to reproduce the results using the Github code are available at figshare (https://doi.org/10.6084/m9.figshare.23609505). The raw data are available for research

purposes only upon request from the corresponding author (giulio.degano@unige.ch) or Peter

Donhauser (peter.donhauser@esi-frankfurt.de), because of constraints imposed by the ethics

approval under which this study was conducted.

Code availability

The code for the stimulus analysis and results visualization is available at GitHub

(https://github.com/gDegano/MEG_ProsodyEnhSyntax)

Author information

Authors and Affiliations

Department of Psychology, Faculty of Psychology and Educational Sciences, University of Geneva, Geneva, Switzerland.

Giulio Degano and Narly Golestani

Brain and Language Lab, Cognitive Science Hub, University of Vienna.

Narly Golestani

Dept of Behavioral and Cognitive Biology, Faculty of Life Sciences, University of Vienna.

Narly Golestani

Ernst Strüngmann Institute for Neuroscience in Cooperation with Max Planck Society, Frankfurt am Main, Germany.

Peter Donhauser

Department of Neurosurgery, University of California, San Francisco, California, USA

Laura Gwilliams

Department of Linguistics, University of Geneva, Geneva, Switzerland.

Paola Merlo

University Centre for Informatics, University of Geneva, Geneva, Switzerland.

Paola Merlo

Contributions

Conceptualization: G.D., N.G.; Methodology: G.D., L.G.; Software: G.D.; Formal analysis:

G.D., N.G., L.G., P.M.; Investigation: G.D. N.G..; Resources: N.G.; Data curation: G.D. P.D..;

Writing—original draft: G.D., N.G.; Writing—review and editing: G.D., N.G., L.G., P.D., P.M.;

Visualization: G.D.; Supervision: N.G.; Funding acquisition: N.G.

Corresponding author

Correspondence to Giulio Degano

Ethics declarations

567 Competing interests
568 The authors declare no competing interests.
569

References

1. Elfner, E. The syntax-prosody interface: current theoretical approaches and outstanding

questions. *Linguistics Vanguard* **4**, (2018).

2. Wagner, M. & Watson, D. G. Experimental and theoretical advances in prosody: A

review. *Lang. Cogn. Process.* **25**, 905–945 (2010).

3. Morgan, J. L. & Demuth, K. *Signal to Syntax: Bootstrapping From Speech To Grammar

in Early Acquisition.* (Psychology Press, 1996).

4.   Christophe, A., Guasti, T. & Nespor, M. Reflections on phonological bootstrapping: Its

579   role for lexical and syntactic acquisition. *Lang. Cogn. Process.* **12**, 585–612 (1997).

580   5.   Hawthorne, K. & Gerken, L. From pauses to clauses: prosody facilitates learning of

581   syntactic constituency. *Cognition* **133**, 420–428 (2014).

582   6.   Massicotte-Laforge, S. & Shi, R. The role of prosody in infants' early syntactic analysis

583   and grammatical categorization. *J. Acoust. Soc. Am.* **138**, EL441–6 (2015).

584   7.   Bion, R. A. H., Benavides-Varela, S. & Nespor, M. Acoustic markers of prominence

585   influence infants' and adults' segmentation of speech sequences. *Lang. Speech* **54**,

586   123–140 (2011).

587   8.   Millotte, S. *et al.* Phrasal prosody constrains word segmentation in French 16-month-

588   olds. *J Port Linguist* **10**, 67–86 (2011).

589   9.   Gervain, J. & Werker, J. F. Prosody cues word order in 7-month-old bilingual infants.

590   *Nat. Commun.* **4**, 1490 (2013).

591   10. Mehler, J. *et al.* A precursor of language acquisition in young infants. *Cognition* **29**, 143–

592   178 (1988).

593   11. Nazzi, T., Bertoncini, J. & Mehler, J. Language discrimination by newborns: toward an

594   understanding of the role of rhythm. *J. Exp. Psychol. Hum. Percept. Perform.* **24**, 756–

595   766 (1998).

596   12. Ghio, M., Cara, C. & Tettamanti, M. The prenatal brain readiness for speech processing:

597   A review on foetal development of auditory and primordial language networks. *Neurosci.*

598   *Biobehav. Rev.* **128**, 709–719 (2021).

599   13. Gervain, J. & Geffen, M. N. Efficient Neural Coding in Auditory and Speech Perception.

600   *Trends Neurosci.* **42**, 56–65 (2019).

601   14. Jardri, R. *et al.* Fetal cortical activation to sound at 33 weeks of gestation: a functional

602   MRI study. *Neuroimage* **42**, 10–18 (2008).

603   15. Chi, J. G., Dooling, E. C. & Gilles, F. H. Gyral development of the human brain. *Ann.*

604   *Neurol.* **1**, 86–93 (1977).

16. Granier-Deferre, C., Ribeiro, A., Jacquet, A.-Y. & Bassereau, S. Near-term fetuses

process temporal features of speech. *Dev. Sci.* **14**, 336–352 (2011).

17. Granier-Deferre, C., Ribeiro, A., Jacquet, A.-Y. & Bassereau, S. Near-term fetuses

process temporal features of speech. *Dev. Sci.* **14**, 336–352 (2011).

18. Griffiths, S. K., Brown, W. S., Gerhardt, K. J., Abrams, R. M. & Morris, R. J. The

perception of speech sounds recorded within the uterus of a pregnant sheep. *The*

Journal of the Acoustical Society of America vol. 96 2055–2063 Preprint at

https://doi.org/10.1121/1.410147 (1994).

19. Querleu, D., Renard, X., Versyp, F., Paris-Delrue, L. & Crèpin, G. Fetal hearing. *Eur. J.*

Obstet. Gynecol. Reprod. Biol. **28**, 191–212 (1988).

20. Richards, D. S., Frentzen, B., Gerhardt, K. J., McCann, M. E. & Abrams, R. M. Sound

levels in the human uterus. *Obstet. Gynecol.* **80**, 186–190 (1992).

21. Jusczyk, P. W., Houston, D. M. & Newsome, M. The beginnings of word segmentation in

english-learning infants. *Cogn. Psychol.* **39**, 159–207 (1999).

22. Ma, W., Golinkoff, R. M., Houston, D. & Hirsh-Pasek, K. Word Learning in Infant- and

Adult-Directed Speech. *Lang. Learn. Dev.* **7**, 185–201 (2011).

23. Kreiner, H. & Eviatar, Z. The missing link in the embodiment of syntax: prosody. *Brain*

Lang. **137**, 91–102 (2014).

24. Langus, A., Marchetto, E., Bion, R. A. H. & Nespor, M. Can prosody be used to discover

hierarchical structure in continuous speech? *J. Mem. Lang.* **66**, 285–306 (2012).

25. Nakamura, C., Arai, M. & Mazuka, R. Immediate use of prosody and context in

predicting a syntactic structure. *Cognition* **125**, 317–323 (2012).

26. Kjelgaard, M. M. & Speer, S. R. Prosodic Facilitation and Interference in the Resolution

of Temporary Syntactic Closure Ambiguity. *J. Mem. Lang.* **40**, 153–194 (1999).

27. Bögels, S., Schriefers, H., Vonk, W., Chwilla, D. J. & Kerkhofs, R. The interplay between

prosody and syntax in sentence processing: the case of subject- and object-control

verbs. *J. Cogn. Neurosci.* **22**, 1036–1053 (2010).

28. Kerkhofs, R., Vonk, W., Schriefers, H. & Chwilla, D. J. Discourse, syntax, and prosody:

the brain reveals an immediate interaction. *J. Cogn. Neurosci.* **19**, 1421–1434 (2007).

29. Pauker, E., Itzhak, I., Baum, S. R. & Steinhauer, K. Effects of cooperating and conflicting

prosody in spoken English garden path sentences: ERP evidence for the boundary

deletion hypothesis. *J. Cogn. Neurosci.* **23**, 2731–2751 (2011).

30. Bögels, S., Schriefers, H., Vonk, W., Chwilla, D. J. & Kerkhofs, R. Processing

consequences of superfluous and missing prosodic breaks in auditory sentence

comprehension. *Neuropsychologia* **51**, 2715–2728 (2013).

31. Honbolygó, F., Török, Á., Bánréti, Z., Hunyadi, L. & Csépe, V. ERP correlates of

prosody and syntax interaction in case of embedded sentences. *J. Neurolinguistics* **37**,

22–33 (2016).

32. Steinhauer, K., Alter, K. & Friederici, A. D. Brain potentials indicate immediate use of

prosodic cues in natural speech processing. *Nat. Neurosci.* **2**, 191–196 (1999).

33. Itzhak, I., Pauker, E., Drury, J. E., Baum, S. R. & Steinhauer, K. Event-related potentials

show online influence of lexical biases on prosodic processing. *Neuroreport* **21**, 8–13

(2010).

34. Glushko, A., Poeppel, D. & Steinhauer, K. Overt and implicit prosody contribute to

neurophysiological responses previously attributed to grammatical processing. *Sci. Rep.*

12, 14759 (2022).

35. Meyer, M., Steinhauer, K., Alter, K., Friederici, A. D. & von Cramon, D. Y. Brain activity

varies with modulation of dynamic pitch variance in sentence melody. *Brain Lang.* **89**,

277–289 (2004).

36. Plante, E., Creusere, M. & Sabin, C. Dissociating sentential prosody from sentence

processing: activation interacts with task demands. *Neuroimage* **17**, 401–410 (2002).

37. Kreitewolf, J., Friederici, A. D. & von Kriegstein, K. Hemispheric lateralization of

linguistic prosody recognition in comparison to speech and speaker recognition.

Neuroimage **102 Pt 2**, 332–344 (2014).

38. Sammler, D., Grosbras, M.-H., Anwander, A., Bestelmeyer, P. E. G. & Belin, P. Dorsal

and Ventral Pathways for Prosody. *Curr. Biol.* **25**, 3079–3085 (2015).

39. Wildgruber, D., Ackermann, H., Kreifelts, B. & Ethofer, T. Cerebral processing of

linguistic and emotional prosody: fMRI studies. *Prog. Brain Res.* **156**, 249–268 (2006).

40. Chien, P.-J., Friederici, A. D., Hartwigsen, G. & Sammler, D. Neural correlates of

intonation and lexical tone in tonal and non-tonal language speakers. *Hum. Brain Mapp.*

41, 1842–1858 (2020).

41. van der Burght, C. L., Goucha, T., Friederici, A. D., Kreitewolf, J. & Hartwigsen, G.

Intonation guides sentence processing in the left inferior frontal gyrus. *Cortex* **117**, 122–

134 (2019).

42. Hagoort, P. Nodes and networks in the neural architecture for language: Broca's region

and beyond. *Curr. Opin. Neurobiol.* **28**, 136–141 (2014).

43. Matchin, W. & Hickok, G. The Cortical Organization of Syntax. *Cereb. Cortex* **30**, 1481–

1498 (2020).

44. Friederici, A. D. *Language in Our Brain: The Origins of a Uniquely Human Capacity*.

(MIT Press, 2017).

45. Chien, P.-J., Friederici, A. D., Hartwigsen, G. & Sammler, D. Neural correlates of

intonation and lexical tone in tonal and non-tonal language speakers. *Hum. Brain Mapp.*

41, 1842–1858 (2020).

46. Luck, S. J. *An Introduction to the Event-Related Potential Technique, second edition*.

(MIT Press, 2014).

47. Nastase, S. A., Goldstein, A. & Hasson, U. Keep it real: rethinking the primacy of

experimental control in cognitive neuroscience. *Neuroimage* **222**, 117254 (2020).

48. Hamilton, L. S. & Huth, A. G. The revolution will not be controlled: natural stimuli in

speech neuroscience. *Lang Cogn Neurosci* **35**, 573–582 (2020).

49. Ivanova, A. A. *et al.* Beyond linear regression: mapping models in cognitive

neuroscience should align with research goals. *arXiv [q-bio.NC]* (2022).

50. Bouton, S., Chambon, V., Golestani, N., Formisano, E. & Giraud, A.-L. Interpretability of

statistical approaches in speech and language neuroscience. *PsyArXiv* (2019).

51. Broderick, M. P., Anderson, A. J. & Lalor, E. C. Semantic Context Enhances the Early

Auditory Encoding of Natural Speech. *J. Neurosci.* **39**, 7564–7575 (2019).

52. de Heer, W. A., Huth, A. G., Griffiths, T. L., Gallant, J. L. & Theunissen, F. E. The

Hierarchical Cortical Organization of Human Speech Processing. *J. Neurosci.* **37**, 6539–

6557 (2017).

53. Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L. Natural

speech reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458

(2016).

54. Pallier, C., Devauchelle, A.-D. & Dehaene, S. Cortical representation of the constituent

structure of sentences. *Proc. Natl. Acad. Sci. U. S. A.* **108**, 2522–2527 (2011).

55. Brennan, J. *et al.* Syntactic structure building in the anterior temporal lobe during natural

story listening. *Brain Lang.* **120**, 163–173 (2012).

56. Brennan, J. R., Dyer, C., Kuncoro, A. & Hale, J. T. Localizing syntactic predictions using

recurrent neural network grammars. *Neuropsychologia* **146**, 107479 (2020).

57. Donhauser, P. W. & Baillet, S. Two Distinct Neural Timescales for Predictive Speech

Processing. *Neuron* **105**, 385–393.e9 (2020).

58. Mesgarani, N., Cheung, C., Johnson, K. & Chang, E. F. Phonetic feature encoding in

human superior temporal gyrus. *Science* **343**, 1006–1010 (2014).

59. Rutten, S., Santoro, R., Hervais-Adelman, A., Formisano, E. & Golestani, N. Cortical

encoding of speech enhances task-relevant acoustic information. *Nat Hum Behav* **3**,

974–987 (2019).

60. Santoro, R. *et al.* Reconstructing the spectrotemporal modulations of real-life sounds

from fMRI response patterns. *Proc. Natl. Acad. Sci. U. S. A.* **114**, 4799–4804 (2017).

61. Tang, C., Hamilton, L. S. & Chang, E. F. Intonational speech prosody encoding in the

human auditory cortex. *Science* **357**, 797–801 (2017).

62. Suni, A., Šimko, J., Aalto, D. & Vainio, M. Hierarchical representation and estimation of

prosody using continuous wavelet transform. *Comput. Speech Lang.* **45**, 123–136

(2017).

63. Liu, Y. *et al.* RoBERTa: A Robustly Optimized BERT Pretraining Approach. *arXiv [cs.CL]*

(2019).

64. Hodari, Z. *et al.* Camp: A Two-Stage Approach to Modelling Prosody in Context. in

ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal

Processing (ICASSP) 6578–6582 (2021).

65. Tyagi, S., Nicolis, M., Rohnke, J., Drugman, T. & Lorenzo-Trueba, J. Dynamic Prosody

Generation for Speech Synthesis using Linguistics-Driven Acoustic Embedding

Selection. *arXiv [cs.CL]* (2019).

66. Tran, T. *et al.* Parsing Speech: a Neural Approach to Integrating Lexical and Acoustic-

Prosodic Information. *Proceedings of the 2018 Conference of the North American*

Chapter of the Association for Computational Linguistics: Human Language

Technologies, Volume 1 (Long Papers) Preprint at https://doi.org/10.18653/v1/n18-1007

(2018).

67. Köhn, A., Baumann, T. & Dörfler, O. An Empirical Analysis of the Correlation of Syntax

and Prosody. *arXiv [cs.CL]* (2018).

68. Bögels, S., Schriefers, H. & Vonk, W. Prosodic Breaks in Sentence Processing

Investigated by Event- Related Potentials. *Language* (2010) doi:10.1111/j.1749-

818X.2011.00291.x.

69. Brown, S. A Joint Prosodic Origin of Language and Music. *Front. Psychol.* **8**, 1894

(2017).

70. Benítez-Burraco, A. & Elvira-García, W. Human self-domestication and the evolution of

prosody. *Lang. Linguist. Compass* **17**, e12485 (2023).

71. Meyer, M., Steinhauer, K., Alter, K., Friederici, A. D. & von Cramon, D. Y. Brain activity

varies with modulation of dynamic pitch variance in sentence melody. *Brain Lang.* **89**,

277–289 (2004).

72. Doherty, C. P., West, W. C., Dilley, L. C., Shattuck-Hufnagel, S. & Caplan, D.

Question/statement judgments: an fMRI study of intonation processing. *Hum. Brain*

Mapp. **23**, 85–98 (2004).

73. Chien, P.-J., Friederici, A. D., Hartwigsen, G. & Sammler, D. Neural correlates of

intonation and lexical tone in tonal and non-tonal language speakers. *Hum. Brain Mapp.*

746  **41**, 1842–1858 (2020).

747 74. Wildgruber, D., Ackermann, H., Kreifelts, B. & Ethofer, T. Cerebral processing of

748   linguistic and emotional prosody: fMRI studies. *Prog. Brain Res.* **156**, 249–268 (2006).

749 75. Friederici, A. D. *Language in Our Brain: The Origins of a Uniquely Human Capacity.*

750   (MIT Press, 2017).

751 76. Matchin, W. & Hickok, G. The Cortical Organization of Syntax. *Cereb. Cortex* **30**, 1481–

752   1498 (2020).

753 77. Hagoort, P. Nodes and networks in the neural architecture for language: Broca's region

754   and beyond. *Curr. Opin. Neurobiol.* **28**, 136–141 (2014).

755 78. van der Burght, C. L., Numssen, O., Schlaak, B., Goucha, T. & Hartwigsen, G.

756   Differential contributions of inferior frontal gyrus subregions to sentence processing

757   guided by intonation. *Hum. Brain Mapp.* **44**, 585–598 (2023).

758 79. Huang, M. X., Mosher, J. C. & Leahy, R. M. A sensor-weighted overlapping-sphere head

759   model and exhaustive head model comparison for MEG. *Phys. Med. Biol.* **44**, 423–440

760   (1999).

761 80. Dale, A. M. *et al.* Dynamic statistical parametric mapping: combining fMRI and MEG for

762   high-resolution imaging of cortical activity. *Neuron* **26**, 55–67 (2000).

763 81. Rousseau, Deléglise & Esteve. TED-LIUM: an Automatic Speech Recognition dedicated

764   corpus. *LREC Int. Conf. Lang. Resour. Eval.* (2014).

765 82. McAuliffe, M., Socolof, M., Mihuc, S., Wagner, M. & Sonderegger, M. Montreal Forced

766   Aligner: Trainable Text-Speech Alignment Using Kaldi. *Interspeech 2017* Preprint at

767   https://doi.org/10.21437/interspeech.2017-1386 (2017).

768 83. Panayotov, V., Chen, G., Povey, D. & Khudanpur, S. Librispeech: An ASR corpus based

769   on public domain audio books. in *2015 IEEE International Conference on Acoustics,*

770   *Speech and Signal Processing (ICASSP)* 5206–5210 (2015).

771 84. Boersma, P. Praat, a system for doing phonetics by computer. *Glot. Int.* **5**, 341–345

772   (2001).

773 85. Nelson, M. J. *et al.* Neurophysiological dynamics of phrase-structure building during

774 sentence processing. *Proc. Natl. Acad. Sci. U. S. A.* **114**, E3669–E3678 (2017).