Comparing a language model and a physics-based approach to modify MHC Class-I immune-visibility for the design of vaccines and therapeutics

Hans-Christof Gasser[*,1]
Diego Oyarzun[1,2]
Ajitha Rajan[*,**,1] (co-directing)
Javier Alfaro[*,**,1,3,4] (co-directing)

[1]School of Informatics, University of Edinburgh, Edinburgh, UK, [2]School of Biological Sciences, University of Edinburgh, Edinburgh, UK, [3]International Centre for Cancer Vaccine Science, University of Gdańsk, Gdańsk, Poland, [4]Department of Biochemistry and Microbiology, University of Victoria, Victoria, British Columbia, Canada
[*]Correspondence to: Informatics Forum, 10 Crichton Street, Edinburgh, EH8 9AB
h.gasser@sms.ed.ac.uk, arajan@ed.ac.uk, javier.alfaro@proteogenomics.ca
[**]co-directing

November 2023

Protein therapeutics already have an arsenal of applications that include disrupting protein interactions, acting as potent vaccines, and replacing genetically deficient proteins. Therapeutics must avoid triggering unwanted immune-responses towards the therapeutic protein or viral vector proteins. In contrast, vaccines must support a robust immune-reaction targeting a broad range of pathogen variants. Therefore, computational methods modifying proteins' immunogenicity without disrupting function are needed. While many components of the immune-system can be involved in a reaction, we focus on Cytotoxic T-lymphocytess (CTLs). These target short peptides presented via the MHC Class I (MHC-I) pathway. To explore the limits of modifying the visibility of those peptides to CTL within the distribution of naturally occurring sequences, we developed a novel machine learning technique, `CAPE-XVAE`. It combines a language model with reinforcement learning to modify a protein's immune-visibility. Our results show that `CAPE-XVAE` effectively modifies the visibility of the HIV Nef protein to CTL. We contrast `CAPE-XVAE` to `CAPE-Packer`, a physics-based method we also developed. Compared to `CAPE-Packer`, the machine learning approach suggests sequences that draw upon local sequence similarities in the training set. This is beneficial for vaccine development, where the synthetic sequence should be representative of the real viral population. Additionally, the language model approach holds promise for preserving both known and unknown functional constraints, which are essential for the immune-modulation of therapeutic proteins. In contrast, `CAPE-Packer`, emphasizes preserving the protein's overall fold and can reach greater extremes of immune-visibility, but falls short of capturing the sequence diversity of viral variants available to learn from.
Source code: https://github.com/hcgasser/CAPE (Tag: `v1.1`)

Keywords: Deimmunization; Vaccines; MHC Class I; Machine Learning; Language Models

Acronyms

AA amino acid
Ab Antibody
AE auto encoder
AR auto-regressive
CAPE Controlled Amplitude of Present Epitopes
CTL Cytotoxic T-lymphocytes
LM language model
MD Molecular Dynamics
MHC major histocompatibility complex

MHC-II MHC Class II
MHC-I MHC Class I
ML machine learning
PWM position weight matrix
RL reinforcement learning
RMSD root mean squared distance
TCR T-cell receptor
VAE Variational Autoencoder

1 Introduction

The recent SARS-CoV-2 pandemic has shown that RNA vaccines are safe, quick to develop and can reliably induce the production of viral proteins by patients. This success has spurred development of more vaccines against other pathogens [1]. Additionally, similar technologies could also be used to stimulate production of other proteins exhibiting a broad range of functions. As of May 4, 2023, the pharmaceutical company Moderna is advancing mRNA therapeutics targeting conditions including autoimmune hepatitis, cancer, and genetic disorders like propionic acidemia and cystic fibrosis [1]. Although an immune response to the SARS-CoV-2 spike protein vaccine was intended, an unintended immune response to a protein designed to provide a beneficial function could compromise therapy effectiveness or, in extreme cases, trigger autoimmune reactions. Hence, cost-efficient computational methods that design proteins to retain their beneficial functions while eliciting the desired immune reaction, are crucial to the success of these therapeutics.

In particular, deimmunization of proteins has garnered attention [2, 3, 4]. So far, deimmunization research has mainly been directed towards immune-reactions by Antibodys (Abs). One approach is to remove Ab surface epitopes. For example, Bootwala et al. demonstrated a significant reduction in Ab binding using computational protein resurfacing [5]. Another strategy, utilized by Yachnin et al. [6], aims to decrease the presentation of MHC Class II (MHC-II) epitopes crucial for B-cell activation.

mRNA therapeutics and vaccines translate into proteins within cells, so flexible computational methods are needed to modify their immune visibility, particularly to the MHC-I pathway - the cell's internal antigen presentation system. Also, in the context of gene therapy, effective MHC-I deimmunizers are essential, as demonstrated by anti-transgene immunity [7, 8] and examples where vector capsid proteins flag hepatocytes for CTL destruction [9, 10] as well as examples of unwanted immune responses to the bacterial-derived CRISPR-Cas9 gene editing machinery [11]. Conversely, vaccines - particularly those targeting rapidly mutating viruses with highly diverse quasi-species like HIV [12] - need to include sequences that expose the immune-system to a wide array of MHC-I immune-visible peptides, mirroring the diversity found in the viral population. This is underscored by Borrow et al. [13] who found evidence for rapid intra-patient evolution of HIV to evade CTL recognition leading to the conclusion that a key aim of HIV-vaccines should be to elicit strong CTL responses against multiple codominant viral epitopes. Nevertheless, immune-reaction to an antigen is a complex process and many aspects are not fully understood yet. Therefore, methods need to be flexible to incorporate the latest developments.

This article introduces the first stage of developing the Controlled Amplitude of Present Epitopes (CAPE) framework, which is focused on managing MHC-I visibility. In this article we make the following novel contributions. (1) We develop `CAPE-XVAE`, a flexible and novel machine learning (ML)-based approach that combines the abilities of Variational Autoencoders (VAEs) and reinforcement learning (RL), to generate MHC-I immune-visibility modified protein sequences. Its flexibility will allow extension to other components of the immune system in the future. (2) We introduce `CAPE-Packer`, a modification of an existing physics-based approach from Yachnin et al. [6], enabling it to reduce or increase MHC-I immune-visibility. And finally, (3) we apply these two novel methods to the HIV Nef protein, comparing their ability to modify immune-visibility while maintaining stability and similarity to naturally occurring sequences. We find that `CAPE-XVAE` effectively modifies the immune-visibility of generated Nef proteins, while maintaining sequence similarity to natural proteins. In contrast `CAPE-Packer` achieves even greater immune-visibility modification, albeit it generates proteins markedly different from naturally occurring ones in sequence space.

Box 1: Terms and concepts

- **Support sequences and natural sequences:** Often applying an analysis to all sequences in the dataset would be prohibitively computationally expensive. To still be able to describe the behavior of all sequences in the dataset, we once randomly selected 300 sequences from the whole dataset and apply the analysis just to those. We refer to these 300 sequences as *support sequences*, while we use *natural sequences* to refer to all sequences in the whole dataset.

- **Closest support sequence:** For a given (query) sequence, *closest support sequence* refers to the support (subject) sequence with the highest pairwise TMscore. If the query sequence is a support sequences, the query sequence is excluded from the potential subject sequences.

Box 2: More terms and concepts

- **MHC-I immune-visibility (also just 'immune-visibility' or 'visibility'):** The human immune-system is comprised of many components. Our study focuses on the MHC-I pathway which is used by CTL to detect destruction targets (see 2.1.1).

  We define the visibility of a protein to be the number of different 8, 9 and 10-mers within a protein sequence, that are predicted to be presented on the cell's surface. Overlapping k-mers are counted separately. Also, if a k-mer is presented by several MHC-I alleles, then each one is independently increasing the visibility number by one. For this study we selected the following common MHC-I alleles to tailor it towards a hypothetical patient: HLA-A*02:01, HLA-A*24:02, HLA-B*07:02, HLA-B*39:01, HLA-C*07:01, HLA-C*16:01. Hence, a sequence's visibility is the same as the sum of peptide rewards (see Subsection 2.3) under the *increased* visibility profile (see inside box below) over all 8 to 10 amino acid long peptides within the sequence.

  Importantly, while being visible/presented on the cell's surface is a necessary condition for a peptide to cause an immune-reaction by CTLs, this is by no means a sufficient one (see 2.1.1).

- **Visibility profiles - *baseline/reduced/increased/inc-nat*:** We are trying to modify how the protein is visible to the immune-system. We use the word *baseline* to refer to generated sequences that were produced by a model without any immune-visibility modification. For `CAPE-XVAE`, this means just using the VAE decoder without any modification step. For `CAPE-Packer` this means using an energy term that does not consider the visibility of the designed sequence. In contrast, we use *reduced/increased* to refer to synthetic sequences with (lower/higher) modified immune-visibility. In *inc-nat* (*increased-natural*) we modified the protein's visibility profile by maximizing naturally occurring visible peptides and minimizing artificial ones. (see also Subsection 2.3)

- **Highly/lowly immune-visible sequences:** All natural or designed sequences that have an immune-visibility of equal or above/below the 99.5%/0.5% percentile of immune-visibility in the natural sequences.
---

2 Material and methods

This section introduces the methods and dataset employed in this paper, with essential terms summarized in `Boxes 1 and 2`. The first subsection delves into the MHC-I pathway. Following that, we present an approximation method designed to accelerate the prediction of peptides presented through this pathway. We then introduce the dataset used in our analysis before explaining how each peptide's reward is calculated. Subsequently, we shed light on the inner workings of our ML approach, `CAPE-XVAE`. This is followed by a description of our physics-based approach, `CAPE-Packer`. Finally, we present a comprehensive overview of our evaluation process.

2.1 The MHC-I pathway and predicting its presented peptides

The MHC-I pathway is key in immune response, presenting cellular peptides to T cells. Detailed exploration of this pathway and its broader immune-system integration are reviewed elsewhere, beyond the scope of this paper. Nevertheless, we provide a concise overview and refer the interested reader to Murphy and Weaver [14] for more in-depth information before introducing how we assessed peptide presentation via this pathway.

2.1.1 The MHC-I pathway

Within most human cells ribosomes constantly produce proteins, while proteasomes constantly degrade them into small fragments, known as peptides. Some of these get transferred into the cell's endoplasmic reticulum, where some bind to MHC-I proteins (typically 8 to 10 amino acids (AAs) long [14, Chapter 4-15]), forming pMHC complexes. These are transported and displayed on the cell's surface for surveillance by CTL.

CTL use a T-cell receptor (TCR) to bind to these visible/presented pMHC. Due to random genetic recombination, the TCRs within a person's population of CTL vary - leading to differences in the specific pMHC they bind to. To prevent auto-immunity, TCR undergo selection in the thymus to be tolerant of the person's own naturally occurring peptides while still binding specifically to foreign peptides. These foreign peptides can originate from viral proteins, cancer proteins, or other intra-cellular pathogens. Additionally, CTL develop from naive CD8 T cells via priming. These T cells circulate the bloodstream visiting lymph nodes, where they transiently bind to antigen-presenting cells (typically dendritic cells). If a naive CD8 T cell encounters its cognate antigenic peptide presented on an antigen-presenting cell and receives co-stimulation [14, Fig. 9.22], the T cell proliferates and its progeny differentiate into CTL. If a CTL detects a foreign peptide on a cell's surface, it initializes the destruction of this cell. [14, Chapter 9]

MHC-I alleles exhibit variation in peptide specificity. To ensure the presentation of a broad range of peptides on the cell surface and make them visible to CTL, evolution has led to the expression of a diverse set of MHC-I proteins across the human population. In fact, three main genes (HLA-A, HLA-B, and HLA-C) are present in humans, allowing each individual to express up to six different MHC-I proteins [14, Chapter 6].

From the above, it becomes evident that *visibility* to CTL of a peptide is a necessary but not a sufficient condition for an immune-reaction. For example, presented self-peptides, as well as foreign peptides for which no matching TCR exists, will not trigger an immune reaction. Additionally, an immune-reaction requires prior activation of the CTL. Therefore, *visibility* and immune-reaction are not the same.

2.1.2 Assessing antigen presentation via MHC Class I

For the estimation of MHC-I immune-visibility, our study employs *netMHCpan-4.1* [15]. This tool represents the latest iteration in a series of MHC-I prediction models dating back to the early 2000s. Based on a given peptide sequence and a specific MHC-I allele, the model produces a score. Higher values indicate greater confidence in the peptide's presentation by the MHC-I protein. The score's reversed rank relative to random peptides, known as *EL-rank*, serves us to assess MHC-I presentation of the peptide. Peptides with an *EL-rank* of below 2% are considered "weak binding" and those below 0.5% are deemed "strong binding" [1].

In our exploration of methods to integrate the immune-visibility constraint into the protein design process, we encountered challenges with an approach suggested by Yachnin et al. [6]. This method involves numerous peptide presentation prediction requests, rendering direct use of *netMHCpan* in `CAPE-Packer` impractical (see Subsection 2.5). To reduce the execution time of the immune modification process in `CAPE-Packer` and `CAPE-XVAE` (while still relying directly on *netMHCpan* during evaluation), we approximated the behavior of *netMHCpan* using a position weight matrix (PWM) based approach.

To construct the PWMs, we initially generated a uniform sample of three million random peptides of lengths 8, 9, and 10 AAs. Subsequently, we employed *netMHCpan* to calculate the *EL-rank* for all considered MHC-I alleles, selecting peptides with an *EL-rank* below 2%. For each position within these peptides, we computed the distribution of AAs, obtaining a PWM for each MHC-I allele and peptide length. Next, we scored all the random peptides using these PWMs. This involved summing up the logarithmic probabilities assigned by the PWM to each AAs at their corresponding positions within the peptide. The scores were then used to establish rankings for peptides, equivalent to the *EL-rank*.

2.2 Protein dataset

We applied our protein design methods to the HIV Nef protein. HIV's urgent need for effective vaccines as well as Nef's relatively short sequence length, slightly above 200 AAs, and the availability of approximately 25 thousand different sequence examples make it a suitable test case. On 6 June 2023, we retrieved unaligned HIV Nef sequences from the *Los Alamos National Laboratory* HIV Sequence Database [2]. To avoid using dysfunctional sequences or sequences with sequencing errors, we only considered sequences between 200 and 220 AAs length. Many sequences occur multiple times and we assigned proportionally higher weights during `CAPE-XVAE` training to those. While 'X'-containing sequences (unknown AA, absent in *complete sequences*) were retained for training, they were excluded from the evaluation process. We randomly partitioned our dataset into the following subsets:

Subset	Number of Sequences	Complete Sequences
Train	24,026	21,378
Validation	1,334	1,189
Test	1,336	1,189

Table 1: Number of unique sequences in dataset splits

2.3 Peptide reward

As the protein is designed, newly generated peptides receive a reward depending on the targeted immune-visibility profile (see `Box2`). It is also influenced by how many of the considered MHC-I alleles present the peptide via the MHC-I pathway (M) and whether the peptide is present in the *natural sequences* or not (see `Box1`). The reward for a given peptide is computed as the product of the corresponding value in **Table 2** and M. To prediction of M is done using the PWM classifier for MHC-I presentation (see Subsection 2.1.2).

---

[1]https://services.healthtech.dtu.dk/services/NetMHCpan-4.1/
[2]https://www.hiv.lanl.gov/components/sequence/HIV/search/search.html

	baseline	reduced	increased	inc-nat
natural	0	-1	1	1
artificial	0	-1	1	-1

Table 2: **Rewards for a single peptide presentation:** Rows signify if a peptide is present in the *natural sequences* or not. Columns represent the immune-visibility profile we aim to modify towards.

2.4   CAPE-XVAE

This model is a VAE (see 2.4.1). During the VAE-training stage (see 2.4.2) its encoder is trained to map a protein sequence into a low dimensional latent space, based on which its auto-regressive (AR) decoder aims to reconstruct the protein sequence. Afterwards, the immune-visibility profile modification procedure (see 2.4.3) employs RL to modify the protein's immune-visibility by updating its latent space representation in the direction of the desired MHC-I immune-visibility profile (see Box2). The improved latent space representation can then be converted to a sequence by the decoder.

Similar to Dauparas et al. [16] we train the decoder to generate sequences in any ordering - allowing certain parts of the sequence to be fixed upfront. This as well as the ability to adjust the modification procedure to a wide range of immune-visibility profiles, makes CAPE-XVAE a particularly flexible approach for protein design.

After presenting CAPE-XVAE's architecture, we delve into its VAE training process. Finally, the immune-visibility modification procedure is outlined.

Figure 1: **Overview of the CAPE-XVAE model architecture, training and immune-visibility modification process.** (a) Sketch of the CAPE-XVAE architecture. On the left side is the encoder, in the middle the latent space and on the right side the decoder. More details can be found in the Supplement **S.1**. (b) Shows the evolution of the KL-divergence term weight during CAPE-XVAE training. (c) Depicts the steps followed during the immune-visibility modification process

2.4.1   Architecture

CAPE-XVAE is based on the VAE architecture [17] and, therefore, comprises the three main components listed below: an encoder, a latent space, and a decoder (see **Figure 1a**). The encoder and the decoder were realized as transformers [18]. More details on the various sub-components can be found in the Supplement **S.1.2**.

- **Encoder:** CAPE-XVAE's encoder consists of an *Embedding Layer*, an *Encoder Stack*, a *Cross Attention Block* and two linear transformations embedding the stack's output into latent space. Along with a learnt positional encoding, each AA in the input protein sequence x is first encoded as a d dimensional vector using a learnt embedding layer. The *Encoder Stack* (comprising multiple *Self Attention Blocks*) processes these into a same length sequence of contextually encoded vectors.

  To create an information bottleneck, first a *Cross Attention Block* converts this sequence into set of $L < N$ (currently $L = 1$) vectors (each of dimension d). Subsequently, two linear transformations further compress each latent vector

to $l < d$ dimensions. The first transformation (μ) generates a mean vector for the latent's conditional distribution $p(z|x)$, while the second one (σ) produces its log variance vector.

- **Latent Space:** To generate sequences, first a vector z needs to be sampled in latent space. Sampling from the latent's conditional distribution $p(z|x)$ is appropriate when z should represent a sequence similar to x (e.g. during training). In contrast, when we are only interested in generating any sequence similar to the training set, sampling from the unconditional distribution $p(z)$ is possible. For the loss function, we assume $p(z)$ to be a standard normal distribution. However, we acknowledge that this assumption may not accurately represent the distribution of natural sequences in latent space. So, when generating new *baseline* (see `Box2`) examples, we calculate the mean and covariance matrix of the latent vectors of the training set examples and sample from a Normal distribution with those parameters.

- **Decoder:** As input, it receives the latent vector, and the AAs in the sequences sampled so far (or the whole sequence x during training). It comprises an embedding layer for the AA sequence, a transformer decoder stack (see Supplement **S.1.2**) and a head for AA prediction. We embed each sequence element with a learnt token embedding, a learnt positional embedding and a learnt next position embedding. The next-position embedding allows the prediction of protein sequences in arbitrary order (not only in N to C direction). Then, the decoder stack consists of multiple cross-attention blocks. These blocks can attend to the latent vector z and already generated tokens but, importantly for training, they cannot attend to not yet generated ones. The sampling is initialized with a start/stop token in the AA sequence. For training this is followed by the ground truth tokens, while during inference the predicted tokens are used (dashed line **Figure 1a**).

2.4.2 VAE-training stage

Training a VAE in conjunction with an AR decoder is challenging, due to "KL-vanishing" (Supplement **S.1**). To address this, we adopted the approach proposed by Li et al.[19] (see Supplement **S.1.1**). So, our training process (see **Figure 1b**) follows the steps below:

1. **Auto encoder (AE) training:** We trained `CAPE-XVAE` like an AE for 500 epochs (KL divergence weight β in VAE loss function is zero). This focuses training solely on reconstructing the input sequence resulting in very meaningful latent representations.

2. **Reset the decoder**: Afterwards, the decoder is reset to its initialization. This counters the risk of the decoder learning faster than the encoder.

3. **Transition to VAE training:** Over the next 250 epochs the KL-divergence weight in the loss function is increased linearly until it reaches one.

4. **VAE training:** Then we continue training the model for an additional 750 epochs. This phase optimizes the full VAE objective with free bits. We fixed the free bits parameter λ as one.

To further increase the decoder's reliance on the latent variable, we train the decoder to sample the protein sequence in random permutations of the ordering - not just N-C direction. This means that, while the normal next token prediction task is: here are amino acids 1, 2, 3 and 4 - please give me amino acid 5, we train the model on the following task: here are amino acids 22, 11, 59 and 37 - please give me amino acid 17. Further details about the hyper-parameter search, the eventually obtained hyper-parameters and the training procedure can be found in the Supplement **S.1.4**.

2.4.3 Immune-visibility profile modification procedure

We modify the immune-visibility profile of sampled proteins by combining the capabilities of VAEs and RL techniques. VAEs excel at assigning reasonable protein sequences to probable points in a latent space. However, as seen in [20], directly sampling from this latent space typically leads to only marginal reductions in immune-visibility. Therefore, we would like to relay immune-visibility information through the decoder to the latent space. Since back-propagation through the decoder's discrete output is not directly feasible, we formulate our task as a RL problem (see Supplement **S.1.3**). Unlike in a typical RL setting, we do not modify the parameters of `CAPE-XVAE`. Instead, we adjust the latent vector to better align with our desired immune-visibility profile (see `Box2`). Given that, in theory, all probable vectors in latent space should be mapped to plausible proteins by the decoder, we only need to ensure that the modification does not shift the latent vector to an improbable region of the latent space.

We formulate the RL problem as follows: `CAPE-XVAE`'s decoder represents the agent. The state is the protein sequence produced so far. `CAPE-XVAE`'s next token prediction represents the policy. We also define an immune-visibility dependent reward function (see 'Episode' below). The episode ends when the decoder generates a stop token. Overall, the modification process follows the following steps (**Figure 1c**):

1. **Initialization:** First a random *natural sequence x* (see `Box1`) is sampled from the dataset and a conditional latent distribution $p(z|x) = \mathcal{N}(z, \exp(\sigma))$ obtained from the encoder. From this an initial latent vector $z^{(0)} \sim \mathcal{N}(z, \exp(\sigma))$ is sampled. To ensure that the modified latent variable stays in a likely area of the latent space, we force it to be within a certain range $m \cdot \sigma$ around $z^{(0)}$. To do so, we use an auxiliary latent vector $w^{(j)}$ in an auxiliary latent space W, which is mapped into the sphere with radius $m \cdot \sigma$ in latent space surrounding $z^{(0)}$. We use Manhattan distance and m is currently set to 2.

2. **Episode:** At the beginning of each episode j the current auxiliary $w^{(j)}$ is converted to a latent variable $z^{(j)}$, which remains constant throughout the episode. The decoder uses this to sample 64 AA sequences in parallel in N-C direction. The temperature used for this is linearly decreased from 1.2 to 0.1 over the modification phase. The gradient of the log-probability of the sampled AA with respect to the auxiliary latent variables is calculated and saved. Also, for each added AA the reward function is called and its result saved as this step's reward. In addition to the current state, e.g. MGGKWSKSSSEAKWPAVRERMRRTEPADG), and the current action (e.g. V) the **reward function** receives the selected MHC-I alleles as input. As most MHC-I epitopes have length 8, 9 or 10 AAs, only the terminal 8-, 9- and 10-mers of the combined sequence (e.g. MRRTEPADGV, RRTEPADGV, RTEPADGV) are examined. The reward at the corresponding step in the trajectory is then the sum of the peptide rewards (see Subsection 2.3) for all the terminal k-mers. This penalizes or rewards presented peptides as soon as they are fully sampled - but not at all before.

3. **Updating auxiliary latent variables:** At the end of each episode j, the auxiliary latent variable $w^{(j)}$ is updated to $w^{(j+1)}$ using the REINFORCE algorithm (see Supplement **S.1.3**). As baseline, we use the average across the batch of the future rewards for each step. Then the algorithm goes back to step 2 until 100 updating steps have been completed.

2.5 CAPE-Packer

The underlying physics-based idea is, that proteins will fold into their energy minimizing state. So, `CAPE-Packer` searches for the energy minimizing sequence for a fixed 3D structure. By considering immune-visibility in the energy function (score function), the search process can be steered towards a desired immune-visibility profile. The implementation of `CAPE-Packer` builds upon the framework developed by Yachnin et al. [6] utilizing the *Rosetta Packer* [21, 22] (see 2.5.1) for protein design. Yachnin et al. modify Rosetta's score function to discourage the *Rosetta Packer* protein design algorithm from incorporating MHC-II epitopes.

2.5.1 Rosetta software for macro-molecular modeling and Rosetta Packer

Rosetta is a versatile software suite for modeling and analyzing protein structures. Next to others, it comprises algorithms dealing with structure prediction, docking and membrane proteins [3]. It has been developed for more than two decades and is extensively used in laboratories worldwide [23]. At its core lies the score (energy) function. This is the weighted sum of terms describing van der Waals energies, hydrogen bonds, electrostatics, disulfide bonds, residue solvation, backbone torsion angles, sidechain rotamer energies, and an average unfolded state reference energy [23].

Rosetta also features a key algorithm called the *Packer*, serving as a side-chain optimization tool. It identifies score function minimizing rotamers for a given sequence and fixed backbone structure (3D structure) [24]. Additionally, the *Packer* can be used for sequence design by considering different side-chain AA identities. In fact, this is its standard behavior and the *Packer* designs at every position, allowing for all 20 standard amino acid rotamers (position dependent subsets of eligible rotamers can be specified). The space of possible rotamer combinations expands rapidly, making enumeration infeasible. Therefore, Monte Carlo simulation is utilized. Starting from a random initialization, random changes are made to the rotamers. If the change decreases the score, it is always accepted. Conversely, if it increases the score, acceptance is stochastic with a probability that decreases with the energy [24].

2.5.2 Rosetta Packer adaptations for immune-visibility modifications

Yachnin et al. [6] have suggested an additional term for the score function, that takes into account the number of peptides in the protein that get presented on the cell's surface. In their case, they used MHC-II. We adapted their tool for MHC-I. The method only considers 9-mer peptides and out of the box it is only implemented using a PWM approach as well as a lookup database. While they mention that they have experimented with a tensorflow based presentation predictor, no implementation of this is known to us. In fact Mulligan [24] state that "In order to be compatible with the *Packer*, an energy term must either be residue-level pairwise-decomposable, or must otherwise be very fast to compute and update as rotamer substitutions are considered". Therefore, we think the reason for the lack of a more advanced predictor backbone is, that the *Rosetta Packer* requires many, many score function evaluations - and, hence, peptide presentation evaluations.

---

[3] https://new.rosettacommons.org/docs/latest/application_documentation/Application-Documentation

For a short 203 amino acid long Nef sequence, we counted roughly 42 million peptide evaluation requests. This must be multiplied by the number of considered major histocompatibility complex (MHC) alleles to arrive at the actual number of predictor calls. Using one of the modern and larger MHC-I presentation prediction state-of-the-art models - like *MHCflurry 2.0* [25] or *netMHCpan 4.1* [15] - is, therefore, very time intensive.

We implemented a new Rosetta class `MHCEpitopePredictorClient` that inherits from `MHCEpitopePredictor` and receives 9-mer evaluation requests from Yachnin et al.'s framework. Our client then forwards these peptides together with the MHC-I alleles and the profile to modify towards to a server that we also implemented. This server returns the peptide's reward (see Subsection 2.3). This number is multiplied by -1 and then integrated into the energy function used by the *Rosetta Packer* that ultimately designs the protein.

Being based on the *Rosetta Packer*, CAPE-Packer requires a 3D structure of the protein as input. *AlphaFold* generated 3D structures of the *support* sequences (see Box1) were used for this. We design at every AA position in the sequence, without any restrictions to admissible AAs.

2.6 Evaluation

We assessed the generated sequences based on three criteria: immune-visibility, similarity to natural sequences and stability. Each criterion is detailed below. It is noteworthy that, in the absence of experimentally determined 3D structures, we employed *AlphaFold* [26] to predict the necessary 3D structures as needed.

2.6.1 Visibility

To assess how MHC-I visible (see Box2) the proteins are to CTL, we used *netMHCpan-4.1* [15]. We used the same MHC-I alleles during the evaluation step as we had used for the modification process. The visibility number is calculated as outlined in Box2.

2.6.2 Similarity

We assess the similarity of the generated sequences to natural ones with regards to three criteria: local-, structural- and functional similarity.

- **Local similarity** is used to demonstrate the extent to which local sequence patterns in protein design are captured. To assess whether there is a similarity in parts of the sequences to the natural sequences (see Box1), we checked short sub-sequences of length k (k-mers) in the sequence against all k-mers occurring in the natural sequences. The percentage that is also present in the natural sequences we define as the *k-mer similarity*. 9-mer similarity is of particular interest since most presented peptides have 9 AA length, making it especially relevant for vaccine design, where we try to design sequences that more broadly capture epitopes across variants of a protein. To assess the overlap between k-mers we define the following metrics: (a) the *k-mer recall* of a query sequence (a generated or natural sequence) wrt a subject sequence (a natural sequence) is the percentage of k-mers in the subject sequence that are also present in the query sequence; (b) the *k-mer precision* of a query sequence wrt a subject sequence is the percentage of k-mers in the query sequence that are also present in the subject sequence; (c) for a specific k-mer, *k-mer precision* is defined as the percentage of the natural sequences that include this k-mer.

- **Structural similarity** is used to compare the overall fold of the predicted structure of the designed sequence to that of its *closest support sequence* (see Box1). The TMscore between the two structures was calculated using *TMalign* [27]. The TMscore ranges between zero and one. A score of one signifies a perfect match while scores below 0.2 are associated with randomly chosen unrelated proteins. Scores higher than 0.5 assume generally the same fold in SCOP/CATH [4].

- **Functional similarity** is used to determine whether the designed protein is likely to preserve function. Function is assessed via the ability of a classifier to distinguish the generated from the support sequences. In a first step, we used the GO term predictor of Boadu, Cao, and Cheng [28] to predict the scores of `11,156` molecular function GO categories for each of our generated sequences as well as the support sequences. After normalization, we performed a PCA keeping the first `19` components which cover `99%` of the observed variance. Based on this dataset we then trained a Gaussian Naive Bayes classifier (called *GO based Sequence Pack Classifier*) to distinguish between `8` potential sequence origins: support, CAPE-XVAE-*baseline/reduced/increased/inc-nat*, CAPE-Packer-*baseline/reduced/increased*. As we do not want to perform prediction but simply want to assess the classifier's ability to distinguish between the classes, no holdout dataset was used.

---

[4]https://seq2fun.dcmb.med.umich.edu/TM-align/

2.6.3 Stability

To assess the stability of our generated protein sequences we select a subset of these and the support sequences and run a Molecular Dynamics (MD) simulation on this. We then calculate the maximum root mean squared distance (RMSD) (based only on CA-atoms) between the confirmations observed during the simulation and the original *AlphaFold* prediction. We use OpenMM to run the MD simulation for 2 microseconds (2 femtoseconds step-size) at a temperature of 25 degrees Celsius using the amber99sb force field and an implicit solvent model (amber99_obc). Positions were reported every 4 picoseconds. Due to the high computational requirements, we only performed this analysis on a sub-sample of sequences.

2.7 2D sequence space visualizations

We used t-SNE to visualize the distribution of sequences in two-dimensional space. First, we construct a 300-dimensional representation for each sequence. Each dimension represents the dissimilarity between the sequence and one of the *support sequences* (see Box1). We compute this dissimilarity based on the pairwise alignment score of the sequence with the *support sequence*. Gotoh global alignment algorithm [29] as implemented by the biopython [30] PairwiseAligner (using BLOSUM62, open gap score of -20 and extend gap score of -10) was used for this. The dissimilarity is then defined as the difference between the alignment score of the sequence with itself and the alignment score of the sequence with the *support sequence*. To further reduce the dimension of these vectors to only two, we use t-SNE with a perplexity of 30 and running for 500 iterations. We have observed similar results for a broad range of perplexity numbers.

3 Results and discussion

In this section, we present the outcomes of the experiments conducted using `CAPE-XVAE` and `CAPE-Packer` for modifying immune-visibility concerning six common MHC-I alleles from a hypothetical patient: HLA-A*02:01, HLA-A*24:02, HLA-B*07:02, HLA-B*39:01, HLA-C*07:01, HLA-C*16:01. Evaluation criteria include MHC-I immune-visibility (see `Box2`), similarity to natural sequences, and the stability of the generated proteins. For each *visibility profile* (see `Box2`), 100 `CAPE-XVAE` and 300 `CAPE-Packer` sequences were generated.

3.1 Differential distribution in sequence space: `CAPE-XVAE` sequences distribute more naturally than `CAPE-Packer` ones

We first explored the landscape of naturally occurring and `CAPE-XVAE` and `CAPE-Packer` generated sequences (**Figure 2**, see Subsection 2.7). Notably, the baseline sequences (see `Box2`) produced by `CAPE-XVAE` are dispersed across the natural sequence space in **Figure 2ab**, showing no aggregation in any particular region. However, The modification step removes them from several areas of the sequence space and moves some even outside the range occupied by natural sequences. This is not observed for `CAPE-XVAE`-*inc-nat* sequences.

Starkly, the sequences generated by `CAPE-Packer` all aggregate outside the natural background distribution of sequences (**Figure 2bdf**). Despite appearing close in t-SNE plots (**Figure 2a-f**), which is a cluster-preserving but not distance-preserving dimension reduction technique, the sequences outside the natural background distribution are highly dissimilar from each other. In fact, **Figure 2h** illustrates that the `CAPE-Packer` baseline sequences are markedly different from all other sets and even differ from each other, while support sequences are similar to themselves (**Figure 2g**).

3.2 `CAPE-XVAE` designs incorporate many natural peptides

In **Figure 3** we compare the generated sequences to naturally occurring ones with respect to immune-visibility (**Figure 3a**, see `Box2`), local similarity (**Figure 3b-e**) and structural similarity (**Figure 3f**, see 2.6.2). These results indicate that `CAPE-XVAE` and `CAPE-Packer` are effective in altering MHC-I immune-visibility (**Figure 3a**, **Table 3**) while maintaining structural similarity.

In **Figure 3a** we see that `CAPE-Packer` can produce extremely immune-visibility modified sequences. `CAPE-Packer` is only cognizant of protein fold, without access to the natural grammar of protein function. It seems unlikely, that longer natural peptides are randomly sampled during *Rosetta Packer's* Monte Carlo simulation process (see Subsection 2.5), preventing it from incorporating those (**Figure 3b**) even when rewarded - like in the case of `CAPE-Packer`-*inc-nat*. This limits `CAPE-Packer`'s usefulness in vaccine design. In fact, `CAPE-Packer`-*inc-nat* is effectively turned into `CAPE-Packer`-*reduced* and will, therefore, be ignored from here on. With regards to `CAPE-Packer`-*reduced*, Yachnin et al. [6, Figure 2b] observed a slightly higher reduction in MHC-II visibility for de-immunizing human erythropoietin when using the same weighting of the immune-visibility term in the score function as us (see 2.5). With regards to structural similarity, **Figure 3f** shows that, despite their unnatural looking sequences, there are `CAPE-Packer` proteins with high TMscores.

In comparison, `CAPE-XVAE` sequences tend to be less immune-visibility modified (**Figure 3a**). The incorporation of artificial visible peptides enables `CAPE-XVAE`-*increased* to achieve higher visibility than `CAPE-XVAE`-*inc-nat*. **Figure 3b** demonstrates that nudging `CAPE-XVAE`-*inc-nat* to only incorporate natural visible peptides also seems to cause it to incorporate more of the natural k-mers in general.

The analysis of k-mer similarity for *highly* and *lowly immune-visible* (see `Box2`) `CAPE-XVAE` generated sequences reveals that, even within strongly modified sequences, many exhibit high k-mer similarity to natural sequences (**Figure 3c-e**). In particular `CAPE-XVAE`-*inc-nat* designed sequences demonstrate high values. This conservative behavior of `CAPE-XVAE`-*inc-nat* may be beneficial in vaccine design, which might benefit from representative sequences that sample the breadth of potential MHC-I epitopes (visible 8, 9 and 10-mers) observed in the pathogen. Even for generated sequences with reduced visibility, remaining close to natural proteins in sequence space may increase the chances that complex nuances of protein function are retained in the synthetic sequence.

The structural similarity of `CAPE-XVAE` designs is more dispersed than for `CAPE-Packer` designs (**Figure 3f**). Very interestingly, `CAPE-XVAE`-*inc-nat* designs tend boast higher TMscores than `CAPE-XVAE`-*baseline* ones. Applying some form of RL inspired latent space search might, therefore, be beneficial in the protein design process of VAE approaches in general.

mean visibility	baseline	reduced	increased	inc-nat
Support	87			
`CAPE-XVAE`	86	52	146	96
`CAPE-Packer`	71	41	286	42

Table 3: **Mean Visibility:** Rows represent the sequence sources and columns the modification profile (see `Box2`)

Figure 2: **Differential distribution of CAPE-XVAE and CAPE-Packer sequences in natural sequence space**. The density of the natural sequences used to train the models is depicted pink in the background. (a,b) The dark red/blue crosses correspond to the sampled sequences obtained through CAPE-XVAE/CAPE-Packer without modification process (baseline). (c,d) Show the reduced immune-visibility results. The red/blue crosses are the finally obtained CAPE-XVAE-*reduced*/CAPE-Packer-*reduced* sequences. (e,f) Here increased and increased-natural immune-visibility results are displayed. CAPE-XVAE designs are in orange and CAPE-Packer ones in blue. The light/dark crosses show the finally obtained *inc-nat*/*increased* sequences. (g,h) The distribution of the average dissimilarity to the 300 support sequences (g, see Box1) as well as to the CAPE-Packer-*baseline* sequences (h). Colors correspond to the other plots

3.3 There are tradeoffs between modifying immune-visibility and maintaining local and structural similarity

Modifying immune-visibility comes at a cost: the more the sequences diverge, the more they lose local similarities to the training set, though their stability remains unaffected. Figure 4 demonstrates, that the further we move away from the data distribution, the less similar the generated sequences become at the peptide length pertinent to antigen presentation (9-mers). Stability does not seem to be affected as assessed using a sub-sample of RMSDs from computationally expensive MD simulations. Despite this trade-off, we find among `CAPE-XVAE` designs many that contain significant 9-mer similarity even with high visibility. In contrast, 9-mer similarity is not present for any of the `CAPE-Packer` generated sequences. For `CAPE-XVAE`, the proportion of high TMscore (above 0.8) proteins generated decreases with distance to the natural visibility range, while this seems not to be the case with `CAPE-Packer`.

3.4 Distinguishing between designed and natural sequences is difficult based on predicted function

We explored whether `CAPE-XVAE` and `CAPE-Packer` designs are likely to retain natural functionality (see *Functional similarity* 2.6.2). For each sequence we first predicted the scores for various molecular functions. This long vector representation for each sequence was reduced by principal components analysis. The first two components **Figure 5** (explaining 68% of variance) visualize the challenge posed to distinguish many of the generated sequences from the support sequences. Certainly, many `CAPE-XVAE` generated sequences would be challenging to distinguish this way from natural sequences.

We then trained a *GO based Sequence Pack Classifier* (Subsection 2.6.2) using the first 19 principal components covering 99% of variance. This classifier also struggles to distinguish between the various sources as demonstrated in the confusion matrix (**Table 4**). `CAPE-Packer` sequences are easier to distinguish from natural sequences than `CAPE-XVAE` generated sequences where only 60% of support sequences are correctly identified as support sequences, while it considers 28% of them to be `CAPE-XVAE`-*baseline* sequences. It also classifies 28% of `CAPE-XVAE`-*baseline* as well as many `CAPE-XVAE` modified sequences as support sequences. In fact, a third of the `CAPE-XVAE`-*inc-nat* sequences are classified as natural.

It appears that while as a whole there are differences in predicted function between natural and generated sequences. More importantly, a considerable proportion of the proposed `CAPE-XVAE` sequences closely resemble natural ones in terms of predicted molecular function. In practical applications, these sequences may be more desirable to advance.

[%]			support	CAPE XVAE baseline	CAPE XVAE reduced	CAPE XVAE increased	CAPE XVAE inc-nat	CAPE Packer baseline	CAPE Packer reduced	CAPE Packer increased
support			60	28	1	1	4	0	5	1
CAPE XVAE		baseline	28	47	11	8	5	0	0	1
		reduced	16	21	51	5	1	1	4	1
		increased	13	39	13	20	6	0	2	7
		inc-nat	33	36	10	4	13	2	1	1
CAPE Packer		baseline	7	5	5	5	0	52	16	9
		reduced	4	8	8	4	0	37	26	14
		increased	0	3	1	11	0	7	3	74

Table 4: **Confusion matrix:** The rows signify the actual sequence origin, while the columns their predicted one

Figure 3: `CAPE-XVAE` **Alters MHC Class I immune-visibility while maintaining natural sub-sequence characteristics.** (a) **Visibility:** Shows the distribution of the visibility of the various sequence sets. The visibility is calculated equivalently to how the *reward function* is calculated for the *increased* modification profile (See Subsection 2.4.3). The dashed pink line signifies the mean of the natural sequences. (b) **K-mer Similarity:** Dependent on k-mer length, this chart shows the average proportion of k-mers with that length in the sequences that can also be found in the natural sequence data. One means that all k-mers can be found in the data and zero means that none of the k-mers can be found in the data. (c-e) Boxplots show the k-mer length dependent distribution of k-mer similarity for the `CAPE-XVAE` modified sequences that are either in the bottom (*reduced*) (c) or top (d,e) 0.5 percentile (*increased*, *inc-nat*) of natural sequences. (f) Shows the distribution of TM Score as calculated by *TMalign* [27] between the sequences and their *closest natural sequence*. Color scheme continues from **Figure 2**.

Figure 4: **Assessing similarity and stability dynamics in protein design: A comparative study of visibility-dependent trends in CAPE-XVAE and CAPE-Packer generated sequences.** In each row of this chart, we show how the natural data sequences compare to `CAPE-XVAE` and `CAPE-Packer` generated sequences with respect to one of the following criteria: 9-mer similarity, TM Score and maximum RMSD in an MD simulation. Each dot in the left column represents a single sequence - the same color coding as in Figure 2 applies. The x-axis shows the immune-visibility. The three boxplots per row on the right display the distribution within the compared values for the support as well as the two model generated sequences. The horizontal boxplot on the bottom shows the distribution of visibility within the data.

Figure 5: **Many designed sequences are hard to distinguish from support sequences based on molecular function GO term predictors**. Each of the six plots shows the first two principal components used to train the *GO based Sequence Pack Classifier* (see Subsection 2.6.2). The figure compares in two lines the results for CAPE-XVAE and CAPE-Packer designed sequences (as colored crosses) to always the same support sequences (blue). Each column depicts a different visibility modification profile.

3.5   CAPE-XVAE-*inc-nat* designs tend to have high mean recall and precision

While the intricacies of vaccine design are best managed by vaccinologists with the capacity to experimentally test various strategies, CAPE-XVAE offers a tool to suggest chimeric sequences capable of exposing the immune-system to a representative set of epitopes, potentially enhancing population-wide protection. As CAPE-XVAE proposes similar sequences to natural ones, we were interested in understanding how diversely potential epitopes (k-mers predicted to be immune-visible) were sampled from the natural sequences. **Figure 6** shows how the natural sequences compare to CAPE-XVAE-*inc-nat* designed sequences with respect to how well they recall naturally occurring visible peptides. First, we observe that even the sequences with the highest recalls in expectation include a third of the visible peptides of a randomly chosen natural sequence. Furthermore, we find that although the highest recall value can still be found in naturally occurring sequences, the set of designed ones has a significantly higher average mean recall as determined by a two-sided t-test. Interestingly, for highly visible sequences, this is even more pronounced. In conclusion, we believe proteins designed using language model (LM) can be valuable constituents of vaccines due to their ability to tap into the array of natural viral variant epitopes - even for less common ones.

Figure 6: **Average recall and precision of natural and `CAPE-XVAE`-*inc-nat* designed sequences**. Each dot in the scatterplots represents a natural or designed sequence. Its x-coordinate shows the sequences average precision over all natural sequences, while its y-coordinate depicts the sequences average recall over all natural sequences (8-, 9- and 10-mers). The boxplots on the right and bottom depict the distributions of average recall and precision for the two sources. The blue p-values are the t-test p values for the null hypothesis that the mean recalls of natural and designed sequences are the same. While plot (a) depicts the situation considering all sequences, (b) is restricted to highly immune-visible sequences (see `Box2`)

    Figure 7 then explores the ability of the highest mean recall `CAPE-XVAE`-*inc-nat* sequence with a TMscore of above 0.95 to capture the naturally occurring k-mer and epitope diversity. We find that all visible 9-mers in the `CAPE-XVAE` designed sequence can indeed be found in the natural sequences (**Figure 7b**). Only 3 of the visible 9-mers (red boxes in **Figure 7a**) were present in less than 0.1% of the natural sequences (**Figure 7b**). In contrast, six of these were present in more than 50% of all natural sequences. Finally, **Figure 7c** shows the distribution of the visible 8, 9 and 10-mer recall. We find that only a few sequences have less than 10% of their visible peptides being present in the designed sequence.

Figure 7: **Language models in vaccine design: borrowing from the diversity of existing protein variants**. `CAPE-XVAE` supports the design of vaccines that contain real epitopes existing across variants of a virus. This figure shows an epitope map of the highest mean recall `CAPE-XVAE`-*inc-nat* designed sequence (see **Figure 6**). Its predicted visibility is 103 and its mean recall 31%. The *GO based Sequence Pack Classifier* predicts it to be a *support* sequence. We investigate where each epitope is derived from within the natural distribution of input sequences. (a) We present 9-mer peptides in the designed Nef protein sequence using a sliding window approach advancing 1 amino acid at a time. The N-Terminal 9-mer is top left progressing one amino acid at a time to the C-Terminal 9-mer on the bottom right. The colors signify how often these 9-mers occur among the natural sequences (see *k-mer precision* in 2.6.2). A red box signifies that this 9-mer is predicted to be presented by at least one MHC allele (a visible 9-mer). (b) The labels of the stacked bar chart are the number of visible 9-mers [red boxes in (a)] in a precision category (signifying the percentage of natural sequences that contain this visible 9-mer). (c) For all natural sequences we identify the visible 8-, 9- and 10-mers and calculate the percentage of those present in the designed sequence. The histogram shows the distribution of this number over all natural sequences (see *k-mer recall* in 2.6.2).

3.6   Limitations

The results presented are limited by several factors. First, we are heavily reliant on the state-of-the-art *AlphaFold* folding prediction model to produce accurate structures. The assessment of structural and functional similarity of the designed sequences to naturally occurring ones relies on these. *AlphaFold* was trained on naturally occurring sequences - in particular for `CAPE-Packer` designs, which are very divergent sequences, it is questionable whether predicted structures will remain accurate - and if they even were able to fold into those.

Next, we are using a GO term predictor to assess functional similarity. On occasions, even a single mutated amino acid can lead to a loss of function. GO term predictors that are trained to predict the function of working proteins may miss those subtle differences. However, we are not aware of any ML method in protein design that performs a major modification to a protein and still proposes a functional protein in each attempt. In reality, the protein design process involves many filtering steps. The *GO based Sequence Pack Classifier* can be seen as another way to filter sequences. The difficulty of assessing designs is a challenge for the whole field and ultimately only confirmation in the wet lab on the output of tools like ours will deliver definite results.

Finally, our model does not directly control immune-reaction by CTLs, but only visibility to CTLs (see 2.1.1). Furthermore, other immune-system components (e.g. Abs) were not considered.

4   Conclusions

Designed protein-based medicines hold transformative potential for healthcare, serving as potent vaccines and therapeutics for various diseases. Ensuring these medicines do not inadvertently trigger an immune response, except when intended (as with vaccines), is crucial. This paper focuses on the design of proteins with controlled visibility to CTLs via the MHC Class I pathway.

We introduce `CAPE-XVAE`, a latent space controlled language model trained on natural sequences to propose new synthetic constructs that are more visible to the immune-system when needed, and stealthy when not. We compare its outputs to those generated by another method we developed - the physics-based `CAPE-Packer` which is based on the deimmunization protocol developed by Yachnin et al. [6] and ignorant of the target protein's natural sequence space.

We find that both methods can modify immune-visibility compared to natural sequences while maintaining high levels of structural similarity. As `CAPE-Packer` is not limited by the diversity in the target protein's natural sequence space, we find that it is more flexible in adjusting immune-visibility. However, designing proteins within the boundaries of natural sequence space is crucial for two main reasons. Firstly, it helps in preserving the known and potentially undiscovered functions of the protein being designed by conserving local functional constraints. Secondly, for vaccines, it allows to incorporate the diversity of in particular sequence-based MHC-I epitopes. That `CAPE-XVAE` can capture this local sequence similarity is demonstrated by the substantial proportion of naturally occurring short sub-sequences within its generated sequences (k-mer similarity). In fact, it generated sequences with particularly high visible peptide recall, allowing it to capture the diversity of potential epitopes found in viral protein sequence variants. This contrasts with `CAPE-Packer`, which is unable to incorporate those.

We conclude that methods like `CAPE-Packer` that disregard sequence information will be useful when designing completely synthetic proteins de novo under immune-visibility constraints. The designer needs to have full knowledge of the functions the protein is supposed to fulfill as well as the mechanism to achieve those. Functional regions can then be fixed, before allowing the algorithm to design around them. However, when we want to modify naturally occurring proteins where no full information about functionality and its mechanism is available, the hope is for machine learning algorithms to infer these from countless existing examples.

Flexible models trained from natural sequences and able to incorporate naturally occurring epitopes, like `CAPE-XVAE`, will be particularly useful for vaccine design. `CAPE-XVAE` can be easily adapted to modify for a broad range of immune-visibility profiles (see `Box2`) dependent on the latest developments in vaccine design. Generating chimeric sequences could potentially make escape mutations more unlikely and capturing the diversity in naturally occurring sequences may provide better, more universal vaccines in the future, compared to those that use just one strain of a virus. The concept will need validation, and this will be the subject of future studies.

However, with regards to reducing immune-visibility, we have also observed that `CAPE-XVAE` is not able to completely hide proteins from CTLs in our example case. As it solely relies on the distribution of natural protein sequences it might struggle to propose sub-sequences that need to be introduced to achieve invisibility if they do not exist in the training data. Because of this, we think that new ML-based approaches will need to be developed implementing a tunable and hybrid approach. These methods would incorporate structural information in addition to sequence. They could also utilize information from other proteins in addition to the target protein and be able to diverge by a defined and tunable amount in sequence space. Eventually, more complex immune-visibility profiles - considering immunogenicity and immunodominance also with regards to other components of the immune system (e.g. MHC-II) - need to be explored, but using a feedback loop with wet-lab validation.

5   Acknowledgements

This work was supported by the United Kingdom Research and Innovation (grant EP/S02431X/1), UKRI Centre for Doctoral Training in Biomedical AI at the University of Edinburgh, School of Informatics. For the purpose of open access, the author has applied a creative commons attribution (CC BY) licence to any author accepted manuscript version arising.

This project was supported by the Royal Academy of Engineering and the Office of the Chief Science Adviser for National Security under the UK Intelligence Community Postdoctoral Research Fellowship programme.

J.A. Alfaro was supported by (i) United Kingdom Research and Innovation (grant EP/S02431X/1), (ii) the project 'International Centre for Cancer Vaccine Science' which is carried out within the International Agendas Program of the Foundation for Polish Science, cofinanced by the European Union under the European Regional Development Fund. The authors would like to thank 'CI-TASK, Gdansk', and the 'PL-Grid Infrastructure, Poland' for providing their hardware and software resources. Dr. Rajan was supported by the KATY Consortium H2020-SCI-FA-DTS-2020-1.

6   Author contributions

Hans-Christof Gasser: Conceptualization, Methodology, Software, Validation, Writing - Original Draft, Writing - Review & Editing, Visualization **Diego Oyarzun:** Conceptualization, Writing - Review & Editing, Visualization, Supervision **Ajitha Rajan:** Conceptualization, Writing - Review & Editing, Visualization, Supervision **Javier Alfaro:** Conceptualization, Writing - Review & Editing, Visualization, Supervision

During the preparation of this work the author(s) used ChatGPT in order to increase the readability of the text. After using this tool/service, the author(s) reviewed and edited the content as needed and take(s) full responsibility for the content of the publication.

References

[1] Moderna. *mRNA Medicines We Are Currently Developing*. 2023. URL: https://www.modernatx.com/en-US/research/product-pipeline (visited on 07/07/2023).

[2] Léa V. Zinsli et al. "Deimmunization of Protein Therapeutics – Recent Advances in Experimental and Computational Epitope Prediction and Deletion". In: *Computational and Structural Biotechnology Journal* 19 (Jan. 2021), pp. 315–329. URL: https://www.sciencedirect.com/science/article/pii/S2001037020305493 (visited on 01/09/2023).

[3] Yoonjoo Choi, Karl E. Griswold, and Chris Bailey-Kellogg. "Structure-Based Redesign of Proteins for Minimal T-cell Epitope Content". In: *Journal of Computational Chemistry* 34.10 (2013), pp. 879–891. URL: https://onlinelibrary.wiley.com/doi/abs/10.1002/jcc.23213 (visited on 01/10/2023).

[4] Yoonjoo Choi et al. "EpiSweep: Computationally Driven Reengineering of Therapeutic Proteins to Reduce Immunogenicity While Maintaining Function". In: *Computational Protein Design*. Ed. by Ilan Samish. Methods in Molecular Biology. New York, NY: Springer, 2017, pp. 375–398. URL: https://doi.org/10.1007/978-1-4939-6637-0_20 (visited on 01/10/2023).

[5] Ali Bootwala et al. "Protein Re-Surfacing of E. Coli L-Asparaginase to Evade Pre-Existing Anti-Drug Antibodies and Hypersensitivity Responses". In: *Frontiers in Immunology* 13 (2022). URL: https://www.frontiersin.org/articles/10.3389/fimmu.2022.1016179 (visited on 01/09/2023).

[6] Brahm J. Yachnin et al. "MHCEpitopeEnergy, a Flexible Rosetta-Based Biotherapeutic Deimmunization Platform". In: *Journal of Chemical Information and Modeling* 61.5 (May 2021), pp. 2368–2382. URL: https://doi.org/10.1021/acs.jcim.1c00056 (visited on 02/16/2023).

[7] Maxime Carpentier et al. "Intrinsic Transgene Immunogenicity Gears CD8+ T-cell Priming After rAAV-Mediated Muscle Gene Transfer". In: *Molecular Therapy* 23.4 (Apr. 2015), pp. 697–706. URL: https://linkinghub.elsevier.com/retrieve/pii/S1525001616300892 (visited on 11/20/2023).

[8] Jerry R. Mendell et al. "Dystrophin Immunity in Duchenne's Muscular Dystrophy". In: *New England Journal of Medicine* 363.15 (Oct. 2010), pp. 1429–1437. URL: https://doi.org/10.1056/NEJMoa1000228 (visited on 11/20/2023).

[9] Gary C. Pien et al. "Capsid Antigen Presentation Flags Human Hepatocytes for Destruction after Transduction by Adeno-Associated Viral Vectors". In: *The Journal of Clinical Investigation* 119.6 (June 2009), pp. 1688–1695. URL: https://www.jci.org/articles/view/36891 (visited on 03/05/2023).

[10] Jamie L. Shirley et al. "Immune Responses to Viral Gene Therapy Vectors". In: *Molecular Therapy* 28.3 (Mar. 2020), pp. 709–722. URL: https://www.cell.com/molecular-therapy-family/molecular-therapy/abstract/S1525-0016(20)30002-2 (visited on 11/20/2023).

[11] Julie M. Crudele and Jeffrey S. Chamberlain. "Cas9 Immunity Creates Challenges for CRISPR Gene Editing Therapies". In: *Nature Communications* 9.1 (Aug. 2018), p. 3497. URL: https://www.nature.com/articles/s41467-018-05843-9 (visited on 03/05/2023).

[12] Jonathan M. Carlson and Zabrina L. Brumme. "HIV Evolution in Response to HLA-restricted CTL Selection Pressures: A Population-Based Perspective". In: *Microbes and Infection* 10.5 (Apr. 2008), pp. 455–461. URL: https://www.sciencedirect.com/science/article/pii/S1286457908000348 (visited on 11/13/2023).

[13] Persephone Borrow et al. "Antiviral Pressure Exerted by HIV-l-specific Cytotoxic T Lymphocytes (CTLs) during Primary Infection Demonstrated by Rapid Selection of CTL Escape Virus". In: *Nature Medicine* 3.2 (Feb. 1997), pp. 205–211. URL: https://www.nature.com/articles/nm0297-205 (visited on 12/12/2022).

[14] Kenneth Murphy and Casey Weaver. *Janeway's Immunobiology*. 9th. Garland Science, 2017.

[15] Birkir Reynisson et al. "NetMHCpan-4.1 and NetMHCIIpan-4.0: Improved Predictions of MHC Antigen Presentation by Concurrent Motif Deconvolution and Integration of MS MHC Eluted Ligand Data". In: *Nucleic Acids Research* 48.W1 (July 2020), W449–W454. URL: https://doi.org/10.1093/nar/gkaa379 (visited on 04/05/2021).

[16] J. Dauparas et al. "Robust Deep Learning–Based Protein Sequence Design Using ProteinMPNN". In: *Science* 378.6615 (Oct. 2022), pp. 49–56. URL: https://www.science.org/doi/10.1126/science.add2187 (visited on 09/04/2023).

[17] Diederik P. Kingma and Max Welling. "Auto-Encoding Variational Bayes". In: *arXiv:1312.6114 [Cs, Stat]*. May 2014. URL: http://arxiv.org/abs/1312.6114 (visited on 02/07/2022).

[18] Ashish Vaswani et al. "Attention Is All You Need". In: *Advances in Neural Information Processing Systems* 30 (2017), pp. 5998–6008. URL: https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html (visited on 11/06/2020).

[19] Bohan Li et al. "A Surprisingly Effective Fix for Deep Latent Variable Modeling of Text". In: *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*. Hong Kong, China: Association for Computational Linguistics, 2019, pp. 3601–3612. URL: https://www.aclweb.org/anthology/D19-1370 (visited on 02/15/2023).

[20] Dominic Phillips et al. "Generating Immune-aware SARS-CoV-2 Spike Proteins for Universal Vaccine Design". In: *Proceedings of the 1st Workshop on Healthcare AI and COVID-19, ICML 2022*. PMLR, July 2022, pp. 100–116. URL: https://proceedings.mlr.press/v184/phillips22a.html (visited on 07/25/2022).

[21] Andrew Leaver-Fay et al. "Chapter Nineteen - Rosetta3: An Object-Oriented Software Suite for the Simulation and Design of Macromolecules". In: *Methods in Enzymology*. Ed. by Michael L. Johnson and Ludwig Brand. Vol. 487. Computer Methods, Part C. Academic Press, Jan. 2011, pp. 545–574. URL: https://www.sciencedirect.com/science/article/pii/B9780123812704000196 (visited on 07/07/2023).

[22] Sarel J. Fleishman et al. "RosettaScripts: A Scripting Language Interface to the Rosetta Macromolecular Modeling Suite". In: *PLOS ONE* 6.6 (June 2011), e20161. URL: https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0020161 (visited on 07/07/2023).

[23] Julia Koehler Leman et al. "Macromolecular Modeling and Design in Rosetta: Recent Methods and Frameworks". In: *Nature Methods* 17.7 (July 2020), pp. 665–680. URL: https://www.nature.com/articles/s41592-020-0848-2 (visited on 10/03/2022).

[24] Vikram Khipple Mulligan. *Optimizing Side-Chains: Introduction to the Packer*. June 2016. URL: https://www.rosettacommons.org/demos/latest/tutorials/Optimizing_Sidechains_The_Packer/Optimizing_Sidechains_The_Packer (visited on 06/07/2023).

[25] Timothy J. O'Donnell, Alex Rubinsteyn, and Uri Laserson. "MHCflurry 2.0: Improved Pan-Allele Prediction of MHC Class I-Presented Peptides by Incorporating Antigen Processing". In: *Cell Systems* 11.1 (July 2020), 42–48.e7. URL: https://www.sciencedirect.com/science/article/pii/S2405471220302398 (visited on 04/05/2021).

[26] John Jumper et al. "Highly Accurate Protein Structure Prediction with AlphaFold". In: *Nature* 596.7873 (Aug. 2021), pp. 583–589. URL: https://www.nature.com/articles/s41586-021-03819-2 (visited on 09/29/2022).

[27] Yang Zhang and Jeffrey Skolnick. "TM-align: A Protein Structure Alignment Algorithm Based on the TM-score". In: *Nucleic Acids Research* 33.7 (Apr. 2005), pp. 2302–2309. URL: https://doi.org/10.1093/nar/gki524 (visited on 03/31/2023).

[28] Frimpong Boadu, Hongyuan Cao, and Jianlin Cheng. "Combining Protein Sequences and Structures with Transformers and Equivariant Graph Neural Networks to Predict Protein Function". In: *Bioinformatics* 39.Supplement_1 (June 2023), pp. i318–i325. URL: https://doi.org/10.1093/bioinformatics/btad208 (visited on 08/29/2023).

[29] Osamu Gotoh. "An Improved Algorithm for Matching Biological Sequences". In: *Journal of Molecular Biology* 162.3 (Dec. 1982), pp. 705–708. URL: https://www.sciencedirect.com/science/article/pii/0022283682903989 (visited on 06/01/2023).

[30] Peter JA Cock et al. "Biopython: Freely Available Python Tools for Computational Molecular Biology and Bioinformatics". In: *Bioinformatics (Oxford, England)* 25.11 (2009), pp. 1422–1423.

[31] Jacob Devlin et al. "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding". In: *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Minneapolis, Minnesota: Association for Computational Linguistics, June 2019, pp. 4171–4186. URL: https://www.aclweb.org/anthology/N19-1423 (visited on 04/21/2021).

[32] Alec Radford and Karthik Narasimhan. "Improving Language Understanding by Generative Pre-Training". In: 2018. URL: https://www.semanticscholar.org/paper/Improving-Language-Understanding-by-Generative-Radford-Narasimhan/cd18800a0fe0b668a1cc19f2ec95b5003d0a5035 (visited on 03/01/2023).

[33] Alec Radford et al. "Language Models Are Unsupervised Multitask Learners". In: (2019). URL: https://cdn.openai.com/better-language-models/language_models_are_unsupervised_multitask_learners.pdf.

[34] Tom B. Brown et al. "Language Models Are Few-Shot Learners". In: *arXiv:2005.14165 [Cs]*. July 2020. URL: http://arxiv.org/abs/2005.14165 (visited on 11/30/2021).

[35] Richard Sutton and Andrew Barto. *Reinforcement Learning - An Introduction.* 2nd ed. MIT Press, 2018.

[36] Yaser Keneshloo et al. "Deep Reinforcement Learning for Sequence-to-Sequence Models". In: *IEEE Transactions on Neural Networks and Learning Systems* 31.7 (July 2020), pp. 2469–2489.

[37] Ronald J. Williams. "Simple Statistical Gradient-Following Algorithms for Connectionist Reinforcement Learning". In: *Machine Learning* 8.3 (May 1992), pp. 229–256. URL: https://doi.org/10.1007/BF00992696 (visited on 03/03/2023).

[38] Diederik P. Kingma and Jimmy Ba. "Adam: A Method for Stochastic Optimization". In: *arXiv:1412.6980 [cs]* (Jan. 2017). URL: http://arxiv.org/abs/1412.6980 (visited on 10/22/2020).

[39] Takuya Akiba et al. "Optuna: A Next-generation Hyperparameter Optimization Framework". In: *arXiv:1907.10902 [cs, stat]* (July 2019). URL: http://arxiv.org/abs/1907.10902 (visited on 03/15/2022).

S Supplementary material

S.1 CAPE-XVAE

S.1.1 Variational Autoencoders

The basic idea behind AEs and VAEs is, that there are some hidden "latent" variables that can be used to reconstruct high dimensional data from a lower dimensional latent representation. For pictures of faces, these latent variables could be the length, color and shape of hair, the facial expression, etc.

AEs consist of an encoder that maps an input example x to a latent representation vector z and a decoder that takes in this vector and reconstructs the example. They are trained together to minimize the reconstruction error. Unfortunately, AE may suffer from "holes" in the latent space where there are no corresponding realistic examples. VAEs aim to address this by incorporating an additional KL-divergence term into their objective function, that encourages the latent representations to be normally distributed around the origin in latent space.

VAE may then suffer from another problem known as "posterior-collapse" or "KL-vanishing". This arises when using a very powerful decoder - often a AR model. Here the following strategy often ends up being optimal. The encoder simply learns to minimize the KL-divergence term while the decoder ignores the latent representations and directly learns to construct realistic examples. Various methods have been developed to mitigate it and preserve the meaningfulness of the latent representations. We follow an approach suggested by [19] which combines three methods.

- **Free bits:** The KL divergence term in the objective function is cut off by a hyper-parameter λ in each latent dimension. This allows for a controlled amount of information about the input to be retained in the latent variable without penalty.

- **Annealing:** During training, the KL-divergence term in the objective function gets weighted by a factor β. This starts out at zero - effectively allowing AE training for a certain period of time - before slowly rising to one.

- **Resetting the Decoder:** The uninformative latent representations provided by the encoder initially during training may lead to the decoder learning to disregard them. Therefore, when the AE training ends, the decoder is reset to its untrained state. This allows the decoder to learn from more meaningful latents provided by the encoder.

S.1.2 Transformers

Transformer networks [18] operate on a set of elements, each represented by a vector of dimension m, which undergoes transformation by multiple transformer layers. To incorporate positional information and convert tokens into vectors, each token needs to undergo an embedding process, mapping it to a m-dimensional space using an embedding layer. The attention mechanism allows elements to selectively focus on and incorporate relevant information from other elements, facilitating effective information exchange and processing within the transformer architecture.

Overview
The two main categories of transformer networks were already outlined in the original transformer architecture [18], that described a translation system consisting of an encoder- and a decoder. The encoder evolved into the Bidirectional Encoder Representations for Transformers (BERT) architecture [31], while the decoder inspired the Generative Pretrained Transformer (GPT) family of auto-regressive models [32, 33, 34], including ChatGPT.

- **Encoder:** When translating from for example English to French, the encoder stack would take in the English text sequence and convert it into a sequence of contextual embeddings of the same length - only attending to all English tokens during the process.

- **Decoder:** In contrast, the decoder would predicting each French word based on all previous French words in the sentence and the encoding provided by the encoder for the whole English text. Therefore, two modifications to the attention mechanism are required.

  Firstly, the decoder is an AR model, meaning it predicts the next token in a sequence based on the preceding tokens. To train AR models efficiently, teacher forcing is commonly used. This means that the entire target sequence, like the French translation, is provided at once. To prevent the model from attending to future information during training, a masking mechanism is employed, setting the weights of future values to zero.

  Secondly, in translation tasks, the decoder needs to have access to the encoding of the original input sequence, such as the English sentence encoded by the encoder. This is achieved through cross-attention. This allows the decoder to attend to and incorporate information from a different sequence. In contrast, self-attention - which is also used in the encoder - refers to attending only within the same sequence.

Figure 8: **Transformer blocks add to a residual stream received from a preceding block or embedding layer.** (a) The Self Attention Block uses self-attention only over the single input sequence itself. (b) In contrast, the Cross Attention Block applies attention two times. First, to self-attend over the residual stream sequence (this is typically done in a masked way - not attending over 'future' sequence elements that have not been generated yet). And second, to attend over a sequence that is different from the residual stream.

Details

In **Figure 8** we depict the details of the transformer blocks that are used to implement the encoder and decoder. Multiple sequential *Self Attention Blocks* form an *Encoder Stack* while multiple sequential *Cross Attention Blocks* form a *Decoder Stack*.

Each transformer block updates a *Residual Stream* - a sequence of vectors received from the precedent transformer block or from an embedding layer. While the *Self Attention Block* (see **Figure 8a**) only considers information in the *Residual Stream* for updating the *Residual Stream*, the *Cross Attention Block* (see **Figure 8b**) also incorporates information from a separate stream (red lines in **Figure 8b**) into it.

S.1.3 Reinforcement Learning

We want to backpropagate gradient information from the MHC-I presentation predictor, through the `CAPE-XVAE` decoder, to the latent space. However, directly backpropagating through the discrete decoder output is not possible, so we require an alternative method. One such approach is RL, which involves learning how to take actions to maximize a reward signal [35]. RL has been utilized for training the model parameters of sequence-to-sequence models [36]. In contrast, we employ RL to train the latent vector z, which steers the decoders behavior.

The typical RL setting involves an agent observing its current state s_t and based on this taking an action a_t in an environment. The agent follows a policy π_θ, parameterized by θ, to select an action, which can be stochastic. After performing the action, the environment provides the agent with a reward signal r_t based on the immediate benefit of the action in the environment. An episode consists of sequential iterations of this process until a terminal state is reached. The complexity of RL arises from the fact that actions taken at earlier stages of an episode can have repercussions on future rewards, either increasing or decreasing them. Consequently, the agent's objective is to maximize the (sometimes discounted) expected sum of rewards ($J(\theta) = \mathbb{E}_{\pi(\theta)} \sum_t r_t$) over the course of the episode. Additionally, we define the state value function $q_\pi(s, a)$, which represents the expected value of discounted rewards when taking action a in state s and subsequently following policy π. The state-value function serves as a useful estimate for evaluating the long-term desirability of actions within a given state.

The policy function $\pi_\theta(s_t)$ is crucial for maximizing the expected reward J. To find its optimal parameters θ (in our case the latent vector), the gradient ascent method shown in Equation 1 can be used:

$$\theta_{j+1} = \theta_j + \alpha \nabla J(\theta_j) \tag{1}$$

Directly back-propagating each trajectory through the discrete tokens is not possible. Fortunately, the REINFORCE

[37] algorithm allows us to approximate $\nabla J(\theta_j)$ by the following Equation 2.

$$\nabla J(\theta_j) \approx \mathbb{E}_\pi \left[q_\pi(S_t, A_t) \frac{\nabla \pi(A_t | S_t, \theta)}{\pi(A_t | S_t, \theta)} \right] \tag{2}$$

When we then define $\mathbb{E}_\pi[G_t | S_t, A_t] = q_\pi(S_t, A_t), G_t = \sum_{k=0}^{\inf} R_{t+1+k}$ [35, Section 13.3], we get the following gradient ascent formula:

$$\theta_{j+1} = \theta_j + \alpha G_t \nabla \ln \pi_\theta(A_t | S_t)$$

All of the terms therein can be calculated by us.

S.1.4 Training and hyper-parameter search

To optimize the model parameters we use Adam [38] ($\beta_1 = 0.9, \beta_2 = 0.999$) in combination with cosine annealing and utilize teacher-forcing during training.

To perform a systematic hyperparameter search, we employ Optuna [39] using the tree-structured parzen estimator method. The search objective is to minimize the VAE validation set loss including free bits.

In a first step we ran 51 trials of a hyper-parameter search across several dimensions to minimize the modified VAE loss on the validation set. We arrived at the following best hyper-parameter configuration in the column **Selected**.

Hyper-parameter	Distribution	Selected
Number of latent variables (L)	1	1
Dimension of latent variables (l)	32	32
Lambda (λ)	1.0	1.0
Model dimensions (d)	256	256
Feed-forward dimensions	512	512
Number of heads	8	8
Number of layers	1 to 5	3
Dropout	Uniform(0, 0.4)	0.015
Learning rate	Log-Uniform(0.0001, 0.01)	0.00013
Batch size	32	32

Table 5: Hyper-parameter search

Each of the trials was trained for 500 epochs on an auto-encoder objective ($\beta = 0$). Then, the decoder weights were reset to their initial state. Over the next 250 epochs of training the β parameter would linearly be increase to reach one. Afterwards training ran for another 750 epochs with $\beta = 1$. Figure 9 shows the development of the train and validation reconstruction losses during training. You can clearly see a spike when the CAPE-decoder got reinitialized.

Figure 9: Reconstruction loss during training