Regression and Alignment for Functional Data and Network Topology

Danni Tu[1,*], Julia Wrobel[2], Theodore D. Satterthwaite[3,4], Jeff Goldsmith[5], Ruben C. Gur[3,6],

Raquel E. Gur[3,6], Jan Gertheiss[7,+], Dani S. Bassett[8,9,10,11,+], Russell T. Shinohara[1,+]

[1] The Penn Statistics in Imaging and Visualization Endeavor (PennSIVE),

Department of Biostatistics, Epidemiology, and Informatics, University of Pennsylvania,

Philadelphia, PA, USA

[2] Department of Biostatistics and Bioinformatics, Emory University, Atlanta, GA, USA

[3] Department of Psychiatry, Perelman School of Medicine, Philadelphia, PA USA

[4] Penn Lifespan Informatics and Neuroimaging Center, Philadelphia, PA, USA

[5] Department of Biostatistics, Columbia University, New York, NY, USA

[6] The Penn Medicine-CHOP Lifespan Brain Institute, Philadelphia, PA, USA

[7] Department of Mathematics and Statistics, School of Economics and Social Sciences, Helmut

Schmidt University, Hamburg, Germany

[8] Department of Bioengineering, University of Pennsylvania, Philadelphia, PA, USA

[9] Department of Physics and Astronomy, University of Pennsylvania, Philadelphia, PA, USA

[10] Department of Electrical and Systems Engineering, University of Pennsylvania, Philadelphia,

PA, USA

[11] Department of Neurology, University of Pennsylvania, Philadelphia, PA, USA

[*]dtu@alumni.upenn.edu [+]co-senior authors

[*]To whom correspondence should be addressed.

Summary

In the brain, functional connections form a network whose topological organization can be described by graph-theoretic network diagnostics. These include characterizations of the community structure, such as modularity and participation coefficient, which have been shown to change over the course of childhood and adolescence. To investigate if such changes in the functional network are associated with changes in cognitive performance during development, network studies often rely on an arbitrary choice of pre-processing parameters, in particular the proportional threshold of network edges. Because the choice of parameter can impact the value of the network diagnostic, and therefore downstream conclusions, we propose to circumvent that choice by conceptualizing the network diagnostic as a function of the parameter. As opposed to a single value, a network diagnostic curve describes the connectome topology at multiple scales—from the sparsest group of the strongest edges to the entire edge set. To relate these curves to executive function and other covariates, we use scalar-on-function regression, which is more flexible than previous functional data-based models used in network neuroscience. We then consider how systematic differences between networks can manifest in misalignment of diagnostic curves, and consequently propose a supervised curve alignment method that incorporates auxiliary information from other variables. Our algorithm performs both functional regression and alignment via an iterative, penalized, and nonlinear likelihood optimization. The illustrated method has the potential to improve the interpretability and generalizability of neuroscience studies where the goal is to study heterogeneity among a mixture of function- and scalar-valued measures.

Key words: Alignment; Functional Data Analysis; Functional Regression; Network Neuroscience.

1. Introduction

Functional magnetic resonance imaging (fMRI) is a powerful, non-invasive method to measure blood oxygen level dependent (BOLD) signals in the brain. A major goal of network neuroscience studies is to use the observed coherence of these BOLD time series to uncover functional relationships between brain regions. These connections, which collectively form a functional network or *connectome*, exhibit a complex hierarchical and small-world topology that promotes efficient information processing (Muldoon *and others*, 2016) and can be described by various graph-theoretical diagnostics (Bullmore and Bassett, 2011).

Importantly, the functional connectome is modular: it can be partitioned into communities that are strongly intraconnected and relatively weakly interconnected (Garcia *and others*, 2018; Sporns and Betzel, 2016). These communities are either known *a priori* or may be estimated from the data using greedy algorithms (Fortunato, 2010; Gates *and others*, 2016). The modularity index quantifies the saturation of within-community connections relative to that of a null graph where community structure has been reconfigured at random (Newman and Girvan, 2004). Relatedly, the participation coefficient (Betzel and Bassett, 2017) assesses the degree to which nodes are connected to different communities. Modular systems and other characterizations of mesoscale network organization have been linked to cognitive outcomes in both healthy adults (Gallen and D'Esposito, 2019) and neurodegenerative disease (Gamboa *and others*, 2014). In adolescents, reorganization and integration of modules during development (Fair *and others*, 2009; Gu *and others*, 2019; Morgan *and others*, 2018) are thought to support simultaneous changes in executive functioning (Baum *and others*, 2017).

In most connectome studies, the matrix corresponding to network edge weights is thresholded (i.e., sparsified) to limit the data to connections with stronger signal (Wang *and others*, 2009; Geerligs *and others*, 2014; Achard, 2006). However, there is much disagreement about what threshold to use, and this somewhat arbitrary choice can significantly impact the conclusions

about how network structure relates to group differences and other outcomes (Garrison *and others*, 2015; Scheinost *and others*, 2012). We circumvent this choice by considering a range of all possible thresholds t (Bullmore and Bassett, 2011; Bassett *and others*, 2012). As a result, the network diagnostics—modularity and participation coefficient—are functions of t (Figure 1). To relate these functional data to scalar-valued outcomes (e.g., executive function) and covariates (e.g., age and motion), we introduce a functional regression framework.

Our proposed statistical model, Regression and Alignment for Functional Data and Network Topology (RAFT), is motivated by three aspects of the data that current methods for network diagnostic curves do not address. First, we address the function-valued nature of our data by using a scalar-on-function regression model, which is more powerful than pointwise comparisons of curves at fixed values of t (Figure S.1). Regression models can be used to predict a continuous scalar-valued outcome, in contrast to permutation tests which are more often used in neuroscience studies (Bassett *and others*, 2012; Singh *and others*, 2013; Palaniyappan *and others*, 2016). And through functional principal components analysis (FPCA), we can describe variation in the curve shape that cannot be evaluated by existing summaries such as the area under the curve (Giusti *and others*, 2015). Second, our method addresses misalignment in the functional data, which can materialize due to confounding in network diagnostic measures that stems from systematic differences in edge strength distribution (van den Heuvel *and others*, 2017). To align the data, we introduce a simple parameterization of a warping function based on the cumulative distribution of a Beta random variable. Third, while the majority of alignment methods use only the information observed in the curves themselves ("unsupervised" alignment), we propose a *supervised* algorithm that incorporates information from other covariates.

In simulated data, we demonstrate that our proposed curve alignment methods improve parameter estimation in downstream regression analyses. We then apply our method to network and neurocognitive data obtained from the Philadelphia Neurodevelopmental Cohort (PNC), a

community-based study of brain development in youth aged 8 to 21 years (Satterthwaite *and others*, 2016), thereby complementing previous findings that link the differentiation of cortical systems to cognitive performance in the PNC (Gu *and others*, 2015).

2. Multiscale Network Topology as Functional Data

2.1 *Brain Network Topology*

A brain network is a weighted graph $\mathbf{g} = (V, E)$ consisting of a node set $V = \{v_i\}_{i=1}^R$, where v_i is a brain region out of R total regions, and edge set $E = \{(v_i, v_j)|i \neq j\}$ whose weights $A_{ij} = a(v_i, v_j) \in [0, 1]$ quantify the strength of the connections between each pair of nodes. In functional connectivity studies, v_i are determined based on a parcellation of brain regions and A_{ij} are often calculated using the absolute value of the between-region correlations of fMRI time series (Achard, 2006). The adjacency matrix associated with $\mathbf{g}$ is then defined as the matrix A with i, jth entry equal to A_{ij}.

The topology of $\mathbf{g}$ can be described using network diagnostics (Bullmore and Bassett, 2011) that are lower dimensional than A, but that are more informative about the overall network organization than a single edge. For a graph $\mathbf{g}$ and any partition of its nodes into communities, the modularity of $\mathbf{g}$ describes the abundance of connections within communities that we observe compared to a null graph:

$$m = \frac{1}{2k} \sum_{i,j} \left[A_{ij} - \frac{e_i e_j}{2k} \right] \delta\left(h_i, h_j\right),$$

where e_i is the degree of (i.e., the number of edges connecting to) node i, k is the total number of edges, h_i is the community assigned to node i, and δ is the Kronecker delta. Intuitively, when nodes v_i and v_j are in the same community, the term $\left[A_{ij} - \frac{e_i e_j}{2k} \right]$ is the difference between the observed connectivity A_{ij} and $\frac{e_i e_j}{2k}$, the expected connectivity of a random graph under a configuration null model (Newman and Girvan, 2004). In the configuration null, the degree of each

node is preserved, but all k edges are cut in half, creating $2k$ "open" half-edges. Then, the network

is re-wired: all $2k$ open half-edges are randomly connected to each other with equal probability, a

process that allows for self-loops and multiple edges between any two nodes. Therefore, any edge

emanating from a node has $2k-1$ possible locations to connect to. For two nodes v_i and v_j with

degree e_i and e_j, respectively, the probability of an edge existing between them is $\frac{e_i e_j}{2k-1}$, which is

often approximated by $\frac{e_i e_j}{2k}$ when k is large. A larger value of $\left[A_{ij} - \frac{e_i e_j}{2k}\right]$, and hence modularity,

means that more connections within communities are observed than might be expected under

the configuration null. Community assignments h_i may either be known *a priori* or calculated as

part of an iterative and greedy modularity maximization algorithm (Blondel *and others*, 2008;

Fortunato, 2010). In our paper, we use pre-defined communities based on a 7-community node

partition resulting in functionally coupled clusters in the cerebral cortex; these are described in

further detail in Yeo *and others* (2011).

Similarly, the participation coefficient (Guimerà and Amaral, 2005) captures how often the

average node connects to nodes outside its own community, and is calculated as

$$p = \frac{1}{R} \sum_{i=1}^{R} \left[1 - \sum_{s=1}^{C} \left(\frac{e_{is}}{e_i} \right)^2 \right],$$

where e_{is} is the number of edges between node v_i and all nodes in community s, e_i is the degree

of node i, and C is the total number of communities. When the term $1 - \sum_{s=1}^{C} \left(\frac{e_{is}}{e_i} \right)^2 = 0$, node

i is only connected to nodes in its own community; when it equals 1, node i is equally connected

to every community.

2.2   *Network Thresholding and Diagnostic Curves*

Thresholding is a common technique when the goal is to produce binary networks, or weighted

networks where the weakest edges—lower correlation values that are most impacted by measure-

ment error—have been removed (Zalesky *and others*, 2012; Bordier *and others*, 2017). Because

two networks with different numbers of non-zero edges may not be comparable in terms of their network diagnostics (Garrison *and others*, 2015; van Wijk *and others*, 2010), we threshold the edges such that the same proportion of strongest edges is preserved. The fraction t of edges preserved is the proportional threshold (Geerligs *and others*, 2014; Bassett *and others*, 2012).

As the choice of threshold t is often arbitrary, we instead consider network diagnostics as a function of all $t \in [0, 1]$. For person $i = 1, \ldots, n$ and threshold value t_k for $k = 1, \ldots, r$, we observe a single weighted network upon which we can calculate the modularity $m_i(t_k)$ and participation coefficient $p_i(t_k)$ (Figure 1). By repeating this process for all i and t_k, we obtain the discrete observations $\{m_i(t_k)\}_{k=1}^{r}$ and $\{p_i(t_k)\}_{k=1}^{r}$, which are then assumed to be samples of the smooth curves $m_i(t) \in \mathcal{L}^2[0, 1]$ and $p_i(t) \in \mathcal{L}^2[0, 1]$.

Functional data analysis methods (Wang *and others*, 2016) automatically encode the autocorrelation of the network diagnostic between neighboring values of t. Because functions are infinite-dimensional objects (i.e., they can be parameterized by infinitely many parameters), they are often replaced with a lower-dimensional representation during model estimation. One widely-used approach is functional principal components analysis (FPCA), which can simultaneously perform dimension reduction and decompose the functional variance in a set of curves. Letting $\mu_m(t)$ and $\Sigma_m(s, t) \equiv \text{Cov}(m_i(s), m_i(t))$ be the mean and covariance functions of $m_i(t)$, we can express $m_i(t)$ as

$$m_i(t) = \mu_m(t) + \sum_{j=1}^{\infty} U_{ij} \psi_j(t),$$

where $\psi_j(t)$ is the jth eigenfunction or functional principal component (FPC) of $\Sigma_m(s, t)$ based on its spectral decomposition, and U_{ij} is the associated FPC score

$$U_{ij} = \int \left(m_i(t) - \mu_m(t) \right) \psi_j(t) dt.$$

Typically, this infinite sum can be well approximated by the first N_m terms:

$$m_i(t) \approx \mu_m(t) + \sum_{j=1}^{N_m} U_{ij}\psi_j(t).$$

In practice, the observed curves $m_i(t)$ may be conceptualized as true curves $m_i^*(t)$ distorted by measurement error:

$$m_i(t) = m_i^*(t) + \varepsilon_{im}(t),$$

where $\varepsilon_{im}(t)$ is a mean zero measurement error process with variance σ_m^2. Then, $\Sigma_{m^*}(s,t)$ can be estimated by smoothing the method of moments estimator of $\Sigma_m(s,t)$ from the observed data (Goldsmith *and others*, 2011). Putting these together, we can write the FPCA expansion of $m_i(t)$ as the sum of the mean, a linear combination of finitely many FPCs, and measurement error:

$$m_i(t) = \mu_m(t) + \sum_{j=1}^{N_m} U_{ij}\psi_j(t) + \varepsilon_{im}(t).$$

Similarly, we write the FPCA decomposition of $p_i(t)$ as

$$p_i(t) = \mu_p(t) + \sum_{j=1}^{N_p} V_{ij}\eta_j(t) + \varepsilon_{ip}(t),$$

allowing us to express the participation coefficient curves again as the sum of the mean, a linear combination of FPCs, and measurement error.

2.3   *Scalar-on-Function Regression*

To relate a scalar-valued outcome y_i to a function-valued covariate $m_i(t)$, we first consider the simplest possible scalar-on-function regression model (Ramsay and Silverman, 2005):

$$y_i = \beta_0 + \int \beta_2(t)m_i(t)dt + \varepsilon_i, \tag{2.1}$$

where $\varepsilon_i \sim N(0, \sigma^2)$ is independent Gaussian noise, $\beta_2(t)$ is a smooth coefficient function, and β_0 is an intercept. Model 2.1 can be estimated assuming that $m_i(t)$ is replaced with its low-dimensional FPCA decomposition, and $\beta_2(t)$ can be represented in terms of penalized splines. Thus, a data-driven way to identify the thresholds t where $m_i(t)$ influences the outcome y is to find the values of t for which $\beta_2(t)$ is substantially different from zero.

2.4 *Curve Alignment*

Proportional thresholding can introduce a new type of confounding if there are systematic differences in the distribution of network edge weights (van den Heuvel *and others*, 2017). For example, brain networks in older children tend to have stronger connections overall, compared to younger children. As a result, the strongest 15% of edges for older participants are less likely to contain spurious connections (which have a more random topology) than the same percentage of edges in younger participants. This fact implies that for persons $i \neq j$, $m_i(t_0)$ and $m_j(t_0)$ may not be comparable at the same value t_0.

When the modularity curves $m(t)$ are functional objects, this lack of comparability can be conceptualized as phase (horizontal) variation: although the curves $m_i(\cdot)$ and $m_j(\cdot)$ describe the same underlying process, one curve may be a horizontally shifted or more intricately warped version of the other (Figure 2). Inferences based on amplitude (vertical) variation—the difference in the height of the modularity curve at fixed values of t—may be biased in the presence of phase variation, since phase variation precludes the accurate calculation of fundamental quantities such as the mean curve. As a result, methods for functional alignment (also called curve registration or warping) have been extensively studied and reviewed (Marron *and others*, 2015; Wang *and others*, 2016; Wrobel *and others*, 2018; Srivastava *and others*, 2011). A common strategy is to address phase and amplitude variation separately: functions are pre-aligned before applying a downstream analysis such as regression or clustering (Reiss *and others*, 2017).

An important note is that curve alignment and scalar-on-function regression are two methods that frequently occur in tandem but differ in their ends, given the structure of our data. Since the network diagnostic curves are simple and monotonic, it is possible to perfectly align them. But if the curves are perfectly aligned such that $m_i(t) = m(t)$ for all t, then Model 2.1 cannot be estimated. In general, the more these curves overlap (i.e., the less variation between curves), the more unstable the estimate of $\beta_2(t)$ is likely to be. In other words, we need variation in the predictors to draw any conclusions about associations with the response. At the same time, estimating Model 2.1 without performing any warping of the data may lead to incorrect conclusions, as stated above. We therefore investigate if it is possible to find an optimal middle ground between no alignment and perfect alignment in the case of simple, monotonic curves. Note that this issue is less of a concern when working with other types of functional data that have multiple non-monotonic features and residual differences in amplitude that remain after alignment.

Another concern is that, due to the flexibility of the scalar-on-function regression model, it is likely that there will be multiple ways to warp the data such that the predicted value of y is exactly equal to the observed value (i.e., the model is overfit to the data). Our proposed method aims to warp the data such that the prediction of an *auxiliary* variable z is improved, and we explore whether alignment using z can improve the prediction of y later on, regardless of the relationship between y and z.

Previous methods have considered the joint estimation of regression parameters and warping functions in the context of function-on-scalar and function-on-function regression. In Gervini (2014), the amplitude variation is decomposed using FPCA and the phase variation decomposed using Hermite splines; the associated scores and knots of these decompositions are then related to scalar covariates through a linear mixed effects model. However, as noted in Tucker *and others* (2018), this method involves applying FPCA to the unaligned curves, which is suboptimal as much amplitude variation may be artifactual due to misalignment. In Hadjipantelis *and others*

(2015), a function-on-scalar model is proposed where both the amplitude and phase variation are

decomposed using FPCA and the associated FPC scores are related to covariates. In Tucker *and*

others (2018), phase and amplitude variation are simultaneously assessed via a joint FPCA, and

then the outcome is regressed on these FPCs. However, FPCA is performed in a transformed space

via the square root velocity function, which renders the principal components less interpretable.

Our proposed model differs from these in that we consider a scalar-on-function framework where

the outcome y is regressed onto the aligned curves $m_i(t)$, which are aligned in a supervised way,

involving an auxiliary variable z that is related to the aligned $m_i(t)$ and possibly y. The proposed

alignment algorithm alternates between estimation of the parameters of a model for z given the

warped curves, and the warping functions given the z model.

2.5 *Warping Functions*

As others have done, we differentiate between the "individual threshold" t_i^* of the observed

unaligned curves, and the "system threshold" t of the aligned curves (Wrobel *and others*, 2018),

which are connected through the warping function $\phi_i(t) = t_i^*$. Therefore, the model in (2.1)

becomes

$$y_i = \beta_0 + \int \beta_2(t) m_i \left(\phi_i^{-1} \left(t_i^* \right) \right) dt + \varepsilon_i. \tag{2.2}$$

Note that Model (2.2) involves the aligned curves $m_i(\phi_i^{-1}(t_i^*))$, though we only observe the

unaligned curves $m_i(t_i^*)$.

As network diagnostic curves tend to be simple in shape, we choose a simple parameterization

for the inverse warping functions,

$$\phi_i^{-1}(u) \equiv \phi^{-1}(u; \alpha_{i1}, \alpha_{i2}) = \frac{\int_0^u s^{\alpha_{i1}-1}(1-s)^{\alpha_{i2}-1} ds}{\int_0^1 s^{\alpha_{i1}-1}(1-s)^{\alpha_{i2}-1} ds},$$

the regularized incomplete Beta function with parameters $\alpha_{i1}, \alpha_{i2} > 0$. Note that $\phi_i^{-1}(t)$ is the

cumulative distribution function (CDF) of a Beta$(\alpha_{i1}, \alpha_{i2})$ random variable, and is naturally monotonic and constrained at the endpoints so that $\phi^{-1}(0; \alpha_{i1}, \alpha_{i2}) = 0$ and $\phi^{-1}(1; \alpha_{i1}, \alpha_{i2}) = 1$ for all $\alpha_{i1}, \alpha_{i2} > 0$. For identifiability, alignment methods often require that the warping function is equal to the identity on average: $\mathbb{E}[\phi(t)] = t$, though many prefer to enforce $\mathbb{E}[\phi^{-1}(t)] = t$ for computational convenience (Fu and Heckman, 2019). Here, we note an advantage of using a CDF-based warping function: both $\phi^{-1}(t)$ and its inverse $\phi(t)$—a quantile function—are simple to evaluate numerically. The requirement that $\mathbb{E}[\phi^{-1}(t)] = t$ can also be replaced with the weaker requirement that $\mathbb{E}[(\alpha_{i1}, \alpha_{i2})] = (1, 1)$.

Even with these restrictions, Model (2.2) is not identifiable without further assumptions, since the true aligned curves are not observed for any person. A full likelihood involving the penalized regression parameters and fixed effects α_{i1}, α_{i2} would be over-parameterized, with the number of parameters increasing with the number of participants n. Therefore, we consider an iterative and penalized likelihood heuristic to estimate α_{i1}, α_{i2} given an auxiliary variable z, with the ultimate goal of using the aligned functions to predict an outcome y. The reason we do not use y itself for alignment is that, in many settings, it is possible to find α_{i1}, α_{i2} that results in a perfect fit (i.e., $y_i = \hat{y}_i$) even when there is no true association between y and the predictor curves. Therefore, we should believe *a priori* that the auxiliary variable z is strongly associated with the functional covariate (as we do with age and the network characteristics discussed above).

2.6 *RAFT Algorithm*

The RAFT algorithm estimates Model (2.2) using a two-step iterative process. In the model step, we estimate the parameters for the model involving z and $m_i(t)$; for instance, scalar-on-function regression with coefficients $\theta \equiv \{\beta_{z0}, \beta_1(t)\}$. In the warp step, we estimate warping functions $\phi_i(t)$ and aligned curves $m_i(\phi_i^{-1}(t_i^*))$.

1. **Initialize** at no warping: $\alpha_{1i}^{(0)} = \alpha_{i2}^{(0)} = 1$ for $i = 1, \cdots, n$.

2. **Model step.** At iteration k, fit a penalized functional regression model for outcome z with parameters $\theta^{(k)}$ given $\phi_i^{-1,(k)}(t)$ and the warped data $m_i\left(\phi_i^{-1,(k)}(t_i^*)\right)$:

$$\hat{\theta} = \underset{\theta}{\operatorname{argmin}} \sum_{i=1}^{n} \left|z_i - \hat{z}_i^{(k)}\right|^2 - p(\theta),$$

$$\hat{z}^{(k)} = \hat{\beta}_{z0} + \int \hat{\beta}_1(t) m_i\left(\phi_i^{-1,(k)}(t_i^*)\right) dt.$$

The functional coefficient $\beta_1(t)$ is estimated using penalized B-splines with a large number of knots $\{b_k\}_{k=1}^{N_b}$ with a smoothness-inducing penalty term $p(\theta)$ (Goldsmith *and others*, 2011). The functional predictor is represented using its FPCA decomposition:

$$m_i^{(k)}(t) = m_i\left(\phi_i^{-1,(k)}(t_i^*)\right) = \mu_m^{(k)}(t) + \sum_{j=1}^{N_m} U_{ij}^{(k)} \psi_j^{(k)}(t).$$

The model above can be readily estimated using scalar-on-function regression software, from the `refund` R package (Goldsmith *and others*, 2011, 2016).

3. **Warp step.** Estimate warping functions $\phi_i^{-1,(k+1)}(t)$ given $\theta^{(k)}$:

$$\alpha_{i1}^{(k+1)}, \alpha_{i2}^{(k+1)} = \underset{\alpha_{i1}, \alpha_{i2}}{\operatorname{argmax}} L\left(\alpha_{i1}, \alpha_{i2}, \theta^{(k)}\right),$$

where the objective function

$$L\left(\alpha_{i1}, \alpha_{i2}, \theta^{(k)}\right) = \ell\left(z_i \mid \alpha_{i2}, \alpha_{i2}, \theta^{(k)}\right) - \lambda_1 \left\|m_i\left(\phi_i^{-1}(t_i^*; \alpha_{i1}, \alpha_{i2})\right) - m_T(t)\right\|$$
$$- \lambda_2 \left\|m_i\left(\phi_i^{-1}(t_i^*; \alpha_{i1}, \alpha_{i2})\right) - m_i(t_i^*)\right\|,$$

and the term $\ell\left(z_i \mid \alpha_{i2}, \alpha_{i2}, \theta^{(k)}\right)$ is the likelihood of z assumed in Step 2.

4. **Iterate** steps 2 and 3 until convergence: $\left\|\alpha_j^{(k)} - \alpha_j^{(k-1)}\right\|^2 < \varepsilon$, $j = 1, 2$.

5. Finally, we fit the scalar-on-function model for the outcome of interest y,

$$\hat{y}^{(k)} = \hat{\beta}_0 + \int \hat{\beta}_2(t) m_i \left(\phi_i^{-1,(K)} \left(t_i^* \right) \right) dt, \tag{2.3}$$

where $\phi_i^{-1,(K)}(\cdot)$ is the final warping function after K iterations.

The objective function in Step 3 has three terms. Intuitively, the warp $\phi_i^{-1,(k+1)}(t)$ is chosen to maximize the likelihood

$$\ell \left(z_i \mid \alpha_{i2}, \alpha_{i2}, \theta^{(k)} \right) = -\log \left(\sqrt{2\pi \hat{\sigma}_z^{2(k)}} \right) - \frac{\left(z_i - \hat{\beta}_{z0}^{(k)} - \int \hat{\beta}_1^{(k)}(t) m_i \left(\phi_i^{-1} \left(t_i^*; \alpha_{i1}, \alpha_{i2} \right) \right) dt \right)}{2 \hat{\sigma}_z^{(2k)}},$$

given the observations z_i and estimated coefficients $\hat{\sigma}_z^{2,(k)}$, $\hat{\beta}_{z0}^{(k)}$, and $\hat{\beta}_1(t)^{(k)}$, but within certain parameters: the second term ensures that the data are warped towards a template curve, which can be known *a priori* or selected in a data-driven manner. For example, we select the centroid curve in the data which minimizes the L_2 distance from all other curves. The third term ensures that the warped curve is somewhere between the original curve and the template. Note that an *unsupervised* warping procedure can be done in a single step with the modified loss function

$$L' \left(\alpha_{i1}, \alpha_{i2}, \theta^{(k)} \right) = -\lambda_1 \left\| m_i \left(\phi_i^{-1} \left(t_i^*; \alpha_{i1}, \alpha_{i2} \right) \right) - m_T(t) \right\| - \lambda_2 \left\| m_i \left(\phi_i^{-1} \left(t_i^*; \alpha_{i1}, \alpha_{i2} \right) \right) - m_i \left(t_i^* \right) \right\|,$$

where the likelihood term—the only term involving the supervising variable z—is removed.

2.6.1 *Tuning Parameters* The parameters λ_1 and λ_2 control the balance of these penalties: when λ_2 is very large, no warping is performed, and when λ_1 is very large, curves are aligned towards the template. The values of these parameters must be chosen ahead of time or through an automated procedure. In the latter case, we suggest setting aside a portion of the data as a tuning set, where the data are warped using λ_1 and λ_2 selected from a grid of possible values, and

the optimal λ_1 and λ_2 are those which maximize the R-squared of Model (2.3). Having selected the tuning parameters, the algorithm is then applied to the remainder of the data.

2.6.2 *Generalized Algorithms*   In principle, the model for z in Step 2 of the RAFT algorithm can be any method for scalar-on-function regression, such as non-parametric regression or a suitable machine learning algorithm. In that case, the term $\ell\left(z_i \mid \alpha_{i2}, \alpha_{i2}, \theta^{(k)}\right)$ in the objective function may be replaced by another criterion, such as the MSE. Finally, in addition to the "model-first" algorithm above, where the model for z is estimated after initialization and before the first iteration of warping, it is also possible to consider a "warp-first" algorithm where the initial warps are estimated using an unsupervised step initially.

3. SIMULATION RESULTS

Performance of RAFT versus similar methods was first gauged using simulated data under multiple conditions. We first describe the simulation strategy at a high level; further details about the specific data generating process can be found in Section 3.1 below.

We generated $n = 600$ curves with the same base curve shape $f_0(t)$ for all individuals, similar to those used by Carroll *and others* (2020). Two strategies were used to induce amplitude (vertical) variation between these base curves: sinusoidal noise, where a random sine and cosine curve defined on [0,1] were added to $f_0(t)$ (Figure 3, Panels A and C); and Gaussian noise, where a random Gaussian variable was added to $f_0(t)$ in a pointwise fashion (Figure 3, Panels B and D). Finally, we considered two coefficient functions $\beta_1(t)$ and $\beta_2(t)$ representing the true association between the aligned curves and (z, y). Thus, the true data generating process involved the aligned curves $f_i(t)$:

$$z_i = \int \beta_1(t) f_i(t) dt$$
$$y_i = \int \beta_2(t) f_i(t) dt,$$

while the observed data include the unaligned curves $f_i(\phi(t; \alpha_{i1}, \alpha_{i1}))$ and (z, y), with the goal to accurately estimate $\beta_2(t)$, as y is the ultimate outcome of interest.

Model performance was measured by the mean squared error (MSE) of y and mean integrated squared error (MISE) of $\beta_2(t)$ over 100 iterations. For the supervised methods, the tuning parameters (λ_1, λ_2) were automatically selected as described in Section 2.6.1 on a tuning set of $n = 100$ other curves, and performance was assessed on the remaining 500 curves. In addition to the proposed methods from this paper—model-first RAFT, warp-first RAFT, and unsupervised "beta-cdf" warping—we also compared our results to *registr*, an FPCA-based unsupervised warping method (Wrobel *and others*, 2018; Wrobel, 2018). These four alignment methods were evaluated against the performance levels reached when using either the unaligned curves and the true aligned curves.

We found that aligning the functional covariate almost always improved (lowered) MISE($\beta_2(t)$) beyond simply using the unaligned curves to predict y (Figure 3). In scenario 1, model-first and warp-first RAFT had the best MISE($\beta_2(t)$), closest to that observed in the ideal case where the true aligned curves are known. In scenario 2, RAFT methods performed well again, but the unsupervised beta-cdf alignment proposed in Section 2.6.1 also performed well. The true coefficient $\beta_2(t)$ in scenario 2 has a sharp increase at $t = 0$, suggesting that for this type of relationship, FPCA-based warping methods such as *registr* may be less optimal than the more constrained warping provided by our proposed beta-cdf alignment. The value of in-sample MSE(y) did not vary appreciably between any of these methods.

3.1   *Simulation Details*

The base curve had the form $f_0(t) = 20 - (25t) + 30 \exp\left\{-\frac{(50t-25)^2}{72}\right\}$. To add sinusoidal noise

to the base curve, we generated observed curves $f_i(t) = f_0(t) + u_{1i}\sin(2\pi t) + u_{2i}\cos(2\pi t)$, with

i.i.d. $u_{ji} \sim N(\mu = 0, \sigma = 0.5r)$ and $r = \max|f_0(t)| - \min(f_0(t))|$. To add Gaussian noise to the

base curve, we generated observed curves $f_i(t) = f_0(t) + u_i(t)$ with i.i.d $u_i(t) \sim N(\mu = 0, \sigma =$

$0.015r)$ independently for all t. The final sample of observed but unaligned curves were then

generated as $f_i(t_i^*) = f_i(\phi_i(t; \alpha_{i1}, \alpha_{i2}))$, with i.i.d. $\alpha_{ij}^* \sim N(\mu = 1, \sigma = 0.1)$ for $j = 1, 2$ and

$\alpha_{ij} = \min(\max(\alpha_{ij}^*, 0.1), 3)$ to ensure all $\alpha_{ij} > 0$. We found that values of $\alpha_{ij} > 3$ and $\alpha_{ij} < 0.1$

produced extreme warps, where the entire curve was compressed towards one of the endpoints.

We also considered two options for the true coefficient functions $\beta_1(t)$ and $\beta_2(t)$. In case 1,

$\beta_1(t) = \frac{20}{\sqrt{2\pi}}\exp\left\{-\frac{(t-0.45)^2}{0.1}\right\}$ and $\beta_2(t) = \frac{20}{\sqrt{2\pi}}\exp\left\{-\frac{(t-0.55)^2}{0.1}\right\}$ for $t \in [0, 1]$. In case 2, $\beta_1(t) =$

$\frac{20}{\sqrt{2\pi}}\exp\left\{-\frac{(t-0.1)^2}{0.1}\right\}$ and $\beta_2(t) = \frac{20}{\sqrt{2\pi}}\exp\left\{-\frac{t^2}{0.1}\right\}$. Both sets of coefficient functions were chosen

to be more hill-shaped so that results were more sensitive to the effects of misalignment.

4.   Community Structure and Cognitive Performance in Neurodevelopment

We next asked if modularity and participation coefficient curves could improve prediction of ex-

ecutive function, a z-scored quantity representing non-verbal reasoning ability (Appendix S.1),

once the curves had been warped using either age or motion information. To do so, we applied

our method to $n = 1122$ participants from the Philadelphia Neurodevelopmental Cohort (Sat-

terthwaite *and others*, 2014) who underwent functional connectivity and neurocognitive studies.

For each participant, the functional connectivity matrix was calculated by taking the correlation

between the averaged BOLD time series in 400 cortical regions defined by Schaefer *and others*

(2017). To generate a sequence of thresholded weighted matrices, the correlation matrix was cu-

mulatively thresholded by a proportional threshold value $t = \{0.01, 0.02, \ldots, 0.99, 1\}$. For each

person and value of t, we obtained a weighted network on which we calculated the modularity

and participation coefficient values given the 7-community node partition described in Yeo *and others* (2011).

We also considered scalar covariates that are often studied in conjunction with functional connectivity in youth: age in years and in-scanner subject motion measured in millimeters (mm). Motion, defined as the average relative root mean square (RMS) displacement, has been shown to impact functional connectivity estimates and downstream network diagnostics (Power *and others*, 2012). Our data were pre-processed to reduce motion effects and all participants had average RMS displacement < 0.2 mm per frame as part of the inclusion criteria, although residual motion effects may persist (Ciric *and others*, 2017; Satterthwaite *and others*, 2014). Further details on data collection and scanner settings can be found in Appendix S.1.

Older adolescents had less motion (Figure S.2) and stronger, heavier-tailed distributions of raw functional connectivity (FC) edge weights, i.e. a greater proportion of strong connections (Figure 4). Specifically, we observed weak positive correlations (ρ, [95% CI]) between age and the following: average edge weight, ρ=0.197 [0.140,0.254]; standard deviation of edge weights, ρ=0.217 [0.161,0.272]; and the inter-quartile range of edge weights, ρ=0.205 [0.149,0.261]. We found weak negative correlations between motion and the following: average edge weight, ρ=-0.155 [-0.097,-0.211]; standard deviation of edge weights, ρ=-0.191 [-0.247,-0.134]; and the inter-quartile range of edge weights, ρ=-0.173 [-0.230,-0.116].

Figure 4 shows the network diagnostic curves in our sample. Modularity curves followed a similar shape, with a sharp peak around $t \approx 0.05$ and then a downward slope as t increased. There was greater amplitude variation of the curves when $t < 0.5$. Participation coefficient curves followed a complementary path, with an upwards-sloping shape as t increased: they then levelled off at around $t = 0.4$ and remained relatively flat thereafter.

We then compared various alignment methods, including no alignment, in terms of their ability to predict executive function. This process involved fitting Model (2.2), where the outcome y was

executive function and the covariate $m_i(\phi_i^{-1}(t_i^*))$ was the aligned participation coefficient or modularity curve. As in the simulations, we compared supervised warping (model-first and warp-first RAFT) with *registr* and unsupervised warping methods. Because the true aligned curves and model coefficients are not observed, the performance of the alignment methods was gauged using the MSE of y and the corresponding R-squared.

Supervised alignment was performed using either the auxiliary variable $z = $ age (years) or $z = $ motion (mm), as both are thought to be related to observed FC. As before, the tuning parameters (λ_1, λ_2) in the supervised alignment method were selected using the method in Section 2.6.1. The data were split into 5 folds, and for each iteration (out of 5), one fold was the tuning set and the other 4 folds were the testing set on which the MSE(y) and R-squared were evaluated. This process ensured that any data used to tune (λ_1, λ_2) in one iteration could later be re-used as testing data.

When the auxiliary warping variable z is age, then the curve alignment with RAFT resulted in a model with lowest MSE(y) and consequently highest R-squared (Figure 5). By comparison, unsupervised methods did not significantly improve performance beyond that of the unaligned curves. This behavior was observed for both the modularity and participation coefficient curves. When the auxiliary warping variable z is motion, then no method outperformed the others in predicting executive function, in that they each had a high MSE(y) and R-squared approximately equal to 0. In other words, alignment using motion did not improve model performance beyond no alignment whatsoever, and in either case the model fit was poor.

We also asked if the functional predictors provide information beyond z by including the latter in the regression model for predicting y. When a linear term for z_i was included in the model so that

$$y_i = \beta_0 + \int \beta_2(t)m_i\left(\phi_i^{-1}\left(t_i^*\right)\right)dt + \beta_3 z_i + \varepsilon_i,$$

then the RAFT alignment still out-performed other methods for when z is age but not for when z is motion (Figure S.3). However, when a non-linear smooth term $s(z_i)$ using penalized regression splines was included in the model so that

$$y_i = \beta_0 + \int \beta_2(t) m_i \left(\phi_i^{-1} \left(t_i^* \right) \right) dt + s \left(z_i \right) + \varepsilon_i,$$

then the RAFT alignment did not result in performance improvements (Figure S.4). In other words, there was similar performance when predicting executive function using either solely the curves warped using age, or the combination of the aligned curves and the highly flexible smooth age term $s(z_i)$.

4.1   *Windowed Thresholding*

The proportional thresholding procedure used to create the sequence of thresholded networks (Section 2.2 and Figure 1), and thus the function-valued network diagnostic curves, has the potential drawback that weaker edges are always analyzed in tandem with stronger edges. This process can conceal organizational patterns that are important to executive function but that occur only in the weakest edges. Therefore, we also considered an alternative *windowed thresholding* approach, which partitions the edges into bins based on their weight (Bassett *and others*, 2012; Lohse *and others*, 2014; Schwarz and McGonigle, 2011). Within each bin, the edges form a network on which the network diagnostic can be calculated, and the network diagnostic curve is a function of the bins (e.g., the bin's end- or mid-points).

As in Bassett *and others* (2012), we considered windows based on percentile bins, so that a windowed threshold $s = 0.01$ corresponds to the top percentile of edges by strength, $s = 0.02$ is the next highest percentile of edges, and so on. In contrast to proportional-threshold modularity curves, windowed-threshold modularity curves showed that all but the strongest edges had a modularity close to 0 (Figure S.5). The participation coefficient curves in the overall sample

appeared similar under both types of thresholding, with age-related patterns similar to those observed in proportional thresholding. Overall, both types of thresholding revealed complementary information: stronger edges exhibited more variation in modularity and participation coefficient between individuals.

5. DISCUSSION

In this paper, we represented network models of the brain as functions that describe their multi-scale topology. We modeled the association between these function-valued data and executive function, age, and motion through functional regression. To address possible misalignment in the data, we proposed RAFT, a novel approach to combine functional regression with a *supervised* alignment step that incorporates information from auxiliary variables such as age. Through simulations, we investigated the impact of the alignment method on the accuracy of downstream models, thereby demonstrating that supervised alignment often results in functional regression coefficient estimates that are more accurate than—and no worse than—those obtained without any alignment. Moreover, across different simulation settings, RAFT performed well more consistently than the other alignment methods.

While the unsupervised methods sometimes worked well in simulations, they did not improve prediction of executive function in the PNC data. When z encoded age as the auxiliary variable, age-aligned RAFT curves on their own were more predictive of executive function compared to the unaligned curves and all other alignment methods (Figure 5). However, we note that this excellent performance may be due to the high correlation between z and y ($\rho = 0.64$)—any warping of the data designed to maximize prediction accuracy of z will naturally also predict y well.

Therefore, we investigated if curves that were aligned using z to reflect motion as the auxiliary variable would improve prediction of executive function. Unlike age, motion and executive

function are not strongly correlated (ρ= -0.13), but we anticipated that motion-aligned curves would still improve prediction, as previous studies have established the impact of motion on FC estimates (Power *and others*, 2012). However, this was not the case, and all alignment methods (including no alignment) led to low predictive power in the downstream model (Figure 5), perhaps because motion showed only slight nonlinear and linear associations with the network diagnostics (Figure S.7 and Figure S.8). Therefore, warping the curves did not benefit from any additional information from the motion variable. Another reason could be the limited signal from the FC curves, especially when $t > 0.5$. Curves with flat regions, such as the right tail of both the modularity and participation coefficient curves, could have led to identifiability issues during warping, since in flat regions there are multiple (infinitely many) warping functions that can give rise to the same alignment.

While the main subject of our analysis was network diagnostic curves obtained from a cumulative, proportional thresholding approach, we had also repeated our analyses in curves that were generated by windowed thresholding. The resulting prediction performance was similar to that of the proportional-threshold curves (Figure S.6): namely, the functional data themselves could not explain most of the variability in executive function, unless aligned by age.

There are several limitations of our method. First and most importantly, the model for z in Step 2 of the supervised alignment method is inherently overfit. This overfitting derives from the fact that the warping functions are flexible enough that, even with heavy penalization, a small perturbation in the functional predictors can result in predictions $\hat{z}$ that perfectly overlap with the observed z. It is for this reason that we do not use the outcome of interest y itself to warp the curves, as explained in Section 2.4. Consequentially, curves aligned using z should not be used in downstream analyses where z is the outcome of interest. This observation also means that the variable z should be chosen such that its correlation with y is substantially less than 1. (In simulations, we found that correlations of up to around 0.8 still resulted in acceptable estimation

of the true association $\beta_2(t)$ between y and the aligned curves.) Otherwise, it is possible to predict y well using the aligned curves, even if no true association between y and the aligned curves exists (Figure 5). This prediction is possible because the curves are aligned such that they best predict z, and if y and z are similar, then they will also predict y (which we may have observed in the age-aligned curves in the PNC data). Thus, our method is most useful in situations where z is not associated with y, but is associated with the warping process. In that case, we can be more confident that any significant estimate of $\beta_2(t)$ in Model (2.3) indicates a true association between the curves and y.

Second, the functions ϕ_i^{-1} have at most one inflection point and may be too simple to align data with multiple features and complex misalignment mechanisms. In that case, B-splines or spline-like methods that join multiple CDF functions together at pre-determined knots may be a useful extension. Third, the coefficient functions represent the non-parametric relationship between y and the network diagnostic curves in their entirety. Because they are sensitive to the alignment method, coefficient functions estimated on data that were aligned differently are not comparable. Even within a given alignment method, interpretation requires extreme care. Template alignment methods require that the coefficient function be interpreted relative to the template curve. As such, we recommend interpreting these coefficient curves with caution. Finally, we proposed alignment as a possible solution to the problems outlined in (van den Heuvel *and others*, 2017); we did not compare our method to other pre-processing models that address the reasons for systematic differences in the distribution of functional connectivity edge weights (Afyouni *and others*, 2019).

Our work has several straightforward extensions. As the warping functions $\phi_i^{-1}(t)$ are themselves functional data, and may be related to the outcome of interest, we could consider including them in an additional term in Model (2.2):

$$y_i = \beta_1 + \int \beta_2(t) m_i \left(\phi_i^{-1}\left(t_i^*\right) \right) dt + \int \gamma(t) \phi_i^{-1}(t) dt + \varepsilon_i.$$

Another mode of future work could involve the estimation of a single warping function for two or more functional predictors simultaneously, such as $m_i(t)$ and $p_i(t)$, assuming that the warping mechanism is the same across network diagnostics. As alignment is highly relevant to time-varying data with periodic trends, future work could involve the application of our method to alternate domains, such as accelerometry and activity measurements from wearables (McDonnell *and others*, 2021). Finally, the intersection of topological data analysis and functional data analysis is not yet fully explored, and we look forward to more work at this fascinating juncture.

6. Software

The R code implementation of the proposed methods, both the unsupervised beta-cdf warping and RAFT, will be made publicly available on Github upon publication: `https://github.com/danni-tu/RAFT`.

7. Supplementary Material

Supplementary material is available online at `http://biostatistics.oxfordjournals.org`.

Acknowledgments

The authors thank Haochang Shou for helpful discussions and Ellyn Butler for help with data acquisition. This work was supported by the NIH grants R01 MH112847, R37 MH125829, R01 MH113550, and R01 MH120482. The Philadelphia Neurodevelopmental Cohort was supported by the National Institute of Mental Health grants MH089983 and MH089924.

Conflict of Interest: None declared.

References

ACHARD, SOPHIE. (2006, January). A resilient, low-frequency, small-world human brain functional network with highly connected association cortical hubs. *Journal of Neuroscience* **26**(1), 63–72.

AFYOUNI, SOROOSH, SMITH, STEPHEN M. AND NICHOLS, THOMAS E. (2019, October). Effective degrees of freedom of the pearson's correlation coefficient under autocorrelation. *NeuroImage* **199**, 609–625.

BASSETT, DANIELLE S., NELSON, BRENT G., MUELLER, BRYON A., CAMCHONG, JAZMIN AND LIM, KELVIN O. (2012, February). Altered resting state complexity in schizophrenia. *NeuroImage* **59**(3), 2196–2207.

BAUM, GRAHAM L., CIRIC, RASTKO, ROALF, DAVID R., BETZEL, RICHARD F., MOORE, TYLER M., SHINOHARA, RUSSELL T., KAHN, ARI E., VANDEKAR, SIMON N., RUPERT, PETRA E., QUARMLEY, MEGAN, COOK, PHILIP A., ELLIOTT, MARK A., RUPAREL, KOSHA, GUR, RAQUEL E., GUR, RUBEN C., BASSETT, DANIELLE S. *and others.* (2017, June). Modular segregation of structural brain networks supports the development of executive function in youth. *Current Biology* **27**(11), 1561–1572.e8.

BETZEL, RICHARD F. AND BASSETT, DANIELLE S. (2017, October). Multi-scale brain networks. *NeuroImage* **160**, 73–83.

BLONDEL, VINCENT D, GUILLAUME, JEAN-LOUP, LAMBIOTTE, RENAUD AND LEFEBVRE, ETIENNE. (2008, October). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment* **2008**(10), P10008.

BORDIER, CÉCILE, NICOLINI, CARLO AND BIFONE, ANGELO. (2017, August). Graph analysis

and modularity of brain functional connectivity networks: Searching for the optimal threshold. *Frontiers in Neuroscience* **11**.

BULLMORE, EDWARD T. AND BASSETT, DANIELLE S. (2011, April). Brain graphs: Graphical models of the human brain connectome. *Annual Review of Clinical Psychology* **7**(1), 113–140.

CARROLL, CODY, MÜLLER, HANS-GEORG AND KNEIP, ALOIS. (2020, August). Cross-component registration for multivariate functional data, with application to growth curves. *Biometrics* **77**(3), 839–851.

CIRIC, RASTKO, WOLF, DANIEL H., POWER, JONATHAN D., ROALF, DAVID R., BAUM, GRAHAM L., RUPAREL, KOSHA, SHINOHARA, RUSSELL T., ELLIOTT, MARK A., EICKHOFF, SIMON B., DAVATZIKOS, CHRISTOS, GUR, RUBEN C., GUR, RAQUEL E., BASSETT, DANIELLE S. *and others.* (2017, July). Benchmarking of participant-level confound regression strategies for the control of motion artifact in studies of functional connectivity. *NeuroImage* **154**, 174–187.

CUI, ZAIXU, LI, HONGMING, XIA, CEDRIC H., LARSEN, BART, ADEBIMPE, AZEEZ, BAUM, GRAHAM L., CIESLAK, MATT, GUR, RAQUEL E., GUR, RUBEN C., MOORE, TYLER M., OATHES, DESMOND J., ALEXANDER-BLOCH, AARON F., RAZNAHAN, ARMIN, ROALF, DAVID R., SHINOHARA, RUSSELL T., WOLF, DANIEL H., DAVATZIKOS, CHRISTOS, BASSETT, DANIELLE S., FAIR, DAMIEN A., FAN, YONG *and others.* (2020, April). Individual variation in functional topography of association networks in youth. *Neuron* **106**(2), 340–353.e8.

FAIR, DAMIEN A., COHEN, ALEXANDER L., POWER, JONATHAN D., DOSENBACH, NICO U. F., CHURCH, JESSICA A., MIEZIN, FRANCIS M., SCHLAGGAR, BRADLEY L. AND PETERSEN, STEVEN E. (2009, May). Functional brain networks develop from a "local to distributed" organization. *PLoS Computational Biology* **5**(5), e1000381.

FORTUNATO, SANTO. (2010, February). Community detection in graphs. *Physics Reports* **486**(3-5), 75–174.

FU, ERIC AND HECKMAN, NANCY. (2019, March). Model-based curve registration via stochastic approximation EM algorithm. *Computational Statistics and Data Analysis* **131**, 159–175.

GALLEN, COURTNEY L. AND D'ESPOSITO, MARK. (2019, April). Brain modularity: A biomarker of intervention-related plasticity. *Trends in Cognitive Sciences* **23**(4), 293–304.

GAMBOA, O.L., TAGLIAZUCCHI, E., VON WEGNER, F., JURCOANE, A., WAHL, M., LAUFS, H. AND ZIEMANN, U. (2014, July). Working memory performance of early MS patients correlates inversely with modularity increases in resting state functional connectivity networks. *NeuroImage* **94**, 385–395.

GARCIA, JAVIER O., ASHOURVAN, ARIAN, MULDOON, SARAH, VETTEL, JEAN M. AND BASSETT, DANIELLE S. (2018, May). Applications of community detection techniques to brain graphs: Algorithmic considerations and implications for neural function. *Proceedings of the IEEE* **106**(5), 846–867.

GARRISON, KATHLEEN A., SCHEINOST, DUSTIN, FINN, EMILY S., SHEN, XILIN AND CONSTABLE, R. TODD. (2015, September). The (in)stability of functional brain network measures across thresholds. *NeuroImage* **118**, 651–661.

GATES, KATHLEEN M., HENRY, TEAGUE, STEINLEY, DOUG AND FAIR, DAMIEN A. (2016, November). A monte carlo evaluation of weighted community detection algorithms. *Frontiers in Neuroinformatics* **10**.

GEERLIGS, LINDA, RENKEN, REMCO J., SALIASI, EMI, MAURITS, NATASHA M. AND LORIST, MONICQUE M. (2014, February). A brain-wide study of age-related changes in functional connectivity. *Cerebral Cortex* **25**(7), 1987–1999.

28   REFERENCES

GERVINI, D. (2014, December). Warped functional regression. *Biometrika* **102**(1), 1–14.

GIUSTI, CHAD, PASTALKOVA, EVA, CURTO, CARINA AND ITSKOV, VLADIMIR. (2015, October). Clique topology reveals intrinsic geometric structure in neural correlations. *Proceedings of the National Academy of Sciences* **112**(44), 13455–13460.

GOLDSMITH, JEFF, BOBB, JENNIFER, CRAINICEANU, CIPRIAN M., CAFFO, BRIAN AND REICH, DANIEL. (2011, January). Penalized functional regression. *Journal of Computational and Graphical Statistics* **20**(4), 830–851.

GOLDSMITH, JEFF, SCHEIPL, FABIAN, HUANG, LEI, WROBEL, JULIA, GELLAR, J, HAREZLAK, J, MCLEAN, MW, SWIHART, B, XIAO, L, CRAINICEANU, C *and others*. (2016). Refund: Regression with functional data. *R package version 0.1-16* **572**.

GU, SHI, SATTERTHWAITE, THEODORE D., MEDAGLIA, JOHN D., YANG, MUZHI, GUR, RAQUEL E., GUR, RUBEN C. AND BASSETT, DANIELLE S. (2015, October). Emergence of system roles in normative neurodevelopment. *Proceedings of the National Academy of Sciences* **112**(44), 13681–13686.

GU, SHI, XIA, CEDRIC HUCHUAN, CIRIC, RASTKO, MOORE, TYLER M, GUR, RUBEN C, GUR, RAQUEL E, SATTERTHWAITE, THEODORE D AND BASSETT, DANIELLE S. (2019, August). Unifying the notions of modularity and core–periphery structure in functional brain networks during youth. *Cerebral Cortex* **30**(3), 1087–1102.

GUIMERÀ, ROGER AND AMARAL, LUÍS A. NUNES. (2005, February). Functional cartography of complex metabolic networks. *Nature* **433**(7028), 895–900.

GUR, RUBEN C., RICHARD, JAN, CALKINS, MONICA E., CHIAVACCI, ROSETTA, HANSEN, JOHN A., BILKER, WARREN B., LOUGHEAD, JAMES, CONNOLLY, JOHN J., QIU, HAIJUN, MENTCH, FRANK D., ABOU-SLEIMAN, PATRICK M., HAKONARSON, HAKON *and others*.

(2012, March). Age group and sex differences in performance on a computerized neurocognitive battery in children age 8-21. *Neuropsychology* **26**(2), 251–265.

HADJIPANTELIS, P. Z., ASTON, J. A. D., MÜLLER, H. G. AND EVANS, J. P. (2015, April). Unifying amplitude and phase analysis: A compositional data approach to functional multivariate mixed-effects modeling of mandarin chinese. *Journal of the American Statistical Association* **110**(510), 545–559.

LOHSE, CHRISTIAN, BASSETT, DANIELLE S., LIM, KELVIN O. AND CARLSON, JEAN M. (2014, October). Resolving anatomical and functional structure in human brain organization: Identifying mesoscale organization in weighted network representations. *PLoS Computational Biology* **10**(10), e1003712.

MARRON, J. S., RAMSAY, JAMES O., SANGALLI, LAURA M. AND SRIVASTAVA, ANUJ. (2015, November). Functional data analysis of amplitude and phase variation. *Statistical Science* **30**(4).

MCDONNELL, ERIN I., ZIPUNNIKOV, VADIM, SCHRACK, JENNIFER A., GOLDSMITH, JEFF AND WROBEL, JULIA. (2021, May). Registration of 24-hour accelerometric rest-activity profiles and its application to human chronotypes. *Biological Rhythm Research* **53**(8), 1299–1319.

MOORE, TYLER M., REISE, STEVEN P., GUR, RAQUEL E., HAKONARSON, HAKON AND GUR, RUBEN C. (2015, March). Psychometric properties of the penn computerized neurocognitive battery. *Neuropsychology* **29**(2), 235–246.

MORGAN, SARAH E., WHITE, SIMON R., BULLMORE, EDWARD T. AND VÉRTES, PETRA E. (2018, September). A network neuroscience approach to typical and atypical brain development. *Biological Psychiatry: Cognitive Neuroscience and Neuroimaging* **3**(9), 754–766.

Muldoon, Sarah Feldt, Bridgeford, Eric W. and Bassett, Danielle S. (2016, February). Small-world propensity and weighted brain networks. *Scientific Reports* **6**(1).

Newman, Mark E. J. and Girvan, Michelle. (2004, February). Finding and evaluating community structure in networks. *Physical Review E* **69**(2).

Palaniyappan, Lena, Marques, Tiago Reis, Taylor, Heather, Mondelli, Valeria, Reinders, A. A. T. Simone, Bonaccorso, Stefania, Giordano, Annalisa, DiForti, Marta, Simmons, Andrew, David, Anthony S., Pariante, Carmine M., Murray, Robin M. *and others.* (2016, June). Globally efficient brain organization and treatment response in psychosis: A connectomic study of gyrification. *Schizophrenia Bulletin* **42**(6), 1446–1456.

Power, Jonathan D., Barnes, Kelly A., Snyder, Abraham Z., Schlaggar, Bradley L. and Petersen, Steven E. (2012, February). Spurious but systematic correlations in functional connectivity MRI networks arise from subject motion. *NeuroImage* **59**(3), 2142–2154.

Ramsay, James O. and Silverman, Bernard W. (2005). *Functional Data Analysis*. Springer New York.

Reiss, Philip T., Miller, David L., Wu, Pei-Shien and Hua, Wen-Yu. (2017, April). Penalized nonparametric scalar-on-function regression via principal coordinates. *Journal of Computational and Graphical Statistics* **26**(3), 569–578.

Satterthwaite, Theodore D., Connolly, John J., Ruparel, Kosha, Calkins, Monica E., Jackson, Chad, Elliott, Mark A., Roalf, David R., Hopson, Ryan, Prabhakaran, Karthik, Behr, Meckenzie, Qiu, Haijun, Mentch, Frank D., Chiavacci, Rosetta, Sleiman, Patrick M.A., Gur, Ruben C., Hakonarson, Hakon *and others.*

(2016, January). The philadelphia neurodevelopmental cohort: A publicly available resource for the study of normal and abnormal brain development in youth. *NeuroImage* **124**, 1115–1119.

SATTERTHWAITE, THEODORE D., ELLIOTT, MARK A., GERRATY, RAPHAEL T., RUPAREL, KOSHA, LOUGHEAD, JAMES, CALKINS, MONICA E., EICKHOFF, SIMON B., HAKONARSON, HAKON, GUR, RUBEN C., GUR, RAQUEL E. *and others*. (2013, January). An improved framework for confound regression and filtering for control of motion artifact in the preprocessing of resting-state functional connectivity data. *NeuroImage* **64**, 240–256.

SATTERTHWAITE, THEODORE D., ELLIOTT, MARK A., RUPAREL, KOSHA, LOUGHEAD, JAMES, PRABHAKARAN, KARTHIK, CALKINS, MONICA E., HOPSON, RYAN, JACKSON, CHAD, KEEFE, JACK, RILEY, MARISA, MENTCH, FRANK D., SLEIMAN, PATRICK, VERMA, RAGINI, DAVATZIKOS, CHRISTOS, HAKONARSON, HAKON, GUR, RUBEN C. *and others*. (2014, February). Neuroimaging of the philadelphia neurodevelopmental cohort. *NeuroImage* **86**, 544–553.

SCHAEFER, ALEXANDER, KONG, RU, GORDON, EVAN M, LAUMANN, TIMOTHY O, ZUO, XI-NIAN, HOLMES, AVRAM J, EICKHOFF, SIMON B AND YEO, B T THOMAS. (2017, July). Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity MRI. *Cerebral Cortex* **28**(9), 3095–3114.

SCHEINOST, D., BENJAMIN, J., LACADIE, C.M., VOHR, B., SCHNEIDER, K.C., MENT, L.R., PAPADEMETRIS, X. AND CONSTABLE, R.T. (2012, September). The intrinsic connectivity distribution: A novel contrast measure reflecting voxel level functional connectivity. *NeuroImage* **62**(3), 1510–1519.

SCHWARZ, ADAM J. AND MCGONIGLE, JOHN. (2011, April). Negative edges and soft thresholding in complex network analysis of resting state functional connectivity data. *NeuroImage* **55**(3), 1132–1146.

32   REFERENCES

SINGH, MANPREET K., KESLER, SHELLI R., HOSSEINI, S.M. HADI, KELLEY, RYAN G., AM-
ATYA, DEBHA, HAMILTON, J. PAUL, CHEN, MICHAEL C. AND GOTLIB, IAN H. (2013, Novem-
ber). Anomalous gray matter structural networks in major depressive disorder. *Biological
Psychiatry* **74**(10), 777–785.

SPORNS, OLAF AND BETZEL, RICHARD F. (2016, January). Modular brain networks. *Annual
Review of Psychology* **67**(1), 613–640.

SRIVASTAVA, ANUJ, WU, WEI, KURTEK, SEBASTIAN, KLASSEN, ERIC AND MARRON, J. S.
(2011). Registration of functional data using fisher-rao metric.

TOOLEY, URSULA A, MACKEY, ALLYSON P, CIRIC, RASTKO, RUPAREL, KOSHA, MOORE,
TYLER M, GUR, RUBEN C, GUR, RAQUEL E, SATTERTHWAITE, THEODORE D AND BAS-
SETT, DANIELLE S. (2019, April). Associations between neighborhood SES and functional
brain network development. *Cerebral Cortex* **30**(1), 1–19.

TUCKER, J. DEREK, LEWIS, JOHN R. AND SRIVASTAVA, ANUJ. (2018, December). Elastic
functional principal component regression. *Statistical Analysis and Data Mining: The ASA
Data Science Journal* **12**(2), 101–115.

VAN DEN HEUVEL, MARTIJN P., DE LANGE, SIEMON C., ZALESKY, ANDREW, SEGUIN, CAIO,
YEO, B.T. THOMAS AND SCHMIDT, RUBEN. (2017, May). Proportional thresholding in
resting-state fMRI functional connectivity networks and consequences for patient-control con-
nectome studies: Issues and recommendations. *NeuroImage* **152**, 437–449.

VAN WIJK, BERNADETTE C. M., STAM, CORNELIS J. AND DAFFERTSHOFER, ANDREAS. (2010,
October). Comparing brain networks of different size and connectivity density using graph
theory. *PLoS ONE* **5**(10), e13701.

WANG, JINHUI, WANG, LIANG, ZANG, YUFENG, YANG, HONG, TANG, HEHAN, GONG, QIY-

ONG, CHEN, ZHANG, ZHU, CHAOZHE AND HE, YONG. (2009, May). Parcellation-dependent small-world brain functional networks: A resting-state fMRI study. *Human Brain Mapping* **30**(5), 1511–1523.

WANG, JANE-LING, CHIOU, JENG-MIN AND MÜLLER, HANS-GEORG. (2016, June). Functional data analysis. *Annual Review of Statistics and Its Application* **3**(1), 257–295.

WROBEL, JULIA. (2018, February). register: Registration for exponential family functional data. *The Journal of Open Source Software* **3**(22), 557.

WROBEL, JULIA, ZIPUNNIKOV, VADIM, SCHRACK, JENNIFER AND GOLDSMITH, JEFF. (2018, September). Registration for exponential family functional data. *Biometrics* **75**(1), 48–57.

YEO, B. T. THOMAS, KRIENEN, FENNA M., SEPULCRE, JORGE, SABUNCU, MERT R., LASHKARI, DANIAL, HOLLINSHEAD, MARISA, ROFFMAN, JOSHUA L., SMOLLER, JORDAN W., ZÖLLEI, LILLA, POLIMENI, JONATHAN R., FISCHL, BRUCE, LIU, HESHENG *and others*. (2011, September). The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of Neurophysiology* **106**(3), 1125–1165.

ZALESKY, ANDREW, FORNITO, ALEX AND BULLMORE, ED. (2012, May). On the use of correlation as a measure of network connectivity. *NeuroImage* **60**(4), 2096–2106.

Fig. 1. Network diagnostic curves represent graph topology at multiple scales. For any adjacency matrix, the threshold $t \in [0, 1]$ represents the proportion of strongest edges to keep, which defines a sparser weighted network. When $t = 0$, the resulting network is the set of disconnected nodes. As t increases, edges are added to those nodes in decreasing order of strength. For each network, various network diagnostics describing the topology of edge connections can be evaluated (e.g., modularity). Therefore, calculating the network diagnostic at multiple values of $t \in [0, 1]$ results in a network diagnostic curve.

Fig. 2. Forms of variation in functional data. Left: For network diagnostic curves that are functions of t, amplitude variation refers to differences in the vertical distance between curves at fixed values of t. Right: For curves with similar features, phase variation manifests as differences in the "timing" of those features, i.e., horizontal misalignment.

Fig. 3. In simulated data, alignment improves the accuracy of model coefficient estimation beyond using the unwarped curves, and towards the scenario where the true curves are known. The data generating mechanism consisted of a set of true $\beta_1(t)$ and $\beta_2(t)$ functions describing the association between the true aligned curves and z and y, respectively, where sinusoidal noise (Panel A) and Gaussian noise (Panel B) were added to the functions to induce amplitude variation. This process was repeated for curves with added sinusoidal noise (Panel C) and Gaussian noise (Panel D) under a different set of true $\beta_1(t)$ and $\beta_2(t)$ functions. For the supervised alignment methods, the tuning parameters λ_1, λ_2 were chosen in that order, and using the automated method in 2.6.1. Performance was assessed using $\mathrm{MISE}(\beta_2(t))$ and $\mathrm{MSE}(y)$. Box-and-whisker plots show the median, 25th, and 75th percentile for the box, and 1.5 $*$ (Interquartile Range) for the whiskers. Overall, we found that RAFT most consistently improved prediction performance, even when the variables z and y were not linearly related (Panels B and D), while the unsupervised FPCA-based method *registr* worked often but occasionally performed worse than using the unwarped curves, likely due to the increased flexibility in modeling the warping functions.

Fig. 4. Data from the Philadelphia Neurodevelopmental Cohort (Satterthwaite *and others*, 2016). Left column: The distribution of functional connectivity (FC) strength, which determine network edge weights, is related to age (Panel A) but not motion (Panel B). Middle and right columns: Modularity and participation coefficient given the 7 communities defined in Yeo *and others* (2011) as a function of t. The color of the curve corresponds to age (Panel A; darker = younger) or motion (Panel B; darker = less motion).

Fig. 5. In data from the Philadelphia Neurodevelopmental Cohort (Satterthwaite *and others*, 2016), RAFT alignment of the modularity and participation coefficient curves improved prediction of executive function when the auxiliary variable was age, but not when the auxiliary variable was motion. We considered modularity (left column) and participation coefficient (right column) using communities defined by the 7-community parcellation described in (Yeo *and others*, 2011); age was measured in years, and motion measured as average relative RMS displacement in millimeters. (Panel A) The superior performance of RAFT when z is age could be due to multiple factors: age has a strong association with both the network diagnostic curves (Figure S.7 and Figure S.8) and executive function. Therefore, warping the curves to predict age well will likely improve prediction of y. Another possibility is that age-related misalignment has obscured the true association between executive function and network diagnostic curves, which RAFT has recovered. (Panel B) The similarly poor performance of all alignment methods, including RAFT, when z is motion could be due to the weak association between z and the network diagnostics, leading to a warping that look similar to the unsupervised case.