Learning a deep language model for microbiomes: the power of large scale unlabeled microbiome data

Quintin Pope[1☯], Rohan Varma[2☯], Chritine Tataru [3], Maude David[3,4], Xiaoli Fern[1]

1 School of Electrical Engineering and Computer Science, Oregon State University, Corvallis, Oregon, United States

2 Computer Science and Engineering, University of Michigan, Ann Arbor, Michigan, United States

3 Department of Microbiology, Oregon State University, Corvallis, Oregon,United States

4 Department of Pharmaceutical Sciences, Oregon State University, Corvallis, Oregon, United States

☯These authors contributed equally to this work.

*popeq@oregonstate.edu

Abstract

We use open source human gut microbiome data to learn a microbial "language" model by adapting techniques from Natural Language Processing (NLP). Our microbial "language" model is trained in a self-supervised fashion (i.e., without additional external labels) to capture the interactions among different microbial taxa and the common compositional patterns in microbial communities. The learned model produces contextualized taxa representations that allow a single microbial taxon to be represented differently according to the specific microbial environment it appears in. The model further provides a sample representation by collectively interpreting different microbial taxa in the sample and their interactions as a whole. We show that, compared to baseline representations, our sample representation consistently leads to improved performance for multiple prediction tasks including predicting Irritable Bowel Disease (IBD) and diet patterns. Coupled with a simple ensemble strategy, it produces a highly

robust IBD prediction model that generalizes well to microbiome data independently collected from different populations with substantial distribution shift.

We visualize the contextualized taxa representations and find that they exhibit meaningful phylum-level structure, despite never exposing the model to such a signal. Finally, we apply an interpretation method to highlight microbial taxa that are particularly influential in driving our model's predictions for IBD.

Author summary

Human microbiomes and their interactions with various body systems have been linked to a wide range of diseases and lifestyle variables. To understand these links, citizen science projects such as the American Gut Project (AGP) have provided large open-source datasets for microbiome investigation. In this work we leverage such open-source data and learn a "language" model for human gut microbiomes using techniques derived from natural language processing. We train the "language" model to capture the interactions among different microbial taxa and the common compositional patterns that shape gut microbiome communities. By considering the entirety of taxa within a sample and their interactions, our model produces a representation that enables contextualized interpretation of individual microbial taxa within their microbial environment. We demonstrate that our sample representation enhances prediction performance compared to baseline methods across multiple microbiome tasks including prediction of Irritable Bowel Disease (IBD) and diet patterns. Furthermore, our learned representation yields a robust IBD prediction model that generalizes well to independent data collected from different populations. To gain insight into our model's workings, we present interpretation results that showcase its ability to learn biologically meaningful representations.

1 Introduction

Identifiable features of the human microbiome and its interactions with various body systems have been associated with a wide range of diseases, including cancer [1], depression [2, 3] and inflammatory bowel disease [4–6]. As our knowledge of such

connections has advanced, research on the human microbiome has undergone a shift in focus, moving from establishing links to unraveling the underlying mechanisms and utilizing them to develop clinical interventions [7]. This transition has sparked interest in applying statistical methods to microbiome data, leading to the launch of open source projects such as the American Gut Project (AGP) and Human Food Project (HFP), which provide open source datasets for microbiome investigation [8]. These repositories offer data in the form of raw genetic reads, which, even after being processed into taxa counts, still present thousands of features per sample. Consequently, researchers often employ dimension reduction techniques to transform this data into a more manageable feature space.

Significantly, the relevance of microbes to any particular analysis is often intertwined with the presence and potential interactions of other microbes in the environment. However, common techniques for reducing microbiome data dimensions — such as binning based on phylogenetic relationships [9, 10], clustering by gene similarity [11], or using PCA and other techniques [12] — don't account for the interactions between taxa when producing lower dimensional representations of samples. Consequently, a significant challenge in microbiome data analysis is to produce lower dimension representations (embeddings) of samples that not only take into account the presence of specific taxa but also their interactions and overall functioning as a whole.

Fortunately, a similar challenge has been investigated in the natural language processing (NLP) domain, which shares many similarities with the microbiome domain. Just as a sample comprises numerous microbes, a sentence consists of multiple words. Similarly, certain microbes hold greater relevance for specific analyses, while certain words are more important for different NLP tasks. Furthermore, just as a microbe can assume different functional roles under varying conditions, a word can possess different meanings in different contexts.

Given the strong similarities between the two domains and the shared goal of producing quality lower-dimensional sample / sentence representations, there is a growing interest in applying NLP techniques to microbiome analysis. Notably, previous work has successfully applied NLP word embedding algorithms to microbiome data, generating taxa embeddings that have shown promising results surpassing the performance of traditional dimension reduction techniques like PCA for various

microbiome prediction tasks [13].

Specifically, [13] apply the GloVe (Global Vectors for Word Representation) embedding algorithm [14] to co-occurrence data derived from the AGP dataset. GloVe maps each taxon in the vocabulary to a vector representation, and optimizes those vectors such that the inner product of any two vectors will match the log of the co-occurrence rate of the associated pair of taxa.

However, this prior work [13] has several limitations. First, the embeddings are learned based on aggregated global microbe-to-microbe co-occurrence statistics — in reality, microbe interactions can be dynamic and context-dependent. Second, given a sample containing many taxa, the embedding for the sample is computed by taking an abundance-weighted-average of the taxa embeddings without considering the context-specific roles of individual microbes in the sample. Similar to how the word "fly" changes from an insect in "I caught a fly" to an action in "I like to fly" based on context, the role of a bacteria can also shift based on its context and interactions. For example, susceptibility to infection with Campylobacter jejuni was shown to depend on the species composition of the microbiota [15].

Transformers, a powerful and flexible machine learning architecture originally developed for NLP [16], provides a potential solution to above issues. Past work [17–21] has applied transformers to biological data. However, such work has focused on learning a sequence encoder for representing DNA [21] or, more commonly, protein amino acid sequences [17–20] (e.g., each token might represent a k-mer in such a sequence). In contrast, we focus on representing entire microbial communities and their interactions, using each token to represent a single microbe in such a community.

We present the first use of transformers to learn representations of microbiome at the taxa level by adapting "self-supervised" pre-training techniques from NLP, allowing the model to learn from vast amounts of unlabeled 16S microbiome data and mitigating the required amount of expensive labeled data. The pre-trained models can be viewed as a form of "language model" for microbiome data, capturing the inherent composition rules of microbial communities, which we can easily adapt to downstream prediction tasks with a smaller amount of labeled "finetuning" data.

We show that using a transformer model pre-trained on data from the American Gut Project (AGP) as the starting point, we can achieve state of the art performance for

multiple downstream host phenotype prediction tasks including IBD disease state prediction. These results showcase the remarkable capability of the pre-trained microbial "language" model in generating enhanced representation of the microbiome.

Focusing on the IBD prediction task, we demonstrate that our IBD prediction model, trained on the IBD data from the American Gut Project, with a simple ensemble strategy, exhibits robust generalization across several IBD studies with notable distributional shifts. We further visualize the contextualized taxa embeddings produced by our pre-trained language model and show that they capture biologically meaningful information. Finally, we analyze the learned IBD prediction model to identify taxa that strongly influence the model's prediction.

2 Materials and Methods

We begin by introducing the general workflow of applying a transformer model for generating a sample embedding (Fig. 1) and explaining each step of the work flow, including a detailed look into the transformer architecture. We then explain how we perform the pretraining, followed by finetuning for specific down stream tasks (Fig. 2). This section will also explain how we identify those taxa that most affect the model's classification decisions (Eq. 1) and conclude with a description of the datasets used in this paper.

2.1 Transformers for microbiome data: workflow overview

Since their introduction in 2017, [16] transformers have emerged as one of the most powerful classes of neural models invented to date, demonstrating state-of-the-art performance in many domains, though different tasks and data types require specific adaptations. Figure 1 summarizes the basic workflow of applying transformer to microbiome data for generating sample representations and context-sensitive taxa embeddings.

Preprocessing steps.

We assume that microbiome samples are represented as vectors of relative taxa abundances (Fig. 1A). To prepare our input for the transformer model, we perform a

Fig 1. Workflow of using a transformer model for generating sample embedding/classification and context sensitive taxa embeddings. The inputs (A), which are samples represented as relative abundance vectors, first go through the preprocessing step (B) to generate text-like inputs (C) for the transformer model (D). The transformer model generates a sample embedding (h_{cls}) that goes through a sample classification layer (E) to produce task specific sample level predictions (F). The transformer model also generates context sensitive embedding (G) for each taxa in the sample. The same taxa appearing in different samples can have different embedding because of contextual differences.

¹⁴⁸

pre-process step (Fig. 1B) to transform the microbiome sample into 'text-like' inputs
(Fig. 1C). Specifically, we rank all the taxa present in the sample in decreasing order of
abundance to create an ordered list of taxa (truncated to contain no more than the 512
most abundant taxa). This step creates inputs that are analogous to texts, which are
ordered lists of tokens of variable length capped at 512. Transformer computational
costs increase with the square of their input lengths, so truncating inputs to at most 512
helps ensure our method remains computationally efficient to run, while affecting less
than 6% of the training data points.

Similar to what is done in processing textual inputs, we prepend a special
'classification (CLS)' token to our input list. We use the 'CLS' token's representation as
the final sample representation, which we treat as a summary of the full sample for
classification purposes.

The transformer model

Fig. 1D provides a sketch of our transformer architecture for performing a sample
classification task. The input to the transformer model is an ordered list of taxa. The
list first goes through an embedding layer and a projection layer. The output of the
projection layer then feeds into a sequence of multiple encoder blocks (we use 5 encoder
blocks in this work), where each encoder block produces a new representation based on
outputs of the previous block. Below we explain the individual components.

Embedding layer. The embedding layer maps from discrete tokens/taxa to their
corresponding vector representations. We use absolute positional embeddings [16] to
encode the abundance-based taxa order into the taxa embeddings. We experimented
with a variety of methods to incorporate abundance information, including different
positional embedding methods such as relative key [22] and relative key query [23]
methods, as well as using additional embedding dimensions to directly store abundance
values. We found little difference between these methods, and hence opted for the
absolute positional embeddings based on rank ordering for its relative simplicity.

We preset the embedding layer using the 100-dimensional GloVe taxa embedding
from [13], learned using the co-occurrence data from the AGP dataset, and keep it frozen

during training, except for the 'CLS' token embedding, which is initialized randomly

and trained during pre-training and fine-tuning. We do this to enable a more direct

comparison of the contextualized embeddings with the original vocabulary embedding

learned through GloVe, thus emphasizing the benefits of contextualized representations.

Projection layer.   The projection layer is a linear transformation from the

vocabulary embedding space to the model's hidden representation space. The projection

layer allows the model to process inputs of different dimensionality than the model's

hidden space. In this work, the projection layer projects from the 100 dimensional

vocabulary embedding into a richer 200 dimensional hidden space used by the model.

Encoder blocks.   This is where the transformer begins incorporating "context" into

the representation of each ASV in the sample. Here we provide an intuitive explanation

of the encoder block. Please see [16] for concrete mathematical definitions.

An encoder block consists of a multi-headed self-attention layer [16] and a fully

connected layer. The multi-headed attention layer computes a set of self-attention

scores (one per head). Each attention head can read and write to different subspaces in

the embeddings, and can track its own set of all-pairs interactions between every taxon

in the sample. This could allow different heads to track different collections of

statistical factors that influence community composition and metabolic functions.

The network modulates how much 'attention' is paid to each context taxon when

updating the representation for a particular taxon in the sample. For example, in the

context of language and given a sentence such as "I waved at the band, but they didn't

see me", a properly trained encoder block could update the embedding of word "they"

to reflect that it is referencing "the band". Analogously, in microbiome data, if bacteria

A performs a functional role conditioned on the presence of bacteria B, a properly

trained encoder block could update the embedding for bacteria A to reflect the presence

or absence of bacteria B.

Classification head.   We rely on a special 'CLS' token to summarize information

from all the other taxa / tokens. The CLS token then feeds into a classification head,

which is a standard two-layer feed forward neural network with 200 hidden nodes, to

produce a prediction for a specific classification task.

Fig 2. Training of the transformer model. Unlabeled microbiome data (A) is fed into a randomly initialized transformer (B) as inputs to the self-supervised pre-training process (C), which produces a pre-trained transformer that generates token-level classifications (D). We replace the token-level classification head with a randomly initialized CLS classification head (E), and use labeled microbiome data (F) to fine-tune the CLS classification head (G), which produces the fine-tuned transformer (H).

2.2 Transformer training

A critical challenge in applying complex deep learning models like transformers is the lack of large amounts of labeled training data. This can be addressed, however, using a technique referred to as self-supervised pre-training [24], which leverages readily available unlabeled data. In this work, we follow this approach and our training process is described in Fig. 2.

Pre-training

We begin with a randomly initialized transformer and first train a task-agnostic transformer using unlabeled data via self-supervised pre-training. Specifically, We use ELECTRA (Efficiently Learning an Encoder that Classifies Token Replacements Accurately) [25] to pre-train the encoder layers of the transformer model. We chose ELECTRA because it reaches comparable performance to other popular pre-training approaches (BERT [26] and its various flavors) while being computationally efficient.

The ELECTRA pre-training approach has two steps. The first step trains a generator model by randomly masking out 15% of taxa in microbiome samples and training the generator model to predict the missing taxa based on the remainder of the sample. For the second step, we use the trained generator to produce perturbed

Electra pre-training scheme

Fig 3. Electra pre-training diagram. A generator is trained to predict the masked taxa from a sample. A discriminator is trained to differentiate taxa filled in by the generator from the original taxa in the sample. Both use the same transformer architecture, and have token level classification heads. The generator token level classification head predicts the taxa ID whereas the discriminator token level classification head predicts the input taxa as "Real" or "Modified"

microbiome samples by replacing all the masked taxa with generator predictions and train a discriminator model to differentiate the original taxa of the sample from those replaced by the generator. Essentially, the generator attempts to fill in the masks with taxa predictions and the discriminator takes in the predicted sequence and attempts to identify which taxa are modified by the generator.

Both the generator and discriminator models have the same general architecture as shown in Fig. 3. To train the generator, the inputs are randomly corrupted by replacing 15% of taxa IDs with a special 'mask' ID, and the embedding of each masked taxa after the final encoder layer is fed into a classification head to predict the ID of the masked taxa.

To train the discriminator model, we take the masked sample completed by the generator as input to the discriminator, and feed the embedding of each taxon after the final encoder layer into a classification head that differentiates 'real' (original taxa) from 'modified' (generated taxa).

At the end of pre-training, we have two transformer models, the generator and discriminator. Following the practice of the original work, we use the encoder of the pre-trained discriminator as the initial model to be fine tuned for downstream tasks.

Pre-training details. We perform pre-training on 18,480 gut microbiome samples from the American Gut Project Database using the ELECTRA scheme as described above. Specifically, the generator was trained for 240 epochs to predict masked microbe embeddings, and checkpoints of the model were saved every 30 epochs. The discriminator was then trained on the replacement prediction task for 120 epochs with replacements generated by the increasingly trained generator. Specifically, for every 15 epochs of discriminator training, we replace the generator used to produce inputs for the discriminator with a stronger generator using the previously mentioned checkpoints. For example, the generator trained for 30 epochs provided inputs for the first 15 epochs of discriminator training. Then, for epochs 16-30, discriminator inputs were provided by the generator trained for 60 epochs. This was done to gradually ramp up the difficulty of the replacement prediction task.

Architecture and pre-training choices

We performed model architecture selection on the basis of pretraining results. We used 16,000 AGP samples to perform the training for both the generator and discriminator models, and used the remaining 2,480 samples as a hold-out validation set to decide the model architecture as well as the stopping point for the pretraining. Specifically, we observed that fewer than 5 layers of encoders leads to reduced capacity for the discriminator to differentiate between real and imputed taxa, whereas a larger number of layers does not produce noticeable benefit. We additionally chose to stop the discriminator's pretraining at 120 epochs because we observed its prediction accuracy on the holdout set stabilizing at that point, even when substituting in better-trained generators.

Task specific fine-tuning

Given a specific prediction task and the pre-trained discriminator, we remove the token classification head and add a new (randomly initialized) sequence classification head to the 'CLS' token. In addition to the embedding layer, we also freeze the parameters of the encoder blocks such that only the classification head and the projection layer were trained during fine-tuning. In other words, the pre-trained discriminator encoders are used as a universal encoder for representing microbiome samples for different prediction

tasks. Empirically we have found this practice reduces overfitting and produces more

robust generalization performance across different tasks.

Fine-tuning details. We perform fine-tuning using Stochastic Gradient Descent

(SGD) optimization with a learning rate of 0.01, momentum of 0.9, and the mean

squared error loss, which we found gave better results than the more traditional

negative cross-entropy loss, potentially because mean squared error is more robust to

noise and outliers. Furthermore, during training, we perform data augmentation by

randomly deleting 10% of the input taxa (meaning we randomly select one in ten of the

taxa in the data point and remove them from the input sequence, similar to the method

introduced by [27]) in each training sample to increase the robustness of the trained

model and reduce overfitting. The SGD optimization is performed for a total of 50

epochs on the training subsets of the labeled AGP data. As the labeled AGP datasets

have highly unbalanced labels (Table 1), we oversample the minority class to ensure the

model sees equal numbers of samples from each class. We use cross-validation on a

subset of the IBD data to tune the hyperparameters (random deletion percentage for

data augmentation and the choice of MSE vs the Cross Entropy loss) for fine-tuning.

2.3 Feature ablation attribution: finding the important taxa

We are interested in finding which microbial taxa the model relies on most for making a

positive or negative classification of the samples. To this end, we use feature ablation

attribution [28].

Consider a sample X containing n microbial taxa, which the model predicts as being

positive (for some property, e.g, IBD) with probability $M(X)$. Feature ablation

individually deletes each microbe taxon from the original X, then records how much

each taxon's removal reduces the model's predicted probability of being positive. We

average these changes across every sample in which a taxon appears, giving the

expected change in classification probability caused by deleting the taxon in question

from a random sample containing the taxon.

Given a dataset $\mathbf{D}$, let $\mathbf{D}_m$ denote the set of samples that contains a specific

microbe m, we can calculate m's attribution $a(m)$ as:

$$a(m) = \frac{1}{|\mathbf{D}_m|} \sum_{X \in \mathbf{D}_m} \mathbf{M}(X) - \mathbf{M}(X \setminus m) \tag{1}$$

where $\mathbf{M}(\cdot)$ denotes the model's probabilistic output for the given input and $X \setminus m$ denotes sample X with microbe m removed.

2.4   Datasets

We use three different datasets over the course of this study. We now describe them and summarize where they are used.

American Gut Project (AGP).   The American Gut Project (AGP) [8] is a crowdsourced microbiome data gathering effort. From it, we used 18,480 microbiome samples sequenced from the v4 hypervariable region of the 16S gene that were curated by the authors of [13]. The sample sequences come with metadata information on the subject the sample originates from, providing information about their diet, medical status on inflammatory bowel disease and more. We used all 18480 samples for our pre-training and relevant portions in our evaluation of downstream tasks. We now describe the three downstream tasks we ran experiments on.

- Inflammatory Bowel Disease (IBD). This task aims to predict whether a given microbiome sample belongs to an individual diagnosed with IBD or not. Samples originating from individuals with IBD are the positive class. Label information was drawn from AGP metadata producing 435 samples from IBD positive individuals and 8,136 healthy controls.

- Frequency of fruit in diet. This task aims to determine the frequency with which an individual consumes fruits based on their microbiome sample. The label is derived from AGP metadata, which ranks fruit consumption frequency on a one to five scale. For this experiment, samples ranked 3-5 are grouped to form the positive (frequent) class. Samples ranked 0-2 are considered negative (infrequent). Out of 6,540 AGP examples with fruit metadata, 4,026 were labeled positive.

- Frequency of vegetable in diet. This task aims to determine the frequency with which an individual consumes vegetables based on their microbiome sample. In

³²⁷ the same manner as the fruit task, label information was drawn from the AGP

³²⁸ metadata and frequency ranks from 0-5 were grouped to form the "frequent" (3-5)

³²⁹ and "infrequent" (0-2) classes. Out of 6,549 AGP examples containing vegetable

³³⁰ frequency metadata, 5654 were labeled positive.

³³¹ Table 1 provides the summary statistics for the three classification tasks. Table 2

³³² provides the run times and costs required to perform the pretraining and 5

³³³ training runs on the relevant portions of AGP.

Table 1. Three classification tasks derived from the AGP data and meta data.

Datasets	AGP	AGP-IBD	AGP-Fruit	AGP-Vegetable
# of samples	18480	8571	6540	6549
# of positive samples	N/A	435	4026	5654
# of negative samples	N/A	8136	1514	895

³³⁴ **Halfvarson (HV).** This dataset comes from an IBD study performed in [29]. We

³³⁵ used the curated dataset produced in [13], which contains 564 microbiome samples, with

³³⁶ 510 of them IBD positive.

³³⁷ **HMP2.** This dataset comes from an IBD study performed as part of phase 2 of the

³³⁸ Human Microbiome Project [30]. Again, we used the curated dataset produced in [13],

³³⁹ which contains 197 microbiome samples with 155 IBD positive examples.

Experiment name	Time (hr)	Cost ($)
Pretraining	23.43	9.44
Fine-tuning IBD (5 runs)	12.20	4.92
Fine-tuning Fruit (5 runs)	13.98	5.63
Fine-tuning Vegetable (5 runs)	10.74	4.33

Table 2. Runtimes and estimate costs of different experiments performed in this paper. All runtimes were measured on a single Nvidia A40 GPU, and costs are estimated based on the hourly price of $0.403 required to rent an Nvidia A40 from vast.ai as of 03/11/2024.

³⁴⁰ Because AGP-IBD, AGP-Fruit and AGP-Vegetable all derive from the larger AGP

³⁴¹ dataset, there is overlap between the data used for model development and the

³⁴² evaluation data that provide the results in Table 3. Specifically, both the GLoVE

³⁴³ embeddings from [13] and our own pretrained model are trained on the full 18,480

³⁴⁴ sample AGP dataset. However, neither process has access to any of the *labels* for

³⁴⁵ AGP-IBD, AGP-Fruit or AGP-Vegetable, only the unlabeled taxa sequences associated

with the samples. Additionally, each dataset includes at least some patients from which

multiple samples were taken. When both training and testing on AGP (as in Table 3),

we employ patient–level blocking of data between training, validation, and testing sets.

We ensure a fair comparison between our approach and the baselines by providing all

baselines with equivalent access to both unsupervised and labeled data across every

evaluation. Thus, any baseline with a representation learning phase will use the same

18,480 AGP samples as our method.

Data and code availability.   All data and code used in this study are available at

the following Dryad repository [31]: https://doi.org/10.5061/dryad.tb2rbp08p. File

descriptions and usage instructions are available in the repository's README.

3   Results and Discussions

3.1   Transformer representations outperform baselines on multiple microbiome tasks

In this section, we empirically compare transformer-produced sample representations

against a variety of baseline methods. Our baselines include **Weighted**, a simple

non-contextualized abundance-weighted-averaging of the GloVe embeddings from [13],

two classic dimension reduction based methods, and two deep learning based methods

introduced by [32], each of which performs dimension reduction using the sample

taxonomic abundance profiles as input features:

- **PCA**: Principle Component Analysis, configured to retain at least 99% of the variance.
- **RandP**: Random Gaussian Projection, relying on the Johnson-Lindenstrauss lemma [33] and implemented with scikit-learn [34] using eps 0.5.
- **AE**: An MLP-based autoencoder architecture [35], with two sizes: AE_{Best} (28.4M parameters) and AE_{Match} (7.2M parameters).
- **CAE**: An convolutional neural network-based autoencoder architecture [36], with two sizes: CAE_{Best} (12.3K parameters) and CAE_{Match} (102.6K parameters).

We used a reduced training set to quickly sweep the full range of model

hyperparameters described in [32] for their effectiveness in our setting. We found that the variational autoencoder failed to produce useful results, regardless of hyperparameters, and thus omitted this architecture in the comparisons. For the two remaining architecture (AE and CAE), we selected two sizes: one that achieved the best validation performance using the reduced training set (CAE_{Best}), and another that aims to match the parameter count of our own model (7.07M) as closely as possible.

For the baselines from [32], we adapt that work's random forest classification layer (and the range of hyperparameters to consider), because random forest most consistently achieved the best performance across the settings [32] explored.

As mentioned previously, our method applies a standard multi-layered perceptron (MLP) classifier to the transformer-produced sample representations for classification. To allow Weighted to act as a more consistent comparison with our model, we replaced the random forest classifier used in prior work with the same MLP classifier. We evaluate our method and the baseline methods using the AGP dataset on three microbiome classification tasks.

For each method and task, we perform 5 training runs. Our methods (meaning the Transformer and Weighted baseline) adopt the evaluation framework described in [32] to decide the stopping epoch: each run first blocks out 20% of the data to be used only for testing, then splits the remaining 80% into train and validation subsets to decide the best stopping epoch. Then, the 80% of non-test data is recombined into a single training set, and the model is re-finetuned from scratch on the non-test data using the discovered stopping epoch. Note that PCA, RandP, AE, and CAE baselines also use the train / validation split of non-test data from [32] to tune the random forest hyperparameters in addition to stopping epoch.

We consider two different evaluation criteria: the Area Under the ROC Curve (AUROC) and the Area Under the Precision-Recall curve (AUPR). We select these two metrics because they allow us to rigorously compare the discriminative capabilities of our models and baselines on unbalanced classes, without having to specify a particular threshold for what we consider a "positive" or "negative" classification.

Table 3 shows the performance of all methods on three tasks. We see that for the IBD and Fruit tasks, the transformer produced representation achieved substantially improved performance for both AUROC and AUPR. Performances on the Vegetable

⁴⁰⁶ task are much closer together across methods, especially between Weighted, PCA and

⁴⁰⁷ Transformer, with PCA even marginally edging out Transformer's AUPR score. This

⁴⁰⁸ confirms that our approach learns a transformer model that produces robust sample

⁴⁰⁹ representation that performs well across multiple prediction tasks.

Table 3. Average performance (standard deviation) on Three Tasks

	IBD Task		Fruit Diet Task		Vegetable Diet Task	
	AUROC	AUPR	AUROC	AUPR	AUROC	AUPR
Weighted	0.646(.02)	0.089(.02)	0.585(.02)	0.674(.04)	0.695(.02)	0.930(.01)
PCA	0.571(.04)	0.082(.02)	0.576(.03)	0.689(.04)	**0.700(.01)**	**0.932(.01)**
RandP	0.621(.03)	0.095(.02)	0.540(.03)	0.653(.04)	0.669(.02)	0.926(.01)
AE_{Best}	0.576(.05)	0.090(.02)	0.532(.03)	0.647(.05)	0.654(.02)	0.922(.01)
AE_{Match}	0.604(.06)	0.097(.03)	0.542(.01)	0.660(.04)	0.669(.02)	0.926(.01)
CAE_{Best}	0.625(.03)	0.093(.03)	0.571(.03)	0.677(.05)	0.662(.06)	0.920(.03)
CAE_{Match}	0.607(.03)	0.086(.02)	0.563(.02)	0.675(.04))	0.684(.02)	0.927(.01)
Transformer	**0.687(.04)**	**0.121(.02)**	**0.619(.02)**	**0.707(.02)**	**0.700(.02)**	0.928(.01)

⁴¹⁰ 3.2 Generalization to independent datasets

⁴¹¹ One of the largest challenges in working with microbiome data is that there is large

⁴¹² variance in the distributions and characteristics of data used from study to study.

⁴¹³ Therefore it is important to test how well our transformer based prediction models

⁴¹⁴ generalize on independent datasets that come from different population/sample

⁴¹⁵ distributions. To test this, we applied our transformer model trained for the IBD

⁴¹⁶ prediction task using the AGP data on the Halfvarson and HMP2 datasets from

⁴¹⁷ independent studies, without finetuning our model on any data from those independent

⁴¹⁸ studies.

⁴¹⁹   An issue that arises when performing such cross-study tests is the need to decide a

⁴²⁰ stopping point during finetuning to pick the best model to use on the test data. In the

⁴²¹ previous single study experiments, using a held-out validation set for this purpose

⁴²² proved to be an effective strategy. However, due to the substantial distributional shift

⁴²³ between the AGP data used for training/validation and the independent test set of

⁴²⁴ Halfvarson and HMP2, using a held-out AGP validation set for stopping is observed to

⁴²⁵ lead to poor and highly unstable results (shown by "Transformer (original)" in Table 4).

⁴²⁶ We address this problem by introducing a simple ensemble strategy. During fine tuning,

⁴²⁷ we train an ensemble of k classifiers using different random initializations of the

⁴²⁸ classification head. Similar to the standard practice when applying transformer to

₄₂₉ language [26], we found that each individual classifier only needs to be fine-tuned for a

₄₃₀ single epoch, i.e., going over all of the training once, and that training more epochs

₄₃₁ often leads to overfitting. In our experiments, we used ensemble size $k = 10$.

₄₃₂ We compare our ensemble performance with the baselines described above, and

₄₃₃ additionally strengthen the Weighted baseline of [13] by using an ensembled MLP

₄₃₄ classifier and reporting the best *testing* performance achieved by the Weighted baseline

₄₃₅ method during training. The baselines from [32] use random forest as the classifier and

₄₃₆ do not have a similar free parameter regarding their stopping condition.

₄₃₇ We report the performance of all methods averaged across five random runs with

₄₃₈ different initialization in Table 4. The results show that our method consistently

₄₃₉ achieves better performance on the Halfvarson dataset compared to all baselines, and

₄₄₀ comparable performance on the HMP2 dataset compared to the best performing of the

₄₄₁ Weighted baseline model selected using testing data. Although CAE_{Best} and CAE_{Match}

₄₄₂ achieve slightly higher HMP2 performance, this comes at the cost of an enormous deficit

₄₄₃ on Halfvarson. These results illustrate our approach's ability to consistently generalize

₄₄₄ well to out of distribution settings.

Table 4. Average performance (standard deviation) on independent IBD datastes. Weighted's standard deviation is close to zero, thus omitted.

	HMP2		Halfvarson	
	AUC	AUPR	AUC	AUPR
Weighted (ensemble)	0.668	0.863	0.752	0.962
PCA	0.570 (.02)	0.795 (.01)	0.578 (.06)	0.931 (.01)
RandP	0.583 (.03)	0.813 (.02)	0.509 (.03)	0.909 (.01)
AE_{Best}	0.618 (.02)	0.839 (.01)	0.519 (.02)	0.912 (.01)
AE_{Match}	0.644 (.02)	0.850 (.01)	0.499 (.05)	0.903 (.02)
CAE_{Best}	0.697 (.01)	0.879 (.01)	0.426 (.04)	0.890 (.01)
CAE_{Match}	**0.706** (.04)	**0.883** (.04)	0.488 (.04)	0.906 (.01)
Transformer (original)	0.460 (.03)	0.773 (.02)	0.719 (.09)	0.957 (.02)
Transformer (ensemble)	0.682 (.02)	0.855 (.01)	**0.805** (.01)	**0.973** (.001)

₄₄₅ In this section we take a closer look at the pre-trained language model to interpret

₄₄₆ the learned context-sensitive representations of microbial taxa.

Fig 4. t-SNE visualization of (a) original taxa vocabulary embeddings and (b) contextualize taxa embeddings. Both are colored by phylum. See Figure 9 for embedding spaces colored by phylum, class, order, and family.

3.3 Context sensitive taxa embedding captures biologically meaningful information

We hypothesize that the superior predictive performance of our model is because our pre-trained language model transforms the input taxa embedding into a more meaningful latent space capturing context sensitive information (Fig. 1G), making biologically relevant features of the taxa more readily extracted and applied to downstream tasks.

Phylogenetic information. We focus on the top 5,000 (out of 26,726) most frequent taxa from the IBD dataset and compute their averaged contextualized embeddings across every entry in the IBD dataset. Fig. 4 shows the t-SNE [37] visualization of the taxa using the original vocabulary embedding from [13] (a) and the averaged contextualized embeddings produced by our model (b), colored by the phylum of the taxa assigned by the DADA2 tool [38]. t-SNE is better suited to capturing the local neighborhood than the global structure, with points close together in the t-SNE visualization also generally being close together in the original embedding space. However, t-SNE gives a much worse impression of the overall (global) shape of the data [39].

From Fig. 4, we see that the original embedding space in panel (a) displays a degree of clustering by phylum. In particular, Proteobacteria (red) tend to cluster in distinct manifolds from the rest of the taxa. However, most of the taxa lie in a single large but stratified manifold of mixed phyla. In contrast, the contextualized representations in

panel (b) appear to have more consistent clustering by phylum in this reduced 2-D space. We further verify that the contextualized embedding does cluster more strongly in the full-dimensional embedding spaces with Fig. 5 d), which shows that clusters in the contextualized embedding space consistently have less cross-phylum contamination (as shown by higher phylum purity) as compared to clusters in the GloVe embedding space, showing that the appearance of improved clustering in the contextualized embedding space is not simply a t-SNE projection artifact.

To highlight the differences between the two representations, Figure 5 explores the mapping between them by highlighting the same group of taxa in both figures, where the left column shows the t-SNE visualization of the original taxa embeddings, and the right column shows the t-SNE of the contextualized taxa embeddings. From the comparison, we can see that the phyla that are well separated in the original embedding space as distinct manifolds are well preserved and further compacted into tighter clusters (see Fig. 5 a).

The data in the original vocabulary embedding space appear to lie on long "strands", rather than clump together in clusters. In particular, we see a large strand in the middle that contains most of the data, and seems to be made up of smaller "threads" very close together. The contextual representations appear to "unwind" the large strand so that the smaller threads can be extracted and grouped together in their own isolated clusters, which more cleanly separate by phylum (see Fig. 5 a). This highlights the capability of self-supervised representation learning to flexibly extract important features from unlabeled data.

Our model's ability to cluster taxa by phylum seems to degrade for taxa whose vocabulary embeddings are too close together. Figure 5 b) highlights taxa in a less compact region of the original embedding space, and highlights the same taxa in the contextualized embedding space, where the taxa show reasonable separation by phylum. In comparison, Figure 5 c) highlights a more compact region of the vocabulary space, as well as the corresponding taxa in the contextualized embedding space, which appear to show worse separation than we see in Figure 5 b).

Metabolic pathways.   Similar to [13], we investigate whether our contextualized embedding dimensions correlate with known metabolic pathways. We map the

Fig 5. Mapping between the original vocabulary and contextualized embedding spaces. Figure a) shows how the contextualized embeddings can extract "threads" of a single phylum from the vocabulary embedding space, and map those taxa to tight clusters in the contextualized embeddings. Figure b) shows that the mapping to the contextual embedding space is able to more cleanly separate taxa by phylum. Figure c) contrasts Figure b) and shows that taxa which are very tightly clustered in the vocabulary embeddings may not map to meaningful clusters or phylum-level separation in the contextualized embedding space. Figure d) shows cluster purity versus K for K-means clustering in the vocabulary and contextualized embedding spaces, showing the tighter clustering of the embedding space isn't simply an artifact of the t-SNE dimension reduction.

vocabulary taxa ASVs to their nearest neighbors in the KEGG database [40] using Piphillin [41], following the method used by [13]. Metabolic pathways for each mapped ASV are then extracted using the KEGGREST API [42], leading to a total of 141 pathways. Each ASV is represented using a one-hot encoding of the 141 metabolic pathways, assigning a 0 if the ASV is not involved in the pathway, and a 1 if it is involved. We limit the following analysis to ASVs involved in at least one of the 141 pathways, resulting in 11,893 ASVs, each represented by a 141-dimension binary vector indicating their involvement in the extracted pathways. We have seven fewer pathways than were present in the metabolic pathways analysis of [13], due to changes in the KEGG [40] database.

We compute the Spearman's correlation between each of our contextualized embedding dimensions and the 141 extracted metabolic pathways, producing a 200 by 141 correlation matrix. The same process is repeated for the 100-dimensional GloVe embedding, producing a 100 by 141 correlation matrix. Figure6 shows both sets of correlations using heatmaps. We can see that, although both embeddings show clear correlations with some metabolic pathways, the contextualized embedding dimensions capture stronger correlation, signified by the darker blue and red colors in the heatmap. To assess the statistical significance of the observed correlations, we applied a permutation test with 1,000 permutations. This test generates a distribution of correlations under the null hypothesis that the embeddings and the pathways are independent. By comparing the observed correlations to this null distribution, we filtered out correlations that were not statistically significant. We then compare the strengths of the remaining statistically significant correlations found for our contextualized embeddings to those found for the GloVe embeddings, by contrasting the distribution of the filtered correlation magnitudes from both embeddings in Figure 7, which visually shows that the normalized histograms of the contextualized embedding dimensions are shifted to the right compared to that of the GloVe embedding dimensions.

To verify that the two distributions of correlation magnitude are indeed different, we perform two different non-parametric statistical tests: the Kolmogorov–Smirnov two-sample test [43, 44] and the Epps–Singleton two-sample test [45] using SciPy's [46] implementation. Both tests reject the null hypothesis that the two distributions are

Contextualized   GloVe

Fig 6. Heatmaps showing how strongly each embedding dimension (y-axis) correlates with each metabolic pathway (x-axis), for both our contextualized embeddings and the prior GloVe embeddings.

equivalent with p-values of 4.19×10^{-26} and 9.71×10^{-50}, respectively.

3.4 Understanding taxa importance for IBD prediction

In this part, we focus on the fine-tuned IBD ensemble prediction model to understand what taxa play critical roles in our model's IBD prediction by studying their attribution. We first consider the 5,000 most frequent taxa shown in Figure 4 and compute for each taxon its average attribution toward the model's IBD prediction using the AGP IBD data, as described in Sec. 2.3.

Figure 8 (a) presents the t-SNE visualizations of the contextualized embeddings colored by taxa attribution strength. The visualization shows multiple clusters of high and low attribution taxa, indicating that local neighborhood distances in the original embedding space reflect taxa attributions. It is important to note that the contextualized embeddings generated by our pre-trained language model have never been trained on any IBD labels, yet their local structure appears to reflect taxa attributions, suggesting that our pre-trained language model indeed captures meaningful biological information.

Next, we wish to find the most important taxa for our model's correct IBD

Fig 7. Distribution of the magnitude of statistically significant correlations between embedding dimensions and metabolic pathways, for both contextualized embeddings and the prior GloVe embeddings.

Fig 8. t-SNE visualization of the contextualized embeddings colored by attribution to IBD. The taxa associated with IBD are visualized in lighter color (yellow) and the taxa associated with no-disease state are in dark purple.

classifications across different study populations. We therefore filter the data to focus

on samples for which our model makes confident and correct predictions. Specifically,

we filter each of the three IBD datasets (American Gut Project (AGP) [8], the

curated [13] versions of the Human Microbiome Project phase 2, (HMP2) [30], and

Halfvarson (HV) [29]) and include only correctly classified samples with a predicted

probability ranking within the top 50%, regardless of being positive or negative. To

focus on reasonably common microbial taxa, we also filter out taxa that appear in less

than 5% of all samples across all three IBD datasets (AGP, HMP2 and HV).

To allow for independent validation of our attribution estimation, we combine HV

and HMP2, into a single dataset (HV+HMP2), filter for correct confidence again, and

compute the average attribution on APG and HV+HMP2 separately, and reduce noise

by filtering out any taxa that appear in less than five samples in each dataset. The

attribution for a taxon is considered validated if it has two estimates from AGP and

HV+HMP2 respectively, and they have the same sign. Of the 5,716 taxa that appear in

HV+HMP2, 695 appear in at least 5% of the combined IBD-labeled data points, 530 of

those appear in at least five confident and correct samples in HV+HMP2 (and have

been assigned attributions), and 399 of those taxa have matching signs in their

attributions between the AGP data and the HV+HMP2 data. This ensures that we

only identify these microbial taxa that have consistent impact on the model in two

different populations. We then compute the average attribution of all validated taxa

across the combined (filtered) datasets. We show the 10 taxa most attributed to

negative IBD classification (Table 6) and the 10 taxa most attributed to positive IBD

classification (Table 5).

Table 5. Top 10 Taxa associated with negative (non-disease) IBD classification ordered by attribution strength.

Phylum	Class	Order	Family	Genus
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	NA
Proteobacteria	Gammaproteobacteria	Betaproteobacteriales	Burkholderiaceae	Sutterella
Bacteroidetes	Bacteroidia	Bacteroidales	Prevotellaceae	Prevotella
Proteobacteria	Gammaproteobacteria	Pasteurellales	Pasteurellaceae	NA
Bacteroidetes	Bacteroidia	Bacteroidales	Prevotellaceae	Prevotella_9
Fusobacteria	Fusobacteriia	Fusobacteriales	Fusobacteriaceae	Fusobacterium
Firmicutes	Bacilli	Lactobacillales	Lactobacillaceae	Lactobacillus
Bacteroidetes	Bacteroidia	Bacteroidales	Muribaculaceae	NA
Bacteroidetes	Bacteroidia	Bacteroidales	Bacteroidaceae	Bacteroides
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	NA

Table 6. Top ten Taxa associated with positive IBD classification ordered by attribution strength.

Phylum	Class	Order	Family	Genus
Proteobacteria	Gammaproteobacteria	Betaproteobacteriales	Burkholderiaceae	Sutterella
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	Ruminiclostridium_5
Bacteroidetes	Bacteroidia	Bacteroidales	Tannerellaceae	Parabacteroides
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	NA
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	Ruminococcaceae_UCG-9
Firmicutes	Clostridia	Clostridiales	NA	NA
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	Candidatus_Soleaferrea
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	Lachnoclostridium
Firmicutes	NA	NA	NA	NA
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	Anaerostipes

Comparing identified taxa to existing data repository

We compared the top 10 ASV attributions to IBD and the healthy cohort (20 ASVs total) found with our model to 284 markers taxa identified in the data repository for the human gut microbiota [47] across three projects (NCBI PRJEB7949 (95 entries), NCBI PRJNA368966 (32 entries), NCBI PRJNA3x85949 (157 entries)) comparing IBD and healthy controls (query request: gmrepo.humangut.info/phenotypes/comparisons/D006262/D015212).

Due to the difference in technologies between all the datasets, we compare the markers across the studies at the genus level. In our study, seven ASVs were not resolved beyond the family level, and are therefore excluded from this analysis. Further, two of our ASVs belonged to sub-clade of a genus, we considered them belonging to the genus of the clade: specifically Prevotella_9 (which was considered Prevotella in this analysis) and Ruminoccocus_1 (which was considered Ruminoccocus in this analysis).

Out of our 13 ASVs, four ASVs belong to genera Prevotella, Paraprevotella, and Lachnoclostridium, which were also found to be consistently associated with the healthy cohort in the data repository for the human gut microbiota (DRHM). Therefore they constitute consistent markers with the previous literature. One ASV, belonging to the genus Atopobium, was only associated with IBD in both our study and the DRHM, also constituting a markers of IBD consistent across our study and the database. Out of the remaining eight, we found two new ASVs markers that were not previously identified: the genera Allisonella (Associated with health) and Methanosphaera (associated with IBD).

Finally, the six remaining ASVs showed mixed patterns in the DRHM, where some

taxa of the genus seem to be a marker for the IBD and other taxa are enriched in healthy individuals. Out of these six genera, three markers mostly agree with our results: Bacteroides, which was associated with healthy individuals in 17/20 taxa, Ruminococcus showing the same pattern in 5/9 taxa, and Rosebduria also with the same pattern for 2/3 taxa. The other three genera show the opposite trend when comparing the DRHM markers with our work. Most notably, Lactobacillus is associated with the healthy cohort in our analysis, while 8/9 markers from this genus are enriched in the IBD cohort in the DRHM. We see more nuanced results for the genera Parabacteroides where 3/7 markers are associated with the control cohort in the DRHM (and a marker of IBD for us), as well as Oscillibacter, associated with the healthy individuals in 2/3 taxa in the database, which contradict our finding.

In summary, out of the 13 ASVs resolved at the genus level from our study, our analysis revealed two new markers not included in the DRHM. For five of these ASVs, our result is consistent with the DRHM markers. For the remaining three, we see mixed results. Here, the taxonomic resolution of our 16S becomes a limiting factor as these genera show different behavior at the species level.

4 Conclusion and Future Work

We apply recent natural language processing techniques to learn a language model for microbiomes from public domain human gut microbiome data. The pre-trained language model provides powerful contextualized representations of microbial communities and can be broadly applied as a starting point for any downstream prediction tasks involving human gut microbiome. In this work, we show the power of the pre-trained model by fine-tuning the representations for IBD disease state and diet classification tasks, achieving strong performance in all tasks. For IBD, our ensemble model demonstrates competitive performance that is robust across study populations even with strong distributional shifts.

We visualize the contextualized taxa embedding learned by our pre-trained language model and show that it captures biologically meaningful information including phylogenetic structure and IBD association without any prior training on such signals. We employ an interpretability technique to investigate the basis for our models' IBD

⁶²³ classification decisions and identify sets of taxa that negatively and positively attribute
⁶²⁴ to the model's predictions. We find known biomarkers of both IBD and gut homeostasis,
⁶²⁵ as well as evidence that our embeddings learn to separate ASVs by their pathogenicity,
⁶²⁶ even among ASVs sharing the same family and genus level phylogenetic classifications.

⁶²⁷   Our investigation suggests that NLP techniques like deep language models represent
⁶²⁸ a promising direction to better understand the microbiome. However, our effort is
⁶²⁹ limited in both volume and breath of the data that is used for training the microbial
⁶³⁰ language model. Currently, our pre-trained model is primarily optimized for tasks
⁶³¹ involving human gut microbiomes based on 16S data. Despite this, the utility of our
⁶³² model extends beyond its initial configuration. With adjustments, our methodology can
⁶³³ be highly versatile, offering numerous paths for generalization.

⁶³⁴   Specifically, it is possible to adapt our pre-trained language model directly to other
⁶³⁵ sources and types of microbiome data, such as taxonomic profiles of Metagenome
⁶³⁶ Assembled Genomes (MAGs), by replacing the initial embedding layer with one that is
⁶³⁷ fine-tuned using the new source of data. Strong precedents in natural language
⁶³⁸ processing support the feasibility of this approach, where pretrained models from one
⁶³⁹ domain have been shown to lead to predictable transfer when adapted to another
⁶⁴⁰ domain (e.g., from Python code to natural text [48], or from natural text to image
⁶⁴¹ classification [49]). Finally, we are enthusiastic about the potential to develop a unified
⁶⁴² model by training on a broad spectrum of microbiome data, encompassing various
⁶⁴³ sources and modalities, to create a generalized, versatile microbiome model capable of
⁶⁴⁴ instantaneous adaptation to the varied data distributions encountered in different
⁶⁴⁵ studies and methodologies across the microbiome research landscape.

⁶⁴⁶ Acknowledgments

We thank the National Science Foundation for the funding of this work under grant
number URoL:MTM2 2025457.

References

1. Kostic AD, Chun E, Robertson L, Glickman JN, Gallini CA, Michaud M, et al. Fusobacterium nucleatum Potentiates Intestinal Tumorigenesis and Modulates the Tumor-Immune Microenvironment. Cell Host & Microbe. 2013;14(2):207–215. doi:https://doi.org/10.1016/j.chom.2013.07.007.

2. Jiang H, Ling Z, Zhang Y, Mao H, Ma Z, Yin Y, et al. Altered fecal microbiota composition in patients with major depressive disorder. Brain, Behavior, and Immunity. 2015;48:186–194. doi:https://doi.org/10.1016/j.bbi.2015.03.016.

3. Zheng P, Zeng B, Zhou C, Liu M, Fang Z, Xu X, et al. Gut microbiome remodeling induces depressive-like behaviors through a pathway mediated by the host's metabolism. Molecular Psychiatry. 2016;21(6):786–796. doi:10.1038/mp.2016.44.

4. Frank DN, St Amand AL, Feldman RA, Boedeker EC, Harpaz N, Pace NR. Molecular-phylogenetic characterization of microbial community imbalances in human inflammatory bowel diseases. Proceedings of the National Academy of Sciences. 2007;104(34):13780–13785. doi:10.1073/pnas.0706625104.

5. Gevers D, Kugathasan S, Denson L, Vázquez-Baeza Y, Van Treuren W, Ren B, et al. The Treatment-Naive Microbiome in New-Onset Crohn's Disease. Cell Host & Microbe. 2014;15(3):382–392. doi:10.1016/j.chom.2014.02.005.

6. Ni J, Shen TCD, Chen EZ, Bittinger K, Bailey A, Roggiani M, et al. A role for bacterial urease in gut dysbiosis and Crohn's disease. Science Translational Medicine. 2017;9(416):eaah6888. doi:10.1126/scitranslmed.aah6888.

7. Gilbert JA, Blaser MJ, Caporaso JG, Jansson JK, Lynch SV, Knight R. Current understanding of the human microbiome. Nature Medicine. 2018;24(4):392–400. doi:10.1038/nm.4517.

8. McDonald D, Hyde E, Debelius JW, Morton JT, Gonzalez A, Ackermann G, et al. American Gut: an Open Platform for Citizen Science Microbiome Research. mSystems. 2018;3(3). doi:10.1128/mSystems.00031-18.

9. McMurdie PJ, Holmes S. phyloseq: an R package for reproducible interactive analysis and graphics of microbiome census data. PloS one. 2013;8(4):e61217.

10. Brooks AW, Priya S, Blekhman R, Bordenstein SR. Gut microbiota diversity across ethnicities in the United States. PLoS biology. 2018;16(12):e2006842.

11. Washburne AD, Morton JT, Sanders J, McDonald D, Zhu Q, Oliverio AM, et al. Methods for phylogenetic analysis of microbiome data. Nature microbiology. 2018;3(6):652–661.

12. Woloszynek S, Zhao Z, Chen J, Rosen GL. 16S rRNA sequence embeddings: Meaningful numeric feature representations of nucleotide sequences that are convenient for downstream analyses. PLoS computational biology. 2019;15(2):e1006721.

13. Tataru CA, David MM. Decoding the language of microbiomes using word-embedding techniques, and applications in inflammatory bowel disease. PLOS Computational Biology. 2020;16(5):e1007859. doi:10.1371/journal.pcbi.1007859.

14. Pennington J, Socher R, Manning CD. GloVe: Global Vectors for Word Representation. In: Empirical Methods in Natural Language Processing (EMNLP); 2014. p. 1532–1543. Available from: http://www.aclweb.org/anthology/D14-1162.

15. Kmann C, Dicksved J, Engstrand L, Rautelin H. Composition of human faecal microbiota in resistance to Cylobacter infection. Clinical Microbiology and Infection. 2016;22(1):61.e1–61.e8. doi:10.1016/j.cmi.2015.09.004.

16. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention Is All You Need. arXiv:170603762 [cs]. 2017;.

17. Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Wang Y, Jones L, et al. ProtTrans: Toward Understanding the Language of Life Through Self-Supervised Learning. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2022;44(10):7112–7127. doi:10.1109/tpami.2021.3095381.

18. Heinzinger M, Elnaggar A, Wang Y, Dallago C, Nechaev D, Matthes F, et al. Modeling aspects of the language of life through transfer-learning protein sequences. BMC Bioinformatics. 2019;20(1). doi:10.1186/s12859-019-3220-8.

19. Brandes N, Ofer D, Peleg Y, Rappoport N, Linial M. ProteinBERT: a universal deep-learning model of protein sequence and function. Bioinformatics. 2022;38(8):2102–2110. doi:10.1093/bioinformatics/btac020.

20. Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. Proceedings of the National Academy of Sciences. 2021;118(15):e2016239118. doi:10.1073/pnas.2016239118.

21. Ji Y, Zhou Z, Liu H, Davuluri RV. DNABERT: pre-trained Bidirectional Encoder Representations from Transformers model for DNA-language in genome. Bioinformatics. 2021;37(15):2112–2120. doi:10.1093/bioinformatics/btab083.

22. Shaw P, Uszkoreit J, Vaswani A. Self-Attention with Relative Position Representations. In: Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers). Association for Computational Linguistics; 2018.

23. Huang Z, Liang D, Xu P, Xiang B. Improve Transformer Models with Better Relative Position Embeddings. In: Findings of the Association for Computational Linguistics: EMNLP 2020; 2020. p. 3327–3335.

24. Ericsson L, Gouk H, Loy CC, Hospedales TM. Self-Supervised Representation Learning: Introduction, advances, and challenges. IEEE Signal Processing Magazine. 2022;39(3):42–62. doi:10.1109/MSP.2021.3134634.

25. Clark K, Luong MT, Le QV, Manning CD. ELECTRA: Pre-training Text Encoders as Discriminators Rather Than Generators. arXiv:200310555 [cs]. 2020;.

26. Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. arXiv:181004805 [cs]. 2019;.

27. Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R. Dropout: A Simple Way to Prevent Neural Networks from Overfitting. Journal of Machine Learning Research. 2014;15(56):1929–1958.

28. Zeiler MD, Fergus R. Visualizing and Understanding Convolutional Networks. In: Fleet D, Pajdla T, Schiele B, Tuytelaars T, editors. Computer Vision – ECCV 2014. Cham: Springer International Publishing; 2014. p. 818–833.

29. Halfvarson J, Brislawn CJ, Lamendella R, Vázquez-Baeza Y, Walters WA, Bramer LM, et al. Dynamics of the human gut microbiome in inflammatory bowel disease. Nature Microbiology. 2017;2(5):17004. doi:10.1038/nmicrobiol.2017.4.

30. Lloyd-Price J, Arze C, Ananthakrishnan AN, Schirmer M, Avila-Pacheco J, Poon TW, et al. Multi-omics of the gut microbial ecosystem in inflammatory bowel diseases. Nature. 2019;569(7758):655–662. doi:10.1038/s41586-019-1237-9.

31. Pope Q, Varma R, Tataru C, Maude DM, Fern X. Data and code from: Learning a deep language model for microbiomes: The power of large scale unlabeled microbiome data; 2024. Available from: https://datadryad.org/stash/dataset/doi:10.5061/dryad.tb2rbp08p.

32. Oh M, Zhang L. DeepMicro: deep representation learning for disease prediction based on microbiome data. Scientific Reports. 2020;10(1). doi:10.1038/s41598-020-63159-5.

33. Dasgupta S, Gupta A. An elementary proof of a theorem of Johnson and Lindenstrauss. Random Structures ; Algorithms. 2002;22(1):60–65. doi:10.1002/rsa.10073.

34. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine Learning in Python. Journal of Machine Learning Research. 2011;12:2825–2830.

35. Kramer MA. Nonlinear principal component analysis using autoassociative neural networks. Aiche Journal. 1991;37:233–243.

36. Li F, Qiao H, Zhang B. Discriminatively boosted image clustering with fully convolutional auto-encoders. Pattern Recognition. 2018;83:161–173. doi:https://doi.org/10.1016/j.patcog.2018.05.019.

37. van der Maaten L, Hinton G. Visualizing Data using t-SNE. Journal of Machine Learning Research. 2008;9(86):2579–2605.

38. Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJA, Holmes SP. DADA2: High-resolution sample inference from Illumina amplicon data. Nature methods. 2016;13(7):581—583. doi:10.1038/nmeth.3869.

39. Kobak D, Berens P. The art of using t-SNE for single-cell transcriptomics. Nature Communications. 2019;10(1). doi:10.1038/s41467-019-13056-x.

40. Kanehisa M, Goto S. KEGG: kyoto encyclopedia of genes and genomes. Nucleic acids research. 2000;28(1):27–30.

41. Narayan NR, Weinmaier T, Laserna-Mendieta EJ, Claesson MJ, Shanahan F, Dabbagh K, et al. Piphillin predicts metagenomic composition and dynamics from DADA2-corrected 16S rDNA sequences. BMC Genomics. 2020;21(1). doi:10.1186/s12864-019-6427-1.

42. Tenenbaum D, Maintainer B. KEGGREST: client-side REST access to the Kyoto Encyclopedia of Genes and Genomes (KEGG). R package. In: KEGGREST: client-side REST access to the Kyoto Encyclopedia of Genes and Genomes (KEGG). R package; 2018.

43. L KA. Sulla determinazione empirica di una legge di distribuzione. G Ist Ital Attuari. 1933;4:83–91.

44. Smirnov N. Table for Estimating the Goodness of Fit of Empirical Distributions. The Annals of Mathematical Statistics. 1948;19(2):279 – 281. doi:10.1214/aoms/1177730256.

45. Epps TW, Singleton KJ. An omnibus test for the two-sample problem using the empirical characteristic function. Journal of Statistical Computation and Simulation. 1986;26:177–203.

46. Virtanen P, Gommers R, Oliphant TE, Haberland M, Reddy T, Cournapeau D, et al. SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. Nature Methods. 2020;17:261–272. doi:10.1038/s41592-019-0686-2.

47. Dai D, Zhu J, Sun C, Li M, Liu J, Wu S, et al. GMrepo v2: a curated human gut microbiome database with special focus on disease markers and cross-dataset comparison. Nucleic Acids Research. 2021;50(D1):D777–D784. doi:10.1093/nar/gkab1019.

48. Hernandez D, Kaplan J, Henighan T, McCandlish S. Scaling Laws for Transfer; 2021.

49. Lu K, Grover A, Abbeel P, Mordatch I. Frozen pretrained transformers as universal computation engines. In: Proceedings of the AAAI conference on artificial intelligence. vol. 36; 2022. p. 7628–7636.

Supporting information

Fig 9. Vocabulary and contextualized embedding spaces colored by different levels of the phylogenetic hierarchy: phylum, class, order, and family.

Table 7. Top 10 non-disease associated ASVs. Entries match those in Table 5.

TACGTATGGTGCAAGCGTTATCCGGATTTACTGGGTGTAAAGGGAGCGTAGACG GATGGGCAAGTCTGATGTGAAAACCCGGGGCTCAACCCCGGGACTGCATTGGAA ACTGTTCATCTAGAGTGCTGGAGAGGTAAGTG
TACGGAGGATCCGAGCGTTATCCGGATTTATTGGGTTTAAAGGGAGCGTAGATG GGTTGTTAAGTCAGTTGTGAAAGTTTGCGGCTCAACCGTAAAATTGCAATTGAT ACTGGCAGTCTTGAGTACAGTTGAGGTAGGCG
TACGGAGGATGCGAGCGTTATCCGGATTTATTGGGTTTAAAGGGAGCGCAGGCT GCGAGGCAAGTCAGCGGTCAAATGTCGGGGCTCAACCCCGGCCTGCCGTTGAAA CTGTCCTGCTAGAGTTCGAGTGAGGTATGCGG
TACGTATGTCACGAGCGTTATCCGGATTTATTGGGCGTAAAGCGCGTCTAGGTG GTTATGTAAGTCTGATGTGAAAATGCAGGGCTCAACTCTGTATTGCGTTGGAAA CTGTATAACTAGAGTACTGGAGAGGTAAGCGG
TACGTAGGTGGCGAGCGTTGTCCGGATTTATTGGGCGTAAAGGGAACGCAGGCG GTCTTTTAAGTCTGATGTGAAAGCCTTCGGCTTAACCGAAGTAGTGCATTGGAA ACTGGAAGACTTGAGTGCAGAAGAGGAGAGTG
TACGGAAGGTCCGGGCGTTATCCGGATTTATTGGGTTTAAAGGGAGCGTAGGCC GGAGATTAAGCGTGTTGTGAAATGTAGACGCTCAACGTCTGCACTGCAGCGCGA ACTGGTTTTCTTGAGTACGCACAAAGTGGGCG
TACGGAGGGTGCGAGCGTTAATCGGAATAACTGGGCGTAAAGGGCACGCAGGCG GACTTTTAAGTGAGGTGTGAAAGCCCCGGGCTTAACCTGGGAATTGCATTTCAG ACTGGGAGTCTAGAGTACTTTAGGGAGGGGTA
TACGGAAGGTTCGGGCGTTATCCGGATTTATTGGGTTTAAAGGGAGCGTAGGCC GTTTGGTAAGCGTGTTGTGAAATGTAGGAGCTCAACTTCTAGATTGCAGCGCGA ACTGTCAGACTTGAGTGCGCACAACGTAGGCG
TACGTAGGGTGCAAGCGTTAATCGGAATTACTGGGCGTAAAGCGTGCGCAGGCG GTTCTGTAAGACAGATGTGAAATCCCCGGGCTCAACCTGGGAATTGCATTTGTG ACTGCAGGACTAGAGTTCATCAGAGGGGGGTG
TACGTAGGGGGCAAGCGTTATCCGGATTTACTGGGTGTAAAGGGAGCGTAGACG GCATGGCAAGCCAGATGTGAAAGCCCGGGGCTCAACCCCGGGACTGCATTTGGA ACTGTCAGGCTAGAGTGTCGGAGAGGAAAGCG

Table 8. Top 10 disease associated ASVs. Entries match those in Table 6.

TACGTAGGGTGCAAGCGTTAATCGGAATTACTGGGCGTAAAGCGTGCGCAGGCG GTTCTGTAAGATAGATGTGAAATCCCCGGGCTCAACCTGGGAATTGCATATATG ACTGCAGAACTTGAGTTTGTCAGAGGAGGGTG
TACGTAGGGAGCGAGCGTTGTCCGGATTTACTGGGTGTAAAGGGTGCGTAGGCG GATTGGCAAGTCAGAAGTGAAATCCATGGGCTTAACCCATGAACTGCTTTTGAA ACTGTTAGTCTTGAGTGAAGTAGAGGTAGGCG
TACGGAGGATCCGAGCGTTATCCGGATTTATTGGGTTTAAAGGGTGCGTAGGCG GCCCCTTAAGTCAGCGGTGAAAGTCTGTGGCTCAACCATAGAATTGCCGTTGAA ACTGGGAGGCTTGAGTATGTTTGAGGCAGGTG
TACGTAGGGGGCAAGCGTTATCCGGATTTACTGGGTGTAAAGGGTGCGTAGGTG GCAAGGCAAGTCAGATGTGAAAGCCCGGGGCTCAACCCCGGTACTGCATTTGAA ACTGTCTGGCTAGAGTGCAGGAGAGGTAAGCG
TACGTAGGTGGCAAGCGTTGTCCGGATTTACTGGGTGTAAAGGGCGAGTAGGCG GGCATGCAAGTCAGATGTGAAATCTGGGGGCTTAACCCCCAAACTGCATTTGAA ACTGTGTGTCTTGAGTGATGGAGAGGCAGGCG
TACGTAGGGGGCAAGCGTTGTCCGGAATTATTGGGCGTAAAGGGTGCGTAGGCG GCCTTACAAGTTGGATGTGAAATCCCCGTGCTTAACATGGGAACTGCATCCAAA ACTGTAGGGCTTGAGTGTGGAAGAGGTAAGTG
TACGTAGATGGCGAGCGTTGTCCGGAATTACTGGGTGTAAAGGGAGTGTAGGCG GGCTGGTAAGTTGAATGTGAAACCTTCGGGCTCAACCCGGAGCGTGCGTTCAAA ACTGCTGGTCTTGAGTGAAGTAGAGGCAGGCG
TACGTAGGGGGCAAGCGTTATCCGGATTTACTGGGTGTAAAGGGAGCGTAGACG GCGATGCAAGCCAGATGTGAAAGCCCGGGGCTCAACCCCGGGACTGCATTTGGA ACTGCGTGGCTGGAGTGTCGGAGAGGCAGGCG
TACGTAGGGGGCAAGCGTTGTCCGGAATTACTGGGCGTAAAGGGCGCGTAGGCG GCCTGCCAAGTCTTGTGTGAAAACCCTGGTTTCAAGCCAGGAGGTGCACGGGAAA CTGGCGGGCTTGAGTGCAGGAGAGGGAAGTG
TACGTAGGGGGCAAGCGTTATCCGGAATTACTGGGTGTAAAGGGTGCGTAGGTG GTATGGCAAGTCAGAAGTGAAAACCCAGAGCTTAACTCTGGGACTGCTTTTGAA ACTGTCAGACTGGAGTGCAGGAGAGGTAAGCG