Learning a deep language model for microbiomes: the power of large scale unlabeled microbiome data

Quintin Pope[1]☯, Rohan Varma[2]☯, Chritine Tataru [3], Maude David[3,4], Xiaoli Fern[1]

1 School of Electrical Engineering and Computer Science, Oregon State University, Corvallis, Oregon, United States

2 Computer Science and Engineering, University of Michigan, Ann Arbor, Michigan, United States

3 Department of Microbiology, Oregon State University, Corvallis, Oregon,United States

4 Department of Pharmaceutical Sciences, Oregon State University, Corvallis, Oregon, United States

☯These authors contributed equally to this work.

*popeq@oregonstate.edu

Abstract

We use open source human gut microbiome data to learn a microbial "language" model by adapting techniques from Natural Language Processing (NLP). Our microbial "language" model is trained in a self-supervised fashion (i.e., without additional external labels) to capture the interactions among different microbial species and the common compositional patterns in microbial communities. The learned model produces contextualized taxa representations that allow a single bacteria species to be represented differently according to the specific microbial environment it appears in. The model further provides a sample representation by collectively interpreting different bacteria species in the sample and their interactions as a whole. We show that, compared to baseline representations, our sample representation consistently leads to improved performance for multiple prediction tasks including predicting Irritable Bowel Disease (IBD) and diet patterns. Coupled with a simple ensemble strategy, it produces

a highly robust IBD prediction model that generalizes well to microbiome data

independently collected from different populations with substantial distribution shift.

We visualize the contextualized taxa representations and find that they exhibit

meaningful phylum-level structure, despite never exposing the model to such a signal.

Finally, we apply an interpretation method to highlight bacterial species that are

particularly influential in driving our model's predictions for IBD.

Author summary

Human microbiomes and their interactions with various body systems have been linked

to a wide range of diseases and lifestyle variables. To understand these links, citizen

science projects such as the American Gut Project (AGP) have provided large

open-source datasets for microbiome investigation. In this work we leverage such

open-source data and learn a "language" model for human gut microbiomes using

techniques derived from natural language processing. We train the "language" model to

capture the interactions among different microbial species and the common

compositional patterns that shape gut microbiome communities. By considering the

entirety of species within a sample and their interactions, our model produces a

representation that enables contextualized interpretation of individual bacterial species

within their microbial environment. We demonstrate that our sample representation

enhances prediction performance compared to baseline methods across multiple

microbiome tasks including prediction of Irritable Bowel Disease (IBD) and diet

patterns. Furthermore, our learned representation yields a robust IBD prediction model

that generalizes well to independent data collected from different populations. To gain

insight into our model's workings, we present interpretation results that showcase its

ability to learn biologically meaningful representations.

1 Introduction

Identifiable features of the human microbiome and its interactions with various body

systems have been associated with a wide range of diseases, including cancer [1],

depression [2,3] and inflammatory bowel disease [4–6]. As our knowledge of such

connections has advanced, research on the human microbiome has undergone a shift in focus, moving from establishing links to unraveling the underlying mechanisms and utilizing them to develop clinical interventions [7]. This transition has sparked interest in applying statistical methods to microbiome data, leading to the launch of open source projects such as the American Gut Project (AGP) and Human Food Project (HFP), which provide open source datasets for microbiome investigation [8]. These repositories offer data in the form of raw genetic reads, which, even after being processed into taxa counts, still present thousands of features per sample. Consequently, researchers often employ dimension reduction techniques to transform this data into a more manageable feature space.

Significantly, the relevance of microbes to any particular analysis is often intertwined with the presence and potential interactions of other microbes in the environment. However, common techniques for reducing microbiome data dimensions — such as binning based on phylogenetic relationships [9, 10], clustering by gene similarity [11], or using PCA and other techniques [12] — don't account for the interactions between species when producing lower dimensional representations of samples. Consequently, a significant challenge in microbiome data analysis is to produce lower dimension representations (embeddings) of samples that not only take into account the presence of specific taxa but also their interactions and overall functioning as a whole.

Fortunately, a similar challenge has been investigated in the natural language processing (NLP) domain, which shares many similarities with the microbiome domain. Just as a sample comprises numerous microbes, a sentence consists of multiple words. Similarly, certain microbes hold greater relevance for specific analyses, while certain words are more important for different NLP tasks. Furthermore, just as a microbe can assume different functional roles under varying conditions, a word can possess different meanings in different contexts.

Given the strong similarities between the two domains and the shared goal of producing quality lower-dimensional sample / sentence representations, there is a growing interest in applying NLP techniques to microbiome analysis. Notably, previous work has successfully applied NLP word embedding algorithms to microbiome data, generating taxa embeddings that have shown promising results surpassing the performance of traditional dimension reduction techniques like PCA for various

microbiome prediction tasks [13].

Specifically, [13] apply the GloVe (Global Vectors for Word Representation) embedding algorithm [14] to co-occurrence data derived from the AGP dataset. GloVe maps each taxa in the vocabulary to a vector representation, and optimizes those vectors such that the inner product of any two vectors will match the log of the co-occurrence rate of the associated pair of taxa.

However, this prior work [13] has several limitations. First, the embeddings are learned based on aggregated global microbe-to-microbe co-occurrence statistics — in reality, microbe interactions can be dynamic and context-dependent. Second, given a sample containing many taxa, the embedding for the sample is computed by taking an abundance-weighted-average of the taxa embeddings without considering the context-specific roles of individual microbes in the sample. Similar to how the word "fly" changes from an insect in "I caught a fly" to an action in "I like to fly" based on context, the role of a bacteria can also shift based its context and interactions. For example, susceptibility to infection with Campylobacter jejuni was shown to depend on the species composition of the microbiota [15].

Transformers, a powerful and flexible machine learning architecture originally developed for NLP [16], provides a potential solution to above issues. Past work [17–21] has applied transformers to biological data. However, such work has focused on learning a sequence encoder for representing DNA [21] or, more commonly, protein amino acid sequences [17–20] (e.g., each token might represent a k-mer in such a sequence). In contrast, we focus on representing entire microbial communities and their interactions, using each token to represent a single microbe in such a community.

We present the first use of transformers to learn representations of microbiome at the taxa level by adapting "self-supervised" pre-training techniques from NLP, allowing the model to learn from vast amounts of unlabeled 16S microbiome data and mitigating the required amount of expensive labeled data. The pre-trained models can be viewed as a form of "language model" for microbiome data, capturing the inherent composition rules of microbial communities, which we can easily adapt to downstream prediction tasks with a smaller amount of labeled "finetuning" data.

We show that using a transformer model pre-trained on data from the American Gut Project (AGP) as the starting point, we can achieve state of the art performance for

multiple downstream host phenotype prediction tasks including IBD disease state prediction. These results showcase the remarkable capability of the pre-trained microbial "language" model in generating enhanced representation of the microbiome.

Focusing on the IBD prediction task, we demonstrate that our IBD prediction model, trained on the IBD data from the American Gut Project, with a simple ensemble strategy, exhibits robust generalization across several IBD studies with notable distributional shifts. We further visualize the contextualized taxa embeddings produced by our pre-trained language model and show that they capture biologically meaningful information. Finally, we analyze the learned IBD prediction model to identify taxa that strongly influence the model's prediction.

2   Materials and Methods

We begin by introducing the general workflow of applying a transformer model for generating a sample embedding (Fig. 1) and explaining each step of the work flow, including a detailed look into the transformer architecture. We then explain how we perform the pretraining, followed by finetuning for specific down stream tasks (Fig. 2). This section will also explain how we identify those taxa that most affect the model's classification decisions (Eq. 1) and conclude with a description of the datasets used in this paper.

2.1   Transformers for microbiome data: workflow overview

Since their introduction in 2017, [16] transformers have emerged as one of the most powerful classes of neural models invented to date, demonstrating state-of-the-art performance in many domains, though different tasks and data types require specific adaptations. Figure 1 summarizes the basic workflow of applying transformer to microbiome data for generating sample representations and context-sensitive taxa embeddings.

Preprocessing steps.

We assume that microbiome samples are represented as vectors of relative taxa abundances (Fig. 1A). To prepare our input for the transformer model, we perform a

Fig 1. Workflow of using a transformer model for generating sample embedding/classification and context sensitive taxa embeddings. The inputs (A), which are samples represented as relative abundance vectors, first go through the preprocessing step (B) to generate text-like inputs (C) for the transformer model (D). The transformer model generates a sample embedding (h_{cls}) that goes through a sample classification layer (E) to produce task specific sample level predictions (F). The transformer model also generates context sensitive embedding (G) for each taxa in the sample. Same taxa appearing in different samples can have different embedding because of contextual differences.

pre-process step (Fig. 1B) to transform the microbiome sample into 'text-like' inputs (Fig. 1C). Specifically, we rank all the taxa present in the sample in decreasing order of abundance to create an ordered list of taxa (truncated to contain no more than the 512 most abundant taxa). This step creates inputs that are analogous to texts, which are ordered lists of tokens of variable length capped at 512. Transformer computational costs increase with the square of their input lengths, so truncating inputs to at most 512 helps ensure our method remains computationally efficient to run, while affecting less than 6% of the training data points.

Similar to what is done in processing textual inputs, we prepend a special 'classification (CLS)' token to our input list. We use the 'CLS' token's representation as the final sample representation, which we treat as a summary of the full sample for classification purposes.

The transformer model

Fig. 1D provides a sketch of our transformer architecture for performing a sample classification task. The input to the transformer model is an ordered list of taxa. The list first goes through an embedding layer and a projection layer. The output of the projection layer then feeds into a sequence of multiple encoder blocks (we use 5 encoder blocks in this work), where each encoder block produces a new representation based on outputs of the previous block. Below we explain the individual components.

Embedding layer. The embedding layer maps from discrete tokens/taxa to their corresponding vector representations. We use absolute positional embeddings [16] to encode the abundance-based taxa order into the taxa embeddings. We experimented with a variety of methods to incorporate abundance information, including different positional embedding methods such as relative key [22] and relative key query [23] methods, as well as using additional embedding dimensions to directly store abundance values. We found little difference between these methods, and hence opted for the absolute positional embeddings based on rank ordering for its relative simplicity..

We preset the embedding layer using the 100-dimensional GloVe taxa embedding from [13], learned using the co-occurrence data from the AGP dataset, and keep it frozen during training, except for the 'CLS' token embedding, which is initialized randomly

and trained during pre-training and fine-tuning. We do this to enable a more direct comparison of the contextualized embeddings with the original vocabulary embedding learned through GloVe, thus emphasizing the benefits of contextualized representations.

Projection layer. The projection layer is a linear transformation from the vocabulary embedding space to the model's hidden representation space. The projection layer allows the model to process inputs of different dimensionality than the model's hidden space. In this work, the projection layer projects from the 100 dimensional vocabulary embedding into a richer 200 dimensional hidden space used by the model.

Encoder blocks. This is where the transformer begins incorporating "context" into the representation of each ASV in the sample. Here we provide an intuitive explanation of the encoder block. Please see [16] for concrete mathematical definitions.

An encoder block consists of a multi-headed self-attention layer [16] and a fully connected layer. The multi-headed attention layer computes a set of self-attention scores (one per head). Each attention head can read and write to different subspaces in the embeddings, and can track its own set of all-pairs interactions between every taxon in the sample. This could allow different heads to track different collections of statistical factors that influence community composition and metabolic functions.

The network modulates how much 'attention' is paid to each context taxon when updating the representation for a particular taxon in the sample. For example, in the context of language and given a sentence such as "I waved at the band, but they didn't see me", a properly trained encoder block could update the embedding of word "they" to reflect that it is referencing "the band". Analogously, in microbiome data, if bacteria A performs a functional role conditioned on the presence of bacteria B, a properly trained encoder block could update the embedding for bacteria A to reflect the presence or absence of bacteria B.

Classification head. We rely on a special 'CLS' token to summarize information from all the other taxa / tokens. The CLS token then feeds into a classification head, which is a standard two-layer feed forward neural network with 200 hidden nodes, to produce a prediction for a specific classification task.

Fig 2. Training of the transformer model. Unlabeled microbiome data (A) is fed into a randomly initialized transformer (B) as inputs to the self-supervised pre-training process (C), which produces a pre-trained transformer that generates token-level classifications (D). We replace the token-level classification head with a randomly initialized CLS classification head (E), and use labeled microbiome data (F) to fine-tune the CLS classification head (G), which produces the fine-tuned transformer (H).

2.2 Transformer training

A critical challenge in applying complex deep learning models like transformers is the lack of large amounts of labeled training data. This can be addressed, however, using a technique referred to as self-supervised pre-training [24], which leverages readily available unlabeled data. In this work, we follow this approach and our training process is described in Fig. 2.

Pre-training

We begin with a randomly initialized transformer and first train a task-agnostic transformer using unlabeled data via self-supervised pre-training. Specifically, We use ELECTRA (Efficiently Learning an Encoder that Classifies Token Replacements Accurately) [25] to pre-train the encoder layers of the transformer model. We chose ELECTRA because it reaches comparable performance to other popular pre-training approaches (BERT [26] and its various flavors) while being computationally efficient.

The ELECTRA pre-training approach has two steps. The first step trains a generator model by randomly masking out 15% of taxa in microbiome samples and training the generator model to predict the missing taxa based on the remainder of the sample. For the second step, we use the trained generator to produce perturbed

Electra pre-training scheme

Fig 3. Electra pre-training diagram. A generator is trained to predict the masked taxa from a sample. A discriminator is trained to differentiate taxa filled in by the generator from the original taxa in the sample. Both use the same transformer architecture, and have token level classification heads. The generator token level classification head predicts the taxa ID whereas the discriminator token level classification head predicts the input taxa as "Real" or "Modified"

microbiome samples by replacing all the masked taxa with generator predictions and train a discriminator model to differentiate the original taxa of the sample from those replaced by the generator. Essentially, the generator attempts to fill in the masks with taxa predictions and the discriminator takes in the predicted sequence and attempts to identify which taxa are modified by the generator.

Both the generator and discriminator models have the same general architecture as shown in Fig. 3. To train the generator, the inputs are randomly corrupted by replacing 15% of taxa IDs with a special 'mask' ID, and the embedding of each masked taxa after the final encoder layer is fed into a classification head to predict the ID of the masked taxa.

To train the discriminator model, we take the masked sample completed by the generator as input to the discriminator, and feed the embedding of each taxa after the final encoder layer into a classification head that differentiates 'real' (original taxa) from 'modified' (generated taxa).

At the end of pre-training, we have two transformer models, the generator and discriminator. Following the practice of the original work, we use the encoder of the pre-trained discriminator as the initial model to be fine tuned for downstream tasks.

Pre-training details. We perform pre-training on 18480 gut microbiome samples from the American Gut Project Database using the ELECTRA scheme as described above. Specifically, the generator was trained for 240 epochs to predict masked microbe embeddings, and checkpoints of the model were saved every 30 epochs. The discriminator was then trained on the replacement prediction task for 120 epochs with replacements generated by the increasingly trained generator. Specifically, for every 15 epochs of discriminator training, we replace the generator used to produce inputs for the discriminator with a stronger generator using the previously mentioned checkpoints. For example, the generator trained for 30 epochs provided inputs for the first 15 epochs of discriminator training. Then, for epochs 16-30, discriminator inputs were provided by the generator trained for 60 epochs. This was done to gradually ramp up the difficulty of the replacement prediction task.

Architecture and pre-training choices

We performed model architecture selection on the basis of pretraining results. We used 16000 AGP samples to perform the training for both the generator and discriminator models, and used the remaining 2480 samples as a hold-out validation set to decide the model architecture as well as the stopping point for the pretraining. Specifically, we observed that fewer than 5 layers of encoders leads to reduced capacity for the discriminator to differentiate between real and imputed taxa, whereas a larger number of layers does not produce noticeable benefit. We additionally chose to stop the discriminator's pretraining at 120 epochs because we observed its prediction accuracy on the hold set stabilizing at that point, even when substituting in better-trained generators.

Task specific fine-tuning

Given a specific prediction task and the pre-trained discriminator, we remove the token classification head and add a new (randomly initialized) sequence classification head to the 'CLS' token. In addition to the embedding layer, we also freeze the parameters of the encoder blocks such that only the classification head and the projection layer was trained during fine-tuning. In other words, the pre-trained discriminator encoders are used as a universal encoder for representing microbiome samples for different prediction

tasks. Empirically we have found this practice reduces overfitting and produces more

robust generalization performance across different tasks.

Fine-tuning details.   We perform fine-tuning using Stochastic Gradient Descent

(SGD) optimization with a learning rate of 0.01, momentum of 0.9, and the mean

squared error loss, which we found gave better results than the more traditional

negative cross-entropy loss, potentially because mean squared error is more robust to

noise and outliers. Furthermore, during training, we perform data augmentation by

randomly deleting 10% of the input taxa in each training sample to increase the

robustness of the trained model and reduce overfitting. The SGD optimization is

performed for a total of 50 epochs. Instead of using the final model, we use a separate

set of validation data to evaluate the model's performance at the end of each epoch and

select the best model to use. We use cross-validation on a subset of the IBD data to

tune the hyperparameters (random deletion percentage for data augmentation and the

choice of MSE vs the Cross Entropy loss) for fine-tuning.

2.3   Feature ablation attribution: finding the important taxa

We are interested in finding which microbe species the model relies on most for making

a positive or negative classification of the samples. To this end, we use feature ablation

attribution [27].

Consider a sample X containing n microbial species, which the model predicts as

being positive (for some property, e.g, IBD) with probability $M(X)$. Feature ablation

individually deletes each microbe species from the original X, then records how much

each species' removal reduces the model's predicted probability of being positive. We

average these changes across every sample in which a species appears, giving the

expected change in classification probability caused by deleting the species in question

from a random sample containing the species.

Given a dataset $\mathbf{D}$, let $\mathbf{D}_m$ denote the set of samples that contains a specific

microbe m, we can calculate m's attribution $a(m)$ as:

$$a(m) = \frac{1}{|\mathbf{D}_m|} \sum_{X \in \mathbf{D}_m} \mathbf{M}(X) - \mathbf{M}(X \setminus m) \tag{1}$$

₂₉₈ where $\mathbf{M}(\cdot)$ denotes the model's probabilistic output for the given input and $X \setminus m$

₂₉₉ denotes sample X with microbe m removed.

2.4 Datasets

₃₀₁ We use three different datasets over the course of this study. We now describe them and

₃₀₂ summarize where they are used.

₃₀₃ **American Gut Project (AGP).** The American Gut Project (AGP) [8] is a

₃₀₄ crowdsourced microbiome data gathering effort. From it, we used 18480 microbiome

₃₀₅ samples sequenced from the v4 hypervariable region of the 16S gene that were curated

₃₀₆ by the authors of [13]. The sample sequences come with metadata information on the

₃₀₇ subject the sample originates from, providing information about their diet, medical

₃₀₈ status on inflammatory bowel disease and more. We used all 18480 samples for our

₃₀₉ pre-training and relevant portions in our evaluation of downstream tasks. We now

₃₁₀ describe the three downstream tasks we ran experiments on.

₃₁₁ • Inflammatory Bowel Disease (IBD). This task aims to predict whether a given

₃₁₂ microbiome sample belongs to an individual diagnosed with IBD or not. Samples

₃₁₃ originating from individuals with IBD are the positive class. Label information

₃₁₄ was drawn from AGP metadata producing 435 samples from IBD positive

₃₁₅ individuals and 8136 healthy controls.

₃₁₆ • Frequency of fruit in diet. This task aims to determine the frequency with which

₃₁₇ an individual consumes fruits based on their microbiome sample. The label is

₃₁₈ derived from AGP metadata, which ranks fruit consumption frequency on a one to

₃₁₉ five scale. For this experiment, samples ranked 3-5 are grouped to form the

₃₂₀ positive (frequent) class. Samples ranked 0-2 are considered negative (infrequent).

₃₂₁ Out of 6540 AGP examples with fruit metadata, 4026 were labeled positive.

₃₂₂ • Frequency of vegetable in diet. This task aims to determine the frequency with

₃₂₃ which an individual consumes vegetables based on their microbiome sample. In

₃₂₄ the same manner as the fruit task, label information was drawn from the AGP

₃₂₅ metadata and frequency ranks from 0-5 were grouped to form the "frequent" (3-5)

and "infrequent" (0-2) classes. Out of 6549 AGP examples containing vegetable

frequency metadata, 5654 were labeled positive.

Table 1 provides the summary statistics for the three classification tasks.

Table 1. Three classification tasks derived from the AGP data and meta data.

Datasets	AGP-IBD	AGP-Fruit	AGP-Vegetable
# of samples	8571	6540	6549
# of positive samples	435	4026	5654
# of negative samples	8136	1514	895

Halfvarson (HV). This dataset comes from an IBD study performed in [28]. We used the curated dataset produced in [13], which contains 564 microbiome samples, with 510 of them IBD positive.

HMP2. This dataset comes from an IBD study performed as part of phase 2 of the Human Microbiome Project [29]. Again, we used the curated dataset produced in [13], which contains 197 microbiome samples with 155 IBD positive examples.

3 Results and Discussions

3.1 Transformer representations outperform baselines on multiple microbiome tasks

In this section, we empirically compare transformer-produced sample representations against a variety of baseline methods. Our baselines include **Weighted**, a simple non-contextualized abundance-weighted-averaging of the GloVe embeddings from [13], two classic dimension reduction based methods, and two deep learning based methods introduced by [30], each of which performs dimension reduction using the sample taxonomic abundance profiles as input features:

- **PCA**: Principle Component Analysis, configured to retain at least 99% of the variance.
- **RandP**: Random Gaussian Projection, relying on the Johnson-Lindenstrauss lemma [31] and implemented with scikit-learn [32] using eps 0.5.

- **AE**: An MLP-based autoencoder architecture, with two sizes: AE_{Best} (28.4M parameters) and AE_{Match} (7.2M parameters).
- **CAE**: An convolutional neural network-based autoencoder architecture, with two sizes: CAE_{Best} (12.3K parameters) and CAE_{Match} (102.6K parameters).

We used a reduced training set to quickly sweep the full range of model hyperparameters described in [30] for their effectiveness in our setting. We found that the variational autoencoder failed to produce useful results, regardless of hyperparameters, and thus omitted this architecture in the comparisons. For the two remaining architecture (AE and CAE), we selected two sizes: one that achieved the best validation performance using the reduced training set (CAE_{Best}), and another that aims to match the parameter count of our own model (7.07M) as closely as possible.

For the baselines from [30], we adapt that work's random forest classification layer (and the range of hyperparameters to consider), because random forest most consistently achieved the best performance across the settings [30] explored.

As mentioned previously, our method applies a standard multi-layered perceptron (MLP) classifier to the transformer-produced sample representations for classification. To allow **Weighted** to act as a more consistent comparison with our model, we replaced the random forest classifier used in prior work with the same MLP classifier. We evaluate our method and the baseline methods using the AGP dataset on three microbiome classification tasks.

For each task, we perform evaluation using 5-fold Cross Validation. For each cross-validation run, 80% of the available labeled data was used for training, and the remaining 20% was split between a validation and test set. We use the validation set for hyperparameter tuning and choosing the stopping point for training the MLP classifier, and use the test set to evaluate the resulting classifiers. We consider two different evaluation criteria: the Area Under the ROC Curve (AUROC) and the Area Under the Precision-Recall curve (AUPR). We select these two metrics because they allow us to rigorously compare the discriminative capabilities of our models and baselines on unbalanced classes, without having to specify a particular threshold for what we consider a "positive" or "negative" classification.

Table 2 shows the performance of all methods on three tasks. We see that for all

three tasks, the transformer produced representation achieved substantially improved performance for both AUROC and AUPR. This confirms that our approach learns a transformer model that produces robust sample representation that performs well across multiple prediction tasks.

Table 2. Average performance (standard deviation) on Three Tasks

	IBD Task		Fruit Diet Task		Vegetable Diet Task	
	AUROC	AUPR	AUROC	AUPR	AUROC	AUPR
Weighted	0.777(.03)	0.391(.05)	0.581(.02)	0.697(.02)	0.663(.01)	0.927(.004)
PCA	0.743(.04)	0.406(.05)	0.630(.01)	0.718(.01)	0.679(.02)	0.927(.01)
RandP	0.722(.02)	0.378(.04)	0.606(.02)	0.697(.02)	0.662(.02)	0.920(.01)
AE_{Best}	0.711(.03)	0.370(.05)	0.606(.01)	0.704(.02)	0.662(.03)	0.920(.01)
AE_{Match}	0.690(.03)	0.336(.02)	0.595(.01)	0.695(.01)	0.654(.02)	0.919(.01)
CAE_{Best}	0.716(.04)	0.390(.06)	0.638(.01)	0.726(.02)	0.668(.03)	0.919(.01)
CAE_{Match}	0.717(.05)	0.385(.06)	0.629(.01)	0.719(.01)	0.665(.03)	0.919(.01)
Transformer	0.802(.02)	0.529(.07)	0.676(.01)	0.777(.01)	0.735(.03)	0.949(.01)

3.2 Generalization to independent datasets

One of the largest challenges in working with microbiome data is that there is large variance in the distributions and characteristics of data used from study to study. Therefore it is important to test how well our transformer based prediction models generalize on independent datasets that come from different population/sample distributions. To test this, we applied our transformer model trained for the IBD prediction task using the AGP data on the Halfvarson and HMP2 datasets from independent studies.

An issue that arises when performing such cross-study tests is the need to decide a stopping point during finetuning to pick the best model to use on the test data. In the previous single study experiments, using a held-out validation set for this purpose proved to be an effective strategy. However, due to the substantial distributional shift between the AGP data used for training/validation and the independent test set of Halfvarson and HMP2, using a held-out AGP validation set for stopping is observed to lead to poor and highly unstable results (shown by "Transformer (original)" in Table 3). We address this problem by introducing a simple ensemble strategy. During fine tuning, we train an ensemble of k classifiers using different random initializations of the classification head. Similar to the standard practice when applying transformer to language [26], we found that each individual classifier only needs to be fine-tuned for a

⁴⁰² single epoch, i.e., going over all of the training once, and that training more epochs

⁴⁰³ often leads to overfitting. In our experiments, we used ensemble size $k = 10$.

⁴⁰⁴ We compare our ensemble performance with the baselines described above, and

⁴⁰⁵ additionally strengthen the Weighted baseline of [13] by using an ensembled MLP

⁴⁰⁶ classifier and reporting the best *testing* performance achieved by the Weighted baseline

⁴⁰⁷ method during training. The baselines from [30] use random forest as the classifier and

⁴⁰⁸ do not have a similar free parameter regarding their stopping condition.

⁴⁰⁹ We report the performance of all methods averaged across five random runs with

⁴¹⁰ different initialization in Table 3. The results show that our method consistently

⁴¹¹ achieves better performance on the Halfvarson dataset compared to all baselines, and

⁴¹² comparable performance on the HMP2 dataset compared to the best performing of the

⁴¹³ Weighted baseline model selected using testing data. Although CAE_{Best} and CAE_{Match}

⁴¹⁴ achieve slightly higher HMP2 performance, this comes at the cost of an enormous deficit

⁴¹⁵ on Halfvarson. These results illustrate our approach's ability to consistently generalize

⁴¹⁶ well to out of distribution settings.

Table 3. Average performance (standard deviation) on independent IBD datastes. Weighted's standard deviation is close to zero, thus omitted.

	HMP2		Halfvarson	
	AUC	AUPR	AUC	AUPR
Weighted (ensemble)	0.668	0.863	0.752	0.962
PCA	0.570 (.02)	0.795 (.01)	0.578 (.06)	0.931 (.01)
RandP	0.583 (.03)	0.813 (.02)	0.509 (.03)	0.909 (.01)
AE_{Best}	0.618 (.02)	0.839 (.01)	0.519 (.02)	0.912 (.01)
AE_{Match}	0.644 (.02)	0.850 (.01)	0.499 (.05)	0.903 (.02)
CAE_{Best}	0.697 (.01)	0.879 (.01)	0.426 (.04)	0.890 (.01)
CAE_{Match}	0.706 (.04)	0.883 (.04)	0.488 (.04)	0.906 (.01)
Transformer (original)	0.460 (.03)	0.773 (.02)	0.719 (.09)	0.957 (.02)
Transformer (ensemble)	0.682 (.02)	0.855 (.01)	0.805 (.01)	0.973 (.001)

⁴¹⁷ In this section we take a closer look at the pre-trained language model to interpret

⁴¹⁸ the learned context-sensitive representations of microbial species.

3.3 Context sensitive taxa embedding captures biologically meaningful information

⁴²¹ We hypothesize that the superior predictive performance of our model is because our

⁴²² pre-trained language model transforms the input taxa embedding into a more

Fig 4. t-SNE visualization of (a) original taxa vocabulary embeddings and (b) contextualize taxa embeddings. Both are colored by phylum. See Figure 9 for embedding spaces colored by phylum, class, order, and family.

meaningful latent space capturing context sensitive information (Fig. 1G), making biologically relevant features of the taxa more readily extracted and applied to downstream tasks.

Phylogenetic information. We focus on the top 5000 (out of 26726) most frequent taxa from the IBD dataset and compute their averaged contextualized embeddings across every entry in the IBD dataset. Fig. 4 shows the t-SNE [33] visualization of the taxa using the original vocabulary embedding from [13] (a) and the averaged contextualized embeddings produced by our model (b), colored by the phylum of the taxa assigned by the DADA2 tool [34].

From Fig. 4, we see that the original embedding space in panel (a) displays a degree of clustering by phylum. In particular, Proteobacteria (red) tend to cluster in distinct manifolds from the rest of the taxa. However, most of the taxa lie in a single large but stratified manifold of mixed phyla. In contrast, the contextualized representations in panel (b) appear to have more consistent clustering by phylum in this reduced 2-D space. We further verify that the contextualized embedding does cluster more strongly in the full-dimensional embedding spaces with Fig. 5 d), which shows that clusters in the contextualized embedding space consistently have less cross-phylum contamination (as shown by higher phylum purity) as compared to clusters in the GloVe embedding space.

To highlight the differences between the two representations, Figure 5 explores the mapping between them by highlighting the same group of taxa in both figures, where the left column shows the t-SNE visualization of the original taxa embeddings, and the right column shows the t-SNE of the contextualized taxa embeddings. From the

Fig 5. Mapping between the original vocabulary and contextualized embedding spaces. Figure a) shows how the contextualized embeddings can extract "threads" of a single phylum from the vocabulary embedding space, and map those taxa to tight clusters in the contextualized embeddings. Figure b) shows that the mapping to the contextual embedding space is able to more cleanly separate taxa by phylum. Figure c) contrasts Figure b) and shows that taxa which are very tightly clustered in the vocabulary embeddings may not map to meaningful clusters or phylum-level separation in the contextualized embedding space. Figure d) shows cluster purity versus K for K-means clustering in the vocabulary and contextualized embedding spaces, showing the tighter clustering of the embedding space isn't simply an artifact of the t-SNE dimension reduction.

comparison, we can see that the phyla that are well separated in the original embedding

space as distinct manifolds are well preserved and further compacted into tighter

clusters (see Fig. 5 a).

The data in the original vocabulary embedding space appear to lie on long "strands",

rather than clump together in clusters. In particular, we see a large strand in the

middle that contains most of the data, and seems to be made up of smaller "threads"

very close together. The contextual representations appear to "unwind" the large strand

so that the smaller threads can be extracted and grouped together in their own isolated

clusters, which more cleanly separate by phylum (see Fig. 5 a). This highlights the

capability of self-supervised representation learning to flexibly extract important

features from unlabeled data.

Our model's ability to cluster taxa by phylum seems to degrade for taxa whose

vocabulary embeddings are too close together. Figure 5 b) highlights taxa in a less

compact region of the original embedding space, and highlights the same taxa in the

contextualized embedding space, where the taxa show reasonable separation by phylum.

In comparison, Figure 5 c) highlights a more compact region of the vocabulary space, as

well as the corresponding taxa in the contextualized embedding space, which appear to

show worse separation than we see in Figure 5 b).

Metabolic pathways. Similar to [13], we investigate whether our contextualized

embedding dimensions correlate with known metabolic pathways. We use the mapping

from vocabulary taxa ASVs to their nearest neighbor in the KEGG [35] database

computed by [13] using Piphillin [36], then extract metabolic pathways using the

KEGGREST API [37]. Each possible metabolic pathway underwent a one-hot coding (0

if it is absent or a 1 if it is present) for each ASV. Limiting the following analysis to

include only those ASVs that had near neighbors pathway in the database.

We compute the correlations between each embedding dimension of our model's

pretrained taxa representations and the extracted metabolic pathways, and then we

repeat this process for the GloVe embeddings. Then, to ascertain whether those

correlations were significant, we applied a permutation test with 10,000 permutations to

generate a null distribution and filtered the correlation based on this test. We compare

<center>Contextualized   GloVe</center>

Fig 6. Heatmaps showing how strongly each embedding dimension (y-axis) correlates with each metabolic pathway (x-axis), for both our contextualized embeddings and the prior GloVe embeddings.

the strengths of the remaining statistically significant correlations found for our contextualized embeddings to those found for the GloVe embeddings. Figure 6 shows heatmaps for both sets of correlations. We can see that, although both embeddings show clear correlation with some metabolic pathways, the contextualized embedding dimensions capture stronger correlation, signified by the darker blue and red colors in the heatmap.

We further compare the distribution of the statistically significant correlation magnitudes from both embeddings in Figure 7, which shows that the normalized histograms of the contextualized embedding dimensions are shifted to the right compared to that of the GloVe embedding dimensions.

3.4 Understanding taxa importance for IBD prediction

In this part, we focus on the fine-tuned IBD ensemble prediction model to understand what taxa play critical roles in our model's IBD prediction by studying their attribution. We first consider the 5000 most frequent taxa shown in Figure 4 and compute for each taxa its average attribution toward the model's IBD prediction using the AGP IBD data, as described in Sec. 2.3.

Fig 7. Distribution of the magnitude of statistically significant correlations between embedding dimensions and metabolic pathways, for both contextualized embeddings and the prior GloVe embeddings.

Fig 8. t-SNE visualization of the contextualized embeddings colored by attribution to IBD. The taxa associated with IBD are visualized in lighter color (yellow) and the taxa associated with no-disease state are in dark purple.

Figure 8 (a) presents the t-SNE visualizations of the contextualized embeddings colored by taxa attribution strength. We can see one cluster of highly attributing taxa appearing close to the center of the figure, another at the bottom left corner. It is important to note that the contextualized embeddings generated by our pre-trained language model have never been trained on any IBD labels, yet these highly attributing taxa exhibit strong clustering behavior, suggesting that our pre-trained language model indeed captures meaningful biological information.

Next, we wish to find the most important taxa for our model's correct IBD classifications across different study populations. We therefore filter the data to focus on samples for which our model makes confident and correct predictions. Specifically, we filter each of the three IBD datasets (American Gut Project (AGP) [8], the curated [13] versions of the Human Microbiome Project phase 2, (HMP2) [29], and Halfvarson (HV) [28]) and include only correctly classified samples with a predicted probability ranking within the top 50%, regardless of being positive or negative. To focus on reasonably common microbial species, we also filter out taxa that appear in less than 5% of all samples across all three IBD datasets (AGP, HMP2 and HV).

To allow for independent validation of our attribution estimation, we combine HV and HMP2, into a single dataset (HV+HMP2), filter for correct confidence again, and compute the average attribution on APG and HV+HMP2 separately, and reduce noise by filtering out any taxa that appear in less than five samples in each dataset. The attribution for a taxon is considered validated if it has two estimates from AGP and HV+HMP2 respectively, and they have the same sign. Of the 5716 taxa that appear in HV+HMP2, 695 appear in at least 5% of the combined IBD-labeled data points, 530 of those appear in at least five confident and correct samples in HV+HMP2 (and have been assigned attributions), and 399 of those taxa have matching signs in their attributions between the AGP data and the HV+HMP2 data. This ensures that we only identify these microbial species that have consistent impact on the model in two different populations. We then compute the average attribution of all validated taxa across the combined (filtered) datasets. We show the 10 taxa most attributed to negative IBD classification (Table 4) and the 10 taxa most attributed to positive IBD classification (Table 5).

Table 4. Top 10 Taxa associated with negative (non-disease) IBD classification ordered by attribution strength.

Phylum	Class	Order	Family	Genus
Bacteroidetes	Bacteroidia	Bacteroidales	Prevotellaceae	Prevotella
Bacteroidetes	Bacteroidia	NA	NA	NA
Firmicutes	Bacilli	Lactobacillales	Lactobacillaceae	Lactobacillus
Firmicutes	Negativicutes	Selenomonadales	Veillonellaceae	Allisonella
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	Roseburia
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	Ruminococcus_1
Bacteroidetes	Bacteroidia	Bacteroidales	Prevotellaceae	Paraprevotella
Bacteroidetes	Bacteroidia	Bacteroidales	Prevotellaceae	Prevotella_9
Bacteroidetes	Bacteroidia	Bacteroidales	Bacteroidaceae	Bacteroides
Firmicutes	Clostridia	Clostridiales	Lachnospiraceae	Lachnoclostridium

Table 5. Top ten Taxa associated with positive IBD classification ordered by attribution strength.

Phylum	Class	Order	Family	Genus
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	NA
Euryarchaeota	Methanobacteria	Methanobacteriales	Methanobacteriaceae	Methanosphaera
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	NA
Firmicutes	Clostridia	Clostridiales	NA	NA
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	Oscillibacter
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	NA
Actinobacteria	Coriobacteriia	Coriobacteriales	Atopobiaceae	Atopobium
Bacteroidetes	Bacteroidia	Bacteroidales	Tannerellaceae	Parabacteroides
Firmicutes	Clostridia	Clostridiales	Ruminococcaceae	NA
Firmicutes	Clostridia	Clostridiales	NA	NA

Comparing identified taxa to existing data repository

We compared the top 10 ASV attributions to IBD and the healthy cohort (20 ASVs total) found with our model to 284 markers taxa identified in the data repository for the human gut microbiota [38] across three projects (NCBI PRJEB7949 (95 entries), NCBI PRJNA368966 (32 entries), NCBI PRJNA3x85949 (157 entries)) comparing IBD and healthy controls (query request: gmrepo.humangut.info/phenotypes/comparisons/D006262/D015212).

Due to the difference in technologies between all the datasets, we compare the markers across the studies at the genus level. In our study, seven ASVs were not resolved beyond the family level, and are therefore excluded from this analysis. Further, two of our ASVs belonged to sub-clade of a genus, we considered them belonging to the genus of the clade: specifically Prevotella_9 (which was considered Prevotella in this analysis) and Ruminoccocus_1 (which was considered Ruminoccocus in this analysis).

Out of our 13 ASVs, four ASVs belong to genera Prevotella, Paraprevotella, and Lachnoclostridium, which were also found to be consistently associated with the healthy

cohort in the data repository for the human gut microbiota (DRHM). Therefore they constitute consistent markers with the previous literature. One ASV, belonging to the genus Atopobium, was only associated with IBD in both our study and the DRHM, also constituting a markers of IBD consistent across our study and the database. Out of the remaining eight, we found two new ASVs markers that were not previously identified: the genera Allisonella (Associated with health) and Methanosphaera (associated with IBD).

Finally, the six remaining ASVs showed mixed patterns in the DRHM, where some species of the genus seem to be a marker for the IBD and other species are enriched in healthy individuals. Out of these six genera, three markers mostly agree with our results: Bacteroides, which was associated with healthy individuals in 17/20 species, Ruminococcus showing the same pattern in 5/9 species, and Rosebduria also with the same pattern for species. The other three genera show the opposite trend when comparing the DRHM markers with our work. Most notably, Lactobacillus is associated with the healthy cohort in our analysis, while 8/9 markers from this genus are enriched in the IBD cohort in the DRHM. We see more nuanced results for the genera Parabacteroides where 3/7 markers are associated with the control cohort in the DRHM (and a marker of IBD for us), as well as Oscillibacter, associated with the healthy individuals in species in the database, which contradict our finding.

In summary, out of the 13 ASVs resolved at the genus level from our study, our analysis revealed two new markers not included in the DRHM. For five of these ASVs, our result is consistent with the DRHM markers. For the remaining three, we see mixed results. Here, the taxonomic resolution of our 16S becomes a limiting factor as these genera show different behavior at the species level.

4 Conclusion and Future Work

We apply recent natural language processing techniques to learn a language model for microbiomes from public domain human gut microbiome data. The pre-trained language model provides powerful contextualized representations of microbial communities and can be broadly applied as a starting point for any downstream prediction tasks involving human gut microbiome. In this work, we show the power of

the pre-trained model by fine-tuning the representations for IBD disease state and diet classification tasks, achieving strong performance in all tasks. For IBD, our ensemble model demonstrates competitive performance that is robust across study populations even with strong distributional shifts.

We visualize the contextualized taxa embedding learned by our pre-trained language model and show that it captures biologically meaningful information including phylogenetic structure and IBD association without any prior training on such signals. We employ an interpretability technique to investigate the basis for our models' IBD classification decisions and identify sets of taxa that negatively and positively attribute to the model's predictions. We find known biomarkers of both IBD and gut homeostasis, as well as evidence that our embeddings learn to separate ASVs by their pathogenicity, even among ASVs sharing the same family and genus level phylogenetic classifications.

Our investigation suggests that NLP techniques like deep language models represent a promising direction to better understand the microbiome. However, our effort is limited in both volume and breath of the data that is used for training the microbial language model. Currently, our pre-trained model is primarily optimized for tasks involving human gut microbiomes based on 16S data. Despite this, the utility of our model extends beyond its initial configuration. With adjustments, our methodology can be highly versatile, offering numerous paths for generalization.

Specifically, it is possible to adapt our pre-trained language model directly to other sources and types of microbiome data, such as taxonomic profiles of Metagenome Assembled Genomes (MAGs), by replacing the initial embedding layer with one that is fine-tuned using the new source of data. Strong precedents in natural language processing support the feasibility of this approach, where pretrained model from one domain had been shown to lead to predictable transfer when adapted to another domain (e.g., from Python code to natural text [39], or from natural text to image classification [40]). Finally, we are enthusiastic about the potential to develop a unified model by training on a broad spectrum of microbiome data, encompassing various sources and modalities, to create a generalized, versatile microbiome model capable of instantaneous adaptation to the varied data distributions encountered in different studies and methodologies across the microbiome research landscape.

Acknowledgments

We thank the National Science Foundation for the funding of this work under grant number URoL:MTM2 2025457.

References

1. Kostic AD, Chun E, Robertson L, Glickman JN, Gallini CA, Michaud M, et al. Fusobacterium nucleatum Potentiates Intestinal Tumorigenesis and Modulates the Tumor-Immune Microenvironment. Cell Host & Microbe. 2013;14(2):207–215. doi:https://doi.org/10.1016/j.chom.2013.07.007.

2. Jiang H, Ling Z, Zhang Y, Mao H, Ma Z, Yin Y, et al. Altered fecal microbiota composition in patients with major depressive disorder. Brain, Behavior, and Immunity. 2015;48:186–194. doi:https://doi.org/10.1016/j.bbi.2015.03.016.

3. Zheng P, Zeng B, Zhou C, Liu M, Fang Z, Xu X, et al. Gut microbiome remodeling induces depressive-like behaviors through a pathway mediated by the host's metabolism. Molecular Psychiatry. 2016;21(6):786–796. doi:10.1038/mp.2016.44.

4. Frank DN, St Amand AL, Feldman RA, Boedeker EC, Harpaz N, Pace NR. Molecular-phylogenetic characterization of microbial community imbalances in human inflammatory bowel diseases. Proceedings of the National Academy of Sciences. 2007;104(34):13780–13785. doi:10.1073/pnas.0706625104.

5. Gevers D, Kugathasan S, Denson L, Vázquez-Baeza Y, Van Treuren W, Ren B, et al. The Treatment-Naive Microbiome in New-Onset Crohn's Disease. Cell Host & Microbe. 2014;15(3):382–392. doi:10.1016/j.chom.2014.02.005.

6. Ni J, Shen TCD, Chen EZ, Bittinger K, Bailey A, Roggiani M, et al. A role for bacterial urease in gut dysbiosis and Crohn's disease. Science Translational Medicine. 2017;9(416):eaah6888. doi:10.1126/scitranslmed.aah6888.

7. Gilbert JA, Blaser MJ, Caporaso JG, Jansson JK, Lynch SV, Knight R. Current understanding of the human microbiome. Nature Medicine. 2018;24(4):392–400. doi:10.1038/nm.4517.

8. McDonald D, Hyde E, Debelius JW, Morton JT, Gonzalez A, Ackermann G, et al. American Gut: an Open Platform for Citizen Science Microbiome Research. mSystems. 2018;3(3). doi:10.1128/mSystems.00031-18.

9. McMurdie PJ, Holmes S. phyloseq: an R package for reproducible interactive analysis and graphics of microbiome census data. PloS one. 2013;8(4):e61217.

10. Brooks AW, Priya S, Blekhman R, Bordenstein SR. Gut microbiota diversity across ethnicities in the United States. PLoS biology. 2018;16(12):e2006842.

11. Washburne AD, Morton JT, Sanders J, McDonald D, Zhu Q, Oliverio AM, et al. Methods for phylogenetic analysis of microbiome data. Nature microbiology. 2018;3(6):652–661.

12. Woloszynek S, Zhao Z, Chen J, Rosen GL. 16S rRNA sequence embeddings: Meaningful numeric feature representations of nucleotide sequences that are convenient for downstream analyses. PLoS computational biology. 2019;15(2):e1006721.

13. Tataru CA, David MM. Decoding the language of microbiomes using word-embedding techniques, and applications in inflammatory bowel disease. PLOS Computational Biology. 2020;16(5):e1007859. doi:10.1371/journal.pcbi.1007859.

14. Pennington J, Socher R, Manning CD. GloVe: Global Vectors for Word Representation. In: Empirical Methods in Natural Language Processing (EMNLP); 2014. p. 1532–1543. Available from: http://www.aclweb.org/anthology/D14-1162.

15. Kmann C, Dicksved J, Engstrand L, Rautelin H. Composition of human faecal microbiota in resistance to Cylobacter infection. Clinical Microbiology and Infection. 2016;22(1):61.e1–61.e8. doi:10.1016/j.cmi.2015.09.004.

16. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention Is All You Need. arXiv:170603762 [cs]. 2017;.

17. Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Wang Y, Jones L, et al. ProtTrans: Toward Understanding the Language of Life Through Self-Supervised

Learning. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2022;44(10):7112–7127. doi:10.1109/tpami.2021.3095381.

18. Heinzinger M, Elnaggar A, Wang Y, Dallago C, Nechaev D, Matthes F, et al. Modeling aspects of the language of life through transfer-learning protein sequences. BMC Bioinformatics. 2019;20(1). doi:10.1186/s12859-019-3220-8.

19. Brandes N, Ofer D, Peleg Y, Rappoport N, Linial M. ProteinBERT: a universal deep-learning model of protein sequence and function. Bioinformatics. 2022;38(8):2102–2110. doi:10.1093/bioinformatics/btac020.

20. Rives A, Meier J, Sercu T, Goyal S, Lin Z, Liu J, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. Proceedings of the National Academy of Sciences. 2021;118(15):e2016239118. doi:10.1073/pnas.2016239118.

21. Ji Y, Zhou Z, Liu H, Davuluri RV. DNABERT: pre-trained Bidirectional Encoder Representations from Transformers model for DNA-language in genome. Bioinformatics. 2021;37(15):2112–2120. doi:10.1093/bioinformatics/btab083.

22. Shaw P, Uszkoreit J, Vaswani A. Self-Attention with Relative Position Representations. In: Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers). Association for Computational Linguistics; 2018.

23. Huang Z, Liang D, Xu P, Xiang B. Improve Transformer Models with Better Relative Position Embeddings. In: Findings of the Association for Computational Linguistics: EMNLP 2020; 2020. p. 3327–3335.

24. Ericsson L, Gouk H, Loy CC, Hospedales TM. Self-Supervised Representation Learning: Introduction, advances, and challenges. IEEE Signal Processing Magazine. 2022;39(3):42–62. doi:10.1109/MSP.2021.3134634.

25. Clark K, Luong MT, Le QV, Manning CD. ELECTRA: Pre-training Text Encoders as Discriminators Rather Than Generators. arXiv:200310555 [cs]. 2020;.

26. Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. arXiv:181004805 [cs]. 2019;.

27. Zeiler MD, Fergus R. Visualizing and Understanding Convolutional Networks. In: Fleet D, Pajdla T, Schiele B, Tuytelaars T, editors. Computer Vision – ECCV 2014. Cham: Springer International Publishing; 2014. p. 818–833.

28. Halfvarson J, Brislawn CJ, Lamendella R, Vázquez-Baeza Y, Walters WA, Bramer LM, et al. Dynamics of the human gut microbiome in inflammatory bowel disease. Nature Microbiology. 2017;2(5):17004. doi:10.1038/nmicrobiol.2017.4.

29. Lloyd-Price J, Arze C, Ananthakrishnan AN, Schirmer M, Avila-Pacheco J, Poon TW, et al. Multi-omics of the gut microbial ecosystem in inflammatory bowel diseases. Nature. 2019;569(7758):655–662. doi:10.1038/s41586-019-1237-9.

30. Oh M, Zhang L. DeepMicro: deep representation learning for disease prediction based on microbiome data. Scientific Reports. 2020;10(1). doi:10.1038/s41598-020-63159-5.

31. Dasgupta S, Gupta A. An elementary proof of a theorem of Johnson and Lindenstrauss. Random Structures ; Algorithms. 2002;22(1):60–65. doi:10.1002/rsa.10073.

32. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine Learning in Python. Journal of Machine Learning Research. 2011;12:2825–2830.

33. van der Maaten L, Hinton G. Visualizing Data using t-SNE. Journal of Machine Learning Research. 2008;9(86):2579–2605.

34. Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJA, Holmes SP. DADA2: High-resolution sample inference from Illumina amplicon data. Nature methods. 2016;13(7):581—583. doi:10.1038/nmeth.3869.

35. Kanehisa M, Goto S. KEGG: kyoto encyclopedia of genes and genomes. Nucleic acids research. 2000;28(1):27–30.

36. Narayan NR, Weinmaier T, Laserna-Mendieta EJ, Claesson MJ, Shanahan F, Dabbagh K, et al. Piphillin predicts metagenomic composition and dynamics from DADA2-corrected 16S rDNA sequences. BMC Genomics. 2020;21(1). doi:10.1186/s12864-019-6427-1.

37. Tenenbaum D, Maintainer B. KEGGREST: client-side REST access to the Kyoto Encyclopedia of Genes and Genomes (KEGG). R package. In: KEGGREST: client-side REST access to the Kyoto Encyclopedia of Genes and Genomes (KEGG). R package; 2018.

38. Dai D, Zhu J, Sun C, Li M, Liu J, Wu S, et al. GMrepo v2: a curated human gut microbiome database with special focus on disease markers and cross-dataset comparison. Nucleic Acids Research. 2021;50(D1):D777–D784. doi:10.1093/nar/gkab1019.

39. Hernandez D, Kaplan J, Henighan T, McCandlish S. Scaling Laws for Transfer; 2021.

40. Lu K, Grover A, Abbeel P, Mordatch I. Frozen pretrained transformers as universal computation engines. In: Proceedings of the AAAI conference on artificial intelligence. vol. 36; 2022. p. 7628–7636.

Supporting information

Experiment name	Time (hr)	Cost ($)
Pretraining	23.43	9.44
Fine-tuning IBD (5-fold cross validation)	6.10	2.46
Fine-tuning Fruit (5-fold cross validation)	6.99	2.82
Fine-tuning Vegetable (5-fold cross validation)	5.37	2.16

Table 6. Runtimes and estimate costs of different experiments performed in this paper. All runtimes were measured on a single Nvidia A40 GPU, and costs are estimated based on the hourly price of $0.403 required to rent an Nvidia A40 from vast.ai as of 03/11/2024.

Fig 9. Vocabulary and contextualized embedding spaces colored by different levels of the phylogenetic hierarchy: phylum, class, order, and family.