Evidence of an optimal error rate for motor skill learning

Naser Al-Fawakhiri[1], Sarosh Kayani[2], & Samuel D. McDougle[3,4]

1. Department of Neuroscience, Johns Hopkins School of Medicine, Baltimore MD 21205
2. Department of Neuroscience, Yale School of Medicine, New Haven CT 06520
3. Department of Psychology, Yale University, New Haven CT 06520
4. Wu Tsai Institute, Yale University, New Haven CT 06520

Correspondence: Naser Al-Fawakhiri
aalfawa1@jh.edu
Solomon H Snyder Department of Neuroscience
Johns Hopkins School of Medicine
725 N. Wolfe St., Baltimore MD 21205

Abstract

When acquiring a motor skill, learners must practice the skill at a difficulty that is challenging but still manageable to gradually improve their performance. In other words, during training, the learner must experience success as well as failure. Does there exist an optimal proportion of successes and failures to promote the fastest improvements in skill? Here, we build on a recent theoretical framework for optimal machine learning, extending it to the learning of motor skills. We then designed a custom task whose difficulty dynamically changed along with human subjects' performance, constraining the error rate during training. In a large behavioral dataset (N=192), we observed evidence that learning is greatest at around a ~30% error rate, matching our theoretical predictions.

Key words: motor skill; motor learning; optimal learning; training curriculum

Introduction

Acquiring a new motor skill involves reducing errors (Krakauer & Mazzoni, 2011; Ohlsson, 1996; Tseng

et al., 2007). Consider learning to shoot free throws in basketball: After a miss, the player uses the

observed error information (e.g., "I missed to the right") to fine-tune future attempts (e.g., re-orienting the

shot slightly left). Such performance errors during motor skill learning drive improvements in both

accuracy and precision and, given enough time and practice, can lead to automaticity and expertise (Haith

et al., 2022; Shmuelof et al., 2012; Yang et al., 2022).

Importantly, one's error rate during training can relate to if, and how well, they learn a skill. In the

extreme, if one *never* experienced success, their motor system may have no template upon which to

improve their skill (Sanger, 2004). On the other hand, learning would be unnecessary if one always

experienced success (e.g., the hoop moved to wherever the ball was thrown). Thus, it is reasonable to

assume that there is a "sweet spot" error rate that may generate the most efficient learning process

(Guadagnoli & Lee, 2004). Indeed, in the context of simple non-motor skills (e.g., perceptual decision-

making) it has recently been proposed that an optimal proportion of success and failure – an optimal

"error rate" – can maximize the learning rate of a perceptual skill, such as binary categorization of

sensory input (Wilson et al., 2019). Here, we extend this logic to the domain of sensorimotor skill

learning.

In any task, errors become more likely as the difficulty of the task increases. Since the difficulty of the

task can often be externally modulated, controlling an individual's error rate during training requires

dynamically controlling the difficulty of the task in response to their performance, exemplified by classic

psychophysical methods like "staircasing" (Cornsweet, 1962). But how does task difficulty influence

learning? In an influential framework proposed by Wilson and colleagues (2019), it was shown that

learning using a gradient descent algorithm mathematically specifies an optimal error rate with very few

additional assumptions needed. The authors considered the context of a binary discrimination task and,

using their framework, predicted an optimal error rate of ~15%, a value that was validated by multiple

simulations over a range of binary decision-making tasks.

Can a similar framework be applied to motor skill learning? The first relevant issue is the putative

relationship between motor skill learning and gradient descent. It has been suggested that motor skill

learning, at least in the form of gradual improvements in skill that reduce errors and improve precision

(Diedrichsen & Kornysheva, 2015; Sternad, 2018), does indeed operate via a gradient descent process

(Greenstreet et al., 2025; Haith, 2025; Pierella et al., 2019). In many motor skills, the learner begins with

an initially noisy policy and gradually refines this policy, reducing the variability of their actions as their

skill improves (Haith, 2025; Sternad, 2018). For example, a novice darts player may make errors that span

the whole width of the dartboard initially. But, as they improve, they gradually decrease their variability

to hone in on a particular region of the board.

Here, we hypothesized that the framework proposed by Wilson and colleagues (2019) might apply to

motor skill learning of the form described above, even though motor errors are both signed and

continuous (rather than binary and unsigned, as in perceptual discrimination tasks). First, we analytically

extended their model to demonstrate that a roughly 32% error rate may be the optimal error rate for motor

skill learning, given some basic assumptions. After specifying this prediction, we developed a customized

"Pong" task that required precise online visuomotor control and collected behavioral data on the task

from a large sample of human participants (N = 194). Using a custom dynamic error-control algorithm,

we modified the size of subjects' Pong paddle on a trial-by-trial basis to impose different error rates on

their performance and measured their improvements in the task.

Strikingly, the results of the behavioral experiment appeared to support our predictions – we found

reliable evidence that individuals with an error rate around ~32% showed the most learning in the task,

directly in line with our model simulations. The current work provides a theoretically grounded

specification of a putative optimal error rate for motor learning, and may thus inform both practical

applications (e.g., sport pedagogy, clinical rehabilitation protocols) and theories concerning the

underlying neural algorithms for motor skill learning.

An Optimal Error Rate Framework for Motor Skill Learning in One Dimension

In an idealized motor learning task, an agent prepares an action a in response to some set of internal

conditions or policy π and external stimuli or state s. Thus,

$a = \Phi(\pi, s, \phi)$ (1)

where $\Phi(\cdot)$ represents the function that transforms π and s into motor actions, and ϕ is a set of internal,

tunable free parameters trained by learning.

Whenever an action is executed, it is evaluated in terms of the discrepancy between the actual movement

outcome a and the intended outcome i. This discrepancy is a motor error e

$e = a - i$ (2)

Here, motor learning consists of minimizing this error (distance from the center of a dart board, a golf

hole, or a basketball hoop; in our Pong task, the distance of the puck from the center of the paddle). We

further assume that errors are normally distributed around the target action and that there is no systematic

bias (i.e., the mean of the policy is the optimal solution). Thus, e can be rewritten as a Gaussian with zero-

mean and a standard deviation of σ

$e \sim N(0, \sigma)$ (3)

While we assume a normal distribution, any symmetrical, zero-mean error distribution can be used and

will converge to an optimal error rate that depends on the specific choice of error distribution.

Both laboratory and naturalistic motor tasks typically have some degree of error tolerance, Δ, which still

permits task success despite noise. This tolerance can take many forms: the radius of the green or the hole

in golf, the radius of the dartboard when shooting darts, the width of the basketball hoop; or, in our Pong

task, the center-to-edge length of the paddle.

Under these conditions, the error rate at any point in the task can be formalized as:

$$\hspace{10cm}(4)$$

where $p(\ )$ is the standardized error distribution, here a normal distribution,   is the Gaussian error

function, and   is the agent's motor precision. In our case, would be the inverse of the root-

mean-squared-error (RMSE) centered around the intended outcome i (i.e., the center of the paddle in

Pong, or the center of the target).

The goal of learning is to reduce error, which would require tuning the parameters   in order to generate

an action a as close to i as possible. This amounts to tuning the parameters of the policy to increase the

precision of the policy around the optimal solution, thereby increasing   (Greenstreet et al., 2025; Haith,

2025; Sternad, 2018). Assuming tuning of these parameters is done through a gradient descent process,

we can formalize the learning process over time as:

$$\hspace{10cm}(5)$$

where η is the stepwise learning rate of the gradient descent algorithm. Given Equation 4, the derivative

of the error rate — can be rewritten via the chain rule:

$$\hspace{10cm}(6)$$

The first term of the right-hand side is the only term which depends on   , the task error tolerance (which

can be experimentally controlled), as the second term only reflects how precision changes with the tuning

of the relevant internal parameters outside of experimental control. Thus, to maximize the learning rate in

Equation 5, we must maximize — by optimizing the task error tolerance   at each time point t in training

(see *Methods*). Using Equation 4, — is given by:

—— —   (7)

To maximize Equation 7, we must find its critical points by taking the derivative with respect to the error

tolerance   and setting this derivative to zero:

——— —   (8)

Simple algebraic manipulation of Equation 8 leads to:

═   (9)

which can be plugged directly into Equation 4 to solve for the optimal error rate:

142   ═   (10)

143   In other words, in this framework, the optimal error rate for motor learning in a one-dimensional task is

144   31.73%, and an optimal training schedule should aim to maintain performance at a 68.27% success rate

145   throughout.

Figure 1. Derivation of an optimal error rate for motor learning. Figure adapted from Wilson et al. (2019). (A) Probability distributions of a given motor error e, within a certain error tolerance Δ. Shaded area represents the probability of a failure, or the error rate. Across training, the magnitude of errors shrinks, resulting in increased precision β. (B) As the error tolerance Δ increases (i.e. decreasing difficulty), fewer actions result in failures, leading to a decrease in the error rate. (C) The learning rate is given by the derivative of the error rate (ER) with respect to the agent's precision β. Maximal learning occurs at an error tolerance Δ^* which changes with skill/training (β). (D) Same as C but replotted with the corresponding error rates on the x-axis. The optimal error rate remains constant, regardless of precision β, at ~31.73%.

Methods

Participants

200 participants (N=50/group; 46% female; age: 27±5) were recruited online through Prolific. Sample

size was not determined by a-priori power analysis; instead, this sample size was chosen to ensure

adequate inter-subject variation in error rates for our final analysis, which required subjects to complete

the task with a wide range of experienced error rates. Recruitment was restricted to right-handed or

ambidextrous individuals in the United States between the ages of 18 and 35, who had at least 40 prior

Prolific submissions. All participants provided informed consent, in accordance with procedures approved

by the Yale University Institutional Review Board (Protocol #2000027351 Psychological Mechanisms of

Skill Learning). Due to participant data not posting to the database, two participants did not have any data

recorded. Four participants were further excluded due to not making any recorded movements during the

task. In analyses of learning indices (see *Statistical Analyses*), subjects whose learning index deviated by

3 times the group standard deviation from the group mean were excluded. This excluded 2 subjects. The

final experimental sample was 192 subjects.

Task Design and Protocol

This study was not pre-registered. Participants were recruited on Prolific to play a modified version of the

game Pong, written using PhaserJS 3 (phaser.io). Participants controlled a 15-pixel wide rectangular

paddle, initially set to 200 pixels (px) in length and fixed 10 px from the left edge of the workspace,

inside a 1000 px by 800 px arena enclosed within a white border. Movements of subjects' mouse or

trackpad in the coronal plane directly translated to displacements of the paddle's vertical position (i.e.,

movements away from the body = up; toward = down). Participants were instructed to move the paddle to

intercept a small circular puck (14 px diameter) which would move toward their paddle at an angle,

bouncing off the walls of the arena. They were specifically instructed to try to cause the puck to hit the

middle of the paddle, as this is the strategy most likely to result in success. This task required participants

to integrate visual sensory information regarding the position of the puck into their movements of the

paddle in order to successfully intercept the puck.

Each trial consisted of the puck crossing from 25 pixels left of the right side of the arena to the left side of

the arena where the participant's paddle was located, crossing a horizontal distance of 975 px. At the start

of each trial, the paddle's vertical position was always centered, and the puck began at a random vertical

position sampled from a uniform distribution extending ±375 px from the center of the screen. The launch

angle of the puck could be $\pm30\text{-}45°$, to ensure that the trajectory of the puck was unpredictable. The puck

began moving 1000ms after the start of the trial. If participants successfully intercepted the puck, a green

"+10" text prompt would appear in the center of the screen for 1000 ms, indicating success. Otherwise, if

the puck hit the edge of the arena without being intercepted by the paddle, a red "+0" text prompt was

displayed in the center of the screen for 1000 ms, indicating failure. A running points total was displayed

above the arena and participants were told to maximize the points they earned. After presentation of

reward feedback, the paddle was re-centered, and the puck appeared in a new location to start the next

trial.

Calibration and Error-control Algorithm

The experiment began with a 20-trial calibration phase, in which the horizontal speed of the puck was

calibrated to be comfortable for each participant. The vertical speed of the puck was determined by the

launch angle on a given trial. Since the duration of each trial was dependent on the horizontal speed of the

puck, we needed to calibrate this speed to ensure every participant had ample time to react to the puck and

adjust the paddle. The speed was calibrated using a staircase procedure: if the participant failed to

intercept the puck, the horizontal speed was reduced by 75 px/s; if the participant successfully intercepted

the puck, the speed increased by 75 px/s. The speed was initialized at 800px/s. The minimum allowed

speed was 100px/s, but this was never achieved by any participant. This procedure resulted in a 72% (SD:

12%) success rate during the calibration phase.

Since this calibration phase often ended with a speed that slightly exceeded the comfortable range for the

participant, the speed was cut to 80% of the final speed achieved. At this point, a 10-trial baseline began

in which the puck speed and the paddle size were held constant. This allowed us to assess each

participants' initial degree of skill in the game. Mean success was 77% (SD:17%). At this point, the final

70-trial training phase began, and the paddle size was allowed to dynamically update according to a

custom algorithm that monitored the recent distribution of errors to constrain participants' error rates.

Each participant was randomly assigned to one of four groups, each with their own intended error rate:

15%, 30%, 50%, and 65%. On every trial, the puck's final vertical position relative to the final vertical

position of the center of the paddle was added to a sliding 20-trial buffer, regardless of whether the trial

was successful or not. After excluding outliers (defined as 3 times the median absolute deviation from the

median; this is identical to the MATLAB *rmoutliers* function), we computed the root-mean-squared-error

(RMSE) of this 20-trial history. From this we inferred a zero-mean Gaussian distribution with the RMSE

as the standard deviation and, using the CDF of the Gaussian distribution, we computed a paddle size that

would result in the intended error rate. This outlier criterion was chosen to minimize the number of

excluded trials and only detect extreme outliers that could vastly impact the RMSE calculation for the

duration of the 20-trial buffer, as determined by pilot experiments.

Statistical Analysis

The primary dependent measure on each trial was the task error, defined as the difference between the

final vertical position of the puck and the final vertical position of the center of the paddle. Errors from

every ten trials were binned to compute the RMSE, and these RMSEs were inverted in order to estimate

precision, β. We note that the overall pattern of results does not change if the inverse of the standard

deviation of the errors, an alternative measure of precision, was used instead of the inverse RMSE. RMSE

was preferred since participants were instructed to aim to intercept the puck in the middle of the paddle,

so any biases were random and unintentional. Each subject's baseline (trials 21-30) precision was

subtracted from every subsequent bin in the training phase in order to quantify improvement. Average

improvement, or the learning index (LI), was quantified as the average β of all training bins after baseline

correction. Statistical outliers, defined as 1.75 times the interquartile range (IQR) away from the median

of each of the four error rate groups, were excluded. This excluded 10 people (5.15%), leaving us with a

final experimental sample of 184.

Theoretical Modeling

The theoretical predictions plotted in Figure 1 and Figure 3D were computed in the manner described

above. Since the integral of a Gaussian from   to   cannot be analytically solved, it was estimated

using a 100,000-rectangle Reimann sum from -10 to   , a computationally costly but highly accurate

estimate of the integral. 30,000 values of   from 0 to 3 in increments of 0.0001 were used to generate the

traces in Figure 1 as well as to generate a function that translated   values into theoretically predicted

learning rates ──, using the *approxfun* function in R (Becker, 2018). Since the units of these predicted

learning rates are arbitrary, we fit scaling and offset free parameters that allowed the predictions to match

the observed precision improvements of our subjects using R's optim function most closely, and the

resulting trace was plotted in Figure 3C.

Materials and Data Availability

The Pong task used in this experimentcan be found at pong-baseball-fast.netlify.app. Error rate can be

specified using the URL parameter "GROUP=XX", where XX is the intended error rate as a percentage

(default value is 30). Data and analysis code can be found at

https://osf.io/ew726/overview?view_only=61050a15edb746d1998444bb903e0142.

Skill improvement in a one-dimensional motor task is optimized when performance is maintained

near a 30% error rate

We aimed to test our theoretically grounded "optimal error rate" for motor learning using a motor skill

task fashioned after the video game Pong. In this task, participants (N=192) controlled the vertical

position of a rectangular paddle using a mouse or touchpad to intercept a small white puck that moved

across the screen at various angles. If participants successfully intercepted the puck with the paddle, their

movement was considered successful, and they were awarded 10 points. If the puck intersected the

vertical axis of the paddle without striking the paddle, a red "0" flashed on the screen, indicating failure.

To scale the difficulty of the task with participants' evolving skill level and thus maintain as close to a

fixed error rate as possible during training, the paddle's size dynamically changed across trials according

to the distribution of participants' errors from the center of the paddle over the most recent 20 trials (see

Methods for details). Participants were randomly sorted into 4 groups, each with an imposed error rate:

15%, 30%, 50%, and 65%. It should be noted that, while the dynamic paddle size aimed to constrain

participants' error rates to these pre-specified levels, variation in error rate was possible, and each

participant indeed experienced their own unique error rate during training (Fig. 2B).

After an initial 20-trial calibration phase in which the puck was calibrated to move at a reasonable speed

(see *Methods*), and 10 baseline trials where both the puck speed and paddle size were held constant,

participants completed 70 training trials in which the paddle size varied with their performance. To track

performance improvements across the task, we computed the root-mean-squared-error (RMSE) of the

puck's final position relative to the center of the final position of the user-controlled paddle for every 10-

trial bin. As a proxy for precision, we inverted this RMSE to yield β – β is low when precision is low, and

high when precision is high. Since every participant entered the task at various degrees of skill, we

corrected these   values using the 10-trial baseline in order to measure each participant's *improvement*

(i.e., learning) across the length of the task. A "learning index" (LI) was quantified as the average   over

all 70 training trials.

Baseline rates of successful puck interception were not different between groups, and the average success

rate in the baseline was 77% (SD:17%). The dynamic updates to the paddle size (see *Methods*)

successfully constrained participants' error rates across groups (Fig. 2). We note that the 65% error rate

group did have modestly but significantly greater success than the intended 35% success rate (t(48)=3.03,

p=0.004), averaging 41.6% success (SD: 6.1%) after the baseline. Participants' true error rates, defined as

the percentage of miss trials during the 70-trial baseline phase, on average undershot the intended error

rate by 3.1% (SD: 6.6%), or 2.2 (SD: 4.6) trials. These details were not particularly consequential, as our

goal was simply to generate a wide distribution of different error rates across participants to test our

theoretical predictions of learning rate.

Figure 2. Task description. (A) Participants played a modified version of Pong, where they could control the
paddle's vertical position with their mouse in order to intercept the moving puck. (B) The paddle's length was
dynamically controlled on each trial by an algorithm designed to control the error rate across trials. Each participant
was randomly assigned to one of four groups, each with a specific error rate ("ER"; 15%, 30%, 50%, 65%). The
algorithm was largely successful in limiting the success rates of participants in each group. Shading reflects mean ±
1 S.E.M.

Regardless of error rate group, participants improved their precision (inverse RMSE,) during the

training phase (Fig. 3A). Participants' precision in the final 10 trials was significantly greater than their

precision in the first 10 training trials (t(386)=2.36, p=0.02, d=0.24), and participants' overall

improvement, or Learning Index (LI;   averaged across all 70 training trials) was significantly greater

than zero (t(193)=4.33, p=2.4x10^{-5}, d=0.31).

Different error rate groups exhibited different time courses and degrees of improvement (Fig. 3B, C). As

predicted, the 30% error rate group exhibited the greatest LI over all four groups: Their LIs were

significantly greater than the 15% group (t(89)= 3.11, p=0.003, d=0.65), and marginally greater than the

65% group (t(87)=1.58, p=0.12, d=0.33), but not significantly greater than the 50% group (t(94)=0.98,

p=0.32, d=0.20). Critically, as noted above, group-wise comparisons were not particularly appropriate

given individual variation in actually realized error rates.

Figure 3. Optimal learning when training has an error rate of ~31.7%. (A) All participants significantly
improved over the course of training. β values are the baseline-corrected inverse RMSE for each 10-trial bin
(arbitrary units). (B) Each group displayed different degrees and time courses of improvement. (C) Learning index
reflects the average β across all 7 training bins for each subject. The group with the intended learning rate of 30%
exhibited the greatest learning. (D) Individual subjects' error rates plotted against their individual learning index.
The smooth curve reflects the theoretically predicted learning rates for each error rate. *Inset:* Spearman correlation
between subjects' true LI and theoretically predicted LIs for their experienced error rate during training. Shading in
panels A & B and error bars in panels C reflect standard errors of the mean (SEM).
323

Our main analysis involved comparing each participant's LI to the theoretical learning rate predicted by

our model (Fig. 3D). Supporting our theoretical predictions, participants' learning rates significantly

correlated with the learning rate predicted for their experienced error rate during training (Pearson

correlation: R=0.25, p=0.001; Spearman correlation: ρ=0.23, p=0.0003).

In conclusion, our theoretical prediction of an optimal motor skill learning error rate of ~32% was

supported in a large dataset consisting of people performing and improving at a continuous visuomotor

skill task. These data are consistent with the theoretical framework proposed by Wilson et al. (2019), here

generalized to the novel case of motor learning.

Discussion

Here, we developed a new theoretical framework on optimal motor skill learning and employed a novel

Pong-based motor skill task to provide behavioral evidence supporting our theoretical prediction that the

optimal error rate for learning this and similar (one-dimensional) motor skills should be ~32%. By

controlling human subjects' error rates during our Pong task, we could influence how well they learned

throughout the course of training. Our theoretical predictions, which were closely based on recent work

on optimal learning for binary classification tasks (Wilson et al., 2019), were supported both by showing

the strongest learning in the group with the near-optimal error rate and by revealing a significant

correlation between the model predictions and the empirical data across a range of individuals' actual

error rates (Figure 3). We propose that if an error rate of approximately ~32% is maintained throughout

training of a simple (one-dimensional) motor skill, one may expect to observe the greatest improvements

in said motor skill. This discovery echoes work on "error-less" learning paradigms, where high success

rates are maintained throughout training, and the difficulty of the task increases as the learner improves

(Capio et al., 2013; Maxwell et al., 2001). Given the link between our theoretical predictions and the

measured behavioral results, we also speculate that principles of gradient descent could be helpful for

understanding the underlying psychological and neural algorithms for motor skill learning (Greenstreet et

al., 2025).

Why does the error rate during training influence learning?

In the mathematical framework proposed by (Wilson et al., 2019)and extended here, the relationship

between training difficulty and learning is a necessary consequence of tuning the parameters responsible

for generating responses that reduce errors via gradient descent. Such an approach leaves a key question

unanswered: "How does training difficulty result in changes in learning rate?" Multiple psychological

explanations could be useful for addressing this question.

First, the "Challenge Point" framework (Guadagnoli & Lee, 2004) proposes that an agent's performance

at a motor skill is a source of information for future learning and action attempts. Highly expected

outcomes, such as success when the task is easy, yield very little information as the agent can fully predict

the consequences of their action. However, highly unexpected outcomes, such as success when the task is

extremely difficult, are rare but can provide a high degree of information. When facing high difficulty, the

potentially large amount of information available to the learner risks being uninterpretable: Was success

due to sheer luck and/or external factors? What aspects of this motor plan made it more successful than

previous attempts? The optimal "challenge point" occurs at a critical difficulty where a considerable

amount of information can be learned from success while also maintaining a moderate degree of

difficulty, such that outcome information is interpretable. In other words, this requires balancing the

expectation of success (which decreases with increased difficulty and should be low to maximize

potential information) with the functional difficulty (which should also be low to maximize the amount of

interpretable information learned from feedback). The balance of minimizing both the expectation of

success and the functional difficulty to optimize the amount of interpretable information available for

learning results in a fixed optimal error rate during training (Wilson et al., 2019).

Another psychological explanation focuses on the role of reward and motivation in error-based learning.

Motivation to perform well in a task can drive increased sensitivity to errors (Bengtsson et al., 2009),

which in turn can prompt faster learning (Wu et al., 2006). Additionally, rewarding feedback tends to

increase motivation (Bissonette & Roesch, 2016) and can accelerate motor learning (Nikooyan & Ahmed,

2015). Thus, the recent history of successes and failures may prime an "optimal" degree of motivation,

where errors occur in concert with rewarded trials, keeping the agent's error sensitivity and motivation for

success high. Put another way, if the task is too easy, learning would be minimal; but, if the task is too

difficult, successes are too infrequent to generate the benefits to motivation and error sensitivity that are

crucial for maintaining a high learning rate. The balance of these two opposing forces could also result in

an optimal error rate for learning.

The mathematical framework employed here does not allow us to differentiate or speak to these

explanations, nor other higher-level psychological theories not mentioned here. The formation of internal

models for motor learning requires obtaining information about how observed sensory outcomes relate to

internally generated action plans (Abdelghani et al., 2008; Pierella et al., 2019; Thoroughman &

Shadmehr, 2000) in line with the Challenge Point hypothesis (Guadagnoli & Lee, 2004). But reward

feedback has also been shown to enhance motor learning (Galea et al., 2015; Izawa & Shadmehr, 2011;

Nikooyan & Ahmed, 2015), supporting a motivational account as well. Thus, both explanations are

plausible and may reflect how different brain regions (e.g., the cerebellum and basal ganglia, respectively)

contribute to the fine tuning of motor learning-related parameters (Greenstreet et al., 2025; Seidler et al.,

2013). In general, we position our current findings at a more fundamental, algorithmic level.

Extensions and limitations of the current framework

In our experiment, we chose a simple motor task where motor errors are generally assumed to be

normally distributed. However, in some tasks, such as interval timing (Swanton & Matell, 2011), the

distribution of errors may not be normal and may follow other known distributions. As noted by Wilson

and colleagues (2019), the current approach still applies as long as performance improvements in those

tasks are subserved by a gradient descent algorithm, but it would produce a different optimal error rate

specific to that distribution of errors. In other words, an optimal error rate using non-Gaussian error

distributions could be computed using the same equations described here. In tasks where the error

distribution is unknown or cannot be mathematically described, empirical observation or alternative

methods of estimating the distribution must be applied in order to compute the optimal error rate.

We also restricted our consideration to a simple one-dimensional motor skill task (errors were only in the

vertical dimension). However, many motor tasks involve errors in multiple dimensions (e.g., a dart or

archer's arrow may miss the bullseye in both the vertical and horizontal dimensions), which must be

concurrently trained. Future work must be done to extend the optimal error rate framework to these more

complex, naturalistic tasks. An important question which must be considered is whether learning in each

dimension is fully independent, or if learning in one dimension affects learning in the others; the answer

to this question would allow us to better model the error reduction processes involved in learning

complex motor skills when multiple dimensions must be concurrently controlled (Haith et al., 2022;

Pierella et al., 2019). Additionally, distributions of errors in each dimension may not follow similar

mathematical descriptions, requiring more complicated multi-dimensional integrals to optimize the error

rate. Nonetheless, the general mathematical framework demonstrated here can, in theory, be applied to

such multi-dimensional tasks.

Lastly, our task only examines motor learning as defined as the gradual reduction in errors and

improvement of precision over time through practice, which arguably represents only one component of

skill learning (i.e., improvements in "motor acuity"; Krakauer et al., 2019). Other components of motor

learning, including motor adaptation, may be better modeled as changes in the mean of the policy, rather

than gradual refinement of the precision of the policy (Greenstreet et al. 2025). Explicit strategies,

especially early in learning, can cause a learner to abruptly reduce their errors or discover new solutions

(Mazzoni & Krakauer, 2006; Taylor & Ivry, 2011), abruptly shifting the mean of the policy instead of

gradually learning via gradient descent. Explicit strategies, short-term memory, and cognitive insights

during skill learning likely arise from separate cognitive processes not considered here, though they still

make important contributions to skill learning (Haith & Krakauer, 2013; Hillman et al., 2025; McDougle

et al., 2016, 2022; McDougle & Hillman, 2025). The model presented here is primarily concerned with

how the learner learns to decrease the standard deviation of the policy around this mean, assuming the

mean has already been discovered, thereby improving precision and reducing task-relevant variability

(Haith, 2025; Sternad, 2018).

Future Applications

Our results demonstrate that the error rate during training affects the rate of improvement of a simple

visuomotor skill. We think this insight might be broadly applicable across applied domains.

Rehabilitation paradigms, for example, have already recognized the need to adjust the difficulty of

practice to optimally challenge patients and maximize the therapeutic benefit of training sessions (Lee et

al., 2023; Metzger et al., 2014). In sports coaching, the principle of progressively increasing the difficulty

of practice has been widely applied and shown to facilitate improvements in skill (Marraffino et al., 2021;

Wickens et al., 2013; Zahran et al., 2020). Optimistically, these approaches, in both sports pedagogy and

rehabilitation, may benefit from the theory used here to mathematically uncover the sweet spot of training

difficulty for maximum skill improvement.

Summary

We demonstrate that an optimal error rate for performance improvements in a motor skill may exist and

suggest that this optimal error rate is around ~32%. By testing a large cohort of human participants in a

novel motor skill task (a modified version of Pong), we also provide empirical support for this prediction

and demonstrate the potential importance of maintaining a particular error rate throughout training to

maximize performance improvements. This approach may have broader implications in other domains

concerned with optimizing the acquisition, refinement, and rehabilitation of motor skills.

References

Abdelghani, M. N., Lillicrap, T. P., & Tweed, D. B. (2008). Sensitivity Derivatives for Flexible

Sensorimotor Learning. *Neural Computation*, *20*(8), 2085–2111.

https://doi.org/10.1162/neco.2008.04-07-507

Becker, R. (2018). *The New S Language*. Chapman and Hall/CRC.

https://doi.org/10.1201/9781351074988

Bengtsson, S. L., Lau, H. C., & Passingham, R. E. (2009). Motivation to do Well Enhances Responses to

Errors and Self-Monitoring. *Cerebral Cortex*, *19*(4), 797–804.

https://doi.org/10.1093/cercor/bhn127

Bissonette, G. B., & Roesch, M. R. (2016). Neurophysiology of Reward-Guided Behavior: Correlates

Related to Predictions, Value, Motivation, Errors, Attention, and Action. In E. H. Simpson & P.

D. Balsam (Eds.), *Behavioral Neuroscience of Motivation* (pp. 199–230). Springer International

Publishing. https://doi.org/10.1007/7854_2015_382

Capio, C. M., Poolton, J. M., Sit, C. H. P., Holmstrom, M., & Masters, R. S. W. (2013). Reducing errors

benefits the field-based learning of a fundamental movement skill in children. *Scandinavian*

Journal of Medicine & Science in Sports, *23*(2), 181–188. https://doi.org/10.1111/j.1600-

0838.2011.01368.x

Cornsweet, T. N. (1962). The Staircase-Method in Psychophysics. *The American Journal of Psychology*,

75(3), 485–491. https://doi.org/10.2307/1419876

Diedrichsen, J., & Kornysheva, K. (2015). Motor skill learning between selection and execution. *Trends*

in Cognitive Sciences, *19*(4), 227–233. https://doi.org/10.1016/j.tics.2015.02.003

Galea, J. M., Mallia, E., Rothwell, J., & Diedrichsen, J. (2015). The dissociable effects of punishment and

reward on motor learning. *Nature Neuroscience*, *18*(4), Article 4. https://doi.org/10.1038/nn.3956

Greenstreet, F., Geerts, J. P., Gallego, J. A., & Clopath, C. (2025). *Why motor learning involves multiple*

systems: An algorithmic perspective (p. 2025.12.19.695526). bioRxiv.

https://doi.org/10.64898/2025.12.19.695526

Guadagnoli, M., & Lee, T. (2004). Challenge Point: A Framework for Conceptualizing the Effects of

Various Practice Conditions in Motor Learning. *Journal of Motor Behavior*, *36*, 212–224.

https://doi.org/10.3200/JMBR.36.2.212-224

Haith, A. M. (2025). *Policy-Gradient Reinforcement Learning as a General Theory of Practice-Based*

Motor Skill Learning (p. 2025.10.17.682587). bioRxiv.

https://doi.org/10.1101/2025.10.17.682587

Haith, A. M., & Krakauer, J. W. (2013). Model-Based and Model-Free Mechanisms of Human Motor

Learning. In M. J. Richardson, M. A. Riley, & K. Shockley (Eds.), *Progress in Motor Control*

(pp. 1–21). Springer. https://doi.org/10.1007/978-1-4614-5465-6_1

Haith, A. M., Yang, C. S., Pakpoor, J., & Kita, K. (2022). De novo motor learning of a bimanual control

task over multiple days of practice. *Journal of Neurophysiology*, *128*(4), 982–993.

https://doi.org/10.1152/jn.00474.2021

Hillman, H., McClure, T. N., & McDougle, S. D. (2025). Linking motor working memory to explicit and

implicit motor learning. *Journal of Neurophysiology*, *134*(6), 2036–2046.

https://doi.org/10.1152/jn.00105.2025

Izawa, J., & Shadmehr, R. (2011). Learning from Sensory and Reward Prediction Errors during Motor

Adaptation. *PLOS Computational Biology*, *7*(3), e1002012.

https://doi.org/10.1371/journal.pcbi.1002012

Krakauer, J., Hadjiosif, A., Xu, J., Wong, A., & Haith, A. (2019). Motor Learning. In *Comprehensive*

Physiology (Vol. 9, pp. 613–663). https://doi.org/10.1002/cphy.c170043

Krakauer, J. W., & Mazzoni, P. (2011). Human sensorimotor learning: Adaptation, skill, and beyond.

Current Opinion in Neurobiology, Sensory and Motor Systems, *21*(4), 636–644.

https://doi.org/10.1016/j.conb.2011.06.012

Lee, H., Choi, Y., Eizad, A., Song, W.-K., Kim, K.-J., & Yoon, J. (2023). A Machine Learning-Based

Initial Difficulty Level Adjustment Method for Balance Exercise on a Trunk Rehabilitation

Robot. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, *31*, 1857–1866.

IEEE Transactions on Neural Systems and Rehabilitation Engineering.

https://doi.org/10.1109/TNSRE.2023.3260815

Marraffino, M. D., Schroeder, B. L., Fraulini, N. W., Van Buskirk, W. L., & Johnson, C. I. (2021).

Adapting training in real time: An empirical test of adaptive difficulty schedules. *Military*

Psychology, *33*(3), 136–151. https://doi.org/10.1080/08995605.2021.1897451

Maxwell, J. P., Masters, R. S. W., Kerr, E., & Weedon, E. (2001). The implicit benefit of learning without

errors. *The Quarterly Journal of Experimental Psychology*, *54A*(4), 1049–1068.

https://doi.org/10.1080/713756014

Mazzoni, P., & Krakauer, J. W. (2006). An Implicit Plan Overrides an Explicit Strategy during

Visuomotor Adaptation. *The Journal of Neuroscience*, *26*(14), 3642–3645.

https://doi.org/10.1523/JNEUROSCI.5317-05.2006

McDougle, S. D., & Hillman, H. (2025). Motor working memory. *Trends in Cognitive Sciences*, S1364-

6613(25)00236-0. https://doi.org/10.1016/j.tics.2025.08.011

McDougle, S. D., Ivry, R. B., & Taylor, J. A. (2016). Taking Aim at the Cognitive Side of Learning in

Sensorimotor Adaptation Tasks. *Trends in Cognitive Sciences*, *20*(7), 535–544.

https://doi.org/10.1016/j.tics.2016.05.002

McDougle, S. D., Wilterson, S. A., Turk-Browne, N. B., & Taylor, J. A. (2022). Revisiting the Role of

the Medial Temporal Lobe in Motor Learning. *Journal of Cognitive Neuroscience*, *34*(3), 532–

549. https://doi.org/10.1162/jocn_a_01809

Metzger, J.-C., Lambercy, O., Califfi, A., Dinacci, D., Petrillo, C., Rossi, P., Conti, F. M., & Gassert, R.

(2014). Assessment-driven selection and adaptation of exercise difficulty in robot-assisted

therapy: A pilot study with a hand rehabilitation robot. *Journal of NeuroEngineering and*

Rehabilitation, *11*(1), 154. https://doi.org/10.1186/1743-0003-11-154

Nikooyan, A. A., & Ahmed, A. A. (2015). Reward feedback accelerates motor learning. *Journal of*

Neurophysiology, *113*(2), 633–646. https://doi.org/10.1152/jn.00032.2014

Ohlsson, S. (1996). Learning From Performance Errors. *Psychological Review*, *103*(2), 241–262.

Pierella, C., Casadio, M., Mussa-Ivaldi, F. A., & Solla, S. A. (2019). The dynamics of motor learning

through the formation of internal models. *PLOS Computational Biology*, *15*(12), e1007118.

https://doi.org/10.1371/journal.pcbi.1007118

Sanger, T. D. (2004). Failure of Motor Learning for Large Initial Errors. *Neural Computation*, *16*(9),

1873–1886. https://doi.org/10.1162/0899766041336431

Seidler, R. D., Kwak, Y., Fling, B. W., & Bernard, J. A. (2013). Neurocognitive Mechanisms of Error-

Based Motor Learning. In M. J. Richardson, M. A. Riley, & K. Shockley (Eds.), *Progress in*

Motor Control (pp. 39–60). Springer. https://doi.org/10.1007/978-1-4614-5465-6_3

Shmuelof, L., Krakauer, J. W., & Mazzoni, P. (2012). How is a motor skill learned? Change and

invariance at the levels of task success and trajectory control. *Journal of Neurophysiology*,

108(2), 578–594. https://doi.org/10.1152/jn.00856.2011

Sternad, D. (2018). It's not (only) the mean that matters: Variability, noise and exploration in skill

learning. *Current Opinion in Behavioral Sciences, Habits and Skills*, *20*, 183–195.

https://doi.org/10.1016/j.cobeha.2018.01.004

Swanton, D. N., & Matell, M. S. (2011). Stimulus compounding in interval timing: The modality–

duration relationship of the anchor durations results in qualitatively different response patterns to

the compound cue. *Journal of Experimental Psychology: Animal Behavior Processes*, *37*(1), 94–

107. https://doi.org/10.1037/a0020200

Taylor, J. A., & Ivry, R. B. (2011). Flexible Cognitive Strategies during Motor Learning. *PLOS

Computational Biology*, *7*(3), e1001096. https://doi.org/10.1371/journal.pcbi.1001096

Thoroughman, K. A., & Shadmehr, R. (2000). Learning of Action Through Adaptive Combination of

Motor Primitives. *Nature*, *407*(6805), 742–747. https://doi.org/10.1038/35037588

Tseng, Y., Diedrichsen, J., Krakauer, J. W., Shadmehr, R., & Bastian, A. J. (2007). Sensory Prediction

Errors Drive Cerebellum-Dependent Adaptation of Reaching. *Journal of Neurophysiology*, *98*(1),

54–62. https://doi.org/10.1152/jn.00266.2007

Wickens, C. D., Hutchins, S., Carolan, T., & Cumming, J. (2013). Effectiveness of part-task training and

increasing-difficulty training strategies: A meta-analysis approach. *Human Factors*, *55*(2), 461–

470.

Wilson, R. C., Shenhav, A., Straccia, M., & Cohen, J. D. (2019). The Eighty Five Percent Rule for

optimal learning. *Nature Communications*, *10*(1), Article 1. https://doi.org/10.1038/s41467-019-

12552-4

Wu, S.-W., Trommershäuser, J., Maloney, L. T., & Landy, M. S. (2006). Limits to human movement

planning in tasks with asymmetric gain landscapes. *Journal of Vision*, *6*(1), 5.

https://doi.org/10.1167/6.1.5

Yang, C. S., Cowan, N. J., & Haith, A. M. (2022). Control becomes habitual early on when learning a

novel motor skill. *Journal of Neurophysiology*, *128*(5), 1278–1291.

https://doi.org/10.1152/jn.00273.2022

Zahran, L., El-Beltagy, M., & Saleh, M. (2020). A Conceptual Framework for the Generation of Adaptive

Training Plans in Sports Coaching. In A. E. Hassanien, K. Shaalan, & M. F. Tolba (Eds.),

Proceedings of the International Conference on Advanced Intelligent Systems and Informatics

2019 (pp. 673–684). Springer International Publishing. https://doi.org/10.1007/978-3-030-31129-

2_62