Title. Stable, efficient, and typical dynamic functional connectivity patterns relate to higher

general intelligence

Abbreviated Title. Stable, efficient, and typical dFC increases g

Authors. Justin Ng[1,2], Ju-Chi Yu[1], Jamie D. Feusner[1,2,3,4], Colin Hawco[1,3]

[1]Campbell Family Mental Health Research Institute, Centre for Addiction and Mental Health,

Toronto, ON, Canada, M5T 1R8

[2]Institute of Medical Science, University of Toronto, Toronto, ON, Canada, M5S 1A8

[3]Department of Psychiatry, University of Toronto, Toronto, ON, Canada, M5T 1R8

[4]Department of Women's and Children's Health, Karolinska Institutet, Stockholm, Sweden

Corresponding Author. Colin Hawco, colin.hawco@camh.ca

Conflict of Interest Statement. The authors declare no competing financial interests.

Acknowledgments. This work was supported by funding from the Natural Sciences and

Engineering Research Council (NSERC).

Code Accessibility.

All relevant code for this analysis can be located at: https://github.com/14jwkn/FLEXCOG.

Abstract.

The capacity of the brain to adaptively and flexibly reconfigure into different network

connectivity patterns may underlie general cognitive ability, or g. Network reconfiguration can

be captured via assessments of dynamic connectivity (dFC), which quantifies dominant

temporally recurrent connectivity patterns, or "states", common across the population. While

standard dynamic measures focus on quantifying relative time spent within states, or the

probability transitioning between states, these metrics fail to capture variability between

individuals present in connectivity patterns across states. Here, we provide individualized

assessments of connectivity flexibility and stability over time by considering within-state pattern

stability, the difference in patterns across state transitions, and how well a given state represents

the "typical" state in a particular individual. We leveraged resting-state fMRI data from the

large-scale Human Connectome Project and data-driven multivariate Partial Least Squares

Correlation to examine emergent relationships between dynamic network properties and

cognition. We found that higher g was associated with maintaining distinct states over other

states, efficient reconfiguration (i.e., less pattern change during common small-magnitude state

transitions such as a state to itself, and greater pattern change among rare transitions between

very different states), and less reconfiguration away from population-typical patterns. These

results demonstrate that higher cognitive abilities are associated with greater state-specific

stability, greater connectivity differences when transitioning between distinct states, and

reconfiguration into more typical, potentially optimal, connectivity patterns within states. This

suggests a link between general cognition and the efficiency of reconfiguration connectivity

patterns into stable, well-defined, and typical network states.

Significance Statement.

Cognitive performance can be summarized by a general capability - "g". g has been associated

with academic and professional achievement and is critical in a world where higher-order

cognition is increasingly necessary to excel. Attempts to improve g are hampered by a lack of

mechanistic understanding. A recent theory suggests that the capacity to reconfigure brain

connectivity drives g. We investigate metrics which characterize switches in recurring dominant

connectivity patterns and propose novel metrics which investigate connectivity changes during

the switches and connectivity pattern deviation from the population. Our findings suggest that g

is associated with the maintenance of special patterns, greater pattern changes when necessary,

and having population-typical patterns. This advances our understanding of g and informs future

interventions.

1) **Introduction.**

The g-factor (g) measures general capacity across cognitive domains (Spearman, 1961).

Estimates of g can be obtained by summarizing diverse cognitive tests (Gignac and Bates, 2017).

Lower general capacity is associated with unfavorable outcomes like incarceration and poverty

(Gottfredson, 2002, 2003), whereas higher values relate to physical and mental health, academic

and professional success, and longevity (Terman, 1954; Whalley and Deary, 2001). Moreover,

genetic analyses suggest that such effects can be intergenerational (Panizzon et al., 2014). Since

g measures general capacity, it is thought to be driven by common neurobiology across cognitive

abilities (Barbey, 2018).

The Network Neuroscience Theory of Human Intelligence (Barbey, 2018) hypothesizes

that g arises from the capacity to adaptively reconfigure brain networks. Traditionally, brain

networks are examined via functional connectivity (FC), calculated by correlating fMRI signals

between brain regions across extended time. In contrast, time-varying dynamic FC (dFC)

characterizes FC evolution using FC calculated in segments of the fMRI timeseries - the dFC(t)

at each temporal segment t (Hutchison et al., 2013). dFC therefore allows us to examine

individual capacity to reconfigure brain networks and relate this capacity to cognitive ability

(Barbey, 2018; Girn et al., 2019).

dFC(t) from all t can be clustered into different "states" characterized by the recurring FC

configuration that dominates each t (Cabral et al., 2017). Dynamic switches between states

characterize network reconfiguration, and the frequency of state changes or FC variability while

maintaining a state can be used to define network flexibility. Girn et al. (2019) suggested that

this network flexibility definition might relate to g, as maintenance of states with low FC

strength with high FC variability relates to better performance in executive function domains

(Nomi et al., 2017). However, Hilger et al. (2020) found that higher general intelligence quotient

(IQ) relates to modular stability across dFC(t). Specific state changes have also been related to a

range of cognitive metrics - such as general cognitive integrity (Cabral et al., 2017), and verbal

reasoning and visuospatial ability (Xia et al., 2019).

89   During time points dominated by the same state, minor variability in connectivity

remains. Differences in FC within or between states can be evaluated via distance metrics, where

lower distance represents greater similarity across timepoints. Average distance traveled was

found to be positively correlated with visuomotor performance by Battaglia et al. (2020).

However, they also showed that the dFC(t) trajectory consists of repeated short jumps ("knots",

presumably state maintenance) and distant jumps ("leaps", presumably state changes). Recent

work has also highlighted how "typicality" or "idiosyncrasy" of brain activity (in comparison to

the general population) may relate to cognition (Hahamy et al., 2015; Hawco et al., 2020;

Gallucci et al., 2022), suggesting that group averages reflect optimal patterns evolutionarily

selected for across the population. Characteristics of dFC(t) reconfiguration during short and

distant jumps, and maintaining dFC(t) near optimal state configurations might facilitate cognitive

processing and improve g.

This study explores relationships between dynamic reconfiguration and g using a series

of standard and novel metrics, including frequency of state entrances and switching, distance

during state maintenance and transitions, and state idiosyncrasy. In addition to a univariate

approach which captures g a priori, we used more data-driven Partial Least Squares Correlation

(PLSC; Wold, 1982). PLSC is a multivariate approach which identifies latent variables (LVs)

capturing the greatest covariance between two matrices; in this case, cognitive tests and dFC

reconfiguration metrics (Wold, 1982; McIntosh et al., 1996; McIntosh and Lobaugh, 2004). By

including all cognitive tests in the PLSC, we can consider if g emerges as a property of network

configuration (i.e., we identify a latent variable with large loading on many/most cognitive tests),

as well as identify additional LVs related to specific cognitive domains such as processing speed

or working memory (Agelink van Rentergem et al., 2020). We hypothesized that associations

would exist between g and network reconfiguration metrics (i.e., state dynamics, transition

distance, and idiosyncrasy).

2) Materials and Methods.

2.1) Participants and Data

Data was obtained from the Human Connectome Project 1200 release (HCP1200) (Smith et al.,

2013). The sample consisted of 950 participants (male = 448, age = 28.7 ± 3.70) with all four 3T

resting-state fMRI (rsfMRI) scans, all 10 selected cognitive test scores, and mean relative

framewise displacement (FD) < 0.2 in each scan.

2.2) Cognitive Domain Scores

We selected 10 cognitive tests used in a factor analysis on HCP data by Dubois et al. (2018) to

derive *g*. These include Dimensional Change Card Sort (CardSort), Flanker Inhibitory Control

and Attention (Flanker), List Sorting Working Memory (ListSort), Picture Sequence Memory

(PicSeq), Picture Vocabulary (PicVoc), Pattern Comparison Processing Speed (ProcSpeed), and

Oral Reading Recognition (ReadEng) from the NIH Toolbox (http://www.nihtoolbox.org), and

Penn Progressive Matrices (PMAT24), Penn Word Memory (WordMem), and Variable Short

Penn Line Orientation (LineOrient) (Gur et al., 2010) from the Penn Computerized

Neurocognitive Battery. Given contention in factor analyses (Agelink van Rentergem et al.,

2020), we estimated g by the first principal component (PC) from Principal Component Analysis

(PCA) similar to Trampush et al. (2017).

2.3) fMRI Collection & Preprocessing

3T resting-state fMRI (rsfMRI) acquisition and preprocessing details can be found in the original

publications (Smith et al., 2013; Salimi-Khorshidi et al., 2014). In brief, rsfMRI data was

collected over two sessions (one per day) and two 15 min runs that differed in phase-encoding

direction (left-right and right-left). Participants were instructed to lie still and fixate on a central

cross. A multiband slice acquisition sequence was done using 3T MRI Siemens "Skyra" scanner

(TR = 720 ms, TE = 33 ms, flip angle = 52°, voxel size = 2 mm isotropic, 72 slices at multiband

acceleration factor = 8, 104 x 90 matrix). Selected surface-based data had undergone HCP

minimal preprocessing (including B0 distortion correction, co-registration to T1-weighted

images, and normalization to the surface template), ICA-FIX, and regression with 24 motion

regressors. Voxel timeseries was first demeaned within each voxel, then averaged for the 360

cortical regions according to the Glasser atlas (Glasser et al., 2016).

2.4.1) Leading Eigenvector Dynamics Analysis (LEiDA)

We used Leading Eigenvector Dynamic Analysis (LEiDA; Cabral et al., 2017) to generate states

while minimizing computational costs and avoiding the challenges of the traditional "sliding

window" approaches (Preti et al., 2017; Fig. 1). LEiDA analyzes phase dFC (Cabral et al., 2017),

which is a granular approach to calculate dFC(t) at each time point. The phase $\theta(k, t)$ at each time

point t in each k region's timeseries was derived by the Hilbert transform, which expresses the

regional signal $x(k, t)$ as the product of the amplitude A and the phase θ, $x(k, t) = A(k, t)*\theta(k, t)$.

The phase θ adds a third "imaginary" axis (along with the real and time axes) that converts the

rise and fall of fMRI signals into an angle (Cabral et al., 2017; Lord et al., 2019). At each t,

cosine of the phase difference between regions n and m quantifies the fMRI signal

synchronization and thus FC, namely dFC(k_{1-2}, t) = cos($\theta(k_1$, t) - $\theta(k_2$, t)); cos(0^o) = 1 indicates

perfect coherence, cos(90^o) = 0 indicates an orthogonal (i.e., uncorrelated) relationship, and

cos(180^o) = -1 indicates perfect anti-coherence. Eigendecomposition of dFC(t) at each t was done

to reduce the dimensionality of each phase connectivity matrix to its dominant pattern, as

indicated by the first eigenvector (i.e., the leading eigenvector), LE(t). The dominant pattern at

each t was reconstructed by LE(t) x LE(t)^T. The first and last time points were removed to

exclude boundary artifacts (Vohryzek et al., 2020).

Figure 1. Analysis flowchart. Here, red in the matrices indicates positive values while blue indicates negative

values. Resting-state fMRI from the Human Connectome Project (HCP1200) dataset was used. The Hilbert

transform was used to convert the fMRI timeseries into a revolution and retrieve phase angles, the phase difference

at each time point between every region was calculated for dFC(t), the eigenvector with the largest eigenvalue (i.e.

Leading Eigenvector or LE) was extracted (LE(t)) as per LEiDA (Cabral et al., 2017), and k-medians clustering with

$k = 6$ was conducted on the stacked LE(t) across subjects. Subject clustering was used to generate network

reconfiguration metrics. The relationship between cognition and network reconfiguration was assessed using

univariate correlation between g (first principal component or PC of 10 cognitive tests) and each network

reconfiguration metric and multivariate PLSC between 10 cognitive tests and all network reconfiguration metrics.

2.4.2) Identification of States

Clustering analysis was applied to LE(t) to classify time points into discrete clusters,

representing recurring states (Cabral et al., 2017). k-medians clustering with Manhattan distance

was conducted on all participants and time points for better performance in high-dimensional

data (compared to k-means clustering with Euclidean distance), with 500 repetitions to escape

local minima (Aggarwal et al., 2001; Allen et al., 2014). dFC states were visualized by the

median dFC(t) of each LE(t) cluster. Different numbers of clusters (k) produce states which can

be useful for answering specific neuroscientific questions (Figueroa et al., 2019; Lord et al.,

2019). To choose k for the main analysis, we repeated k-medians clustering for $k = 2$-12 on a

random half of the participants to reduce computational costs. Prior analyses usually choose $k =$

4-5 based on the elbow method (Allen et al., 2014; Damaraju et al., 2014; Cabral et al., 2017;

Nomi et al., 2017). In line with this, we depict similar results for the elbow method in the half-

sample. In addition, the configuration of a state consists of at least one intrinsic connectivity

network (ICN) which is anti-coherent with the rest of the brain, represented by LE loadings with

a different sign (Vohryzek et al., 2020). Given the unique relationship between general cognitive

ability and the frontoparietal network (FPN; Jung and Haier, 2007; Duncan, 2010) and to choose

a k close to the $k = 4$-5 chosen by prior analyses, we chose $k = 6$ in the main analysis to include a

state where the FPN is isolated by anti-coherence with all other networks as defined by the Cole-

Anticevic parcellation (Ji et al., 2019). To further explore how the choice of k contributes to our

results, we also repeated analyses post-hoc for k = 2-5 on the full sample. We stopped at k = 6

due to the greater computational costs associated with further k.

2.5) State FC Variability and Strength

Prior work suggests that higher g is associated with the prevalence of states with low FC strength

and corresponding high FC variability; maintaining low strength, high variability states may be

an index of reconfiguration flexibility (Nomi et al., 2017; Girn et al., 2019). We investigated,

post-hoc, the strength and variability of edges in the dFC matrices. For each state, FC variability

was obtained for each edge by the standard deviation (*SD*) of dFC(*t*) across corresponding time

points for each participant and run (Nomi et al., 2017). Group FC variability was obtained by

averaging across participants and runs. FC strength was obtained for each edge by the mean of

the absolute values of dFC(*t*) across corresponding time points for each participant and run.

Group FC strength was obtained by averaging across participants and runs.

2.6.1) State Dynamics

To investigate network reconfiguration as defined by state dynamics for each participant, we

used the state clustering to calculate 6 state occurrences - the proportion of dFC(*t*) classified to

each of the six states (*high values indicate that the participant enters that state more frequently*

on average); 6 dwell times - the mean number of dFC(*t*) classified to a given state of the six

before switching to another state (*high values indicate that the participant stays in that state*

longer on average); 1 transition number - the total number of state switches (*high values indicate*

that the participant switch between states more on average); and 6 x 6 transition probabilities -

the ratio of the count of each state switch (e.g., from State 1 to 2) to all state switches initiated

from the same starting state (e.g., all state switches from State 1 to another state) (*high values*

indicate that the participant makes that specific transition more often when starting from a given

state on average). Note that transition probability includes both the probability of staying in a

state, as well as switching between states. Each metric was averaged across all runs for each

participant.

2.6.2) State Transition Distance

6 x 6 state transition distances measure the average magnitude of connectivity difference during

a specific state-to-state switch *(larger distances indicate a more drastic change of connectivity*

during the given state switch on average). Formally, the Manhattan distance between all

sequential pairs of LE(t) in each participant's runs was calculated. Each of these LE(t) pairs was

categorized as a specific state-to-state switch. The mean Manhattan distance was computed,

across all runs for each participant, for all possible combinations of state switches (e.g., State 1 to

1, 1 to 2, etc).

2.6.3) State Idiosyncrasy

State idiosyncrasy was obtained for all 6 states by the average deviation of each participant from

the group average *(high values indicate that the participant's LE(t) are more different from the*

group average). Formally, state idiosyncrasy was obtained by finding the Manhattan distance

between each participant LE(t) and the group median of the corresponding LE state, then

averaging for each state to quantify its idiosyncrasy.

2.7) Experimental Design and Statistical Analysis

2.7.1) Univariate Analysis

To adjust for confounds, we regressed out age and sex from both brain metrics and g (Agelink

van Rentergem et al., 2020). To identify brain metrics related to g, we performed Spearman's

correlation tests for each brain metric and g, controlling for False-Discovery Rate (FDR) ($q <$

.05) across the 91 comparisons (Benjamini and Hochberg, 1995). We did this because we found

that several variables had non-normal distributions based on visual observation of quantile-

quantile (QQ) plots.

We estimated g using the first PC of 10 cognitive tests. The stability of the loadings for each

cognitive test variable was quantified using the bootstrap test (Beaton et al., 2014) with 10,000

replicates. For each loading, the bootstrap ratio (BR) was calculated as a Z-approximate that

determines whether a given loading is stably different from 0. We used a critical value of 2.5

(equals, approximately, the critical value at $\alpha = .05$ for a two-tail Z-test) to determine whether the

loading is stable.

2.7.2) Multivariate PLSC

We explored the multivariate association between the 91 network reconfiguration characteristics

(including 49 state dynamic, 36 transition distance, and 6 idiosyncrasy metrics) and the 10

variables of cognitive performance (from 10 cognitive tests) using PLSC (Krishnan et al., 2011).

Age and sex were regressed out from both sets of variables prior to analyses to control for their

effects (Agelink van Rentergem et al., 2020). To allow comparison across measures, the

variables were also standardized by computing their Z-scores.

PLSC extracts pairs of new variables, called latent variables (LVs), representing components of

maximum covariance between the two input matrices (network characteristics and cognitive

scores, respectively). Each pair of latent variables comprises a dimension, with the constraint that

dimensions are uncorrelated (i.e., the latent variable from one input matrix is uncorrelated with

the latent variable from the other input matrix of other dimensions). This is accomplished via

singular value decomposition, which also generates singular values (SVs) representing the

covariance for each dimension. Dimensions are organized according to explained covariance of

the total covariance between the two input matrices, with loadings assigned to each variable in

each matrix reflecting the contribution of the variable onto a given dimension. Importantly,

because dimensions are identified via covariance across both matrices, dimensions are driven by

the relationships across these matrices rather than just correlations within each matrix - that is,

each dimension represents a data-driven reflection of a brain-behavior relationship. Dimensions

can identify aspects of the data which are reflected in different relationships, in our case, PLSC

could identify relationships reflective of generalized cognition and/or of specific cognitive

domains that share common network characteristics. The loadings on specific variables allow

interpretation of the dimension, reflecting the cognitive and network characteristics driving each

dimension. For more details, see Krishnan et al. (2011).

2.7.2.1) Reliability of PLSC Dimensions

Non-parametric permutation tests on the singular values were used to examine if the latent

dimensions are reliable, or significant (McIntosh and Lobaugh, 2004). This procedure was

iterated 10,000 times. If $p < .05$, we considered the SV, thus the latent dimension, reliable ($\alpha =$

.05).

2.7.2.2) Stability of PLSC Loadings

To identify variables that contribute stably, we also used the bootstrap test to estimate the

stability of the cognitive and reconfiguration PLSC loadings for each dimension (McIntosh and

Lobaugh, 2004). This procedure was iterated 10,000 times to generate BRs for each loading. We

also used a critical value of 2.5 (equals, approximately, the critical value at $\alpha = .05$ for a two-tail

Z-test) to determine whether the loading is stable.

2.7.2.3) Reproducibility of PLSC Dimensions and Loadings

To quantify the reproducibility of the singular values, we performed a split-half PLSC procedure

(Churchill et al., 2013, 2016; McIntosh, 2021). In each iteration, the data was split into random

split-half samples, and singular value decomposition was conducted on both halves. To identify

the reproducibility of the dimension across split-half samples in a "train-test" approach, "test"

SVs were derived from using the latent variable pairs of the first "train" half and the correlation

matrix of the second "test" half. Higher SVs would mean higher reproducibility of the

dimension. To identify the reproducibility of loadings across split-half samples, the similarity

between the latent variables of **X** (or **Y**) the first half and the latent variables of **X** (or **Y**) the

second half were derived by the dot product of the latent variables. A higher dot product score

means greater similarity for a specific latent variable of **X** (or **Y**) between the first and second

halves. We repeated split-half resampling 10,000 times. For each dimension, the reproducibility

score was calculated by approximating a Z-score - the mean of the "test" SVs divided by the

standard deviation. For each latent variable of $\mathbf{X}$ (or $\mathbf{Y}$), the reproducibility score was also

calculated by approximating a Z-score - the mean of the dot product for the latent variables of $\mathbf{X}$

(or $\mathbf{Y}$) across the two halves divided by the standard deviation. Values greater than 1.95 were

used to determine reproducibility (approximately 95% confidence interval).

3) Results.

3.1) State characteristics

We investigated k-medians clustering for $k = 2\text{-}12$ on a random half of the participants to choose

k while minimizing computational costs (Extended Data Fig. 2-1). Phase-difference dFC

corresponded well with established ICNs - specifically, regions of each ICN tended to have

similar phase differences with other regions within a given state. Each state generally had at least

one intrinsic connectivity network (ICN) which is anti-coherent with the rest of the brain,

represented by LE loadings with a positive sign (Vohryzek et al., 2020). For each state, we

plotted LE x LE^{T} matrices and all positive LE values on the brain. In the main analysis for $k = 6$,

State 1 had a uniform phase direction, but other states were characterized by at least one ICN

with anticoherence with other ICNs (Fig. 2). State 2 was characterized by the coherence of

attention and sensorimotor ICNs and the posterior multimodal network (PMM); the weak

coherence of default mode network (DMN) and FPN; and the anticoherence of DMN and FPN

with most ICNs. State 3 was characterized by the weak coherence of visual and language ICNs,

FPN, and DMN; the weak coherence of the cingulo-opercular network (CON) and dorsal

attention network (DAN); and the anticoherence of the CON and DAN with most ICNs (with

strong anticoherence between CON and DMN). State 4 was characterized by the weak coherence

of the FPN and DMN and the weak anti-coherence of the secondary visual network (VIS2) with

most ICNs. State 5 was characterized by the coherence of attention and visual ICNs, FPN, and

PMM; and anticoherence of the DMN and the language network (LAN) with most ICNs. State 6

was characterized by the coherence of sensorimotor ICNs, LAN, and PMM; and anticoherence

of the FPN with most ICNs.

It has been hypothesized that greater prevalence of states with low FC strength and

corresponding high FC variability would relate to g (Nomi et al., 2017; Girn et al., 2019). Thus,

we also investigated, post-hoc, the strength and variability of edges in the dFC matrices

(Extended Data Fig. 2-2). As expected, states with lowest FC strength across edges tended to

have the highest FC variability. Notably, States 3 and 4 had the lowest FC strength and highest

FC variability across edges.

Figure 2. dFC states. Coherence is red and anti-coherence is blue in coherence matrices. In the first row, group dFC

states are shown - these are derived from finding the median of phase dFC(*t*) across time and participants according

to the group k-medians clustering of LE(*t*). In the second row, group LE states are shown - these are derived from

multiplying the LE medians from the group k-medians clustering of LE(*t*) by its transpose, LE x LE^T. In the third

row, radar plots characterize intrinsic connectivity networks (ICNs) with phases which follow the main orientation

347 (coherent with most ICNs) and ICNs with phases with opposite direction (anticoherent with most ICNs). Majority

348 coherence was characterized by averaging the negative region elements in the LE for each ICN (LE -, red) and

349 majority anticoherence was characterized by averaging the positive region elements in the LE (LE +, blue)

350 (Vohryzek et al., 2020). In the fourth row, we plotted the positive values of LE in each region to delineate the ICNs

351 with anticoherence with most other ICNs. States other than State 1 tended to exhibit several ICNs with

352 anticoherence with most other ICNs. This is partly why State 1 has been previously interpreted as a "meta-stable"

353 state (Cabral et al., 2017; Vohryzek et al., 2020).

355 **3.2) Network reconfiguration characteristics**

356 Across states, salient patterns emerge when examining state dynamics and transition distance

357 (Extended Data Fig. 3-1; also see Fig. 4 below). Within-state transition probability (probability

358 of remaining in the same state) was the highest and within-state transition distance (average

359 transition distance to itself) was the lowest among all types of state transitions. The distributions

360 of transition distances seemed to be similar for the same pair of states (e.g., comparing transition

361 from 1-2 or from 2-1). We found State 1 to be special. State 1 had the highest and most variable

362 values for occurrence, dwell time, and within-state transition probability. State 1 also had slightly

363 higher mean and variance in target transition probability (transition probability towards that

364 state). Furthermore, State 1 had the lowest within-state transition distance, lower participating

365 transition distances, and the lowest and most variable idiosyncrasy.

367 **3.3) Univariate and PLSC results were similar for the first PLSC latent dimension**

368 The first PC of the cognitive tests explained 32% of the variance and captured the commonality

369 across all tests as indicated by the unidirectional pattern of stable (BR > 2.5) loadings (PMAT24,

370 PicVoc, ProcSpeed, CardSort, Flanker, ListSort, PicSeq, ReadVoc, WordMem, LineOrient;

371 Loading = 20, 22, 14, 16, 14, 18, 14, 23, 12, 19; BR = 17.87, 16.48, 13.20, 14.83, 13.40, 16.72,

13.27, 17.51, 9.80, 15.28); the PC scores were used to quantify g for the participants (Extended

Data Fig. 3-2). Such a unidirectional pattern was also found in the loadings of the first dimension

of PLSC (Fig. 3). The network reconfiguration measures that significantly correlated with g ($p <$

.05 with FDR correction) (Extended Data Fig. 3-2) were similar to the measures which

contributed reliably to the first dimension of PLSC (BR > 2.5) (Fig. 3). All univariate

correlations, *p*-values, and FDR-adjusted *p*-values are noted in Extended Data Figure 3-3. As the

univariate results approximated the more data-driven PLSC results for Dimension 1, we focus on

PLSC results for brevity.

3.4) PLSC indicated two significant and reproducible latent dimensions

The permutation test indicated that the first three latent dimensions each explained a reliable ($p <$

.05) proportion of covariance, as measured by the SV (singular values) (Extended Data Fig. 3-4).

The first dimension accounted for 58.83% (SV $= 1187$, $p = .0001$) of the total covariance

between the cognitive space and the network reconfiguration space. Dimensions 2 and 3

accounted for 24.24% (SV $= 762$, $p < .0001$) and 6.57% (SV $= 397$, $p < .0001$) respectively. The

reproducibility analysis indicated that the **Y** cognitive loadings (Dimensions 1-3; Z $= 4.83, 2.35,$

2.48) and **X** network reconfiguration loadings (Dimensions 1-3; Z $= 2.65, 2.75, 2.074$) of all

three dimensions were reproducible ($Z > 1.95$), but only the SV in Dimensions 1 and 2 were

reproducible (Dimensions 1-2; Z $= 3.77, 3.00$). Thus, we will focus our main analysis on the first

two dimensions.

3.5) The first PLSC latent variable reflects relationships between g and network

reconfiguration

On the first dimension of PLSC, only a selected set of cognitive test loadings stably (BR > 2.5)

contributed (PMAT24, ListSort, PicSeq, ReadVoc, WordMem, LineOrient; Loading = 555.16,

508.13, 405.00, 400.24, 303.05, 466.53; BR = 4.31, 4.31, 3.52, 3.56, 2.54, 3.89), delineating the

cognitive tests that drove the cognitive-network association captured by the first dimension (Fig.

3). Besides Picture Vocabulary, the loadings where we failed to find stability were notably

among cognitive tests which account for reaction speed. Loadings and bootstrap ratios for

cognitive measures are shown in Extended Data Figure 3-5, and for network reconfiguration

measures in Extended Data Figure 3-6.

Figure 3. Relationship between network reconfiguration metrics and cognition. To characterize the relationship

between network reconfiguration and g, we used both univariate and multivariate analysis. Here, we show results for

the multivariate PLSC. All 10 cognitive tests were set as **Y** and all network reconfiguration metrics were set as **X**.

Red refers to stable positive bootstrap ratios (BR > 2.5), blue refers to stable negative bootstrap ratios. Arrows are

transition probabilities for dynamics and transition distances for transition distance; circular arrows represent within-

state transitions or distances. Dim. refers to the dimension. For the Dimension 1 **Y** cognitive test loadings, most

loadings were positive - this suggests that it represents g. For the Dimension 2 **Y** cognitive test loadings, only

processing speed was stable. PLSC loading values and bootstrap ratios are located in Extended Data Figures 3-5 and

3-6.

3.5.1) State dynamics and cognition in Dimension 1

As indicated in Fig. 3, the first dimension of the PLSC revealed stable (BR > 2.5) positive

loadings for the dwell time of States 2 (Loading = 176, BR = 3.21) and 3 (Loading = 146, BR =

2.69), within-state transition probability of States 2 (Loading = 190, BR = 3.48) and 3 (Loading

= 151, BR = 2.72), and target transition probability (transition probability towards the state) for

State 2 (Loading = 145, BR = 2.76). Notably, these states were not both States 3 and 4, which

had the lowest FC strength and highest FC variability (Extended Data Fig. 2-2). The first

dimension also revealed stable (BR < -2.5) negative loadings for the target transition probability

of State 6 (1-6, 3-6; Loading = -184, -132; BR = -3.46, -2.58).

3.5.2) State transition distance and cognition in Dimension 1

As transition distances were usually mirrored for a specific transition (e.g., comparing transition

1-2 to 2-1) (Extended Data Fig. 3-1), relationships between transition distance and cognition for

a specific pair of states were also commonly mirrored (Fig. 3). The first dimension of the PLSC

revealed stable (BR > 2.5) positive loadings for the transition distances between States 2 and 3

(2-3, Loading = 153, BR = 2.64), States 2 and 4 (2-4, 4-2; Loading = 264, 238; BR = 4.49, 3.97),

States 3 and 5 (3-5, 5-3; Loading = 171, 145; BR = 3.11, 2.53), and States 4 and 6 (4-6, 6-4;

Loading = 235, 200; BR = 4.25, 3.61). Notably, these transitions were among the highest

transition distances across subjects (Fig. 4), indicating that g was related to a larger transition

distance when moving to states which are dissimilar. The first dimension also revealed stable

negative loadings (BR < -2.5) for within-state transition distances (2-2, 3-3, 4-4, 5-5; Loading = -

199, -228, -153, -169; BR = -3.56, -4.16, -2.63, -2.99), between State 1 and other states (1-3, 3-1,

1-4, 1-5, 5-1; Loading = -256, -184, -176, -195, -211; BR = -4.88, -3.53, -3.40, -3.38, -3.87), and

between States 2 and 5 (2-5, 5-2; Loading = -227, -140; BR = -4.093, -2.67). These transitions

were among the lowest transition distances across subjects, indicating that a lower transition

distance when moving between similar states was associated with higher g.

Figure 4. Divergence between distant and proximal transitions. Boxes represent the transition distances within

and between states, colored by loadings that have stable bootstrap ratios (BR > 2.5; black indicates that the bootstrap

ratio was unstable). Dim. refers to PLSC dimensions. Dimension 1 X loadings indicate that lower transition distance

among transition distances with lower values compared to other transition distances, and higher transition distance

among transition distances with higher values, relates to higher scores for g. In contrast, Dimension 2 X loadings

indicate that higher transition distance among transition distances with lower values compared to other transition

distances relates to higher scores in processing speed.

3.5.2.1) Visualizing state-space to contextualize state transition distance in Dimension 1

To aid interpretation of transition distances between states, we used PCA to reduce the LE(t) of

all time points of all participants to visualize the points in 3D "state-space". We took the first

three PCs of the LE(t) of each time point of each participant (Fig. 5). In Fig. 5A, the 25%, 50%,

and 75% quartiles along the PCs were plotted as error bars. Note that these three PCs only

accounted for 7.89%, 6.69%, and 4.70% of the variance respectively, leaving significant variance

unexplained, but this visualization allows some understanding of the relative distance across

states. PC1-PC2 exhibited the proximity of States 2 and 5, States 3 and 4, and States 1 and 6. The

PC3-PC2 and PC3-PC1 maps indicate that State 1 lies at the bottom of a "funnel" in the state-

space. These patterns are also demonstrated in the LE(t) points in three exemplar participants

shown in Fig. 5B (where LE(t) are colored according to state assignment).

Figure 5. State-space. (A) To aid interpretation of transition distances via visualization, we used PCA to reduce the LE(t) dimensions from 360 to 3. The median (50% quartile) of each state across all participants are shown with an interval representing the 25% and 75% quartiles along two PC dimensions. PC1-PC2 describes the proximity of States 2 and 5, States 3 and 4, and States 1 and 6. PC2-PC3 and PC1-PC3 indicate that State 1 lies at the bottom of a "funnel" in state-space. (B) Three random exemplar participant LE plots display the LE(t) along all three PC dimensions. The example participant LE views exemplify the distribution of LE(t) and its intersubject variability.

3.5.3) State idiosyncrasy and cognition in Dimension 1

Dimension 1 of the PLSC had stable (BR < -2.5) negative idiosyncrasy loadings for States 2 through 5 (idiosyncrasy 2, 3, 4, 5; Loading = -183, -215, -194, -182; BR = -3.30, -4.0032, -3.59, -3.42) (Fig. 3), indicating that having a more typical pattern for each state was associated with g.

473   3.6) Dimension 2 reflects relationships between processing speed and network

474   reconfiguration

Dimension 2 of PLSC indicated that only the processing speed test loading was stable (BR > 2.5)

(ProcSpeed; Loading = 452; BR = 3.11) (Fig. 3). The other loadings seemed to reflect the

contrast between variables related to reaction speed and those that do not - besides vocabulary

tests (Picture Vocabulary and Reading), the processing speed test loaded in the same direction

with other tasks which account for reaction speed. Thus, Dimension 2 might generally

characterize speed of processing.

482   3.6.1) State dynamics and cognition for Dimension 2

For PLSC Dimension 2, the stable (BR > 2.5) dynamics loadings implicated a higher transition

number (Loading = 121, BR = 3.50), higher occurrence of all states other than State 1

(occurrence 2, 3, 4, 5; Loading = 111, 118, 106, 129; BR = 3.28, 3.59, 2.97, 3.78), higher dwell

time in States 3 and 5 (dwell 3, 5; Loading = 112, 85; BR = 3.39, 2.52), higher within-state

transition probability in States 3 and 5 (3-3, 5-5; Loading = 116, 94; BR = 3.45, 2.78), higher

transition probability away (exit transition probability) from States 1 and 6 (especially to 3, 4,

and 5) (1-3, 1-4, 1-5, 6-3, 6-5; Loading = 121, 111, 132, 83, 99; BR = 3.67, 3.13, 3.96, 2.60,

2.97), and higher transition probability from State 4 to 5 (Loading = 88, BR = 2.64). It also

implicated lower occurrence (Loading = -149, BR = -4.47), dwell time (Loading = -149, BR = -

4.38), within-state transition probability (Loading = -126, BR = -3.74), and target transition

probability of all states for State 1 (2-1, 3-1, 4-1, 5-1, 6-1; Loading = -155, -118, -127, -121, -

136; BR = -4.70, -3.69, - 3.87, -3.44, -4.14).

3.6.2) State transition distance and cognition for Dimension 2

For PLSC Dimension 2, the stable (BR > 2.5) transition distance loadings implicated a higher

within-state transition distance of all states except State 3 (1-1, 2-2, 4-4, 5-5, 6-6; Loading = 159,

92, 98, 85, 107; BR = 4.52, 2.60, 2.77, 2.51, 3.094), and the transition distance between State 6

and States 1 and 2 (1-6, 6-2; Loading = 95, 99; BR = 2.76, 2.77). Notably, these transitions were

among the lowest transition distances across subjects (Fig. 4).

3.6.3) State idiosyncrasy and cognition for Dimension 2

For PLSC Dimension 2, the stable (BR > 2.5) idiosyncrasy loadings implicated higher individual

idiosyncrasy from the group of States 1 and 6 (idiosyncrasy 1, 6; Loading = 165, 117; BR = 4.98,

3.53) (Fig. 3).

3.7) Post-hoc investigation of state FC strength and FC variability suggests that g is (and

processing speed is inversely) associated with strong, stable, and typical states

Higher transition distance among the most distant transitions was associated with better general

cognitive ability (Fig. 3), so we surmised that one contributing factor might be that individuals

with high transition distances in those transitions had more defined states (i.e., higher FC

strength; Fig. 7). To investigate this, we calculated the absolute FC strength for each edge in

each dFC(t) classified to the state and averaged across both time points and edges for all six

states. To create a single "between-distance" score for each participant, we averaged the

participant scores for all transition distances where higher transition distance was associated with

better cognitive performance in the PLSC Dimension 1(those with positive loadings on Fig. 4; 2-

3, 2-4, 3-5, 4-2, 4-6, 5-3, 6-4). After regressing out age and sex from both scores (Agelink van

Rentergem et al., 2020), Spearman's correlation tests were conducted for all states (data was not

all normally distributed). FDR-correction was done across all 48 tests further outlined in this

section. All correlations between FC strength and between-distance were significant (FDR-

corrected $p < 1*10^{-13}$) and positive (rho ranging from 0.24 to 0.57) (Table 1). That is, participants

displaying greater transition distances between specific states with higher transition distance also

displayed a stronger connectivity profile. This suggests more defined network states and greater

segregation between distant states are both associated with higher g.

dFC Strength

Figure 6. FC strength visualized. To visualize states in participants with high or low FC strength in each dFC state,

we ranked participants according to the participant FC strength (absolute FC averaged across edges) for each state,

extracted the states of the top and bottom 10% scorers, and averaged them across participants. Greater FC strength

was characterized by both higher coherence and anticoherence.

Table 1. Correlations between FC strength (STR) and variability (VAR) and summary transition distance

and idiosyncrasy metrics. Higher (+) or lower (+) values correspond to higher cognitive performance. All FDR-

corrected $p < 1*10^{-13}$.

g	State 1	State 2	State 3	State 4	State 5	State 6
Between-Distance (+)	STR = 0.24	STR = 0.53	STR = 0.57	STR = 0.57	STR = 0.54	STR = 0.38
Within-Distance (-)	VAR = 0.60	VAR = 0.78	VAR = 0.77	VAR = 0.78	VAR = 0.81	VAR = 0.70
Idiosyncrasy (-)	STR = -0.49	STR = -0.79	STR = -0.74	STR = -0.76	STR = -0.72	STR = -0.51
	VAR = 0.58	VAR = 0.77	VAR = 0.73	VAR = 0.73	VAR = 0.79	VAR = 0.68
Processing Speed	State 1	State 2	State 3	State 4	State 5	State 6
Between-Distance (+)	STR = -0.50	STR = -0.66	STR = -0.52	STR = -0.56	STR = -0.47	STR = -0.77
Within-Distance (+)	VAR = 0.73	VAR = 0.84	VAR = 0.84	VAR = 0.85	VAR = 0.86	VAR = 0.80
Idiosyncrasy (+)	STR = -0.88	STR = -0.65	STR = -0.42	STR = -0.49	STR = -0.36	STR = -0.86
	VAR = 0.94	VAR = 0.83	VAR = 0.85	VAR = 0.85	VAR = 0.79	VAR = 0.93

Lower transition distance among same-state transitions was also associated with better general

cognitive ability (Fig. 3). This can also be interpreted as an index of having more stable states, in

other words, lower FC variability. To test this, we calculated the FC strength for each edge in

each dFC(t) classified to the state, found the SD for each edge across time points, and averaged

across edges (creating a measure of variability within states) for all six states. To create a single

"within-distance" score, we averaged participant scores for same-state transition distances where

lower transition distance was associated with better cognitive performance in the first PLSC

dimension (2-2, 3-3, 4-4, 5-5). All correlations were significant (FDR-corrected $p < 1*10^{-13}$) and

positive (rho ranging from 0.60 to 0.81) for all states (Table 1). In other words, participants

displaying lower transition distances when maintaining the same state also displayed lower

connectivity variability. It should also be noted that same-state transitions are most frequent

(Extended Data Fig. 3-1), indicating that transition distance among same-state transitions is a

measure of stability for the majority of time points. This suggests that individuals with higher g

display both stronger and more stable connectivity, potentially more "deeply-entering" a given

state.

Lower idiosyncrasy was also associated with higher general cognitive ability (Fig. 3). We

hypothesized that the "defined" strong state patterns that individuals with higher g stably

reconfigured near were also population-typical state patterns. To investigate this, we used a

single average idiosyncrasy score for each participant by averaging participant idiosyncrasy

scores for states where lower idiosyncrasy was associated with higher g (2, 3, 4, 5). As expected,

all Spearman's correlations between idiosyncrasy and FC strength for all six states were

significant (FDR-corrected $p < 1*10^{-13}$) and negative (rho ranging from -0.49 to -0.79), and all

correlations between idiosyncrasy and FC variability were significant (FDR-corrected $p < 1*10^{-13}$

^{13}) and positive (rho ranging from 0.58 to 0.79) (Table 1). That is, participants displaying lower

idiosyncrasy for states where lower idiosyncrasy was associated with higher g, or more

typicality, also displayed stronger and more stable connectivity.

Interestingly, when these analyses were repeated for processing speed, the opposite was found -

higher between-distance (higher distance was associated with higher processing speed; 1-6, 6-2)

related to lower FC strength, higher within-distance (higher distance was associated with higher

processing speed; 1-1, 2-2, 4-4, 5-5, 6-6) related to higher FC variability, and higher

idiosyncrasy (higher idiosyncrasy was associated with higher processing speed; 1, 6) related to

lower FC strength and higher FC variability (Table 1) - weak, variable, atypical states. Notably,

higher transition distance among the most frequent same-state transitions (Extended Data Fig. 3-

1) was associated with processing speed, further suggesting that greater variability on average is

associated with processing speed. In brief, higher scores for processing speed might be

associated with higher variability (which accompanies weaker strength), which might also be

reflected in higher variation away from group states.

3.8) Post-hoc investigation of other k

We also explored $k = 2$-5 post-hoc. PLSC for $k = 2$, 3, or 4 were not found to be reproducible for

all dimensions and latent variables ($Z \leq 1.95$), so we show $k = 5$ as an example (Extended Data

Fig. 3-7). $k = 5$ produced the same pattern of PLSC reproducibility results as $k = 6$, where all

metrics were reproducible ($Z > 1.95$) except for the singular value for the third dimension.

Across k, main findings replicated with minor discrepancies, suggesting that our findings

generalize across choice of k.

<u>4) Discussion.</u>

586   Our results suggest that higher g is related to the capacity to reconfigure into stable,

defined, and typical states. Consistent with studies suggesting that g might relate to established

state dynamics such as dwell time, occupancy, transition number, and state transition probability

(Nomi et al., 2017; Girn et al., 2019), we find that g related to dynamics characterizing stability

(i.e., maintenance of states, such as dwell time). Frequency-based metrics might not fully capture

the rich information embedded in individuals' patterns and their changes. Moving beyond prior

studies, we consider transition distance as a measure of reconfiguration magnitude during

transitions between states (Shine et al., 2019; Battaglia et al., 2020). From this, g related to both

state stability (lower transition distances for frequent within-state transitions) and definition

(higher transition distances for distant transitions). We also integrate novel research on brain

typicality (Hawco et al., 2020; Gallucci et al., 2022) by investigating idiosyncrasy of states

across participants. We find that g related to typicality (lower idiosyncrasy). Critically, PLSC

replicated univariate analyses, demonstrating that these associations emerge in a data-driven way

and represent the strongest relationships between cognition and dynamic network features. A

PLSC dimension related processing speed to dynamic metrics reflecting frequent state change,

higher transition distance among frequent transitions, and greater variability around group-

average states. While g related to state stability, processing speed reflected the capacity to

flexibly transition. This study advances understanding of efficient brain organization, clarifying

nuanced relationships between network reconfiguration and general cognitive performance.

Higher g was associated with stability in States 2 through 5, particularly in States 2 and 3.

Specifically, g was associated with lower within-state transition distance in States 2 through 5

and greater dwell time in States 2 and 3. States 2 and 5 have similar patterns, which might also

make the g and State 2-5 transition relationship another form of the relationship between g and

within-state transitions. Given that within-state transitions were most frequent, this can explain

why less overall network reconfiguration has been found to be associated with better

performance - stable modular brain organization has been related to IQ (Hilger et al., 2020),

while average dFC(t) similarity has been related to general cognitive integrity (Cabral et al.,

2017). Notably, dynamics did not implicate both States 3 and 4, which have the lowest FC

strength and highest FC variability, detracting from the hypothesis that greater prevalence of

such states best relates to g (Nomi et al., 2017; Girn et al., 2019). Instead, we offer alternative

explanations for why States 2 and 3 were implicated. Common network patterns in States 2 and 3

included CON-DAN coherence, CON and DAN anti-coherence with DMN, and FPN-DMN

coherence. CON and DAN are task-positive attentional ICNs that are anticorrelated with task-

negative internally-oriented DMN (Zhou et al., 2018). As intelligence is linked to CON-DAN

correlation and DAN-DMN anticorrelation (Hearne et al., 2016), the segregation between these

networks might be beneficial. FPN is also task-positive, but FPN-DMN correlation increases

with both higher intelligence and task complexity (Hearne et al., 2015, 2016). This association

might relate to FPN's task-general control and DMN's global information integration

(Vatansever et al., 2015), where DMN contributes to internal idea generation, and FPN controls

DMN activity towards external goals (Beaty et al., 2018). Increased prevalence of States 2 and 3

might amplify such ICN communication patterns (i.e., static FC is a proportion-weighted sum of

dFC(t); Cabral et al., 2017) and thus enhance g. Our study contributes to the literature indicating

that higher g is related to maintaining network patterns, and adds to it by considering the specific

patterns.

There was evidence that stronger FC is associated with higher g. Higher transition

distance in rare distant transitions was associated with higher g, and higher distance among these

transitions was associated with higher FC strength. This is consistent with a study suggesting that

general cognition and IQ is associated with higher average "leap size" (i.e., a distance measure)

during state transitions (Ramirez-Mahaluf et al., 2020). Here, we integrate findings on stability

with studies which suggest that greater reconfiguration is also cognitively favorable, suggesting

that higher g relates to both maintenance of states and greater reconfiguration during rare

transitions to fit distant states. In other words, stably entering defined states, or the capacity to

"deeply-enter" states.

We found that g was associated with lower idiosyncrasy of States 2-5. Participants with

lower idiosyncrasy for states implicated for g also tended to have lower FC variability and higher

FC strength. This suggests a closer average fit with prototypical population patterns. Recent

studies have shown that typicality in fMRI task signals and static FC relates to better cognitive

performance (Hawco et al., 2020; Corriveau et al., 2022; Gallucci et al., 2022). Our study adds to

this by suggesting that "deeply-entered" state patterns associated with higher g are also optimal

patterns captured in population averages.

The favorability of attaining and maintaining states can be explained by interpreting the

resting-state as an exploration of "attractor" states in state-space, where task demands constrain

the potential repertoire (Deco and Jirsa, 2012). Assuming that participants reconfigure the

network for processing in the current cognitive context, being able to attain and maintain the

ideal state might be beneficial for general cognitive ability. We speculate that these participants

had stronger and more defined attractors that forced $dFC(t)$ to travel large distances when

participants transitioned between states; thus, these attractors kept $dFC(t)$ within more

circumscribed areas of state-space and facilitated state maintenance. Supporting our

interpretation of the relationship between rest and task, FC stability during task-state has also

been observed and related to increased accuracy and decreased reaction time during cognitive

performance (Elton and Gao, 2015; Hutchison and Morton, 2015). While suggestive, future

studies could replicate these analyses to confirm whether indices of attaining and maintaining

states remain predictors of g in tasks.

Similar to prior work, transitions back to State 1 were more probable than to other states.

State 1 also had uniform phase direction, was most prevalent, and was located at the bottom of

the state-space "funnel" after dimensionality reduction. As a result, State 1 has been interpreted

as a meta-stable state which is returned to after entering "cognitive-processing" states (Cabral et

al., 2017; Vohryzek et al., 2020). Lower transition distance from State 1, suggesting a better

capacity to leave State 1 for cognitive-processing states, was associated with higher g. Prior work

finds that "update efficiency" - greater similarity between resting-state and task-states - is related

to higher general cognitive performance (Schultz and Cole, 2016; Xiang et al., 2022). Lower

necessary goal-directed reconfiguration might conceptually relate to efficient transition from

State 1 to other cognitive-processing states. Transition probability into State 6 was associated

with lower g, where State 6 is characterized by the global anticoherence of FPN. FPN might alter

its FC with other ICNs to act as a substrate for cognitive control (Cole et al., 2013). The

anticoherence of the FPN from other ICNs implies isolation, so prevalence of State 6 might

indicate a predisposition to enter a state where FPN does not accomplish this task-general

cognitive control function - lowering g.

Dimension 2 of PLSC described a relationship between network reconfiguration and

processing speed. Interestingly, less entry and more exits for State 1 was associated with higher

processing speed - better capacity to leave the meta-state for cognitive-processing states might be

beneficial for processing speed. Processing speed was also associated with the capacity to

"weakly-enter" states - to have more flexible reconfiguration, which accompanies weak

connectivity. Prior work has also related processing speed to state switching (de Lacy et al.,

2019), greater average distance between successive dFC(t) (Lombardo et al., 2020), total

distance traveled, and maximum between-state distance (de Lacy et al., 2019). In addition,

having connectivity which varies further from prototypical group connectivity for States 1 and 6

was favorable for processing speed. One interpretation might be that the variation from group

connectivity is a side-effect of greater general connectivity variability, but another interesting

interpretation is that idiosyncratic divergence in a specific situation (i.e., during States 1 and 6,

for processing speed) might benefit cognitive performance.

Current approaches to cognitive enhancement target specific cognitive domains at the

expense of deleterious effects and can be short-lived (Schifano et al., 2022). Properly optimized

enhancement of g requires thorough understanding of brain system interplay. This understanding

might also lend itself to another application - brain-inspired artificial intelligence. Adaptively

changing underlying network weights to control transitions between network configurations

could potentially be used to instantiate general intelligence. Our study progresses this

understanding of cognition by investigating the theory that network reconfiguration underlies

intelligence. Future steps might include exploration of further indices, such as regional levels or

state-free metrics (Barbey 2018; Girn et al. 2019), until an evidence-based model can be

generated.

In summary, our framework finds that entering stable, defined, and typical network states

is associated with better overall cognitive ability, suggests a shift beyond studies focusing on

state frequency, and emphasizes the importance of examining connectivity observed across states

in more individualized ways.

5) References.

Agelink van Rentergem JA, de Vent NR, Schmand BA, Murre JMJ, Staaks JPC, ANDI

Consortium, Huizenga HM (2020) The Factor Structure of Cognitive Functioning in

Cognitively Healthy Participants: a Meta-Analysis and Meta-Analysis of Individual

Participant Data. Neuropsychol Rev 30:51–96.

Aggarwal CC, Hinneburg A, Keim DA (2001) On the Surprising Behavior of Distance Metrics

in High Dimensional Space. In: Database Theory — ICDT 2001, pp 420–434. Springer

Berlin Heidelberg.

Allen EA, Damaraju E, Plis SM, Erhardt EB, Eichele T, Calhoun VD (2014) Tracking whole-

brain connectivity dynamics in the resting state. Cereb Cortex 24:663–676.

Barbey AK (2018) Network Neuroscience Theory of Human Intelligence. Trends Cogn Sci

22:8–20.

Battaglia D, Boudou T, Hansen ECA, Lombardo D, Chettouf S, Daffertshofer A, McIntosh AR,

Zimmermann J, Ritter P, Jirsa V (2020) Dynamic Functional Connectivity between order

and randomness and its evolution across the human adult lifespan. Neuroimage 222:117156.

Beaton D, Chin Fatt CR, Abdi H (2014) An ExPosition of multivariate analysis with the singular

value decomposition in R. Comput Stat Data Anal 72:176–189.

Beaty RE, Chen Q, Christensen AP, Qiu J, Silvia PJ, Schacter DL (2018) Brain networks of the

imaginative mind: Dynamic functional connectivity of default and cognitive control

networks relates to openness to experience. Hum Brain Mapp 39:811–821.

Benjamini Y, Hochberg Y (1995) Controlling the false discovery rate: A practical and powerful

approach to multiple testing. J R Stat Soc 57:289–300.

Cabral J, Vidaurre D, Marques P, Magalhães R, Silva Moreira P, Miguel Soares J, Deco G,

Sousa N, Kringelbach ML (2017) Cognitive performance in healthy older adults relates to

spontaneous switching between states of functional connectivity during rest. Sci Rep

7:5135.

Churchill N, Afshin-Pour B, Strother S (2016) PLS and Functional Neuroimaging: Bias and

Detection Power Across Different Resampling Schemes. In: The Multiple Facets of Partial

Least Squares and Related Methods, pp 93–102. Springer International Publishing.

Churchill N, Spring R, Abdi H, Kovacevic N, McIntosh AR, Strother S (2013) The Stability of

Behavioral PLS Results in Ill-Posed Neuroimaging Problems. In: New Perspectives in

Partial Least Squares and Related Methods, pp 171–183. Springer New York.

Cole MW, Reynolds JR, Power JD, Repovs G, Anticevic A, Braver TS (2013) Multi-task

connectivity reveals flexible hubs for adaptive task control. Nat Neurosci 16:1348–1355.

Corriveau A, Yoo K, Kwon YH, Chun MM, Rosenberg MD (2022) Functional connectome

stability and optimality are markers of cognitive performance. Cereb Cortex Available at:

http://dx.doi.org/10.1093/cercor/bhac396.

Damaraju E, Allen EA, Belger A, Ford JM, McEwen S, Mathalon DH, Mueller BA, Pearlson

GD, Potkin SG, Preda A, Turner JA, Vaidya JG, van Erp TG, Calhoun VD (2014) Dynamic

functional connectivity analysis reveals transient states of dysconnectivity in schizophrenia.

NeuroImage: Clinical 5:298–308 Available at: http://dx.doi.org/10.1016/j.nicl.2014.07.003.

Deco G, Jirsa VK (2012) Ongoing Cortical Activity at Rest: Criticality, Multistability, and Ghost

Attractors. Journal of Neuroscience 32:3366–3375 Available at:

http://dx.doi.org/10.1523/jneurosci.2523-11.2012.

de Lacy N, McCauley E, Kutz JN, Calhoun VD (2019) Sex-related differences in intrinsic brain

dynamism and their neurocognitive correlates. Neuroimage 202:116116.

Dubois J, Galdi P, Paul LK, Adolphs R (2018) A distributed brain network predicts general

intelligence from resting-state human neuroimaging data. Philos Trans R Soc Lond B Biol

Sci 373 Available at: http://dx.doi.org/10.1098/rstb.2017.0284.

Duncan J (2010) The multiple-demand (MD) system of the primate brain: mental programs for

intelligent behaviour. Trends Cogn Sci 14:172–179.

Elton A, Gao W (2015) Task-related modulation of functional connectivity variability and its

behavioral correlations. Hum Brain Mapp 36:3260–3272.

Figueroa CA, Cabral J, Mocking RJT, Rapuano KM, van Hartevelt TJ, Deco G, Expert P,

Schene AH, Kringelbach ML, Ruhé HG (2019) Altered ability to access a clinically relevant

control network in patients remitted from major depressive disorder. Hum Brain Mapp

40:2771–2786.

Gallucci J, Tan T, Schifani C, Dickie EW, Voineskos AN, Hawco C (2022) Greater individual

variability in functional brain activity during working memory performance in

Schizophrenia Spectrum Disorders (SSD). Schizophr Res 248:21–31.

Gignac GE, Bates TC (2017) Brain volume and intelligence: The moderating role of intelligence

measurement quality. Intelligence 64:18–29.

Girn M, Mills C, Christoff K (2019) Linking brain network reconfiguration and intelligence: Are

we there yet? Trends Neurosci Educ 15:62–70.

Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson

J, Beckmann CF, Jenkinson M, Smith SM, Van Essen DC (2016) A multi-modal

parcellation of human cerebral cortex. Nature 536:171–178.

Gottfredson LS (2002) Where and Why g Matters:Not a Mystery. Hum Perform 15:25–46.

Gottfredson LS (2003) g, Jobs and Life. The Scientific Study of General Intelligence:293–342

Available at: http://dx.doi.org/10.1016/b978-008043793-4/50053-2.

Gur RC, Richard J, Hughett P, Calkins ME, Macy L, Bilker WB, Brensinger C, Gur RE (2010)

A cognitive neuroscience-based computerized battery for efficient measurement of

individual differences: standardization and initial construct validation. J Neurosci Methods

187:254–262.

Hahamy A, Behrmann M, Malach R (2015) The idiosyncratic brain: distortion of spontaneous

connectivity patterns in autism spectrum disorder. Nat Neurosci 18:302–309.

Hawco C, Yoganathan L, Voineskos AN, Lyon R, Tan T, Daskalakis ZJ, Blumberger DM,

Croarkin PE, Lai M-C, Szatmari P, Ameis SH (2020) Greater Individual Variability in

Functional Brain Activity during Working Memory Performance in young people with

Autism and Executive Function Impairment. Neuroimage Clin 27:102260.

Hearne L, Cocchi L, Zalesky A, Mattingley JB (2015) Interactions between default mode and

control networks as a function of increasing cognitive reasoning complexity. Hum Brain

Mapp 36:2719–2731.

Hearne LJ, Mattingley JB, Cocchi L (2016) Functional brain networks related to individual

differences in human intelligence at rest. Sci Rep 6:32328.

Hilger K, Fukushima M, Sporns O, Fiebach CJ (2020) Temporal stability of functional brain

modules associated with human intelligence. Hum Brain Mapp 41:362–372.

Hutchison RM, Morton JB (2015) Tracking the Brain's Functional Coupling Dynamics over

Development. J Neurosci 35:6849–6859.

Hutchison RM, Womelsdorf T, Allen EA, Bandettini PA, Calhoun VD, Corbetta M, Della Penna

S, Duyn JH, Glover GH, Gonzalez-Castillo J, Handwerker DA, Keilholz S, Kiviniemi V,

Leopold DA, de Pasquale F, Sporns O, Walter M, Chang C (2013) Dynamic functional

connectivity: promise, issues, and interpretations. Neuroimage 80:360–378.

Ji JL, Spronk M, Kulkarni K, Repovš G, Anticevic A, Cole MW (2019) Mapping the human

brain's cortical-subcortical functional network organization. Neuroimage 185:35–57.

Jung RE, Haier RJ (2007) The Parieto-Frontal Integration Theory (P-FIT) of intelligence:

converging neuroimaging evidence. Behav Brain Sci 30:135–154; discussion 154–187.

Krishnan A, Williams LJ, McIntosh AR, Abdi H (2011) Partial Least Squares (PLS) methods for

neuroimaging: a tutorial and review. Neuroimage 56:455–475.

Lombardo D, Cassé-Perrot C, Ranjeva J-P, Le Troter A, Guye M, Wirsich J, Payoux P, Bartrés-

Faz D, Bordet R, Richardson JC, Felician O, Jirsa V, Blin O, Didic M, Battaglia D (2020)

Modular slowing of resting-state dynamic functional connectivity as a marker of cognitive

dysfunction induced by sleep deprivation. Neuroimage 222:117155.

Lord L-D, Expert P, Atasoy S, Roseman L, Rapuano K, Lambiotte R, Nutt DJ, Deco G, Carhart-

Harris RL, Kringelbach ML, Cabral J (2019) Dynamical exploration of the repertoire of

brain networks at rest is modulated by psilocybin. Neuroimage 199:127–142.

McIntosh AR (2021) Comparison of Canonical Correlation and Partial Least Squares analyses of

simulated and empirical data. arXiv [statME] Available at: http://arxiv.org/abs/2107.06867.

McIntosh AR, Bookstein FL, Haxby JV, Grady CL (1996) Spatial Pattern Analysis of Functional

Brain Images Using Partial Least Squares. Neuroimage 3:143–157.

McIntosh AR, Lobaugh NJ (2004) Partial least squares analysis of neuroimaging data:

applications and advances. Neuroimage 23 Suppl 1:S250–S263.

Nomi JS, Vij SG, Dajani DR, Steimke R, Damaraju E, Rachakonda S, Calhoun VD, Uddin LQ

(2017) Chronnectomic patterns and neural flexibility underlie executive function.

Neuroimage 147:861–871.

Panizzon MS, Vuoksimaa E, Spoon KM, Jacobson KC, Lyons MJ, Franz CE, Xian H,

Vasilopoulos T, Kremen WS (2014) Genetic and environmental influences on general

cognitive ability: Is g a valid latent construct? Intelligence 43:65–76 Available at:

http://dx.doi.org/10.1016/j.intell.2014.01.008.

Preti MG, Bolton TA, Van De Ville D (2017) The dynamic functional connectome: State-of-the-

art and perspectives. Neuroimage 160:41–54.

Ramirez-Mahaluf JP, Medel V, Tepper Á, Alliende LM, Sato JR, Ossandon T, Crossley NA

(2020) Transitions between human functional brain networks reveal complex, cost-efficient

and behaviorally-relevant temporal paths. Neuroimage 219:117027.

Salimi-Khorshidi G, Douaud G, Beckmann CF, Glasser MF, Griffanti L, Smith SM (2014)

Automatic denoising of functional MRI data: combining independent component analysis

and hierarchical fusion of classifiers. Neuroimage 90:449–468.

Schifano F, Catalani V, Sharif S, Napoletano F, Corkery JM, Arillotta D, Fergus S, Vento A,

Guirguis A (2022) Benefits and Harms of "Smart Drugs" (Nootropics) in Healthy

Individuals. Drugs 82:633–647.

Schultz DH, Cole MW (2016) Higher Intelligence Is Associated with Less Task-Related Brain

Network Reconfiguration. J Neurosci 36:8551–8561.

Shine JM, Breakspear M, Bell PT, Ehgoetz Martens KA, Shine R, Koyejo O, Sporns O, Poldrack

RA (2019) Human cognition involves the dynamic integration of neural activity and

neuromodulatory systems. Nat Neurosci 22:289–296.

Smith SM et al. (2013) Resting-state fMRI in the Human Connectome Project. Neuroimage

80:144–168.

Spearman C (1961) "General Intelligence" Objectively Determined and Measured. In: Studies in

individual differences: The search for intelligence , (pp (Jenkins JJ, ed), pp 59–73.

Terman (1954) Scientists and nonscientists in a group of 800 gifted men. Psychological

Monographs: General and Applied 68:1–44.

Trampush JW et al. (2017) GWAS meta-analysis reveals novel loci and genetic correlates for

general cognitive function: a report from the COGENT consortium. Mol Psychiatry

22:1651–1652.

Vatansever D, Menon DK, Manktelow AE, Sahakian BJ, Stamatakis EA (2015) Default Mode

Dynamics for Global Functional Integration. J Neurosci 35:15254–15262.

Vohryzek J, Deco G, Cessac B, Kringelbach ML, Cabral J (2020) Ghost Attractors in

Spontaneous Brain Activity: Recurrent Excursions Into Functionally-Relevant BOLD

Phase-Locking States. Front Syst Neurosci 14:20.

Whalley LJ, Deary IJ (2001) Longitudinal cohort study of childhood IQ and survival up to age

76. BMJ 322:819.

Wold (1982) Soft modelling: the basic design and some extensions. Systems under indirect

observation, Part II Available at: https://cir.nii.ac.jp/crid/1571980074376633216.

Xiang J, Fan C, Wei J, Li Y, Wang B, Niu Y, Yang L, Lv J, Cui X (2022) The Task Pre-

Configuration Is Associated With Cognitive Performance Evidence From the Brain

Synchrony. Front Comput Neurosci 16:883660.

Xia Y, Chen Q, Shi L, Li M, Gong W, Chen H, Qiu J (2019) Tracking the dynamic functional

connectivity structure of the human brain across the adult lifespan. Hum Brain Mapp

40:717–728.

Zhou Y, Friston KJ, Zeidman P, Chen J, Li S, Razi A (2018) The Hierarchical Organization of

the Default, Dorsal Attention and Salience Networks in Adolescents and Young Adults.

Cereb Cortex 28:726–737.

873