Mining drug-target interactions from biomedical literature using chemical and gene descriptions based ensemble transformer model

Jehad Aldahdooh[1,3], Ziaurrehman Tanoli[2*], Jing Tang[1*]

Affiliation: 1) Research Program in Systems Oncology, Faculty of medicine, University of Helsinki, Finland; 2) Institute for Molecular Medicine Finland, University of Helsinki, Finland; 3) Doctoral Programme in Computer Science, University of Helsinki, Finland.

*Correspondence: zia.rehman@helsinki.fi, jing.tang@helsinki.fi

Abstract

Drug-target interactions (DTIs) play a pivotal role in drug discovery, as it aims to identify potential drug targets and elucidate their mechanism of action. In recent years, the application of natural language processing (NLP), particularly when combined with pre-trained language models, has gained considerable momentum in the biomedical domain, with the potential to mine vast amounts of texts to facilitate the efficient extraction of DTIs from the literature. In this article, we approach the task of DTIs as an entity-relationship extraction problem, utilizing different pre-trained transformer language models, such as BERT, to extract DTIs. Our results indicate that an ensemble approach, by combining gene descriptions from the Entrez Gene database with chemical descriptions from the Comparative Toxicogenomics Database (CTD), is critical for achieving optimal performance. The proposed model achieves an F1 score of 80.6 on the hidden DrugProt test set, which is the top-ranked performance among all the submitted models in the official evaluation. Furthermore, we conduct a comparative analysis to evaluate the effectiveness of various gene textual descriptions sourced from Entrez Gene and UniProt databases to gain insights into their impact on the performance. Our findings highlight the potential of NLP-based text mining using gene and chemical descriptions to improve drug-target extraction tasks.

Keywords: DrugProt, BERT, RoBERTa, SciBERT, BioLinkBERT, drug-target interactions, biomedical text mining, drug repurposing, mining drug-target interactions, entity-relationship extraction, ensemble model, Transformers.

Introduction

The study of small molecules and their interactions with protein targets is a key element in drug discovery research. Over the years, a vast amount of information on these interactions has been published in scientific literature including high throughput screening studies [1, 2]. With recent advancements in NLP technologies, there is an ever-increasing need to develop semi-automated text-based transformer models (such as BERT) that can dig further into the text of a screening

study to mine DTIs subject to human approval [3]. In the field of NLP, entity relationship extraction is a process of identifying and extracting meaningful relationships between entities (in this case compounds and protein targets) from textual data. To accelerate the extraction of drug-target interactions (DTIs), the BioCreAtIvE (Critical Assessment of Information Extraction systems in Biology) consortium organized a DrugProt challenge [4], which provided participants with a manually annotated dataset, the DrugProt corpus, which contains PubMed abstracts, manually annotated chemical compound and gene/protein mentions, and their interactions of 13 types that cover key relations of biomedical importance.

Most of the participants in the DrugProt challenge applied the most recent pre-trained models like BERT to train on the domain of drug-target interactions. For example, in [5], authors leveraged ensembles of pre-trained language models such as RoBERTa-large [6], using chemical descriptions to achieve an F1 score of 79.73 as the best model in the DrugProt challenge. More recently, authors in [7] employed a sequence labelling framework, achieving a state-of-the-art F1-score of 80.0 on the test set.

In a recent study [8], the authors proposed to enhance the supervised extraction of DTIs by integrating distantly supervised models. While traditional supervised methods rely on manually labelled data for training, which can be resource-intensive and time-consuming, distantly supervised models utilize existing knowledge bases to label the data automatically. However, their experimental results revealed that the proposed approach could have improved the performance accuracy as expected. On the contrary, the inclusion of mislabeled data resulted in even lower performance accuracy. Therefore, this study highlights the limitations within the current supervised approach to DTIs extraction.

In light of the challenges faced by the supervised extraction approaches, an alternative strategy in [9] has emerged which emphasizes the integration of heterogeneous knowledge graphs (HKGs) into drug-drug interaction extraction from biomedical literature. Recognizing the necessity of incorporating a diversity of background knowledge into the extraction process, like human experts comprehend and dissect the scientific literature, the authors built the drug representations by conducting a link prediction task on a pharmaceutical HKG dataset. Then, they combined the contextual information of the input sentences in the corpus with the drug information from the HKG dataset. On evaluation with the DrugProt dataset, their method achieved an F1-score of 77.9 on the development set.

In this study, we delve into a distinctive aspect of gene descriptions sourced from the Entrez Gene database—an avenue not previously explored, as most research primarily focuses on utilizing information from protein databases such as UniProt [10]. Additionally, we pioneered the combined use of both chemical and gene descriptions. To achieve this, we deployed a Multi-Model Ensemble (CGDE) that combines specialized models focused on analyzing chemical and gene data. Our work not only improves the F1 scores achieved by the aforementioned related works but also highlights the importance of incorporating gene descriptions in the DTI extraction

process. By leveraging the rich information in gene descriptions, our method demonstrates a more comprehensive understanding of the intricate relationships between drugs and their target proteins, ultimately contributing to more efficient and accurate DTI extraction from biomedical text.

Materials and methods

Datasets

We have mainly used DrugProt for training the models. DrugProt is a publicly available dataset containing manually annotated entities and relations relevant to drug discovery research. The DrugProt dataset consists of training, development, and testing subsets. Although the actual labels for the test dataset remain hidden, participants can submit their predictions to the Codelab platform and receive the final prediction results. Figure 1 provides a comprehensive overview of the statistics for the DrugProt training and development datasets. Within this dataset, gene entities are categorized into two primary classifications: GENE-Y, which represents normalizable genes, and GENE-N, marking non-normalizable genes. In terms of relation types, the DrugProt dataset is quite extensive, featuring 13 distinct categories, including: INDIRECT-DOWNREGULATOR, INDIRECT-UPREGULATOR, DIRECT-REGULATOR, ACTIVATOR, INHIBITOR, AGONIST, ANTAGONIST, AGONIST-ACTIVATOR, AGONIST-INHIBITOR, PRODUCT-OF, SUBSTRATE, SUBSTRATE_PRODUCT-OF, and PART-OF. These classifications enable a comprehensive understanding of the relations and interactions among various entities within the DrugProt dataset.

Figure 1: Distribution of the biological entities in the DrugProt dataset. (A) Number of documents (PubMed articles), chemical and gene entities. (B) Number of relation types in DTIs.

We conducted experiments using various model configurations, and subsequently linked chemical and gene entities to their ontologies. To retrieve chemical and gene entities, we utilized the Pubtator's API [11], which utilizes GNormPlus [12] for the gene/protein annotation and determines their NCBI Gene identifiers (Figure 2). For the chemical annotation, Pubtator employs TaggerOne [13] to link the chemical names to MeSH identifiers. Using the gene IDs, we obtained the gene summary descriptions from the Entrez Gene database, making our experiment the first attempt to acquire such information. Furthermore, we extracted the description for each gene from their respective web pages using specific HTML tags. For the protein annotation, we obtained the descriptions from the UniProt database.

Figure 2. An example of gene/protein summary and function descriptions from the Entrez (A) and UniProt (B) databases. Extracted text descriptions from both databases are highlighted in the rectangle.

In our study, we utilized the same chemical descriptions as in [5], which were derived from the Comparative Toxicogenomics Database (CTD). These descriptions were obtained from the Definition field of the CTD's chemical vocabulary, specifically taking the first sentence of the definition. Furthermore, we computed **576** descriptors from the gene sequences using Amino Acid index database [14]. From these, 420 are based on monopeptide and dipeptide frequencies for the 20 amino acids. The remaining 156 features relate to various physicochemical properties, mass, length and free energy.

Methods

We approached the drug-target relation classification task as a multi-label problem similar to [5]. However, we employed various setup configurations, including the use of Focal Loss instead of binary cross-entropy loss. Furthermore, we incorporated both gene and chemical description datasets. We utilized various pre-trained BERT (Bidirectional Encoder Representations from Transformers) models (large and base), including SciBERT [15], BioBERT [16], RoBERTa [6], BioLinkedBert [17], with a primary emphasis on the RoBERTa model. We combined all these models to form an ensemble of different transformer models.

SciBERT [15] is a scientific text-specific version of BERT, fine-tuned on an expansive corpus of scientific papers from Semantic Scholar, encompassing diverse scientific disciplines. SciBERT is designed to better capture and understand the language and terminology used in scientific literature. In our experiments, we employed the allenai/scibert_scivocab_uncased (https://huggingface.co/allenai/scibert_scivocab_uncased) model, which is publicly available through the Hugging Face Hub (https://huggingface.co/models). BioBERT [16] offers a specialized language representation model for the biomedical domain, trained on large-scale biomedical corpora, available at dmis-lab/biobert-large-cased-v1.1 (https://huggingface.co/dmis-

lab/biobert-large-cased-v1.1) model. RoBERTa (Robustly optimized BERT) is a variant of the BERT model developed by Facebook AI and is designed to improve upon the original BERT model in several ways by using a larger and more diverse training datasets, longer training time, and dynamic masking to improve the model's ability to understand natural languages. RoBERTa also removes the next sentence prediction objective used in BERT, which was found to be less important for many NLP tasks. RoBERTa-large is a variant of the RoBERTa model, with even more parameters and a longer training time. It is designed to further improve upon the original RoBERTa model's ability to understand natural languages. RoBERTa-large is generally considered to be more powerful and accurate than the smaller RoBERTa model. We used the RoBERTa-large-PM-M3-Voc [18] (https://github.com/facebookresearch/bio-lm) model in our experiments.

BioLinkBERT [17] is a unique version of BERT that includes document link knowledge, such as hyperlinks and citation links from PubMed abstracts, allowing the model to integrate information from multiple documents. Pre-training involves feeding linked documents into the same language model context, in addition to a single document. In our experiments, we employed the BioLinkBERT-large model that is available at (https://huggingface.co/michiyasunaga/BioLinkBERT-large).

To generate the training and development instances from an abstract, we considered all compound-target pairs that occur in the same sentences. We created one instance for each compound-target entity pair, inserting special tokens [HEAD-S], [HEAD-E], [TAIL-S], and [TAIL-E] to mark the start and end of the head (the chemical entity) and tail (the target gene entity). We used the context embeddings of the [CLS] token from the last hidden layer of the BERT model and fed it to a fully connected layer to obtain the logits. Additionally, we experimented with the embeddings of the target gene features, concatenating them with the [CLS] output. The main framework is shown in Figure 3. Moreover, we incorporated an experimental strategy of varying random seeds to assess their impact on the model's stability and performance. The random seeds used were: 0, 1, 3, 4, 5, 7, 9, 10, 20, 42, and 1024. Whenever the model encountered difficulty in converging with a specific seed (e.g., 123), we removed that particular seed from our set to ensure the optimal performance.

Figure 3: Overview of the best performing ensemble model. Our experiments utilize an ensemble of the RoBERTa-large-PM-M3-Voc, BioBERT-v1.1, BioLinkBERT-large, SciBERT, and Roberta Base models. The abstract texts are processed with BERT, together with target gene and chemical descriptions extracted from the Entrez and CTD databases, respectively. Furthermore, we integrated 576 gene sequence-based features. Special tokens mark the start and end of chemical-gene entities. These tokens are also incorporated in the model's input. The left side of the diagram is represented by blue dashed lines, which emphasize the model's focus on chemical descriptions, whereas the right side section is dedicated to utilizing gene descriptions and features based on gene sequences.

Loss function

We used Focal Loss, which is a loss function designed to address the issue of class imbalance in classification tasks. Focal Loss was first introduced in [19] to improve the performance of object detection models. However, it can also be applied to our classification problem where there is a class imbalance between the relations (Figure 1). The Focal Loss is an extension of the Binary Cross Entropy (BCE) loss, but it introduces a modulating factor that decreases the contribution of well-classified examples to the loss. This helps the model to focus more on the hard-to-classify examples, thus addressing the class imbalance issue. Focal loss has two main parameters:

- Gamma (γ): The focusing parameter, which determines how much the contribution of well-classified examples is reduced. A higher value of gamma will lead to a more focused loss function. In our study, we set the focusing parameter to $\gamma = 0.5$.
- Eps (ε) : A small value added to the logarithm term to prevent division by zero or taking the logarithm of zero. We used the default value 1e-6.

It is defined as:

$$loss = -\sum_{i=1}^{N} [y_i \cdot (1 - p_i)^{\gamma} \cdot \log(p_i + \epsilon) + (1 - y_i) \cdot p_i^{\gamma} \cdot \log(1 - p_i + \epsilon)]$$

where:
- N is the total number of samples in the dataset
- y_i is the true label for the ith sample
- p_i is the predicted probability for the ith sample

Experiments

We ran the experiments with 10 different random seeds and averaged the results to obtain a more robust estimate of the prediction performance. To assess the effectiveness of our approach, we conducted a series of four experiments. Subsequently, we submitted the final predictions to the official site for the evaluation on the hidden test set. The results were reported as micro-averaged F1 computed using the official DrugProt evaluation library (https://github.com/tonifuc3m/drugprot-evaluation-library). The experiments conducted are summarized as follows:

Model 1: Gene Description Ensemble (GDE) Model
The main goal of this experiment was to assess how gene descriptions affect prediction accuracy. To achieve this, we constructed a Gene Description Ensemble (GDE) comprising 10 models. These models encompassed different models to leverage their unique strengths – consisting of the Roberta Base, SciBERT, RoBERTa-large-PM-M3-Voc, BioLinkBERT-large, and BioBERT-v1.1 single models – all of which incorporated gene descriptions. By including a diverse range of model architectures and learning strategies within the GDE, we aimed to provide extensive coverage and enhance the ensemble's overall performance. The ensemble model is constructed by taking the average of the probabilities generated by the models with a threshold of 0.5 or higher.

Model 2 (Base model): Chemical Description Ensemble (CDE) Model
To determine the benchmark for our comparative analysis, we selected the top-performing model from the DrugProt Challenge, which achieved an F1 score of 79.7 on the concealed DrugProt test data as a baseline model. This result was attained by training an ensemble of ten RoBERTa-large-PM-M3-Voc models, incorporating chemical definitions from the Comparative Toxicogenomics Database (CTD) for both the training and development sets.
We employed the same approach by developing an ensemble of 10 RoBERTa-large-PM-M3-Voc models with different seeds. The ensemble model we employed – consisting of the RoBERTa-large-PM-M3-Voc and BioLinkBERT-large single models.

Model 3: Chemical and Gene Description Ensemble (CGDE) Model

We employed an ensemble that utilized both gene and chemical descriptions models as an integration to models 1 and 2.

Model 4: Gene sequence-based Features and text Descriptors Ensemble (GFDE) Model

Gene sequence-based features were incorporated in this experiment. An ensemble of 10 RoBERTa-large-PM-M3-Voc models with different seeds has been constructed using gene descriptions, along with gene sequence-based features. Nevertheless, they did not contribute to an improvement in the results. In order to preprocess the gene sequence-based features, L2 normalization was applied by dividing each vector by its L2 norm, as expressed in Equation (2).

$$\text{Normalized Vector = Vector / }||\text{Vector}||_2 \qquad (2)$$

Where:

- Normalized Vector represents the resulting vector after applying the normalization process.
- Vector represents the original vector.
- $||\text{Vector}||_2$ represents the L2 norm of the vector.

Results and discussion

Performance of the four different models on the hidden DrugProt test data

The four models demonstrated varying levels of performance on the DrugProt hidden test data. The CGDE model achieved the highest F1 score of 80.6, followed by the GDE model with 80.1, the CDE model with 79.7, and the GFDE model with 79.5. These results indicate that the CGDE model outperformed the other models in terms of overall predictive accuracy (Figure 4). Our experiments showed that utilizing only the Entrez gene descriptions (GDE Model) yielded better performance, with an improvement by approximately 0.4 F1 compared to the CDE baseline model. Combining chemical and gene descriptions led to a more significant increase, with approximately 0.9 points F1 improvement over the CDE baseline model. These results suggested that integration of chemical and gene descriptions in an ensemble BERT model achieved the best performance, compared to the top-performing model from the DrugProt Challenge. However, adding gene sequence based features besides gene descriptions led to a slight decrease of approximately 0.2 points F1, suggesting that the numeric features may not be optimal when combined with BERT contextual embeddings..

In Figure 5, we compared the performance per class achieved by the four different models.

It can be shown that the ANTAGONIST relation seems to consistently have the highest F1 score across all models, indicating that this class was the easiest for the models to predict correctly. The highest F1 score is 92.3 by the CGDE model. Furthermore, both the ANTAGONIST and INHIBITOR interaction types display a stable and consistent performance across all the four models. This could suggest that the features for these types of interactions are robust and well-

captured, which consistently rank in the top 2 in terms of precision, recall and F1 scores across all the models. The CGDE model generally performs the best across different interaction types. It achieves the highest F1 score for ANTAGONIST, DIRECT-REGULATOR, SUBSTRATE, PART-OF, ACTIVATOR, INDIRECT-UPREGULATOR, INDIRECT-DOWNREGULATOR, and AGONIST-INHIBITOR. However, the GFDE model performs better for INHIBITOR, and PRODUCT-OF relations.

Performance on rare classes

The AGONIST-INHIBITOR relation shows the most variability in accuracy across different models since it is rarely present (Figure 1). For example, the GFDE model has an F1 score of 50, CGDE has an F1 score of 100, while GDE and CDE have an F1 score of 0. This discrepancy could be due to the different ways these models handle this specific interaction class.

In the case of CGDE, we implemented a lower threshold (>= 0.2 instead of >= 0.5) to detect this relation. This adjustment was necessary due to its relatively low representation in the training and development dataset, as well as the model's tendency to predict this relation with a lower probability. Conversely, in the GFDE model, the gene features appear to aid in capturing the context of the agonist-inhibitor relation, allowing the model to identify it without altering the threshold.

Additionally, none of the four models predict AGONIST-ACTIVATOR or SUBSTRATE_PRODUCT-OF relations, primarily due to the limited size of training and development samples available for these specific relationships (Figure 1).

Recall and Precision trade-off

There is an evident trade-off between precision and recall in the four different models. For example, in the DIRECT-REGULATOR relation, the GDE model has a high precision of 79.3 but a relatively low recall of 68.8. In contrast, the CGDE model has a lower precision of 76.2 but a higher recall of 72.5. This indicates that GDE is more conservative in predicting DIRECT-REGULATOR, resulting in fewer false positives but more false negatives. The CGDE, on the other hand, makes more positive predictions, leading to fewer false negatives but more false positives.

Figure 4: Performance comparison of the four models on the hidden DrugProt test set, presented as micro-averaged precision, recall, and F1 scores, separately.

Performance comparison with the latest top-performing model on DrugProt

After the DrugProt Challenge, more models have been submitted, with one of them outperforming the original top-performing CDE model. The latest top-performing model was achieved by the NLM-NCBI team, who utilized an ensemble approach employing sequence labeling models with standard loss that were trained using DevES and TrainES via majority voting [5]. Based on the results of the hidden test data, our CGDE model has achieved higher overall accuracy compared to the NLM-NCBI model (Table 1).

Figure 5: Comparative analysis of model performance per relation types.

Relation type	Humboldt	NLM-NCBI -ensemble	Our best model (CGDE)
ANTAGONIST	91.5	92.4	92.3
INHIBITOR	88.0	87.6	**88.6**
AGONIST	82.1	85.3	80.4
ACTIVATOR	81.7	83.2	82.4
INDIRECT-UPREGULATOR	77.2	78.1	**78.3**
INDIRECT-DOWNREGULATOR	79.4	75.9	**80.4**
PART-OF	75.5	76.9	75.6
DIRECT-REGULATOR	72.9	70.6	**74.3**

Relation type	Humboldt	NLM-NCBI -ensemble	Our best model (CGDE)
SUBSTRATE	68.2	73.4	70.6
PRODUCT-OF	71.0	68.2	**71.6**
AGONIST-INHIBITOR	0.0	100.0	**100.0**
Overall-F1	79.7	80.0	**80.6**

Table 1. Performance comparison between the NLM-NCBI Ensemble model, and our best model (CGDE) on the DrugProt test data.

In assessing our CGDE ensemble model, alongside the Humboldt (CDE) ensemble model and the NLM-NCBI ensemble model, we observed a significant variance in the class-wise results.

For the ANTAGONIST class, our model demonstrated high efficacy, with a success rate of 92.3. This was nearly on par with the NLM-NCBI ensemble model at 92.4, but markedly superior to that of the Humboldt CDE model, which scored 91.5. In the INHIBITOR class, our CGDE model outstripped the competition, achieving an 88.6 score. This surpassed the NLM-NCBI model's 87.6 and the 88 score of the Humboldt CDE model. This pattern was mirrored in the INDIRECT-DOWNREGULATOR, DIRECT-REGULATOR, and PRODUCT-OF relations categories.

However, a different trend emerged for the AGONIST class. Our model lagged slightly behind at 80.4, compared to the NLM-NCBI and Humboldt ensemble models. Similarly, in the ACTIVATOR class, while our model outpaced the Humboldt ensemble model, it was slightly behind the NLM-NCBI ensemble model at 82.4. In the INDIRECT-UPREGULATOR class, our model performed comparably with the NLM-NCBI model, with a marginal 0.2 F1 points advantage, and surpassed the Humboldt ensemble model. Lastly, in the AGONIST-INHIBITOR class, both models achieved a flawless score of 100.

Despite the class-specific variations, the overall F1-score for our CGDE ensemble model model narrowly topped the list with an overall score of 80.6, compared to the NLM-NCBI model's 80.0 and Humboldt CDE model's 79.7.

Comparison of NCBI Entrez gene summary and UniProt protein function description

The UniProt protein function is a feature available in the UniProt database [10], a comprehensive resource for protein sequence and functional information. The protein function section provides a brief and informative summary of the protein's function including the protein's biological

activity, localization, interaction partners, and related pathways. An example of the data is shown in Figure 2B.

The Humboldt team utilized multiple single models using RoBERTa-large-PM-M3-Voc with different seeds, in conjunction with an ensemble model that integrated UniProt protein function descriptions. Their testing ground was the DrugProt development dataset and reported their single results as the mean and standard deviation of the top three runs from a pool of five different random seeds. For our part, we employed a similar methodology, using a variety of single models using RoBERTa-large-PM-M3-Voc and an ensemble model. However, our findings indicated that the NCBI Entrez gene summary data offered a more comprehensive resource, and consequently resulted in slightly better F1 scores when contrasted with the UniProt protein function (Table 2). The results demonstrate that a single model employing gene summary description attains a superior F1 score, showing an improvement of +0.7 points, in contrast to the performance of three model runs that utilized UniProt protein function.

	Single			Ensemble		
	P	R	F1	P	R	F1
UniProt protein function **3 runs**	77.4 ±0.6	79± 0.5	78.5 ±0.2	78.8	79.6	**79.2**
NCBI Entrez gene summary **1 run**	79.8	79	**79.4**	-	-	-
NCBI Entrez gene summary **3 runs**	79.9 ±1.6	77.9 ±1.7	**78.9 ±0.4**	79.6	79.5	**79.5**

Table 2. Comparative analysis of including the UniProt protein function summaries and the NCBI Entrez Gene summary data.

Conclusions

Data deposition from drug target studies into a public database, such as ChEMBL [20], PubChem [21], and Drug Target Commons (DTC) [22], still requires manual curation which is labor-intensive and time-consuming. To keep pace with the rapid growth of the literature, automated methods

for extracting DTIs are essential for reducing the time and cost associated with drug discovery and development. However, predicting the drug-target interaction types from scientific literature remains a demanding task. Our study demonstrates the efficacy of incorporating gene and chemical descriptions for the extraction of drug-target interactions from biomedical literature. The proposed methodology significantly improves upon the previous state-of-the-art approaches, showcasing the utility of our approach in biomedical text mining and in enhancing drug discovery efforts. Furthermore, the comparison between the usage of the NCBI Entrez gene summary and the UniProt protein function description indicates that the gene summary offers more comprehensive information about the drug-target interactions, yielding better model performance.

Looking ahead, several opportunities remain for further enhancements. For instance, our experiments have shown that the inclusion of gene sequence-based features did not yield significant improvement in the performance.. However, future studies could replace sequence-based features with transcriptomic features as adapted in [23]. Furthermore, we are planning to mine drug-target entities from the 0.3M articles identified in our previous work in [3]. In addition to that, while our method achieved the best performance in the BioCreative DrugProt task, we believe there is still room for improvement in the model architecture. For example, we intend to investigate the potential of leveraging other transformer-based models like BioGPT [24].

Lastly, the developed approach and the conclusions drawn are specific to the extraction of drug-target interactions. It would be interesting to investigate the generalizability of this method for other types of relationship extraction applications in drug discovery such as protein-protein interaction and drug-drug interactions. The results from this study thus represent a significant stride in the field of biomedical text mining and drug discovery, and we believe that the continuous advancements in natural language processing hold immense promise for further progress.

References

1. Davis MI, Hunt JP, Herrgard S, Ciceri P, Wodicka LM, Pallares G, Hocker M, Treiber DK, Zarrinkar PP. Comprehensive analysis of kinase inhibitor selectivity. Nat Biotechnol. 2011 Oct 30;29(11):1046-51. doi: 10.1038/nbt.1990. PMID: 22037378.

2. Anastassiadis T, Deacon SW, Devarajan K, Ma H, Peterson JR. Comprehensive assay of kinase catalytic activity reveals features of kinase inhibitor selectivity. Nat Biotechnol. 2011 Oct 30;29(11):1039-45. doi: 10.1038/nbt.2017. PMID: 22037377; PMCID: PMC3230241.

3. Aldahdooh J, Vähä-Koskela M, Tang J, Tanoli Z. Using BERT to identify drug-target interactions from whole PubMed. BMC Bioinformatics. 2022 Jun 21;23(1):245. doi: 10.1186/s12859-022-04768-x. PMID: 35729494; PMCID: PMC9214985.

4. Miranda A., Mehryary F., Luoma J. et al. (2021) Overview of DrugProt BioCreative VII track: quality evaluation and large scale text mining of drug-gene/protein relations. In: Proceedings of the BioCreative VII challenge evaluation workshop. Online, pp. 11–21

5. Leon Weber, Mario Sänger, Samuele Garda, Fabio Barth, Christoph Alt, Ulf Leser, Chemical–protein relation extraction with ensembles of carefully tuned pretrained language models, Database, Volume 2022, 2022, baac098, https://doi.org/10.1093/database/baac098

6. Liu Y., Ott M., Goyal N. et al. . (2019) Roberta: A robustly optimized bert pretraining approach. preprint, arXiv:1907.11692 (9 February 2022, date last accessed).

7. Luo L, Lai PT, Wei CH, Lu Z. A sequence labeling framework for extracting drug-protein relations from biomedical literature. Database (Oxford). 2022 Jul 19;2022:baac058. doi: 10.1093/database/baac058. PMID: 35856889; PMCID: PMC9297941.

8. Naoki Iinuma, Makoto Miwa, and Yutaka Sasaki. 2022. Improving Supervised Drug-Protein Relation Extraction with Distantly Supervised Models. In Proceedings of the 21st Workshop on Biomedical Language Processing, pages 161–170, Dublin, Ireland. Association for Computational Linguistics.

9. Masaki Asada and others, Integrating heterogeneous knowledge graphs into drug–drug interaction extraction from the literature, Bioinformatics, Volume 39, Issue 1, January 2023, btac754, https://doi.org/10.1093/bioinformatics/btac754

10. Coudert E, Gehant S, de Castro E, Pozzato M, Baratin D, Neto T, Sigrist CJA, Redaschi N, Bridge A; UniProt Consortium. Annotation of biologically relevant ligands in UniProtKB using ChEBI. Bioinformatics. 2023 Jan 1;39(1):btac793. doi: 10.1093/bioinformatics/btac793. PMID: 36484697; PMCID: PMC9825770.

11. C.-H. Wei, A. Allot, R. Leaman, Z. Lu, PubTator central: automated concept annotation for biomedical full text articles, Nucleic Acids Research 47 (2019) W587–W593. URL: https://doi.org/10.1093/nar/gkz389. doi:10.1093/nar/gkz389.

12. Wei C.-H., Kao H.-Y., Lu Z.. GNormPlus: An integrative approach for tagging genes, gene families, and protein domains. Biomed Res Int. 2015; 2015:7.

13. Leaman R., Lu Z.. TaggerOne: joint named entity recognition and normalization with semi-Markov Model. *Bioinformatics*. 2016; 32:2839–2846.

14. Shuichi Kawashima , Minoru Kanehisa, AAindex: Amino Acid index database, Nucleic Acids Research, Volume 28, Issue 1, 1 January 2000, Page 374, https://doi.org/10.1093/nar/28.1.374

15. Iz Beltagy, Kyle Lo, and Arman Cohan. 2019. SciBERT: A Pretrained Language Model for Scientific Text. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 3615–3620, Hong Kong, China. Association for Computational Linguistics.

16. Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, Jaewoo Kang, BioBERT: a pre-trained biomedical language representation model for biomedical text mining, Bioinformatics, Volume 36, Issue 4, February 2020, Pages 1234–1240, https://doi.org/10.1093/bioinformatics/btz682

17. Michihiro Yasunaga, Jure Leskovec, and Percy Liang. 2022. LinkBERT: Pretraining Language Models with Document Links. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 8003–8016, Dublin, Ireland. Association for Computational Linguistics.

18. Lewis P., Ott M., Jingfei D., et al. . (2020) Pretrained language models for biomedical and clinical tasks: understanding and extending the state-of-the-art. In: Proceedings of the 3rd Clinical Natural Language Processing Workshop. Association for Computational Linguistics, pp. 146–157.

19. T. -Y. Lin, P. Goyal, R. Girshick, K. He and P. Dollár, "Focal Loss for Dense Object Detection," 2017 IEEE International Conference on Computer Vision (ICCV), Venice, Italy, 2017, pp. 2999-3007, doi: 10.1109/ICCV.2017.324.

20. David Mendez and others, ChEMBL: towards direct deposition of bioassay data, Nucleic Acids Research, Volume 47, Issue D1, 08 January 2019, Pages D930–D940, https://doi.org/10.1093/nar/gky1075

21. Kim S, Chen J, Cheng T, et al. PubChem 2023 update. Nucleic Acids Res. 2023;51(D1):D1373–D1380. doi:10.1093/nar/gkac956

22. Tang J, Tanoli ZU, Ravikumar B, Alam Z, Rebane A, Vähä-Koskela M, Peddinti G, van Adrichem AJ, Wakkinen J, Jaiswal A, Karjalainen E, Gautam P, He L, Parri E, Khan S, Gupta A, Ali M, Yetukuri L, Gustavsson AL, Seashore-Ludlow B, Hersey A, Leach AR, Overington JP, Repasky G, Wennerberg K, Aittokallio T. Drug Target Commons: A Community Effort to Build a Consensus Knowledge Base for Drug-Target Interactions. Cell Chem Biol. 2018 Feb 15;25(2):224-229.e2. doi: 10.1016/j.chembiol.2017.11.009. Epub 2017 Dec 21. PMID: 29276046; PMCID: PMC5814751.

23. Xie, L., He, S., Song, X. et al. Deep learning-based transcriptome data classification for drug-target interaction prediction. BMC Genomics 19 (Suppl 7), 667 (2018). https://doi.org/10.1186/s12864-018-5031-0

24. Renqian Luo and others, BioGPT: generative pre-trained transformer for biomedical text generation and mining, Briefings in Bioinformatics, Volume 23, Issue 6, November 2022, bbac409, https://doi.org/10.1093/bib/bbac409