GRouNdGAN: GRN-guided simulation of single-cell RNA-seq data using causal generative adversarial networks

Yazdan Zinati[1], Abdulrahman Takiddeen[1], and Amin Emad[1,2,3,*]

[1] Department of Electrical and Computer Engineering, McGill University, Montreal, QC, Canada

[2] Mila, Quebec AI Institute, Montreal, QC, Canada

[3] The Rosalind and Morris Goodman Cancer Institute, Montreal, QC, Canada

* Corresponding Author:

Amin Emad

755 McConnell Engineering Building

3480 University Street, Montreal, Quebec, Canada, H3A 0E9

Email: amin.emad@mcgill.ca

Abstract

We introduce GRouNdGAN, a gene regulatory network (GRN)-guided causal implicit generative

model for simulating single-cell RNA-seq data, *in-silico* perturbation experiments, and

benchmarking GRN inference methods. Through the imposition of a user-defined GRN in its

architecture, GRouNdGAN simulates steady-state and transient-state single-cell datasets where

genes are causally expressed under the control of their regulating transcription factors (TFs).

Training on three experimental datasets, we show that our model captures non-linear TF-gene

dependences and preserves gene identities, cell trajectories, pseudo-time ordering, and

technical and biological noise, with no user manipulation and only implicit parameterization.

Despite imposing rigid causality constraints, it outperforms state-of-the-art simulators in

generating realistic cells. GRouNdGAN learns meaningful causal regulatory dynamics, allowing

sampling from both observational and interventional distributions. This enables it to synthesize

cells under conditions that do not occur in the dataset at inference time, allowing to perform *in-*

silico TF knockout experiments. Our results show that *in-silico* knockout of cell type-specific TFs

significantly reduces cells of that type being generated, even though GRouNdGAN was not

trained on any perturbation datasets. Interactions imposed through the GRN are emphasized in

the simulated datasets, resulting in GRN inference algorithms assigning them much higher scores

than interactions not imposed but of equal importance in the experimental training dataset.

Benchmarking various GRN inference algorithms reveals that GRouNdGAN effectively bridges the

existing gap between simulated and biological data benchmarks of GRN inference algorithms,

providing gold standard ground truth GRNs and realistic cells corresponding to the biological

system of interest. Our results show that GRouNdGAN is a stable, realistic, and effective simulator

with various applications in single-cell RNA-seq analysis.

Introduction

Unraveling gene regulatory interactions plays a crucial role in studying biological processes under

different conditions[1-3], simulating knockdown and knockout experiments[4,5], and identifying

therapeutic drug targets[6,7]. Gene regulatory interactions can be depicted using gene regulatory

networks (GRNs), often modeled as directed acyclic graphs (DAGs) with genes as nodes and

regulatory interactions as directed edges. Many algorithms have been proposed in the literature

for gene regulatory network reconstruction using bulk or single-cell gene expression data; either

alone[8-14] or in combination with other data modalities[15-18]. These algorithmic developments in

GRN inference have been facilitated by technological advances in high-throughput single-cell

RNA sequencing (scRNA-seq), which enabled the measurement of transcriptomic profiles in

individual cells, leading to a wealth of large, high-resolution single-cell gene expression datasets.

The prevalence of such datasets has provided great insights at the cellular level in areas such as

gene regulation[19,20], perturbation experiments[21,22], cell identification[23], and trajectory

inference[24,25], and have opened the door for the use of data-intensive modeling techniques such

as deep learning[26,27].

While these recent advances have provided great biological insights, evaluating the performance

of GRN Inference algorithms remains challenging[28,29]. This is due to the lack of reliable ground

truth for the biological processes under study. Existing evaluation approaches often resort to

curated databases, such as GTRD[30], ESCAPE[31], and KEGG[32], which aggregate known regulatory

interactions from the literature utilizing sources such as ChIP-seq datasets, loss-of-function/gain-

of-function experiments, motif enrichment analysis and text mining. While this approach sheds

some light on known interactions, the regulatory interactions found in these databases are

typically aggregated from a wide range of datasets and may not be specific to the biological

system being studied, given the cell-type and context specificity of gene regulation. An

alternative strategy is to verify regulatory interactions by conducting perturbation experiments

on the system under study or a system that closely replicates its conditions[29]. This approach,

however, is tedious, lengthy, and expensive. Another approach is to employ scRNA-seq

simulation tools. However, most simulators lack the essential properties for this task, such as the

preservation of gene identities and generation based on a user-provided ground truth GRN. For

example, simulators, such as scGAN[26], cscGAN[26], scDESIGN2[33], and SPARSIM[34], can capture inter-

gene dependencies and correlations in their datasets. As such, they are capable of *implicitly*

modeling regulatory relations of their reference datasets. However, since these models do not

explicitly impose a known GRN (that can act as the ground truth) in generating their datasets,

they are not suitable for benchmarking GRN inference methods.

A small subset of existing simulators, such as BoolODE[28], SERGIO[4], and GeneNetWeaver (GNW)[35],

explicitly incorporate GRNs that underlie causal TF-gene dynamics. GNW was used to generate

the gold standard networks for Dialogue on Reverse Engineering Assessment and Methods

(DREAM) network inference challenges[35-37]. However, being a bulk RNA-seq tool, its simulated

datasets do not replicate the distribution of experimental scRNA-seq datasets nor exhibit their

statistical properties despite attempts to adapt the method for single-cell generation through

externally inducing dropout events[10,38]. SERGIO and BoolODE, on the other hand, were

specifically designed to simulate scRNA-seq data based on a ground truth GRN using stochastic

differential equations (SDEs)[4,28]. Both tools have been used to benchmark a variety of GRN

inference algorithms. However, often a mismatch between the GRN benchmarking results

obtained based on experimental and simulated data have been reported. For example, in

BEELINE's benchmarking results (using BoolODE), some of the top ranking GRN inference tools

on simulated datasets reported near random performance on experimental datasets[28]. The

observed mismatch in GRN inference results can be attributed to the poor resemblance between

simulated and real datasets. Both SERGIO and BoolODE enable the user to generate more realistic

simulated datasets by carefully selecting the values of the SDE model parameters. In addition,

using a reference dataset, SERGIO allows the user to fine-tune the added technical noise in an

iterative procedure until the generated and reference datasets are statistically matched[4]. While

these steps can help improve the resemblance to real datasets, they can often be suboptimal and

pose an undue burden on the end-user: for example, in SERGIO, the user must evaluate the

similarity based on five different statistics and change three parameters iteratively until desired

resemblance is achieved (which itself can be subjective). In addition, since the causal GRN is

imposed in the "clean" dataset, but technical noise is added afterwards, this step may affect and

change the encoded causal relationships in a non-trivial way (which may explain why the authors

observed that the performance of GRN inference methods dropped close to random when

applied to the noisy dataset[4]). Furthermore, SERGIO and BoolODE do not readily preserve gene

identities and make simplifying assumptions regarding cooperative regulation. In SERGIO, the

combinatorial effect of multiple regulatory TFs is merely the sum of their individual effects.

BoolODE allows for more complex coregulatory patterns by requiring the user to define Boolean

functions relating a gene to its regulators as a truth table. This results in only 2^R TF state

combinations for a gene with R regulators. These shortcomings demonstrate the need for

simulation tools that are capable of generating scRNA-seq data that better resemble real

datasets, while retaining the underlying gene regulatory dynamics specified by a user-define

GRN.

We present GRouNdGAN (GRN-guided in silico simulation of single-cell RNA-seq data using Causal

generative adversarial networks), a causal implicit generative model for the GRN-guided

simulation of single-cell RNA-seq data inspired by CausalGAN[39]. Given an input user-specified

GRN and a reference scRNA-seq dataset, GRouNdGAN can be trained to generate simulated

scRNA-seq data that is both indistinguishable from real scRNA-seq datasets and faithful to the

causal regulatory interactions defined in the input GRN. Unlike model-based simulators that rely

on simplifying assumptions regarding co-regulatory patterns, in GRouNdGAN these patterns are

learned through complex functions. This allows it not to compromise on the underlying

complexity of the system and to model elaborate regulatory dynamics. Using three experimental

scRNA-seq datasets, we show that GRouNdGAN provides state-of-the-art performance in scRNA-

seq realistic data generation, while preserving gene identities, causal gene regulatory

interactions, and cellular dynamics (e.g., lineage trajectory and pseudo-time ordering). This is

achieved through implicit parameterization without the need for manual fine-tuning. Since causal

TF-gene regulatory relationships defined by the input GRN are enforced in GRouNdGAN's

generated data, GRouNdGAN can be used for benchmarking GRN inference algorithms with the

input GRN as a ground truth. Using GRouNdGAN, we benchmark seven GRN inference methods

on our simulated datasets and find the results to be aligned with BEELINE's experimental results.

Furthermore, the causal structure of GRouNdGAN enables it to be used for sampling from both

interventional and observational data distributions. Using this property, we use GRouNdGAN to

simulate knockout experiments, creating cells under conditions that were not originally observed

in the data. Our results show the potential for GRouNdGAN to bridge the gap between existing

simulated and experimental datasets.

Results

GRouNdGAN generates simulated single-cell RNA-seq data using causal generative adversarial networks

GRouNdGAN is a deep learning model that generates simulated scRNA-seq data while imposing a user-

defined causal GRN to describe the regulatory relationships of the genes and transcription factors (TFs). The

architecture of GRouNdGAN builds on the causal generative adversarial network (CausalGAN)[39] and

includes a causal controller, several target generators, a critic, a labeler and an anti-labeler (Figure 1), all

implemented as separately parameterized neural networks.

Training is composed of two steps. First, the causal controller that generates TF expression values is pre-

trained (Figure 1A). This is achieved by incorporating the causal controller as the generator of a Wasserstein

GAN (WGAN)[40] that generates simulated samples resembling samples of a reference dataset (Methods). In

the second step (Figure 1B), TF expression values (generated by the pre-trained causal controller) along with

randomly generated noise values are provided as input to the target generators. Target generators produce

expression values of target genes of the TFs, while incorporating the dependency of TF-gene relationships

in the causal GRN. To achieve this, each target generator only accepts as input a noise value along with the

generated expression values of TFs that causally regulate it (Figure 1B, Methods). The generated expression

values of genes and TFs are then fed to a library-size normalization (LSN) layer[26].

The GRouNdGAN's critic's role is to quantify the Wasserstein distance between the reference and

simulated data distributions. The target generators are trained in an adversarial manner to

generate such realistic datapoints that are indistinguishable from the experimental datapoints

by the critic. The labeler and the anti-labeler estimate the causal controller's TF expression values

only from the target genes' expressions and ensure that the generated target gene expressions

are encoded with their regulators' information. The labeler is trained using both real and

generated values, while the anti-labeler is trained only from the values generated by the target

generators. The details of this model and training procedure are provided in Methods, the

architectural choices are provided in Supplementary Tables S1 and S2, and an ablation study is

provided in Supplementary File S1 and Table S3.

Figure 1: Architecture and training procedure of GRouNdGAN. A) A WGAN is pre-trained to generate realistic simulated cells. B) The LSN layer of the generator of the trained WGAN (panel A) is removed, its weights are frozen, and is used as the causal controller to generate unnormalized TF expression values. These TF expression values along with a noise vector are provided as input to the target generators, following the provided causal GRN. The generated gene and TF expression values are reorganized and passed through the LSN layer. The normalized simulated expression vectors and experimental reference data are then passed to the critic to estimate Wasserstein distance between the reference and the generated data distributions. The anti-labeler estimates TF values based on generated target gene expressions. The labeler performs a similar task, but in addition to receiving generated values, it also utilizes target gene expression values from the reference data. Labeler and anti-labeler ensure that the causal GRN is incorporated by the target generators. Details of the model are provided in Methods.

GRouNdGAN generates realistic scRNA-seq data

We used GRouNdGAN to generate data based on three reference datasets. The first dataset

contained scRAN-seq profiles of 68579 human peripheral blood mononuclear cells (PBMCs)

represented by UMI counts from 10x Genomics[41] corresponding to eleven cell types (henceforth

"PBMC-All"). We formed a dataset corresponding to the most common cell type in PBMC-All

dataset (CD8+ Cytotoxic T-cell) containing scRAN-seq profile of 20773 cells (henceforth "PBMC-

CTL"). Additionally, we obtained the scRNA-seq profile of 2730 cells corresponding to

differentiation of hematopoietic stem cells to different lineages from mouse bone marrow

b(measured using MARS-seq)[20] (henceforth "BoneMarrow"). For each dataset, we trained

GRouNdGAN on a randomly selected training set and evaluated on a held-out test set (Methods).

Figures 2A-2B and Supplementary Figures S1-S3 show the t-distributed stochastic neighbor

embedding (t-SNE) plots of real (experimental) and simulated cells, qualitatively revealing their

similarity.

Figure 2: Performance of GRouNdGAN in generating realistic scRNA-seq data. All plots correspond to 1000 real (experimental) held-out test cells and 1000 simulated cells. Each gene in the imposed GRN of GRouNdGAN is regulated by 15 TFs (constructed using GRNBoost2 from the experimental training set). Panels A and B depict the t-SNE plots of real (red) and simulated (blue) cells for PBMC-CTL and PBMC-All, respectively, while panels C and D also show their iLISI distributions. E) The ROC curve of a Random Forest classifier in distinguishing between simulated and real cells. F) The distribution of adjusted p-values corresponding to the TF perturbation study on the PBMC-CTL dataset. The p-values are obtained using two-sided Wilcoxon signed ranked tests and are adjusted for multiple hypotheses following the Benjamini-Hochberg procedure.

To quantitatively assess the resemblance of simulated and experimental datasets, we used five

metrics including Euclidean distance, Cosine distance, maximum mean discrepancy (MMD)[42],

mean integration local inverse Simpson's index (miLISI)[43], and the area under the receiver

operating characteristic curve (AUROC) of a random forests (RF) classifier trying to distinguish

simulated and experimental cells (Methods). As a reference ("control"), we also calculated these

metrics using two halves of the experimental test set. Table 1 shows the performance of

GRouNdGAN, control, and three state-of-the-art simulators as baselines for the PBMC-CTL

dataset (see Supplementary Table S4 for training set performance). We should note that to assess

data quality systematically and fairly, we only included methods that automatically generate

scRNA-seq data resembling experimental data, since the quality of data generated by methods

that rely on the input of the user for distribution matching (e.g., SERGIO or BoolODE) is user

dependent and may be subjective.

Table 1: Performance of different simulators in generating realistic scRNA-seq data using the
PBMC-CTL dataset. The metrics are calculated between a simulated dataset of 1000 cells and the
held-out test set of 1000 real cells (see Supplementary Table S4 for training set performance).
Each gene in the imposed GRN of GRouNdGAN is regulated by 15 TFs (constructed using
GRNBoost2 from the experimental training set). For the first three metrics, a value closer to zero
is preferred, for RF AUROC a value closer to 0.5 is preferred, and for miLISI a value closer to 2 is
preferred. Best performance values (excluding control) are in bold-face. The control shows the
value of the metrics comparing the two halves of the real dataset. For the first two metrics, the
values correspond to the distance of the mean centroids of the real and simulated cells.

Simulator	Cosine distance	Euclidean distance	MMD	RF AUROC	miLISI
GRouNdGAN	**0.00057**	**182**	**0.026**	**0.54**	**1.891**
scGAN[26]	0.00095	222	0.031	0.59	1.888
scDESIGN2[33]	0.00100	229	0.065	0.76	1.736
SPARsim[34]	0.00104	235	0.309	0.95	1.625
Control	0.00019	99	0.012	0.50	1.909

Next, we sought to determine whether GRouNdGAN can also generate samples corresponding

to different cell types. If cell type information of the experimental dataset is available a priori,

one can easily generate realistic samples of each cell type separately using GRouNdGAN (similar

to the PBMC-CTL analysis). However, we asked whether our model could generate realistic

samples *without* such prior knowledge, a much more challenging task. This is particularly useful

for scenarios in which such information is unavailable. In addition, not requiring cell type

information reduces the amount of user involvement (to annotate cell types) and improves the

usability of the model. We repeated the analysis above using the PBMC-All dataset, containing

eleven cell types. Although GRouNdGAN did not receive cell type/cluster information, we did not

observe any sign of mode collapse (Supplementary Figure S2). In fact, it was able to generate

cells from distinct clusters of this dataset (Figure 2B) with a test set miLISI score of 1.90.

GRouNdGAN outperformed all simulators that did not use any extra cell cluster labels or ratios

(Table 2). When compared to four simulators that utilized this side information, it was still the

top performing simulator based on MMD and RF AUROC and was the second best performing

model according to the Euclidean distance (only 6% higher than the best performing model) and

miLISI (only 0.5% lower than the best performing model) (Table 2).

Table 2: Performance of different simulators in generating realistic scRNA-seq data using the
PBMC-All dataset. Baseline models that enable utilization of cell cluster labels or ratios are run
with and without this information. The metrics are calculated between a simulated dataset of
1000 cells and the held-out test set of 1000 real cells. Each gene in the imposed GRN of
GRouNdGAN is regulated by 15 TFs (constructed using GRNBoost2 from the experimental training
set). For the first three metrics, a value closer to zero is preferred, for RF AUROC a value closer
to 0.5 is preferred, and for miLISI a value closer to 2 is preferred. Best performance values
(excluding control) are in bold-face. The control shows the value of the metrics comparing the
two halves of the real dataset. For the first two metrics, the values correspond to the distance of
the mean centroids of the real and simulated cells.

Simulator	Cell cluster labels/ratios provided as input	Cosine distance	Euclidean distance	MMD	RF AUROC	miLISI
GRouNdGAN	No	0.00028	168	**0.017**	**0.53**	1.90
cscGAN[26]	Yes	0.00025	242	0.030	0.56	**1.91**
cWGAN	Yes	0.00053	239	0.027	0.57	1.89
scGAN[26]	No	0.00081	300	0.035	0.58	1.90
scDESIGN2[33]	Yes	0.00032	181	0.046	0.86	1.81
scDESIGN2[33]	No	0.00057	256	0.124	0.91	1.53
SPARsim[34]	Yes	**0.00019**	**158**	0.287	0.96	1.66
SPARsim[34]	No	0.00035	245	0.307	0.96	1.39
Positive control	NA	0.00022	116	0.012	0.50	1.91

We repeated the analysis above using the BoneMarrow dataset, which includes continuous

transitional cell states and has a much smaller number of cells compared to the other two

datasets. GRouNdGAN outperformed all other simulators based on all five metrics

(Supplementary Table S4). These results show that GRouNdGAN is a stable simulator of scRNA-

seq data and even though it does not utilize extra information regarding the cell types present in

these heterogenous datasets, it automatically generates realistic simulated samples reflecting

different cell types without facing mode collapse. (See Supplementary File S1 and Table S5 for

further stability analysis and the effect of different GRN properties on the performance). Most

importantly, unlike the aforementioned simulators it incorporates of a causal GRN in the data.

GRouNdGAN imposes a causal GRN in the simulated data

Since one of the main motivations of this work was to impose causal GRNs in the simulated data,

we set out to systematically assess this ability. For this purpose, we performed *in-silico* TF

perturbation (knockout) experiments on the simulated cells using the PBMC-CTL dataset. Since

our goal was to assess whether the expression of the target genes of the TFs (in the imposed

GRN) change as a result of these perturbations, we ensured that the perturbations were

performed on the same batch of simulated cells, forming matched case/control experiments. We

achieved this by performing a forward pass after setting the expression of each TF to zero (one

at a time) in the causal controller output, while keeping all other parameters and TF expressions

unchanged. There was no change in the expression of genes that did not have an incoming edge

from the knocked-out TF (as expected), while the expression of the genes regulated by the

knocked-out TF changed. We performed two-sided Wilcoxon signed-rank tests comparing the

expression of a gene across all cells before and after the knockout of one of its regulating TFs.

Figure 2F shows the distribution of the adjusted p-values (Benjamini-Hochberg) for each TF-gene

edge in the GRN. Based on these analyses, in the majority (66.5%) of cases, the knockout of the

regulating TF of a gene significantly (adjusted p-value < 0.05) altered the expression of the gene,

showcasing that the GRN is indeed imposed in the expression profiles of simulated cells. Note

that since each gene is regulated by multiple TFs, we cannot expect that knockout of a single TF

in all cases result in a significant change in the expression of its target genes.

The imposed GRN can be reconstructed from the simulated data

To test whether the imposed GRN can be reconstructed from the generated data, we first applied

GRNBoost2[8] to the reference PBMC-CTL dataset and recorded the top ten TFs for each gene.

Then for each gene, we created two disjoint sets of five TFs based on the even/odd parity of TF

indices in the ranked list: TFs ranked as 1^{st}, 3^{rd}, 5^{th}, 7^{th}, and 9^{th} were connected to the gene and

were imposed by GRouNdGAN ("positive control GRN"), while the remaining five TFs were not

imposed ("negative control GRN"), resulting in two GRNs with identical densities and the same

number of TFs and target genes. When considering the positive and negative control GRNs as

ground truths (separately), the GRN reconstructed using GRNBoost2 from the experimental

scRNA-seq dataset resulted in comparable AUPRC (0.28 and 0.24, respectively, Supplementary

Table S6), reflecting that the two GRNs contain edges of comparable aggregated importance.

Next, we simulated data using GRouNdGAN by imposing only the positive control GRN, and used

GRNBoost2, PIDC[10] GENIE3[9], and PPCOR[44] to reconstruct the underlying GRN (Figure 3,

Supplementary Figure S4, and Supplementary Table S6). All GRN inference methods could

reconstruct the imposed edges with a much higher AUPRC compared to that of the original

reference dataset, while they did not assign high scores to the unimposed edges, resulting in

close to random AUPRC. Figure 3 shows the performance of GRNBoost2 when applied to the

experimental data, to data simulated by GRouNdGAN and to data simulated by scGAN. The

performance for scGAN (for both GRNs) is lower than the reference (experimental) dataset,

showcasing that it has not preserved the TF-gene relationships of the experimental dataset well.

The performance is relatively consistent between positive (Figures 3A and 3C) and negative

control (Figures 3B and 3D) GRNs using the reference and the scGAN-generated data; however,

the performance is much higher for the positive control GRN (compared to negative control GRN)

when using GRouNdGAN-simulated data. Similar patterns were observed when we repeated

these analyses using the BoneMarrow dataset (Supplementary Table S6 and Figure S5). These

results show that the imposed edges were accentuated by GRouNdGAN, while the unimposed

edges were disrupted and could not be found by GRN inference methods.

Figure 3: Performance of GRNBoost2 in recovering the imposed edges versus unimposed edges
(PBMC-CTL). Left column shows the AUPRC (A) and Precision at k (per gene) (C) when the imposed
edges (positive control GRN) were considered the ground truth. Right column shows the AUPRC
(B) and Precision at k (per gene) (D) when the unimposed edges (negative control GRN) were
considered the ground truth. Precision at k (per gene) refers to the precision when top k TFs for
each gene is used to form the reconstructed GRN.

Next, we asked whether GRNBoost2 can reconstruct the imposed GRN, if GRNs of different

densities are used to simulate data. Using simulated data in which each gene was regulated by

15, 10, 5, and 3 TFs, we observed that in all cases the GRN imposed by GRouNdGAN could be

inferred from the simulated data (Supplementary Table S6). Finally, we repeated the controlled

analysis above, swapping the role of positive and negative control GRNs. Similar to the results

observed in Figure 3, the imposed edges were inferred by GRNBoost2, while the unimposed

edges could not be accurately discovered (Supplementary Table S6).

These results show that 1) GRouNdGAN imposes the causal GRN in the simulated data, 2) the

GRN inference methods can identify the imposed edges, and 3) the TF-gene relationships that

originally existed in the real experimental data but were not imposed by GRouNdGAN are

disrupted during simulation. The last property is particularly desirable for benchmarking GRN

inference methods to ensure that the regulatory relationships present in the input reference

dataset (but not imposed) do not bias the simulated data, which could result in an inflated false

positive rate.

GRouNdGAN-simulated data preserves the trajectory of single cells and can be used for

pseudo-time inference

In addition to deciphering discrete cell types, scRNA-seq data is often used to determine

continuous cell transitions during biological processes such as differentiation, using trajectory

inference and pseudo-time ordering of cells[24,25,45-49]. We sought to determine whether the

simulated data generated by GRouNdGAN conforms to the transitional states and pseudo-time

ordering of the experimental scRNA-seq data. This is particularly important, since one of our goals

was to benchmark GRN inference methods, some of which utilize pseudo-time information[12-14,50-

54]. For this purpose, we used the BoneMarrow dataset corresponding to differentiation of

hematopoietic stem cells to different lineages.

We used Partition-based graph abstraction (PAGA)[24] for trajectory inference and analysis of the

experimental and GRouNdGAN-generated data. PAGA computes graph-like maps of data

manifolds faithful to the global topology of single-cell data, retaining both continuous and

discrete structures of the data. Supplementary Figure S6 shows the PAGA graphs, in which nodes

capture discrete states in the differentiation process and the edges signify transitions between

them. To compare the trajectories identified using the original BoneMarrow dataset with those

identified using simulated data, we used the gene expression of markers of cell types present in

this dataset (Supplementary Table S7)[24]. Figure 4 shows the gene expression patterns of two

marker genes for erythroid cells (*Gata1, Klf1*), neutrophils (*Mpo, Ctsg*), and basophils (*Mcpt8,

Prss34*) for PAGA trajectory graphs of both datasets (See Supplementary Figures S7-S13 for

marker genes of all cell types). The comparison reveals similar activation patterns between

corresponding regions (nodes) of PAGA graphs of the experimental and GRouNdGAN data,

revealing several trajectories (e.g., erythroid and neutrophil branches). Strikingly, even the

number of nodes activated in each figure scales similarly between the two datasets: for example,

in Figures 4E and 4F the two markers of basophils are consistently highly expressed in only one

node in each dataset.

Figure 4: PAGA graphs and cell type marker gene activation patterns in experimental and simulated BoneMarrow dataset. In each figure, nodes represent Louvain clusters (capturing discrete states), edges represent transitions between states, and edge weights indicate confidence in the presence of connections. Low-connectivity edges below a threshold of 0.01 were discarded. Left panels (A, C, E) show the PAGA graph computed on GRouNdGAN-generated cells, and right panels (B, D, F) show the PAGA graph for the original BoneMarrow dataset. Node colors represent normalized expression of marker genes for erythroid cells (A, B), neutrophils (C, D), and basophils (E, F).

Next, we annotated different cell types present in both datasets using these marker genes

(following PAGA's official tutorial) (Figures 5A and 5B). The GRouNdGAN's annotated graph

shows similar topological features to that of the experimental data and captures known biological

properties of hematopoiesis, which were also noted by Wolf, et al.[24] using the experimental

dataset (e.g., proximity between monocytes and neutrophils or association between

 megakaryocyte and erythroid progenitors). These observations show that the key characteristics

 of the experimental data are retained in GRouNdGAN's generated data.

Figure 5: Consistency in trajectories and pseudo-temporal orderings between data generated by
GRouNdGAN and the experimental BoneMarrow hematopoietic dataset. Panels A and B show

the cell type annotations of simulated and experimental data, respectively. The figures on the
left show the force-directed graphs (obtained using ForceAtlas2[55]) and the figures on the right
show the PAGA graphs. Panels C and D show the PAGA-initialized force-directed graphs with cells
colored by their inferred pseudo-time value. The following abbreviations are used: Stem for stem
cells, Ery for erythroid cells, Neu for neutrophils, Mo for monocytes, MK for Megakaryocytes, and
Baso for Basophils. Panels E and F display expression changes in the marker genes of erythrocyte
(*Gata2*, *Gata1*, *Klf1*, and *Hba-a2*), neutrophil (*Elane* and *Cebpe*), and monocyte (*Irf8*, *Csf1r*, and
Ctsg) branches for experimental (E) and simulated data (F). The distance refers to the geodesic
distance from a root cell (here a stem cell). A darker shade of grey shows higher expression.
Panels (G, H) show the performance of different GRN inference methods on data generated by
GRouNdGAN using the BoneMarrow dataset.
379

We used the diffusion pseudotime algorithm[45] (in scanpy[56]) to infer the progression of cells

through geodesic distance (Figures 5C and 5D). We noticed strong concordance when examining

pseudo-time values assigned to cell subgroups in the experimental and GRouNdGAN-generated

data. To track these patterns, we focused on marker gene expression changes along erythroid,

neutrophil, and monocyte trajectories (Supplementary Figures S7-S9), similar to the analysis

performed by Wolf, et al.[24]. In both datasets, the activation of neutrophils' marker, *Elane,* and

monocytes' marker, *Irf8,* were predominantly observed towards the later stages of their

trajectories (corresponding to larger pseudo-time values) (Figures 5E and 5F). Additionally, we

observed the activation of erythroid maturity marker genes *Gata2*, *Gata1*, *Klf1*, and *Hba-a2*

roughly in sequential order along the erythroid trajectory in both datasets (Figures 5E and 5F),

concordant with previous findings[24]. The striking similarity between the activation patterns of

these marker genes in both datasets and the preservation of their ordering highlights

GRouNdGAN's ability to capture dynamic transcriptional properties of single cell data, leading to

correct trajectory inference and pseudo-time ordering.

Benchmarking GRN inference methods using GRouNdGAN confirms prior insights obtained from curated experimental datasets

A recent GRN inference benchmarking study, BEELINE[28], found conflicting performance results when testing methods on curated biological datasets and synthetically generated ones: top two performing models on synthetic data where among the bottom three performing ones on curated data. We sought to re-investigate this pattern using data generated from GRouNdGAN with the BoneMarrow dataset and the positive and negative control GRNs explained earlier. We used seven GRN inference methods used by BEELINE including GRNBoost2[8], GENIE3[9], PIDC[10], PPCOR[44], LEAP[12], SCODE[13], and SINCERITIES[14], capturing a wide range of methods with a broad spread of performances reported on synthetic and curated data in the BEELINE study. We observed a striking resemblance between the performance pattern (order) of the methods on GRouNdGAN-simulated data and curated biological data from BEELINE (Figure 5G-5H and Supplementary Table S6 versus Figure 4 of BEELINE[28]): the only difference was that the order of LEAP[12] and SCODE[13] were swapped in our analysis. We also repeated this analysis using the PBMC-CTL dataset (Supplementary Table S6), obtaining similar patterns.

Overall, PIDC[10] outperformed all methods using both datasets, followed by GENIE3[9] and GRNBoost2[8]. LEAP[12], SCODE[13] and SINCERITIES[14] (which use pseudo-time and could only be applied to the BoneMarrow dataset) performed worse than other methods, a behavior that was also observed in the BEELINE study on curated biological data (but not on synthetic data). All methods performed close to random on unimposed negative control GRN edges. Overall, these results not only show that GRouNdGAN can be used for benchmarking GRN inference methods,

but also shows that the insights obtained from it matches those obtained from curated biological

datasets, the formation of which requires extensive amount of work and effort.

***In-silico* perturbation experiments using GRouNdGAN**

In many studies, one is interested to characterize the relationship between TFs' expression and

phenotypic labels (e.g., cell types). Differential expression (DE) analysis is a common approach to

identify TFs (or other genes) most associated with a specific cell type. However, to directly test

whether perturbing the expression of such candidate TFs change the expression of genes

representative of a cell type, perturbation experiments (e.g., TF knockout) are desired. Since

GRouNdGAN is a causal implicit generative model, it provides the capability to sample from

interventional distributions, thereby enabling *in-silico* perturbation experiments. GRouNdGAN

provides this functionality at inference time by enabling manipulation of TFs' expressions as the

outputs of the causal controller. This change is propagated along the GRN, impacting the

expression of genes regulated by the perturbed TF(s). By enabling a deterministic mode of

operation, GRouNdGAN allows for exact comparison of gene expressions before and after

perturbation while maintaining the invariance of other critical parameters such as input noises,

LSN layer per-cell scaling factor, and unperturbed TFs (Methods).

To test this functionality, we asked whether the knockout of top 3 TFs most differentially

expressed (Mann Whitney U test) between each cell type and the rest would result in less

simulated cells being generated in the vicinity of the cells of that type. If the answer is positive,

this implies that the perturbation in the TFs' expression has modified the gene expression profile

of generated cells so that they no longer resemble that particular cell type (confirming our

expectation). Figure 6A shows the UMAP embedding of the experimental dataset (miLISI = 1.94

when compared with simulated data) and Figure 6B shows the density plots of the experimental

and simulated data, revealing a high degree of resemblance. We focused on the changes in the

iLISI values of experimentally profiled cells of a specific type, when jointly mapped to the same

embedding space with simulated data, before and after knockout. In order for the changes in the

iLISI values to be observable, it was necessary to focus on cell types that occupy relatively distinct

regions of the embedding space; otherwise, the presence of other cell types in that region would

confound the results. We identified four cell types (CD14+ monocytes, CD19+ B cells, Dendritic

cells, CD56+ natural killer cells) that occupied relatively distinct regions of the embedding space

(Supplementary Figure S14). Figure 6C shows the distribution of iLISI values for each cell type

(only for real cells), calculated along with unperturbed simulated cells (blue) and with perturbed

simulated cells (orange). Figure 6D-6E show the iLISI values and the distribution of generated

cells after the knockout experiment for CD19+ B cells as an example (see Supplementary Figure

S15-S18 for other cell types). In all cases, the iLISI values significantly reduced after the knockout

experiment (Figure 6C, Supplementary Table S8), showcasing that after the knockout of top TFs

associated with a cell type, GrouNdGAN generated much fewer cells resembling that cell type

(even though it did not have the knowledge of the cell type annotations). Instead, the simulated

cells were dispersed into other cell types, yet they retained meaningful positions within the

overall dataset embedding space. In addition, the miLISI of the other cell types remained

relatively unchanged (Supplementary Table S8). This analysis shows that *in-silico* TF perturbation

experiments using GRouNdGAN produces results concordant with results directly obtained from

real biological data.

Figure 6: TF knockout experiments and their effect on cell type generation. A) The UMAP shows
the distribution of 2000 randomly selected cells from the experimental PBMC-All dataset. The
color shows the iLISI value of each cell (miLISI = 1.94) calculated from a UMAP embedding, jointly
obtained from the experimental cells and the same number of GRouNdGAN-generated cells. TFs
were omitted as features when generating UMAP plots. In the simulated data, each gene was
regulated by 15 TFs, identified using GRNBoost2. B) Each plot shows the density of cells in the

embedding space: the left plot (blue) corresponds to the real cells and the right plot (red) shows
the simulated cells. C) The boxplots show the distribution of iLISI values of real cells, calculated
along with unperturbed simulated cells (blue) and with perturbed simulated cells (orange). For
each cell type, top three most differentially expressed TFs were knocked out. The p-values
reported in this figure were calculated using one-sided Wilcoxon signed rank tests. D) The scatter
plot shows the iLISI values of CD19+ B cells calculated along with unperturbed simulated cells (x-
axis) and along with perturbed simulated cells (y-axis). The circles correspond to real cells and
their colors reflect the density of datapoints in that region. E) The UMAP embedding of real cells
(left), simulated cells after knockout of top TFs of CD19+ B cells (middle), and all together (right).
478

Discussion

GRouNdGAN is a causal implicit generative model designed to simulate realistic scRNA-seq

datasets based on a user-defined GRN and a reference dataset. By incorporating GRN

connections in its architecture and including auxiliary tasks, it imposes causal TF-gene

relationships in the gene expression profile of simulated cells. These causal relationships are

verifiable by *in-silico* knockout experiments and identifiable by GRN inference methods. Using

three experimental datasets, we demonstrated that GRouNdGAN achieves state-of-the-art

performance on various tasks including realistic scRNA-seq data generation, GRN inference

benchmarking, and performing *in-silico* knockout experiments. Even when applied to

heterogenous datasets, it generated realistic datasets (with no sign of mode collapse) without

utilizing information regarding cell types/clusters, achieving best or second-best performance

compared to models that used this information. We should note that it is trivially possible to use

cell type/cluster information with GRouNdGAN: one can simply provide subsets of the

experimental dataset corresponding to a cell type/cluster as a reference, one at a time. However,

the fact that this model does not require this information makes it easier to use and broadens its

applicability. We also showed that GRouNdGAN-generated data preserves complex cellular

dynamics and patterns present in the reference dataset such as lineage trajectories, pseudo-time

orderings, and patterns of cell type markers' activation.

GRouNdGAN imposes user-defined causal TF-gene regulatory interactions, while excluding

regulatory interactions that are present in the reference dataset, but not in the input GRN. This

property makes GRouNdGAN-simulated datasets ideal for benchmarking GRN inference

algorithms with the user-specified GRN serving as the ground truth. Building on this, we

benchmarked seven popular GRN inference algorithms and showed that GRouNdGAN

benchmarking results highly coincided with results reported by BEELINE[28] on experimental

datasets. This highlights GRouNdGAN's ability to bridge the gap between GRN benchmarking

results obtained on simulated and real datasets without requiring excessive user manipulation.

Since GRouNdGAN generates data based on a structural causal model, it can be used to sample

synthetic cells from both observational and interventional distributions. Using this property, we

conducted *in-silico* perturbation experiments by knocking out key regulating TFs in various cell

types and observed that the targeted cell-states were suppressed in the generated dataset.

GRouNdGAN maintains key advantages over existing tools that incorporate GRNs in scRNA-seq

data simulation such as SERGIO and BoolODE. First, during training, GRouNdGAN's model

parameters are optimized to minimize any mismatch between real and simulated data

distributions. This enables it to replicate scRNA-seq data characteristics, such as technical and

biological noise, without the need for any user-intervention or further post-processing. In

contrast, SERGIO simulates data by first generating a "clean" dataset based on SDEs. Then, the

user would iteratively fine-tune technical noise parameters, such as dropout rate, library size,

and outlier genes, until the simulated and reference datasets are statistically matched. This data-

matching procedure puts extra burden on the end-user and might lead the user to overly rely on

fine-tuning technical noise parameters, instead of SDE parameters. Over relying on added

technical noise to achieve data matching can potentially corrupt the data, rendering the

underlying regulatory patterns unobservable in the final simulated dataset. This might explain

the near-random GRN inference performance reported by SERGIO on their noisy datasets[4].

Another advantage of GRouNdGAN is gene identity preservation. GRouNdGAN is trained such

that each of its generated genes or TFs mimic the expression patterns of a corresponding gene

or TF in the reference dataset. In contrast, BoolODE and SERGIO simulate pseudo-genes whose

identities cannot be readily mapped to their counterparts in the reference dataset. Gene identity

preservation can be attained in SERGIO or BoolODE by fine-tuning the SDE model parameters

until the expression patterns of a given generated gene aligns with a corresponding gene in the

reference dataset. This, however, adds further burden to the end-user. Finally, GRouNdGAN

learns complex non-linear co-regulatory patterns from the data, instead of relying on simplifying

assumptions or user input. In contrast, SERGIO assumes that the combined effect of multiple

regulatory TFs is simply the sum of their individual effects. Similarly, BoolODE requires the user

to provide a truth table specifying combinatory TF co-regulation rules for each target gene. In

contrast, GRouNdGAN's neural network-based generator enables it to implicitly learn complex

non-linear co-regulatory patterns that may represent co-expression, co-inhibition, or co-

activation of individual genes. This is achieved during the training of GRouNdGAN without the

need for user intervention.

Several key considerations need to be taken into account when using GRouNdGAN. First, our

analyses showed that the architectural and hyperparameter choices of the presented model

result in good performance across different datasets. We performed hyperparameter fine-tuning

on one dataset and used the same set of values for all three datasets and for different choices of

GRNs, obtaining state-of-the-art performance. However, when trained on a completely new

dataset, it is still advisable to test different choices of the hyperparameters using a validation set

to obtain the best performance. Second, the default architecture of the model includes LSN layers

and, as such, the model generates library-size normalized gene expression values. Our ablation

study (Supplementary File S1) showed that without the LSN layer, GRouNdGAN can still generate

realistic profiles; however, including this layer improves how well the GRN is imposed and

stabilizes the training procedure. Third, an important consideration for any causal inference

problem is that given an observational dataset, its underlying causal graph is not unique. When

benchmarking GRN inference methods, this problem exists regardless of how the ground truth

GRN is obtained (even using knockout/knockdown experiments), and a GRN inference algorithm

may find a plausible causal GRN, yet not the one that actually generated the data. Despite this,

our analysis using the positive and negative control GRNs showed that GRN inference methods

could detect the imposed edges while ignoring others that were unimposed but whose patterns

originally existed in the reference dataset. Based on this observation, we posit that the imposed

GRN by GRouNdGAN, while not the only causal GRN capable of generating the simulated dataset,

is the most probable one. However, verifying this requires theoretical analyses that are well

beyond the scope of this study. Finally, although GRouNdGAN can generate data with any GRN,

the quality of the data deteriorates if the imposed TF-gene relationships are significantly different

from those observable in the reference dataset. The reason is that in such a scenario, generating

realistic simulated datapoints and imposing the GRN act as contradictory requirements. This is a

fundamental problem that is not unique to GRouNdGAN and is applicable to any simulator with

these two requirements. On the other hand, simulators that do not try to impose a causal graph

(e.g., scGAN) can focus on generating realistic scRNA-seq samples, even at the expense of

disrupting some of the interactions present in the reference dataset (as we observed in Figure

3 with scGAN). As a result, for GRN inference method benchmarking, we recommend first finding

a set of regulatory edges from the experimental dataset (e.g., using GRNBoost2) and imposing

those in the simulated data. This ensures that the imposed edges are encoded in the simulated

data, the unimposed (or undetected) edges are disrupted (as shown in our analyses), and the

simulated dataset resembles the reference dataset.

The existing GRouNdGAN model only allows imposing a GRN in the form of a bipartite graph and

does not support regulation of TFs by other TFs, an assumption that we plan to relax with the

future versions of the model. Moreover, we intend to augment the model's architecture in the

future to enable imposing a causal graph with three layers of nodes capturing TF-gene-phenotype

relationships. This is particularly useful for development and evaluation of phenotype-relevant

GRNs, a concept that we have introduced in the past[11]. Additionally, a conditional version of

GRouNdGAN can be developed, allowing the user to generate cells of specific cell-type or on a

specific stage along a lineage trajectory (i.e., by conditioning on pseudo-time). Finally, by

incorporating DAG structural learning[57], we intend to enable GRouNdGAN to infer a GRN while

simultaneously learning to mimic the reference scRNA-seq dataset.

Conclusion

Overall, GRouNdGAN is a powerful and user-friendly tool that enables researchers to simulate

realistic scRNA-seq datasets, benchmark GRN inference algorithms, and perform *in-silico*

perturbation experiments, with many new features that will be added in the future.

Methods

Datasets and preprocessing

We downloaded the human peripheral blood mononuclear cell (PBMC Donor A) dataset

containing the single-cell gene expression profiles of 68579 PBMCs represented by UMI counts

from the 10x Genomics (https://support.10xgenomics.com/single-cell-gene-

expression/datasets/1.1.0/fresh_68k_pbmc_donor_a). This dataset contains a large number of

well-annotated cells and has been used by other models to generate synthetic scRNA-seq

samples[26]. We also downloaded the scRNA-seq profile of 2730 cells corresponding to

differentiation of hematopoietic stem cells to different lineages from mouse bone marrow[20]

("BoneMarrow" dataset) from Gene Expression Omnibus (accession number: GSE72857)

We followed the pre-processing steps of scGAN and cscGAN[26] using scanpy version 1.8.2[56]. In

each dataset, cells with nonzero counts in less than ten genes were removed. Similarly, genes

that only had nonzero counts in less than three cells were discarded. Next, library-size

normalization was performed on the counts per cell with a library size equal to 20,000 in order

to be consistent with previous studies [26]. Next, top 1000 highly variable genes were selected using

the dispersion-based method described by Satija et al.[58].

GRouNdGAN's model architecture

GRouNdGAN consists of 5 components, each implemented using separately parameterized

neural networks: a causal controller, target generators, a critic, a labeler, and an anti-labeler

(Figure 1B).

Causal controller: The role of causal controller is to generate the expression of TFs that causally

control the expression of their target genes based on a user-defined gene regulatory network

(Figure 1B). To achieve this, it is first pre-trained (Figure 1A) as the generator of a Wasserstein

GAN (WGAN). GANs are a class of deep learning models that can learn to simulate non-parametric

distributions[59]. They typically involve simultaneously training a generative model (called the

"generator") that produces new samples from noise, and its adversary, a discriminative model

that tries to distinguish between real and generated samples (called the "discriminator"). The

generator's goal is to generate samples so realistic that the discriminator cannot determine

whether it is real or simulated (an accuracy value close to 0.5). Through adversarial training, the

generator and discriminator receive feedback, allowing them to co-evolve in a symbiotic manner.

The main difference between a WGAN and a traditional GAN is that in the former, a Wasserstein

distance is used to quantify the similarity between the probability distribution of the real data

and the generator's produced data (instead of Kullback–Leibler or Jensen–Shannon divergences).

Wasserstein distance has been shown to stabilize the training of WGAN without causing mode

collapse[40]. The detailed formulation of the Wasserstein distance used as the loss function in this

study is provided in Supplementary File S1. In addition, instead of a discriminator, WGAN uses a

"critic" that estimates the Wasserstein distance between real and generated data distributions.

In our model, we added a gradient penalty term for the critic (proposed by Gulrajani et al.[60] as

an alternative to weight clipping used in the original WGAN) in order to overcome

vanishing/exploding gradients and capacity underuse issues.

In the pretraining step, we trained a WGAN with a generator (containing an input layer, three

hidden layers, and an output layer), a library-size normalization (LSN) layer[26], and a critic

(containing an input layer, three hidden layers, and an output node). A noise vector of length

128, with independent and identically distributed elements following a standard Gaussian

distribution, was used as the input to the generator. The output of the generator was then fed

into the LSN layer to generate the gene and TF expression values. The details of hyperparameters

and architectural choices of this WGAN are provided in Supplementary Table S1. Although we

were only interested in generating expression of TFs using the generator of this WGAN (in the

second step of pipeline), the model was trained using all genes and TFs to properly enforce the

library-size normalization. Once trained, we discarded the critic and the LSN layer, froze the

weights of the generator and used it as the "causal controller"[39] to generate expression of TFs

(Figure 1B).

Target generators: The role of target generators is to generate the expression of genes causally

regulated by TFs based on the topology of a GRN. Consider a target gene Gj regulated by a set of

TFs: $\{TF_1, TF_2, \dots, TF_n\}$. Under the causal sufficiency assumption and as a result of the manner

by which TFs' expressions are generated from independent noise variables, we can write $E_{Gj} =$

$f_{Gj}\left(E_{TF1}, E_{TF2}, \dots, E_{TFn}, N_{Gj}\right)$ and $E_{TFi} = f_{TFi}(N_{TFi})$ for $i = 1, 2, \dots, n$, where E represents

expression, N represents a noise variable, and f represents a function (to be approximated using

neural networks). All noise variables are jointly independent. Following the theoretical and

empirical results of CausalGAN[39], we can use feedforward neural networks to represent functions

f by making the generator inherit its neural network connections from the causal GRN. To

achieve this, we generate each gene in the GRN by a separate generator such that target gene

generators do not share any neural connections (Figure 1B).

As input, the generator of each gene accepts a vector formed by concatenating a noise variable

and a vector of non-library size normalized TF expressions from the causal controller,

corresponding to the TFs that regulate the gene in the imposed GRN (i.e., its parents in the graph).

The expression values of TFs and the generated values of target genes are arranged into a vector,

which is passed to an LSN layer for normalization. We used target generators with three hidden

layers of equal width. The width of the hidden layers of a generator is dynamically set as twice

the number of its regulators (the noise variable and the set of regulating TFs). If the imposed GRN

is relatively dense and contains more than 5000 edges, we set the depth to 2 and the width

multiplier to 1 to be able to train on a single GPU. The details of hyperparameters and

architectural choices are provided in Supplementary Table S2.

In practice, generating each target gene's expression using separate neural networks introduces

excess overhead. This is because in every forward pass, all target genes' expressions must be first

generated before collectively being sent into the LSN layer. As a result, instead of parallelizing

the generation of each target gene's expression (which due to the bottleneck above does not

provide a significant computational benefit), we implemented target generators using a single

large sparse network. This allows us to reduce the overhead and the training time to train the

model on a single GPU, and to benefit from GPU's large matrix multiplication. We mask weights

and gradients to follow the causal graph, while keeping the generation of genes independent

from each other. From a logical standpoint, our implementation has the same architecture

described earlier, but is significantly more computationally efficient.

Critic: Similar to a traditional WGAN, the objective of GRouNdGAN's critic (Figure 1B) is to

estimate the Wasserstein distance between real and generated data distributions. We used the

same critic architecture as the WGAN trained in the first stage.

Labeler and anti-labeler: Although the main role of the target generators is to produce realistic

cells to confuse the critic, it is crucial that they rely on the TFs' expression (in addition to noise)

in doing so. One potential risk is that the target generators disregard the expression of TFs and

solely rely on the noise variables. This is particularly probable when the imposed GRN does not

conform to the underlying gene expression programs of real cells in the reference dataset; in

such a scenario, and to make realistically looking simulated cells, it is more convenient for a

WGAN to simply ignore the strict constraints of the GRN and solely rely on noise.

To overcome this issue, we used auxiliary tasks and neural networks known as "labeler" and

"anti-labeler"[39]. The task of these two networks is to estimate the causal controller's TF

expressions (here called labels) from the target genes' expressions alone (by minimizing the

squared L2 norm between each element's TF estimates and their true value). This resembles the

idea behind an autoencoder and ensures that the model will not disregard the expression of TFs

in generating the expression of their target genes. The anti-labeler is trained solely based on the

outputs of the target generators, while the labeler utilizes both the outputs of target generators

and the expression of real cells (Figure 1B). They are both implemented as fully connected

networks with a width of 2000 and a depth of 3 and optimized using the AMSGrad[61] algorithm.

Each layer, except the last one, utilizes a ReLU activation function and batch normalization. In

addition to WGAN losses, we add labeler and anti-labeler losses to the generator to minimize

both. This is different from the approach used in CausalGAN, where the anti-labeler's loss is

maximized in the early training stages to ensure that the generator doesn't fall into label-

conditioned mode collapse. In GRouNdGAN, the causal controller is pretrained and generates

continuous labels (TFs expression) and does not face a similar issue. As a result, we instead

minimized the loss of the anti-labeler from the beginning and as such the labeler and anti-labeler

both act as auxiliary tasks to ensure the generated gene expression values take advantage of TFs

expression.

Training procedure and hyperparameter tuning

We follow a two-step training procedure comprising of training two separate WGANs (Figure 1)

to train GRouNdGAN. The generators and critics in both GANs are implemented as fully

connected neural networks with rectified linear unit (ReLU) activation functions in each layer,

except for the last layer of the critic. The weights were initialized using He initialization[62] for layers

containing ReLU activation and Xavier initialization[63] for other layers (containing linear

activations). We used Batch Normalization[64] to normalize layer inputs for each training

minibatch, except for the critic. This is since using it in the critic invalidates the gradient penalty's

objective, as it penalizes the norm of the critic's gradient with respect to the entire batch rather

than to inputs independently. An LSN layer[26] was used in both WGANs (Figure 1A and 1B) to scale

counts in each simulated cell to make it consistent with the library size of input reference dataset.

This normalization results in a dramatic decrease in convergence time and smooths training by

mitigating the inherent heterogeneity of scRNA-seq data.

GRouNdGAN solves a min-max game between the generator (f_g) and the critic (f_c), with the

following objective function:

$$\min_{f_g}\max_{\|f_c\|_L\leq1}\mathbb{E}_{x\sim\mathbb{P}_r}f_c(x)-\mathbb{E}_{x\sim f_g(\mathbb{P}_{noise})}f_c(x). \tag{1}$$

We alternated between minimizing the generator loss for one iteration and maximizing the

generator loss for five iterations. We employed the AMSGrad[61] optimizer with the weight decay

parameters $\beta_1 = 0.5$, $\beta_2 = 0.9$ and employed an exponentially decaying learning rate for the

optimizer of both the critic and generator.

The hyperparameters were tuned using a validation set consisting of 1000 cells from the PBMC-

CTL dataset (Supplementary Tables S1-S2) based on the Euclidean distance and the RF AUROC

score, which were consistently in accord. The same hyperparameters were used for all other

analyses and the other two datasets (PBMC-All and BoneMarrow).

Causal GRN preparation

This section describes the creation of the causal graph inputted to GRouNdGAN used to impose

a causal structure on the model. GRouNdGAN accepts a GRN in the form of a bipartite directed

acyclic graph (DAG) as input, representing the relationship between TFs and their target genes.

In this study, we created the causal graph using the 1000 most highly variable genes identified in

the preprocessing step. First, the set of TFs among the highly variable genes were identified based

on the AnimalTFDB3.0 database[65] and a GRN was inferred using GRNBoost2[8] (with the list of TFs

provided). Supplementary Table S5 shows the characteristics of the different GRNs used in this

study.

Evaluation of the resemblance of real and simulated cells

We evaluated all models using held-out test sets containing randomly selected cells from each

reference dataset (1000 cells from PBMC-CTL and PBMC-All and 500 cells from BoneMarrow). To

quantify the similarity between real and generated cells, we employed various metrics. For each

cell represented as a datapoint in a low dimensional embedding (e.g., t-SNE or UMAP), the

integration local inverse Simpson's Index (iLISI)[43] captures the effective number of datatypes (real

or simulated) to which datapoints of its local neighborhood belong based on weights from a

Gaussian kernel-based distributions of neighborhoods. The miLISI is the mean of all these scores

and in our study ranges between 1 (poor mixing of real and simulated cells) and 2 (perfect mixing

of real and simulated cells). Additionally, we calculated the cosine and Euclidean distances of the

centroids of real cells and simulated cells, where the centroid was obtained by calculating the

mean along the gene axis (across all simulated or real cells).

To estimate the proximity of high-dimensional distributions of real and simulated cells without

creating centroids, we used the maximum mean discrepancy (MMD)[42]. Given two probability

distributions p and q and a set of independently and identically distributed (i.i.d.) samples from

them, denoted by X and Y, MMD with respect to a function class $\mathcal{F}$ is defined as

$$\text{MMD}[\mathcal{F}, X, Y] := \sup_{f \in \mathcal{F}} \left(\mathbb{E}_x[f(x)] - \mathbb{E}_y[f(y)] \right), \tag{2}$$

768   where sup refers to supremum and $\mathbb{E}$ denotes expectation. When the MMD function class $\mathcal{F}$ is a

769   unit ball in a reproducing kernel Hilbert space (RKHS) $\mathcal{H}$ with kernel k, the population MMD takes

770   a zero value if and only if $p = q$ and a positive unique value if $p \neq q$. The squared MMD can be

771   written as the distance of mean embeddings μ_p, μ_q of distributions p and q, which can be

772   expressed in terms of kernel functions:

$$MMD^2[\mathcal{F}, p, q] = \left\| \mu_p - \mu_q \right\|_{\mathcal{H}}^2 \tag{3}$$

$$= \mathbb{E}_{x,x'}[k(x, x')] - 2\mathbb{E}_{x,y}[k(x, y)] + \mathbb{E}_{y,y'}[k(y, y')].$$

775   Following existing implementations of MMD in the single-cell domain[26,66], we chose a kernel that

776   is the sum of three Gaussian kernels to increase sensitivity of the kernel to a wider range:

$$k(x, y) = \sum_i \left(\frac{\|x - y\|^2}{\sigma_i^2} \right), i = 1,2,3, \tag{4}$$

where σ_i denote standard deviations and were chosen to be the median of the average distance

between a point to its 25 nearest neighbors divided by factors of 0.5, 1, and 2 in the three kernels,

respectively.

We also used a random forests (RF) classifier and used its area under the receiver operating

characteristic (AUROC) curve to determine whether the real and simulated cells can be

distinguished from each other. Consistent with previous studies[26,67], we first performed a

dimensionality reduction using principal component analysis (PCA) and used the top 50 PCs of

each cell as the input features to the RF model, which improves the computational efficiency of

this analysis. The RF model was composed of 1000 trees and the Gini impurity was used to

measure the quality of a split.

Baseline simulator models

We compared the performance of GRouNdGAN to scDESIGN2[33], SPARsim[34], and three GAN-

based methods: scGAN[26], cscGAN with projection-based conditioning[26], and a conditional WGAN

(cWGAN). The cWGAN method conditions by concatenation following the cGAN framework[68].

More specifically, it concatenates a one-hot encoded vector (representing the cluster number or

cell type) to the noise vector input to the generator and cells forwarded to the discriminator. We

did not train the cWGAN or cscGAN on the PBMC-CTL dataset, since it contains only one cell type.

For the PBMC-All and the BoneMarrow dataset, we trained all models above. Additionally, we

simulated data using scDESIGN2 and SPARsim with and without cell cluster information, as they

allow providing such side information in their training.

801 To train models that utilized cell cluster information, we performed Louvain clustering and

802 provided the cluster information and ratio of cells per cluster during training. Clustering was done

803 by following the cell ranger pipeline[41], based on the raw unprocessed dataset (and independent

804 of the pre-processing steps described earlier for training simulators). First, genes with no UMI

805 count in any of the cells were removed. Then the gene expression profile of each cell was

806 normalized by the total UMI of all (remaining) genes, and highly variable genes were identified.

807 The gene expression profile of each cell was then re-normalized by the total UMI of retained

808 highly variable genes, and each gene vector (representing its expression across different cells)

809 was z-score normalized. Given the normalized gene expression matrix above, we found top 50

810 principal components (PCs) using PCA analysis. These PCs were then used to compute a

811 neighborhood graph with a local neighborhood size of 15, which was used in Louvain clustering.

812 We ran the Louvain algorithm with a resolution of 0.15.

814 For SPARSim, we set all sample library sizes to 20000 and estimated gene expression level

815 intensities and simulation parameters by providing it with both raw and normalized count

816 matrices. When cell cluster information was provided, distinct SPARSim simulation parameters

817 were estimated per cell for each cluster. scDESIGN2 accepts input matrices where entries are

818 integer count values; we thus performed rounding on the expression matrix before fitting

819 scDESIGN2. With cluster information provided, a scDESIGN2 model was fit separately for cells of

820 each cluster, and similar to conditional GANs, the ratio of cells per cluster was provided to the

821 method.

In-silico perturbation experiments using GroundGAN

To perform perturbation experiments using GroundGAN, we put the trained model in a deterministic mode of operation. This is necessary to ensure that the perturbation experiments are performed on the same batch (i.e., replicate) of generated cells to form matched case/control experiments. To do this, we performed a forward pass through the generator and then saved the input noise to the causal controller, the input noise to the target generators, the TF expression values generated by the causal controller, and the per-cell scaling factor of the LSN layer. Subsequent passes through the generators used the saved parameters so that ensuing runs always output the same batch of cells (instead of generating new unmatched cells).

Trajectory inference and pseudo-time analysis

Following official PAGA tutorial for the BoneMarrow dataset (https://github.com/scverse/scanpy-tutorials/blob/master/paga-paul15.ipynb), we used (Partition-based graph abstraction) PAGA[24] for trajectory inference and analysis. We built force-directed graphs[69] (with ForceAtlas2[55]) using the top 20 principal components of the data (using principal component analysis or PCA) and a neighborhood graph of observations computed using UMAP (to estimate connectivities). We next denoised the graph by representing it in the diffusion map space and computed distances and neighbors as before using this new representation. After denoising, we then ran the Louvain clustering algorithm with a resolution of 0.6. Finally, we ran the PAGA algorithm on the identified clusters and used the obtained graph to initialize and rebuild the force-directed graph.

GRN inference methods

In our GRN benchmarking analysis, we focused on seven GRN inference algorithms: GENIE3[9],

GRNBoost2[8], PPCOR[44], PIDC[10], LEAP[12], SCODE[13] and SINCERITIES[14], which were used in the

BEELINE study[28]. Of these methods, LEAP requires pseudo-time ordering of cells, while SCODE

and SINCERITIES require both pseudo-time ordering and pseudo-time values. Since not all

algorithms inferred the edge directionality or its sign (activatory or inhibitory nature), we did not

consider these factors in our analysis to be consistent among different models. We ran these

models as docker containers using the docker images provided by BEELINE's GitHub

(https://github.com/Murali-group/Beeline)[28] with the default parameters used in BEELINE. To

benchmark algorithms requiring pseudo-time ordering of cells, we computed the pseudo-times

of GRouNdGAN-simulated data (based on the BoneMarrow dataset) using PAGA[24] and diffusion

pseudotime[45], following the methodology described earlier. In the GRN inference benchmark

analysis, we did not provide the list of TFs to GRNBoost2 to make it consistent with other GRN

inference methods.

Competing interests

861   The authors have no conflict of interest to declare.

Funding

864   This work was supported by grants from Natural Sciences and Engineering Research Council of

865   Canada (NSERC) [RGPIN-2019-04460] (AE), Government of Canada's New Frontiers in Research

Data availability

872 The PMBC dataset is available from the 10x genomics repository (corresponding to healthy donor

873 A)   from   the   link   https://support.10xgenomics.com/single-cell-gene-

874 expression/datasets/1.1.0/fresh_68k_pbmc_donor_a?. The BoneMarrow dataset is available in

875 the Gene Expression Omnibus repository under accession number GSE72857.

Code availability

878 Our implementation and evaluation of GRouNdGAN in Python 3.9.6 using the PyTorch

879 framework[70] along with instructions is freely available under the GNU Affero General Public

880 License v3.0 on GitHub (https://github.com/Emad-COMBINE-lab/GRouNdGAN). The repository also

881 contains our PyTorch implementation of scGAN, projection-based conditioning cscGAN[26] and a

882 variation of cscGAN that uses conditioning by concatenation (cWGAN).

References
1   Lee, T. I. *et al.* Transcriptional regulatory networks in Saccharomyces cerevisiae. *science* **298**,
799-804 (2002).
2   Che, D. *et al.* Dynamic and modular gene regulatory networks drive the development of
gametogenesis. *Briefings in bioinformatics* **18**, 712-721 (2017).
3   Olson, E. N. Gene regulatory networks in the evolution and development of the heart. *Science*
313, 1922-1927 (2006).

4   Dibaeinia, P. & Sinha, S. SERGIO: a single-cell expression simulator guided by gene regulatory
892   networks. *Cell systems* **11**, 252-271. e211 (2020).

893   5   Yang, Y. *et al.* Gene knockout inference with variational graph autoencoder learning single-cell
894   gene regulatory networks. *Nucleic Acids Research*, gkad450 (2023).

895   6   Madhamshettiwar, P. B., Maetschke, S. R., Davis, M. J., Reverter, A. & Ragan, M. A. Gene
896   regulatory network inference: evaluation and application to ovarian cancer allows the
897   prioritization of drug targets. *Genome medicine* **4**, 1-16 (2012).

898   7   Manuel, A. M., Dai, Y., Jia, P., Freeman, L. A. & Zhao, Z. A gene regulatory network approach
899   harmonizes genetic and epigenetic signals and reveals repurposable drug candidates for
900   multiple sclerosis. *Human Molecular Genetics* **32**, 998-1009 (2023).

901   8   Moerman, T. *et al.* GRNBoost2 and Arboreto: efficient and scalable inference of gene regulatory
902   networks. *Bioinformatics* **35**, 2159-2161 (2019).

903   9   Huynh-Thu, V. A., Irrthum, A., Wehenkel, L. & Geurts, P. Inferring regulatory networks from
904   expression data using tree-based methods. *PloS one* **5**, e12776 (2010).

905   10   Chan, T. E., Stumpf, M. P. & Babtie, A. C. Gene regulatory network inference from single-cell
906   data using multivariate information measures. *Cell systems* **5**, 251-267. e253 (2017).

907   11   Emad, A. & Sinha, S. Inference of phenotype-relevant transcriptional regulatory networks
908   elucidates cancer type-specific regulatory mechanisms in a pan-cancer study. *NPJ systems
909   biology and applications* **7**, 9 (2021).

910   12   Specht, A. T. & Li, J. LEAP: constructing gene co-expression networks for single-cell RNA-
911   sequencing data using pseudotime ordering. *Bioinformatics* **33**, 764-766 (2017).

912   13   Matsumoto, H. *et al.* SCODE: an efficient regulatory network inference algorithm from single-cell
913   RNA-Seq during differentiation. *Bioinformatics* **33**, 2314-2321 (2017).

914   14   Papili Gao, N., Ud-Dean, S. M., Gandrillon, O. & Gunawan, R. SINCERITIES: inferring gene
915   regulatory networks from time-stamped single cell transcriptional expression profiles.
916   *Bioinformatics* **34**, 258-266 (2018).

917   15   Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nature methods*
918   **14**, 1083-1086 (2017).

919   16   Bravo González-Blas, C. *et al.* SCENIC+: single-cell multiomic inference of enhancers and gene
920   regulatory networks. *Nature Methods*, 1-13 (2023).

921   17   Kartha, V. K. *et al.* Functional inference of gene regulation using single-cell multi-omics. *Cell
922   genomics* **2** (2022).

923   18   Badia-i-Mompel, P. *et al.* Gene regulatory network inference in the era of single-cell multi-omics.
924   *Nature Reviews Genetics*, 1-16 (2023).

925   19   Shalek, A. K. *et al.* Single-cell RNA-seq reveals dynamic paracrine control of cellular variation.
926   *Nature* **510**, 363-369 (2014).

927   20   Paul, F. *et al.* Transcriptional heterogeneity and lineage commitment in myeloid progenitors. *Cell*
928   **163**, 1663-1677 (2015).

929   21   Avey, D. *et al.* Single-cell RNA-seq uncovers a robust transcriptional response to morphine by
930   glia. *Cell reports* **24**, 3619-3629. e3614 (2018).

931   22   Skinnider, M. A. *et al.* Cell type prioritization in single-cell data. *Nature biotechnology* **39**, 30-34
932   (2021).

933   23   Abdelaal, T. *et al.* A comparison of automatic cell identification methods for single-cell RNA
934   sequencing data. *Genome biology* **20**, 1-19 (2019).

935   24   Wolf, F. A. *et al.* PAGA: graph abstraction reconciles clustering with trajectory inference through
936   a topology preserving map of single cells. *Genome biology* **20**, 1-9 (2019).

937   25   Saelens, W., Cannoodt, R., Todorov, H. & Saeys, Y. A comparison of single-cell trajectory
938   inference methods. *Nature biotechnology* **37**, 547-554 (2019).

26 Marouf, M. *et al.* Realistic in silico generation and augmentation of single-cell RNA-seq data
using generative adversarial networks. *Nature communications* **11**, 1-12 (2020).
27 Ma, Q. & Xu, D. Deep learning shapes single-cell data analysis. *Nature Reviews Molecular Cell*
Biology **23**, 303-304 (2022).
28 Pratapa, A., Jalihal, A. P., Law, J. N., Bharadwaj, A. & Murali, T. Benchmarking algorithms for
gene regulatory network inference from single-cell transcriptomic data. *Nature methods* **17**,
147-154 (2020).
29 Emmert-Streib, F., Dehmer, M. & Haibe-Kains, B. Gene regulatory networks and their
applications: understanding biological and medical problems in terms of networks. *Frontiers in*
cell and developmental biology **2**, 38 (2014).
30 Kolmykov, S. *et al.* GTRD: an integrated view of transcription regulation. *Nucleic acids research*
49, D104-D111 (2021).
31 Xu, H. *et al.* ESCAPE: database for integrating high-content published data collected from human
and mouse embryonic stem cells. *Database* **2013**, bat045 (2013).
32 Kanehisa, M. & Goto, S. KEGG: kyoto encyclopedia of genes and genomes. *Nucleic acids research*
28, 27-30 (2000).
33 Sun, T., Song, D., Li, W. V. & Li, J. J. scDesign2: a transparent simulator that generates high-
fidelity single-cell gene expression count data with gene correlations captured. *Genome biology*
22, 1-37 (2021).
34 Baruzzo, G., Patuzzi, I. & Di Camillo, B. SPARSim single cell: a count data simulator for scRNA-seq
data. *Bioinformatics* **36**, 1468-1475 (2020).
35 Schaffter, T., Marbach, D. & Floreano, D. GeneNetWeaver: in silico benchmark generation and
performance profiling of network inference methods. *Bioinformatics* **27**, 2263-2270 (2011).
36 Marbach, D. *et al.* Revealing strengths and weaknesses of methods for gene network inference.
Proceedings of the national academy of sciences **107**, 6286-6291 (2010).
37 Marbach, D. *et al.* Wisdom of crowds for robust gene network inference. *Nature methods* **9**,
796-804 (2012).
38 Chen, S. & Mar, J. C. Evaluating methods of inferring gene regulatory networks highlights their
lack of performance for single cell gene expression data. *BMC bioinformatics* **19**, 1-21 (2018).
39 Kocaoglu, M., Snyder, C., Dimakis, A. G. & Vishwanath, S. Causalgan: Learning causal implicit
generative models with adversarial training. *arXiv preprint arXiv:1709.02023* (2017).
40 Arjovsky, M., Chintala, S. & Bottou, L. in *International conference on machine learning.* 214-223
(PMLR).
41 Zheng, G. X. *et al.* Massively parallel digital transcriptional profiling of single cells. *Nature*
communications **8**, 1-12 (2017).
42 Gretton, A., Borgwardt, K. M., Rasch, M. J., Schölkopf, B. & Smola, A. A kernel two-sample test.
The Journal of Machine Learning Research **13**, 723-773 (2012).
43 Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data with Harmony.
Nature methods **16**, 1289-1296 (2019).
44 Kim, S. ppcor: an R package for a fast calculation to semi-partial correlation coefficients.
Communications for statistical applications and methods **22**, 665 (2015).
45 Haghverdi, L., Büttner, M., Wolf, F. A., Buettner, F. & Theis, F. J. Diffusion pseudotime robustly
reconstructs lineage branching. *Nature methods* **13**, 845-848 (2016).
46 Trapnell, C. *et al.* Pseudo-temporal ordering of individual cells reveals dynamics and regulators
of cell fate decisions. *Nature biotechnology* **32**, 381 (2014).
47 Kumar, P., Tan, Y. & Cahan, P. Understanding development and stem cells using single cell-based
analyses of gene expression. *Development* **144**, 17-32 (2017).

48 Street, K. *et al.* Slingshot: cell lineage and pseudotime inference for single-cell transcriptomics.
BMC genomics **19**, 1-16 (2018).
49 Hwang, B., Lee, J. H. & Bang, D. Single-cell RNA sequencing technologies and bioinformatics
pipelines. *Experimental & molecular medicine* **50**, 1-14 (2018).
50 Aubin-Frankowski, P.-C. & Vert, J.-P. Gene regulation inference from single-cell RNA-seq data
with linear differential equations and velocity inference. *Bioinformatics* **36**, 4774-4780 (2020).
51 Qiu, X. *et al.* Inferring causal gene regulatory networks from coupled single-cell expression
dynamics using scribe. *Cell systems* **10**, 265-274. e211 (2020).
52 Sanchez-Castillo, M., Blanco, D., Tienda-Luna, I. M., Carrion, M. & Huang, Y. A Bayesian
framework for the inference of gene regulatory networks from time and pseudo-time series
data. *Bioinformatics* **34**, 964-970 (2018).
53 Woodhouse, S., Piterman, N., Wintersteiger, C. M., Göttgens, B. & Fisher, J. SCNS: a graphical
tool for reconstructing executable regulatory networks from single-cell genomic data. *BMC
systems biology* **12**, 1-7 (2018).
54 Deshpande, A., Chu, L.-F., Stewart, R. & Gitter, A. Network inference with Granger causality
ensembles on single-cell transcriptomics. *Cell reports* **38**, 110333 (2022).
55 Jacomy, M., Venturini, T., Heymann, S. & Bastian, M. ForceAtlas2, a continuous graph layout
algorithm for handy network visualization designed for the Gephi software. *PloS one* **9**, e98679
(2014).
56 Wolf, F. A., Angerer, P. & Theis, F. J. SCANPY: large-scale single-cell gene expression data
analysis. *Genome biology* **19**, 1-5 (2018).
57 Gao, Y., Shen, L. & Xia, S.-T. in *ICASSP 2021-2021 IEEE International Conference on Acoustics,
Speech and Signal Processing (ICASSP).* 3320-3324 (IEEE).
58 Satija, R., Farrell, J. A., Gennert, D., Schier, A. F. & Regev, A. Spatial reconstruction of single-cell
gene expression data. *Nature biotechnology* **33**, 495-502 (2015).
59 Goodfellow, I. *et al.* Generative adversarial networks. *Communications of the ACM* **63**, 139-144
(2020).
60 Gulrajani, I., Ahmed, F., Arjovsky, M., Dumoulin, V. & Courville, A. C. Improved training of
wasserstein gans. *Advances in neural information processing systems* **30** (2017).
61 Reddi, S. J., Kale, S. & Kumar, S. On the convergence of adam and beyond. *arXiv preprint
arXiv:1904.09237* (2019).
62 He, K., Zhang, X., Ren, S. & Sun, J. in *Proceedings of the IEEE international conference on
computer vision.* 1026-1034.
63 Glorot, X. & Bengio, Y. in *Proceedings of the thirteenth international conference on artificial
intelligence and statistics.* 249-256 (JMLR Workshop and Conference Proceedings).
64 Ioffe, S. & Szegedy, C. in *International conference on machine learning.* 448-456 (PMLR).
65 Hu, H. *et al.* AnimalTFDB 3.0: a comprehensive resource for annotation and prediction of animal
transcription factors. *Nucleic acids research* **47**, D33-D38 (2019).
66 Shaham, U. *et al.* Removal of batch effects using distribution-matching residual networks.
Bioinformatics **33**, 2539-2546 (2017).
67 Shu, H. *et al.* Modeling gene regulatory networks using neural network architectures. *Nature
Computational Science* **1**, 491-501 (2021).
68 Mirza, M. & Osindero, S. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*
(2014).
69 Islam, S. *et al.* Characterization of the single-cell transcriptional landscape by highly multiplex
RNA-seq. *Genome research* **21**, 1160-1167 (2011).
70 Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library. *Advances
in neural information processing systems* **32** (2019).