GRouNdGAN: GRN-guided simulation of single-cell RNA-seq data using causal generative adversarial networks

Yazdan Zinati[1], Abdulrahman Takiddeen[1], and Amin Emad[1,2,3,*]

[1] Department of Electrical and Computer Engineering, McGill University, Montreal, QC, Canada

[2] Mila, Quebec AI Institute, Montreal, QC, Canada

[3] The Rosalind and Morris Goodman Cancer Institute, Montreal, QC, Canada

* Corresponding Author:

Amin Emad

755 McConnell Engineering Building

3480 University Street, Montreal, Quebec, Canada, H3A 0E9

Email: amin.emad@mcgill.ca

1   **Abstract**

2   We introduce GRouNdGAN, a gene regulatory network (GRN)-guided causal implicit generative

3   model for simulating single-cell RNA-seq data, *in-silico* perturbation experiments, and

4   benchmarking GRN inference methods. Through the imposition of a user-defined GRN in its

5   architecture, GRouNdGAN simulates steady-state and transient-state single-cell datasets where

6   genes are causally expressed under the control of their regulating transcription factors (TFs).

7   Training on three experimental datasets, we show that our model captures non-linear TF-gene

8   dependences and preserves gene identities, cell trajectories, pseudo-time ordering, and

9   technical and biological noise, with no user manipulation and only implicit parameterization.

10 Despite imposing rigid causality constraints, it outperforms state-of-the-art simulators in

11 generating realistic cells. GRouNdGAN learns meaningful causal regulatory dynamics, allowing

12 sampling from both observational and interventional distributions. This enables it to synthesize

13 cells under conditions that do not occur in the dataset at inference time, allowing to perform *in-*

14 *silico* TF knockout experiments. Our results show that *in-silico* knockout of cell type-specific TFs

15 significantly reduces cells of that type being generated. Interactions imposed through the GRN

16 are emphasized in the simulated datasets, resulting in GRN inference algorithms assigning them

17 much higher scores than interactions not imposed but of equal importance in the experimental

18 training dataset. Benchmarking various GRN inference algorithms reveals that GRouNdGAN

19 effectively bridges the existing gap between simulated and biological data benchmarks of GRN

20 inference algorithms, providing gold standard ground truth GRNs and realistic cells

21 corresponding to the biological system of interest. Our results show that GRouNdGAN is a stable,

22 realistic, and effective simulator with various applications in single-cell RNA-seq analysis.

Introduction

Unraveling gene regulatory interactions, often represented as a gene regulatory network (GRN),

plays a crucial role in studying biological processes under different conditions[1-3], simulating

knockdown and knockout experiments[4,5], and identifying therapeutic drug targets[6,7]. Many

algorithms have been proposed for GRN reconstruction using bulk or single-cell RNA sequencing

data (scRNA-seq), alone[8-14] or with other modalities[15-18]. While these advances have provided

great biological insights, evaluating the performance of GRN Inference algorithms remains

challenging[19,20] due to the lack of reliable ground truth for the biological processes under study.

Existing evaluation approaches often resort to curated databases[21-23]. However, the regulatory

interactions in these databases are aggregated from a wide range of datasets and are not specific

to a biological system, making them not ideal benchmarks due to context specificity of gene

regulation. Another strategy is to verify regulatory interactions by conducting perturbation

experiments on the system under study[20]. However, this approach is tedious, lengthy, and

expensive. Another approach is to employ scRNA-seq simulators. Despite great progress in this

domain, most simulators lack the essential properties for this task, such as the preservation of

gene identities and simulation based on a user-provided ground truth GRN. For example,

scGAN[24], cscGAN[24], scDESIGN2[25], and SPARSIM[26] capture inter-gene correlations in their

datasets. However, since they do not explicitly impose a known GRN (that can act as the ground

truth), they are not suitable for benchmarking GRN inference methods.

A small subset of simulators (e.g., BoolODE[19], SERGIO[4], and GeneNetWeaver (GNW)[27]) explicitly

incorporate GRNs capturing transcription factor (TF)-gene dynamics. GNW was used to generate

benchmarks for DREAM challenges[27-29]. However, being a bulk RNA-seq tool, its simulated

datasets do not replicate the distribution of experimental scRNA-seq datasets nor exhibit their

statistical properties, despite attempts to adapt it for this purpose by externally inducing dropout

events[10,30]. SERGIO and BoolODE were designed to simulate scRNA-seq data using stochastic

differential equations (SDEs)[4,19] and have been used to benchmark a variety of GRN inference

methods. However, often a mismatch between the benchmarking results based on experimental

and their simulated data have been reported, which may be attributed to differences between

the simulated and experimental datasets. For example, in the BEELINE study (using BoolODE),

some of the top ranking methods on simulated datasets reported near random performance on

experimental datasets[19]. Both simulators enable the user to simulate more realistic datasets by

carefully selecting the values of the SDE parameters. Moreover, using a reference dataset,

SERGIO allows fine tuning the added technical noise in an iterative procedure until the generated

and reference datasets are matched[4]. While these steps can help improve the resemblance to

real datasets, they are often suboptimal and pose an undue burden on the user: for example, in

SERGIO, the user must evaluate the similarity based on five different statistics and change three

parameters iteratively until desired resemblance is achieved (which itself can be subjective). In

addition, since the GRN is imposed on the "clean" dataset, but technical noise is added

afterwards, this step may change the encoded causal relationships in a non-trivial way (which

may explain why the performance of GRN inference methods dropped close to random when

applied to the noisy dataset[4]). Furthermore, SERGIO and BoolODE do not readily preserve gene

identities and make simplifying assumptions regarding cooperative regulation (see Discussion).

These shortcomings demonstrate the need for simulators capable of generating realistic scRNA-

seq data that retain the regulatory dynamics specified by a user-defined GRN. Importantly, with

the growing interest in causal inference, simulators that impose *causal* GRNs are of great need.

GRouNdGAN (GRN-guided in silico simulation of single-cell RNA-seq data using Causal generative

adversarial networks) is a causal implicit generative model for GRN-guided simulation of scRNA-

seq data inspired by CausalGAN[31]. Given an input GRN and a reference dataset, it can be trained

to generate simulated data that is both indistinguishable from the reference data and faithful to

the causal regulatory interactions of the input GRN. Unlike model-based simulators that rely on

simplifying assumptions regarding co-regulatory patterns, in GRouNdGAN these patterns are

learned through complex functions. This allows it not to compromise on the underlying

complexity of the system and to model elaborate regulatory dynamics. GRouNdGAN provides

state-of-the-art performance in realistic scRNA-seq data generation, while preserving gene

identities, user-defined causal gene regulatory interactions, and cellular dynamics (e.g., lineage

trajectory and pseudo-time ordering). This is achieved through implicit parameterization without

the need for manual fine-tuning. Using GRouNdGAN, we benchmark seven GRN inference

methods and find the results to be aligned with BEELINE's experimental results[19]. Furthermore,

the causal structure of GRouNdGAN enables it to be used for sampling from both interventional

and observational data distributions, enabling *in silico* knockout experiments.

Results

GRouNdGAN generates scRNA-seq data using causal generative adversarial networks

GRouNdGAN is a deep learning model that generates scRNA-seq data while imposing a user-defined causal GRN to describe the regulatory relationships of the genes and TFs. Its architecture builds on the causal generative adversarial network[31] and includes a causal controller, target generators, a critic, a labeler and an anti-labeler (Figure 1). Training includes two steps. First, the causal controller that generates TF expression values is pre-trained (Figure 1A) as the generator of a Wasserstein GAN (WGAN)[32] (Methods). In the second step (Figure 1B), TF expression values (generated by the pre-trained causal controller) and randomly generated noise are provided as input to the target generators that produce target genes' expressions, while incorporating the TF-gene relationships of the input GRN. To achieve this, as input, each target generator only accepts a noise value and the generated expression values of TFs that causally regulate it (Figure 1B, Methods). The generated expression of genes and TFs are then fed to a library-size normalization (LSN) layer[24].

The critic's role is to quantify the Wasserstein distance between the reference and simulated data. The target generators are trained in an adversarial manner to generate realistic datapoints indistinguishable from the reference datapoints by the critic. The labeler/anti-labeler estimate the causal controller's TF expression values *only* from the target genes' expressions to ensure that the generated causal TF-gene dependencies are encoded. Details are provided in Methods, the architectural choices in Tables S1-S2, and an ablation study in File S1 and Table S3.

108
Figure 1: Architecture and training procedure of GRouNdGAN. A) A WGAN is pre-trained to
generate realistic simulated cells. B) The LSN layer of the generator of the trained WGAN (panel
A) is removed, its weights are frozen, and is used as the causal controller to generate
unnormalized TF expression values. These TF expression values along with a noise vector are
provided as input to the target generators, following the provided causal GRN. The generated
gene and TF expression values are reorganized and passed through the LSN layer. The normalized
simulated expression vectors and experimental reference data are then passed to the critic to
estimate Wasserstein distance between the reference and the generated data distributions. The
anti-labeler estimates TF values based on generated target gene expressions. The labeler
performs a similar task, but in addition to receiving generated values, it also utilizes target gene
expression values from the reference data. Labeler and anti-labeler ensure that the causal GRN
is incorporated by the target generators. Details of the model are provided in Methods.

GRouNdGAN generates realistic scRNA-seq data

We trained GRouNdGAN on three datasets. The first dataset contained scRAN-seq profiles of

68579 human peripheral blood mononuclear cells (PBMCs) from 10x Genomics[33] corresponding

to eleven cell types ("PBMC-All"). We formed a dataset of the most common cell type in the

PBMC-All dataset containing 20773 CD8+ Cytotoxic T-cells ("PBMC-CTL"). Additionally, we

obtained the scRNA-seq (MARS-seq) profile of 2730 cells corresponding to differentiation of

hematopoietic stem cells to different lineages from mouse bone marrow[34] ("BoneMarrow"). We

used GRNBoost2[8] to identify fifteen TFs for each gene to form the input GRN. Note that these

identified interactions may contain both spurious correlations and causal relationships in the

reference dataset. However, when they are used as input to GRouNdGAN, they will correspond

to causal interactions in the *simulated* dataset (see Kocaoglu et al. for theoretical details of

causality in this architecture[31]). For each dataset, we trained GRouNdGAN on a randomly selected

training set and evaluated on a held-out test set (Methods, Table S4). Figures 2A-2B and S1-S3

show the t-SNE plots of reference and simulated cells, qualitatively revealing their similarity.

136
Figure 2: Performance of GRouNdGAN in generating realistic scRNA-seq data. All plots
correspond to 1000 real (experimental) held-out test cells and 1000 simulated cells. Each gene in
the imposed GRN of GRouNdGAN is regulated by 15 TFs (identified using GRNBoost2 from the
experimental training set). Panels A and B depict the t-SNE plots of real (red) and simulated (blue)
cells for PBMC-CTL and PBMC-All, respectively, while panels C and D also show their iLISI
distributions. E) The ROC curve of a Random Forest classifier in distinguishing between simulated
and real cells. F) The distribution of adjusted p-values corresponding to the TF perturbation study
on the PBMC-CTL dataset. The p-values are obtained using two-sided Wilcoxon signed ranked
tests and are adjusted for multiple hypotheses following the Benjamini-Hochberg procedure.

We quantitatively assessed their similarity using Euclidean distance, Cosine distance, maximum

mean discrepancy (MMD)[35], mean integration local inverse Simpson's index (miLISI)[36], and the

area under the receiver operating characteristic curve (AUROC) of a random forests (RF) classifier

distinguishing simulated and experimental cells (Methods). As a "control", we calculated these

metrics using two halves of the reference test set. Table 1 shows the performance of

GRouNdGAN, control, and three state-of-the-art simulators for the PBMC-CTL dataset (see Table

S4 for training set performance). Note that to assess data quality systematically and fairly, we

only included methods that automatically generate scRNA-seq data resembling experimental

data, since the quality of data generated by methods that rely on the user's judgement for

distribution matching (e.g., SERGIO and BoolODE) is user dependent and subjective.

Table 1: Performance of different simulators in generating realistic scRNA-seq data using the
PBMC-CTL dataset. The metrics are calculated between a simulated dataset of 1000 cells and the
held-out test set of 1000 real cells (see Table S4 for training set performance). Each gene in the
imposed GRN of GRouNdGAN is regulated by 15 TFs (constructed using GRNBoost2 from the
experimental training set). For the first three metrics, a value closer to zero is preferred, for RF
AUROC a value closer to 0.5 is preferred, and for miLISI a value closer to 2 is preferred. Best
performance values (excluding control) are in bold-face. The control shows the value of the
metrics comparing the two halves of the real dataset. For the first two metrics, the values
correspond to the distance of the mean centroids of the real and simulated cells.
166

Simulator	Cosine distance	Euclidean distance	MMD	RF AUROC	miLISI
GRouNdGAN	**0.00057**	**182**	**0.026**	**0.54**	**1.891**
scGAN[24]	0.00095	222	0.031	0.59	1.888
scDESIGN2[25]	0.00100	229	0.065	0.76	1.736
SPARsim[26]	0.00104	235	0.309	0.95	1.625
Control	0.00019	99	0.012	0.50	1.909

We sought to determine whether GRouNdGAN can generate samples from different cell types. If

cell type information of the reference dataset is available a priori, one can easily generate realistic

samples of each cell type separately (similar to the PBMC-CTL analysis) and use either cell type-

specific GRNs, a shared GRN, or a combination of both. However, we asked whether our model

could generate realistic samples *without* this knowledge, a more challenging task and useful for

when such information is unavailable. Also, not requiring cell type information reduces the

amount of user involvement (to annotate cell types) and improves model's usability. We

repeated the analysis using the PBMC-All dataset, containing eleven cell types. Although

GRouNdGAN did not receive cell type/cluster information, we did not observe mode collapse

(Figure S2), and it was able to generate cells from distinct clusters (Figure 2B, test set miLISI =

1.90). GRouNdGAN outperformed all simulators that did not use cell cluster information (Table

2) and compared to those that utilized this information, it was still the top performing based on

MMD and RF AUROC and the second best according to the Euclidean distance (6% higher than

the best) and miLISI (0.5% lower than the best) (Table 2). Finally, GRouNdGAN outperformed all

other simulators based on all metrics when we repeated the analysis using the BoneMarrow

dataset, containing continuous cell states and much fewer cells (Table S4). These results show

that GRouNdGAN is a stable simulator of scRNA-seq data and even without extra cell type

information in heterogenous datasets, it automatically generates realistic samples reflecting

different cell types (while imposing a GRN). (See File S1 and Table S5 for stability analysis and the

effect of different GRN properties on the performance).

Table 2: Performance of different simulators in generating realistic scRNA-seq data using the
PBMC-All dataset. Baseline models that enable utilization of cell cluster labels or ratios are run
with and without this information. The metrics are calculated between a simulated dataset of
1000 cells and the held-out test set of 1000 real cells. Each gene in the imposed GRN of
GRouNdGAN is regulated by 15 TFs (constructed using GRNBoost2 from the experimental training
set). For the first three metrics, a value closer to zero is preferred, for RF AUROC a value closer

 to 0.5 is preferred, and for miLISI a value closer to 2 is preferred. Best performance values
196 (excluding control) are in bold-face. The control shows the value of the metrics comparing the
197 two halves of the real dataset. For the first two metrics, the values correspond to the distance of
198 the mean centroids of the real and simulated cells.

Simulator	Cell cluster labels/ratios provided as input	Cosine distance	Euclidean distance	MMD	RF AUROC	miLISI
GRouNdGAN	No	0.00028	168	**0.017**	**0.53**	1.90
cscGAN[24]	Yes	0.00025	242	0.030	0.56	**1.91**
cWGAN	Yes	0.00053	239	0.027	0.57	1.89
scGAN[24]	No	0.00081	300	0.035	0.58	1.90
scDESIGN2[25]	Yes	0.00032	181	0.046	0.86	1.81
scDESIGN2[25]	No	0.00057	256	0.124	0.91	1.53
SPARsim[26]	Yes	**0.00019**	**158**	0.287	0.96	1.66
SPARsim[26]	No	0.00035	245	0.307	0.96	1.39
Positive control	NA	0.00022	116	0.012	0.50	1.91

GRouNdGAN imposes a causal GRN in the simulated data

To assess the ability of GRouNdGAN in imposing the input causal GRN, we performed *in-silico* TF

knockout experiments (one of GRouNdGAN's capabilities) on the simulated cells from the PBMC-

CTL dataset. We performed a forward pass after setting the expression of each TF to zero (one at

a time) in the causal controller output, while keeping all other parameters and TF expressions

unchanged, ensuring that the perturbations were performed on the same batch of cells forming

matched case/control experiments. There was no change in the expression of genes that were

not regulated by the knocked-out TF (as expected), while the expression of the regulated genes

changed. Figure 2F shows the distribution of the adjusted p-values (Benjamini-Hochberg) for

each TF-gene edge in the GRN, comparing the expression of a gene across all cells before and

after the knockout of one of its regulating TFs (two-sided Wilcoxon signed-rank tests). In the

majority (66.5%) of cases, the knockout of a gene's regulating TF significantly (adjusted p-value <

0.05) altered its expression, showcasing that the GRN is indeed imposed in the expression profiles

of simulated cells. Note that since each gene is regulated by multiple TFs, we cannot expect that

knockout of a single TF result in a significant change in the expression of its target genes in all

cases.

The imposed GRN can be reconstructed from the simulated data

To test whether the imposed GRN can be reconstructed from the generated data, we first applied

GRNBoost2[8] to the reference PBMC-CTL dataset and recorded the top ten TFs for each gene. For

each gene, we created two sets of five TFs based on their even/odd parity in the ranked list: TFs

ranked 1st, 3rd, 5th, 7th, and 9th were connected to the gene and were imposed ("positive control

GRN"), while the remaining five TFs were not ("negative control GRN"), resulting in two GRNs

with identical densities and the same number of TFs and target genes. When considering the

positive and negative control GRNs as ground truths (separately), the GRN reconstructed using

GRNBoost2 from the reference dataset resulted in comparable AUPRC (0.28 and 0.24,

respectively, Table S6), reflecting that these edges are of comparable importance.

We simulated data using GRouNdGAN by imposing only the positive control GRN, and used

GRNBoost2, PIDC[10] GENIE3[9], and PPCOR[37] to reconstruct the underlying GRN (Figure 3, Figure S4,

Table S6). All methods reconstructed the imposed edges with a much higher AUPRC compared

to the reference dataset, while they did not assign high scores to the unimposed edges, resulting

in close to random AUPRC. Figure 3 shows the performance of GRNBoost2 applied to the

reference, GRouNdGAN-simulated, and scGAN-simulated data. The performance for scGAN (both

GRNs) was lower than the reference dataset, showcasing that it had not preserved the TF-gene

relationships of the experimental dataset well. The performance was relatively consistent

between positive (Figures 3A and 3C) and negative control (Figures 3B and 3D) GRNs using the

reference and scGAN-simulated data; however, it was much higher for the positive control GRN

(compared to negative control GRN) using GRouNdGAN-simulated data. Similar patterns were

observed when we repeated these analyses using the BoneMarrow dataset (Table S6, Figure S5).

These results show that the imposed edges were accentuated by GRouNdGAN, while the

unimposed edges were disrupted and could not be found by GRN inference methods.

Next, we asked whether GRNBoost2 can reconstruct the imposed GRN, if GRNs of different

densities are used to simulate data. Using data for which each gene was regulated by 15, 10, 5,

and 3 TFs, we observed that in all cases the GRN imposed by GRouNdGAN could be inferred from

the simulated data (Table S6). Finally, we repeated the controlled analysis above, swapping the

role of positive and negative control GRNs. Similar to the results of Figure 3, the imposed edges

were inferred by GRNBoost2, while the unimposed edges were not accurately discovered (Table

S6). These results show that 1) GRouNdGAN imposes the causal GRN, 2) the GRN inference

methods can identify the imposed edges, and 3) the TF-gene relationships present in the

reference dataset but unimposed by GRouNdGAN are disrupted during simulation. The last

property is particularly desirable for benchmarking GRN inference methods to ensure that the

regulatory relationships present in the reference dataset (but unimposed) do not bias the

simulated data, which could result in an inflated false positive rate.

Figure 3: Performance of GRNBoost2 in recovering the imposed edges versus unimposed edges (PBMC-CTL). Left column shows the AUPRC (A) and Precision at k (per gene) (C) when the imposed edges (positive control GRN) were considered the ground truth. Right column shows the AUPRC (B) and Precision at k (per gene) (D) when the unimposed edges (negative control GRN) were considered the ground truth. Precision at k (per gene) refers to the precision when top k TFs for each gene is used to form the reconstructed GRN.

GRouNdGAN-simulated data preserves trajectories and can be used for pseudo-time inference

In addition to deciphering discrete states, scRNA-seq data is often used to determine continuous cell transitions during biological processes such as differentiation, using trajectory and pseudo-time inference[38-44]. We sought to determine whether GRouNdGAN-simulated data conforms to the transitional states and pseudo-time of the reference data. This is particularly important for benchmarking GRN inference methods that utilize pseudo-time information[12-14]. For this purpose, we used the BoneMarrow dataset corresponding to differentiation of hematopoietic stem cells to different lineages.

We used partition-based graph abstraction (PAGA)[38] for trajectory inference of the reference and GRouNdGAN-simulated data. PAGA computes graph-like maps of data manifolds faithful to the topology of data, retaining its continuous and discrete structures. Figure S6 shows the PAGA graphs, where nodes capture discrete states, and the edges signify transitions between them. To compare the identified trajectories, we used markers of the cell types present in this dataset (Table S7)[38]. Figure 4 shows the expression patterns of two marker genes for erythroid cells (*Gata1, Klf1*), neutrophils (*Mpo, Ctsg*), and basophils (*Mcpt8, Prss34*) for PAGA trajectory graphs of both datasets (Figures S7-S13 shows marker genes of all cell types). The comparison showed similar activation patterns between corresponding regions of PAGA graphs of the experimental and GRouNdGAN data, revealing several trajectories (e.g., erythroid and neutrophil branches). Strikingly, even the number of nodes activated in each figure scaled similarly between the two datasets: e.g., the markers of basophils were consistently expressed in only one node in each dataset (Figures 4E-4F).

Figure 4: PAGA graphs and cell type marker gene activation patterns in experimental and simulated BoneMarrow dataset. In each figure, nodes represent Louvain clusters (capturing discrete states), edges represent transitions between states, and edge weights indicate confidence in the presence of connections. Low-connectivity edges below a threshold of 0.01 were discarded. Left panels (A, C, E) show the PAGA graph computed on GRouNdGAN-generated cells, and right panels (B, D, F) show the PAGA graph for the original BoneMarrow dataset. Node colors represent normalized expression of marker genes for erythroid cells (A, B), neutrophils (C, D), and basophils (E, F).

We annotated different cell types present in both datasets using these marker genes (following PAGA's official tutorial) (Figures 5A-5B). The GRouNdGAN's annotated graph showed similar topological features to that of the reference data and captured known biological properties of hematopoiesis, which were also noted by Wolf, et al.[38] using the reference dataset (e.g.,

proximity between monocytes and neutrophils or association between megakaryocyte and erythroid progenitors). These observations show that the key characteristics of the reference data are retained in GRouNdGAN-simulated data.

Figure 5: Consistency in trajectories and pseudo-temporal orderings between data generated by GRouNdGAN and the experimental BoneMarrow hematopoietic dataset. Panels A and B show the cell type annotations of simulated and experimental data, respectively. The figures on the left show the force-directed graphs (obtained using ForceAtlas2[45]) and the figures on the right show the PAGA graphs. Panels C and D show the PAGA-initialized force-directed graphs with cells colored by their inferred pseudo-time value. The following abbreviations are used: Stem for stem cells, Ery for erythroid cells, Neu for neutrophils, Mo for monocytes, MK for Megakaryocytes, and Baso for Basophils. Panels E and F display expression changes in the marker genes of erythrocyte (*Gata2*, *Gata1*, *Klf1*, and *Hba-a2*), neutrophil (*Elane* and *Cebpe*), and monocyte (*Irf8*, *Csf1r*, and *Ctsg*) branches for experimental (E) and simulated data (F). The distance refers to the geodesic distance from a root cell (here a stem cell). A darker shade of grey shows higher expression. Panels (G, H) show the performance of different GRN inference methods on data generated by GRouNdGAN using the BoneMarrow dataset.

We used the diffusion pseudotime algorithm[39] (in scanpy[46]) to infer the progression of cells through geodesic distance (Figures 5C-5D). We noticed strong concordance when examining pseudo-time values assigned to cell subgroups in the reference and GRouNdGAN-generated data. To track these patterns, we focused on marker expression changes along erythroid, neutrophil, and monocyte trajectories (Figures S7-S9), similar to the analysis performed by Wolf, et al.[38]. In both datasets, the activation of neutrophils' marker, *Elane,* and monocytes' marker, *Irf8,* were predominantly observed towards the later stages of their trajectories (Figures 5E-5F). Additionally, we observed the activation of erythroid maturity marker genes *Gata2*, *Gata1*, *Klf1*, and *Hba-a2* roughly in sequential order along the erythroid trajectory in both datasets (Figures 5E-5F), concordant with previous findings[38]. The striking similarity between the activation patterns of these markers in both datasets and the preservation of their ordering highlights GRouNdGAN's ability to capture dynamic transcriptional properties of scRNA-seq data, leading to correct trajectory inference and pseudo-time ordering.

Benchmarking GRN inference methods using GRouNdGAN confirms prior insights from curated

experimental datasets

The BEELINE study[19] found conflicting results when benchmarking GRN inference methods on

curated biological datasets and synthetic ones: top two performing models on synthetic data

where among the bottom three on biological data. We re-investigated this using GRouNdGAN-

simulated data with the BoneMarrow dataset and the positive and negative control GRNs

(described earlier). We used seven GRN inference methods used by BEELINE, GRNBoost2[8],

GENIE3[9], PIDC[10], PPCOR[37], LEAP[12], SCODE[13], and SINCERITIES[14], capturing a wide range of

methods with a broad spread of performances reported on synthetic and curated data in the

BEELINE study. We observed a striking resemblance between the performance pattern (order) of

the methods on GRouNdGAN-simulated data and curated biological data from BEELINE (Figure

5G-5H and Table S6 versus Figure 4 of BEELINE[19]): the only difference was the swapping of LEAP

and SCODE's order. We repeated this analysis using the PBMC-CTL dataset (Table S6), obtaining

similar patterns.

Overall, PIDC[10] outperformed all methods using both datasets, followed by GENIE3[9] and

GRNBoost2[8]. LEAP[12], SCODE[13] and SINCERITIES[14] (which use pseudo-time and could only be

applied to the BoneMarrow dataset) performed worse than others, matching their behavior in

the BEELINE study on curated biological data (but not on synthetic data). All methods performed

close to random on unimposed negative control GRN edges. These results not only show that

GRouNdGAN can be used for benchmarking GRN inference methods, but also shows that the

insights obtained from it matches those obtained from curated biological datasets, the formation

of which requires extensive amount of resources and effort.

***In-silico* perturbation experiments using GRouNdGAN**

In many studies, one is interested to characterize the relationship between TFs' expression and

phenotypic labels (e.g., cell types). Differential expression (DE) analysis is a common approach to

identify TFs (or other genes) most associated with a specific cell type. However, to directly test

whether perturbing the expression of such candidate TFs change the expression of genes

representative of a cell type, perturbation experiments (e.g., TF knockout) are desired. As a causal

implicit generative model, GRouNdGAN provides the capability to sample from interventional

distributions, thereby enabling *in-silico* perturbation experiments. This functionality is provided

at inference time by enabling manipulation of TFs' expressions as the outputs of the causal

controller. This change is propagated along the GRN (through the model architecture), impacting

the expression of genes regulated by the perturbed TF(s). By enabling a deterministic mode of

operation, GRouNdGAN allows for exact comparison of gene expressions before and after

perturbation while maintaining the invariance of other parameters (Methods).

To test this functionality, we asked whether the knockout of top 3 TFs most differentially

expressed (Mann Whitney U test) between each cell type and the rest (identified from the

reference dataset) would result in less cells being generated in the vicinity of the cells of that

type. If positive, this implies that the perturbation in the TFs' expression has modified the gene

expression profile of generated cells so that they no longer resemble that particular cell type

(confirming our expectation). Figure 6A shows the UMAP embedding of the reference dataset

(miLISI = 1.94 when compared with simulated data) and Figure 6B shows the density plots of the

experimental and simulated data, revealing a high degree of resemblance. We focused on the

changes in the iLISI values of experimentally profiled cells of a specific type (annotated in the

original study), when jointly mapped to the same embedding space with simulated data, before

and after knockout. For the changes in the iLISI values to be observable, it was necessary to focus

on cell types that occupy relatively distinct regions of the embedding space: CD14+ monocytes,

CD19+ B cells, Dendritic cells, CD56+ natural killer cells (Figure S14); otherwise, the presence of

other cell types in that region would confound the results. Figure 6C shows the iLISI distributions

for each cell type (only for real cells), calculated along with unperturbed simulated cells (blue)

and perturbed simulated cells (orange). Figure 6D-6E show the iLISI values and the distribution

of generated cells after the knockout experiment for CD19+ B cells as an example (see Figures

S15-S18 for other cell types). In all cases, the iLISI values significantly reduced after the knockout

experiment (Figure 6C, Table S8), showcasing that after the knockout of top TFs associated with

a cell type, GrouNdGAN generated much fewer cells resembling that cell type (even though it did

not have the knowledge of the cell type annotations). Instead, the simulated cells were dispersed

into other cell types, yet they retained meaningful positions within the overall dataset

embedding space. Also, the miLISI of the other cell types remained relatively unchanged (Table

S8). This analysis shows that *in-silico* TF perturbation experiments using GrouNdGAN produces

results concordant with results directly obtained from real biological data, a direction that we

will explore further in the future studies.

Figure 6: TF knockout experiments and their effect on cell type generation. A) The UMAP shows the distribution of 2000 randomly selected cells from the experimental PBMC-All dataset. The color shows the iLISI value of each cell (miLISI = 1.94) calculated from a UMAP embedding, jointly obtained from the experimental cells and the same number of GRouNdGAN-generated cells. TFs were omitted as features when generating UMAP plots. In the simulated data, each gene was regulated by 15 TFs, identified using GRNBoost2. B) Each plot shows the density of cells in the embedding space: the left plot (blue) corresponds to the real cells and the right plot (red) shows the simulated cells. C) The boxplots show the distribution of iLISI values of real cells, calculated along with unperturbed simulated cells (blue) and with perturbed simulated cells (orange). For each cell type, top three most differentially expressed TFs were knocked out. The p-values

410 reported in this figure were calculated using one-sided Wilcoxon signed rank tests. D) The scatter
411 plot shows the iLISI values of CD19+ B cells calculated along with unperturbed simulated cells (x-
412 axis) and along with perturbed simulated cells (y-axis). The circles correspond to real cells and
413 their colors reflect the density of datapoints in that region. E) The UMAP embedding of real cells
414 (left), simulated cells after knockout of top TFs of CD19+ B cells (middle), and all together (right).
415

Discussion

GRouNdGAN is a causal implicit generative model designed to simulate realistic scRNA-seq

datasets based on a user-defined GRN and a reference dataset. By incorporating GRN

connections in its architecture and including auxiliary tasks, it imposes causal TF-gene

relationships in the gene expression profile of simulated cells. These causal relationships are

verifiable by *in-silico* knockout experiments and identifiable by GRN inference methods. (In

addition to the experimental analyses performed in this study, an interested reader should refer

to Kocaoglu et al.[31] for theoretical evidence of causality of data generated by this architecture.)

We demonstrated that GRouNdGAN achieves state-of-the-art performance on various tasks

including realistic scRNA-seq data generation, GRN inference benchmarking, and *in-silico*

knockout experiments. Even when applied to heterogenous datasets, it generated realistic

datasets without utilizing information regarding cell clusters, achieving best or second-best

performance compared to models that used this information. We should note that it is trivially

possible to use cell type/cluster information with GRouNdGAN: one can simply provide subsets

of the experimental dataset corresponding to a cell type/cluster as a reference, one at a time

with a cell-type specific (or shared) GRN. However, the fact that this model does not require this

information broadens its applicability. We showed that GRouNdGAN-generated data preserves

complex cellular dynamics and patterns of the reference dataset such as lineage trajectories,

pseudo-time orderings, and patterns of cell type markers' activation.

GRouNdGAN imposes user-defined causal regulatory interactions, while excluding those present

in the reference dataset, but not in the input GRN. This makes GRouNdGAN-simulated datasets

ideal for benchmarking GRN inference algorithms with the input GRN as the ground truth. We

benchmarked seven popular GRN inference algorithms and showed that our results coincide with

results reported by BEELINE[19] on experimental datasets. This highlights GRouNdGAN's ability to

bridge the gap between experimental and simulated datasets for GRN benchmarking without

requiring excessive user manipulation. Additionally, since GRouNdGAN generates data based on

a structural causal model, it can be used to sample synthetic cells from both observational and

interventional distributions. Using this property, we conducted *in-silico* perturbation

experiments by knocking out key regulating TFs in various cell types and observed that the

targeted cell-states were suppressed in the generated dataset.

GRouNdGAN maintains key advantages over existing simulators that incorporate GRNs such as

SERGIO and BoolODE. During training, GRouNdGAN's parameters are optimized to minimize any

mismatch between real and simulated data distributions. This enables it to replicate scRNA-seq

data characteristics (e.g., technical and biological noise) without any user intervention or post-

processing. In contrast, SERGIO simulates data by first generating a "clean" dataset based on

SDEs. Then, the user would iteratively fine-tune three noise parameters until the simulated and

reference datasets are matched. This data-matching procedure puts extra burden on the user

and might lead the user to overly rely on fine-tuning technical noise parameters, instead of SDE

parameters. Overreliance on added technical noise to achieve data-matching can potentially

corrupt the data, rendering the underlying regulatory patterns unobservable in the final

simulated dataset. This might explain the near-random GRN inference performance reported by

SERGIO on their noisy datasets[4]. GRouNdGAN is trained such that each of its generated genes or

TFs mimics the expression patterns of a corresponding gene or TF in the reference dataset,

preserving gene/TF identities. In contrast, BoolODE and SERGIO simulate pseudo-genes whose

identities cannot be readily mapped to their counterparts in the reference dataset. Gene identity

preservation can be attained in these simulators by fine-tuning the SDE parameters until the

expression patterns of a given generated gene aligns with a corresponding gene in the reference

dataset. This, however, places further burden on the user. Finally, GRouNdGAN learns complex

non-linear co-regulatory patterns from the data, instead of relying on simplifying assumptions or

user input. In contrast, SERGIO assumes that the combined effect of multiple regulatory TFs is

simply the sum of their individual effects. Similarly, BoolODE requires the user to provide a truth

table specifying combinatory TF co-regulation rules for each target gene. In contrast,

GRouNdGAN's neural network-based generator enables it to implicitly learn complex non-linear

co-regulatory patterns that may represent co-expression, co-inhibition, or co-activation of

individual genes. This is achieved during the training of GRouNdGAN without user intervention.

Several key points need to be considered when using GRouNdGAN. First, our analyses showed

that the architectural and hyperparameter choices of the presented model result in good

performance across different datasets. We performed hyperparameter tuning on one dataset

and used the same set of values for all three datasets and for different choices of GRNs, obtaining

state-of-the-art performance. However, when trained on a completely new dataset, it is still

advisable to test different choices of the hyperparameters using a validation set. Second, the

default architecture of the model includes LSN layers and, as such, the model generates library-

size normalized expression values. Our ablation study (File S1) showed that without the LSN layer,

GRouNdGAN can still generate realistic profiles; however, including it improves the GRN

imposition and stabilizes the training. Third, an important consideration for any causal inference

problem is that given an observational dataset, its underlying causal graph is not unique. When

benchmarking GRN inference methods, this problem exists regardless of how the ground truth

GRN is obtained (even using knockout/knockdown experiments), and a GRN inference algorithm

may find a plausible causal GRN, yet not the one that generated the data. Despite this, our

analysis using the positive/negative control GRNs showed that GRN inference methods could

detect the imposed edges while ignoring others that were unimposed. Based on this observation,

we posit that the imposed GRN by GRouNdGAN, while not the only causal GRN capable of

generating the simulated dataset, is the most probable one. However, verifying this requires

theoretical analyses that are well beyond the scope of this study.

Finally, although GRouNdGAN can generate data with any GRN, the quality of the data

deteriorates if the imposed TF-gene relationships are significantly different from those consistent

with the patterns in the reference dataset. The reason is that in such a scenario, generating

realistic simulated datapoints and imposing the GRN act as contradictory requirements. This is a

fundamental problem that is not unique to GRouNdGAN and is applicable to any simulator with

these two requirements. However, simulators that do not try to impose a causal graph (e.g.,

scGAN) can focus on generating realistic scRNA-seq samples, even at the expense of disrupting

some of the interactions present in the reference dataset (as we observed in Figure 3 with

scGAN). As a result, for GRN inference method benchmarking, we recommend first finding a set

of regulatory edges from the reference dataset (e.g., using GRNBoost2) and imposing a selected

subset of those in the simulated data. This ensures that the imposed edges are encoded in the

simulated data, the unimposed (or undetected) edges are disrupted (as shown in our analyses),

and the simulated dataset resembles the reference dataset. It is important to note that the

regulatory edges inferred from the reference dataset do not need to be all causal; some of them

could represent spurious correlations that are observable in the data. In fact, most GRN inference

methods do not identify causal edges, but can be used to form the input GRN. When a subset of

the (potentially) non-causal edges of the reference dataset are imposed by GRouNdGAN, they

are imposed in a causal manner, representing the *causal* graph underlying the *simulated* data

(and not the reference data).

The current version of GRouNdGAN only allows imposing a bipartite GRN and does not support

regulation of TFs by other TFs, an assumption that we plan to relax with the future versions of

the model. Moreover, we intend to augment the model's architecture in the future to enable

imposing a causal graph with three layers of nodes capturing TF-gene-phenotype relationships.

This is particularly useful for development and evaluation of phenotype-relevant GRNs, a concept

that we have introduced in the past[11]. Additionally, a conditional version of GRouNdGAN can be

developed, allowing the user to generate cells of specific cell type or on a specific stage along a

lineage trajectory. Finally, by incorporating DAG structural learning[47], we intend to enable

GRouNdGAN to infer a GRN while simultaneously learning to mimic the reference dataset.

Methods

Datasets and preprocessing

We downloaded the human peripheral blood mononuclear cell (PBMC Donor A) dataset

containing the single-cell gene expression profiles of 68579 PBMCs represented by UMI counts

from the 10x Genomics (https://support.10xgenomics.com/single-cell-gene-

expression/datasets/1.1.0/fresh_68k_pbmc_donor_a). This dataset contains a large number of

well-annotated cells and has been used by other models to generate synthetic scRNA-seq

samples[24]. We also downloaded the scRNA-seq profile of 2730 cells corresponding to

differentiation of hematopoietic stem cells to different lineages from mouse bone marrow[34]

("BoneMarrow" dataset) from Gene Expression Omnibus (accession number: GSE72857)

We followed the pre-processing steps of scGAN and cscGAN[24] using scanpy version 1.8.2[46]. In

each dataset, cells with nonzero counts in less than ten genes were removed. Similarly, genes

that only had nonzero counts in less than three cells were discarded. Next, library-size

normalization was performed on the counts per cell with a library size equal to 20,000 in order

to be consistent with previous studies [24]. Next, top 1000 highly variable genes were selected using

the dispersion-based method described by Satija et al.[48].

GRouNdGAN's model architecture

GRouNdGAN consists of 5 components, each implemented using separately parameterized

neural networks: a causal controller, target generators, a critic, a labeler, and an anti-labeler

(Figure 1B).

Causal controller: The role of causal controller is to generate the expression of TFs that causally

control the expression of their target genes based on a user-defined gene regulatory network

(Figure 1B). To achieve this, it is first pre-trained (Figure 1A) as the generator of a Wasserstein

GAN (WGAN). GANs are a class of deep learning models that can learn to simulate non-parametric

distributions[49]. They typically involve simultaneously training a generative model (called the

"generator") that produces new samples from noise, and its adversary, a discriminative model

that tries to distinguish between real and generated samples (called the "discriminator"). The

generator's goal is to generate samples so realistic that the discriminator cannot determine

whether it is real or simulated (an accuracy value close to 0.5). Through adversarial training, the

generator and discriminator receive feedback, allowing them to co-evolve in a symbiotic manner.

The main difference between a WGAN and a traditional GAN is that in the former, a Wasserstein

distance is used to quantify the similarity between the probability distribution of the real data

and the generator's produced data (instead of Kullback–Leibler or Jensen–Shannon divergences).

Wasserstein distance has been shown to stabilize the training of WGAN without causing mode

collapse[32]. The detailed formulation of the Wasserstein distance used as the loss function in this

study is provided in File S1. In addition, instead of a discriminator, WGAN uses a "critic" that

estimates the Wasserstein distance between real and generated data distributions. In our model,

we added a gradient penalty term for the critic (proposed by Gulrajani et al.[50] as an alternative

to weight clipping used in the original WGAN) in order to overcome vanishing/exploding

gradients and capacity underuse issues.

In the pretraining step, we trained a WGAN with a generator (containing an input layer, three

hidden layers, and an output layer), a library-size normalization (LSN) layer[24], and a critic

(containing an input layer, three hidden layers, and an output node). A noise vector of length

128, with independent and identically distributed elements following a standard Gaussian

distribution, was used as the input to the generator. The output of the generator was then fed

into the LSN layer to generate the gene and TF expression values. The details of hyperparameters

and architectural choices of this WGAN are provided in Table S1 (in File S1). Although we were

only interested in generating expression of TFs using the generator of this WGAN (in the second

step of pipeline), the model was trained using all genes and TFs to properly enforce the library-

size normalization. Once trained, we discarded the critic and the LSN layer, froze the weights of

the generator and used it as the "causal controller"[31] to generate expression of TFs (Figure 1B).

Target generators: The role of target generators is to generate the expression of genes causally

regulated by TFs based on the topology of a GRN. Consider a target gene Gj regulated by a set of

$TFs: \{TF_1, TF_2, \ldots, TF_n\}$. Under the causal sufficiency assumption and as a result of the manner

by which TFs' expressions are generated from independent noise variables, we can write $E_{Gj} =$

$f_{Gj}\left(E_{TF1}, E_{TF2}, \ldots, E_{TFn}, N_{Gj}\right)$ and $E_{TFi} = f_{TFi}(N_{TFi})$ for $i = 1, 2, \ldots, n$, where E represents

expression, N represents a noise variable, and f represents a function (to be approximated using

neural networks). All noise variables are jointly independent. Following the theoretical and

empirical results of CausalGAN[31], we can use feedforward neural networks to represent functions

f by making the generator inherit its neural network connections from the causal GRN. To

achieve this, we generate each gene in the GRN by a separate generator such that target gene

generators do not share any neural connections (Figure 1B).

As input, the generator of each gene accepts a vector formed by concatenating a noise variable

and a vector of non-library size normalized TF expressions from the causal controller,

corresponding to the TFs that regulate the gene in the imposed GRN (i.e., its parents in the graph).

The expression values of TFs and the generated values of target genes are arranged into a vector,

which is passed to an LSN layer for normalization. We used target generators with three hidden

layers of equal width. The width of the hidden layers of a generator is dynamically set as twice

the number of its regulators (the noise variable and the set of regulating TFs). If the imposed GRN

is relatively dense and contains more than 5000 edges, we set the depth to 2 and the width

multiplier to 1 to be able to train on a single GPU. The details of hyperparameters and

architectural choices are provided in Table S2 (in File S1).

In practice, generating each target gene's expression using separate neural networks introduces

excess overhead. This is because in every forward pass, all target genes' expressions must be first

generated before collectively being sent into the LSN layer. As a result, instead of parallelizing

the generation of each target gene's expression (which due to the bottleneck above does not

provide a significant computational benefit), we implemented target generators using a single

large sparse network. This allows us to reduce the overhead and the training time to train the

model on a single GPU, and to benefit from GPU's large matrix multiplication. We mask weights

and gradients to follow the causal graph, while keeping the generation of genes independent

from each other. From a logical standpoint, our implementation has the same architecture

described earlier, but is significantly more computationally efficient.

Critic: Similar to a traditional WGAN, the objective of GRouNdGAN's critic (Figure 1B) is to

estimate the Wasserstein distance between real and generated data distributions. We used the

same critic architecture as the WGAN trained in the first stage.

Labeler and anti-labeler: Although the main role of the target generators is to produce realistic

cells to confuse the critic, it is crucial that they rely on the TFs' expression (in addition to noise)

in doing so. One potential risk is that the target generators disregard the expression of TFs and

solely rely on the noise variables. This is particularly probable when the imposed GRN does not

conform to the underlying gene expression programs of real cells in the reference dataset; in

such a scenario, and to make realistically looking simulated cells, it is more convenient for a

WGAN to simply ignore the strict constraints of the GRN and solely rely on noise.

To overcome this issue, we used auxiliary tasks and neural networks known as "labeler" and

"anti-labeler"[31]. The task of these two networks is to estimate the causal controller's TF

expressions (here called labels) from the target genes' expressions alone (by minimizing the

squared L2 norm between each element's TF estimates and their true value). This resembles the

idea behind an autoencoder and ensures that the model will not disregard the expression of TFs

in generating the expression of their target genes. The anti-labeler is trained solely based on the

outputs of the target generators, while the labeler utilizes both the outputs of target generators

and the expression of real cells (Figure 1B). They are both implemented as fully connected

networks with a width of 2000 and a depth of 3 and optimized using the AMSGrad[51] algorithm.

Each layer, except the last one, utilizes a ReLU activation function and batch normalization. In

addition to WGAN losses, we add labeler and anti-labeler losses to the generator to minimize

both. This is different from the approach used in CausalGAN, where the anti-labeler's loss is

maximized in the early training stages to ensure that the generator doesn't fall into label-

conditioned mode collapse. In GRouNdGAN, the causal controller is pretrained and generates

continuous labels (TFs expression) and does not face a similar issue. As a result, we instead

minimized the loss of the anti-labeler from the beginning and as such the labeler and anti-labeler

both act as auxiliary tasks to ensure the generated gene expression values take advantage of TFs

expression.

Training procedure and hyperparameter tuning

We follow a two-step training procedure comprising of training two separate WGANs (Figure 1)

to train GRouNdGAN. The generators and critics in both GANs are implemented as fully

connected neural networks with rectified linear unit (ReLU) activation functions in each layer,

except for the last layer of the critic. The weights were initialized using He initialization[52] for layers

containing ReLU activation and Xavier initialization[53] for other layers (containing linear

activations). We used Batch Normalization[54] to normalize layer inputs for each training

minibatch, except for the critic. This is since using it in the critic invalidates the gradient penalty's

objective, as it penalizes the norm of the critic's gradient with respect to the entire batch rather

than to inputs independently. An LSN layer[24] was used in both WGANs (Figure 1A and 1B) to scale

counts in each simulated cell to make it consistent with the library size of input reference dataset.

This normalization results in a dramatic decrease in convergence time and smooths training by

mitigating the inherent heterogeneity of scRNA-seq data.

GRouNdGAN solves a min-max game between the generator (f_g) and the critic (f_c), with the

following objective function:

$$\min_{f_g}\max_{\|f_c\|_L \leq 1} \mathbb{E}_{x\sim\mathbb{P}_r} f_c(x) - \mathbb{E}_{x\sim f_g(\mathbb{P}_{noise})} f_c(x). \tag{1}$$

We alternated between minimizing the generator loss for one iteration and maximizing the

generator loss for five iterations. We employed the AMSGrad[51] optimizer with the weight decay

parameters $\beta_1 = 0.5$, $\beta_2 = 0.9$ and employed an exponentially decaying learning rate for the

optimizer of both the critic and generator.

The hyperparameters were tuned using a validation set consisting of 1000 cells from the PBMC-

CTL dataset (Tables S1-S2 in File S1) based on the Euclidean distance and the RF AUROC score,

which were consistently in accord. The same hyperparameters were used for all other analyses

and the other two datasets (PBMC-All and BoneMarrow).

Causal GRN preparation

This section describes the creation of the causal graph inputted to GRouNdGAN used to impose

a causal structure on the model. GRouNdGAN accepts a GRN in the form of a bipartite directed

acyclic graph (DAG) as input, representing the relationship between TFs and their target genes.

In this study, we created the causal graph using the 1000 most highly variable genes identified in

the preprocessing step. First, the set of TFs among the highly variable genes were identified based

on the AnimalTFDB3.0 database[55] and a GRN was inferred using GRNBoost2[8] (with the list of TFs

provided). Table S5 shows the characteristics of the different GRNs used in this study. It is

important to note that the regulatory edges identified from the reference dataset using

GRNBoost2 are not necessarily causal edges (and they do not need to be for the purpose of

forming the input GRN), but they are consistent with the patterns of the data. However, when

this (potentially non-causal) GRN is imposed by GRouNdGAN, it is imposed in a causal manner

and represents the causal data generating graph of the simulated data (and not the reference

data).

Evaluation of the resemblance of real and simulated cells

We evaluated all models using held-out test sets containing randomly selected cells from each

reference dataset (1000 cells from PBMC-CTL and PBMC-All and 500 cells from BoneMarrow). To

quantify the similarity between real and generated cells, we employed various metrics. For each

cell represented as a datapoint in a low dimensional embedding (e.g., t-SNE or UMAP), the

integration local inverse Simpson's Index (iLISI)[36] captures the effective number of datatypes (real

or simulated) to which datapoints of its local neighborhood belong based on weights from a

Gaussian kernel-based distributions of neighborhoods. The miLISI is the mean of all these scores

and in our study ranges between 1 (poor mixing of real and simulated cells) and 2 (perfect mixing

of real and simulated cells). Additionally, we calculated the cosine and Euclidean distances of the

centroids of real cells and simulated cells, where the centroid was obtained by calculating the

mean along the gene axis (across all simulated or real cells).

To estimate the proximity of high-dimensional distributions of real and simulated cells without

creating centroids, we used the maximum mean discrepancy (MMD)[35]. Given two probability

distributions p and q and a set of independently and identically distributed (i.i.d.) samples from

them, denoted by X and Y, MMD with respect to a function class $\mathcal{F}$ is defined as

$$\mathrm{MMD}[\mathcal{F}, X, Y] := \sup_{f \in \mathcal{F}} \left(\mathbb{E}_x[f(x)] - \mathbb{E}_y[f(y)] \right), \tag{2}$$

707   where sup refers to supremum and $\mathbb{E}$ denotes expectation. When the MMD function class $\mathcal{F}$ is a

708   unit ball in a reproducing kernel Hilbert space (RKHS) $\mathcal{H}$ with kernel k, the population MMD takes

709   a zero value if and only if $p = q$ and a positive unique value if $p \neq q$. The squared MMD can be

710   written as the distance of mean embeddings μ_p, μ_q of distributions p and q, which can be

711   expressed in terms of kernel functions:

$$MMD^2[\mathcal{F}, p, q] = \left\| \mu_p - \mu_q \right\|_{\mathcal{H}}^2 \tag{3}$$

$$= \mathbb{E}_{x,x'}[k(x,x')] - 2\mathbb{E}_{x,y}[k(x,y)] + \mathbb{E}_{y,y'}[k(y,y')].$$

714   Following existing implementations of MMD in the single-cell domain[24,56], we chose a kernel that

715   is the sum of three Gaussian kernels to increase sensitivity of the kernel to a wider range:

$$716 \qquad k(x, y) = \sum_i \left(\frac{\|x - y\|^2}{\sigma_i^2} \right), i = 1,2,3, \qquad\qquad (4)$$

where σ_i denote standard deviations and were chosen to be the median of the average distance

between a point to its 25 nearest neighbors divided by factors of 0.5, 1, and 2 in the three kernels,

respectively.

We also used a random forests (RF) classifier and used its area under the receiver operating

characteristic (AUROC) curve to determine whether the real and simulated cells can be

distinguished from each other. Consistent with previous studies[24,57], we first performed a

dimensionality reduction using principal component analysis (PCA) and used the top 50 PCs of

each cell as the input features to the RF model, which improves the computational efficiency of

this analysis. The RF model was composed of 1000 trees and the Gini impurity was used to

measure the quality of a split.

Baseline simulator models

We compared the performance of GRouNdGAN to scDESIGN2[25], SPARsim[26], and three GAN-

based methods: scGAN[24], cscGAN with projection-based conditioning[24], and a conditional WGAN

(cWGAN). The cWGAN method conditions by concatenation following the cGAN framework[58].

More specifically, it concatenates a one-hot encoded vector (representing the cluster number or

cell type) to the noise vector input to the generator and cells forwarded to the discriminator. We

did not train the cWGAN or cscGAN on the PBMC-CTL dataset, since it contains only one cell type.

For the PBMC-All and the BoneMarrow dataset, we trained all models above. Additionally, we

simulated data using scDESIGN2 and SPARsim with and without cell cluster information, as they

allow providing such side information in their training.

To train models that utilized cell cluster information, we performed Louvain clustering and

provided the cluster information and ratio of cells per cluster during training. Clustering was done

by following the cell ranger pipeline[33], based on the raw unprocessed dataset (and independent

of the pre-processing steps described earlier for training simulators). First, genes with no UMI

count in any of the cells were removed. Then the gene expression profile of each cell was

normalized by the total UMI of all (remaining) genes, and highly variable genes were identified.

The gene expression profile of each cell was then re-normalized by the total UMI of retained

highly variable genes, and each gene vector (representing its expression across different cells)

was z-score normalized. Given the normalized gene expression matrix above, we found top 50

principal components (PCs) using PCA analysis. These PCs were then used to compute a

neighborhood graph with a local neighborhood size of 15, which was used in Louvain clustering.

We ran the Louvain algorithm with a resolution of 0.15.

For SPARSim, we set all sample library sizes to 20000 and estimated gene expression level

intensities and simulation parameters by providing it with both raw and normalized count

matrices. When cell cluster information was provided, distinct SPARSim simulation parameters

were estimated per cell for each cluster. scDESIGN2 accepts input matrices where entries are

integer count values; we thus performed rounding on the expression matrix before fitting

scDESIGN2. With cluster information provided, a scDESIGN2 model was fit separately for cells of

each cluster, and similar to conditional GANs, the ratio of cells per cluster was provided to the

method.

In-silico **perturbation experiments using GroundGAN**

To perform perturbation experiments using GroundGAN, we put the trained model in a

deterministic mode of operation. This is necessary to ensure that the perturbation experiments

are performed on the same batch (i.e., replicate) of generated cells to form matched case/control

experiments. To do this, we performed a forward pass through the generator and then saved the

input noise to the causal controller, the input noise to the target generators, the TF expression

values generated by the causal controller, and the per-cell scaling factor of the LSN layer.

Subsequent passes through the generators used the saved parameters so that ensuing runs

always output the same batch of cells (instead of generating new unmatched cells).

Trajectory inference and pseudo-time analysis

Following   official   PAGA   tutorial   for   the   BoneMarrow   dataset

(https://github.com/scverse/scanpy-tutorials/blob/master/paga-paul15.ipynb),   we   used

(Partition-based graph abstraction) PAGA[38] for trajectory inference and analysis. We built force-

directed graphs[59] (with ForceAtlas2[45]) using the top 20 principal components of the data (using

principal component analysis or PCA) and a neighborhood graph of observations computed using

UMAP (to estimate connectivities). We next denoised the graph by representing it in the diffusion

map space and computed distances and neighbors as before using this new representation. After

denoising, we then ran the Louvain clustering algorithm with a resolution of 0.6. Finally, we ran

the PAGA algorithm on the identified clusters and used the obtained graph to initialize and

rebuild the force-directed graph.

GRN inference methods

In our GRN benchmarking analysis, we focused on seven GRN inference algorithms: GENIE3[9],

GRNBoost2[8], PPCOR[37], PIDC[10], LEAP[12], SCODE[13] and SINCERITIES[14], which were used in the

BEELINE study[19]. Of these methods, LEAP requires pseudo-time ordering of cells, while SCODE

and SINCERITIES require both pseudo-time ordering and pseudo-time values. Since not all

algorithms inferred the edge directionality or its sign (activatory or inhibitory nature), we did not

consider these factors in our analysis to be consistent among different models. We ran these

models as docker containers using the docker images provided by BEELINE's GitHub

(https://github.com/Murali-group/Beeline)[19] with the default parameters used in BEELINE. To

benchmark algorithms requiring pseudo-time ordering of cells, we computed the pseudo-times

of GRouNdGAN-simulated data (based on the BoneMarrow dataset) using PAGA[38] and diffusion

pseudotime[39], following the methodology described earlier. In the GRN inference benchmark

analysis, we did not provide the list of TFs to GRNBoost2 to make it consistent with other GRN

inference methods.

Competing interests

The authors have no conflict of interest to declare.

Authors' contributions:

All authors contributed to the design of the study and the algorithm, the analyses, and the writing

of the manuscript. AE supervised the study. YZ implemented the model and performed the

statistical analyses. All authors read and approved the final manuscript.

Acknowledgements

This work was supported by grants from Natural Sciences and Engineering Research Council of

Canada (NSERC) [RGPIN-2019-04460] (AE), Government of Canada's New Frontiers in Research

Fund (NFRF) [NFRFE-2019-01290] (AE), Canada Foundation for Innovation (CFI) JELF [project

40781], and McGill Initiative in Computational Medicine (AE). This research was enabled in part

by support provided by the Digital Research Alliance of Canada (https://alliancecan.ca) and

Compute Canada (www.computecanada.ca). *This publication is part of the Human Cell Atlas –*

www.humancellatlas.org/publications.

Data availability

The PMBC dataset is available from the 10x genomics repository (corresponding to healthy donor

A) from the link https://support.10xgenomics.com/single-cell-gene-

expression/datasets/1.1.0/fresh_68k_pbmc_donor_a?. The BoneMarrow dataset is available in

the Gene Expression Omnibus repository under accession number GSE72857. A collection of

simulated datasets with known ground truth GRNs will be publicly provided upon publication to

enable GRN inference benchmarking on various datasets.

 Code availability

Our implementation and evaluation of GRouNdGAN in Python 3.9.6 using the PyTorch

framework[60] along with a tutorial is freely available under the GNU Affero General Public License

v3.0 on GitHub (https://github.com/Emad-COMBINE-lab/GRouNdGAN). The repository also

contains our PyTorch implementation of scGAN, projection-based conditioning cscGAN[24] and a

variation of cscGAN that uses conditioning by concatenation (cWGAN).

Supplementary Material

File S1: Contains supplementary notes, all supplementary figures, Tables S1-S3, and caption of

Tables S4-S6 (which are provided as separate files).

References
1   Lee, T. I. *et al.* Transcriptional regulatory networks in Saccharomyces cerevisiae. *science* **298**,
799-804 (2002).
2   Che, D. *et al.* Dynamic and modular gene regulatory networks drive the development of
gametogenesis. *Briefings in bioinformatics* **18**, 712-721 (2017).
3   Olson, E. N. Gene regulatory networks in the evolution and development of the heart. *Science*
313, 1922-1927 (2006).
4   Dibaeinia, P. & Sinha, S. SERGIO: a single-cell expression simulator guided by gene regulatory
networks. *Cell systems* **11**, 252-271. e211 (2020).
5   Yang, Y. *et al.* Gene knockout inference with variational graph autoencoder learning single-cell
gene regulatory networks. *Nucleic Acids Research*, gkad450 (2023).
6   Madhamshettiwar, P. B., Maetschke, S. R., Davis, M. J., Reverter, A. & Ragan, M. A. Gene
regulatory network inference: evaluation and application to ovarian cancer allows the
prioritization of drug targets. *Genome medicine* **4**, 1-16 (2012).
7   Manuel, A. M., Dai, Y., Jia, P., Freeman, L. A. & Zhao, Z. A gene regulatory network approach
harmonizes genetic and epigenetic signals and reveals repurposable drug candidates for
multiple sclerosis. *Human Molecular Genetics* **32**, 998-1009 (2023).
8   Moerman, T. *et al.* GRNBoost2 and Arboreto: efficient and scalable inference of gene regulatory
networks. *Bioinformatics* **35**, 2159-2161 (2019).
9   Huynh-Thu, V. A., Irrthum, A., Wehenkel, L. & Geurts, P. Inferring regulatory networks from
expression data using tree-based methods. *PloS one* **5**, e12776 (2010).
10   Chan, T. E., Stumpf, M. P. & Babtie, A. C. Gene regulatory network inference from single-cell
data using multivariate information measures. *Cell systems* **5**, 251-267. e253 (2017).

11   Emad, A. & Sinha, S. Inference of phenotype-relevant transcriptional regulatory networks
elucidates cancer type-specific regulatory mechanisms in a pan-cancer study. *NPJ systems*
biology and applications **7**, 9 (2021).

12   Specht, A. T. & Li, J. LEAP: constructing gene co-expression networks for single-cell RNA-
sequencing data using pseudotime ordering. *Bioinformatics* **33**, 764-766 (2017).

13   Matsumoto, H. *et al.* SCODE: an efficient regulatory network inference algorithm from single-cell
RNA-Seq during differentiation. *Bioinformatics* **33**, 2314-2321 (2017).

14   Papili Gao, N., Ud-Dean, S. M., Gandrillon, O. & Gunawan, R. SINCERITIES: inferring gene
regulatory networks from time-stamped single cell transcriptional expression profiles.
Bioinformatics **34**, 258-266 (2018).

15   Aibar, S. *et al.* SCENIC: single-cell regulatory network inference and clustering. *Nature methods*
14, 1083-1086 (2017).

16   Bravo González-Blas, C. *et al.* SCENIC+: single-cell multiomic inference of enhancers and gene
regulatory networks. *Nature Methods*, 1-13 (2023).

17   Kartha, V. K. *et al.* Functional inference of gene regulation using single-cell multi-omics. *Cell*
genomics **2** (2022).

18   Badia-i-Mompel, P. *et al.* Gene regulatory network inference in the era of single-cell multi-omics.
Nature Reviews Genetics, 1-16 (2023).

19   Pratapa, A., Jalihal, A. P., Law, J. N., Bharadwaj, A. & Murali, T. Benchmarking algorithms for
gene regulatory network inference from single-cell transcriptomic data. *Nature methods* **17**,
147-154 (2020).

20   Emmert-Streib, F., Dehmer, M. & Haibe-Kains, B. Gene regulatory networks and their
applications: understanding biological and medical problems in terms of networks. *Frontiers in*
cell and developmental biology **2**, 38 (2014).

21   Kolmykov, S. *et al.* GTRD: an integrated view of transcription regulation. *Nucleic acids research*
49, D104-D111 (2021).

22   Xu, H. *et al.* ESCAPE: database for integrating high-content published data collected from human
and mouse embryonic stem cells. *Database* **2013**, bat045 (2013).

23   Kanehisa, M. & Goto, S. KEGG: kyoto encyclopedia of genes and genomes. *Nucleic acids research*
28, 27-30 (2000).

24   Marouf, M. *et al.* Realistic in silico generation and augmentation of single-cell RNA-seq data
using generative adversarial networks. *Nature communications* **11**, 1-12 (2020).

25   Sun, T., Song, D., Li, W. V. & Li, J. J. scDesign2: a transparent simulator that generates high-
fidelity single-cell gene expression count data with gene correlations captured. *Genome biology*
22, 1-37 (2021).

26   Baruzzo, G., Patuzzi, I. & Di Camillo, B. SPARSim single cell: a count data simulator for scRNA-seq
data. *Bioinformatics* **36**, 1468-1475 (2020).

27   Schaffter, T., Marbach, D. & Floreano, D. GeneNetWeaver: in silico benchmark generation and
performance profiling of network inference methods. *Bioinformatics* **27**, 2263-2270 (2011).

28   Marbach, D. *et al.* Revealing strengths and weaknesses of methods for gene network inference.
Proceedings of the national academy of sciences **107**, 6286-6291 (2010).

29   Marbach, D. *et al.* Wisdom of crowds for robust gene network inference. *Nature methods* **9**,
796-804 (2012).

30   Chen, S. & Mar, J. C. Evaluating methods of inferring gene regulatory networks highlights their
lack of performance for single cell gene expression data. *BMC bioinformatics* **19**, 1-21 (2018).

31   Kocaoglu, M., Snyder, C., Dimakis, A. G. & Vishwanath, S. Causalgan: Learning causal implicit
generative models with adversarial training. *arXiv preprint arXiv:1709.02023* (2017).

32   Arjovsky, M., Chintala, S. & Bottou, L. in *International conference on machine learning.* 214-223
(PMLR).

33   Zheng, G. X. *et al.* Massively parallel digital transcriptional profiling of single cells. *Nature*
communications **8**, 1-12 (2017).

34   Paul, F. *et al.* Transcriptional heterogeneity and lineage commitment in myeloid progenitors. *Cell*
163, 1663-1677 (2015).

35   Gretton, A., Borgwardt, K. M., Rasch, M. J., Schölkopf, B. & Smola, A. A kernel two-sample test.
The Journal of Machine Learning Research **13**, 723-773 (2012).

36   Korsunsky, I. *et al.* Fast, sensitive and accurate integration of single-cell data with Harmony.
Nature methods **16**, 1289-1296 (2019).

37   Kim, S. ppcor: an R package for a fast calculation to semi-partial correlation coefficients.
Communications for statistical applications and methods **22**, 665 (2015).

38   Wolf, F. A. *et al.* PAGA: graph abstraction reconciles clustering with trajectory inference through
a topology preserving map of single cells. *Genome biology* **20**, 1-9 (2019).

39   Haghverdi, L., Büttner, M., Wolf, F. A., Buettner, F. & Theis, F. J. Diffusion pseudotime robustly
reconstructs lineage branching. *Nature methods* **13**, 845-848 (2016).

40   Trapnell, C. *et al.* Pseudo-temporal ordering of individual cells reveals dynamics and regulators
of cell fate decisions. *Nature biotechnology* **32**, 381 (2014).

41   Kumar, P., Tan, Y. & Cahan, P. Understanding development and stem cells using single cell-based
analyses of gene expression. *Development* **144**, 17-32 (2017).

42   Saelens, W., Cannoodt, R., Todorov, H. & Saeys, Y. A comparison of single-cell trajectory
inference methods. *Nature biotechnology* **37**, 547-554 (2019).

43   Street, K. *et al.* Slingshot: cell lineage and pseudotime inference for single-cell transcriptomics.
BMC genomics **19**, 1-16 (2018).

44   Hwang, B., Lee, J. H. & Bang, D. Single-cell RNA sequencing technologies and bioinformatics
pipelines. *Experimental & molecular medicine* **50**, 1-14 (2018).

45   Jacomy, M., Venturini, T., Heymann, S. & Bastian, M. ForceAtlas2, a continuous graph layout
algorithm for handy network visualization designed for the Gephi software. *PloS one* **9**, e98679
(2014).

46   Wolf, F. A., Angerer, P. & Theis, F. J. SCANPY: large-scale single-cell gene expression data
analysis. *Genome biology* **19**, 1-5 (2018).

47   Gao, Y., Shen, L. & Xia, S.-T. in *ICASSP 2021-2021 IEEE International Conference on Acoustics,*
Speech and Signal Processing (ICASSP). 3320-3324 (IEEE).

48   Satija, R., Farrell, J. A., Gennert, D., Schier, A. F. & Regev, A. Spatial reconstruction of single-cell
gene expression data. *Nature biotechnology* **33**, 495-502 (2015).

49   Goodfellow, I. *et al.* Generative adversarial networks. *Communications of the ACM* **63**, 139-144
(2020).

50   Gulrajani, I., Ahmed, F., Arjovsky, M., Dumoulin, V. & Courville, A. C. Improved training of
wasserstein gans. *Advances in neural information processing systems* **30** (2017).

51   Reddi, S. J., Kale, S. & Kumar, S. On the convergence of adam and beyond. *arXiv preprint*
arXiv:1904.09237 (2019).

52   He, K., Zhang, X., Ren, S. & Sun, J. in *Proceedings of the IEEE international conference on*
computer vision. 1026-1034.

53   Glorot, X. & Bengio, Y. in *Proceedings of the thirteenth international conference on artificial*
intelligence and statistics. 249-256 (JMLR Workshop and Conference Proceedings).

54   Ioffe, S. & Szegedy, C. in *International conference on machine learning.* 448-456 (PMLR).

55   Hu, H. *et al.* AnimalTFDB 3.0: a comprehensive resource for annotation and prediction of animal
transcription factors. *Nucleic acids research* **47**, D33-D38 (2019).

953 56 Shaham, U. *et al.* Removal of batch effects using distribution-matching residual networks.
954   *Bioinformatics* **33**, 2539-2546 (2017).
955 57 Shu, H. *et al.* Modeling gene regulatory networks using neural network architectures. *Nature*
956   *Computational Science* **1**, 491-501 (2021).
957 58 Mirza, M. & Osindero, S. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*
958   (2014).
959 59 Islam, S. *et al.* Characterization of the single-cell transcriptional landscape by highly multiplex
960   RNA-seq. *Genome research* **21**, 1160-1167 (2011).
961 60 Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library. *Advances*
962   *in neural information processing systems* **32** (2019).