# Sensitive remote homology search by local alignment of small positional embeddings from protein language models

Sean R. Johnson[1]*, Meghana Peshwa[1], Zhiyi Sun[1]*

[1]New England Biolabs Inc., 240 County Road, Ipswich, MA 01938, United States

*Correspondence: sjohnson@neb.com, or sunz@neb.com

## Abstract

Accurately detecting distant evolutionary relationships between proteins remains an ongoing challenge in bioinformatics. Search methods based on primary sequence struggle to accurately detect homology between sequences with less than 20% amino acid identity. Profile- and structure-based strategies extend sensitive search capabilities into this twilight zone of sequence similarity but require slow pre-processing steps. Recently, whole-protein and positional embeddings from deep neural networks have shown promise for providing sensitive sequence comparison and annotation at long evolutionary distances. Embeddings are generally faster to compute than profiles and predicted structures but still suffer several drawbacks related to the ability of whole-protein embeddings to discriminate domain-level homology, and the database size and search speed of methods using positional embeddings. In this work, we show that low-dimensionality positional embeddings can be used directly in speed-optimized local search algorithms. As a proof of concept, we use the ESM2 3B model to convert primary sequences directly into the 3Di alphabet or amino acid profiles and use these embeddings as input to the highly optimized Foldseek, HMMER3, and HH-suite search algorithms. Our results suggest that positional embeddings as small as a single byte can provide sufficient information for dramatically improved sensitivity over amino acid sequence searches without sacrificing search speed.

## Introduction

A common method for assigning a putative function to a protein sequence is to find sequences with experimentally determined functions that have similarities in sequence, structure, or evolutionary origin to the unannotated sequence (Loewenstein et al., 2009). Direct comparisons of primary sequence, for example using BLASTP (Camacho et al., 2009), are fast and reliable but show poor ability to detect homologs with less than about 20% identity to the query (Rost, 1999). Popular approaches for higher sensitivity sequence searches involve using sequence profiles, for example with PSI-BLAST (Altschul et al., 1997), HMMER3 (Eddy, 2011), HH-suite3 (Steinegger et al., 2019), or MMseqs2 (Steinegger and Söding, 2017). Sequence profiles are derived from multiple sequence alignments (MSAs) and are often modeled as profile hidden Markov models (HMMs), for example in HMMER and HH-suite. Profile HMMs model each position as the probability of each amino acid at the position together with insertion and deletion probabilities. Because of their reliance on the construction of MSAs, profile-based methods can have high computational overhead for database construction, query preparation, or both.

Protein structure searches also show higher sensitivity than sequence searches (Jambrich et al., 2023). Until recently, the utility of structure searches for protein annotation was limited by the lack of extensive reference databases and the inability to predict structures quickly and reliably for sequences lacking experimentally determined structures. In the past several years accurate protein structure prediction programs such as AlphaFold2 (Jumper et al., 2021) and ESMFold (Lin et al., 2023) have led to a massive

increase in the size of databases of predicted protein structures. Coupled with fast structure search
algorithms such as Foldseek (van Kempen et al., 2023), RUPEE (Ayoub and Lee, 2019), and Dali (Holm,
2022), structure prediction programs provide another powerful tool for remote homology detection.
Foldseek achieves fast structure search by encoding the tertiary interactions of each amino acid in the 20-
letter 3D interaction (3Di) alphabet. By using a structure alphabet of the same size as the amino acid
alphabet, Foldseek can leverage optimized sequence search algorithms originally developed for amino
acid sequences (Steinegger and Söding, 2017; van Kempen et al., 2023). Structure search methods suffer
from some of the same drawbacks as profile-based methods, including the computational cost of
converting primary sequences to predicted structures.

Emerging methods for protein annotation and remote homology detection rely on deep neural networks
taking protein sequences as inputs and producing either a classification from a controlled vocabulary
(Bileschi et al., 2022; Sanderson et al., 2023), a natural language description (Gane et al., 2022), positional
embeddings, or a sequence embedding. Positional embeddings are fixed length vectors for each amino
acid position of the protein. Positional embeddings produced by popular protein language models (pLMs)
usually have large dimensions such as 1024 for ProtT5-XL-U50 (Elnaggar et al., 2021) and 2560 for ESM-2
3B (Lin et al., 2023). Sequence embeddings represent an entire sequence and are often calculated by
element-wise averaging of the positional embeddings. Positional and sequence embeddings can be used
for remote homology detection by using them to calculate substitution matrices in pairwise local
alignments (Kaminski et al., 2022; Pantolini et al., 2022; Ye and Iovino, 2023), or by k-nearest neighbors
searches (Hamamsy et al., 2022; Schütze et al., 2022), respectively.

While each of these emerging methods shows promise for improving sensitivity of protein search and
annotation, they suffer various limitations. Classification models and methods relying on sequence
embeddings struggle at discriminating individual domains of multi-domain proteins. Methods relying on
large positional embeddings are space inefficient, and current search implementations are slow compared
to other methods. Smaller positional embeddings would be more amenable to algorithmic optimizations
using single instruction multiple data (SIMD) capabilities of central processing units (CPUs) that contribute
to the speed of optimized sequence search algorithms (Buchfink et al., 2021; Eddy, 2011; Steinegger et
al., 2019).

We recognized that profile HMMs and 3Di sequences are types of positional embeddings with
dimensionality as low as 1 (3Di sequences) to about 25 (profile HMMs, including amino acid frequencies
and state transition probabilities). We test the hypothesis that the ESM-2 3B pLM (Lin et al., 2023) could
be used to directly convert primary amino acid sequences into profile HMMs compatible with HMMER3
or HH-suite, and 3Di sequences compatible with Foldseek, providing a sequence search workflow
leveraging the speed and sensitivity advantages of profile and structure search algorithms with an
accelerated query preparation step enabled by the pLM.

## 75　Results

76　ESM-2 was already pretrained on the masked language modeling task (Devlin et al., 2019; Lin et al., 2023)
77　of predicting amino acid distributions at masked positions of input sequences, therefore no additional
78　fine-tuning was necessary to induce it to produce probabilities compatible with profile HMM tools (Figure
79　1A). Positional amino acid frequencies predicted by ESM-2 3B resembled those found in MSAs built from
80　sequence searches (Figure 2).

**Figure 1. Schematics of embedding models and the experimental design.** (**A**) ESM-2 3B can be directly used to predict amino acid probability distributions at masked positions. Our implementation uses seven passes. The second pass is shown in the figure. (**B**) ESM-2 3B 3Di, a fine-tuned ESM-2 3B with a small CNN top model can be used to predict 3Di sequences from amino acid sequences. (**C**) Data flow from amino acid sequences through embedding models and other programs to produce files used in homology searches. Bold words correspond to line labels in Figure 3.

**Figure 2. Logos related to the example test sequence YBGC_HELPY___14-90 from the 4HBT family.** (**A**) 4HBT family hmm from Pfam 32. (**B**) hmmbuild with default settings on an MSA of the top 100 hits supplied by an online blast search (blast.ncbi.nlm.nih.gov) of YBGC_HELPY___14-90 against the NCBI clustered nr database. (**C**) hmmbuild with default settings on the MSA sampled from the ESM-2 3B positional probabilities for YBGC_HELPY___14-90. (**D**) and (**E**) hmmbuild with Dirichlet priors disabled on the same MSAs as for (**B**) and (**C**), respectively. All logos were generated by uploading the corresponding .hmm file to skylign.org (Wheeler et al., 2014).

To produce Foldseek-compatible 3Di sequences, we trained a two-layer 1D convolutional neural network (CNN) to convert positional embeddings from the last transformer layer of ESM-2 3B into 3Di sequences, we then unfroze the last transformer layer and fine-tuned it together with the CNN. The fine-tuned model, which we call ESM-2 3B 3Di (Figure 1B), converted amino acids to 3Di with an accuracy of 64% compared to a test set of 3Di sequences derived from AlphaFold2 predicted structures.

To evaluate the capacity of small embeddings to improve search sensitivity, we generated predicted profiles and 3Di sequences from clustered Pfam 32 splits (Bileschi et al., 2022) and converted them into formats compatible with various search tools (Figure 1C). Pfam (Mistry et al., 2021) is a set of manually curated multiple sequence alignments of families of homologous protein domains. Some families presumed to have a common evolutionary origin are further grouped into clans. In the clustered splits, each family is divided into train and test groups such that each sequence in the test group has less than 25% identity to the most similar protein in the train group (Bileschi et al., 2022). The sensitivity of a search

algorithm is evaluated by the ability to match sequences from the test groups to their corresponding train
group at the family or clan level.

Methods using predicted profiles and those using predicted 3Di sequences both showed greater accuracy
than phmmer (amino acid to amino acid) searches across all identity bins, and hmmscan (amino acid to
profile HMM) searches on test sequences below 20% identity to the closest train sequence (Figure 3,
compare lines 6 and 7 with lines 1 and 2). Foldseek searches where both the queries and database
consisted of 3Di sequences produced by ESM-2 3B 3Di (line 7) performed the best overall. Foldseek
considers both 3Di and amino acid sequences in its alignments and can therefore be conceptualized as
using a 2-byte embedding. Running Foldseek in 3Di-only mode (line 8), a 1-byte embedding, led to a
decrease in accuracy but still outperformed phmmer across all identity bins, and hmmscan on bins below
20% identity. We also tried creating HMMER3 profiles from predicted 3Di sequences (line 9). These
performed worse than single-sequence Foldseek searches. Patching HMMER3 to use 3Di-derived
background frequencies and Dirichlet priors (line 10) did not improve performance. Furthermore, we
noticed that HMMER3 runs very slowly on 3Di sequences and profiles, presumably because the
prefiltering steps were not optimized with 3Di sequences in mind.

While faster than MSA construction or full structure prediction, pLM embedding still have non-trivial
computational overhead. This limits the possibility of using methods based on pLM embeddings to
perform sensitive homology searches against large metagenomic databases such as the 2.4 billion
sequence Mgnify database (Richardson et al., 2023). It would be desirable to have search methods where
the database can remain as amino acid sequences or other cheaply-calculated representations and the
queries can be processed with more expensive methods. To this end, we tested hmmsearch using ESM2
3B generated profiles as queries against amino acid databases (lines 3 and 4). This is similar to a two-
iteration PSI-BLAST (Altschul et al., 1997) or JackHMMER (Johnson et al., 2010) search where the first
search and MSA-building step is replaced by a pLM embedding step. Curiously, hmmsearch using profiles
built directly from the pLM probabilities (line 3) had the lowest accuracy of any algorithm. Nevertheless,
profiles processed with hmmbuild from HMMER3, applying HMMER3 Dirichlet priors on top of the pLM
probabilities (line 4), had better family prediction accuracy than phmmer at all but the highest identity
bin, and accuracy on par with hmmscan at 18% identity and lower.

| Color | Line # | Algorithm | Query (test split) | Target (train split) | Family error rate | Number of errors | Clan error rate | Number of errors |
|---|---|---|---|---|---|---|---|---|
| | 1 | hmmscan | aa seq | aa hmmer profile | 17.6 | 3744 | 10.7 | 1305 |
| | 2 | phmmer | aa seq | aa seq | 32.6 | 6942 | 27.3 | 3341 |
| | 3 | hmmsearch | pred hmmer profile | aa seq | 59.8 | 12740 | 50.9 | 6235 |
| | 4 | hmmsearch | pred hmmer profile dchlet | aa seq | 23.8 | 5078 | 12.7 | 1559 |
| | 5 | hhblits | pred hhsuite profile | aa hhsuite profile | 18.7 | 3979 | 7.8 | 955 |
| | 6 | hhblits | pred hhsuite profile | pred hhsuite profile | 17.7 | 3778 | 6.2 | 760 |
| | 7 | foldseek | pred 3Di | pred 3Di | 14.0 | 2982 | 5.5 | 672 |
| | 8 | foldseek 3Di-only | pred 3Di | pred 3Di | 17.6 | 3753 | 7.4 | 903 |
| | 9 | hmmscan | pred 3Di | pred 3Di hmmer profile | 18.4 | 3909 | 8.0 | 982 |
| | 10 | 3Di_hmmscan | pred 3Di | pred 3Di hmmer3Di profile | 19.9 | 4234 | 9.0 | 1101 |

**Figure 3. Homology detection accuracy.** Test sequences were binned based on percent identity to the
closest training sequence in the same family and annotated based on the top scoring hit from a search
against the entire set of training sequences or training sequence family profiles, depending on the
algorithm. (**A**) family recovery accuracy by bin. (**B**) clan recovery accuracy. (**C**) and (**D**) are detail views of
the 0.8 to 1.0 accuracy range. There are a total of 21,293 test sequences. 12,246 test sequences have clan
assignments.

## Discussion

Our results show that small positional embeddings produced by pLMs can enhance search sensitivity, potentially with less computational overhead than MSA construction or full structure prediction. While this manuscript was being submitted, another group reported an amino acid to 3Di translation model, ProstT5, that also showed strong performance on remote homology detection (Heinzinger et al., 2023). There are many possible directions for future development of improved embeddings, faster conversion and search programs, and comprehensive reference databases. Of particular interest could be conversion to profile HMM-style embeddings in a single pass, rather than the seven we required, and predicting state transition probabilities. Small positional embeddings optimal for local alignment could also be learned directly from a differentiable alignment algorithm (Petti et al., 2023) instead of relying on proxy tasks of amino acid or 3Di prediction. Finally, asymmetric architectures where embedding a database sequence is cheaper than embedding a query, analogous to searches with profile HMM queries against primary sequence databases, could be a powerful method for improving search sensitivity against large and growing reference databases. We've made our model training, search, and data analysis code publicly available. We hope our results and code will serve as a springboard for further exploration of the utility of low-dimensionality positional embeddings of protein sequences.

## Methods

### Alignments

Unless otherwise noted, multiple sequence alignments were made using MAFFT (v7.505) (Katoh and Standley, 2013) with options --anysymbol --maxiterate 1000 --globalpair. Protein alignments used the BLOSUM62 substitution matrix (Henikoff and Henikoff, 1992). 3Di alignments used the 3Di substitution matrix from Foldseek (van Kempen et al., 2023) (https://github.com/steineggerlab/foldseek/blob/master/data/mat3di.out).

### Patching HMMER3 with background frequencies and Dirichlet priors for 3Di

We created a fork of the HMMER3 program, replacing amino acid background frequencies and Dirichlet priors with values calculated from the 3Di alphabet instead of the amino acid alphabet (https://github.com/seanrjohnson/hmmer3di). To generate a set of 3Di MSAs, we converted the AlphaFold UniProt Foldseek database (Jumper et al., 2021; van Kempen et al., 2023; Varadi et al., 2022) to a 3Di fasta file. We then looked up every sequence name from the Pfam 35 seed file in the UniProt 3Di fasta file and, for cases where the corresponding sequence was identifiable, extracted the sub-sequence corresponding to the Pfam 35 seed. 3Di seeds from each profile were aligned using MAFFT. MSA columns with more than 10 rows were used to calculate background frequencies and Dirichlet priors using the HMMER3 program esl-mixdchlet fit with options -s 17 9 20. Amino acid background frequencies and Dirichlet priors in the HMMER3 source code were then replaced with the newly calculated 3Di background frequencies and Dirichlet priors. We call the patched HMMER3 as HMMER3Di.

### Fine tuning ESM-2 3B to convert amino acid sequences into 3Di sequences

A 1D CNN was added on top of ESM-2 3B. The CNN takes as input position-wise embeddings from the last transformer layer of ESM-2 3B. The CNN consists of two layers, the first layer has 2560 input channels (the size of the embeddings from ESM-2 3B), and 300 output channels, kernel size 5, stride 1, padding 3. The second layer has 300 input channels and 21 output channels (one for each 3Di symbol plus a padding symbol), kernel size 5, stride 1, padding 1. The model was trained with a weighted cross-entropy loss

function using weights of 0.1 * the diagonal from 3Di substitution matrix. The neural network was
implemented in PyTorch (Paszke et al., 2019).

Training data was derived from the Foldseek AlphaFold2 UniProt50 dataset (Jumper et al., 2021; van
Kempen et al., 2023; Varadi et al., 2022), a reduced-redundancy subset of the UniProt AlphaFold2
structures. The Foldseek database was downloaded using the Foldseek "databases" command line
program, converted into protein and 3Di fasta files, filtered to remove sequences smaller than 120 amino
acids and larger than 1000 amino acids, and split into train, validation, and test subsets, 90%:5%:5%,
(33,924,764: 1,884,709: 1,884,710 sequences)

With ESM-2 layers frozen, the CNN was trained on the task of converting amino acids to 3Di sequences
using the AdamW optimizer with learning rate 0.001, weight decay 0.001, and exponential learning rate
decrease (gamma 0.98, applied every 100 batches). Training sequences were randomly selected in
batches of 15 sequences. Training proceeded for 1301 batches, leading to a training accuracy of about
58%.

The last transformer layer of ESM-2 was then unfrozen and training restarted from the saved weights,
with the same training parameters. Training continued for another 24001 batches of 10 random training
sequences. Accuracy on the final training batch was 65%. Using the final trained weights, test sequences
were converted to 3Di at an accuracy of 64.4%. We call the fine-tuned model ESM-2 3B 3Di.

The trained weights are available on Zenodo (https://doi.org/10.5281/zenodo.8174959). The training
code is available on Github (https://github.com/seanrjohnson/esmologs). The model training code should
be useful for fine-tuning ESM-2 to convert amino acid sequences to various other kinds of sequences, such
as secondary structure codes, etc.

## Pfam 32 clustered splits

Pfam 32 clustered splits (Bileschi et al., 2022) were downloaded from:
https://console.cloud.google.com/storage/browser/brain-genomics-
public/research/proteins/pfam/clustered_split. Data for mapping of individual Pfam 32 families to clans
was downloaded from: https://ftp.ebi.ac.uk/pub/databases/Pfam/releases/Pfam32.0/. The sequences
from the train, dev, and test splits were sorted into unaligned fasta files according to their split and family
(**aa seq**).

## Predicting 3Di sequences

214 Each training and test sequence was converted into a predicted 3Di sequence (**pred 3Di**) using the ESM-2
215 3B 3Di model described above. MAFFT alignments were made of both the amino acid and predicted 3Di
216 training and test sequences for each family. HMMER3 profiles were built from the alignments using either
217 unaltered HMMER3 (**pred 3Di hmmer profile**), or HMMER3Di (**pred 3Di hmmer3Di profile**).

## Predicting profiles to generate HH-suite hhm files and HMMER3 hmm files from single
sequences

220 Positional amino acid probabilities were calculated for unaligned train and test sequence using pre-trained
221 ESM-2 3B in the following algorithm.

1. Prepend sequence with M. This is because ESM-2 3B has a strong bias towards predicting M as
   the first amino acid in every sequence, and most Pfam domains don't start with M.

224  2. Mask the first, eighth, etc. position in the sequence
225  3. Run a forward pass of ESM-2 3B over the masked sequence.
226  4. Save the logits for each of the 20 amino acid tokens for each masked position.
227  5. Shift the masks one position to the right.
228  6. Repeat steps 3 through 5 another 6 times until logits have been saved for every position.
229  7. Use the softmax function to calculate the amino acid probabilities at each position from the logits.

230 Note that in our actual implementation, a single forward pass was run on a batch of seven copies of the
231 input sequence, each with different masking.

232 The positional probabilities were written directly as an HH-suite compatible .hhm file (**pred hhsuite**
233 **profile**). A 40 sequence fasta MSA file was written where each sequence was randomly sampled from the
234 probability distribution. Hmmbuild was run with default settings on the sampled MSA (**pred hmmer**
235 **profile dchlet**) and with the -pnone setting, which disables adjustments to the probability distribution
236 based on Dirichlet priors (**pred hmmer profile**).

237 Building HH-suite hhm and HMMER3 hmm profiles from train amino acid MSAs
238 The amino acid MSA for each training family were converted into an HH-suite database (**aa hhsuite**
239 **profile**) with the following bash script:

```
240   echo '#'$profile_name > msa/${profile_name}.a3m
241   hhfilter -i $MSA_FASTA -a msa/${profile_name}.a3m -M 50 -id 90;
242   hhconsensus -i msa/${profile_name}.a3m -o consensus/${profile_name}.a3m
243   hhmake -name $base -i consensus/${profile_name}.a3m -o hhm/${base}.hhm
244   ffindex_build -s db_hhm.ffdata db_hhm.ffindex hhm
245   ffindex_build -s db_a3m.ffdata db_a3m.ffindex consensus
246   cstranslate -f -x 0.3 -c 4 -I a3m -i db_a3m -o db_cs219
```

247 HMMER3 profiles were built by calling hmmbuild with default settings on the training family amino acid
248 MSAs (**aa hmmer profile**).

249 Building HH-suite databases from predicted profiles
250 HH-suite databases were built from predicted profiles .hhm files and the corresponding sampled 40
251 sequence MSA fasta files using the following bash script:

```
252   ffindex_build -s db_hhm.ffdata db_hhm.ffindex esm2_3B_profiles
253   ffindex_build -s db_a3m.ffdata db_a3m.ffindex esm2_3B_sampled_msas
254   cstranslate -f -x 0.3 -c 4 -I a3m -i db_a3m -o db_cs219
```

255 Building Foldseek databases from predicted 3Di sequences
256 Amino acid and predicted 3Di fasta files were converted into Foldseek-compatible databases using a new
257 script, fasta2foldseek.py, available from the esmologs python package (see below).

258 Hmmscan, phmmer, and hmmsearch HMMER3 searches
259 In an attempt to mimic the Top pick HMM strategy reported by (Bileschi et al., 2022) we ran all HMMER3
260 searches in up to two iterations. The first iteration was run with default settings. For test sequences where
261 no hits were detected among the training sequences or profiles, depending on the program, a second

iteration was run with the addition of parameters intended to maximize sensitivity at the expense of
search speed:

`--max -Z 1 --domZ 1 -E 1000000 --domE 1000000`

It should be noted that while our phmmer results are directly comparable to the phmmer results reported
by Bileschi et al., our hmmscan results are not directly comparable to the reported "Top Pick HMM" results
because we re-aligned the training sequences for each family instead of using the Pfam seed alignments.
Still our results were very similar. We observed a 17.6% error rate (3744 test sequences with mispredicted
family assignments) by hmmscan, compared to the reported 18.1% error rate (3844 mispredictions).

## 3Di_hmmscan HMMER3Di searches
3Di_hmmscan searches were performed using the same two iteration method described above for
searches using standard HMMER3 programs.

## Hhblits HH-suite searches
Hhbilts was run with the options:

`-tags -n 1 -v 0`

## Foldseek searches
After converting both query and target amino acid and predicted 3Di fasta files into Foldseek compatible
databases (see above), Foldseek searches were run with the following commands:

`foldseek search test_db train_db foldseek_results tmpFolder`
`foldseek convertalis test_db train_db aln_3Di_only ../hits.tsv --format-`
`output query,target,bits`

For 3Di-only searches, the option `--alignment-type 0` was added to the search call.

# Data and Code availability
284 HMMER3 patched with 3Di background frequencies and Dirichlet priors:
285 https://github.com/seanrjohnson/hmmer3di

286 Code for neural network training, sequence searches, and data analysis:
287 https://github.com/seanrjohnson/esmologs
288
289 Model weights for ESM-2 3B 3Di, predicted profiles and 3Di sequences from the Pfam 32 clustered splits,
290 and other data necessary to reproduce the analyses: https://doi.org/10.5281/zenodo.8174959

# Acknowledgements

292 We thank Sergey Ovchinnikov for helpful discussion about protein language models, Sean Eddy for helpful
293 discussion about HMMER3, and Gary Smith for IT support.

# References

Altschul SF, Madden TL, Schäffer AA, Zhang J, Zhang Z, Miller W, Lipman DJ. 1997. Gapped BLAST and PSI-BLAST: a new generation of protein database search programs. *Nucleic Acids Research* **25**:3389–3402. doi:10.1093/nar/25.17.3389

Ayoub R, Lee Y. 2019. RUPEE: A fast and accurate purely geometric protein structure search. *PLOS ONE* **14**:e0213712. doi:10.1371/journal.pone.0213712

Bileschi ML, Belanger D, Bryant DH, Sanderson T, Carter B, Sculley D, Bateman A, DePristo MA, Colwell LJ. 2022. Using deep learning to annotate the protein universe. *Nat Biotechnol* 1–6. doi:10.1038/s41587-021-01179-w

Buchfink B, Reuter K, Drost H-G. 2021. Sensitive protein alignments at tree-of-life scale using DIAMOND. *Nat Methods* **18**:366–368. doi:10.1038/s41592-021-01101-x

Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, Madden TL. 2009. BLAST+: architecture and applications. *BMC Bioinformatics* **10**:421. doi:10.1186/1471-2105-10-421

Devlin J, Chang M-W, Lee K, Toutanova K. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *arXiv:181004805 [cs]*.

Eddy SR. 2011. Accelerated Profile HMM Searches. *PLOS Computational Biology* **7**:e1002195. doi:10.1371/journal.pcbi.1002195

Elnaggar A, Heinzinger M, Dallago C, Rehawi G, Yu W, Jones L, Gibbs T, Feher T, Angerer C, Steinegger M, Bhowmik D, Rost B. 2021. ProtTrans: Towards Cracking the Language of Lifes Code Through Self-Supervised Deep Learning and High Performance Computing. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 1–1. doi:10.1109/TPAMI.2021.3095381

Gane A, Bileschi ML, Dohan D, Speretta E, Héliou A, Meng-Papaxanthos L, Zellner H, Brevdo E, Parikh A, Orchard S. 2022. ProtNLM: Model-based Natural Language Protein Annotation. https://www.uniprot.org/help/ProtNLM

Hamamsy T, Morton JT, Berenberg D, Carriero N, Gligorijevic V, Blackwell R, Strauss CEM, Leman JK, Cho K, Bonneau R. 2022. TM-Vec: template modeling vectors for fast homology detection and alignment. doi:10.1101/2022.07.25.501437

Heinzinger M, Weissenow K, Sanchez JG, Henkel A, Steinegger M, Rost B. 2023. ProstT5: Bilingual Language Model for Protein Sequence and Structure. doi:10.1101/2023.07.23.550085

Henikoff S, Henikoff JG. 1992. Amino acid substitution matrices from protein blocks. *Proc Natl Acad Sci U S A* **89**:10915–10919.

Holm L. 2022. Dali server: structural unification of protein families. *Nucleic Acids Research* gkac387. doi:10.1093/nar/gkac387

Jambrich MA, Tusnady GE, Dobson L. 2023. How AlphaFold shaped the structural coverage of the human transmembrane proteome. doi:10.1101/2023.04.18.537193

Johnson LS, Eddy SR, Portugaly E. 2010. Hidden Markov model speed heuristic and iterative HMM search procedure. *BMC Bioinformatics* **11**:431. doi:10.1186/1471-2105-11-431

Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, Tunyasuvunakool K, Bates R, Žídek A, Potapenko A, Bridgland A, Meyer C, Kohl SAA, Ballard AJ, Cowie A, Romera-Paredes B, Nikolov S, Jain R, Adler J, Back T, Petersen S, Reiman D, Clancy E, Zielinski M, Steinegger M, Pacholska M, Berghammer T, Bodenstein S, Silver D, Vinyals O, Senior AW, Kavukcuoglu K, Kohli P, Hassabis D. 2021. Highly accurate protein structure prediction with AlphaFold. *Nature* 1–11. doi:10.1038/s41586-021-03819-2

Kaminski K, Ludwiczak J, Alva V, Dunin-Horkawicz S. 2022. pLM-BLAST – distant homology detection based on direct comparison of sequence representations from protein language models. doi:10.1101/2022.11.24.517862

Katoh K, Standley DM. 2013. MAFFT Multiple Sequence Alignment Software Version 7: Improvements in
Performance and Usability. *Molecular Biology and Evolution* **30**:772–780.
doi:10.1093/molbev/mst010
Lin Z, Akin H, Rao R, Hie B, Zhu Z, Lu W, Smetanin N, Verkuil R, Kabeli O, Shmueli Y, dos Santos Costa A,
Fazel-Zarandi M, Sercu T, Candido S, Rives A. 2023. Evolutionary-scale prediction of atomic-level
protein structure with a language model. *Science* **379**:1123–1130. doi:10.1126/science.ade2574
Loewenstein Y, Raimondo D, Redfern OC, Watson J, Frishman D, Linial M, Orengo C, Thornton J,
Tramontano A. 2009. Protein function annotation by homology-based inference. *Genome Biology*
**10**:207. doi:10.1186/gb-2009-10-2-207
Mistry J, Chuguransky S, Williams L, Qureshi M, Salazar GA, Sonnhammer ELL, Tosatto SCE, Paladin L, Raj
S, Richardson LJ, Finn RD, Bateman A. 2021. Pfam: The protein families database in 2021. *Nucleic*
*Acids Research* **49**:D412–D419. doi:10.1093/nar/gkaa913
Pantolini L, Studer G, Pereira J, Durairaj J, Schwede T. 2022. Embedding-based alignment: combining
protein language models and alignment approaches to detect structural similarities in the
twilight-zone. doi:10.1101/2022.12.13.520313
Paszke A, Gross S, Massa F, Lerer A, Bradbury J, Chanan G, Killeen T, Lin Z, Gimelshein N, Antiga L,
Desmaison A, Köpf A, Yang E, DeVito Z, Raison M, Tejani A, Chilamkurthy S, Steiner B, Fang L, Bai
J, Chintala S. 2019. PyTorch: An Imperative Style, High-Performance Deep Learning Library.
doi:10.48550/arXiv.1912.01703
Petti S, Bhattacharya N, Rao R, Dauparas J, Thomas N, Zhou J, Rush AM, Koo P, Ovchinnikov S. 2023. End-
to-end learning of multiple sequence alignments with differentiable Smith–Waterman.
*Bioinformatics* **39**:btac724. doi:10.1093/bioinformatics/btac724
Richardson L, Allen B, Baldi G, Beracochea M, Bileschi ML, Burdett T, Burgin J, Caballero-Pérez J, Cochrane
G, Colwell LJ, Curtis T, Escobar-Zepeda A, Gurbich TA, Kale V, Korobeynikov A, Raj S, Rogers AB,
Sakharova E, Sanchez S, Wilkinson DJ, Finn RD. 2023. MGnify: the microbiome sequence data
analysis resource in 2023. *Nucleic Acids Research* **51**:D753–D759. doi:10.1093/nar/gkac1080
Rost B. 1999. Twilight zone of protein sequence alignments. *Protein Engineering, Design and Selection*
**12**:85–94. doi:10.1093/protein/12.2.85
Sanderson T, Bileschi ML, Belanger D, Colwell LJ. 2023. ProteInfer, deep neural networks for protein
functional inference. *eLife* **12**:e80942. doi:10.7554/eLife.80942
Schütze K, Heinzinger M, Steinegger M, Rost B. 2022. Nearest neighbor search on embeddings rapidly
identifies distant protein relations. *Frontiers in Bioinformatics* **2**.
Steinegger M, Meier M, Mirdita M, Vöhringer H, Haunsberger SJ, Söding J. 2019. HH-suite3 for fast remote
homology detection and deep protein annotation. *BMC Bioinformatics* **20**:473.
doi:10.1186/s12859-019-3019-7
Steinegger M, Söding J. 2017. MMseqs2 enables sensitive protein sequence searching for the analysis of
massive data sets. *Nat Biotechnol* **35**:1026–1028. doi:10.1038/nbt.3988
van Kempen M, Kim SS, Tumescheit C, Mirdita M, Lee J, Gilchrist CLM, Söding J, Steinegger M. 2023. Fast
and accurate protein structure search with Foldseek. *Nat Biotechnol* 1–4. doi:10.1038/s41587-
023-01773-0
Varadi M, Anyango S, Deshpande M, Nair S, Natassia C, Yordanova G, Yuan D, Stroe O, Wood G, Laydon A,
Žídek A, Green T, Tunyasuvunakool K, Petersen S, Jumper J, Clancy E, Green R, Vora A, Lutfi M,
Figurnov M, Cowie A, Hobbs N, Kohli P, Kleywegt G, Birney E, Hassabis D, Velankar S. 2022.
AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-
sequence space with high-accuracy models. *Nucleic Acids Research* **50**:D439–D444.
doi:10.1093/nar/gkab1061

Wheeler TJ, Clements J, Finn RD. 2014. Skylign: a tool for creating informative, interactive logos
representing sequence alignments and profile hidden Markov models. *BMC Bioinformatics* **15**:7.
doi:10.1186/1471-2105-15-7
Ye Y, Iovino BG. 2023. Protein Embedding based Alignment (preprint). Preprints.
doi:10.22541/au.168534397.72964200/v1
391