Title：

Stimulus representation in human frontal cortex supports flexible control in

working memory

Authors:

Zhujun Shao[1,2,3], Mengya Zhang[1,3], Qing Yu[1,*]

Affiliations:

[1]Institute of Neuroscience, Key Laboratory of Brain Cognition and Brain-inspired Intelligence

Technology, Center for Excellence in Brain Science and Intelligence Technology, Chinese Academy

of Sciences, Shanghai 200031, China

[2]University of Chinese Academy of Sciences, Beijing 100049, China

[3]These authors contributed equally

[*]**Correspondence should be addressed to:**

Qing Yu

Institute of Neuroscience, Key Laboratory of Brain Cognition and Brain-inspired Intelligence

Technology, Center for Excellence in Brain Science and Intelligence Technology, Chinese Academy

of Sciences, Shanghai 200031, China

Email: qingyu@ion.ac.cn

Keywords: visual working memory, cognitive flexibility, frontal cortex, visual cortex, fMRI,

recurrent neural network

Abstract

When holding visual information temporarily in working memory (WM), the neural representation of the memorandum is distributed across various cortical regions, including visual and frontal cortices. However, the role of stimulus representation in visual and frontal cortices during WM has been controversial. Here we tested the hypothesis that stimulus representation persists in the frontal cortex to facilitate flexible control demands in WM. During functional MRI, participants flexibly switched between simple WM maintenance of visual stimulus or more complex rule-based categorization of maintained stimulus on a trial-by-trial basis. Our results demonstrated enhanced stimulus representation in the frontal cortex that tracked demands for active WM control and enhanced stimulus representation in the visual cortex that tracked demands for precise WM maintenance. This differential frontal stimulus representation traded off with the newly-generated category representation with varying control demands. Simulation using multi-module recurrent neural networks replicated human neural patterns when stimulus information was preserved for network readout. Altogether, these findings help reconcile the long-standing debate in WM research, and provide empirical and computational evidence that flexible stimulus representation in the frontal cortex during WM serves as a potential neural coding scheme to accommodate the ever-changing environment.

Introduction

Real-world flexible behavior relies largely on working memory (WM), which allows the maintenance and manipulation of information in the brain in order to serve diverse behavioral goals (Baddeley, 2003). One central problem in the field of WM is to understand how stimulus information is represented and maintained in WM. Over the past decade, mounting evidence has demonstrated stimulus-specific representation during WM maintenance in a distributed cortical network, including sensory, parietal, and frontal cortices (Christophel et al., 2012; Ester et al., 2015; Gosseries et al., 2018; Harrison & Tong, 2009; Riggall & Postle, 2012; Serences et al., 2009; Sprague & Serences, 2013; Yu & Shim, 2017, 2019). However, the exact nature and functions of stimulus representation in different cortical regions remain controversial. Specifically, while neurophysiological studies in non-human primates have mostly emphasized stimulus representation in the frontal cortex (Funahashi et al., 1989; Fuster & Alexander, 1971; Leavitt et al., 2017), neuroimaging work in humans has reported disparate findings. During maintenance of simple visual features, stimulus representation is robustly encoded in the early visual cortex (EVC), which has been taken as the evidence in support of the sensorimotor recruitment hypothesis of WM (Harrison & Tong, 2009; Riggall & Postle, 2012; Serences et al., 2009). Meanwhile, those in the higher-order frontoparietal cortex are typically weaker and less stable (Emrich et al., 2013; Gosseries et al., 2018; Riggall & Postle, 2012; Yu & Shim, 2019). However, in dynamic environments such as those involving distraction, stimulus representation in EVC could be greatly interrupted or biased (Bettencourt & Xu, 2016; Hallenbeck et al., 2021;

Lorenc et al., 2018). In contrast, stimulus representation in the frontal cortex could be

robust under certain circumstances including attentional prioritization (Christophel et

al., 2018), categorization (Lee et al., 2013) and after extensive training (Miller et al.,

2022). To summarize, stimulus representation could vary markedly depending on

specific brain regions and memory tasks, complicating the interpretation of potential

functions of stimulus representation in WM.

In this study, we consider these apparent discrepancies from the perspective of

cognitive flexibility (Badre et al., 2021; Fusi et al., 2016; Musslick & Cohen, 2021).

We propose that changes in stimulus representation in different cortical regions might

reflect a global reconfiguration in coding strategy and resource allocation in response

to varied WM functions (Henderson et al., 2022; Lee et al., 2013). To elaborate, beyond

the passive maintenance of incoming sensory information, WM provides an online

mental workspace for active manipulation and control of stimulus contents (Baddeley,

2003; Miller & Cohen, 2001). As control functions often result in the generation and

maintenance of new information, the brain needs to manage not only the original

stimulus information but also the newly generated information in WM. Due to the

limited cognitive resources available, it is likely that original stimulus representation in

WM could adapt flexibly to various task goals beyond simple maintenance of WM

contents, which might also co-vary with changes in the representation of the newly-

generated information, leading to a systematic reconfiguration in representations of all

levels across various cortices. We make two specific predictions from this account. First,

in accordance with the findings of elevated neural activity in the frontal cortex with

increasing demand for memory manipulation (D'Esposito et al., 1999; D'Esposito et al.,

2000) and cognitive control (Badre, 2008; Badre et al., 2010; Miller & Cohen, 2001),

stimulus representation in frontal cortex should be enhanced for active-control-related

functions in WM. By contrast, due to the precise nature of stimulus representation in

visual cortex, stimulus representation in this region should be enhanced for precise-

maintenance-related functions in WM (Henderson et al., 2022; Lee et al., 2013). Second,

within the brain regions that encode the newly generated information, a dynamic

tradeoff between representations of original and new information should be observed

to achieve flexible allocation of limited cognitive resources (Badre et al., 2021; Flesch

et al., 2022).

Using functional magnetic resonance imaging (fMRI), we directly tested this

account by systematically investigating stimulus representation in visual, parietal, and

frontal cortices during WM tasks with varying demands for active control. In particular,

we surmised that stimulus representation in the frontal cortex would increase to

accommodate complex control demands such as rule-based categorization. To this end,

we employed a visual WM paradigm that required flexible switching between

maintenance and categorization tasks. Specifically, in the maintenance task,

participants maintained one visual orientation throughout a delay period, whereas in the

categorization task participants were required to categorize the remembered orientation

into one of two categories in accordance with previously learned rules, which could be

either switched randomly between two rules on a block-by-block basis (Experiment 1)

or fixed with one rule (Experiment 2). Thus, compared with the maintenance task, the

categorization task imposed additional control demand of WM information at two

different levels: the first level of control being stimulus categorization, because

participants needed to adapt the stimulus based on the categorization rule in working

memory for subsequent category judgements; the second level of control being

flexibility of rules, because with two categorization rules, the flexibility in control

increased.

In line with our prediction, our results showed that stimulus information was more

prominently represented in the frontal cortex during categorization than maintenance

task, and this differential representation was enhanced with increasing demands for

control. Importantly, the strength of stimulus representation in the frontal cortex was

predictive of WM behavioral performance in the categorization but not in the

maintenance task, implicating a selective involvement of the frontal cortex in control

functions. By contrast, stimulus representation in the visual cortex was found to exhibit

an opposite pattern, with higher strength for maintenance than for categorization task.

Moreover, varying control demands across experiments revealed a dynamic tradeoff

between stimulus and the newly-generated category representations. To further

examine whether the enhanced stimulus representation in the frontal cortex during

categorization task could be explained by global coding strategy, we simulated our

flexible WM tasks with multi-module recurrent neural networks (RNNs). The results

of this computational modeling well replicated our human data when precise stimulus

information was preserved at the output during network training. Taken together, our

results indicate the importance of the frontal cortex for flexible control in WM and

highlight the relative changes of stimulus representation in different cortical regions for

varying task demands of WM.

Results

Behavioral learning and performance of WM tasks

In the fMRI session of Experiment 1, human participants (n = 24) completed two

tasks, maintenance and categorization, inside an MRI scanner. The maintenance task

was a delayed match-to-sample working memory task of orientations. Participants only

needed to maintain the cued orientation throughout a memory delay. In categorization

task, participants also started with maintaining an orientation. After the task cue, they

needed to categorize the remembered orientation into one of two categories using the

cued categorization rule. Within an experimental block of nine trials, participants

randomly switched between the two tasks. Across blocks, participants randomly

switched between two categorization rules acquired during a preceding learning session.

We randomized response mapping across trials to avoid potential influence by motor-

planning signals (see Figure 1A for probe design). Prior to the main session, participants

first completed a behavioral learning session to learn two categorization rules (Rule A

and Rule B, see Figure 1B) that were orthogonal to each other. Participants acquired

the two rules with equal familiarity ($t(23) = 0.24$, $p = 0.813$; for Rule A, $M = 0.85$, SD

$= 0.050$; for Rule B, $M = 0.85$, $SD = 0.05$; Figure 1C) and comparable precision

(averaged error in reported boundaries for Rule A were $8.80° \pm 6.29°$ and that for Rule

B was $9.02° \pm 5.69°$; Figure 1D).

Figure 1. Experimental design and behavioral performance.

(A) Main task procedure. Each block started with a rule cue indicating the categorization rule for this block. On each trial, participants saw two orientations consecutively and were then cued to remember one of the orientations. In maintenance task (cued by letter "P"), participants needed to maintain the remembered orientation as precisely as possible. In categorization task (cued by letter "C"), participants needed to categorize the remembered orientation following the categorization rule of the current block. Maintenance and categorization trials were interleaved within an experimental block of nine trials. Categorization rule (Rule A or Rule B) switched randomly on a block-by-block basis. Response keys ("F" and "J") for categorization task were randomly assigned to the two categories. Each pair of keys displayed at random locations within the category to eliminate information on rule boundaries. (B) Illustration of the two orthogonal categorization rules (Rule A and Rule B). (C) Rule learning performance during learning session for Rule A (purple) and Rule B (pink). (D) Errors in participants' self-reported rule boundaries. Errors were calculated as the average distance from reported boundaries to ground truth boundaries. (E) Accuracy compared between tasks. Boxplots show the median and the 25th and 75th percentiles.

Whiskers extend to 1.5 Inter quartile range (IQR) from the quartiles. Asterisks denote
significant results, n.s.: not significant; **: $p < 0.01$. (F) Reaction time compared
between tasks. Same conventions as (E). (G) Upper panel: accuracy in relation to
distance from categorization boundaries. Lower panel: reaction time in relation to
distance from categorization boundaries. Shaded areas represent ± SEM.

Overall, participants performed equally well on both tasks in the fMRI session.

Accuracy for the maintenance task ($M \pm SD$: 0.81 ± 0.07) and that for the categorization

task (0.82 ± 0.05) did not significantly differ ($t(23)$ = 1.51, p = 0.144; Figure 1E),

suggesting that the two tasks were matched in terms of task difficulty. In line with

previous categorization studies demonstrating a boundary effect (Ester et al., 2020;

Freedman & Assad, 2006), only in the categorization task but not in the maintenance

task did participants perform better for trials distant from category boundaries in terms

of both accuracy and reaction time (see Figure 1G). These results demonstrated the

effect of categorization and confirmed that participants faithfully followed task

instructions.

Enhanced stimulus representation in frontal cortex during categorization task

The primary goal of this study was to determine the role of stimulus representation

in various cortices in WM. Using conventional multivariate encoding and decoding

methods, we tracked stimulus (i.e., orientation) representation in three brain regions of

interest (ROIs) that have been implicated in representing WM information, including

early visual cortex (EVC), intraparietal sulcus (IPS), and superior precentral sulcus

(sPCS) (Christophel et al., 2018; Ester et al., 2015; Hallenbeck et al., 2021; Yu & Shim,

2017), see Figure S1 for a visualization of the anatomical locations of the ROIs.

First, we used multivariate inverted encoding models (IEMs) (Brouwer & Heeger,

2009, 2011; Ester et al., 2015; Rademaker et al., 2019; Yu & Shim, 2017) to reconstruct

orientation representation at the population level in each ROI. Figure 2A shows

example orientation reconstructions from representative time points. To quantify the

strength of orientation reconstructions, we calculated the reconstruction fidelity by first

projecting the channel response at each orientation onto a vector at the cued orientation

and then averaging the projected vectors to obtain the representational fidelity

(Rademaker et al., 2019). A larger fidelity value indicates a stronger positive

representation of orientation (See Figure 2B for illustration). Figure 2C demonstrates

the time course of orientation reconstruction as quantified by representational fidelity.

Critically, by comparing the representational fidelity values within the same ROI across

conditions (maintenance vs. categorization), we minimized the impact of effect size on

our comparisons between ROIs, as all the comparisons were primarily performed

within the same ROI with a comparable effect size. In EVC, we found significant

orientation representation in both maintenance and categorization tasks starting from

the sample period (Figure 2C left panel; see Supplemental Table 1 for full statistics),

even when the categorization task did not require explicit memory of stimulus

information. Additionally, the strength of orientation representation in the maintenance

task became significantly higher than that in the categorization task after the task cue

during the delay, suggesting the strength of orientation representations in EVC reflected

the degrees of task demands for maintaining visual details. In IPS, orientation

representation was significant in both tasks, but did not differ from each other at most

time points (Figure 2C middle panel). In sPCS, a reversed pattern was observed. In the

maintenance task, orientation information was maintained during early delay period

and then dropped to baseline level during late delay period. By contrast, in the

categorization task, orientation representation was persistent throughout the delay and

response periods. The strength of orientation representation in the categorization task

became statistically higher than that in the maintenance task in late delay period (Figure

2C right panel), suggesting that this differential representations of visual stimulus in the

frontal cortex reflected the demand for active control of memory contents. To facilitate

comparison of the differential stimulus representation across ROIs, we averaged the

difference in representational strength across a late task epoch (11 – 16 s), and the

difference in stimulus representation between ROIs remained (Figure 2D).

Figure 2. Orientation reconstructions at the population level using IEMs.
(A) Reconstructed population-level orientation representations from selected time points at EVC, IPS, and sPCS for maintenance (blue) and categorization (orange) tasks, respectively. X axis represents distance from the cued orientation (at 0º), and y axis represents reconstructed channel responses in arbitrary units. Significant orientation representation was observed at 6 s and 12 s but not at 0 s. Shaded areas represent ± SEM. (B) To quantify the strength of orientation reconstructions, we calculated the reconstruction fidelity by first projecting the channel response at each orientation onto a vector at the cued orientation and then averaging the projected vectors. (C) Time course of representational strength of orientations at EVC, IPS and sPCS. Gray shaded areas indicate the entire memory delay following task cue. Blue and orange dots at the bottom indicate the FDR-corrected significance of representational fidelity at each time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). The bottom black dots indicate significant difference in representational fidelity between tasks (uncorrected). Horizontal dashed lines represent a baseline of 0. Shaded areas represent ± SEM. (D) Average difference of representational strength across 11 – 16 s in each ROI (from EVC to sPCS: $p < 0.00001$, $p = 0.063$, $p = 0.007$, respectively). Positive difference indicates higher representational strength for categorization, and

vice versa for negative difference. Black asterisks denote FDR-corrected significance, **: $p < 0.01$; ***: $p < 0.001$.

We validated the difference in stimulus representations through a series of control analyses. First, we demonstrated that these results cannot be explained by the specific model used to train the data (Liu et al., 2018; Sprague et al., 2018) nor the specific analytical approach used, because similar patterns were observed when we trained the IEM separately for each condition (Figure S2A) or adopted a Support Vector Machine (SVM) decoding approach (Figure S2B) (Henderson et al., 2022; Rademaker et al., 2019). Mean activation differences between tasks cannot account for the results either, because when we removed the mean differences in BOLD activity between tasks, the difference in representational strength remained (Figure S2C). Furthermore, to remove the potential impact of voxel number on IEM, we selected the top 500 of most sample- or delay-selective voxels from each ROI and trained IEM using the selected voxels. Again, this analysis yielded similar findings (Figure S2D). Lastly, when repeating the IEM analyses in primary motor cortex (M1), no similar patterns were observed, suggesting that our results cannot be explained by motor- or response-related activity (Figure S3).

Together, these results demonstrated enhanced stimulus representation in the frontal cortex with increased demand for active control, as well as those in the visual cortex with increased demand for precise WM maintenance.

Prediction of categorization behavior by frontal stimulus representation

Previous WM studies have shown that the strength of stimulus representation in

EVC positively correlated with memory performance (Emrich et al., 2013; Ester et al.,

2013; Gosseries et al., 2018), suggesting that EVC plays an important role in precise

WM maintenance. However, stimulus representation in the frontal cortex rarely

predicted behavioral performance in maintenance task (Hallenbeck et al., 2021),

although univariate activation in the same brain region can predict memory-guided

saccade performance (Curtis et al., 2004). Nevertheless, if frontal stimulus

representation is involved in WM control, its behavioral relevance should be subject to

observation with increased control demands. Therefore, we assessed the behavioral

predictability of stimulus representation during the delay period in EVC, IPS, and sPCS.

Figure 3A, 3B, and 3C illustrate the time course of correlation results, results from

representative time points, and results collapsed across the late epoch, respectively.

Consistent with previous findings, we found the strength of stimulus representation in

EVC during the early delay period predicted behavioral accuracies in both maintenance

and categorization tasks (see Supplemental Table 2 for full statistics). Similar

predictability was found in IPS, with stimulus representation predicted behavior in the

maintenance task during early delay and in the categorization task throughout the entire

memory delay. Interestingly, we found that, throughout the entire memory delay, the

strength of stimulus representation in sPCS predicted behavioral accuracies only in the

categorization task but not in the maintenance task. These results highlighted the

functional significance of stimulus representation in sPCS exclusively for the

categorization task.

Figure 3. Behavioral correlation of stimulus representation for maintenance (blue) and categorization (orange) tasks.

(A) Time course of correlation coefficients between behavioral performance and orientation representational fidelity in EVC, IPS, and sPCS. Gray shaded areas indicate the entire memory delay following task cue. Blue and orange dots at the top indicate significance of correlation (uncorrected) at each time point at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). (B) Correlation scatter plots at representative time points (7 s and at 12 s) in EVC, IPS, and sPCS. R denotes Pearson correlation coefficients. (C) Correlation between behavioral performance and orientation representational fidelity collapsed across the late epoch (11 – 16 s). Asterisks denote significant results, *: $p < 0.05$; **: $p < 0.01$.

Reduced frontal stimulus representation with lower control demand

In Experiment 1, participants flexibly switched between two categorization rules

to prompt the manipulation of WM content on a trial-by-trial basis. The rule switching

increased control demand but also complicated the interpretation of our results. To

exclude potential impact of rule switching, we conducted Experiment 2, in which

participants performed maintenance and categorization tasks with only one fixed rule.

Behavioral results of Experiment 2 again demonstrated a classic boundary effect and

were comparable to Experiment 1, with no significant difference between experiments

in terms of either accuracy or reaction time (Fs < 1.28, ps > 0.26; Figure S4). When

using IEMs to reconstruct stimulus representation, we found EVC and IPS both showed

patterns similar to those in Experiment 1 (Figure 4A left and middle panels), with

stimulus representation decreased in EVC in categorization task and remained at the

same level in IPS between the two tasks (see Supplemental Table 3 for full statistics).

The frontal region, sPCS, also showed a differential enhancement of stimulus

representation in categorization task as in Experiment 1, but in an earlier period (Figure

4A right panel). To validate such a temporal difference, we defined an additional early

task epoch (5 – 10 s), and confirmed a significant difference in stimulus representation

in sPCS during the early ($p = 0.015$; Figure 4B) but not during the late epoch ($p = 0.372$;

Figure 4C). In addition, we performed a mixed ANOVA on experiments (Experiment 1

vs. 2) and epochs (early vs. late epoch) and observed a significant interaction effect

between the two, $F(1, 46) = 7.43$, $p = 0.009$, suggesting that the two experiments

differed in terms of the temporal emergence of the differential stimulus representation

in the frontal cortex. Taken together, these results are consistent with our expectation

that, with reduced control demand, the differential enhancement of stimulus

representation in frontal cortex was still present but decreased during late memory delay.

Nevertheless, stimulus representation in Experiment 2 still predicted behavioral

performance as in Experiment 1, although the difference between task was reduced

(Figure S5).

Figure 4. Orientation reconstructions in Experiment 2 at the population level using IEMs.

(A) Time course of representational strength of orientations at EVC, IPS and sPCS. Gray shaded areas indicate the entire memory delay following task cue. Blue and orange dots at the bottom indicate the FDR-corrected significance of representational fidelity at each time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). The bottom black dots indicate significant difference in representational fidelity between tasks (uncorrected). Horizontal dashed lines represent a baseline of 0. Shaded areas represent ± SEM. (B) Average difference of representational strength across an early (top, 5 – 10 s) and a late (bottom, 11 – 16 s) task epoch in each ROI. Positive difference indicates higher representational strength for categorization, and vice versa for negative difference (FDR-corrected). *: $p < 0.05$; ***: $p < 0.001$.

Category representation in WM in various cortices

Having observed a differential representation of stimulus in the frontal cortex, we next asked how newly generated information in WM during the categorization task emerged and sustained in the distributed WM network and how representations of the original stimulus and new information interacted. The categorization task could demand additional generation of category information in WM. We therefore trained SVMs to decode category information during the categorization task. For each rule, the SVM decoder was trained to discriminate between the two categories. In both experiments, we found that during the late epoch, category information could be well decoded across

ROIs ($ps < 0.044$, Figure 5A; also see Figure S6A for full decoding time course), with

a marginal difference between experiments in sPCS ($p = 0.055$).

One might argue that the category decoding results could at least be partially

attributed to stimulus similarity. To minimize the impact of stimulus similarity on

category decoding, we additionally trained another decoder using the opposite rule (i.e.,

using category labels from the orthogonal rule; see Figure 5B for results). We then

calculated an abstract category index by subtracting decoding accuracy under the

opposite rule from that under the true rule (Mok & Love, 2020) (Figure 5C). The

rationale was that the amount of stimulus similarity would be comparable for the

opposite rule, but additional category information, if existed, should result in higher

decoding accuracy for the true rule. In other words, positive abstract category index

indicates evidence for stimulus-independent category representation. After removing

stimulus-related signals, average decoding performance of abstract category was only

evident in Experiment 2 ($ps < 0.017$) but not in Experiment 1 ($ps > 0.14$) for all ROIs.

Moreover, decoding performance of abstract category was significantly higher in

Experiment 2 than Experiment 1 in sPCS ($p = 0.034$; Figure 5D). These results together

suggest a potential tradeoff between stimulus difference and category representation in

the frontal cortex.

Figure 5. Decoding performance for category and abstract category information.
(A) Average category decoding accuracy using category labels under true rule across
the late task epoch (11 – 16 s) in each ROI of both experiments. (B) Average category
decoding accuracy using category labels under orthogonal rule across the late task
epoch (11 – 16 s) in each ROI of both experiments. (C) Schematic illustration of abstract
category decoding. In categorization task, category information can be decoded using
category labels according to the true categorization rule. On the other hand, category
can also be decoded due to stimulus similarity. Thus, to remove stimulus-dependent
categorical information, we calculated an abstract category index by removing
decoding accuracy using orthogonal category boundaries (assuming comparable
stimulus-dependent effect) from that using true rule boundaries. (D) Average abstract
category decoding index across the late task epoch (11 – 16 s) in each ROI of both
experiments. Black asterisks denote FDR-corrected significance, *: $p < 0.05$; **: $p <$
0.01; ***: $p < 0.001$.

Lastly, for completeness, we repeated the IEM and category decoding analyses on

additional ROIs in the frontal cortex, to investigate whether the observed results were

specific to sPCS. Specifically, we defined three additional ROIs based on the HCP atlas

(Glasser et al., 2016), including the inferior precentral sulcus (iPCS), inferior frontal

sulcus (IFS), and middle frontal gyrus (MFG) (Ester et al., 2015; Mackey et al., 2017;

Yu & Shim, 2017). Overall, results in the three ROIs were comparably weaker than

sPCS (Figure S7). There was some indication that the MFG might share some results

for orientation representation and category decoding, although this pattern was weaker

and was only observed in some analyses in Experiment 2.

Differential stimulus representation in frontal cortex replicated by RNN modeling

Finally, we tested how stimulus representation could emerge in frontal cortex at the

mechanistic level using recurrent neural network (RNN) models. Our hypothesis is that

precise stimulus representation during WM might emerge in frontal cortex in response

to complex task demands such as rule-based categorization. In other words, instead of

relying (solely) on category representations, the cortical network might have adopted a

different strategy to accommodate the flexible task requirements in the current study,

for instance, by preserving stimulus information until a later stage of information

processing. This different strategy can be implemented by altering the RNN's output

structure. Therefore, the logic of this modeling analysis was to examine whether

explicitly placing a demand for the model to preserve stimulus representation would

recapitulate our fMRI findings in frontal cortex, in comparison to a model that did not

specify such a demand.

Two types of modular RNNs were trained on the maintenance and categorization

tasks simultaneously (Masse et al., 2019; Zhou et al., 2021). The networks shared

common input and hidden layer structures (i.e., orientation-tuned and retro/task cue-

related units as the input layer, recurrent units with short-term synaptic plasticity in the

hidden layer [80% excitatory + 20% inhibitory units, equally distributed in three

separate modules]). The only difference was in the structure of the output layer. The

first type of RNN (RNN1; n = 20) had only two units in the output layer to indicate

networks' choice (Figure 6A), whereas the second type of RNN (RNN2; n = 20) had

additional units in the output layer corresponding to the original stimulus information.

In other words, the second RNN was designed to maintain stimulus information

throughout the network modules. For the common hidden layer, we included three

hierarchically organized (posterior, middle, and anterior) modules of recurrent units

generated according to neurobiological principles of neuronal connections (e.g., denser

connectivity within than between modules) to simulate the interconnected brain areas

in our ROI-based fMRI analyses above: the posterior module (Module 1, simulating

EVC) was directly connected with the input layer, the middle module (Module 2,

simulating IPS) received projections from the posterior module and relaying

information to the anterior module, and the anterior module (Module 3, simulating

sPCS) projected to the output layer. Task events were simulated as numerical inputs to

the model, matching the procedures of Experiment 1 (see Methods for details).

After successful training, defined as reaching at least 90% accuracies in all tasks in

the same training batch, we applied an SVM decoding approach to investigate

population-level stimulus representations in neuronal spiking activities of the RNNs.

We found that in RNN1, both the middle and anterior modules showed stronger

stimulus representation in the maintenance task than the categorization task during the

delay period ($p_{posterior} = 0.09$, $p_{middle} = 0.011$, $p_{anterior} = 0.007$; Figure 6B upper panel),

opposite to our fMRI observation in IPS and sPCS (Figure 6B inset). In comparison,

decoding performance in RNN2, which was explicitly required to maintain stimulus

information for the output, yielded results consistent with our human findings, with

increased stimulus decoding performance during categorization only in the anterior

module ($p_{posterior} = 0.436$, $p_{middle} = 0.212$, $p_{anterior} = 0.026$; Figure 6B lower panel).

Besides the difference in stimulus representation, we further tested whether RNN2

could also replicate the human results on category representation. For this analysis we

focused on abstract category representation to fully remove the impact of stimulus on

category decoding. To examine the influence of control demand on category decoding,

following our fMRI experiment we trained 20 additional RNNs with the same output

structure as RNN2 (preserving stimulus information) to perform the tasks with a fixed

categorization rule, mimicking the task structure of Experiment 2. Consistent with our

human findings, we observed increased abstract category decoding performance in the

fixed-rule models compared to the flexible-rule RNNs, throughout the modules

($p_{posterior} = 0.045$, $p_{middle} = 0.003$, $p_{anterior} < 0.001$; Figure 6C lower panel). Similar

differences between fixed-rule and flexible-rule models were also observed in RNN1

(all ps < 0.001; Figure 6C upper panel).

Altogether, these findings demonstrated that our fMRI results could be simulated

by RNN models when stimulus information for readout was preserved, suggesting that

the requirement for flexible control of WM content could demand high-fidelity stimulus

representation at the output stage of the model. Notably, we found that RNN2 generally

took fewer iterations for training and had fewer failures in learning the task (with a

defined maximal number of iterations).

Figure 6. Architecture of RNNs and simulation results.

(A) All networks consist of 3 layers of artificial units: the input, hidden and output layers. For both RNN1 and RNN2, the input layer contains 20 units including 15 orientation-tuned units (red) and 5 cue units (retro-cue and task cue, orange and yellow). The hidden layer consists of three modules of 200 recurrent units with short-term synaptic plasticity (STSP), further divided into 80% excitatory (black) and 20% inhibitory (white). Connectivity within each module (black arrow) is denser compared to between modules (red and green arrows), which only occur between excitatory units. Only excitatory units in Module 1 receive projections from the input layer and only excitatory units in Module 3 project to the output units. For RNN1, networks output (0,1) or (1,0) through the 2 units in the output layer to indicate responses. For RNN2, the network output (0,1) or (1,0) to report the category to which the cued orientation belonged in the categorization task, or (0,0) in the maintenance task (blue units). Importantly, the models also output the orientation itself through 15 additional

orientation-tuned units (red). (B) Difference in stimulus decoding between tasks in RNN1 (upper panel) and RNN2 (lower panel). Results were averaged across the delay period. Positive difference indicates higher decoding accuracy for categorization, and negative difference indicates higher decoding accuracy for maintenance. The inset above illustrates stimulus difference in human fMRI results during late epoch in Experiment 1 to provide a reference for expected patterns in RNNs. (C) Average abstract category information across the delay period for RNN1 (upper panel) and RNN2 (lower panel). The inset above illustrates abstract category representation in human fMRI. Error bars represent ± SEM. Black asterisks denote FDR-corrected significance, *: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$.

Discussion

In this study, we investigated the emergence and maintenance of stimulus representation with varied control demands of WM. In a distributed human cortical network encompassing visual, parietal, and frontal cortex, we found enhanced stimulus representations in the frontal cortex that tracked increasing demands on active WM control, as well as enhanced stimulus representations in the visual cortex that tracked the demand for the precise maintenance of WM content. The enhanced stimulus representation in frontal cortex was well predicted by RNNs that preserved stimulus information for readout at the output stage. Together, these results highlight the unique and critical contributions of stimulus representations in different cortical regions for distinct aspects of WM, and help to resolve the current controversy in the roles of various cortices in WM.

Role of visual cortex in WM maintenance

The visual cortex has been considered a critical site for maintaining visual WM in the context of sensorimotor recruitment hypothesis (D'Esposito & Postle, 2015;

Harrison & Tong, 2009). This idea, however, has been challenged in recent years due

to some seemingly contradictory findings from the human neuroimaging studies. For

example, compared to the frontoparietal cortex, mnemonic representations in EVC

were found to be more vulnerable to distractors (Bettencourt & Xu, 2016; Hallenbeck

et al., 2021; Lorenc et al., 2018). The decodability of memory contents in visual cortex

also depends on the specific task type. A previous study showed that in nonvisual tasks

that required judgements on object category instead of visual details, memory contents

were no longer decodable in the visual cortex (Lee et al., 2013). In this study, we found

that, although the strength of stimulus representation in EVC differed between WM

maintenance and categorization tasks, a copy of stimulus representation remained in

EVC during the categorization task. Moreover, stimulus representations in both tasks

were equally predictive of subsequent memory performance, suggesting the functional

significance of EVC representations in WM.

The discrepancy between our results and that of the previous work (Lee et al.,

2013) could be attributed to the fact that our categorization task required participants to

manipulate remembered information according to arbitrary yet flexible categorization

rules, rather than simply paying selective attention to different aspects (visual details

vs. category membership) of everyday objects. In our case, maintaining visual details

of the memoranda was critical for accurate behavioral responses. Our finding is

consistent with the prediction of sensorimotor recruitment hypothesis that

representation of memory contents in the visual cortex is necessary for the precise

maintenance of visual information. The observation of robust category representation

in EVC during the response period further indicated the recruitment of EVC in

categorization, possibly for boundary comparison and rule implementation. In fact, our

results are consistent with a recent study demonstrating significant stimulus

representation in EVC even when memoranda had been transformed into a motor

format (Henderson et al., 2022). In addition, electrophysiological research in non-

human primates has also shown robust feature selectivity in the visual cortex during a

categorization task (Brincat et al., 2018), and recent computational modeling work has

suggested intact maintenance of sensory information during categorical judgements

(Luu & Stocker, 2021).

Role of frontal cortex in active WM control

Compared to the prominent role of EVC in memory maintenance, sPCS in the

frontal cortex played a dominant role in WM tasks that require active control of memory

contents such as categorization. Although stimulus representations in sPCS have been

observed during WM in previous studies, the nature of these representations remained

debatable. In WM tasks that required mere maintenance of memoranda, stimulus was

not always decodable in the frontal cortex (Emrich et al., 2013; Gosseries et al., 2018;

Riggall & Postle, 2012), raising the issue of functional significance of stimulus

representation in the frontal cortex. On the other hand, stimulus representation in the

frontal cortex could become robust in the face of tasks that require attentional

prioritization and extensive training (Bettencourt & Xu, 2016; Christophel et al., 2018;

Hallenbeck et al., 2021; Lorenc et al., 2018; Miller et al., 2022). Our current study

contributes to the resolution of this issue by demonstrating that stimulus representation

in sPCS increased with increasing demands for WM control. This finding is in line with

recent computational studies proposing that active WM functions may involve neuronal

mechanisms different from that for passive maintenance. For example, passive

maintenance could rely mainly on synaptic plasticity mechanisms, whereas active

control functions such as distractor resistance and information manipulation involve

more neuronal spiking activity (Masse et al., 2019; Wang, 2021). In this study, we

provided the first empirical evidence that the frontal cortex exhibits enhanced stimulus

representation in categorization task requiring active WM control and this

representation is predictive of WM performance. In contrast, stimulus representation of

WM maintenance failed to predict WM performance at high control demand. Moreover,

by examining additional ROIs in the frontal cortex (i.e., iPCS, IFS, and MFG), we

found that results in these brain regions were overall weaker, with the MFG

demonstrating the most comparable, albeit much weaker, results to sPCS. The specific

involvement of sPCS in our experiment could be due to the type of stimulus (i.e.,

orientation) we used, as previous work has highlighted a prominent role of sPCS in

encoding stimulus-specific information in spatial (Hallenbeck et al., 2021; Sprague &

Serences, 2013) and orientation working memory (Ester et al., 2015; Yu & Shim, 2017,

2019), but to a lesser extent in other working memory tasks such as color (Yu & Shim,

2017, 2019). It would be of interest to further investigate whether this active control in

the sPCS could be generalized to other frontal regions and tasks that require other types

of WM control such as mental rotation (Shi & Yu, 2024), and how other types of control

task may adapt to changing flexible control demands.

WM representations in frontal cortex support cognitive flexibility

Our results in the frontal cortex are also in line with recent theoretical proposals in

the field of cognitive flexibility. To behave flexibly in complex environments with

limited cognitive resources, two mechanisms have been proposed: low-dimensional

abstraction of stimulus representation for generalization and efficient learning, and

high-dimensional stimulus representation for separability and flexible readout (Badre

et al., 2021; Flesch et al., 2022; Fusi et al., 2016). Within this framework, high-

dimensional stimulus representations during WM might emerge in the frontal cortex in

response to complex control demands such as rule-based categorization. The results of

the two fMRI experiments in the current study jointly demonstrate a dynamic tradeoff

between high-dimensional stimulus and low-dimensional category representations

depending on the control demand. Specifically, when control demand was reduced with

a single categorization rule in Experiment 2 compared to Experiment 1, the differential

stimulus representation in the frontal cortex was also reduced during the late delay

period, accompanied by an increase in category decoding performance especially in the

frontal cortex. This result is consistent with neurophysiological findings in non-human

primates: while robust category selectivity was observed in frontoparietal cortex during

the delay period of categorization tasks when the animal was trained on the

categorization task only (Brincat et al., 2018; Freedman & Assad, 2006; Freedman et

al., 2001; McKee et al., 2014), category selectivity in the parietal cortex was significantly reduced when the animal had been exposed to a maintenance task prior to categorization training (Latimer & Freedman, 2023). Our RNN simulation further confirmed that this dynamic reconfiguration in information coding at the network level can be well explained by a change in the coding strategy for the network readout. In other words, in flexible environments, and with rich prior experience, the brain might adopt an entirely different strategy for processing information in WM. High-dimensional stimulus information might be preserved in its original identity in the higher-order cortex, potentially reducing processing demands in dealing with each task and thereby facilitating efficiency and flexibility (Badre et al., 2021; Flesch et al., 2022; Fusi et al., 2016). One important future direction would be to further address the meta-control mechanisms that determine the flexible selection of coding strategies for WM (Eppinger et al., 2021).

Differentiating between frontal and parietal cortex in WM functions

While many previous WM studies have focused on the functional distinction between sensory and frontoparietal cortex, it has remained less clear how frontal and parietal cortex might differ in terms of WM functions. Some studies have reported stimulus representations with similar functionality in frontal and parietal cortex (Christophel et al., 2018; Yu & Shim, 2019), while others have observed differential patterns (Hu & Yu, 2023; Lee et al., 2013; Li et al., 2023). We interpret the differential patterns as reflecting a difference in the potential origin of the corresponding cognitive

functions. For example, in our study, sPCS demonstrated the most prominent effect for

enhanced stimulus representation during categorization as well as the tradeoff between

stimulus difference and category representation, suggesting that sPCS might serve as

the source region for such effects. On the other hand, IPS did show visually similar

patterns to sPCS in some analyses. For instance, stimulus representation in IPS was

visually but not statistically higher in the categorization task. Additionally, stimulus

representation in IPS also predicted behavioral performance in the categorization task.

These results together support the view that our findings in sPCS do not occur in

isolation, but rather reflect a dynamic reconfiguration of functional gradients along the

cortical hierarchy from early visual to parietal and then to frontal cortex.

The alignment between RNN and fMRI results

Although the current RNNs effectively captured our key fMRI findings, including

increased stimulus representation in the frontal cortex as well as the tradeoff in category

representation with varying control demands, we acknowledge that differences remain

between the two modalities. For instance, all three RNN modules demonstrated

significant abstract category decoding as well as difference in category decoding

between experiments, which differed from our fMRI results. This discrepancy could

partially be due to the higher signal sensitivity in RNNs. In addition, RNN2 did not

show decreased stimulus decoding for categorization in the EVC module. However, we

found that applying IEMs to the RNN data revealed a similar negative trend in the EVC

module (Figure S8), though it was not statistically significant. This result suggests that

any negative difference between categorization and maintenance in EVC module was

weaker compared to fMRI, if existed. We speculate that enhancing the negative

difference in the EVC module might require additional modules or inputs to strengthen

fine-grained stimulus representation in EVC, a mechanism that could be of interest for

future research.

Conclusion

In conclusion, we observed a distributed cortical network, including early visual,

parietal, and frontal cortex, in representing stimulus-specific information in WM. These

stimulus representations in visual and frontal cortex played distinct functional roles,

with those in EVC contributing primarily to precise maintenance and those in frontal

cortex contributing primarily to active control in WM. RNN simulations indicated that

the stimulus representation in the frontal cortex might have emerged as a result of output

selection to facilitate cognitive flexibility. Collectively, these results help to reconcile

current debates on the functional roles of different cortical regions in WM, and provide

new insights into how a unified WM framework could support varied control demands.

Methods

Participants

A total of 54 participants were recruited at Chinese Academy of Sciences,

Shanghai Branch. Twenty-six healthy participants (21 female, all right-handed, mean

age = 24.0 ± 1.4 years) were recruited for Experiment 1. Two were excluded due to

failure in completing the experiment or low conformity to task instructions, remaining

24 participants who completed the main experiment (19 female, mean age = 23.92 ±

1.41 years). Twenty-eight (22 female, mean age = 24.14 ± 1.51 years) participants were

recruited for Experiment 2. Two quitted after behavioral training and two did not finish

scanning due to technical problems with the scanner, resulting in 24 participants (20

female, mean age = 24.13 ± 1.60 years) in the final analyses. All participants were

neurologically healthy and eligible for MRI, had normal or corrected-to-normal vision,

provided written informed consent approved by the Ethics Committee of Institute of

Neuroscience, Center for Excellence in Brain Science and Intelligence Technology,

Chinese Academy of Sciences, and were monetarily compensated for their participation.

Sample sizes were not estimated a priori but were comparable and even superior to

those in previous studies.

Stimuli and Procedure

All stimuli were generated and presented using MATLAB (The MathWorks) and

Psychtoolbox 3 extensions (Brainard, 1997; Pelli, 1997). During behavioral training,

stimuli were presented on a ThinkVision monitor at a viewing distance of 45 cm.

Behavioral responses were acquired with a keyboard. During scanning, stimuli were

projected onto a SinoRad monitor (1280 x 1024 pixels, refreshing at 60 Hz) viewed

through a coil-mounted mirror in the scanner at a viewing distance of 90.5 cm.

Participants' behavioral responses were acquired with a Sinorad MRI-compatible

button box.

Behavioral Training

In Experiment 1, prior to scanning, participants were trained to learn two novel

rules, Rule A and Rule B, for categorizing orientations. Thirty oriented bars were used

as sample stimuli, ranging from 5° to 179° (in increments of 6°; two participants used

another set of thirty orientations ranging from 4° to 178°). Each abstract rule was

constructed by two orthogonal boundaries that divided the thirty orientations into two

categories with fifteen orientations each. Rule A and Rule B were orthogonal to each

other. Corresponding boundaries were 20°/110° and 65°/155° (15°/105° and 60°/150°

for the two participants using different stimuli sets).

Participants learned new rules through a rule learning task. Each run of learning

started with a rule disk informing the target rule. To avoid any potential verbal coding,

rule specifics were visually illustrated as rule disks containing two distinct colors

(colors randomly assigned to categories every time; see Figure 1A for an example).

Rule disk was presented on the screen for 2 s followed by 1 s of fixation. On each trial,

an oriented bar (radius=7°) was presented for 1 s followed by a delay of 1 s. Participants

were instructed to report the category of the orientation by pressing a response key ("F"

or "J"). To avoid category-response mapping, we randomized the relationship between

categories and key buttons across trials. Moreover, to avoid presenting rule boundaries

explicitly, we presented key names at random positions within the range defining each

category. In other words, participants had to memorize the exact rule boundaries as

accurately as possible in order to find the correct key buttons for each trial. Feedback

was given at the end of each trial to assist learning.

Participants completed 30 learning trials in each run. They reviewed rule disks after

every 10 trials for memory reconsolidation. Each participant completed at least two

runs for each rule. After achieving an average accuracy above 86% (26 out of 30 trials)

for the first rule, they proceeded to learn the other rule and then to practice the main

task for scanning (see next section). Learning order of rules was counterbalanced across

subjects. Upon completion of practicing, participants needed to report the boundaries

of learned rules as a qualification of behavioral training. If the total error in reported

boundaries had exceeded 20°, participants had one more chance to learn by repeating

the learning task. Two participants completed one additional behavioral training to

recap rule knowledge prior to scanning.

Behavioral training for Experiment 2 followed the same procedure and used the

identical sample set (30 orientations ranging from 4° to 178°, in increments of 6°) as

Experiment 1, except that only one rule was trained. Half of the participants in

Experiment 2 learned rule boundaries of 19°/109°; the other half learned rule

boundaries of 67°/157°.

Flexible WM Task (fMRI Task)

In Experiment 1, during scanning, participants completed a flexible WM task

which implemented levels of control demand with different rules. To be specific,

participants randomly switched between a maintenance task and a categorization task.

In the maintenance task, participants needed to memorize stimulus information (i.e.,

orientations). In the categorization task, participants needed to categorize orientations

following the rule that was randomly assigned and cued on a block basis. Procedure of

the main task was visualized in Figure 1A. At the beginning of each block, participants

were presented with a rule disk for 3 s, followed by a 2-s interval, instructing the

categorization rule of the current block. For each trial, participants saw two oriented

bars presented successively. Each bar was presented for 0.75 s, with an inter-stimulus-

interval of 0.5 s. Sample sets were the same as those used in behavioral training. After

a 0.5-s interval, a retro-cue occurred for 0.5 s, indicating the orientation of which

participants should remember. After a 1.5-s delay, a task cue was displayed at fixation

for 0.5 s, following by an 8-s memory delay. The task cue was either a letter "P" on

maintenance trials, instructing participants to maintain the cued orientation during

memory delay as precisely as possible; or the task cue was a letter "C" on categorization

trials, asking participants to categorize the cued orientation using the block rule during

the delay. Then, participants were probed to respond within 2 s. On maintenance trials,

participants needed to select the memorized orientation from two probe orientations;

while on categorization trials, participants needed to report the category of the cued

orientation. Response mapping followed the same operation as in the learning tasks.

Inter-trial-intervals were randomly selected from 3, 5, and 7 s with an equal trial number,

resulting in an average trial length of 20 s. Participants switched to the next block after

every six categorization trials and three maintenance trials. Each run contained two

blocks (i.e., 18 trials).

In Experiment 2, to isolate potential effect of rule switching, the categorization rule

stayed the same throughout the experiment. In Experiment 2, participants randomly

switched between the maintenance task and the categorization task. Each trial followed

the same procedure as Experiment 1.

In Experiment 1, orientations, tasks, and cued target order (1st or 2nd) were

counterbalanced across trials, resulting in an equal trial number of 90 across all three

conditions (categorization-Rule A, categorization-Rule B, and maintenance). Nineteen

out of the twenty-four participants completed 15 runs of the main task. One participant

completed 13 runs due to technical difficulties with the scanner. Another four

participants completed 30 runs across two scan sessions. The same counterbalancing

procedure was conducted for Experiment 2 (90 trials for maintenance task and 180 trials

for categorization task). In Experiment 2, six participants completed 15 runs of 18 trials;

the other seven completed 18 runs of 15 trials each due to scanner limitations. At the

end of scanning, participants reported the rule boundaries three times as a final check

of their rule memory.

Data Acquisition

MRI data of Experiment 1 were collected using a 3 Tesla Siemens MRI scanner

(Tim Trio; Siemens Healthineers) with a 32-channel head coil at the Functional Brain

Imaging Platform at Institute of Neuroscience, Center for Excellence in Brain Science

and Intelligence Technology, Chinese Academy of Sciences. Functional scanning was

performed using a gradient-echo echo-planar sequence with the following parameters:

repetition time (TR) = 1000 ms; echo time (TE) = 30 ms; flip angle (FA) = 40°; voxel

size = 3 x 3 x 3 mm; multi-band accelerate factor = 4; matrix size = 74 x 74; slice

number = 60. A high-resolution anatomical T1 image was collected before functional

scanning (TR = 2300 ms; TE = 2.98 ms; FOV = 256 x 240 x 192 mm; voxel size = 1 x

1 x 1 mm). During scanning, participants' head positions were restricted with

surrounding paddings to prevent head movements. MRI data of Experiment 2 were

collected using identical procedure and settings except that the last eleven participants

were scanned using a newly installed 3 Tesla Siemens MRI scanner (Prisma; Siemens

Healthineers) at the Functional Brain Imaging Platform.

Preprocessing

All preprocessing of individual MRI data was performed using AFNI

(afni.nimh.nih.gov) (Cox, 1996; Cox & Hyde, 1997). Functional data of all runs were

registered to the last volume of the final run with the first eight volumes of each run

removed. Then, individuals' aligned functional data were registered to their

corresponding T1 volume. Alignment of registration was manually checked for each

subject to ensure quality. The registered data were further motion corrected and

detrended.

ROI Definition

Our primary ROI-based analyses focused on three most commonly-studied, WM-

related brain areas: early visual cortex (EVC), intraparietal sulcus (IPS) in parietal

cortex, and superior precentral sulcus (sPCS) in frontal cortex (Ester et al., 2015;

Hallenbeck et al., 2021; Yu & Shim, 2017). We created anatomical ROI masks based

on the probabilistic atlas by Wang and colleagues (Wang et al., 2015). EVC (merging

bilateral V1, V2, and V3), IPS (merging bilateral IPS0-5), and sPCS (merging bilateral

FEF) masks were generated by warping masks from the probabilistic atlas to

individuals' anatomical image in their native space. In order to generate functional ROI

masks, we then performed general linear models (GLMs) to quantify task-related

univariate activity changes in each voxel. Task events were modeled using boxcar

functions convolved with a canonical hemodynamic response function (durations of

event epochs for sample, post retro-cue delay, memory delay, and response were 2.5 s,

2 s, 8.5 s, and 2 s, respectively). Six nuisance regressors were also included to account

for head motion artifacts in the six dimensions of rigid body motion. Functional EVC

mask was defined by the 500 most active voxels during sample display. Functional IPS

and sPCS masks were defined by the 500 most active voxels during memory delay.

Additional ROIs in the frontal cortex were defined using the HCP atlas (Glasser et al.,

2016), including the inferior precentral sulcus (iPCS, generated by merging 6v, 6r, and

PEF), inferior frontal sulcus (IFS, generated by merging IFJp, IFJa, IFSp, IFSa, and

p47r), middle frontal gyrus (MFG, generated by merging 9-46d, 46, a9-46v, and p9-

46v), and primary motor cortex (M1).

MRI Data Analyses

Multivariate Inverted Encoding Modeling (IEM)

Neural representations of orientations were reconstructed using inverted encoding

modeling (IEM) (Brouwer & Heeger, 2009, 2011; Ester et al., 2015; Rademaker et al.,

2019; Yu & Shim, 2017) with custom MATLAB scripts on individuals' BOLD

activation patterns in the ROIs. IEM provides an estimate of population-level

reconstructions of stimulus-specific information. The general procedure for IEM

includes using training data to train model weights and then applying weights to testing

data to obtain reconstructed channel responses. For the main analyses, we used trials

from all conditions to train and to test IEM in order to avoid potential biases from a

specific task condition. Results for categorization task were averaged across rules for

Experiment 1. Training and testing were performed for each TR separately. As a control,

IEMs were also estimated for each condition separately (within-condition IEM).

Training and testing underwent a leave-one-run-out cross-validation procedure, in

which each run was taken out as the testing run, and the rest of the data served as the

training run. This procedure was iterated until all runs had served as training and testing

runs. Results from all cross-validated folds were averaged. Detailed computations for

each fold were elucidated below:

We first modeled responses of voxels into nine equidistant orientation channels

(initial channels were 1°, 21°, 41°, 61°, 81°, 101°, 121°, 141°, 161°), characterizing

voxel selectivity for orientations. At each channel, the modeled orientation tuning curve

was a half-wave-rectified and squared sinusoid raised to eighth power, defined as the

function below (c was the center of the channel):

$$\int (\theta) = \cos(\theta - c)^8$$

Population-level tuning responses of voxels was described using the function:

$$B_1 = W C_1$$

B_1 was the training dataset from our fMRI data (v voxels $\times n$ trials). C_1

represented the hypothesized channel responses (k channels $\times n$ trials) which were

modulated by W, a weight matrix (v voxels $\times k$ channels).

The least-squared estimates of the weight matrix ($\widehat{W}$) was computed using linear

regression:

$$\widehat{W} = B_1 C_1^T (C_1 C_1^T)^{-1}$$

The weight matrix was then applied on the test dataset to reconstruct estimated

channel responses ($\hat{C}_2$):

$$\hat{C}_2 = (\widehat{W}^T \widehat{W})^{-1} \widehat{W}^T B_2$$

The analysis above were repeated for 20 times in step of 1° using leave-one-run-

out cross-validation so that the nine channel centers covered all 180 orientations

(Rademaker et al., 2019; Yu & Postle, 2021). All channel responses were combined to

create responses for all 180 orientation channels. For statistical comparisons and for

visualization, all channel responses were shifted to a common center of 0° (true

orientation of trials). The responses from all trials were averaged to obtain reconstructed

orientation representations for the test datasets.

To quantify the strength of each IEM reconstruction, we calculated reconstruction

fidelity of channel responses (Rademaker et al., 2019). First, channel responses of each

trial were shifted so that the orientation of each trial was centered in stimulus space.

Thus, for each shifted channel response with a vector length of r at orientation θ, the

orientation was wrapped onto a 2π circular space, and r was projected to the vector at

the true orientation (center of stimulus space, $0°$) using the absolute angle between the

channel and the center following the equation:

$d = r\cos(\mathrm{abs}(0°\text{-}2\theta))$

The reconstruction fidelity was then calculated as the mean of all projected vectors d.

A larger fidelity value indicates a stronger positive representation of orientation.

Multivariate Pattern Analysis (MVPA)

Besides IEM, we tracked neural representations of stimulus and of category using

linear Support Vector Machine (SVM) decoders. All decoding analyses were performed

using the templateSVM and fitcecoc functions in MATLAB.

Decoding of stimulus was performed for every TR. We divided the thirty

orientations into four bins of $45°$ each, two cardinal bins centered at $90°$ or $180°$ and

two oblique bins centered at $45°$ or $135°$. We then performed two two-way

classifications, one trained and tested on cardinal bins, and the other trained and tested

on oblique bins. We trained and tested decoders separately for each condition using the

same leave-one-run-out cross-validation procedure as in IEM analyses. To avoid biases

in model training, we randomly balanced the trial numbers for each bin in the training

set. Decoding accuracies were then computed by averaging performance of cardinal

and oblique classifiers. For the categorization task, we averaged accuracies across rules.

Decoding of category information for Experiment 1 was performed under each

rule (90 trials for each rule) using a leave-one-trial-out cross-validation procedure (see

next paragraph for details), and the decoding accuracies were then averaged across rules.

Since Experiment 2 adopted a fixed rule with 180 trials in the categorization task, we

randomly divided categorization trials into two halves with 90 trials each, and decoded

category information for Experiment 2 using identical procedures as for Experiment 1.

Because closer orientations are more similar to each other inherently, orientations

per se could contain categorical information by visual similarity. Thus, to isolate the

influence of stimulus on category, in addition to the decoder using true category labels,

we trained an opposite category decoder using category labels based on the opposite

rule. If the two-way classification on categories only captured stimulus information,

then true category and opposite category decoding should have had comparable

performance. If abstract category information existed beyond stimulus information,

then true category decoder should have outperformed the opposite category decoder.

Thus, an abstract category index was calculated by subtracting opposite category

decoding accuracy from true category decoding accuracy (i.e., chance level = 0). Since

the opposite category decoding used re-assigned labels, to eliminate imbalance in trial

number between true and opposite categories, we used a leave-one-trial-out cross-

validation procedure for true category and opposite category decoders. Decoding for

Experiment 1 was performed separately for each rule and were then averaged. Decoding

for Experiment 2 was performed separately for randomly divided halves and averaged.

Recurrent Neural Network Simulations

RNN architecture

The network model was built following the details in previous work (Masse et al.,

2019), and implemented in TensorFlow (version: Nvidia-tensorflow 1.15.0) (Abadi et

al., 2016). The general network architecture consisted of three layers of artificial units:

the input, hidden, and output layers. The input layer contains units served to present

various task-related signals corresponding to those in the fMRI paradigm, including

orientations, retro-cues, task cues. In order to simulate neural activity patterns in

hierarchically connected brain regions (EVC, IPS and sPCS), we separated the hidden

layer into three modules, each containing 200 recurrent units with short-term synaptic

plasticity (STSP). Within each module, units were further divided into 80% excitatory

and 20% inhibitory following Dale's principle. Similar to previous work (Zhou et al.,

2021), modularity was achieved by constraining the recurrent connectivity in the hidden

layer. Specifically, only posterior module's (Module 1) excitatory units received inputs

from the input layer and only anterior module's (Module 3) excitatory units projected

to the output units. Between-module connections were culled so that only 50% of a

module's excitatory units were randomly connected to their counterparts in the

neighboring module(s), and vice versa (feedforward and feedback connections).

Connections among inhibitory units remained strictly within-module in accordance

with the observation that inhibitory connections in cortex are largely local. Thus,

posterior, middle and anterior modules were intended to simulate the three

interconnected ROIs we used in the fMRI analyses that posited differently at the

processing hierarchy. We specifically manipulated the output demand to investigate

whether it would alter similarity of the results to the fMRI observations. To this end,

one type of network architecture (RNN1) implemented a two-unit output layer with

each unit corresponding to one of two possible response options, presented through the

input units before the test period; In contrast, the other type of RNN architecture (RNN2)

had additional units in the output layer, creating a demand for preserving the original

stimulus information alongside categorical representations.

Task simulation

Orientations were simulated as Gaussian signals from 15 orientation-tuned units in

the input layer distributed equally across 0-180 degrees, forming a ring of receptive

field. The magnitude of an orientation-tuned input unit represented the closeness of its

preferred orientation to the input angle. Stimulus values were selected from an array of

20 orientations evenly spanned from [0 to 180) degrees. The sequentially-presented

stimuli were presented through the same receptive field, followed by retro-cue and task

cue indicated through the separate input units. For RNN1, before the test period when

the network was required to make a choice, two response options were presented

sequentially through the same input receptive field. The selection of the options varied

slightly between the maintenance and categorization tasks: in maintenance, one

orientation was always the cued sample while the other was randomly chosen from all

other possible angles. In categorization, one option was taken from the same category

as the cued sample but not necessarily the exact angle, while the other option was

randomly chosen from orientations belonging to the other category. The network output

(0,1) or (1,0) in the output units to report its choice. In comparison, RNN2 output (0,1)

or (1,0) to report the category to which the cued orientation belonged in the

categorization task, or (0,0) in the maintenance task. Importantly, the model also needed

to report the cued orientation itself through a receptive field consisting of 15 orientation

-tuned units in the output layer.

Training parameters and procedure

The hyperparameters and procedure for training the models were consistent with

those detailed in previous work (Masse et al., 2019), with the following exceptions:

standard deviations of input and recurrent noise were set to 0.01 as our tasks were much

harder to train compared to those used in the reference study (especially networks were

trained on both tasks simultaneously). Lowering the noise level may provide an edge

for the models to successfully learn to perform the tasks. In a similar vein, we also

expanded the number of hidden units to 600 and number of training iteration to a

maximum of 10000. Additionally, spike penalty was set to 0 for both RNN models to

remove constraints on neuronal activity.

We trained 20 models for each type of RNN and results were obtained by averaging

over all of them (for single-rule RNN, 10 models for each categorization rule). The goal

of the training process was to minimize the mean square error between the model

outputs and correct outputs during the test period via back propagation (with a 50 ms

grace period at onset when model output was not taken into account in calculating error).

Training was conducted in a block-interleaved fashion in which each gradient batch

consisted of 300 maintenance, 300 categorization Rule A and 300 categorization Rule

B trials, with the task block order randomized (for single rule RNN, each batch

consisted of 300 maintenance and 300 categorization trials). Training would

automatically stop if the model achieved 90% accuracy in the last training batch on all

tasks. For RNN2, the accuracies for category and stimulus outputs were calculated

separately to ensure precision of the stimulus outputs.

Population decoding

We measured the strength of stimulus and category representations through training

SVMs on time-resolved neuronal activity. Activities were obtained by feeding new

batches of tasks into the already-successfully trained networks after freezing all

connection weights to prevent further changes to the models' behaviors. The intrinsic

noise for the recurrent layer was also set to 0 for decoding analyses. To ensure accurate

decoding results, we sampled large number of trials (900 trials for each condition) and

implemented a 5-fold cross-validation procedure in which 80% of trials were used as

training set and the remaining 20% as testing set in each fold. Decoders were trained

separately for each module and time point.

Statistical Testing

Participants' behavioral performance for the main task was assessed using

accuracy and reaction time. Paired t-test was conducted for the two task types

(maintenance & categorization) to evaluate differences between conditions.

Statistical significance was evaluated via a sign-flip permutation procedure for all other analyses. For example, to characterize the significance of IEM fidelity, we computed the p-value by comparing the true mean fidelity of our sample with a null distribution reflecting no IEM fidelity. The null distribution was created by randomly assigning 1 or -1 to fidelity scores of our sample and then averaging the sign-flipped samples for 10,000 times, resulting in a null distribution of 10,000 fidelity scores. To characterize the difference of IEM fidelity between tasks, we sign-flipped the fidelity sample for each condition and then averaged the difference for 10,000 times. The p-value was calculated by comparing the true mean difference with the generated null distribution of difference. P-values were corrected using FDR across ROIs, time (TRs), and tasks for all analyses unless specified. An early (5-10 s; 6^{th}-11^{th} TR) and late (11-16 s; 12^{th}-17^{th} TR) task epoch was also defined to facilitate comparisons between ROIs and experiments when needed.

For RNN decoding results, we adopted a cluster-based permutation approach (using MNE-Python (Gramfort et al., 2013) function *permutation_cluster_1samp_test* to accommodate the large number of time points to be corrected for) to determine statistical significance of the time course, for stimulus decoding accuracies in maintenance/categorization, difference between stimulus decoding accuracies between tasks, and abstract category decoding accuracy in categorization task. Moreover, we also pooled decoding accuracies across a critical task period (50-75 time points during delay) to produce summary statistics aligning with what was reported in the fMRI results. Average decoding results were corrected using the FDR method.

1012

Acknowledgements

We would like to thank Dr. Mu-ming Poo for valuable comments on an earlier version of the manuscript, and Dr. Tianming Yang for helpful discussions. This work was supported by the Strategic Priority Research Program of the Chinese Academy of Sciences (Grant No. XDB1010202), the Ministry of Science and Technology of China (STI2030-Major Projects 2021ZD0203701, 2021ZD0204202), the National Natural Science Foundation of China (32271089), CAS Project for Young Scientists in Basic Research (YSBR-071), and Shanghai Pujiang Program (22PJ1414400) to Q.Y..

Reference

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., . . . Zheng, X. (2016). TensorFlow: A System for Large-Scale Machine Learning. *12th USENIX Symposium on Operating Systems Design and Implementation*, 265–283.

Baddeley, A. (2003). Working memory: looking back and looking forward. *Nat Rev Neurosci, 4*(10), 829-839. doi:10.1038/nrn1201

Badre, D. (2008). Cognitive control, hierarchy, and the rostro-caudal organization of the frontal lobes. *Trends Cogn Sci, 12*(5), 193-200. doi:10.1016/j.tics.2008.02.004

Badre, D., Bhandari, A., Keglovits, H., & Kikumoto, A. (2021). The dimensionality of neural representations for control. *Curr Opin Behav Sci, 38*, 20-28. doi:10.1016/j.cobeha.2020.07.002

Badre, D., Kayser, A. S., & D'Esposito, M. (2010). Frontal cortex and the discovery of abstract action rules. *Neuron, 66*(2), 315-326. doi:10.1016/j.neuron.2010.03.025

Bettencourt, K. C., & Xu, Y. (2016). Decoding the content of visual short-term memory under distraction in occipital and parietal areas. *Nat Neurosci, 19*(1), 150-157. doi:10.1038/nn.4174

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spat Vis, 10*(4), 433-436. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/9176952

Brincat, S. L., Siegel, M., von Nicolai, C., & Miller, E. K. (2018). Gradual progression from sensory to task-related processing in cerebral cortex. *Proc Natl Acad Sci U S A, 115*(30), E7202-E7211. doi:10.1073/pnas.1717075115

Brouwer, G. J., & Heeger, D. J. (2009). Decoding and reconstructing color from responses in human visual cortex. *J Neurosci, 29*(44), 13992-14003. doi:10.1523/JNEUROSCI.3577-09.2009

Brouwer, G. J., & Heeger, D. J. (2011). Cross-orientation suppression in human visual cortex. *J Neurophysiol, 106*(5), 2108-2119. doi:10.1152/jn.00540.2011

Christophel, T. B., Hebart, M. N., & Haynes, J. D. (2012). Decoding the contents of visual short-term

memory from human visual and parietal cortex. *J Neurosci, 32*(38), 12983-12989. doi:10.1523/JNEUROSCI.0184-12.2012

Christophel, T. B., Iamshchinina, P., Yan, C., Allefeld, C., & Haynes, J. D. (2018). Cortical specialization for attended versus unattended working memory. *Nat Neurosci, 21*(4), 494-496. doi:10.1038/s41593-018-0094-4

Cox, R. W. (1996). AFNI: software for analysis and visualization of functional magnetic resonance neuroimages. *Comput Biomed Res, 29*(3), 162-173. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/8812068

Cox, R. W., & Hyde, J. S. (1997). Software tools for analysis and visualization of FMRI Data. *NMR in Biomedicine, 10*, 171-178.

Curtis, C. E., Rao, V. Y., & D'Esposito, M. (2004). Maintenance of spatial and motor codes during oculomotor delayed response tasks. *J Neurosci, 24*(16), 3944-3952. doi:10.1523/JNEUROSCI.5640-03.2004

D'Esposito, M., & Postle, B. R. (2015). The cognitive neuroscience of working memory. *Annu Rev Psychol, 66*, 115-142. doi:10.1146/annurev-psych-010814-015031

D'Esposito, M., Postle, B. R., Ballard, D., & Lease, J. (1999). Maintenance versus manipulation of information held in working memory: an event-related fMRI study. *Brain Cogn, 41*(1), 66-86. doi:10.1006/brcg.1999.1096

D'Esposito, M., Postle, B. R., & Rypma, B. (2000). Prefrontal cortical contributions to working memory: evidence from event-related fMRI studies. *Exp Brain Res, 133*(1), 3-11. doi:10.1007/s002210000395

Emrich, S. M., Riggall, A. C., Larocque, J. J., & Postle, B. R. (2013). Distributed patterns of activity in sensory cortex reflect the precision of multiple items maintained in visual short-term memory. *J Neurosci, 33*(15), 6516-6523. doi:10.1523/JNEUROSCI.5732-12.2013

Eppinger, B., Goschke, T., & Musslick, S. (2021). Meta-control: From psychology to computational neuroscience. *Cogn Affect Behav Neurosci, 21*(3), 447-452. doi:10.3758/s13415-021-00919-4

Ester, E. F., Anderson, D. E., Serences, J. T., & Awh, E. (2013). A neural measure of precision in visual working memory. *J Cogn Neurosci, 25*(5), 754-761. doi:10.1162/jocn_a_00357

Ester, E. F., Sprague, T. C., & Serences, J. T. (2015). Parietal and Frontal Cortex Encode Stimulus-Specific Mnemonic Representations during Visual Working Memory. *Neuron, 87*(4), 893-905. doi:10.1016/j.neuron.2015.07.013

Ester, E. F., Sprague, T. C., & Serences, J. T. (2020). Categorical Biases in Human Occipitoparietal Cortex. *J Neurosci, 40*(4), 917-931. doi:10.1523/JNEUROSCI.2700-19.2019

Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., & Summerfield, C. (2022). Orthogonal representations for robust context-dependent task performance in brains and neural networks. *Neuron, 110*(7), 1258-1270 e1211. doi:10.1016/j.neuron.2022.01.005

Freedman, D. J., & Assad, J. A. (2006). Experience-dependent representation of visual categories in parietal cortex. *Nature, 443*(7107), 85-88. doi:10.1038/nature05078

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2001). Categorical representation of visual stimuli in the primate prefrontal cortex. *Science, 291*(5502), 312-316. doi:10.1126/science.291.5502.312

Funahashi, S., Bruce, C. J., & Goldman-Rakic, P. S. (1989). Mnemonic coding of visual space in the monkey's dorsolateral prefrontal cortex. *J Neurophysiol, 61*(2), 331-349. doi:10.1152/jn.1989.61.2.331

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Curr Opin Neurobiol, 37*, 66-74. doi:10.1016/j.conb.2016.01.010

Fuster, J. M., & Alexander, G. E. (1971). Neuron activity related to short-term memory. *Science, 173*(3997), 652-654. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/4998337

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E., . . . Van Essen, D. C. (2016). A multi-modal parcellation of human cerebral cortex. *Nature, 536*(7615), 171-178. doi:10.1038/nature18933

Gosseries, O., Yu, Q., LaRocque, J. J., Starrett, M. J., Rose, N. S., Cowan, N., & Postle, B. R. (2018). Parietal-Occipital Interactions Underlying Control- and Representation-Related Processes in Working Memory for Nonspatial Visual Features. *J Neurosci, 38*(18), 4357-4366. doi:10.1523/JNEUROSCI.2747-17.2018

Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., . . . Hamalainen, M. (2013). MEG and EEG data analysis with MNE-Python. *Front Neurosci, 7*, 267. doi:10.3389/fnins.2013.00267

Hallenbeck, G. E., Sprague, T. C., Rahmati, M., Sreenivasan, K. K., & Curtis, C. E. (2021). Working memory representations in visual cortex mediate distraction effects. *Nat Commun, 12*(1), 4714. doi:10.1038/s41467-021-24973-1

Harrison, S. A., & Tong, F. (2009). Decoding reveals the contents of visual working memory in early visual areas. *Nature, 458*(7238), 632-635. doi:10.1038/nature07832

Henderson, M. M., Rademaker, R. L., & Serences, J. T. (2022). Flexible utilization of spatial- and motor-based codes for the storage of visuo-spatial information. *Elife, 11*. doi:10.7554/eLife.75688

Hu, Y., & Yu, Q. (2023). Spatiotemporal dynamics of self-generated imagery reveal a reverse cortical hierarchy from cue-induced imagery. *Cell Rep, 42*(10), 113242. doi:10.1016/j.celrep.2023.113242

Latimer, K. W., & Freedman, D. J. (2023). Low-dimensional encoding of decisions in parietal cortex reflects long-term training history. *Nat Commun, 14*(1), 1010. doi:10.1038/s41467-023-36554-5

Leavitt, M. L., Mendoza-Halliday, D., & Martinez-Trujillo, J. C. (2017). Sustained Activity Encoding Working Memories: Not Fully Distributed. *Trends Neurosci, 40*(6), 328-346. doi:10.1016/j.tins.2017.04.004

Lee, S. H., Kravitz, D. J., & Baker, C. I. (2013). Goal-dependent dissociation of visual and prefrontal cortices during working memory. *Nat Neurosci, 16*(8), 997-999. doi:10.1038/nn.3452

Li, S., Zeng, X., Shao, Z., & Yu, Q. (2023). Neural Representations in Visual and Parietal Cortex Differentiate between Imagined, Perceived, and Illusory Experiences. *J Neurosci, 43*(38), 6508-6524. doi:10.1523/JNEUROSCI.0592-23.2023

Liu, T., Cable, D., & Gardner, J. L. (2018). Inverted Encoding Models of Human Population Response Conflate Noise and Neural Tuning Width. *J Neurosci, 38*(2), 398-408. doi:10.1523/JNEUROSCI.2453-17.2017

Lorenc, E. S., Sreenivasan, K. K., Nee, D. E., Vandenbroucke, A. R. E., & D'Esposito, M. (2018). Flexible coding of visual working memory representations during distraction. *J Neurosci*. doi:10.1523/JNEUROSCI.3061-17.2018

Luu, L., & Stocker, A. A. (2021). Categorical judgments do not modify sensory representations in working memory. *PLoS Comput Biol, 17*(6), e1008968. doi:10.1371/journal.pcbi.1008968

Mackey, W. E., Winawer, J., & Curtis, C. E. (2017). Visual field map clusters in human frontoparietal

cortex. *Elife, 6*. doi:10.7554/eLife.22974

Masse, N. Y., Yang, G. R., Song, H. F., Wang, X. J., & Freedman, D. J. (2019). Circuit mechanisms for the maintenance and manipulation of information in working memory. *Nat Neurosci, 22*(7), 1159-1167. doi:10.1038/s41593-019-0414-3

McKee, J. L., Riesenhuber, M., Miller, E. K., & Freedman, D. J. (2014). Task dependence of visual and category representations in prefrontal and inferior temporal cortices. *J Neurosci, 34*(48), 16065-16075. doi:10.1523/JNEUROSCI.1660-14.2014

Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annu Rev Neurosci, 24*, 167-202. doi:10.1146/annurev.neuro.24.1.167

Miller, J. A., Tambini, A., Kiyonaga, A., & D'Esposito, M. (2022). Long-term learning transforms prefrontal cortex representations during working memory. *Neuron, 110*(22), 3805-3819 e3806. doi:10.1016/j.neuron.2022.09.019

Mok, R. M., & Love, B. C. (2020). Abstract Neural Representations of Category Membership beyond Information Coding Stimulus or Response. *J Cogn Neurosci*, 1-17. doi:10.1162/jocn_a_01651

Musslick, S., & Cohen, J. D. (2021). Rationalizing constraints on the capacity for cognitive control. *Trends Cogn Sci, 25*(9), 757-775. doi:10.1016/j.tics.2021.06.001

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers into movies. *Spat Vis, 10*(4), 437-442. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/9176953

Rademaker, R. L., Chunharas, C., & Serences, J. T. (2019). Coexisting representations of sensory and mnemonic information in human visual cortex. *Nat Neurosci, 22*(8), 1336-1344. doi:10.1038/s41593-019-0428-x

Riggall, A. C., & Postle, B. R. (2012). The Relationship between Working Memory Storage and Elevated Activity as Measured with Functional Magnetic Resonance Imaging. *Journal of Neuroscience, 32*(38), 12990-12998. doi:10.1523/Jneurosci.1892-12.2012

Serences, J. T., Ester, E. F., Vogel, E. K., & Awh, E. (2009). Stimulus-specific delay activity in human primary visual cortex. *Psychol Sci, 20*(2), 207-214. doi:10.1111/j.1467-9280.2009.02276.x

Shi, D., & Yu, Q. (2024). Distinct neural signatures underlying information maintenance and manipulation in working memory. *Cereb Cortex, 34*(3). doi:10.1093/cercor/bhae063

Sprague, T. C., Adam, K. C. S., Foster, J. J., Rahmati, M., Sutterer, D. W., & Vo, V. A. (2018). Inverted Encoding Models Assay Population-Level Stimulus Representations, Not Single-Unit Neural Tuning. *eNeuro, 5*(3). doi:10.1523/ENEURO.0098-18.2018

Sprague, T. C., & Serences, J. T. (2013). Attention modulates spatial priority maps in the human occipital, parietal and frontal cortices. *Nat Neurosci, 16*(12), 1879-1887. doi:10.1038/nn.3574

Wang, L., Mruczek, R. E., Arcaro, M. J., & Kastner, S. (2015). Probabilistic Maps of Visual Topography in Human Cortex. *Cereb Cortex, 25*(10), 3911-3931. doi:10.1093/cercor/bhu277

Wang, X. J. (2021). 50 years of mnemonic persistent activity: quo vadis? *Trends Neurosci, 44*(11), 888-902. doi:10.1016/j.tins.2021.09.001

Yu, Q., & Postle, B. R. (2021). The Neural Codes Underlying Internally Generated Representations in Visual Working Memory. *J Cogn Neurosci*, 1-16. doi:10.1162/jocn_a_01702

Yu, Q., & Shim, W. M. (2017). Occipital, parietal, and frontal cortices selectively maintain task-relevant features of multi-feature objects in visual working memory. *Neuroimage, 157*, 97-107. doi:10.1016/j.neuroimage.2017.05.055

Yu, Q., & Shim, W. M. (2019). Temporal-Order-Based Attentional Priority Modulates Mnemonic

1178   Representations in Parietal and Frontal Cortices. *Cereb Cortex, 29*(7), 3182-3192.

1179   doi:10.1093/cercor/bhy184

1180 Zhou, Y., Rosen, M. C., Swaminathan, S. K., Masse, N. Y., Zhu, O., & Freedman, D. J. (2021).

1181   Distributed functions of prefrontal and parietal cortices during sequential categorical decisions.

1182   *Elife, 10*. doi:10.7554/eLife.58782

1183

1184 **Supplemental Figures**

1185

1186 **Figure S1.** Visualization of the anatomical locations of the ROIs on the MNI brain.

1187
Figure S2. Control analyses for stimulus representation results in Experiment 1.
(A) Time course of representational strength of orientations in EVC, IPS and sPCS
using IEMs trained separately for each condition. Bar plot on the right shows
corresponding averaged difference between tasks across the late task epoch (11 – 16 s)
in each ROI. Positive difference indicates higher representational strength for
categorization, and vice versa for negative difference. Gray shaded areas indicate the
entire memory delay following task cue. Horizontal dashed lines represent a baseline
of 0 or 0.5. Blue and orange dots at the bottom indicate the significance of
representational fidelity at each time point of the corresponding task at $p < 0.05$ (small),
$p < 0.01$ (medium), and $p < 0.001$ (large). The bottom black dots indicate significant
difference in representational fidelity between tasks. Shaded areas represent $\pm$ SEM.
black asterisks denote significance, *: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$. Gray
asterisk denotes marginal significance $p < 0.1$. (B) Time course of stimulus decoding
accuracy. Same conventions as (A). (C) Time course of representational strength of
orientations after removing voxel-wise mean activation for each condition at each TR.

1203 Same conventions as (A). (D) Time course of representational strength of orientations
1204 in functional ROIs defined by top 500 most selective voxels during sample or delay
1205 period. Same conventions as (A).
1206

1207

Figure S3. Orientation reconstructions in primary motor cortex (M1) at the population
level using IEMs.
(A) Time course of representational strength of orientations at M1 in Experiment 1.
Gray shaded areas indicate the entire memory delay following task cue. The bottom
black dots indicate significant difference in representational fidelity between tasks
(uncorrected) at $p < 0.05$. Horizontal dashed lines represent a baseline of 0. Shaded
areas represent ± SEM. (B) Time course of representational strength of orientations at
M1 in Experiment 2. Same conventions as (A).
1216
1217

1218

Figure S4. Behavioral performance of Experiment 2.

(A) Accuracy (upper) and reaction time (lower) of maintenance (blue) and

categorization (orange) tasks in Experiment 2. Asterisks denote significant results, n.s.:

not significant; **: $p < 0.01$. (B) Accuracy (upper) and reaction time (lower) for

orientations based on their distances from category center for categorization task.

Shaded areas represent ± SEM. Vertical dashed line represents category center.

1225

1226

Figure S5. Behavioral correlation of stimulus representation in Experiment 2.
Time course of correlation coefficients in EVC, IPS, and sPCS. Correlation was
performed between strength of stimulus representations and behavioral performance
(accuracy) for maintenance (blue) and categorization (orange) tasks. Gray shaded areas
indicate the entire memory delay following task cue. Horizontal dashed lines represent
a baseline of 0. Bottom dots indicate the significance of corresponding analyses at each
time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p <$
0.001 (large). Shaded areas represent ± SEM.
1235

Figure S6. Time course of category and abstract category decoding performance in Experiment 1 and 2.

(A) Time course of category decoding strength in Experiment 1 with flexible rule (orange) and in Experiment 2 with fixed rule (light orange). Horizontal dashed lines represent the chance level of 0.5. Gray shaded areas indicate the entire memory delay following task cue. Bottom dots indicate uncorrected significance of decoding accuracy at each time point at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). Shaded areas represent $\pm$ SEM. (B) Time course of abstract category decoding strength in Experiment 1 (dark blue) and in Experiment 2 (light blue). Horizontal dashed lines represent a baseline of 0.

1248

Figure S7. Stimulus, category, and abstract category results in additional frontal ROIs

in Experiment 1 and 2.

(A) Time course of representational strength of orientations in iPCS, IFS, and MFG in

Experiment 1 (top panel) and Experiment 2 (bottom panel). Gray shaded areas indicate

the entire memory delay following task cue. Blue and orange dots at the bottom indicate

the FDR-corrected significance of representational fidelity at each time point of the

corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). The

bottom black dots indicate significant difference in representational fidelity between

tasks (uncorrected). Horizontal dashed lines represent a baseline of 0. Shaded areas

represent ± SEM. (B) Average category decoding accuracy across the late task epoch

(11 – 16 s) in iPCS, IFS, and MFG of both experiments. (C) Average abstract category

decoding index across the late task epoch (11 – 16 s) in the same regions of both

experiments, black asterisks denote FDR-corrected significance, n.s.: not significant; *:

$p < 0.05$.

1263

1264

Figure S8. RNN results using IEMs.

Difference in the IEM fidelity of orientation representations between tasks in RNN2.

Results were averaged across the delay period. Uncorrected p-values from Module 1 to

3: 0.10, 0.48, 0.01. Positive difference indicates higher fidelity for categorization, and

negative difference indicates higher fidelity for maintenance. Error bars represent ±

SEM.

1271

1272 **Supplemental Tables**

1273

Time	Maintenance			Categorization			Maintenance vs. Categorization		
	EVC	IPS	sPCS	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.486	0.389	0.286	0.838	0.838	0.747	0.206	0.814	0.827
1	0.385	0.576	0.743	0.747	0.822	0.717	0.205	0.675	0.460
2	0.060	0.286	0.219	0.174	0.626	0.626	0.188	0.788	0.779
3	0.000	0.286	0.764	0.000	0.353	0.389	0.497	0.630	0.232
4	0.000	0.154	0.422	0.000	0.038	0.784	0.534	0.299	0.812
5	0.000	0.042	0.618	0.000	0.027	0.269	0.816	0.389	0.241
6	0.000	0.002	0.094	0.000	0.002	0.056	0.927	0.528	0.594
7	0.000	0.000	0.033	0.000	0.000	0.001	0.914	0.301	0.274
8	0.000	0.000	0.001	0.000	0.000	0.001	0.588	0.651	0.655
9	0.000	0.000	0.004	0.000	0.000	0.007	0.119	0.277	0.399
10	0.000	0.000	0.060	0.000	0.000	0.003	0.007	0.258	0.127
11	0.000	0.001	0.264	0.000	0.000	0.032	0.001	0.162	0.123
12	0.000	0.003	0.759	0.000	0.000	0.039	0.000	0.090	0.018
13	0.000	0.001	0.377	0.000	0.000	0.003	0.000	0.054	0.022
14	0.000	0.007	0.747	0.000	0.000	0.038	0.000	0.046	0.034
15	0.000	0.000	0.667	0.000	0.000	0.003	0.000	0.145	0.012
16	0.000	0.000	0.948	0.000	0.000	0.020	0.000	0.190	0.001
17	0.000	0.000	0.838	0.000	0.000	0.031	0.000	0.889	0.004

1274 **Supplemental Table 1**. P-values for the time course of IEM results in Figure 2.
1275 Underline denotes significant results ($p < 0.05$).

1276

	Maintenance			Categorization		
Time	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.569	0.202	0.603	0.674	0.347	0.368
1	0.866	0.549	0.871	0.913	0.459	0.291
2	0.757	0.808	0.846	0.921	0.651	0.224
3	0.246	0.264	0.576	0.438	0.708	0.075
4	0.232	0.147	0.749	0.092	0.052	0.093
5	0.310	0.062	0.537	0.136	<u>0.032</u>	<u>0.033</u>
6	0.114	<u>0.049</u>	0.911	<u>0.045</u>	0.003	0.009
7	<u>0.012</u>	<u>0.024</u>	0.125	<u>0.019</u>	0.002	0.012
8	<u>0.034</u>	0.076	0.140	<u>0.022</u>	0.001	0.004
9	0.050	0.069	0.143	<u>0.027</u>	0.000	0.001
10	0.160	0.699	0.377	0.101	<u>0.000</u>	<u>0.000</u>
11	0.320	0.944	0.612	0.140	<u>0.015</u>	<u>0.004</u>
12	0.494	0.983	0.339	0.271	<u>0.027</u>	<u>0.007</u>
13	0.344	0.546	0.140	0.435	0.062	<u>0.009</u>
14	0.173	0.768	0.538	0.275	0.082	0.068
15	0.127	0.809	0.811	0.493	0.181	0.080
16	0.083	0.145	0.516	0.284	0.097	<u>0.032</u>
17	0.396	0.085	<u>0.030</u>	0.122	<u>0.042</u>	0.118

Supplemental Table 2. P-values for the time course of correlation results in Figure 3. Underline denotes significant results ($p < 0.05$).

Time	Maintenance			Categorization			Maintenance vs. Categorization		
	EVC	IPS	sPCS	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.005	0.028	0.203	0.511	0.359	0.395	0.007	0.976	0.804
1	0.007	0.090	0.079	0.339	0.181	0.412	0.018	0.810	0.979
2	0.001	0.152	0.444	0.154	0.371	0.548	0.021	0.816	0.668
3	0.000	0.079	0.481	0.000	0.237	0.600	0.057	0.851	0.669
4	0.000	0.021	0.170	0.000	0.001	0.224	0.385	0.578	0.675
5	0.000	0.018	0.548	0.000	0.000	0.045	0.578	0.396	0.071
6	0.000	0.006	0.525	0.000	0.000	0.000	0.811	0.197	0.002
7	0.000	0.000	0.018	0.000	0.000	0.000	0.900	0.275	0.072
8	0.000	0.000	0.152	0.000	0.000	0.000	0.884	0.059	0.011
9	0.000	0.000	0.117	0.000	0.000	0.000	0.612	0.090	0.040
10	0.000	0.000	0.028	0.000	0.000	0.000	0.045	0.207	0.066
11	0.000	0.001	0.017	0.000	0.000	0.000	0.005	0.272	0.209
12	0.000	0.000	0.028	0.000	0.000	0.000	0.014	0.574	0.266
13	0.000	0.001	0.052	0.000	0.000	0.000	0.029	0.344	0.139
14	0.000	0.001	0.117	0.000	0.000	0.021	0.120	0.420	0.395
15	0.000	0.002	0.022	0.000	0.000	0.005	0.001	0.644	0.340
16	0.000	0.000	0.003	0.000	0.000	0.000	0.000	0.866	0.546
17	0.000	0.000	0.039	0.000	0.000	0.000	0.000	0.881	0.259

Supplemental Table 3. P-values for the time course of IEM results in Figure 4. Underline denotes significant results ($p < 0.05$).