Title：

Stimulus representation in human frontal cortex supports flexible control in

working memory

Authors:

Zhujun Shao[1,2,3], Mengya Zhang[1,3], Qing Yu[1,*]

Affiliations:

[1]Institute of Neuroscience, Key Laboratory of Brain Cognition and Brain-inspired Intelligence

Technology, Center for Excellence in Brain Science and Intelligence Technology, Chinese Academy

of Sciences, Shanghai 200031, China

[2]University of Chinese Academy of Sciences, Beijing 100049, China

[3]These authors contributed equally

[*]**Correspondence should be addressed to:**

Qing Yu

Institute of Neuroscience, Key Laboratory of Brain Cognition and Brain-inspired Intelligence

Technology, Center for Excellence in Brain Science and Intelligence Technology, Chinese Academy

of Sciences, Shanghai 200031, China

Email: qingyu@ion.ac.cn

Keywords: visual working memory, cognitive flexibility, frontal cortex, visual cortex, fMRI,

recurrent neural network

Abstract

When holding visual information temporarily in working memory (WM), the neural representation of the memorandum is distributed across various cortical regions, including visual and frontal cortices. However, the role of stimulus representation in visual and frontal cortices during WM has been controversial. Here we tested the hypothesis that stimulus representation persists in the frontal cortex to facilitate flexible control demands in WM. During functional MRI, participants flexibly switched between simple WM maintenance of visual stimulus or more complex rule-based categorization of maintained stimulus on a trial-by-trial basis. Our results demonstrated enhanced stimulus representation in the frontal cortex that tracked demands for active WM control and enhanced stimulus representation in the visual cortex that tracked demands for precise WM maintenance. This differential frontal stimulus representation traded off with the newly-generated category representation with varying control demands. Simulation using multi-module recurrent neural networks replicated human neural patterns when stimulus information was preserved for network readout. Altogether, these findings help reconcile the long-standing debate in WM research, and provide empirical and computational evidence that flexible stimulus representation in the frontal cortex during WM serves as a potential neural coding scheme to accommodate the ever-changing environment.

Introduction

Real-world flexible behavior relies largely on working memory (WM), which allows the maintenance and manipulation of information in the brain in order to serve diverse behavioral goals (Baddeley, 2003). One central problem in the field of WM is to understand how stimulus information is represented and maintained in WM. Over the past decade, mounting evidence has demonstrated stimulus-specific representation during WM maintenance in a distributed cortical network, including sensory, parietal, and frontal cortices (Christophel et al., 2012; Ester et al., 2015; Gosseries et al., 2018; Harrison & Tong, 2009; Riggall & Postle, 2012; Serences et al., 2009; Sprague & Serences, 2013; Yu & Shim, 2017, 2019). However, the exact nature and functions of stimulus representation in different cortical regions remain controversial. Specifically, while neurophysiological studies in non-human primates have mostly emphasized stimulus representation in the frontal cortex (Funahashi et al., 1989; Fuster & Alexander, 1971; Leavitt et al., 2017), neuroimaging work in humans has reported disparate findings. During maintenance of simple visual features, stimulus representation is robustly encoded in the early visual cortex (EVC), which has been taken as the evidence in support of the sensorimotor recruitment hypothesis of WM (Harrison & Tong, 2009; Riggall & Postle, 2012; Serences et al., 2009). Meanwhile, those in the higher-order frontoparietal cortex are typically weaker and less stable (Emrich et al., 2013; Gosseries et al., 2018; Riggall & Postle, 2012; Yu & Shim, 2019). However, in dynamic environments such as those involving distraction, stimulus representation in EVC could be greatly interrupted or biased (Bettencourt & Xu, 2016; Hallenbeck et al., 2021;

Lorenc et al., 2018). In contrast, stimulus representation in the frontal cortex could be

robust under certain circumstances including attentional prioritization (Christophel et

al., 2018), categorization (Lee et al., 2013) and after extensive training (Miller et al.,

2022). To summarize, stimulus representation could vary markedly depending on

specific brain regions and memory tasks, complicating the interpretation of potential

functions of stimulus representation in WM.

In this study, we consider these apparent discrepancies from the perspective of

cognitive flexibility (Badre et al., 2021; Fusi et al., 2016; Musslick & Cohen, 2021).

We propose that changes in stimulus representation in different cortical regions might

reflect a global reconfiguration in coding strategy and resource allocation in response

to varied WM functions (Henderson et al., 2022; Lee et al., 2013). To elaborate, beyond

the passive maintenance of incoming sensory information, WM provides an online

mental workspace for active manipulation and control of stimulus contents (Baddeley,

2003; Miller & Cohen, 2001). As control functions often result in the generation and

maintenance of new information, the brain needs to manage not only the original

stimulus information but also the newly generated information in WM. Due to the

limited cognitive resources available, it is likely that original stimulus representation in

WM could adapt flexibly to various task goals beyond simple maintenance of WM

contents, which might also co-vary with changes in the representation of the newly-

generated information, leading to a systematic reconfiguration in representations of all

levels across various cortices. We make two specific predictions from this account. First,

in accordance with the findings of elevated neural activity in the frontal cortex with

increasing demand for memory manipulation (D'Esposito et al., 1999; D'Esposito et al.,

2000) and cognitive control (Badre, 2008; Badre et al., 2010; Miller & Cohen, 2001),

stimulus representation in frontal cortex should be enhanced for active-control-related

functions in WM. By contrast, due to the precise nature of stimulus representation in

visual cortex, stimulus representation in this region should be enhanced for precise-

maintenance-related functions in WM (Henderson et al., 2022; Lee et al., 2013). Second,

within the brain regions that encode the newly generated information, a dynamic

tradeoff between representations of original and new information should be observed

to achieve flexible allocation of limited cognitive resources (Badre et al., 2021; Flesch

et al., 2022).

Using functional magnetic resonance imaging (fMRI), we directly tested this

account by systematically investigating stimulus representation in visual, parietal, and

frontal cortices during WM tasks with varying demands for active control. In particular,

we surmised that stimulus representation in the frontal cortex would increase to

accommodate complex control demands such as rule-based categorization. To this end,

we employed a visual WM paradigm that required flexible switching between

maintenance and categorization tasks. Specifically, in the maintenance task,

participants maintained one visual orientation throughout a delay period, whereas in the

categorization task participants were required to categorize the remembered orientation

into one of two categories in accordance with previously learned rules, which could be

either switched randomly between two rules on a block-by-block basis (Experiment 1)

or fixed with one rule (Experiment 2). Thus, compared with the maintenance task, the

categorization task imposed additional control demand of WM information at two

different levels.

In line with our prediction, our results showed that stimulus information was more

prominently represented in the frontal cortex during categorization than maintenance

task, and this differential representation was enhanced with increasing demands for

control. Importantly, the strength of stimulus representation in the frontal cortex was

predictive of WM behavioral performance in the categorization but not in the

maintenance task, implicating a selective involvement of the frontal cortex in control

functions. By contrast, stimulus representation in the visual cortex was found to exhibit

an opposite pattern, with higher strength for maintenance than categorization task.

Moreover, varying control demands across experiments revealed a dynamic tradeoff

between stimulus and the newly-generated category representations. To further

examine whether the enhanced stimulus representation in the frontal cortex during

categorization task could be explained by global coding strategy, we simulated our

flexible WM tasks with multi-module recurrent neural networks (RNNs). The results

of this computational modeling well replicated our human data when precise stimulus

information was preserved at the output during network training. Taken together, our

results indicate the importance of the frontal cortex for flexible control in WM and

highlight the relative changes of stimulus representation in different cortical regions for

varying task demands of WM.

Results

Behavioral learning and performance of WM tasks

In the fMRI session of Experiment 1, human participants (n = 24) completed two tasks, maintenance and categorization, inside an MRI scanner. The maintenance task was a delayed match-to-sample working memory task of orientations. Participants only needed to maintained the cued orientation throughout a memory delay. In categorization task, participants also started with maintaining an orientation. After the task cue, they needed to categorize the remembered orientation into one of two categories using the cued categorization rule. Within an experimental block of nine trials, participants randomly switched between the two tasks. Across blocks, participants randomly switched between two categorization rules acquired during a preceding learning session. We randomized response mapping across trials to avoid potential influence by motor-planning signals (see Figure 1A for probe design). Prior to the main session, participants first completed a behavioral learning session to learn two categorization rules (Rule A and Rule B, see Figure 1B) that were orthogonal to each other. Participants acquired the two rules with equal familiarity ($t(23) = 0.24$, $p = 0.813$; for Rule A, $M = 0.85$, $SD = 0.050$; for Rule B, $M = 0.85$, $SD = 0.05$; Figure 1C) and comparable precision (averaged error in reported boundaries for Rule A were $8.80° \pm 6.29°$ and that for Rule B was $9.02° \pm 5.69°$; Figure 1D).

Figure 1. Experimental design and behavioral performance.
(A) Main task procedure. Each block started with a rule cue indicating the categorization rule for this block. On each trial, participants saw two orientations consecutively and were then cued to remember one of the orientations. In maintenance task (cued by letter 'P'), participants needed to maintain the remembered orientation as precisely as possible. In categorization task (cued by letter 'C'), participants needed to categorize the remembered orientation following the categorization rule of the current block. maintenance and categorization trials were interleaved within an experimental block of nine trials. Categorization rule (Rule A or Rule B) switched randomly on a block-by-block basis. Response keys ('F' and 'J') for categorization task were randomly assigned to the two categories. Each pair of keys displayed at random locations within the category to eliminate information on rule boundaries. (B) Illustration of the two orthogonal categorization rules (Rule A and Rule B). (C) Rule learning performance during learning session for Rule A (purple) and Rule B (pink). (D) Errors in participants' self-reported rule boundaries. Errors were calculated as the average distance from reported boundaries to ground truth boundaries. (E) Accuracy compared between tasks. Boxplots show the median and the 25th and 75th percentiles.

Whiskers extend to 1.5 Inter quartile range (IQR) from the quartiles. Asterisks denote
significant results, n.s.: not significant; **: $p < 0.01$. (F) Reaction time compared
between tasks. Same conventions as (E). (G) Upper panel: accuracy in relation to
distance from categorization boundaries. Lower panel: reaction time in relation to
distance from categorization boundaries. Shaded areas represent ± SEM.

Overall, participants performed equally well on both tasks in the fMRI session.

Accuracy for the maintenance task ($M \pm SD$: 0.81 ± 0.07) and that for the categorization

task (0.82 ± 0.05) did not significantly differ ($t(23)$ = 1.51, p = 0.144; Figure 1E),

suggesting that the two tasks were matched in terms of task difficulty. In line with

previous categorization studies (Ester et al., 2020; Freedman & Assad, 2006)

demonstrating a boundary effect, only in the categorization task but not in the

maintenance task did participants perform better for trials distant from category

boundaries in terms of both accuracy and reaction time (see Figure 1G). These results

demonstrated the effect of categorization and confirmed that participants faithfully

followed task instructions.

Enhanced stimulus representation in frontal cortex during categorization task

The primary goal of this study was to determine the role of stimulus representation

in various cortices in WM. Using conventional multivariate encoding and decoding

methods, we tracked stimulus (i.e., orientation) representation in three brain regions of

interest (ROIs) that have been implicated in representing WM information, including

early visual cortex (EVC), intraparietal sulcus (IPS), and superior precentral sulcus

(sPCS) (Christophel et al., 2018; Ester et al., 2015; Hallenbeck et al., 2021; Yu & Shim,

2017).

First, we used multivariate inverted encoding models (IEMs) (Brouwer & Heeger,

2009, 2011; Ester et al., 2015; Rademaker et al., 2019; Yu & Shim, 2017) to reconstruct

orientation representation at the population level in each ROI. Figure 2A shows

example orientation reconstructions from representative time points, and Figure 2C

demonstrates the time course of orientation reconstruction as quantified by

representational fidelity. A larger fidelity value indicates a stronger orientation

representation (Figure 2B). In EVC, we found significant orientation representation in

both maintenance and categorization tasks starting from the sample period (Figure 2C

left panel; see Supplemental Table 1 for full statistics), even when the categorization

task did not require explicit memory of stimulus information. Additionally, the strength

of orientation representation in the maintenance task became significantly higher than

that in the categorization task after the task cue during the delay, suggesting the strength

of orientation representations in EVC reflected the degrees of task demands for

maintaining visual details. In IPS, orientation representation was significant in both

tasks, but did not differ from each other at most time points (Figure 2C middle panel).

In sPCS, a reversed pattern was observed. In the maintenance task, orientation

information was maintained during early delay period and then dropped to baseline

level during late delay period. By contrast, in the categorization task, orientation

representation was persistent throughout the delay and response periods. The strength

of orientation representation in the categorization task became statistically higher than

that in the maintenance task in late delay period (Figure 2C right panel), suggesting that

this differential representations of visual stimulus in the frontal cortex reflected the

demand for active control of memory contents. To facilitate comparison of the

differential stimulus representation across ROIs, we averaged the difference in

representational strength across a late task epoch (11 – 16 s), and the difference in

stimulus representation between ROIs remained (Figure 2D).

Figure 2. Orientation reconstructions at the population level using IEMs.
(A) Reconstructed population-level orientation representations from selected time
points at EVC, IPS, and sPCS for maintenance (blue) and categorization (orange) tasks,
respectively. X axis represents distance from the cued orientation (at 0º), and y axis
represents reconstructed channel responses in arbitrary units. Significant orientation
representation was observed at 6 s and 12 s but not at 0 s. Shaded areas represent ±
SEM. (B) To quantify the strength of orientation reconstructions, we calculated the
reconstruction fidelity by first projecting the channel response at each orientation onto
a vector at the cued orientation and then averaging the projected vectors. (C) Time
course of representational strength of orientations at EVC, IPS and sPCS. Gray shaded

areas indicate the entire memory delay following task cue. Blue and orange dots at the bottom indicate the FDR-corrected significance of representational fidelity at each time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). The bottom black dots indicate significant difference in representational fidelity between tasks (uncorrected). Horizontal dashed lines represent a baseline of 0. Shaded areas represent $\pm$ SEM. (D) Average difference of representational strength across 11 – 16 s in each ROI (from EVC to sPCS: $p < 0.00001$, $p = 0.063$, $p = 0.007$, respectively). Positive difference indicates higher representational strength for categorization, and vice versa for negative difference. Black asterisks denote FDR-corrected significance, *: $p < 0.05$; **: $p < 0.01$; ***: $p < 0.001$.

We validated the difference in stimulus representations through a series of control analyses. First, we demonstrated that these results cannot be explained by the specific model used to train the data (Liu et al., 2018; Sprague et al., 2018) nor the specific analytical approach used, because similar patterns were observed when we trained the IEM separately for each condition (Figure S2A) or adopted a Support Vector Machine (SVM) decoding approach (Figure S2D) (Henderson et al., 2022; Rademaker et al., 2019). Mean activation differences between tasks cannot account for the results either, because when we removed the mean differences in BOLD activity between tasks, the difference in representational strength remained (Figure S2C). Furthermore, to remove the potential impact of voxel number on IEM, we selected the top 500 of most sample- or delay-selective voxels from each ROI and trained IEM using the selected voxels. Again, this analysis yielded similar findings (Figure S2B). Together, these results demonstrated enhanced stimulus representation in the frontal cortex with increased demand for active control, as well as those in the visual cortex with increased demand for precise WM maintenance.

Prediction of categorization behavior by frontal stimulus representation

Previous WM studies have shown that the strength of stimulus representation in

EVC positively correlated with memory performance (Emrich et al., 2013; Ester et al.,

2013; Gosseries et al., 2018), suggesting that EVC plays an important role in precise

WM maintenance. However, stimulus representation in the frontal cortex rarely

predicted behavioral performance in maintenance task (Hallenbeck et al., 2021).

Nevertheless, if frontal stimulus representation is involved in WM control, its

behavioral relevance should be subject to observation with increased control demands.

Therefore, we assessed the behavioral predictability of stimulus representation during

the delay period in EVC, IPS, and sPCS (Figure 3). Consistent with previous findings,

we found the strength of stimulus representation in EVC during the early delay period

predicted behavioral accuracies in both maintenance and categorization tasks (see

Supplemental Table 2 for full statistics). Similar predictability was found in IPS, with

stimulus representation predicted behavior in the maintenance task during early delay

and in the categorization task throughout the entire memory delay. Interestingly, we

found that, throughout the entire memory delay, the strength of stimulus representation

in sPCS predicted behavioral accuracies only in the categorization task but not in the

maintenance task. These results highlighted the functional significance of stimulus

representation in sPCS exclusively for the categorization task.

Figure 3. Behavioral correlation of stimulus representation for maintenance (blue) and
categorization (orange) tasks.
(A) Time course of correlation coefficients in EVC, IPS, and sPCS. Gray shaded areas
indicate the entire memory delay following task cue. Blue and orange dots at the top
indicate significance of correlation (uncorrected) at each time point at $p < 0.05$ (small),
$p < 0.01$ (medium), and $p < 0.001$ (large). (B) Correlation scatter plots at representative
time points (7 s and at 12 s) in EVC, IPS, and sPCS. R denotes Pearson correlation
coefficients. Asterisks denote significant results, *: $p < 0.05$; **: $p < 0.01$.

Reduced frontal stimulus representation with lower control demand

In Experiment 1, participants flexibly switched between two categorization rules

to prompt the manipulation of WM content on a trial-by-trial basis. The rule switching

increased control demand but also complicated the interpretation of our results. To

exclude potential impact of rule switching, we conducted Experiment 2, in which

participants performed maintenance and categorization tasks with only one fixed rule.

Behavioral results of Experiment 2 again demonstrated a classic boundary effect and

were comparable to Experiment 1 (Figure S1), with no significant difference between

experiments in terms of either accuracy or reaction time (Fs < 1.28, ps > 0.26). When

using IEMs to reconstruct stimulus representation, we found EVC and IPS both showed

patterns similar to those in Experiment 1 (Figure 4A), with stimulus representation

decreased in EVC in categorization task and remained at the same level in IPS between

the two tasks (see Supplemental Table 3 for full statistics). The frontal region, sPCS,

also showed a differential enhancement of stimulus representation in categorization

task as in Experiment 1, but in an earlier delay period (Figure 4A). To validate such a

temporal difference, we defined an additional early task period (5 – 10 s), and confirmed

a significant difference in stimulus representation in sPCS during the early (p = 0.015;

Figure 4B) but not during the late epoch (p = 0.372; Figure 4C). In addition, we

performed a mixed ANOVA on experiments (Experiment 1 vs. 2) and epochs (early vs.

late epoch) and observed a significant interaction effect between the two, $F(1, 46)$ =

7.43, p = 0.009, suggesting that the two experiments differed in terms of the temporal

emergence of the differential stimulus representation in the frontal cortex. Taken

together, these results are consistent with our expectation that, with reduced control

demand, the differential enhancement of stimulus representation in frontal cortex was

still present but decreased during late memory delay. Nevertheless, stimulus

representation in Experiment 2 still predicted behavioral performance as in Experiment

1, although the difference between task was reduced (Figure S3).

Figure 4. Orientation reconstructions in Experiment 2 at the population level using
IEMs.
(A) Time course of representational strength of orientations at EVC, IPS and sPCS.
Gray shaded areas indicate the entire memory delay following task cue. Blue and
orange dots at the bottom indicate the FDR-corrected significance of representational
fidelity at each time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$
(medium), and $p < 0.001$ (large). The bottom black dots indicate significant difference
in representational fidelity between tasks (uncorrected). Horizontal dashed lines
represent a baseline of 0. Shaded areas represent ± SEM. (B) Average difference of
representational strength across an early task epoch (5 – 10 s) in each ROI. Positive
difference indicates higher representational strength for categorization, and vice versa
for negative difference (FDR-corrected). n.s.: not significant; *: $p < 0.05$; ***: $p < 0.001$.
(C) Average difference of representational strength across a late task epoch (11 – 16 s)
in each ROI. Same conventions as (B).

Category representation in WM in various cortices

Having observed a differential representation of stimulus in the frontal cortex, we

next asked how newly generated information in WM during the categorization task

emerged and sustained in the distributed WM network and how representations of the

original stimulus and new information interacted. The categorization task could demand

additional generation of category information in WM. We therefore trained SVMs to

decode category information during the categorization task. For each rule, the SVM

decoder was trained to discriminate between the two categories. In both experiments,

we found that during the late epoch, category information could be well decoded across

ROIs (*ps* < 0.044, Figure 5A; also see Figure S4A for full decoding time course), with

a marginal difference between experiments in sPCS (*p* = 0.055).

One might argue that the category decoding results could at least be partially

attributed to stimulus similarity. To minimize the impact of stimulus similarity on

category decoding, we additionally trained another decoder using the opposite rule (i.e.,

using category labels from the orthogonal rule). We then calculated an abstract category

index by subtracting decoding accuracy under the opposite rule from that under the true

rule (Mok & Love, 2020) (Figure 5B). The rationale was that the amount of stimulus

similarity would be comparable for the opposite rule, but additional category

information, if existed, should result in higher decoding accuracy for the true rule. After

removing stimulus-related signals, average decoding performance of abstract category

was only evident in Experiment 2 (*ps* < 0.017) but not in Experiment 1 (*ps* > 0.14) for

all ROIs. Moreover, decoding performance of abstract category was significantly higher

in Experiment 2 than Experiment 1 in sPCS (*p* = 0.034; Figure 5C). These results

together suggest a potential tradeoff between stimulus difference and category

representation in the frontal cortex.

Figure 5. Decoding performance for category and abstract category information.

(A) Average category decoding accuracy across the delay period (11 – 16 s) in each
ROI of both experiments, black asterisks denote FDR-corrected significance, n.s.: not
significant; *: $p < 0.05$; ***: $p < 0.001$. (B) Schematic illustration of abstract category
decoding. In categorization task, category information can be decoded using category
labels according to the true categorization rule. On the other hand, category can also be
decoded due to stimulus similarity. Thus, to remove stimulus-dependent categorical
information, we calculated an abstract category index by removing decoding accuracy
using orthogonal category boundaries (assuming comparable stimulus-dependent effect)
from that using true rule boundaries. (C) Average abstract category decoding index
across the delay period (11 – 16 s) in each ROI of both experiments, black asterisks
denote FDR-corrected significance, n.s.: not significant; *: $p < 0.05$; **: $p < 0.01$.

Differential stimulus representation in frontal cortex replicated by RNN modeling

Lastly, we tested how stimulus representation could emerge in frontal cortex at the

mechanistic level using recurrent neural network (RNN) models. Our hypothesis is that

precise stimulus representation during WM might emerge in frontal cortex in response

to complex task demands such as rule-based categorization. In other words, instead of

relying (solely) on category representations, the cortical network might have adopted a

different strategy to accommodate the flexible task requirements in the current study,

for instance, by preserving stimulus information until a later stage of information

processing. This different strategy can be implemented by altering the RNN's output

structure. Therefore, the logic of this modeling analysis was to examine whether

explicitly placing a demand for the model to preserve stimulus representation would

recapitulate our fMRI findings in frontal cortex, in comparison to a model that did not

specify such a demand.

Two types of modular RNNs were trained on the maintenance and categorization

tasks simultaneously (Masse et al., 2019; Zhou et al., 2021). The networks shared

common input and hidden layer structures (i.e., orientation-tuned and retro/task cue-

related units as the input layer, recurrent units with short-term synaptic plasticity in the

hidden layer (80% excitatory + 20% inhibitory units, equally distributed in three

separate modules). The only difference was in the structure of the output layer. The first

type of RNN (RNN1; n = 20) had only two units in the output layer to indicate networks'

choice (Figure 6A), whereas the second type of RNN (RNN2; n = 20) had additional

units in the output layer corresponding to the original stimulus information. In other

words, the second RNN was designed to maintain stimulus information throughout the

network modules. For the common hidden layer, we included three hierarchically

organized (posterior, middle, and anterior) modules of recurrent units generated

according to neurobiological principles of neuronal connections (e.g., denser

connectivity within than between modules) to simulate the interconnected brain areas

in our ROI-based fMRI analyses above: the posterior module (Module 1, simulating

EVC) was directly connected with the input layer, the middle module (Module 2,

simulating IPS) received projections from the posterior module and relaying

information to the anterior module, and the anterior module (Module 3, simulating

sPCS) projected to the output layer. Task events were simulated as numerical inputs to

the model, matching the procedures of Experiment 1 (see Methods for details).

After successful training, defined as reaching at least 90% accuracies in all tasks in

the same training batch, we applied an SVM decoding approach to investigate

population-level stimulus representations in neuronal spiking activities of the RNNs.

We found that in RNN1, both the middle and anterior modules showed stronger

stimulus representation in the maintenance task than the categorization task during the

delay period ($p_{posterior}$ = 0.09, p_{middle} = 0.011, $p_{anterior}$ = 0.007; Figure 6B and Figure S7A),

opposite to our fMRI observation in IPS and sPCS. In comparison, decoding

performance in RNN2, which was explicitly required to maintain stimulus information

for the output, yielded results consistent with our human findings, with increased

stimulus decoding performance during categorization only in the anterior module

($p_{posterior}$ = 0.436, p_{middle} = 0.212, $p_{anterior}$ = 0.026; Figure 6B).

Besides difference in stimulus representation, we further tested whether RNN2

could also replicate the human results on category representation. For this analysis we

focused on abstract category representation to fully remove the impact of stimulus on

category decoding. To examine the influence of control demand on category decoding,

following our fMRI experiment we trained 20 additional RNNs with the same output

structure as RNN2 (preserving stimulus information) to perform the tasks with a fixed

categorization rule, mimicking the task structure of Experiment 2. Consistent with our

human findings, we observed increased abstract category decoding performance in the

fixed-rule RNNs compared to the flexible-rule RNNs, throughout the modules ($p_{posterior}$

= 0.045, p_{middle} = 0.003, $p_{anterior}$ < 0.001; Figure 6C). By contrast, abstract category

decoding in RNN1 across modules demonstrated a distinct pattern from human data,

with numerically increasing decoding accuracy towards later modules (Figure 6C).

Altogether, these findings demonstrated that our fMRI results could be simulated

by RNN models when stimulus information for readout was preserved, suggesting that

the requirement for flexible control of WM content could demand high-fidelity stimulus

representation at the output stage of the model. Notably, we found that RNN2 generally

took less iterations for training and had fewer failures in learning the task (with a

defined maximal number of iterations).

Figure 6. Architecture of RNNs and simulation results.

(A) All networks consist of 3 layers of artificial units: the input, hidden and output
layers. For both RNN1 and RNN2, the input layer contains 20 units including 15
orientation-tuned, red) units and 5 cue units (retro-cue and task cue, orange and yellow).
The hidden layer consists of three modules of 200 recurrent units with short-term
synaptic plasticity (STSP), further divided into 80% excitatory (black) and 20%
inhibitory (white). Connectivity within each module (black arrow) is denser compared
to between modules (red and green arrows), which only occur between excitatory units.
Only excitatory units in module 1 receive projections from the input layer and only
excitatory units in module 3 project to the output units. For RNN1, networks output
(0,1) or (1,0) through the 2 units in the output layer to indicate responses. For RNN2,
the network output (0,1) or (1,0) to report the category to which the cued orientation
belonged in the categorization task, or (0,0) in the maintenance task (blue units).
Importantly, the models also output the orientation itself through 15 additional
orientation-tuned units (red). (B) Difference in orientation decoding between tasks in
RNN1 and RNN2. Results were averaged across the delay period. Positive difference
indicates higher decoding accuracy for categorization, and negative difference indicates
higher decoding accuracy for maintenance. Error bars represent ± SEM. Black asterisks
denote FDR-corrected significance, n.s.: not significant; *: $p < 0.05$; **: $p < 0.01$; ***:

p < 0.001. (C) Average abstract category information across the delay period for RNN1
and RNN2. Same conventions as (B).

Discussion

In this study, we investigated the emergence and maintenance of stimulus

representation with varied control demands of WM. In a distributed human cortical

network encompassing visual, parietal, and frontal cortex, we found enhanced stimulus

representations in the frontal cortex that tracked increasing demands on active WM

control, as well as enhanced stimulus representations in the visual cortex that tracked

the demand for the precise maintenance of WM content. The enhanced stimulus

representation in frontal cortex was well predicted by RNNs that preserved stimulus

information for readout at the output stage. Together, these results highlight the unique

and critical contributions of stimulus representations in different cortical regions for

distinct aspects of WM, and help to resolve the current controversy in the roles of

various cortices in WM.

Role of visual cortex in WM maintenance

The visual cortex has been considered a critical site for maintaining visual WM in

the context of sensorimotor recruitment hypothesis (D'Esposito & Postle, 2015;

Harrison & Tong, 2009). This idea, however, has been challenged in recent years due

to some seemingly contradictory findings from the human neuroimaging studies. For

example, compared to the frontoparietal cortex, mnemonic representations in EVC

were found to be more vulnerable to distractors (Bettencourt & Xu, 2016; Hallenbeck

et al., 2021; Lorenc et al., 2018). The decodability of memory contents in visual cortex

also depends on the specific task type. A previous study showed that in nonvisual tasks

that required judgements on object category instead of visual details, memory contents

were no longer decodable in the visual cortex (Lee et al., 2013). In this study, we found

that, although the strength of stimulus representation in EVC differed between WM

maintenance and categorization tasks, a copy of stimulus representation remained in

EVC during the categorization task. Moreover, stimulus representations in both tasks

were equally predictive of subsequent memory performance, suggesting the functional

significance of EVC representations in WM.

The discrepancy between our results and that of the previous work (Lee et al.,

2013) could be attributed to the fact that our categorization task required participants to

manipulate remembered information according to arbitrary yet flexible categorization

rules, rather than simply paying selective attention to different aspects (visual details

vs. category membership) of everyday objects. In our case, maintaining visual details

of the memoranda was critical for accurate behavioral responses. Our finding is

consistent with the prediction of sensorimotor recruitment hypothesis that

representation of memory contents in the visual cortex is necessary for the precise

maintenance of visual information. The observation of robust category representation

in early visual cortex during the response period further indicated the recruitment of

EVC in categorization, possibly for boundary comparison and rule implementation. In

fact, our results are consistent with a recent study demonstrating significant stimulus

representation in EVC even when memoranda had been transformed into a motor

format (Henderson et al., 2022). In addition, electrophysiological research in non-

human primates has also shown robust feature selectivity in the visual cortex during a

categorization task (Brincat et al., 2018), and recent computational modeling work has

suggested intact maintenance of sensory information during categorical judgements

(Luu & Stocker, 2021).

Role of frontal cortex in active WM control

Compared to the prominent role of EVC in memory maintenance, sPCS in the

frontal cortex played a dominant role in WM tasks that require active control of memory

contents such as categorization. Although stimulus representations in sPCS have been

observed during WM in previous studies, the nature of these representations remained

debatable. In WM tasks that required mere maintenance of memoranda, stimulus was

not always decodable in the frontal cortex (Emrich et al., 2013; Gosseries et al., 2018;

Riggall & Postle, 2012), raising the issue of functional significance of stimulus

representation in the frontal cortex. On the other hand, stimulus representation in the

frontal cortex could become robust in the face of tasks that require attentional

prioritization and extensive training (Bettencourt & Xu, 2016; Christophel et al., 2018;

Hallenbeck et al., 2021; Lorenc et al., 2018; Miller et al., 2022). Our current study

contributes to the resolution of this issue by demonstrating that stimulus representation

in sPCS increased with increasing demands for WM control. This finding is in line with

recent computational studies proposing that active WM functions may involve neuronal

mechanisms different from that for passive maintenance. For example, passive

maintenance could rely mainly on synaptic plasticity mechanisms, whereas active

control functions such as distractor resistance and information manipulation involve

more neuronal spiking activity (Masse et al., 2019; Wang, 2021). In this study, we

provided the first empirical evidence that the frontal cortex exhibits enhanced stimulus

representation in categorization task requiring active WM control and this

representation is predictive of WM performance. In contrast, stimulus representation of

WM maintenance failed to predict WM performance at high control demand. It would

be of interest to further investigate whether this active control in the frontal cortex could

be generalized to tasks that require other types of WM control such as mental rotation.

WM representations in frontal cortex support cognitive flexibility

Our results in the frontal cortex are also in line with recent theoretical proposals in

the field of cognitive flexibility. To behave flexibly in complex environments with

limited cognitive resources, two mechanisms have been proposed: low-dimensional

abstraction of stimulus representation for generalization and efficient learning, and

high-dimensional stimulus representation for separability and flexible readout (Badre

et al., 2021; Flesch et al., 2022; Fusi et al., 2016). Within this framework, high-

dimensional stimulus representations during WM might emerge in the frontal cortex in

response to complex control demands such as rule-based categorization. The results of

the two fMRI experiments in the current study jointly demonstrate a dynamic tradeoff

between high-dimensional stimulus and low-dimensional category representations

depending on the control demand. Specifically, when control demand was reduced with

a single categorization rule in Experiment 2 compared to Experiment 1, the differential

stimulus representation in the frontal cortex was also reduced during the late delay

period, accompanied by an increase in category decoding performance especially in the

frontal cortex. This result is consistent with neurophysiological findings in non-human

primates: while robust category selectivity was observed in frontoparietal cortex during

the delay period of categorization tasks when the animal was trained on the

categorization task only (Brincat et al., 2018; Freedman & Assad, 2006; Freedman et

al., 2001; McKee et al., 2014), category selectivity in the parietal cortex was

significantly reduced when the animal had been exposed to a maintenance task prior to

categorization training (Latimer & Freedman, 2023). Our RNN simulation further

confirmed that this dynamic reconfiguration in information coding at the network level

can be well explained by a change in the coding strategy for the network readout. In

other words, in flexible environments, and with rich prior experience, the brain might

adopt an entirely different strategy for processing information in WM. High-

dimensional stimulus information might be preserved in its original identity in the

higher-order cortex, potentially reducing processing demands in dealing with each task

and thereby facilitating efficiency and flexibility (Badre et al., 2021; Flesch et al., 2022;

Fusi et al., 2016). One important future direction would be to further address the meta-

control mechanisms that determine the flexible selection of coding strategies for WM

(Eppinger et al., 2021).

Differentiating between frontal and parietal cortex in WM functions

While many previous WM studies have focused on the functional distinction

between sensory and frontoparietal cortex, it has remained less clear how frontal and

parietal cortex might differ in terms of WM functions. Some studies have reported

stimulus representations with similar functionality in frontal and parietal cortex

(Christophel et al., 2018; Yu & Shim, 2019), while others have observed differential

patterns (Hu & Yu, 2023; Lee et al., 2013; Li et al., 2023). We interpret the differential

patterns as reflecting a difference in the potential origin of the corresponding cognitive

functions. For example, in our study, sPCS demonstrated the most prominent effect for

enhanced stimulus representation during categorization as well as the tradeoff between

stimulus difference and category representation, suggesting that sPCS might serve as

the source region for such effects. On the other hand, IPS did show visually similar

patterns to sPCS in some analyses. For instance, stimulus representation in IPS was

visually but not statistically higher in the categorization task. These results together

support the view that our findings in sPCS do not occur in isolation, but rather reflect a

dynamic reconfiguration of functional gradients along the cortical hierarchy from early

visual to parietal and then to frontal cortex.

Conclusion

In conclusion, we observed a distributed cortical network, including early visual,

parietal, and frontal cortex, in representing stimulus-specific information in WM. These

stimulus representations in visual and frontal cortex played distinct functional roles,

with those in EVC contributing primarily to precise maintenance and those in frontal

584 cortex contributing primarily to active control in WM. RNN simulations indicated that

585 the stimulus representation in the frontal cortex might have emerged as a result of output

586 selection to facilitate cognitive flexibility. Collectively, these results help to reconcile

587 current debates on the functional roles of different cortical regions in WM, and provide

588 new insights into how a unified WM framework could support varied control demands.

590 **Methods**

591 **Participants**

592  A total of 54 participants were recruited at Chinese Academy of Sciences,

593 Shanghai Branch. Twenty-six healthy participants (21 female, all right-handed, mean

594 age = 24.0 ± 1.4 years) were recruited for Experiment 1. Two were excluded due to

595 failure in completing the experiment or low conformity to task instructions, remaining

596 24 participants who completed the main experiment (19 female, mean age = 23.92 ±

597 1.41 years). Twenty-eight (22 female, mean age = 24.14 ± 1.51 years) participants were

598 recruited for Experiment 2. Two quitted after behavioral training and two did not finish

599 scanning due to technical problems with the scanner, resulting in 24 participants (20

600 female, mean age = 24.13 ± 1.60 years) in the final analyses. All participants were

601 neurologically healthy and eligible for MRI, had normal or corrected-to-normal vision,

602 provided written informed consent approved by the Ethics Committee of Institute of

603 Neuroscience, Center for Excellence in Brain Science and Intelligence Technology,

604 Chinese Academy of Sciences, and were monetarily compensated for their participation.

605 Sample sizes were not estimated a priori but were comparable and even superior to

those in previous studies.

Stimuli and Procedure

All stimuli were generated and presented using MATLAB (The MathWorks) and

Psychtoolbox 3 extensions (Brainard, 1997; Pelli, 1997). During behavioral training,

stimuli were presented on a ThinkVision monitor at a viewing distance of 45 cm.

Behavioral responses were acquired with a keyboard. During scanning, stimuli were

projected onto a SinoRad monitor (1280 x 1024 pixels, refreshing at 60 Hz) viewed

through a coil-mounted mirror in the scanner at a viewing distance of 90.5 cm.

Participants' behavioral responses were acquired with a Sinorad MRI-compatible

button box.

Behavioral Training

In Experiment 1, prior to scanning, participants were trained to learn two novel

rules, Rule A and Rule B, for categorizing orientations. Thirty oriented bars were used

as sample stimuli, ranging from 5° to 179° (in increments of 6°; two participants used

another set of thirty orientations ranging from 4° to 178°). Each abstract rule was

constructed by two orthogonal boundaries that divided the thirty orientations into two

categories with fifteen orientations each. Rule A and Rule B were orthogonal to each

other. Corresponding boundaries were 20°/110° and 65°/155° (15°/105° and 60°/150°

for the two participants using different stimuli sets).

Participants learned new rules through a rule learning task. Each run of learning

started with a rule disk informing the target rule. To avoid any potential verbal coding, rule specifics were visually illustrated as rule disks containing two distinct colors (colors randomly assigned to categories every time; see Figure 1A for an example). Rule disk was presented on the screen for 2 s followed by 1 s of fixation. On each trial, an oriented bar (radius=7°) was presented for 1 s followed by a delay of 1 s. Participants were instructed to report the category of the orientation by pressing a response key ('F' or 'J'). To avoid category-response mapping, we randomized the relationship between categories and key buttons across trials. Moreover, to avoid presenting rule boundaries explicitly, we presented key names at random positions within the range defining each category. In other words, participants had to memorize the exact rule boundaries as accurately as possible in order to find the correct key buttons for each trial. Feedback was given at the end of each trial to assist learning.

Participants completed 30 learning trials in each run. They reviewed rule disks after every 10 trials for memory reconsolidation. Each participant completed at least two runs for each rule. After achieving an average accuracy above 86% (26 out of 30 trials) for the first rule, they proceeded to learn the other rule and then to practice the main task for scanning (see next section). Learning order of rules was counterbalanced across subjects. Upon completion of practicing, participants needed to report the boundaries of learned rules as a qualification of behavioral training. If the total error in reported boundaries had exceeded 20°, participants had one more chance to learn by repeating the learning task. Two participants completed one additional behavioral training to recap rule knowledge prior to scanning.

Behavioral training for Experiment 2 followed the same procedure and used the

identical sample set (30 orientations ranging from 4° to 178°) as Experiment 1, except

that only one rule was trained. Half of the participants in Experiment 2 learned rule

boundaries of 19°/109°; the other half learned rule boundaries of 67°/157°.

Flexible WM Task (fMRI Task)

In Experiment 1, during scanning, participants completed a flexible WM task

which implemented levels of control demand with different rules. To be specific,

participants randomly switched between a maintenance task and a categorization task.

In the maintenance task, participants needed to memorize stimulus information (i.e.,

orientations). In the categorization task, participants needed to categorize orientations

following the rule that was randomly assigned and cued on a block basis. Procedure of

the main task was visualized in Figure 1A. At the beginning of each block, participants

were presented with a rule disk for 3 s, followed by a 2-s interval, instructing the

categorization rule of the current block. For each trial, participants saw two oriented

bars presented successively. Each bar was presented for 0.75 s, with an inter-stimulus-

interval of 0.5 s. Sample sets were the same as those used in behavioral training. After

a 0.5-s interval, a retro-cue occurred for 0.5 s, indicating the orientation of which

participants should remember. After a 1.5-s delay, a task cue was displayed at fixation

for 0.5 s, following by an 8-s memory delay. The task cue was either a letter 'P' on

maintenance trials, instructing participants to maintain the cued orientation during

memory delay as precisely as possible; or the task cue was a letter 'C' on categorization

trials, asking participants to categorize the cued orientation using the block rule during

the delay. Then, participants were probed to respond within 2 s. On maintenance trials,

participants needed to select the memorized orientation from two probe orientations;

while on categorization trials, participants needed to report the category of the cued

orientation. Response mapping followed the same operation as in the learning tasks.

Inter-trial-intervals were randomly selected from 3, 5, and 7 s with an equal trial number,

resulting in an average trial length of 20 s. Participants switched to the next block after

every six categorization trials and three maintenance trials. Each run contained two

blocks (i.e., 18 trials).

In Experiment 2, to isolate potential effect of rule switching, the categorization rule

stayed the same throughout the experiment. In Experiment 2, participants randomly

switched between the maintenance task and the categorization task. Each trial followed

the same procedure as Experiment 1.

In Experiment 1, orientations, tasks, and cued target order (1st or 2nd) were

counterbalanced across trials, resulting in an equal trial number of 90 across all three

conditions (categorization-Rule A, categorization-Rule B, and maintenance). Nineteen

out of the twenty-four participants completed 15 runs of the main task. One participant

completed 13 runs due to technical difficulties with the scanner. Another four

participants completed 30 runs across two scan sessions. The same counterbalancing

procedure was conducted for Experiment 2 (90 trials for maintenance task and 180 trials

for categorization task). In Experiment 2, six participants completed 15 runs of 18 trials;

the other seven completed 18 runs of 15 trials each due to scanner limitations. At the

end of scanning, participants reported the rule boundaries three times as a final check

of their rule memory.

Data Acquisition

MRI data of Experiment 1 were collected using a 3 Tesla Siemens MRI scanner

(Tim Trio; Siemens Healthineers) with a 32-channel head coil at the Functional Brain

Imaging Platform at Institute of Neuroscience, Center for Excellence in Brain Science

and Intelligence Technology, Chinese Academy of Sciences. Functional scanning was

performed using a gradient-echo echo-planar sequence with the following parameters:

repetition time (TR) = 1000 ms; echo time (TE) = 30 ms; flip angle (FA) = 40°; voxel

size = 3 x 3 x 3 mm; multi-band accelerate factor = 4; matrix size = 74 x 74; slice

number = 60. A high-resolution anatomical T1 image was collected before functional

scanning (TR = 2300 ms; TE = 2.98 ms; FOV = 256 x 240 x 192 mm; voxel size = 1 x

1 x 1 mm). During scanning, participants' head positions were restricted with

surrounding paddings to prevent head movements. MRI data of Experiment 2 were

collected using identical procedure and settings except that the last eleven participants

were scanned using a newly installed 3 Tesla Siemens MRI scanner (Prisma; Siemens

Healthineers) at the Functional Brain Imaging Platform.

Preprocessing

All preprocessing of individual MRI data was performed using AFNI

(afni.nimh.nih.gov) (Cox, 1996; Cox & Hyde, 1997). Functional data of all runs were

registered to the last volume of the final run with the first eight volumes of each run

removed. Then, individuals' aligned functional data were registered to their

corresponding T1 volume. Alignment of registration was manually checked for each

subject to ensure quality. The registered data were further motion corrected and

detrended.

ROI Definition

Our primary ROI-based analyses focused on three most commonly-studied, WM-

related brain areas: early visual cortex (EVC), intraparietal sulcus (IPS) in parietal

cortex, and superior precentral sulcus (sPCS) in frontal cortex (Ester et al., 2015;

Hallenbeck et al., 2021; Yu & Shim, 2017). We created anatomical ROI masks based

on the probabilistic atlas by Wang and colleagues (Wang et al., 2015). EVC (merging

bilateral V1, V2, and V3), IPS (merging bilateral IPS0-5), and sPCS masks were

generated by warping masks from the probabilistic atlas to individuals' anatomical

image in their native space. In order to generate functional ROI masks, we then

performed general linear models (GLMs) to quantify task-related univariate activity

changes in each voxel. Task events were modeled using boxcar functions convolved

with a canonical hemodynamic response function (durations of event epochs for sample,

post retro-cue delay, memory delay, and response were 2.5 s, 2 s, 8.5 s, and 2 s,

respectively). Six nuisance regressors were also included to account for head motion

artifacts in the six dimensions of rigid body motion. Functional EVC mask was defined

by the 500 most active voxels during sample display. Functional IPS and sPCS masks

were defined by the 500 most active voxels during memory delay.

MRI Data Analyses

Multivariate Inverted Encoding Modeling (IEM)

Neural representations of orientations were reconstructed using inverted encoding

modeling (IEM) (Brouwer & Heeger, 2009, 2011; Ester et al., 2015; Rademaker et al.,

2019; Yu & Shim, 2017) with custom MATLAB scripts on individuals' BOLD

activation patterns in the three ROIs. IEM provides an estimate of population-level

reconstructions of stimulus-specific information. The general procedure for IEM

includes using training data to train model weights and then applying weights to testing

data to obtain reconstructed channel responses. For the main analyses, we used trials

from all conditions to train and to test IEM in order to avoid potential biases from a

specific task condition. Results for categorization task were averaged across rules for

Experiment 1. Training and testing were performed for each TR separately. As a control,

IEMs were also estimated for each condition separately (within-condition IEM).

Training and testing underwent a leave-one-run-out cross-validation procedure, in

which each run was taken out as the testing run, and the rest of the data served as the

training run. This procedure was iterated until all runs had served as training and testing

runs. Results from all cross-validated folds were averaged. Detailed computations for

each fold were elucidated below:

We first modeled responses of voxels into nine equidistant orientation channels

(initial channels were 1°, 21°, 41°, 61°, 81°, 101°, 121°, 141°, 161°), characterizing

voxel selectivity for orientations. At each channel, the modeled orientation tuning curve was a half-wave-rectified and squared sinusoid raised to eighth power, defined as the function below (c was the center of the channel):

$$\int (\theta) = \cos (\theta - c)^8$$

Population-level tuning responses of voxels was described using the function:

$$B_1 = W C_1$$

B_1 was the training dataset from our fMRI data (v voxels $\times n$ trials). C_1 represented the hypothesized channel responses (k channels $\times n$ trials) which were modulated by W, a weight matrix (v voxels $\times k$ channels).

The least-squared estimates of the weight matrix ($\widehat{W}$) was computed using linear regression:

$$\widehat{W} = B_1 C_1^T (C_1 C_1^T)^{-1}$$

The weight matrix was then applied on the test dataset to reconstruct estimated channel responses ($\hat{C}_2$):

$$\hat{C}_2 = (\widehat{W}^T \widehat{W})^{-1} \widehat{W}^T B_2$$

The analysis above were repeated for 20 times in step of 1° using leave-one-run-out cross-validation so that the nine channel centers covered all 180 orientations (Rademaker et al., 2019; Yu & Postle, 2021). All channel responses were combined to create responses for all 180 orientation channels. For statistical comparisons and for visualization, all channel responses were shifted to a common center of 0° (true orientation of trials). The responses from all trials were averaged to obtain reconstructed orientation representations for the test datasets.

To quantify the strength of each IEM reconstruction, we calculated reconstruction

fidelity of channel responses. First, all channel responses were projected to the vector

at the true orientation. Then the reconstruction fidelity was calculated as the mean of

all projected vectors (Rademaker et al., 2019). A larger fidelity value indicates a

stronger positive representation of orientation.

Multivariate Pattern Analysis (MVPA)

Besides IEM, we tracked neural representations of stimulus and of category using

linear Support Vector Machine (SVM) decoders. All decoding analyses were performed

using the templateSVM and fitcecoc functions in MATLAB.

Decoding of stimulus was performed for every TR. We divided the thirty

orientations into four bins of 45° each, two cardinal bins centered at 90° or 180° and

two oblique bins centered at 45° or 135°. We then performed two two-way

classifications, one trained and tested on cardinal bins, and the other trained and tested

on oblique bins. We trained and tested decoders separately for each condition using the

same leave-one-run-out cross-validation procedure as in IEM analyses. To avoid biases

in model training, we randomly balanced the trial numbers for each bin in the training

set. Decoding accuracies were then computed by averaging performance of cardinal

and oblique classifiers. For the categorization task, we averaged accuracies across rules.

Decoding of category information for Experiment 1 was performed under each

rule (90 trials for each rule) using a leave-one-trial-out cross-validation procedure (see

next paragraph for details), and the decoding accuracies were then averaged across rules.

Since Experiment 2 adopted a fixed rule with 180 trials in the categorization task, we

randomly divided categorization trials into two halves with 90 trials each, and decoded

category information for Experiment 2 using identical procedures as for Experiment 1.

Because closer orientations are more similar to each other inherently, orientations

per se could contain categorical information by visual similarity. Thus, to isolate the

influence of stimulus on category, in addition to the decoder using true category labels,

we trained an opposite category decoder using category labels based on the opposite

rule. If the two-way classification on categories only captured stimulus information,

then true category and opposite category decoding should have had comparable

performance. If abstract category information existed beyond stimulus information,

then true category decoder should have outperformed the opposite category decoder.

Thus, an abstract category index was calculated by subtracting opposite category

decoding accuracy from true category decoding accuracy (i.e., chance level = 0). Since

the opposite category decoding used re-assigned labels, to eliminate imbalance in trial

number between true and opposite categories, we used a leave-one-trial-out cross-

validation procedure for true category and opposite category decoders. Decoding for

Experiment 1 was performed separately for each rule and were then averaged. Decoding

for Experiment 2 was performed separately for randomly divided halves and averaged.

Recurrent Neural Network Simulations

RNN architecture

The network model was built following the details in previous work (Masse et al.,

2019), and implemented in TensorFlow (version: Nvidia-tensorflow 1.15.0) (Abadi et

al., 2016). The general network architecture consisted of three layers of artificial units:

the input, hidden, and output layers. The input layer contains units served to present

various task-related signals corresponding to those in the fMRI paradigm, including

orientations, retro-cues, task cues. In order to simulate neural activity patterns in

hierarchically connected brain regions (EVC, IPS and sPCS), we separated the hidden

layer into three modules, each containing 200 recurrent units with short-term synaptic

plasticity (STSP). Within each module, units were further divided into 80% excitatory

and 20% inhibitory following Dale's principle. Similar to previous work (Zhou et al.,

2021), modularity was achieved by constraining the recurrent connectivity in the hidden

layer. Specifically, only posterior module's (module 1) excitatory units received inputs

from the input layer and only anterior module's (module 3) excitatory units projected

to the output units. Between-module connections were culled so that only 50% of a

module's excitatory units were randomly connected to their counterparts in the

neighboring module(s), and vice versa (feedforward and feedback connections).

Connections among inhibitory units remained strictly within-module in accordance

with the observation that inhibitory connections in cortex are largely local. Thus,

posterior, middle and anterior modules were intended to simulate the three

interconnected ROIs we used in the fMRI analyses that posited differently at the

processing hierarchy. We specifically manipulated the output demand to investigate

whether it would alter similarity of the results to the fMRI observations. To this end,

one type of network architecture (RNN1) implemented a two-unit output layer with

each unit corresponding to one of two possible response options, presented through the

input units before the test period; In contrast, the other type of RNN architecture (RNN2)

had additional units in the output layer, creating a demand for preserving the original

stimulus information alongside categorical representations.

Task simulation

Orientations were simulated as Gaussian signals from 15 orientation-tuned units in

the input layer distributed equally across 0-180 degrees, forming a ring of receptive

field. The magnitude of an orientation-tuned input unit represented the closeness of its

preferred orientation to the input angle. Stimulus values were selected from an array of

20 orientations evenly spanned from [0 to 180) degrees. The sequentially-presented

stimuli were presented through the same receptive field, followed by retro-cue and task

cue indicated through the separate input units. For RNN1, before the test period when

the network was required to make a choice, two response options were presented

sequentially through the same input receptive field. The selection of the options varied

slightly between the maintenance and categorization tasks: in maintenance, one

orientation was always the cued sample while the other was randomly chosen from all

other possible angles. In categorization, one option was taken from the same category

as the cued sample but not necessarily the exact angle, while the other option was

randomly chosen from orientations belonging to the other category. The network output

(0,1) or (1,0) in the output units to report its choice. In comparison, RNN2 output (0,1)

or (1,0) to report the category to which the cued orientation belonged in the categorization task, or (0,0) in the maintenance task. Importantly, the model also needed to report the cued orientation itself through a receptive field consisting of 15 orientation -tuned units in the output layer.

Training parameters and procedure

The hyperparameters and procedure for training the models were consistent with those detailed in previous work (Masse et al., 2019), with the following exceptions: standard deviations of input and recurrent noise were set to 0.01 as our tasks were much harder to train compared to those used in the reference study (especially networks were trained on both tasks simultaneously). Lowering the noise level may provide an edge for the models to successfully learn to perform the tasks. In a similar vein, we also expanded the number of hidden units to 600 and number of training iteration to a maximum of 10000. Additionally, spike penalty was set to 0 for both RNN models to remove constraints on neuronal activity.

We trained 20 models for each type of RNN and results were obtained by averaging over all of them (for single-rule RNN, 10 models for each categorization rule). The goal of the training process was to minimize the mean square error between the model outputs and correct outputs during the test period via back propagation (with a 50 ms grace period at onset when model output was not taken into account in calculating error). Training was conducted in a block-interleaved fashion in which each gradient batch consisted of 300 maintenance, 300 categorization Rule A and 300 categorization Rule

B trials, with the task block order randomized (for single rule RNN, each batch

consisted of 300 maintenance and 300 categorization trials). Training would

automatically stop if the model achieved 90% accuracy in the last training batch on all

tasks. For RNN2, the accuracies for category and stimulus outputs were calculated

separately to ensure precision of the stimulus outputs.

Population decoding

We measured the strength of stimulus and category representations through training

SVMs on time-resolved neuronal activity. Activities were obtained by feeding new

batches of tasks into the already-successfully trained networks after freezing all

connection weights to prevent further changes to the models' behaviors. The intrinsic

noise for the recurrent layer was also set to 0 for decoding analyses. To ensure accurate

decoding results, we sampled large number of trials (900 trials for each condition) and

implemented a 5-fold cross-validation procedure in which 80% of trials were used as

training set and the remaining 20% as testing set in each fold. Decoders were trained

separately for each module and time point.

Statistical Testing

Participants' behavioral performance for the main task was assessed using

accuracy and reaction time. Paired t-test was conducted for the two task types

(maintenance & categorization) to evaluate differences between conditions.

Statistical significance was evaluated via a sign-flip permutation procedure for all

other analyses. For example, to characterize the significance of IEM fidelity, we

computed the p-value by comparing the true mean fidelity of our sample with a null

distribution reflecting no IEM fidelity. The null distribution was created by randomly

assigning 1 or -1 to fidelity scores of our sample and then averaging the sign-flipped

samples for 10,000 times, resulting in a null distribution of 10,000 fidelity scores. To

characterize the difference of IEM fidelity between tasks, we sign-flipped the fidelity

sample for each condition and then averaged the difference for 10,000 times. The p-

value was calculated by comparing the true mean difference with the generated null

distribution of difference. P-values were corrected using FDR across ROIs, time (TRs),

and tasks for all analyses unless specified. An early (5-10 s; 6th-11th TR) and late (11-

16 s; 12th-17th TR) task epoch was also defined to facilitate comparisons between ROIs

and experiments when needed.

For RNN decoding results, we adopted a cluster-based permutation approach

(using MNE-Python (Gramfort et al., 2013) function *permutation_cluster_1samp_test*

to accommodate the large number of time points to be corrected for) to determine

statistical significance of the time course, for stimulus decoding accuracies in

maintenance/categorization, difference between stimulus decoding accuracies between

tasks, and abstract category decoding accuracy in categorization task. Moreover, we

also pooled decoding accuracies across a critical task period (50-75 time points during

delay) to produce summary statistics aligning with what was reported in the fMRI

results. Average decoding results were corrected using the FDR method.

Acknowledgements

We would like to thank Dr. Mu-ming Poo for valuable comments on an earlier version of the manuscript, and Dr. Tianming Yang for helpful discussions. This work was supported by the Ministry of Science and Technology of China (STI2030-Major Projects 2021ZD0203701, 2021ZD0204202), the National Natural Science Foundation of China (32271089), CAS Project for Young Scientists in Basic Research (YSBR-071), and Shanghai Pujiang Program (22PJ1414400) to Q.Y..

Reference

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., . . . Zheng, X. (2016). TensorFlow: A System for Large-Scale Machine Learning. *12th USENIX Symposium on Operating Systems Design and Implementation*, 265–283.

Baddeley, A. (2003). Working memory: looking back and looking forward. *Nat Rev Neurosci, 4*(10), 829-839. doi:10.1038/nrn1201

Badre, D. (2008). Cognitive control, hierarchy, and the rostro-caudal organization of the frontal lobes. *Trends Cogn Sci, 12*(5), 193-200. doi:10.1016/j.tics.2008.02.004

Badre, D., Bhandari, A., Keglovits, H., & Kikumoto, A. (2021). The dimensionality of neural representations for control. *Curr Opin Behav Sci, 38*, 20-28. doi:10.1016/j.cobeha.2020.07.002

Badre, D., Kayser, A. S., & D'Esposito, M. (2010). Frontal cortex and the discovery of abstract action rules. *Neuron, 66*(2), 315-326. doi:10.1016/j.neuron.2010.03.025

Bettencourt, K. C., & Xu, Y. (2016). Decoding the content of visual short-term memory under distraction in occipital and parietal areas. *Nat Neurosci, 19*(1), 150-157. doi:10.1038/nn.4174

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spat Vis, 10*(4), 433-436. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/9176952

Brincat, S. L., Siegel, M., von Nicolai, C., & Miller, E. K. (2018). Gradual progression from sensory to task-related processing in cerebral cortex. *Proc Natl Acad Sci U S A, 115*(30), E7202-E7211. doi:10.1073/pnas.1717075115

Brouwer, G. J., & Heeger, D. J. (2009). Decoding and reconstructing color from responses in human visual cortex. *J Neurosci, 29*(44), 13992-14003. doi:10.1523/JNEUROSCI.3577-09.2009

Brouwer, G. J., & Heeger, D. J. (2011). Cross-orientation suppression in human visual cortex. *J Neurophysiol, 106*(5), 2108-2119. doi:10.1152/jn.00540.2011

Christophel, T. B., Hebart, M. N., & Haynes, J. D. (2012). Decoding the contents of visual short-term memory from human visual and parietal cortex. *J Neurosci, 32*(38), 12983-12989. doi:10.1523/JNEUROSCI.0184-12.2012

Christophel, T. B., Iamshchinina, P., Yan, C., Allefeld, C., & Haynes, J. D. (2018). Cortical specialization for attended versus unattended working memory. *Nat Neurosci, 21*(4), 494-496.

doi:10.1038/s41593-018-0094-4

Cox, R. W. (1996). AFNI: software for analysis and visualization of functional magnetic resonance
neuroimages. *Comput Biomed Res, 29*(3), 162-173. Retrieved from
https://www.ncbi.nlm.nih.gov/pubmed/8812068

Cox, R. W., & Hyde, J. S. (1997). Software tools for analysis and visualization of FMRI Data. *NMR in*
Biomedicine, 10, 171-178.

D'Esposito, M., & Postle, B. R. (2015). The cognitive neuroscience of working memory. *Annu Rev*
Psychol, 66, 115-142. doi:10.1146/annurev-psych-010814-015031

D'Esposito, M., Postle, B. R., Ballard, D., & Lease, J. (1999). Maintenance versus manipulation of
information held in working memory: an event-related fMRI study. *Brain Cogn, 41*(1), 66-86.
doi:10.1006/brcg.1999.1096

D'Esposito, M., Postle, B. R., & Rypma, B. (2000). Prefrontal cortical contributions to working memory:
evidence from event-related fMRI studies. *Exp Brain Res, 133*(1), 3-11.
doi:10.1007/s002210000395

Emrich, S. M., Riggall, A. C., Larocque, J. J., & Postle, B. R. (2013). Distributed patterns of activity in
sensory cortex reflect the precision of multiple items maintained in visual short-term memory.
J Neurosci, 33(15), 6516-6523. doi:10.1523/JNEUROSCI.5732-12.2013

Eppinger, B., Goschke, T., & Musslick, S. (2021). Meta-control: From psychology to computational
neuroscience. *Cogn Affect Behav Neurosci, 21*(3), 447-452. doi:10.3758/s13415-021-00919-4

Ester, E. F., Anderson, D. E., Serences, J. T., & Awh, E. (2013). A neural measure of precision in visual
working memory. *J Cogn Neurosci, 25*(5), 754-761. doi:10.1162/jocn_a_00357

Ester, E. F., Sprague, T. C., & Serences, J. T. (2015). Parietal and Frontal Cortex Encode Stimulus-
Specific Mnemonic Representations during Visual Working Memory. *Neuron, 87*(4), 893-905.
doi:10.1016/j.neuron.2015.07.013

Ester, E. F., Sprague, T. C., & Serences, J. T. (2020). Categorical Biases in Human Occipitoparietal
Cortex. *J Neurosci, 40*(4), 917-931. doi:10.1523/JNEUROSCI.2700-19.2019

Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., & Summerfield, C. (2022). Orthogonal
representations for robust context-dependent task performance in brains and neural networks.
Neuron, 110(7), 1258-1270 e1211. doi:10.1016/j.neuron.2022.01.005

Freedman, D. J., & Assad, J. A. (2006). Experience-dependent representation of visual categories in
parietal cortex. *Nature, 443*(7107), 85-88. doi:10.1038/nature05078

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2001). Categorical representation of visual
stimuli in the primate prefrontal cortex. *Science, 291*(5502), 312-316.
doi:10.1126/science.291.5502.312

Funahashi, S., Bruce, C. J., & Goldman-Rakic, P. S. (1989). Mnemonic coding of visual space in the
monkey's dorsolateral prefrontal cortex. *J Neurophysiol, 61*(2), 331-349.
doi:10.1152/jn.1989.61.2.331

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition.
Curr Opin Neurobiol, 37, 66-74. doi:10.1016/j.conb.2016.01.010

Fuster, J. M., & Alexander, G. E. (1971). Neuron activity related to short-term memory. *Science,*
173(3997), 652-654. Retrieved from https://www.ncbi.nlm.nih.gov/pubmed/4998337

Gosseries, O., Yu, Q., LaRocque, J. J., Starrett, M. J., Rose, N. S., Cowan, N., & Postle, B. R. (2018).
Parietal-Occipital Interactions Underlying Control- and Representation-Related Processes in
Working Memory for Nonspatial Visual Features. *J Neurosci, 38*(18), 4357-4366.

doi:10.1523/JNEUROSCI.2747-17.2018

Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., . . . Hamalainen,
M. (2013). MEG and EEG data analysis with MNE-Python. *Front Neurosci, 7*, 267.
doi:10.3389/fnins.2013.00267

Hallenbeck, G. E., Sprague, T. C., Rahmati, M., Sreenivasan, K. K., & Curtis, C. E. (2021). Working
memory representations in visual cortex mediate distraction effects. *Nat Commun, 12*(1), 4714.
doi:10.1038/s41467-021-24973-1

Harrison, S. A., & Tong, F. (2009). Decoding reveals the contents of visual working memory in early
visual areas. *Nature, 458*(7238), 632-635. doi:10.1038/nature07832

Henderson, M. M., Rademaker, R. L., & Serences, J. T. (2022). Flexible utilization of spatial- and motor-
based codes for the storage of visuo-spatial information. *Elife, 11*. doi:10.7554/eLife.75688

Hu, Y., & Yu, Q. (2023). Spatiotemporal dynamics of self-generated imagery reveal a reverse cortical
hierarchy   from   cue-induced   imagery.   *Cell   Rep,   42*(10),   113242.
doi:10.1016/j.celrep.2023.113242

Latimer, K. W., & Freedman, D. J. (2023). Low-dimensional encoding of decisions in parietal cortex
reflects long-term training history. *Nat Commun, 14*(1), 1010. doi:10.1038/s41467-023-36554-
5

Leavitt, M. L., Mendoza-Halliday, D., & Martinez-Trujillo, J. C. (2017). Sustained Activity Encoding
Working   Memories: Not   Fully   Distributed.   *Trends   Neurosci,   40*(6),   328-346.
doi:10.1016/j.tins.2017.04.004

Lee, S. H., Kravitz, D. J., & Baker, C. I. (2013). Goal-dependent dissociation of visual and prefrontal
cortices during working memory. *Nat Neurosci, 16*(8), 997-999. doi:10.1038/nn.3452

Li, S., Zeng, X., Shao, Z., & Yu, Q. (2023). Neural Representations in Visual and Parietal Cortex
Differentiate between Imagined, Perceived, and Illusory Experiences. *J Neurosci, 43*(38), 6508-
6524. doi:10.1523/JNEUROSCI.0592-23.2023

Liu, T., Cable, D., & Gardner, J. L. (2018). Inverted Encoding Models of Human Population Response
Conflate   Noise   and   Neural   Tuning   Width.   *J   Neurosci,   38*(2),   398-408.
doi:10.1523/JNEUROSCI.2453-17.2017

Lorenc, E. S., Sreenivasan, K. K., Nee, D. E., Vandenbroucke, A. R. E., & D'Esposito, M. (2018). Flexible
coding   of   visual   working   memory   representations   during   distraction.   *J   Neurosci*.
doi:10.1523/JNEUROSCI.3061-17.2018

Luu, L., & Stocker, A. A. (2021). Categorical judgments do not modify sensory representations in
working memory. *PLoS Comput Biol, 17*(6), e1008968. doi:10.1371/journal.pcbi.1008968

Masse, N. Y., Yang, G. R., Song, H. F., Wang, X. J., & Freedman, D. J. (2019). Circuit mechanisms for
the maintenance and manipulation of information in working memory. *Nat Neurosci, 22*(7),
1159-1167. doi:10.1038/s41593-019-0414-3

McKee, J. L., Riesenhuber, M., Miller, E. K., & Freedman, D. J. (2014). Task dependence of visual and
category representations in prefrontal and inferior temporal cortices. *J Neurosci, 34*(48), 16065-
16075. doi:10.1523/JNEUROSCI.1660-14.2014

Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annu Rev
Neurosci, 24*, 167-202. doi:10.1146/annurev.neuro.24.1.167

Miller, J. A., Tambini, A., Kiyonaga, A., & D'Esposito, M. (2022). Long-term learning transforms
prefrontal cortex representations during working memory. *Neuron, 110*(22), 3805-3819 e3806.
doi:10.1016/j.neuron.2022.09.019

Mok, R. M., & Love, B. C. (2020). Abstract Neural Representations of Category Membership beyond
1059   Information Coding Stimulus or Response. *J Cogn Neurosci*, 1-17. doi:10.1162/jocn_a_01651

1060   Musslick, S., & Cohen, J. D. (2021). Rationalizing constraints on the capacity for cognitive control.
1061   *Trends Cogn Sci, 25*(9), 757-775. doi:10.1016/j.tics.2021.06.001

1062   Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers into
1063   movies. *Spat Vis, 10*(4), 437-442. Retrieved from
1064   https://www.ncbi.nlm.nih.gov/pubmed/9176953

1065   Rademaker, R. L., Chunharas, C., & Serences, J. T. (2019). Coexisting representations of sensory and
1066   mnemonic information in human visual cortex. *Nat Neurosci, 22*(8), 1336-1344.
1067   doi:10.1038/s41593-019-0428-x

1068   Riggall, A. C., & Postle, B. R. (2012). The Relationship between Working Memory Storage and Elevated
1069   Activity as Measured with Functional Magnetic Resonance Imaging. *Journal of Neuroscience,*
1070   *32*(38), 12990-12998. doi:10.1523/Jneurosci.1892-12.2012

1071   Serences, J. T., Ester, E. F., Vogel, E. K., & Awh, E. (2009). Stimulus-specific delay activity in human
1072   primary visual cortex. *Psychol Sci, 20*(2), 207-214. doi:10.1111/j.1467-9280.2009.02276.x

1073   Sprague, T. C., Adam, K. C. S., Foster, J. J., Rahmati, M., Sutterer, D. W., & Vo, V. A. (2018). Inverted
1074   Encoding Models Assay Population-Level Stimulus Representations, Not Single-Unit Neural
1075   Tuning. *eNeuro, 5*(3). doi:10.1523/ENEURO.0098-18.2018

1076   Sprague, T. C., & Serences, J. T. (2013). Attention modulates spatial priority maps in the human occipital,
1077   parietal and frontal cortices. *Nat Neurosci, 16*(12), 1879-1887. doi:10.1038/nn.3574

1078   Wang, L., Mruczek, R. E., Arcaro, M. J., & Kastner, S. (2015). Probabilistic Maps of Visual Topography
1079   in Human Cortex. *Cereb Cortex, 25*(10), 3911-3931. doi:10.1093/cercor/bhu277

1080   Wang, X. J. (2021). 50 years of mnemonic persistent activity: quo vadis? *Trends Neurosci, 44*(11), 888-
1081   902. doi:10.1016/j.tins.2021.09.001

1082   Yu, Q., & Postle, B. R. (2021). The Neural Codes Underlying Internally Generated Representations in
1083   Visual Working Memory. *J Cogn Neurosci*, 1-16. doi:10.1162/jocn_a_01702

1084   Yu, Q., & Shim, W. M. (2017). Occipital, parietal, and frontal cortices selectively maintain task-relevant
1085   features of multi-feature objects in visual working memory. *Neuroimage, 157*, 97-107.
1086   doi:10.1016/j.neuroimage.2017.05.055

1087   Yu, Q., & Shim, W. M. (2019). Temporal-Order-Based Attentional Priority Modulates Mnemonic
1088   Representations in Parietal and Frontal Cortices. *Cereb Cortex, 29*(7), 3182-3192.
1089   doi:10.1093/cercor/bhy184

1090   Zhou, Y., Rosen, M. C., Swaminathan, S. K., Masse, N. Y., Zhu, O., & Freedman, D. J. (2021).
1091   Distributed functions of prefrontal and parietal cortices during sequential categorical decisions.
1092   *Elife, 10*. doi:10.7554/eLife.58782

1093

1094 **Supplemental Figures**

1095

Figure S1. Behavioral performance of Experiment 2.

(A) Accuracy (upper) and reaction time (lower) of Maintenance (blue) and

Categorization (orange) tasks in Experiment 2. Asterisks denote significant results, n.s.:

not significant; **: $p < 0.01$. (B) Accuracy (upper) and reaction time (lower) for

orientations based on their distances from category center for Categorization task.

Shaded areas represent $\pm$ SEM. Vertical dashed line represents category center.

1102

1103

Figure S2. Control analyses for stimulus representation results.

(A) Time course of representational strength of orientations in EVC, IPS and sPCS
using IEMs trained separately for each condition. Bar plot on the right showing
corresponding averaged difference between tasks. Average difference of
representational strength across later delay period (11 – 16 s) in each ROI. Positive
difference indicates higher representational strength for categorization, and vice versa
for negative difference. (B) Time course of representational strength of orientations
in functional ROIs defined by top 500 most selective voxels during sample or delay
period. Bar plot same as (A). (C) Time course of representational strength of
orientations after removing voxel-wise mean activation for each condition at each TR.
Bar plot same as (A). (D) Time course of stimulus decoding accuracy. Bar plot same as
(A). Gray shaded areas indicate the entire memory delay following task cue. Horizontal
dashed lines represent a baseline of 0 or 0.5. Blue and orange dots at the bottom indicate
the significance of representational fidelity at each time point of the corresponding task
at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). The bottom black dots

indicate significant difference in representational fidelity between tasks. Shaded areas
represent ± SEM. n.s.: not significant; black asterisks denote significance, *: $p < 0.05$;
**: $p < 0.01$; ***: $p < 0.001$. Gray asterisk denotes marginal significance $p < 0.1$.
1122

1123

Figure S3. Behavioral correlation of stimulus representation in Experiment 2.
(A) Time course of correlation coefficients in EVC, IPS, and sPCS. Correlation was
performed between strength of stimulus representations and behavioral performance
(accuracy) for Maintenance (blue) and Categorization (orange) tasks. Gray shaded areas
indicate the entire memory delay following task cue. Horizontal dashed lines represent
a baseline of 0. Bottom dots indicate the significance of corresponding analyses at each
time point of the corresponding task at $p < 0.05$ (small), $p < 0.01$ (medium), and $p <$
0.001 (large). Shaded areas represent ± SEM.
1132

1133

Figure S4. Category, Abstract Category and Rule Information in Experiment 1 and 2. (A) Time course of category decoding strength in Experiment 1 with flexible rule (orange) and in Experiment 2 with fixed rule (light orange). Horizontal dashed lines represent the chance level of 0.5. Gray shaded areas indicate the entire memory delay following task cue. Bottom dots indicate FDR-corrected significance of decoding accuracy at each time point at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). Error bars represent $\pm$ SEM. (B) Time course of abstract category decoding strength in Experiment 1 (dark blue) and in Experiment 2 (light blue). Horizontal dashed lines represent a baseline of 0. Gray shaded areas indicate the entire memory delay following task cue. Bottom dots indicate uncorrected significance of decoding accuracy at each time point at $p < 0.05$ (small), $p < 0.01$ (medium), and $p < 0.001$ (large). Error bars represent $\pm$ SEM.

1146

Supplemental Tables

Time	Maintenance			Categorization			Maintenance vs. Categorization		
	EVC	IPS	sPCS	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.486	0.389	0.286	0.838	0.838	0.747	0.206	0.814	0.827
1	0.385	0.576	0.743	0.747	0.822	0.717	0.205	0.675	0.460
2	0.060	0.286	0.219	0.174	0.626	0.626	0.188	0.788	0.779
3	0.000	0.286	0.764	0.000	0.353	0.389	0.497	0.630	0.232
4	0.000	0.154	0.422	0.000	0.038	0.784	0.534	0.299	0.812
5	0.000	0.042	0.618	0.000	0.027	0.269	0.816	0.389	0.241
6	0.000	0.002	0.094	0.000	0.002	0.056	0.927	0.528	0.594
7	0.000	0.000	0.033	0.000	0.000	0.001	0.914	0.301	0.274
8	0.000	0.000	0.001	0.000	0.000	0.001	0.588	0.651	0.655
9	0.000	0.000	0.004	0.000	0.000	0.007	0.119	0.277	0.399
10	0.000	0.000	0.060	0.000	0.000	0.003	0.007	0.258	0.127
11	0.000	0.001	0.264	0.000	0.000	0.032	0.001	0.162	0.123
12	0.000	0.003	0.759	0.000	0.000	0.039	0.000	0.090	0.018
13	0.000	0.001	0.377	0.000	0.000	0.003	0.000	0.054	0.022
14	0.000	0.007	0.747	0.000	0.000	0.038	0.000	0.046	0.034
15	0.000	0.000	0.667	0.000	0.000	0.003	0.000	0.145	0.012
16	0.000	0.000	0.948	0.000	0.000	0.020	0.000	0.190	0.001
17	0.000	0.000	0.838	0.000	0.000	0.031	0.000	0.889	0.004

Supplemental Table 1. P-values for the time course of IEM results in Figure 2. Underline denotes significant results ($p < 0.05$).

	Maintenance			Categorization		
Time	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.569	0.202	0.603	0.674	0.347	0.368
1	0.866	0.549	0.871	0.913	0.459	0.291
2	0.757	0.808	0.846	0.921	0.651	0.224
3	0.246	0.264	0.576	0.438	0.708	0.075
4	0.232	0.147	0.749	0.092	0.052	0.093
5	0.310	0.062	0.537	0.136	<u>0.032</u>	<u>0.033</u>
6	0.114	<u>0.049</u>	0.911	<u>0.045</u>	0.003	0.009
7	<u>0.012</u>	<u>0.024</u>	0.125	<u>0.019</u>	0.002	0.012
8	<u>0.034</u>	0.076	0.140	<u>0.022</u>	0.001	0.004
9	0.050	0.069	0.143	<u>0.027</u>	<u>0.000</u>	<u>0.001</u>
10	0.160	0.699	0.377	0.101	<u>0.000</u>	<u>0.000</u>
11	0.320	0.944	0.612	0.140	<u>0.015</u>	<u>0.004</u>
12	0.494	0.983	0.339	0.271	<u>0.027</u>	<u>0.007</u>
13	0.344	0.546	0.140	0.435	0.062	<u>0.009</u>
14	0.173	0.768	0.538	0.275	0.082	0.068
15	0.127	0.809	0.811	0.493	0.181	0.080
16	0.083	0.145	0.516	0.284	0.097	<u>0.032</u>
17	0.396	0.085	<u>0.030</u>	0.122	<u>0.042</u>	0.118

Supplemental Table 2. P-values for the time course of correlation results in Figure 3. Underline denotes significant results ($p < 0.05$).

Time	Maintenance			Categorization			Maintenance vs. Categorization		
	EVC	IPS	sPCS	EVC	IPS	sPCS	EVC	IPS	sPCS
0	0.005	0.028	0.203	0.511	0.359	0.395	0.007	0.976	0.804
1	0.007	0.090	0.079	0.339	0.181	0.412	0.018	0.810	0.979
2	0.001	0.152	0.444	0.154	0.371	0.548	0.021	0.816	0.668
3	0.000	0.079	0.481	0.000	0.237	0.600	0.057	0.851	0.669
4	0.000	0.021	0.170	0.000	0.001	0.224	0.385	0.578	0.675
5	0.000	0.018	0.548	0.000	0.000	0.045	0.578	0.396	0.071
6	0.000	0.006	0.525	0.000	0.000	0.000	0.811	0.197	0.002
7	0.000	0.000	0.018	0.000	0.000	0.000	0.900	0.275	0.072
8	0.000	0.000	0.152	0.000	0.000	0.000	0.884	0.059	0.011
9	0.000	0.000	0.117	0.000	0.000	0.000	0.612	0.090	0.040
10	0.000	0.000	0.028	0.000	0.000	0.000	0.045	0.207	0.066
11	0.000	0.001	0.017	0.000	0.000	0.000	0.005	0.272	0.209
12	0.000	0.000	0.028	0.000	0.000	0.000	0.014	0.574	0.266
13	0.000	0.001	0.052	0.000	0.000	0.000	0.029	0.344	0.139
14	0.000	0.001	0.117	0.000	0.000	0.021	0.120	0.420	0.395
15	0.000	0.002	0.022	0.000	0.000	0.005	0.001	0.644	0.340
16	0.000	0.000	0.003	0.000	0.000	0.000	0.000	0.866	0.546
17	0.000	0.000	0.039	0.000	0.000	0.000	0.000	0.881	0.259

Supplemental Table 3. P-values for the time course of IEM results in Figure 4. Underline denotes significant results ($p < 0.05$).