`disperseNN2`: a neural network for estimating dispersal distance from georeferenced polymorphism data

Chris C. R. Smith[1] and Andrew D. Kern[1]

[1]University of Oregon, Institute of Ecology and Evolution

July 30, 2023

Summary: We present a deep learning tool, `disperseNN2`, for estimating the mean per-generation dispersal distance from georeferenced polymorphism data. Our neural network performs feature extraction on pairs of genotypes, and uses the geographic information that comes with each sample. These attributes led `disperseNN2` to outperform a state-of-the-art deep learning method that does not use explicit spatial information: error was reduced by 33% and 42% using sample sizes of 10 and 100 individuals, respectively. `disperseNN2` is particularly useful for non-model organisms or systems with sparse genomic resources, as it uses unphased, single nucleotide polymorphisms as its input.

Availability and Implementation: https://github.com/kr-colab/disperseNN2

Contact: chriscs@uoregon.edu

1   Introduction

The per-generation dispersal distance of an organism is a critical variable for the management of endangered and invasive species, understanding range shifts under climate change, and studying vectors of human disease (Driscoll et al., 2014; Harris et al., 2009; Orsborne et al., 2019). A potent source of information that may be used to estimate this ecologically-relevant parameter is population genetic data that are geographically distributed. Accordingly, numerous methods to perform dispersal estimation have been proffered in the literature. For example, Rousset (1997) presented a method to infer dispersal that requires two inputs: the slope of the least squares fit of genetic distance against geographic distance, and an independent estimate for population density. Other existing methods require very high-depth sequencing combined with statistical inference to obtain the necessary input data types: blocks of identity by descent (Ringbauer et al., 2017), or

tree sequences (Osmond and Coop, 2021). While approaches for inferring the latter data types are continually improving, these data are still unavailable for most species.

We previously presented a deep learning tool, called `disperseNN`, that estimates dispersal rate using input data that are accessible even for some non-model species—single nucleotide polymorphisms (SNPs)—and that performs as well or better than existing methods (Smith et al., 2023). Notably our previous method relied only on population genetic variation and did not utilize the spatial coordinates of the samples. In the current study, we present an improved neural network architecture, called `disperseNN2`, that explicitly uses geographic information and provides substantial performance gains over `disperseNN`, which was already more accurate than previous methods for small sample sizes.

2   Approach

2.1   Overview

The `disperseNN2` program uses a deep neural network trained on simulated data to infer the mean, per-generation parent-offspring distance (Figure 1). Specifically, we aim to infer σ, the root-mean-square displacement along a given axis between a randomly chosen child and one of their parents chosen at random (Rousset, 1997; Ringbauer et al., 2017). As with `disperseNN`, `disperseNN2` is designed for SNP data obtained from RADseq or whole genome sequencing, with either short-range or full linkage information. The model is trained on simulated data; therefore, the general workflow requires generating training datasets that accurately reflect the empirical genotypes of interest. While the neural network model has diverged substantially and is described below in detail, the general approach and analysis workflow are similar to Smith et al. (2023). The `disperseNN2` documentation includes complete instructions, example commands for the analysis workflow, and a number of usage vignettes (`https://dispersenn2.readthedocs.io/en/latest/`).

2.2   Network architecture

`disperseNN2` uses a pairwise convolutional network that performs feature extraction on *pairs* of individuals at a time (Figure 1). The first part of the model, which we refer to as "the extractor", extracts pertinent information from pairs of genotypes, and merges the extracted features from all combinatorial pairs into a summary table for downstream processing. The latter part of the model uses the extracted data from many sample-pairs to predict σ. This strategy allows us to convey spatial information to the network, which is accomplished by attaching the geographic distance between each sample-pair directly to the genotype summaries from the corresponding pair.

The first input to `disperseNN2` is a genotype matrix consisting of minor allele counts (0s, 1s, and 2s) for m SNPs from n individuals. However, rather than show the full genotype matrix to the network, we loop through all $\binom{n}{2}$ pairs of individuals and sub-set the genotypes of each pair. Feature extraction is then performed on each individual pair using convolution and pooling, where the convolution kernel spans two SNPs and each pooling step averages ten SNPs.

The second input is a table of geographic coordinates for the sample locations. As with the genotypes, the x and y coordinates are sub-set for each sample-pair. The Euclidean distance is calculated between the individuals within each pair and concatenated with the convolved genotype information for the pair. Last, the concatenated features are put through a fully connected layer, resulting in a vector of information gleaned from the pair. The convolution and dense layers include rectified linear unit activation functions, and the weights of the extractor are shared across all sample-pairs.

After performing feature extraction on each pair of individuals, the features from all pairs are stacked together, and a final, fully connected layer with a single filter and linear activation is used to produce an estimate for σ.

By default the network uses all combinatorial pairs of samples. However, GPU memory might be limiting with larger sample sizes. For example, with $n = 100$ there are 4950 sample-pairs. While one solution might be to omit some pairs from the analysis entirely, we instead exclude a number of pairs from the optimization of certain model parameters. Specifically, `disperseNN2` has the option to stop some pairs from contributing to the calculation of the gradient with respect to the weights in the extractor. Under this strategy, a smaller number of pairs, k_{extract}, are used to optimize the extractor's weights, which reduces memory demands appreciably. Meanwhile, features are still extracted from the full set of pairs during the forward pass, and all pairs help optimize the weights in the latter half of the network. The ideal value for k_{extract} will likely depend on the total number of pairs, as well as the training data and other parameters. Tensorflow (Abadi et al., 2016) and Keras (`https://github.com/keras-team/keras`) libraries were used to develop `disperseNN2`.

2.3   Generating training data

To use `disperseNN2`, researchers must simulate training datasets that are tailored to the study system. In particular, producing training data requires deciding on training distributions for dispersal rate and other parameters. Some other values that are relevant to dispersal inference, i.e. nuisance parameters, include population density, demographic history, and the shape and size of the species distribution (Smith et al., 2023). Choices for these simulation settings will depend on the information available in each unique species or population. Recent developments, namely the programs `SLiM` (Haller and Messer, 2019) and `slendR`

Figure 1: (A. network schematic) From left to right: a pair of individuals is selected for the feature-extraction step. The genotype matrix shows the genotypes for the pair. Cream colored tensors are the output from convolution layers. The blue box over the genotypes shows the convolution kernel for the first layer. Red tensors are the output from pooling layers. The second input is a table of spatial coordinates, and a subset is taken for the current pair. The Euclidean distance is calculated and then concatenated with the flattened convolution output. Green tensors are the output from flattening, concatenating, or dense layers. The extractor is repeated for $\binom{n}{2}$ different pairs of individuals, and the resulting features are stacked together. The dimensions noted beneath each tensor will vary depending on the input size; this example uses 5,000 SNPs (although the image of the genotypes shows a smaller number of SNPs). The visualized size of each tensor is proportional to the square root of the actual dimensions. Neural network images were generated using `PlotNeuralNet` (`https://github.com/HarisIqbal88/PlotNeuralNet`). (B. box plots) Also shown are validation results using simulated data with `disperseNN` (white) and `disperseNN2` (grey) with two different sample sizes. Outliers are excluded.

(Petr et al., 2022), make it feasible to simulate genomes in continuous space. The `disperseNN2` repository includes a `SLiM` script that may serve as a template for new simulations, and the `SLiM` manual includes general information for designing spatial simulations.

2.4 Analysis

The `disperseNN2` software includes tools for pre-processing input data, making it easy for practitioners to turn tree sequences (e.g., `SLiM` output) into `disperseNN2` input. Specifically, a sample of individuals is taken from each simulation and their genotypes and locations—inputs to the neural network—are saved in binary format, which improves training efficiency. To mirror the empirical sampling scheme, individuals are chosen from simulations that are closest to the empirical sample localities, after projecting the empirical latitude and longitude onto a flat surface—this step aims to make the training data as similar to the empirical data as possible. The genotype input to `disperseNN2` is unphased or phased SNP data in standard variant call format (VCF). The model is trained with mean squared error loss, Adam optimizer, and learning rate 10^{-4}. The training duration depends on the input size: for example, using a training set of 50,000 datasets, each with 5,000 SNPs and $n = 10$, it takes 4.5 hours for 100 training iterations on a GPU; with $n = 100$ it takes approximately a week using all 4950 pairs and $k_{\text{extract}} = 100$. The program also parallelizes well across CPUs: using 50 cores leads to similar performance to one GPU. The `disperseNN2` documentation provides a complete vignette taking a user through the cycle of simulation, training, and eventual prediction for an empirical dataset.

3 Results

For testing purposes, we used simulated data as described in Smith et al. (2023). Briefly, the simulated genome is a single chromosome with length 10^8 base pairs, recombination rate 10^{-8} crossovers per base pair per generation, and mutation rate 10^{-8} substitutions per site per generation. The habitat is a 50×50 square; local carrying capacity was set to 5 individuals per square map unit; and the mother-offspring dispersal distance, mating distance, and competition distance all shared the same value, σ_f, which varied uniformly between 0.2 and 3. To obtain the "effective" dispersal rate to a randomly chosen parent, σ, the simulation parameter σ_f was multiplied by $\sqrt{\frac{3}{2}}$ (see Smith et al., 2023).

We validated the `disperseNN2` architecture on held-out simulations and calculated the mean relative absolute error (MRAE) for 1000 test datasets:

$$\text{MRAE} = \sum \left| \frac{\text{estimated } \sigma_i - \text{true } \sigma_i}{\text{true } \sigma_i} \right| \Big/ \text{ total tests}$$

Prediction error with `disperseNN2` was substantially decreased relative to `disperseNN`: using 100 spatially distributed individuals and 5,000 SNPs as input, we observed a 42% reduction in MRAE, from 0.12 with `disperseNN` (the previous model) to 0.07 with `disperseNN2`. Using a smaller sample size, $n = 10$, we

observed a 33% reduction in MRAE, from 0.21 with `disperseNN` to 0.14 with `disperseNN2`. This is a tremendous improvement to what was already state-of-the-art software. In the $n = 100$ experiment we used all 4950 pairs, but found that using $k_{\text{extract}} = 100$ instead of $k_{\text{extract}} = 4950$ reduced memory consumption and computation time considerably, without a reduction in accuracy.

Importantly, these tests used data that were generated under the same process that produced the training data, and only a single model parameter, σ, was unknown. Thus, the reported accuracy represents a best case scenario. In practice, there may be additional unknown parameters, for example, population density, that should be incorporated into training by varying the unknown parameters between simulations (i.e., using a 'prior' distribution). See Smith et al. (2023) for further discussion and experiments involving model misspecification.

4   Discussion

We present a novel deep learning architecture, `disperseNN2`, for estimating the mean, per-generation dispersal rate from genotypes and their geographic coordinates. The `disperseNN2` neural network differs from our previous model, `disperseNN`, in two ways. First, `disperseNN2` loops through *pairs* of genotypes at a time, extracting relevant information from each pair. Second, the neural network makes use of the geographic coordinates associated with each genotype. These changes cause `disperseNN2` to outperform `disperseNN` by a sizeable margin. Our approach will be especially useful for non-model organisms that lack accurate identity-by-descent tracts and empirically-inferred tree sequences, because it can be used with unphased SNP data. One limitation for our method is generating the required training data, which must be designed carefully to reflect the empirical data of interest and can be computationally expensive for large populations.

Whereas some studies in population genetics have applied convolutional neural networks to the full genotype matrix, our deep learning model performs feature extraction on pairs of genotypes. Having the network focus on pairs is an intuitive strategy for many genetics applications, particularly those involving spatial genetic data, where researchers are often interested in the relatedness between individuals. For studying dispersal, this approach brings the model's attention to the genetic and geographic distances between individuals, which follows the intuition of well-established models like Rousset (1997). Architectures like ours may be useful for explicitly between-individual tasks like characterizing identity by descent tracts, or for other tasks in population genetics like inferring demographic history.

5   Acknowledgements

We thank Peter Ralph and members of the Kern-Ralph colab for comments on the project and manuscript. This work was supported by the National Institutes of Health awards F32GM146484 to C.S. and R01HG010774 and R35GM148253 to A.D.K..

References

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, et al. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *arXiv preprint arXiv:1603.04467*, 2016.

Don A Driscoll, Sam C Banks, Philip S Barton, Karen Ikin, Pia Lentini, David B Lindenmayer, Annabel L Smith, Laurence E Berry, Emma L Burns, Amanda Edworthy, et al. The trajectory of dispersal research in conservation biology. Systematic review. *PloS one*, 9(4):e95053, 2014.

Benjamin C Haller and Philipp W Messer. SLiM 3: forward genetic simulations beyond the Wright-Fisher model. *Molecular biology and evolution*, 36(3):632–637, 2019.

Catriona M Harris, Kirsty J Park, Rachel Atkinson, Colin Edwards, and Justin MJ Travis. Invasive species control: incorporating demographic data and seed dispersal into a management model for *Rhododendron ponticum*. *Ecological Informatics*, 4(4):226–233, 2009.

James Orsborne, Luis Furuya-Kanamori, Claire L Jeffries, Mojca Kristan, Abdul Rahim Mohammed, Yaw A Afrane, Kathleen O'Reilly, Eduardo Massad, Chris Drakeley, Thomas Walker, et al. Investigating the blood-host plasticity and dispersal of *Anopheles coluzzii* using a novel field-based methodology. *Parasites & vectors*, 12(1):1–8, 2019.

Matthew M Osmond and Graham Coop. Estimating dispersal rates and locating genetic ancestors with genome-wide genealogies. *bioRxiv*, pages 2021–07, 2021.

Martin Petr, Benjamin C Haller, Peter L Ralph, and Fernando Racimo. slendr: a framework for spatio-temporal population genomic simulations on geographic landscapes. *bioRxiv*, pages 2022–03, 2022.

Harald Ringbauer, Graham Coop, and Nicholas H Barton. Inferring recent demography from isolation by distance of long shared sequence blocks. *Genetics*, 205(3):1335–1351, 2017.

François Rousset. Genetic differentiation and estimation of gene flow from F-statistics under isolation by distance. *Genetics*, 145(4):1219–1228, 1997.

Chris CR Smith, Silas Tittes, Peter L Ralph, and Andrew D Kern. Dispersal inference from population genetic variation using a convolutional neural network. *Genetics*, 224(2):iyad068, 2023.