VACmap: An Accurate Long-Read Aligner for Unraveling Complex Genomic Rearrangements

Hongyu Ding[1], Fritz J Sedlazeck[2,3,4], Christos Proukakis[5], Caoimhe Morley[5], Marco Toffoli[5],

Anthony HV Schapira[5], Zhirui Liao[1], Lianrong Pu[6] and Shanfeng Zhu[1,*]

[1]Institute of Science and Technology for Brain-Inspired Intelligence and MOE Frontiers Center for Brain Science, Fudan University, Shanghai 200433, China.

[2]Human Genome Sequencing Center, Baylor College of Medicine, Houston, TX, USA

[3]Department of Molecular and Human Genetics, Baylor College of Medicine, TX, USA

[4]Department of Computer Science, Rice University, 6100 Main Street, Houston, TX, USA

[5] Department of Clinical and Movement Neurosciences, UCL Queen Square Institute of Neurology, London, UK.

[6] College of Computer Science and Technology, Shandong University, Qingdao, China

22110850043@m.fudan.edu.cn, zhusf@fudan.edu.cn

Abstract

Inversions, duplications, and other critical medically challenging variations are often ignored by routine genetic analyses. This is due to the complexity of these alleles but also because of the inability to accurately align them with state-of-the-art methods. We introduce VACmap, a novel non-linear long-read mapping method designed to improve detection of these difficult genomic regions, including critical genes like *LPA* and *GBA1*, which are significant risk factors for cardiovascular disease and Parkinson's disease, respectively.

Main

Structural variations (SVs) have emerged as crucial elements in genomic research, with their biological significance becoming increasingly apparent [1-4]. These genomic alterations, typically defined as changes of 50 base pairs or more, encompass five main categories: insertions, inversions, deletions, duplications, and translocations, as well as combinations thereof [1]. The impact of SVs on genomic composition is substantial, affecting more nucleotides than any other type of genetic variation [3, 5-7]. Consequently, their influence is being recognized across evolutionary processes, human health, and contribute to both Mendelian and complex diseases as well as cancer development [8-11]. Despite their critical

importance, our understanding of SVs remains limited [12]. This is in part due to the complexities of complex SV but also the inability of the current state of art aligners to represent them. Research has predominantly focused on simpler SV classes, such as deletions and insertions, while more intricate variations—like duplications, inversions, and complex clustered events—are often misrepresented and thus missed. This gap in our analytical approach hinders a comprehensive understanding of these important genomic phenomena [13, 14], despite their importance being highlighted in several publications already [7-11, 14-16].

These publications have mainly been driven by long-read sequencing that indeed enables the characterization of tandem repeats and thus regions where SV are predominantly observed [17]. Despite their advancements, long-reads are challenging to align due to their length and generally higher sequencing errors. In the past, others have highlighted that specialized aligners are required to accurately align them using predominantly linear alignments to the reference where multiple linear subalignments represent a potential SV. These sub-alignments are formed by identifying small, exact matching subsequences (k-mers) between the read and the reference sequence. Linear alignment algorithms then attempt to extend these matches in both directions until significant differences between the read and reference are detected. However, this process splits the read into segments and results in a large number of redundant subalignments, particularly in repetitive regions. In these regions, each segment of the read may map to multiple locations in the reference, making it difficult to determine the correct alignment. To improve this, long-read mapping methods have introduced additional steps aimed at choosing the most suitable subset of alignments to represent the complex structures introduced by SV. For example, minimap2 employs a greedy approach, selecting the highest-scoring sub-alignment at each step until all alignable regions of the read are accounted for [18]. In contrast, YAHA uses a graph-based algorithm that optimizes alignment selection by considering factors such as alignment length, quality, and genomic position [19]. NGMLR takes a similar approach but enhances the process with a scoring function and dynamic programming to identify the optimal combination of sub-alignments with the highest overall score [20]. Despite these advancements, post-alignment processes for determining the ideal set of sub-alignments are often inadequate because of the complexity of the allele and the underlying repetitive regions. They fail especially for duplication, inversion, and translocation, which are often missed or falsely identified by the linear alignment algorithms. Duplications are often misaligned as insertion because linear alignment algorithms prefer a single continuous alignment and treat duplication, which would require splitting reads, as insertion. Similarly, inversion and translocation, are often rather misaligned as splitting the reads is penalized and thus avoided.

Figure 1 The workflow of VACmap non-linear alignment algorithm and impact on downstream SV detection. a-d The workflows of the VACmap approach for mapping complex rearrangements. **a.** Collect matching k-mers between the long read and reference (blue for the forward strand, orange for the reverse strand). **b**. Computing non-linear alignments. **c**. Extract the non-linear alignment with the highest score. **d**. Divide the highest score non-linear alignment into multiple linear subalignments and easy to interpret SV. **e, f.** Performance assessment of SVIM using four aligners' alignments on GIAB benchmarks. **g.** Venn diagram showing the number of inversions discovered by SVIM call sets using alignments from four different mapping methods on HiFi data. **h.** The distribution of types and lengths among variants detected by SVIM on VACmap and minimap2 produced alignments.

To overcome this limitation of current methods, we propose VACmap, a long-read mapping
method specially designed to improve the representations of all SV with a focus on complex
genomic rearrangements. VACmap eliminating the conversational necessity of the post-
alignment step for alignment selection by allowing both linear and non-linear extension in the
alignment process. This novel approach simplifies the conversational workflow for read
mapping and significantly improves the representation of complex alleles, providing a more
accurate and comprehensive view of SVs.

Figure 1a-d gives an overview of VACmap's non-linear mapping approach. The most important
differentiation between VACMap and other approaches is implemented after initial matches
between reference and read sequences have been identified. Here existing methods try to
conserve the order of all subalignments by heavily penalizing splits when searching chains of
matches maintained. The linear alignment approach can efficiently model genomic alterations
such as deletions, insertions, and substitutions since these don't break the collinearity of a chain.
However, the linear approach penalizes the detection of complex SV such as duplication,
inversion, translocation, or combinations of SV. In VACmap, we propose a novel hybrid
alignment algorithm, which combines both linear and non-linear linkage approaches in a chain.
In detail, VACmap represent matches as quadruples called 'anchors', which include the start

positions in the long read and reference sequences, the strand match, and the anchor's length.
They are ordered by their start positions in the long read. The VACmap's non-linear chaining
algorithm then promotes the extension of the chain to subsequent anchors that preserve a strictly
linear relationship with the preceding anchor, enhancing this connection with a positive score.
Conversely, it penalizes extensions to anchors that disrupt this linearity by assigning negative
scores to such connections. Then the optimal non-linear alignment of the entire sequence is the
chain with the highest aggregate score (the longest path). Each of these linear subalignments
can be extracted by dividing the non-linear alignment at the non-linear junction, eliminating the
traditional necessity of additional post-alignment steps that reconstruct genomics
rearrangement from a pool of error-prone independent subalignments. See methods for details.
96

We evaluated the SV detection performance of VACmap, NGMLR, Winnowmap2, and
minimap2 alignments using the GIAB benchmark set [4, 21] with SVIM [22]. Truvari [23] was
used to assess precision, recall, and F1 scores. Before evaluation, SVIM's tandem duplication
calls were relabeled as insertions to allow for comparability to GIAB assembly-derived
benchmark. As expected all four alignment approaches demonstrated similar performance in
detecting deletions and insertions in both GIAB tier 1 and CMRG regions (Figure 1e). And the
runtime of VACmap is faster than NGMLR and Winnowmap2, but slower than minimap2.
However, VACmap requires approximately half the memory usage compared to the other
aligners (Supplementary Table 1). To evaluate SVIM's sensitivity in detecting duplications
using alignments from different tools, we isolated tandem duplication calls within the GIAB
benchmark set using REPTYPE annotation. The results (Figure 1f) showed that SVIM, using
VACmap-produced alignments, exhibited the highest sensitivity for duplication detection,
identifying approximately 70% and 80% more duplications compared to other alignment
approaches in the GIAB tier 1 and CRMG regions, respectively. This is highly important for
the interpretability of the impact of SV. The SV distribution detected by SVIM using VACmap-
produced alignments differed notably from other approaches (Figure 1h, Supplementary
Figures 1). The VACmap approach suggested that multiple insertions are indeed duplications,
aligning with previous findings [14]. The enhanced ability to accrue mapping duplication
segment also enabled VACmap to better characterization of a previously reported de novo
variation [24] (Supplementary Figures 2). This variation, located at chr14:23,280,711 (GRCh38
coordinate), was initially reported as a de novo insertion due to different insertion sizes in the
child (HG002: 537 bp) and parents (HG003: 214 bp and HG004: 15 bp). With VACmap
alignment, this de novo insertion was revealed to be a 109 bp Variable Number Tandem Repeat
(VNTR) with different repeat number in the child (n=5) and paternal parent (n=2).

Furthermore, the VACmap-SVIM callset included nearly all inversions (104/110) of the
combined callset from minimap2, Winnowmap2, and NGMLR approaches and uncovered an
additional 100 inversions (Figure 1g). For inversions that overlapped with previously reported
inversion callset [25], the VACmap-SVIM pipeline identified nearly all inversions (49/50)
reported by the other three approaches and identified an additional 12 inversions that were
missed by the other three approaches (Supplementary Figures 3). We manually inspected the
missed inversion from VACmap-SVIM pipeline and found out it's actually an inversion flanked

Figure 2 Comparison of four aligners on challenging gene regions. a, The IGV visualization of a segmental duplications flanked simple inversion at *SPIDR* gene locus. **b.** Comparison of sequences difference of HG002 assembly with GRCh37 assembly in inversion region at *SPIDR* gene locus. **c.** The IGV visualization of a potential *SIGLEC11* and *SIGLEC16* gene conversion event, the SVIM inversion prediction is shown in the top panel. **d.** Proposed scenario of gene conversions between *SIGLEC11* and *SIGLEC16* loci. **e.** The IGV visualization of alignments produced by four aligners in the *LPA* KIV-2 region. **f.** The illustration of GRCh38 reference modification and the exon structure of the KIV-2 domain. The exon 2 (red) in the type A KIV-2 repeat unit, type B KIV-2 repeat unit, and KIV-1 repeat unit have 100% identical sequences. The exon 1 (green) in the KIV-3 repeat unit and type B KIV-2 have 100% identical sequences. The light green and light orange regions indicate the reserved and removed regions, respectively. This figure is modified from [10]. **g, h.** The alignments scheme of type A KIV-2 sequence and type B KIV-2 sequence against modified GRCh38 reference. **i.** The dot plot depicting non-linear alignments generated by the VAC algorithm of GRCh38, CHM13, and HG002 assembly against modified GRCh38 reference. **j.** The IGV visualization of alignments produced by four aligners in the *GBA1 / GBAP1* region, with the SVIM deletion call shown at the top panel. Note, that Figures a, b, and c, d, e, j are under GRCh37, and GRCh38 coordinates, respectively.

by inverted duplication and deletion. VACmap successfully resolves the complex structure but
SVIM failed to detect it due to the intricacy structure not matching SVIM's predefined rule to

detect SV (Supplementary Figures 4).

Thus, highlighting that inversions remain challenging to resolve due to their locations often
being surrounded by large segmental duplications. To further investigate this, we analyze the
combined call set of 209 inversion regions from four aligners. Across all inversions, 32%
(67/209) of them are overlapped with segmental duplications and half of them (39/67) are only
detectable through VACmap alignment. For instance, VACmap alignment enables arcuate
identification of a homozygous 16-kb inversion located in the *SPIDR* gene (Figure 2a), a gene
is involved in DNA repair and associated with gonadal dysgenesis diseases [26]. On the contrary,
other aligners' alignments are less reliable, as they showed more mismatch bases (ie. signal of
wrongly mapping of reads [20]) and inconstant breakpoints across different read alignments.
It's evidence in the size standard deviation of the inversion in SVIM calls is 254.2 and 2066.4
for VACmap and NGMLR alignment, respectively. A higher variance will be considered an
unreliable SV prediction and assign a lower quality score (the SVIM quality score for this
inversion is 13, 0 for VACmap, NGMLR alignment) and be discarded by downstream analyses.
Figure 2b explains why NGMLR and other aligners failed to pinpoint the precise inversion
breakpoints and force unrelate sequences to align together. The linear alignment approach will
not terminate linear extension when reaching the inversion breakpoints since the subsequent
sequence is too similar to the reference, leading to a wrongful linear alignment without the
indication of inversion breakpoints. Supplementary Figures 5-9 showed additional examples of
VACmap's improved capabilities in mapping inversions.

However, SVIM may misinterpret complex inversion events as simple inversions. Figure 2c
and Supplementary Figures 10 show an SVIM misidentified inversion is actually a potential
SIGLEC11 and *SIGLEC16* gene conversion event on the maternal haplotype. The *SIGLEC11*
and *SIGLEC16* gene sequences are extremely similar in the region encoding the extracellular
domain due to gene conversions [27]. The most recent gene conversion events were reported to
occur one million years ago and involve regions A and A* in *SIGLEC11* and *SIGLEC16* genes,
respectively [27] (Figure 2d). However, the VACmap alignment suggested a potential novel
gene conversion event involving other similar regions B and B* in *SIGLEC11* and *SIGLEC16*
genes, respectively (Figure 2d). This region B* in the *SIGLEC16* gene was previously observed
by GIAB due to a dense series of heterozygous variants [21]. However, the gene conversion
event is not resolved by GIAB due to limitations in the alignment technique and it causes dozens
of false positive SNP calls in the GIAB CMRG benchmark set (Figure 2c). Further, VACmap
alignment successfully resolved the homozygous *RHCE* and *RHD* gene conversion event when
existing aligners failed and reduced over a hundred false positive SNP and indel calls in the
GIAB CMRG benchmark set (Supplementary Figures 11-12).

We next assessed the *LPA* gene to highlight a medically important region that is further
improved using VACmap. The complexity of this region raises due to high diversity in the
population which represents 5-40 copies of the KIV-2 repeat in the *LPA* gene [10]. This copy
number is inversely correlated with human lipoprotein(a) levels, which are strongly linked to
coronary heart disease [10]. However, quantifying the KIV-2 copy number accurately poses
significant challenges due to repetitiveness and thus the low mappability of sequencing reads

in the *LPA* gene region [28]. We assessed the performance of four mapping methods by aligning
PacBio HiFi and ONT sequencing data from human samples (CHM13 and HG002) against the
GRCh38 reference genome. IGV visualizations revealed that NGMLR, Winnowmap2, and
minimap2 produced alignments with excessive mismatches and less informative coverage
information compared to VACmap (Figure 2e). VACmap demonstrated a superior ability to
accurately represent KIV-2 repeats, showing clear and distinct coverage boundaries (Figure 2e,
Supplementary Figures 13-15).
182
To simplify KIV-2 copy number determination, we modified the GRCh38 reference by
removing the second to sixth KIV-2 repeat units and including the first 1000bp sequence of the
follow-up KIV-1 unit (Figure 2f). We then realigned the PacBio HiFi and ONT data to the
modified reference. Alignment dot plot and IGV visualizations indicated that VACmap-
produced alignments (Figure 2i, Supplementary Figures 16-19) showed the expected alignment
scheme of both type A and type B KIV-2 units (Figure 2g, 2h). Other mapping methods
struggled to produce correct alignments despite the reduced complexity of the modified
reference. Furthermore, the ONT reads facilitated the resolution of all 23 copies of the KIV-2
repeat unit in the CHM13 sample due to its longer read length compared to PacBio HiFi data
(Supplementary Figures 20).
193
To further demonstrate the clinical utility of VACmap, we chose *GBA1*. This is a major risk
factor for Parkinson's disease [29], a challenging gene to analyze [30], which is prone to
structural variants caused by recombination with a nearby highly homologous pseudogene
(*GBAP1*). We previously detected using ONT long reads with adaptive sampling a pathogenic
deletion which could not be correctly called after minimap2 or NGMLR alignment [31].
VACmap allowed SVIM to correctly report the breakpoints (Figure 2j), which is crucial in
determining whether a deletion is pathogenic.
201
In summary, VACmap breaks through this long-standing barrier of inaccurate representing
complex variants. This is achieved via an entirely new non-linear mapping approach and
demonstrating the novelty and need of its method especially on inversions and other critical
medically challenging genes such as *LPA* [21] and *GBA1*. Indeed, inversions remain challenging
to resolve especially due to their location often surrounded by large segmental duplications [25].
Furthermore, these regions often form more complex events than simple inversions. Neither of
forms complex or simple inversions are routinely detectable with state-of-the-art methods [25].
This is despite their clinical importance [32]. VACmap enables this detection with more precise
alignments of read segments than any other method available due to its novel non-linear
mapping approach. This further improves the characterization of complex duplications such as
shown in KIV-2 a region in *LPA* itself and of gene / pseudogene recombination as shown in
GBA1. VACmap can more precisely recapitulate the exact breakpoints within the reads which
leads to an improved detection and thus will provide novel insights. These are only two
examples of multiple medically important but challenging genes that VACmap can improve
upon and thus deliver a more precise picture of the variants currently often missed by analytical
methods [21].
218

Method

Variant-aware Chaining Algorithm

Current sequence alignment algorithms [13, 18-20, 33] attempt to align homology sequences via linear edits—deletions, insertions, and substitutions—that preserve the original sequence order and orientation. While effective for point mutations and small insertions or deletions (indels), this linear paradigm falls short when sequences exhibit complex genomic rearrangements such as duplications, inversions and translocations. Under this linear framework, duplications are often erroneously interpreted as insertions due to their identical signatures from a linear alignment perspective. Inversions, which do not result in a net gain or loss of genetic material, are challenging to distinguish from block substitutions. For more complex rearrangements—where multiple rearrangement events are clustered closely—the linear mapping approach attempts to reconstruct the complex structure by identifying all potential linear subalignments and selecting the most suitable subalignments from the pool of possibilities. The ideal representation, however, should consist of a series of linear subalignments connected by non-linear junctions at the breakpoints of these rearrangements. Yet, accurately retrieving the optimal set of subalignments is particularly challenging, especially for sequences located in highly repetitive regions or with substantial rearrangement complexity [34]. Moreover, since each linear subalignment is aligned independently, there is no assurance that a selection from locally optimal subalignments will culminate in a globally optimal alignment.

We present a novel solution with VACmap, a method that significantly deviates from the linear alignment model. VACmap integrates the Variant-aware Chaining (VAC) algorithm, which deftly combines linear and non-linear edits to achieve alignment. This dual-operation approach empowers VACmap to deliver a unified, globally optimal alignment that accurately reflects the genomic rearrangement in its entirety, bypassing the flawed post-alignment selection process.

To elaborate, our approach involved identifying k-mers that matched exactly between a reference sequence and a long-read sequence. These exact matches are expressed as quadruples, denoted as (x, y, s, k), and are termed anchors. Here, 'x' represents the start position of the anchor within the long-read sequence, while 'y' indicates the corresponding start position within the reference sequence. The variable 's' signifies the orientation of the match, with a value of 1 indicating alignment with the forward strand and -1 indicating alignment with the reverse strand. The 'k' variable specifies the extent of the sequence encompassed by the anchor. Within the framework of the VAC algorithm, these anchors are conceptualized as nodes within a graph that is both directed and weighted. We apply specific rules to the linkage of these nodes: Only nodes that precede others in the long-read sequence can form connections to those that follow. To determine the weight of the directed edge from node[i] to node[j], where i is less than j, symbolized as w(i, j), we utilize a set of predefined formulas.

$$diff < max(maxdiff - c_j, 10), 0 \leq s_j \times refgap < maxgap, s_i = s_j \qquad (1)$$

$$w(i,j) = \min(k_j, x_j + k_j - x_i - k_i) - CP_{i,j} \tag{2}$$

$$CP_{i,j} = 0.01 \times k_j * diff + \alpha \times log_2(\max(diff, 1)) + 0.1 \times log_2(\max(readgap, 1)) \tag{3}$$

$$w(i,j) = \min(k_j, x_j + k_j - x_i - k_i) - VP_{i,j} \tag{4}$$

$$VP_{i,j} = \beta + min(c_j, 20) + min\left\{ \begin{array}{l} 30 + 0.5 \times \ln(\max(1, diff)) \\ \underbrace{\min\left(10, \frac{diff}{100}\right) + \min\left(30, \frac{diff}{1000}\right)}_{\gamma} \end{array} \right. \tag{5}$$

$$if \begin{cases} a = 0.5 & diff < 10 \\ a = 2 & diff \geq 10 \end{cases} \tag{6}$$

$$diff = |readgap - refgap| \tag{7}$$

$$readgap = x_j - x_i - k_i, refgap = \begin{cases} y_j - y_i - k_i, \text{if } s_j = s_i = 1 \\ y_i - y_j - k_j, \text{if } s_j = s_i = -1 \\ y_j + k_j - y_i - k_j, \text{if } s_j \neq s_i, s_i = 1 \\ y_j - y_i, \text{if } s_j \neq s_i, s_i = -1 \end{cases} \tag{8}$$

$$readgap = 0, refgap = \begin{cases} y_j - y_i - x_j + x_i, \text{if } s_j = s_i = 1 \\ y_i + k_i - y_j - k_j - x_j + x_i, \text{if } s_j = s_i = -1 \\ y_j + k_j - y_i - x_j + x_i, \text{if } s_j \neq s_i, s_i = 1 \\ y_j + k_i - y_i - x_j + x_i, \text{if } s_j \neq s_i, s_i = -1 \end{cases} \tag{9}$$

When two nodes exhibit strict collinearity, as defined by Formula 1, we calculate their connecting edge weight using Formula 2. Edges that fall under this category are termed "normal" edges. Formula 1 allows small deletions or insertions between nodes, which are regulated by the hyperparameter *maxdiff*, set by default to 50, and 30 for the first and second rounds of chaining, respectively. To incorporate an additional penalty for small indels, we adopt the affine-convex gap penalty model from minimap2 as outlined in Formula 3, which we refer to as the *CP* (colinear penalty). Conversely, when nodes do not conform to the conditions of Formula 1, we determine their edge weight with Formula 4, designating these as "variation" edges. The variation penalty, *VP*, is established through Formula 5, with its maximum value set to the sum of β, γ, and 20. The default settings for β and γ are 30 and 36, respectively. Given that k-mers occurring with high frequency are typically less informative [20], we impose an additional penalty, c[j], when extending a chain to a node associated with a frequently occurring k-mer, thus enforcing a stricter collinearity criterion. Here, c[j] represents the count of occurrences in the k-mer index corresponding to node j. For overlapping and non-overlapping anchors, we use formulas 8 and 9 to compute their distance, respectively. To further clarity regarding these principles, we provide illustrative examples in Supplementary Figure 21 to show the conditions for assigning normal and variation edges. The selection of hyperparameter values critically affects the quality of the non-linear alignment, with maxdiff and maxgap (default values of (50, 30) and 100, respectively) being particularly influential. A reduced maxdiff value tends to yield a more strictly collinear subalignment, while a smaller maxgap value helps to prevent the erroneous alignment of unrelated sequences.

To find the optimal non-linear alignment path among *N* nodes can be computed in *O(hN)* time if by dynamic programming. For a given *node[j]*, we can determine its maximum score *S(j)* and its best predecessor *node[i]* by utilizing the following formulas:

$$S(j) = max\left(max_{i \in M}(S(i) + w(i,j)), k_j\right) \qquad i \in M \tag{10}$$

$$i \in M \qquad if\ S(i) \geq max_{k<j \wedge x_j > x_k}(S(k)) - (\beta + \gamma + 20) \tag{11}$$

The *node[j]* best predecessor score $S(i)$ has a low bound (Formula 10, 11). The
low bound is equal to the current highest score *S[k]* minus $(\beta + \gamma + 20)$, and *h* is equal
to the size of set M.
Once the maximum score of all nodes is computed, we can identify the highest
scores non-colinear chain by backtracking. The optimal set of colinear subalignments is
recovered by discarding variation edges in the highest score chain.
300

Local Index and Anchor Reduction

When sequence errors or SNPs occur in clusters, accurate mapping becomes
challenging, especially when utilizing a large k-mer size setting and a minimizer k-mer
sampling strategy. To mitigate this issue, VACmap adopts a similar approach used in a
previous study [33] by constructing a local index with a smaller k-mer size, typically a 9-
mer. The local index is built by collecting all possible k-mers from the previously
computed highest-scoring chain's covered reference genome region. Subsequently, all the
k-mers in the long read are employed to query the index, obtaining matching information
known as anchors. The highest scoring chain is then recomputed based on these anchors.
However, the runtime of the VAC algorithm depends on the number of anchors.
Using a smaller k-mer size setting often results in an increased number of anchors,
consequently escalating computational time. To address this issue, two strategies are
employed to reduce the number of anchors and improve runtime efficiency. Firstly,
VACmap iterates through the anchors and removes an anchor if the distance between the
anchor and the previously computed highest-scoring chain exceeds a certain threshold
(2000 bp). The distance between an anchor and the previous chain is defined as the
distance between the anchor and its closest anchor in the chain under the reference
sequence coordinate. Determining the closest anchor in the chain can be accomplished
through a binary search, with a time complexity of $O(log^{N})$, where N is the number of
anchors. Secondly, VACmap merges two anchors (x_i, y_i, s_i, k_i) and (x_j, y_j, s_j, k_j) into a new
anchor $(x_i, min(y_i, y_j), s_i, x_j + k_j - x_i)$ if they satisfy certain conditions (Formula 12). The
sorting of *N* anchors in ascending order based on their position in the long read allows the
merging process to be computed in $O(N)$ time using a hash table. The hash table utilizes
an integer key and maintains a list of merged anchors as its value. For *anchor$_i$*, if s$_i$ equals
1, then the key is set to y_i - x_i; otherwise, it is set to -$(y_i + x_i)$. VACmap tests the last *anchor$_j$*
in the list corresponding to a key. If the two anchors are overlapped or closely adjacent
and the covered sequence in reference and long read is identical, VACmap updates the last
anchor in the list; otherwise, *anchor$_i$* is appended to the list. If a key does not exist in the
hash table, a new key-value pair is inserted. Finally, the merged anchors set can be
obtained by traversing the hash table.

331
$$\begin{cases} y_i - x_i = y_j - x_j, x_i + k_i \geq x_{j,} s_j = s_i = 1, x_j > x_i, x_j + k_j - x_i \leq 19 \\ \qquad\qquad\qquad or \\ y_i + x_i + k_i = y_j + x_j + k_j, x_i + k_i \geq x_{j,} s_j = s_i = -1, x_j > x_i, x_j + k_j - x_i \leq 19 \end{cases} \qquad (12)$$

Quality Control of Linear Subalignment

The presence of sequencing error and closely situated SNPs complicates the process of gathering sufficient anchors for the chaining process. To accommodate the occurrence of sequencing errors and clustered SNPs, VACmap employs a sizeable hyperparameter, maxgap, with a default setting of 100, within the VAC algorithm. However, a large maxgap value has the potential drawback of mistakenly aligning sequences that are not actually related. To address this problem, we assess the error ratio within each linear subalignment and exclude those that demonstrate a high propensity for errors. This error ratio is ascertained by employing edlib [35] to calculate the edit distance between the matched sequences in the reference genome and the long read. The edit distance obtained is then normalized by dividing the length of the shorter sequence involved in the comparison. A linear subalignment is deemed unreliable and is therefore rejected if its error ratio surpasses the predetermined threshold: 0.2 for sequences generated using PacBio CLR or ONT, and 0.1 for sequences generated using PacBio HiFi.

Evaluation with GIAB callset

We evaluated four mapping methods, namely VACmap, NGMLR, Winnowmap2, and minimap2, using the GIAB Tier1 (v0.6) and CMRG (1.00) SV benchmark set for the HG002 human sample. These benchmark sets are available at the following links: https://ftp-trace.ncbi.nlm.nih.gov/ReferenceSamples/giab/release/AshkenazimTrio/HG002_NA24385_son/NIST_STRUCTURAL VARIANT_v0.6/ and https://ftp-trace.ncbi.nlm.nih.gov/ReferenceSamples/giab/release/AshkenazimTrio/HG002_NA24385_son/CMRG_v1.00/, respectively. PacBio CLR, PacBio HiFi, and ONT sequencing data were accessible at s3://giab/data/AshkenazimTrio/. The SVIM (v1.4.2) and were used to detect SVs. Subsequently, we evaluated the SVs against the GIAB benchmark set using Truvari (v2.0.0). Command line parameters provided to these tools are listed in Supplementary Table 2.

Data availability

This study utilized four human assembly genome sequences: GRCh37, GRCh38, CHM13 T2T (v2.0), and HG002 T2T (v1.1) [36]. They can be downloaded from the following links: http://ftp.1000genomes.ebi.ac.uk/vol1/ftp/technical/reference/phase2_reference_assembly_sequence/, https://ftp.1000genomes.ebi.ac.uk/vol1/ftp/technical/reference/GRCh38_reference_genome/, https://github.com/marbl/CHM13, and https://s3-us-west-2.amazonaws.com/human-pangenomics/T2T/HG002/assemblies/hg002v1.0.1.fasta.gz, respectively.

For the Pacbio CLR, Pacbio HiFi, and ONT sequencing data of the human sample HG002, HG003 and HG004. They can be downloaded from the following links:

s3://giab/data/AshkenazimTrio,   s3://giab/data/AshkenazimTrio,   and

s3://giab/data/AshkenazimTrio.

The Pacbio HiFi and ONT data for the human sample CHM13 were downloaded

from SRA under accessions SRR11292120-SRR11292123 and s3://human-

pangenomics/T2T/CHM13/nanopore/UW/chm13_UW_Guppy_3.6.0.fastq.gz,

respectively.

The *GBA1* data are available from Prof C Proukakis (c.proukakis@ucl.ac.uk) on

reasonable request, when compatible with consent/IRB restrictions.

Code availability

379   VACmap are available on GitHub: https://github.com/micahvista/VACmap.

Ethics statement

381   Ethics approval for the *GBA1* carrier was provided by the National Research Ethics

382   Service London—Hampstead Ethics Committee as part of the RAPSODI study

383   (www.rapsodi.com) [37]. Informed consent was provided.

Reference

[1] Mahmoud, M., Gobet, N., Cruz-Dávalos, D.I. et al. Structural variant calling: the long and the short of it. Genome Biol 20, 246 (2019). https://doi.org/10.1186/s13059-019-1828-7

[2] Ho, S. S., Urban, A. E. & Mills, R. E. Structural variation in the sequencing era. Nat. Rev. Genet. 21, 171–189 (2020).

[3] Sudmant PH, Rausch T, Gardner EJ, Handsaker RE, Abyzov A, Huddleston J, et al. An integrated map of structural variation in 2,504 human genomes. Nature. 2015;526(7571):75–81.

[4] Zook, J. M. et al. A robust benchmark for detection of germline large deletions and insertions. Nat. Biotechnol. 38, 1347–1355 (2020).

[5] Redon, R. et al. Global variation in copy number in the human genome. Nature 444, 444–454 (2006).

[6] Chaisson, M. J. P. et al. Multi-platform discovery of haplotype-resolved structural variation in human genomes. Nat. Commun. 10, 1784 (2019).

[7] Audano, P. A. et al. Characterizing the major structural variant alleles of the human genome. Cell 176, 663–675.e619 (2019).

[8] Sekar, S. et al. Complex mosaic structural variations in human fetal brains. Genome Res. 30, 1695–1704 (2020).

[9] Leija-Salazar, M. et al. Evaluation of the detection of GBA missense mutations and other variants using the Oxford Nanopore MinION. Mol. Genet. Genomic Med. 7, e564 (2019).

[10] Schmidt, K., Noureen, A., Kronenberg, F. & Utermann, G. Structure, function, and genetics of lipoprotein (a). J. Lipid Res. 57, 1339–1359 (2016).

[11] Aganezov, S. et al. Comprehensive analysis of structural variants in breast cancer genomes using single-molecule sequencing. Genome Res. 30, 1258–1273 (2020).

[12] Hanlon, V. C. T., Lansdorp, P. M., & Guryev, V. (2022). A survey of current methods to detect and genotype inversions. Human Mutation, 43(11), 1576–1589.

[13] Jain, C., Rhie, A., Hansen, N.F. et al. Long-read mapping to repetitive reference sequences using Winnowmap2. Nat Methods 19, 705–710 (2022). https://doi.org/10.1038/s41592-022-01457-8.

[14] https://www.biorxiv.org/content/10.1101/2024.04.18.590093v1

[15] Carvalho, C. M. B. & Lupski, J. R. Mechanisms underlying structural variant formation in genomic disorders. Nat. Rev. Genet. 17, 224–238 (2016).

[16] Beck, C. R. et al. Megabase length hypermutation accompanies human structural variation at 17p11.2. Cell 176, 1310–1324 (2019).

[17] English, A.C., Dolzhenko, E., Ziaei Jam, H. et al. Analysis and benchmarking of small and large genomic variants across tandem repeats. Nat Biotechnol (2024). https://doi.org/10.1038/s41587-024-02225-z

[18] Li H. Minimap2: pairwise alignment for nucleotide sequences. Bioinformatics. 2018;34(18):3094–100.

[19] Faust GG, Hall IM. YAHA: fast and flexible long-read alignment with optimal breakpoint detection. Bioinformatics.
2012;28(19):2417–24.

[20] Sedlazeck FJ, Rescheneder P, Smolka M, Fang H, Nattestad M, von Haeseler A, Schatz MC. Accurate detection of
Complex structural variants using single-molecule sequencing. Nat Methods. 2018;15:461–8.

[21] Wagner, J., Olson, N.D., Harris, L. et al. Curated variation benchmarks for challenging medically relevant autosomal
genes. Nat Biotechnol 40, 672–680 (2022). https://doi.org/10.1038/s41587-021-01158-1

[22] David Heller, Martin Vingron, SVIM: structural variant identification using mapped long reads, Bioinformatics, Volume
35, Issue 17, 1 September 2019, Pages 2907–2915.

[23] English, A.C., Menon, V.K., Gibbs, R.A. et al. Truvari: refined structural variant comparison preserves allelic diversity.
Genome Biol 23, 271 (2022). https://doi.org/10.1186/s13059-022-02840-6.

[24] Kirsche, M., Prabhu, G., Sherman, R. et al. Jasmine and Iris: population-scale structural variant comparison and analysis.
Nat Methods 20, 408–417 (2023). https://doi.org/10.1038/s41592-022-01753-3

[25] Porubsky D., Höps W., Ashraf H., Hsieh P., Rodriguez-Martin B., Yilmaz F., et al. (2022). Recurrent inversion
polymorphisms in humans associate with genetic instability and genomic disorders. Cell 185, 1986–2005.e26.
10.1016/j.cell.2022.04.017

[26] Smirin-Yosef P, Zuckerman-Levin N, Tzur S, Granot Y, Cohen L, Sachsenweger J, Borck G, Lagovsky I, Salmon-Divon
M, Wiesmüller L, Basel-Vanagaite L. A Biallelic Mutation in the Homologous Recombination Repair Gene SPIDR Is
Associated With Human Gonadal Dysgenesis. J Clin Endocrinol Metab. 2017 Feb 1;102(2):681-688. doi: 10.1210/jc.2016-
2714. Erratum in: J Clin Endocrinol Metab. 2018 Jan 1;103(1):364. doi: 10.1210/jc.2017-02413. PMID: 27967308.

[27] Wang X, Mitra N, Cruz P, Deng L; NISC Comparative Sequencing Program; Varki N, Angata T, Green ED, Mullikin J,
Hayakawa T, Varki A. Evolution of siglec-11 and siglec-16 genes in hominins. Mol Biol Evol. 2012 Aug;29(8):2073-86. doi:
10.1093/molbev/mss077. Epub 2012 Mar 1. PMID: 22383531; PMCID: PMC3408085.

[28] Chen-Shan Chin, Sairam Behera, Ginger A. Metcalf, Richard A. Gibbs, Eric Boerwinkle, Fritz J. Sedlazeck. A pan-
genome approach to decipher variants in the highly complex tandem repeat of LPA. bioRxiv 2022.06.08.495395;

[29] O'Regan, Grace et al. 'Glucocerebrosidase Mutations in Parkinson Disease'. 1 Jan. 2017 : 411 – 422.

[30] Mandelker, D., Schmidt, R., Ankala, A. et al. Navigating highly homologous genes in a molecular diagnostic setting: a
resource for clinical next-generation sequencing. Genet Med 18, 1282–1289 (2016). https://doi.org/10.1038/gim.2016.58

[31] Toffoli, M., Chen, X., Sedlazeck, F.J. et al. Comprehensive short and long read sequencing analysis for the Gaucher and
Parkinson's disease-associated GBA gene. Commun Biol 5, 670 (2022). https://doi.org/10.1038/s42003-022-03610-7

[32] Carvalho, C., Lupski, J. Mechanisms underlying structural variant formation in genomic disorders. Nat Rev Genet 17,
224–238 (2016). https://doi.org/10.1038/nrg.2015.25

[33] Ren J, Chaisson MJ. lra: A long read aligner for sequences and contigs. PLOS Comput Biol. 2021;17(6):e1009078.

[34] Quinlan AR, et al. Genome-wide mapping and assembly of structural variant breakpoints in the mouse genome. Genome
Res. 2010;20:623–635.

[35] Šošic M, Šikic M. Edlib: a C/C ++ library for fast, exact sequence alignment using edit distance. Bioinformatics. 2017
May 1;33(9):1394-1395. doi: 10.1093/bioinformatics/btw753. PMID: 28453688; PMCID: PMC5408825.

[36] Nurk, S. et al. The complete sequence of a human genome. Science 376, 44–53 (2022).

[37] Toffoli, M. et al. Phenotypic effect of GBA1 variants in individuals with and without Parkinson's disease: the RAPSODI
study. Neurobiol. Dis. 188, 106343 (2023).

Acknowledgment

We would like to thank Dr. Kristoffer Sahlin (Stockholm University) and Dr. Mingfu Shao (Pennsylvania State University) for their helpful suggestions and insightful comments on the manuscript. This work has been supported by the National Natural Science Foundation of China (Grant No. 62272105), the Shanghai Municipal Science and Technology Major Project (Grant No. 2018SHZDZX01), 111 Project (Grant No. B18015), the ZJ Lab, the Shanghai Research Center for Brain Science and Brain-inspired Intelligence Technology. C.M. is supported by the MSA Trust.

Author contributions

S.Z. supervised this study. H.D. designed the study and implemented the software. H.D., F.J.S., C.P. and C.M. performed the data analysis. H. D. drafted the paper. F.J.S., C.P., M.T., A.H.V.S., Z. L., L.P. and S.Z. modified the paper. All authors agree to the content of the final paper.

Competing interests

F.J.S. receives research support from Illumina, PacBio and Oxford Nanopore. The remaining authors declare no competing interests.