1 **Can Prediction Error Explain Predictability Effects on the N1 during Picture-Word**

2 **Verification?**

3   Jack E. Taylor[1,2], Guillaume A. Rousselet[2], and Sara C. Sereno[2]

4   [1]Department of Psychology, Goethe University Frankfurt

5   [2]School of Psychology and Neuroscience, University of Glasgow

Author Note

Jack E. Taylor https://orcid.org/0000-0003-4765-0118

Guillaume A. Rousselet https://orcid.org/0000-0003-0006-8729

Sara C. Sereno https://orcid.org/0000-0001-7957-9542

Correspondence concerning this article should be addressed to Jack E. Taylor Department of Psychology, Goethe University Frankfurt; E-mail: Taylor@psych.uni-frankfurt.de

Author Contributions: *J.E.T.* - Conceptualisation, Methodology, Software, Formal Analysis, Investigation, Data Curation, Writing, Visualisation. *S.C.S.* - Conceptualisation, Methodology, Writing, Supervision. *G.A.R.* - Methodology, Formal Analysis, Writing, Supervision.

Authors report no conflict of interest.

This research was supported in part by an Economic and Social Research Council (ESRC) postgraduate fellowship awarded to J. E. Taylor (reference: ES/P000681/l).

Abstract

Do early effects of predictability in visual word recognition reflect prediction error? Electrophysiological research investigating word processing has demonstrated predictability effects in the N1, or first negative component of the event-related potential (ERP). However, findings regarding the magnitude of effects and potential interactions of predictability with lexical variables have been inconsistent. Moreover, past studies have typically used categorical designs with relatively small samples and relied on by-participant analyses. Nevertheless, reports have generally shown that predicted words elicit less negative-going (i.e., lower amplitude) N1s, a pattern consistent with a simple predictive coding account. In our preregistered study, we tested this account via the interaction between prediction magnitude and certainty. A picture-word verification paradigm was implemented in which pictures were followed by tightly matched picture-congruent or picture-incongruent written nouns. The predictability of target (picture-congruent) nouns was manipulated continuously based on norms of association between a picture and its name. ERPs from 68 participants revealed a pattern of effects opposite to that expected under a simple predictive coding framework.

Keywords: N1, N170, Prediction, Predictive Coding, Word Recognition

Can Prediction Error Explain Predictability Effects on the N1 during Picture-Word Verification?

Introduction

Readers and listeners routinely use context to predict upcoming semantic and lexical content. Evidence for such predictive processes arises from both behavioural and neural correlates of language comprehension (Kuperberg & Jaeger, 2016; Luke & Christianson, 2016; Pickering & Gambi, 2018; Rayner et al., 2011; Van Petten & Luka, 2012), with demonstrated facilitation for the processing of predicted information (Federmeier, 2007; Pickering & Garrod, 2013).

A key question in this area is, how early in the processing stream are predictive processes able to modulate visual word recognition. One early stage in visual word recognition, which may be sensitive to prediction, involves the processing of visual word forms. A word form can be defined as the visual pattern of a single written word, comprised of smaller orthographic components (e.g., letters, letter bigrams, graphemes, strokes). While some electrophysiological evidence suggests sensitivity to orthographic variables in an earlier posterior P1 component peaking at around 100 ms after word presentation (e.g., Nobre et al., 1994; Segalowitz & Zheng, 2009; Sereno et al., 1998), the event-related potential (ERP) component most identified as an index of orthographic processing across different scripts is the first posterior negative-going wave, the N1 (Bentin et al., 1999; Lin et al., 2011; Ling et al., 2019; Maurer, Brandeis, & McCandliss, 2005; Maurer et al., 2008; Pleisch et al., 2019). The N1 is also sometimes referred to as the N170 due to the timing of its peak in some studies, at around 170 ms. This typically occipitotemporal, negative-going component shows reliable differences between orthographic and non-orthographic stimuli (e.g., words elicit more negative-going N1s than false-font strings do; Appelbaum et al., 2009; Bentin et al., 1999; Eberhard-Moscicka et al., 2016; Maurer, Brandeis, & McCandliss, 2005; Maurer, Brem, et al., 2005; Pleisch et al., 2019; Zhao et al., 2014).

Accounts of orthographic processing often stress the importance of top-down predictions, and their interactions with bottom-up sensory input. For instance, the interactive account of the ventral occipito-temporal cortex (vOT), a region which is a likely generator of the N1 ERP component (Allison et al., 1994; Brem et al., 2009; Cohen et al., 2000; Dale et al., 2000; Maurer, Brem, et al., 2005; Nobre et al., 1994; Taha et al., 2013; Woolnough et al., 2021), suggests that sensitivity to orthography arises through the synthesis of bottom-up visuospatial information and top-down predictions informed by prior experience and knowledge (Price & Devlin, 2011). Such accounts exist within a predictive coding framework, according to which the brain utilises higher-level information to build, maintain, and continually update hierarchical series of estimators that form generative models of sensory information (Friston, 2010; Rao & Ballard, 1999; Rauss et al., 2011). Predictive coding accounts have been employed to explain prediction effects observed in early evoked responses across a range of domains, such as the mismatch negativity (Garrido et al., 2009) and sensory attenuation of self-generated percepts (Knolle et al., 2013). A key feature of such accounts is that higher-level predictions cause lower-level features to be preactivated, and that the difference between the bottom-up sensory input and top-down predictions corresponds to a prediction error, which the brain attempts to minimise (Clark, 2013; Walsh et al., 2020).

In a predictive coding framework, prediction errors are commonly determined by two key attributes: the magnitude of the error, and the precision or certainty of the error (Feldman & Friston, 2010; Kanai et al., 2015). Such variants of predictive coding models are commonly referred to as *precision-weighted*. Feldman and Friston (2010) likened the error signal to the calculation of the *t* statistic, where magnitude of an observation (i.e., mean, or mean difference) is divided by the inverse of its precision (i.e., standard error). Prediction errors, weighted by precision in this manner, can be conceptualised as representing the degree of "surprise" associated with a set of observations under a specified hypothesis.

Firstly, the magnitude of the error should determine the size of the error signal,

with larger prediction errors resulting from greater mismatch between descending

(top-down) predictions and ascending (bottom-up) sensory input. In neutral

(non-biasing) contexts, a predictive coding account that includes learning of statistical

regularities over extended periods would assert that error signals should vary as a

function of stimulus regularity. More specifically, a predictive coding account of

orthographic processing would expect error signals to vary as a function of the size of

the difference between a general orthographic prior (e.g., an average word form) and a

presented word form. Some recent findings appear to support the notion that the N1

reflects a neutral-context error signal, with greater distance from an orthographic prior

eliciting greater amplitude (Gagl et al., 2020), while the profile of the N1's sensitivity to

word form regularity over experience matches that expected under a predictive coding

account (Huang et al., 2022; Zhao et al., 2019).

Secondly, the precision or certainty of the prediction error should influence the

response, with more certain descending predictions, and more certain ascending

sensory input, eliciting greater error signals when predictions are violated. In neutral

contexts, predictions, and certainty about them, may not be expected to vary much from

a context-general prior. Indeed, it is easier to envisage the expected role of prediction

precision for orthographic processing in biasing contexts, where precision is more

variable than it is in neutral contexts. A predictive coding model of orthographic

processing that allows for online, context-informed updating of orthographic priors would

expect that the predictability of word forms should influence error responses, with more

predictable contexts eliciting stronger prediction error effects. For instance, a sentential

context that elicits a clear and reliable prediction for an upcoming word (i.e., that has high

Cloze probability) should show a larger prediction error difference, between succeeding

prediction-congruent and -incongruent word forms, than should a more neutral sentential

context that is consistent with a large number of low-probability candidate words.

¹²² In this paper, we examine whether a simple predictive coding account that ¹²³ includes online updating of context-biased predictions and expectations can explain ¹²⁴ neural activity, captured in the N1, elicited by a word in context. Specifically, we examine ¹²⁵ whether sensitivity to prediction error in the N1 is dependent on contextual predictability ¹²⁶ in the manner that a predictive coding account would expect. This question is prompted ¹²⁷ by (1) the emerging evidence that the N1 in neutral contexts is consistent with an ¹²⁸ orthographic prediction error signal (Gagl et al., 2020; Huang et al., 2022; Zhao et al., ¹²⁹ 2019), and (2) existing evidence that biasing semantic contexts can modulate the N1 ¹³⁰ ERP (outlined below). To address our question, we employ a paradigm informed directly ¹³¹ by predictive coding models, manipulating prediction congruency and precision ¹³² independently, to examine whether the N1 shows the pattern of amplitudes expected ¹³³ under such a model, in biasing contexts. Moreover, we maximise our sensitivity to an ¹³⁴ orthographic prediction error by presenting prediction-congruent and -incongruent words ¹³⁵ that are carefully matched item-wise on possible confounders, with maximal orthographic ¹³⁶ distance from one another. Importantly, evidence for a context-informed prediction error ¹³⁷ signal at an early, likely orthographic, stage of processing, would not preclude the ¹³⁸ existence of similar prediction error signals at later stages. Indeed, the hierarchically ¹³⁹ composed generative model posited by a predictive coding account is fully compatible ¹⁴⁰ with the production of prediction errors spanning a hierarchy of linguistic representations.

¹⁴¹ We hypothesise that according to a simple predictive coding model, the N1 should ¹⁴² be larger for prediction-incongruent than prediction-congruent word forms (i.e., prediction ¹⁴³ error), in a manner dependent on the level of predictability (i.e., precision). We ¹⁴⁴ hypothesise that as predictability increases, so too should the prediction error effect.

¹⁴⁵ We begin by reviewing findings from prior studies. We make a distinction between ¹⁴⁶ those studies that have biased expectations via *linguistic cues* (text preceding the target ¹⁴⁷ word), and those that have employed *non-linguistic cues* (e.g., cross-modal contexts and ¹⁴⁸ manipulation of task demands).

Biasing Word Form Predictions via Linguistic Cues

Readers' predictions of upcoming word forms are generally manipulated via linguistic cues. In these studies, a target word's predictability is typically determined in a pre-experiment norming study, operationalised via Cloze probability (i.e., the probability that the target is correctly guessed given its preceding context). Such a measure of word form predictability aligns closely with the concept of prediction precision or certainty in a predictive coding account.

Recent ERP investigations that have manipulated sentential context have also often varied word frequency, with the assumption that an interaction of predictability with word frequency would provide evidence for top-down influences on lexical access. In **Table** 1, we summarise N1 results reported from studies using sentential paradigms that have employed such *Predictability × Frequency* designs. While effects often extend to earlier and later components, we limit our summary to those involving predictability within the N1 window. In Figure 1 we visualise the timing of N1 windows applied in these studies and others cited in this introduction. Sentential studies using a Predictability × Frequency design have demonstrated effects in the N1, although the pattern of effects observed across studies is varied (for a review, see Sereno et al., 2019). We also note that studies using average reference showed more posterior effects, while effects reported from studies using mastoid reference showed more centroparietal topography.

In addition to such studies that focused on the N1, some studies designed to focus on N400 effects of predictability may also provide insight into early prediction effects. For instance, Brothers et al. (2015) examined correlates of prediction accuracy in the N400, in a sentential design with cloze probability of either medium (.5) or low (<.01) cloze probability. Although they did not report effects in the N1, Brothers et al. did show that accurate predictions of upcoming words were associated with more positive amplitudes after 200 ms, in a P2 component immediately following the N1. In another N400 study using a design related to that employed in the present study, Lau et al.

Study and Results Summary	SOA	Window	Effect Sites	Reference
Sereno et al. (2003)				
More negative amplitudes at lower predictability, but only for low frequency words.	450	132-192	Posterior & Anterior [a]	Average
Penolazzi et al. (2007) [b]				
More negative amplitudes at higher predictability, and no interaction with frequency.	700	170-190	Centroparietal	Mastoids
Dambacher et al. (2012)				
More negative amplitudes for low than high frequency words, but only at higher predictability.	280 [c]	135-155	Posterior	Average
More negative amplitudes for low than high frequency words, and no interaction with predictability.	280 [c]	190-260	Posterior	Average
Kretzschmar et al. (2015)				
More negative amplitudes at higher predictability, and no interaction with frequency.	- [d]	150-200	Centroparietal	Mastoids
Sereno et al. (2019)				
More negative amplitudes at higher predictability, but only for high frequency words.	300	160-200	Left	Average
More negative amplitudes at lower predictability, but only for high frequency words.	300	160-200	Right	Average

SOA: Stimulus Onset Asynchrony (ms).
Window: Analysed ERP Window (ms).

[a] This topography describes the first factor in a spatial factor analysis.
[b] This study additionally manipulated word length, finding no interaction in the N1.
[c] SOA varied (280, 490, & 700 ms), with N1 effects only observed at the SOA of 280 ms.
[d] This study analysed Fixation-Related Potentials in self-paced reading.

Table 1
Summary of N1 effects reported in studies that biased word form predictions in sentential paradigms, using a Predictability (low, high) × Frequency (low, high) factorial design.

Figure 1

N1 windows in predictability studies.

Some studies analysed two N1 windows (e.g., onset and offset). N1 windows reported to show a predictability effect are highlighted in black, while N1 windows that failed to show a predictability effect are highlighted in grey. Studies are listed in order of their mention in our review. For reference, the blue region displays the N1 period that we pre-registered.

(2016) presented adjective-noun pairs to participants in which the effects of both congruency and predictability were examined, showing small congruency, and large predictability, effects in the N400. As with Brothers et al., Lau et al. report ERPs with no robust differences prior to a P2 component.

Instead of manipulating error precision or certainty, as the above studies have by varying predictability, Kim and Lai (2012) manipulated the orthographic error *magnitude*. Using a 550 ms SOA, the target word or alternative orthographic versions of it were presented in contexts that were acutely predictive of the target (M_{Cloze}=.90). Contexts were followed by the predictable target word (e.g., *cake*), an orthographically similar pseudoword (e.g., *ceke*), an orthographically dissimilar pseudoword (e.g., *tont*), or a consonant-string nonword (e.g., *srdt*). Consistent with an orthographic explanation for prediction effects in the N1, relative to targets, N1 (175-205 ms) amplitude was more

negative-going for orthographically dissimilar pseudowords and nonwords (i.e., when

orthographic prediction error magnitude was greater). Orthographically similar

pseudowords, while significantly different from all other conditions in the earlier P1,

elicited N1 components more similar in amplitude to target words.

Another linguistic cue that has been manipulated is grammaticality. Kim and

Gilley (2013) demonstrated effects of syntactic anomaly on the N1. Sentences leading to

a strong prediction for the determiner, *the*, were presented unchanged or with the

determiner replaced with an agrammatic preposition (e.g., *The thief was caught by*

the/for police). The left-lateralised occipitotemporal N1 (170-270 ms) was more

negative-going with the syntactically anomalous preposition than with the determiner. As

the authors point out, the N1 effect is unlikely to be evidence for sensitivity to syntax per

se. Rather, given evidence of the N1's sensitivity to orthographic features, it is probably

more accurate to posit that the high predictability of the determiner's orthographic

features elicited a less negative-going N1 when these predictions were confirmed.

Kim and Gilley's simultaneous manipulation of orthography and syntax highlights

a prevalent issue within the literature: namely, altering the visual word form necessitates

alteration of the semantics, syntax, and/or plausibility of the sentence or wider discourse.

Another limitation shared by studies using word-by-word presentation of sentences is

that ERPs elicited by the target word can become difficult to disentangle from ERPs

elicited by preceding or succeeding words, especially if the SOA is short or unjittered.

While fast presentation times of sentential contexts and targets are useful for

demonstrating that early modulation by predictive processes extends to realistic reading

rates, their application may not be necessary to demonstrate that such modulation can

occur. It is also of note that in a recent review of ERP studies using sentence- and

discourse-level contexts to examine early neural correlates of word form prediction,

Nieuwland (2019) concluded that findings thus far have been weak, inconsistent, and in

need of more replication attempts. Moreover, most studies to date were not

pre-registered and often used inappropriate analysis models that did not account for

measurement variability, raising questions about false positives in that literature.

Biasing Word Forms via Non-Linguistic Cues

Effects of prediction and expectation may alternatively be investigated using

paradigms that modulate non-linguistic features of tasks and stimuli. In one approach,

identical or suitably matched stimuli are presented under different task instructions (e.g.,

Compton et al., 1991). In that context, tasks requiring more explicit lexical and semantic

processing cause words to elicit more negative-going N1s (144-176 ms; Chen et al.,

2013). Tasks requiring more in-depth lexicosemantic processing may also increase

sensitivity to lexical variables such as word frequency in the N1 (144-176 ms, Chen et al.,

2015; 150-250 ms, Strijkers et al., 2015), and may increase the size of script familiarity

effects (more negative amplitudes for familiar scripts) (F. Wang & Maurer, 2017). This

may be especially in the N1's offset period (172-253 ms F. Wang & Maurer, 2017), where

onsets and offsets are defined respectively as the periods in the component's time

window which precede and succeed its peak. F. Wang and Maurer (2020) further

showed that biasing participants' word form predictions towards expecting a familiar

script increased the size of the script familiarity effect in the N1 offset (162-212 ms).

In addition to task manipulations, non-sentential semantic contexts, leading to

predictions for specific words or categories of words, have also been used to investigate

predictive processing. Segalowitz and Zheng (2009) reported an interaction between

stimulus type (word vs. pseudoword) and expectation (one vs. five categories) in the N1

(158-178 ms), wherein expectation affected N1 amplitudes for words but not for

pseudowords. Their finding suggested that the N1 was sensitive to the greater predictive

strength of a single semantic category. Using a similar paradigm, Hauk et al. (2012)

compared ERPs in lexical and semantic decision tasks, showing that effects of category

relevance were observed in the semantic decision task as early as 166 ms (data were

analysed continuously, with no N1 window definition). This finding suggests, consistent

with the findings of Segalowitz and Zheng, an early sensitivity to category relevance

during the N1 which, given the N1's robust sensitivity to orthography, is likely to reflect an

influence of semantic-level predictions on orthographic processing.

In another attempt to modulate top-down expectancy without linguistic context,

Dikker and Pylkkänen (2011) implemented a picture-noun phrase verification task. An

image of a target object alone or an image of objects related to the target object was

followed by a written noun phrase (article + noun) denoting the target object. They

manipulated congruency and predictability. For congruent trials, the noun phrase referred

to a food/drink or animal (e.g., *the apple* or *the monkey*) that matched the prior image of

the object presented on its own or 'contained' in a stylized image (e.g., a grocery bag or

Noah's Ark, respectively). In the incongruent condition, the noun phrase did not match

the prior image (single object or collection of objects). Predictability was considered high

when the target object appeared on its own, and was considered low when the target

object could be inferred to exist within the stylized images. Example conditions for the

noun phrase, *the apple*, are determined by its preceding image as follows: an apple

(congruent, high predictability), a banana (incongruent, high predictability), a bag of

groceries (congruent, low predictability), or Noah's Ark (incongruent, low predictability).

Noun phrases (40 food/drink, 40 animal) were repeated four times across conditions.

Although Dikker and Pylkkanen did not examine effects in the MEG equivalent of an N1

window, they did find effects of congruency only in the high predictive condition (i.e., the

apple preceded by an apple vs. a banana image) in temporal windows preceding ($\sim$100

ms) and succeeding (250-400 ms) the N1. Their stimuli were designed to minimise

orthographic similarity between congruent and incongruent pairs of noun phrases (i.e.,

maximising the magnitude of orthographic errors), suggesting that the authors

anticipated that any early sensory effect of predictability may be related to orthographic

processing. With only 7 participants, the study likely lacked the sample size necessary to

identify such an effect in an N1-like window. In a study using the same stimuli as Dikker

and Pylkkänen, Cheimariou et al. (2019) examined the effects of aging on lexical

prediction indexed by the N400 component. Cheimariou et al. also did not analyse an

N1 window, and used Mastoid reference sites, but did show that an early, though wide,

window from 125-348 ms showed topographically broad prediction effects in younger

adults, with more negative amplitudes for predictive content.

We note that related paradigms using fMRI often show orthography-semantics

interactions in the likely N1 generator, the left vOT (e.g., Branzi et al., 2022; Kherif et al.,

2011; J. Wang et al., 2019). However, fMRI prevents the interpretation of the timing of

such effects - its coarse temporal resolution means that mapping of semantic content to

representations in vOT could occur so late after word presentation as to be irrelevant to

initial orthographic word recognition processes.

One advantage of paradigms like picture-word verification tasks is that the

researcher can control and manipulate variables like predictability and specificity of the

picture-word relation. This was demonstrated in the design used by Dikker and

Pylkkänen (2011), where the picture preceding the target word unambiguously biased

participants' expectations to a single word form (with an image of one clearly identifiable

object), or instead biased a set of semantically related possible word forms (with an

image inducing multiple object candidates). Such a manipulation is comparable to the

use of Cloze probability in sentential contexts or single versus multiple category priming,

and similarly aligns with the concept of error precision or certainty.

The Present Study

In the present study, we adapted the picture-word verification paradigm to

examine the Congruency-Predictability interaction in the N1. We presented participants

with PICTURE-word pairs that were congruent (e.g., ONION-onion) or incongruent (e.g.,

ONION-torch). Predictability of the congruent word, given the picture that precedes it,

was operationalised via a continuous variable drawn from picture naming norms

(Brodeur et al., 2014) reflecting the probability of the congruent word being given as a

name for the picture (**Figure 2**). Picture-congruent words with very low predictability

were always semantically appropriate names for their associated image, though they

were difficult to predict, often because several acceptable names exist. For example, the

image for *spear* in **Figure 2** could also be plausibly named with words like *lance*, *javelin*,

or *pole*. Incongruent words, meanwhile, were specifically selected to be semantically

incongruent with congruent words, but matched on relevant psycholinguistic dimensions.

By manipulating both Congruency and Predictability of word forms, we were able to

examine whether the effect of Congruency on the N1 (sensitivity to prediction error) is

contingent on Predictability (certainty or precision of prediction errors), in the manner

expected according to a simple predictive coding account of the N1 in which observed

N1 magnitude indexes prediction error.

Figure 2
Illustration of the experimental stimuli.

PICTURE-word pairs were either congruent (e.g., NAPKIN-*napkin*) or incongruent (e.g., NAPKIN-*weasel*), while predictability of congruent picture-word pairs varied continuously. Ten example picture-congruent and -incongruent pairs are presented, with their predictability corresponding to the histogram bin they appear above.

We hypothesised, consistent with such a predictive coding account, that that there

would be a Congruency-Predictability interaction in which at the highest levels of

Predictability, N1s elicited by picture-incongruent words would be more negative-going

than those elicited by picture-congruent words, while at the lowest level of Predictability

picture-congruent and -incongruent words should elicit N1s of similar magnitude. We

anticipated three patterns of results that would have been consistent with this hypothesis:

(1) higher levels of Predictability lead to a reduction in N1 magnitude only for picture-congruent words, with no such effect for picture-incongruent words (**Figure 3a**);

(2) higher levels of Predictability lead to an increase in N1 magnitude only for picture-incongruent words, with no such effect for picture-congruent words (**Figure 3b**); or

(3) higher levels of Predictability lead to both a reduction in N1 magnitude for picture-congruent words and an increase in N1 magnitude for picture-incongruent words (**Figure 3c**).

In our power analysis, we focused on the first of these possible patterns of results, but importantly, the Congruency-Predictability interaction term that we pre-registered to test our hypothesis would capture any of these patterns, as the interaction term's coefficient would be in the same direction in all cases.

In our analysis, we found a pattern of effects counter to our pre-registered hypothesis (**Figure 3d**), with a Congruency-Predictability interaction in the opposite direction. An exploratory Bayesian analysis revealed that the observed interaction was 16.61 times more likely than our hypothesis. Based on these findings, we argue our results suggest that such a simplistic predictive coding account is, at least on its own, insufficient to explain the pattern of prediction effects observed in the N1 during a picture-word verification task.

This study was pre-registered at https://osf.io/jk3r4 and the reported methodology and planned analysis conform to that specified in the pre-registration, except for two changes: an accidental change to timing of stimuli, and a lowering of the EEG high-pass filter cut-off. We explain these changes in the relevant sections, and demonstrate in **Supplementary Materials F** that the change to the high-pass filter cut-off had minimal effect on the results and conclusions. All data and code are available at https://osf.io/389ce/.

Figure 3

*A comparison between the predicted (**a,b,c**) and observed (**d**) patterns of results.*

The predicted pattern of results was based on a predictive coding interpretation of the N1, according to which the magnitude of the N1 should be smaller for picture-congruent words relative to picture-incongruent words, and to a greater extent as Predictability increases. The observed pattern of results depicts the fixed effect predictions from the pre-registered linear mixed-effects model, with dashed lines depicting 95% bootstrapped prediction intervals (estimated from 5,000 bootstrap samples).

Method

The experiment included two separate tasks: The principal picture-word task was

preceded by a localiser task to account for between-participant variability in the N1's

timing and location. The details of stimulus selection and control as well as presentation

timing are provided in the following sections. For clarity, we first introduce the overall

Congruency-Predictability design of the picture-word task. In this task, pictures of single

objects are presented, followed by a noun, and participants decide whether the noun

corresponds to the object. The level of Predictability of the noun was determined from

norms of possible terms used to label a set of individual pictures (Brodeur et al., 2014).

The most frequent, modal name agreement varied across pictures. Thus, level of noun

Predictability was continuous and varied between 7% and 100%. The Congruency of the

noun was either congruent (matching the modal name of the picture) or incongruent (a

semantically unrelated noun matched across several lexical variables).

Materials: Picture-Word Task

A total of 400 words (200 per Congruency condition) were selected with LexOPS (Taylor et al., 2020), a package for the generation and control of lexical variables in the R programming language (R Core Team, 2021). Picture-congruent and -incongruent words were matched precisely in an item-wise manner on a range of relevant psycholinguistic variables, comprising word length, frequency, concreteness, OLD20, and character bigram probability. To ensure that picture-incongruent words were not inadvertent possible descriptors for images, we minimised the semantic relatedness between pairs of words. Additionally, counterbalanced sets of stimuli were matched on distributions in these variables using a measure of distributional similarity (Pastore & Calcagnì, 2019). A full description of the method by which stimuli were selected, and a full list of stimuli, is available in **Supplementary Materials A**.

Before embarking on the electrophysiological picture-word experiment, we first ran a proof-of-concept behavioural experiment using a different stimulus set generated from a very similar pipeline. We anticipated that increased Predictability should cause faster response time (RT) for congruent trials and have either no effect or a minimal effect on performance for incongruent trials. The results from this behavioural validation are presented in **Supplementary Materials B**. In short, we observed the pattern of results consistent with our expectations, with Predictability leading to faster RTs for congruent trials, but having almost no effect on incongruent trials.

Materials: Localiser Task

The precise location of the N1, and timing of its peak amplitude, is known to vary across studies and among participants. As such, we did not specify a common N1 electrode or timepoint shared among all participants before data collection. Instead, we employed a localiser task to identify, within an appropriate region and time period of interest, the electrode and timepoint at which each participant's maximal sensitivity to orthography emerges (i.e., more extreme amplitudes for words than false-font stimuli).

This data could then be used to extract N1 amplitudes in the picture-word task, while

accounting for variability among participants in timing and topography of orthographic

processes.

For the localiser task, three categories of stimuli were presented for 100 trials

each (**Figure 4**). These consisted of matched triplets of words (Courier New font),

false-font strings (BACS2serif font; Vidal et al., 2017), and phase-shuffled words. The

comparison between words and false-font strings is a standard measure of N1 sensitivity

to orthography, with previous evidence suggesting a more robust difference than exists

between nonwords and words (Brem et al., 2018; Maurer, Brandeis, & McCandliss,

2005; Pleisch et al., 2019). However, phase-shuffled words were employed as an

alternative comparison for exploratory analyses, with equal spatial-frequency amplitude

and permuted spatial-frequency phase. Similar phase-shuffled word stimuli have shown

robust differences to word forms in fMRI investigations of vOT activity (Rauschecker

et al., 2012; Rodrigues et al., 2019; White et al., 2019; Yeatman et al., 2013).

The word stimuli were selected to be widely known by participants (>90%

proportion known), and to be representative on a range of psycholinguistic variables

including length, frequency, part of speech, and prevalence. A full description of how the

Localiser Stimuli were selected, and a list of all word stimuli, is presented in

Supplementary Materials C.

Participants

The sample size of 68 participants was decided via a power analysis using

Monte-Carlo simulations of a realistic effect size (**Supplementary Materials D**). This

revealed that with ≥68 participants we could expect >80% statistical power in the long

run (**Figure 5**). All 68 participants (40 female, 27 male, 1 non-binary) were monolingual

native English speakers. Participants were randomly allocated into one of the four

combinations of stimulus set (Set 1, Set 2) and response group (i.e., the left-right

mapping of the two response buttons for affirmative and negative responses), such that

Figure 4

Ten example stimuli for each stimulus type in the localiser task.

Each row represents a matched triplet of word, false-font string, and phase-shuffled word stimuli. The phase-shuffled word images were generated uniquely for each trial.

each combination of stimulus set and response group comprised 17 participants. No

participants reported diagnosis of any reading disorder. Ages ranged from 18 to 37 years

(M=22.69, SD=4.9), and all participants reported having normal or corrected-to-normal

vision. Participants' handedness was assessed via the revised short form of the

Edinburgh Handedness Inventory (Veale, 2014), with participants only permitted to take

part if they scored a laterality quotient of +40 indicating right handedness. Exclusion

criteria for participants were determined prior to data collection as follows: (1) if 10 or

more channels showed an offset more extreme than ±25 mV (as measured on the

BioSemi acquisition software, ActiView), or (2) if more than 5% of the trials were lost due

to technical issues with the EEG system. As no participants satisfied these criteria, no

participants were excluded after data collection. Data collection was approved by the

Ethics Committee of the University of Glasgow College of Science and Engineering

(application number: 300200117), and all participants provided informed consent.

Procedure

Stimuli were presented on a VPixx Technologies VIEWPixx screen (resolution

1920×1080 pixels, diagonal length 23", model VPX-VPX-2004A). Participants completed

Figure 5

Estimated relationship between number of participants and statistical power.

Black points and error bars depict point estimates ±99% Binomial confidence intervals, each from 500 simulations. As 500 simulations provides a noisy estimate, we interpolated the relationship between N and power via a loglinear, logit-link Binomial model. The *orange* region depicts the 99% confidence intervals of this loglinear model.

the experiment on a chin rest positioned 48 cm from the centre of the screen. Stimuli were presented on a grey background equal to 50% of the maximum intensity in each colour channel, roughly 12.3 cd/m^2. The experiment was written using the Python library PsychoPy (Peirce, 2007), and all code and materials are available in the repository associated with the study. All stimuli were presented centrally (horizontally and vertically). All trials in both tasks were presented in a pseudo-randomised order, such that no more than five consecutive trials required the same response from the participant. Trials were randomised across blocks, with the exception of the practice block, for which trials were randomised within the one block.

A mistake in the lab setup, which we discovered after data collection, meant that the display screen was running at 120 Hz rather than an expected 60 Hz. As we were controlling stimulus presentation by screen refreshes, this meant that all our stimuli were presented for half the expected durations. For this reason, the veridical stimulus durations described here differ from those described in the pre-registration.

Participants started with the localiser task, in the form of a lexical decision task (**Figure 6a**). The localiser task began with 30 practice trials, and was then followed by

300 trials split into 5 blocks of 60 trials. Each trial began with the bullseye fixation target

recommended by Thaler et al. (2013) (outer and inner circle diameters were 0.6° and

0.2° of visual angle), presented for 150 ms. This was followed by a jittered interval of

between 150 and 650 ms, during which the screen was blank. The stimulus (word,

false-font string, or phase-shuffled word image) was then presented at a height of 1.5°

(width of 1.07° for one character). Words and false-font strings were presented in white

(80 cd/m^2), in the respective fonts of non-proportional Courier New and BACS2serif font.

The stimulus was visible for 250 ms, after which the font colour changed to green to

signal participants to respond. Participants were requested to respond once after the

stimulus changed colour, quickly and accurately, to indicate whether the stimulus they

saw in each trial was either a word or not a word. The stimulus remained on screen until

the participant responded. Responses were given with the right and left control ('Ctrl')

keys of a QWERTY keyboard, with the mapping of affirmative and negative responses

counterbalanced across participants. After the participant had responded, there was a

delay of around 100 ms (variable as data was saved to disk during this interval), and

then the next trial began.

After the localiser task, participants completed the picture-word task (**Figure 6b**),

comprising an initial practice block of 20 trials, followed by 200 trials split into 5 blocks of

40 trials. As in the localiser task, each trial in the picture-word task began with the

bullseye fixation point, presented for 150 ms, after which there was a blank screen for a

jittered interval of between 150 and 650 ms. An image was then presented for 1000 ms,

at a size of 10x10°. The bullseye fixation point was then presented again for 150 ms,

followed by another interval jittered between 150 and 650 ms. The word was then

presented in white Courier New font, at a height of 1.5° (width 1.07° for one character).

After 500 ms, the word turned green, and participants could provide their response to

indicate whether the word described the image they saw. The word remained on screen

until the participant responded. As in the localiser task, responses were given with the

Figure 6

*Trial structure of the (**a**) localiser task and (**b**) picture-word task.*

This figure is illustrative and the sizes are not to scale; in the experiment, images were in fact presented at a much larger scale than words.

right and left control ('Ctrl') keys of a QWERTY keyboard, with the mapping of affirmative

and negative responses counterbalanced across participants, but kept consistent within

participants across the two tasks. After participants had responded, there was a delay of

around 100 ms (again, variable as data was saved to disk during this interval), and then

the next trial began. There was no deadline for participants to respond. The instructions

given to participants for the picture-word task are presented in **Supplementary**

Materials E.

The first blocks of both tasks consisted of practice trials with 10 exemplars for

each stimulus type (word or false-font string or phase-shifted image, and congruent or

incongruent noun for the localiser and picture-word tasks, respectively), during which

participants were additionally given immediate feedback on their accuracy for each trial.

These practice trials were followed by green text reading "CORRECT!" if the participant

responded correctly, or else by red text reading "INCORRECT!", presented in Courier

New font with a height of 1.5°, for 1000 ms. Participants had self-paced breaks between

blocks for each task. Before the practice trials and at the start of every experimental

block, participants were presented with instructions for the task (available in

Supplementary Materials E), summarising what would occur in each trial, and

specifying that they should respond as quickly and accurately as possible once the

stimulus turned green. These instructions also specified which keys participants should

press to indicate their decision. After each experimental block, including the practice

trials, participants were presented with their average accuracy and median response

time. After the practice trials, participants were additionally given the option to run the

practice trials again. In the experimental blocks, no trial-level feedback was provided.

Recording

EEG data were recorded using a 64-channel BioSemi ActiveTwo system,

sampling at 512 Hz, with an online anti-aliasing low-pass filter cutoff at one fifth of the

sample rate (i.e., 102.4 Hz). Electrodes were positioned in the standard 10-20 system

locations. Four electro-oculography (EOG) electrodes were placed to record eye

movements and blinks: 2 were placed to the sides of eyes (on the right and left outer

canthi), and 2 below the eyes (on the infraorbital foramen). Electrode offset was kept

stable and low through the recording, within ±25 mV, as measured by the BioSemi

ActiView EEG acquisition tool. Electrodes whose activity exceeded this threshold were

recorded but were removed (and interpolated) in data preprocessing.

Preprocessing

The following section details the procedure applied to EEG data from each

individual session, with the same pipeline being applied to both the localisation task and

picture-word task unless otherwise specified. EEG preprocessing was achieved using

functions from the EEGLAB (Delorme & Makeig, 2004) toolbox for MATLAB (MATLAB,

2022) or OCTAVE (Eaton et al., 2020). For both tasks, trials were excluded if responded

to incorrectly (total of N_{trials}=368, or .02%, in localiser task, and N_{trials}=226, or .02%, in

picture-word). Further trials were excluded if responded to later than 1500 ms after the

word (or nonword) changed colour (total of N_{trials}=41, or .002%, in localiser task,

N_{trials}=42, or .003%, in picture-word).

Channels recorded as having offsets ±25 mV during data acquisition were

removed from the data (in both tasks, 56 channels, or 1.27%, were removed across all

participants), with their activity to be later interpolated. In addition, we found that even

when not identified as problematic during recording, the channel PO4 was consistently

noisy, and so we interpolated this channel for all participants. PO4 was not part of our

left occipitotemporal region of interest, but was interpolated for exploratory analyses of

the whole scalp, and to avoid affecting other preprocessing steps. Interpolating electrode

PO4 was not a preregistered step. However, we note that this change did not alter the

direction of any results, rather, only reducing the size of effects. After interpolation, the

EEG data were then re-referenced to the average activity across all electrodes and

filtered with a 4th order Butterworth filter between .1 and 40 Hz. To counteract the

distortion in signals' timing (phase) that is inherent to causal filters, the filter was applied

in both directions (i.e., two-pass), with the MATLAB function *filtfilt()*. In our

pre-registration, we specified that we would apply a Butterworth filter with a bandpass of

.5-40 Hz. However, after the pre-registration, we considered that, consistent with

research into the effects of high-pass filters (Rousselet, 2012; Tanner et al., 2015;

VanRullen, 2011), this could produce artefactually early effects. As a result, we lowered

the high-pass filter to a less problematic .1 Hz. For comparison, demonstrating that our

change to the pre-registered pipeline had minimal effect on the results or our

conclusions, the results using the original filter are presented in **Supplementary**

Materials F.

Segments of data outside of experimental blocks (i.e., in break periods) were

identified and removed so they did not impact the independent components analysis

(ICA) applied later in the pipeline. Blocks were identified as beginning 500 ms before

stimulus presentation in the first trial of each block, ending 500 ms after the end of the last trial's epoch. To reduce the impact of occasional non-stationary artefacts with high amplitude (such as infrequent muscle movements), artefact subspace reconstruction (ASR; Chang et al., 2020) was used with a standard deviation cutoff of 20 to remove non-stationary artefacts. Following this, an ICA was run on the data to identify more stationary artefacts. The ICA was run using the FastICA algorithm (Hyvärinen & Oja, 1997), with a recorded random seed for reproducibility. The ICA was run on a copy of the data with channel offsets removed to allow for better sensitivity to electro-oculogram (EOG) artefacts (Groppe et al., 2009). The ICLabel classifier (Pion-Tonachini et al., 2019) was used to automatically identify artefacts which were eye- or muscle-related. Components classified by ICLabel as eye-related or muscle-related with a probability of $\geq$85% were removed from the data. Following eye movement artefact removal, activity from channels which were removed was interpolated via spherical splines (Localiser: M=1.14 per participant, SD=1.58; Picture-Word: M=1.68, SD=2.03), as implemented in EEGLAB. Trials were then epoched and baseline-corrected to the 200 ms preceding stimulus presentation. For the localiser task, stimulus presentation refers to the time point at which words, false-font strings, or phase-shuffled images were presented; in the picture-word task, stimulus presentation refers to the target word.

For the planned analysis, we pre-registered an approach to maximise sensitivity to effects of Congruency and Predictability on the N1. To encompass the typical topography and timing of the posterior left-lateralised N1, we selected eight occipitotemporal electrodes (**Figure 7**; electrodes O1, PO3, PO7, P5, P7, P9, CP5, and TP7) and a 120-200 ms window. In contrast to some previous studies whose N1 windows extended beyond 200 ms, we set 200 ms as an upper bound for the possible maximal timepoint in the main analysis, to ensure effects were indeed restricted to the N1, and not later components like the N400. For each participant, we identified the electrode that showed maximal sensitivity to orthographic information in the N1 during

the localisation task. Specifically, each participant's "maximal electrode" (within the

region of interest and selected time window) was the one which showed the largest

mean amplitude difference, in the expected direction, across all localiser trials between

word and false-font string stimuli. The expected direction was a more negative-going N1

for words than for false-font strings, a pattern based on previous findings (Appelbaum

et al., 2009; Bentin et al., 1999; Eberhard-Moscicka et al., 2016; Pleisch et al., 2019;

Zhao et al., 2014). Each participant's "maximal timepoint" was the timepoint at which the

maximal electrode showed the greatest sensitivity to the word-versus-false-font

difference in the expected direction. Each participant's maximal electrode and maximal

timepoint were then used to extract their trial-level N1 amplitudes from the picture-word

task. To reduce the influence of noise on trial-level data, the trial-level N1 amplitudes in

the picture-word task were calculated as the maximal electrode's mean amplitude across

3 timepoints: the participant's maximal timepoint, and the timepoints immediately

preceding and following it. At the recorded sample rate of 512 Hz, this is equivalent to a

window of 5.85 ms (i.e., 1/512*3) centred on the maximal timepoint.

Figure 7
The left-lateralised occipitotemporal region of interest selected for the N1 (highlighted in red).

Planned Analysis

Our planned analysis tested the pre-registered hypothesis of a

Congruency-Predictability interaction in which N1 amplitudes are reduced (i.e., less

negative going) for picture-congruent trials than for picture-incongruent trials, and in

which this difference is greatest at the highest levels of predictability, and smallest at the

lowest levels of predictability. This was based on the notion that the N1 indexes

prediction error in biasing contexts.

The trial-level N1 amplitudes from the picture-word task were modelled using a

linear mixed-effects model fit with the R package *lme4* (Bates et al., 2015), estimating

the maximal random effects structure justified by the experiment's design (Barr et al.,

2013) as detailed in the section on the power analysis. The model was fit using the

bobyqa optimiser (Powell, 2009). In *lme4* syntax, the formula for the mixed-effect model

was specified as:

```
587 amplitude ~ 1 + congruency * predictability +
588     (1 + congruency * predictability | participant_id) +
589     (1 + congruency | image_id) +
590     (1 | word_id)
591
```

In this formula, *amplitude* is the trial-level N1 amplitude in microvolts, while

congruency is a deviation-coded categorical variable indicating whether a given trial's

word was picture-congruent or -incongruent, and *predictability* refers to the proportion of

name agreement in the BOSS norms, normalised between 0 and 1. A consequence of

this coding method is that the model's intercept reflects the predicted amplitude at the

lowest level of Predictability, averaged across both levels of Congruency, while the

slopes' coefficients are standardised and directly comparable in their magnitude. The

variables of *participant_id*, *image_id*, and *word_id*, in the formula, identify each trial's

participant, image, and word, respectively.

Results

602   The planned, pre-registered analysis examined whether the hypothesised effect

603 of a Predictability-dependent reduction of N1 amplitudes for picture-congruent words

604 was observed at the electrode/timepoint in which each participant showed maximal

605 sensitivity to orthography. We then present exploratory analyses, which respectively

examine the Bayesian probability that our data are consistent with the hypothesis, and delineate the time-course of the Congruency-Predictability interaction. We also conducted further exploratory analyses, which we report in the supplementary materials, examining behavioural results in the picture-word study (**Supplementary Materials G**), and EEG and behavioural results from the localiser task (**Supplementary Materials H**)

Planned Analysis

The fixed effect relationships estimated in the planned analysis are presented in **Figure 8**. The model intercept, reflecting the average N1 amplitude at the lowest level of Predictability, was estimated to be β=-3.4 µV (*SE*=.48). The fixed effect of Congruency from this model was estimated as β=-.12 µV (*SE*=.34), which captures that, at the lowest level of Predictability (7%), N1 components for picture-congruent and -incongruent words were estimated to be quite similar (.12 µV difference). The main effect of Predictability was estimated as β=.25 µV (*SE*=.27), meaning that N1 amplitudes, averaged across congruent and incongruent conditions, were .25 µV less negative-going at the highest level (100%) than at the lowest level of Predictability (7%). The effect of interest, the interaction between Congruency and Predictability, was in the opposite direction from that hypothesised, estimated as β=-.79 µV (*SE*=.52). As our hypothesis was directional, with a prediction in the opposite direction, we interpret these results as a failure to find evidence in favour of the hypothesis.

To describe the estimated interaction, for picture-incongruent words, the effect of Predictability was estimated to be β=.63 µV (*SE*=.36), while for picture-congruent words, the effect of Predictability was estimated to be β=-.15 µV (*SE*=.4). As such, the slopes for the effect of Predictability in both Congruency conditions were of different magnitudes, and were both in directions inconsistent with our predictive coding hypothesis.

For comparison, we also analysed the data altering aspects of our planned analysis method: first using the maximal electrodes that would be identified from the comparison between words and phase-shuffled words, and second using averages

Figure 8

Fixed effect predictions from the planned analysis of the picture-word task.

Picture–Word Congruency — Congruent — Incongruent

(**a**) Model-derived fixed-effect predictions, visualised over results from all trials (individual points). (**b**) Fixed-effect predictions visualised alone for visibility, with dashed lines depicting the bounds of 95% bootstrapped prediction intervals (estimated from 5,000 samples), where bootstrapped predictions were generated using the *bootMer()* function of *lme4*. For feasibility, bootstrapped predictions were generated from a version of the model that lacked random slopes.

within the occipitotemporal region of interest (**Supplementary Materials I**). These

exploratory analyses revealed very similar patterns of effects, with estimates of the

Congruency-Predictability interaction similarly inconsistent with our hypothesis, which we

derived from a simple predictive coding account of the N1.

Exploratory Bayesian Analysis

        We observed a Congruency-Predictability interaction in the opposite direction

(i.e., negative) to what we expected under our predictive coding hypothesis (i.e.,

positive). To explicitly quantify the probability of our predictive coding hypothesis, we fit a

Bayesian implementation of the model described in the planned analysis, in STAN

(STAN Development Team, 2023) via *brms* (Bürkner, 2017). This model was fit to the

same data, and estimated the same hierarchical formula, with the same Gaussian link

function as that described above, but was specified with weakly informative priors for the

fixed effects. Specifically, the prior for the fixed effect intercept was specified as a normal

distribution of mean -5, and *SD* 10, while all fixed effect slopes' priors were specified as

normal distributions centred on 0, with *SD*s of 5. Covariance matrices were assigned flat

priors, and default priors for brms were used for random effect *SD*s and the sigma

parameter of the normal distribution. The model was fit with 5 chains and 5000 iterations

per chain (split equally between warmup and sampling) such that there were a total of

12,500 posterior samples. Consistent with the linear mixed-effects model we fit via *lme4*,

this analysis revealed a median posterior estimate for the Congruency-Predictability

interaction of β=-.79 µV (89% highest density interval = [-1.59, .013]; **Figure 9**). We

calculated, given this posterior distribution, that the Congruency-Predictability interaction

is 16.61 times more likely to be less than 0, than it is to be greater than zero (that is,

BF_{01}), which we consider to be strong evidence against our hypothesis.

Figure 9
Posterior density for the Congruency-Predictability interaction.

The region of the posterior distribution consistent with the predictive coding hypothesis (where β>0) is highlighted in *red*. The point and horizontal line below the density plot depict respectively the median estimate and 89% highest density interval of the posterior distribution.

We considered that our use of a localiser task may have been an inappropriate

approach for identifying electrodes sensitive to orthographic information. Indeed, our

pre-registered approach for identifying maximal electrodes specified the direction of the

difference that should be used, with more negative N1s for words than for false-font

strings. However, exploratory ERP analyses of the localiser task showed that

left-lateralised occipitotemporal electrodes showed a more negative N1 peak overall for

false-font strings than for words (**Supplementary Materials H**). Our approach may

therefore have systematically selected electrodes that are not representative of the ROI.

As a result, we re-ran the Bayesian analysis as described above, but modelling average

amplitudes from all electrodes in the left occipitotemporal ROI (**Supplementary**

Materials I). This revealed even stronger evidence against the hypothesis, with a

Congruency-Predictability interaction for the average amplitude in the ROI of β=-1.03 µV

(89% highest density interval = [-1.52, -.058], estimated to be 2082 times more likely to

be less than 0, than it is to be greater than zero.

Exploratory Time-Course Analysis

To examine the time-course of effects, we fit separate linear mixed-effects models

to sample level data for the left-lateralised occipitotemporal region of interest, with

variables coded as described for the planned analysis. For feasibility, data were

down-sampled to 256 Hz, and the models did not estimate random slopes. To account

for variability between electrodes, and for per-participant differences in topography,

random intercepts were estimated for each combination of participant and electrode. In

lme4 syntax, the model formula was specified as follows:

```
amplitude ~ 1 + congruency * predictability +
    (1 | participant_id) +
    (1 | participant_id:electrode_id) +
    (1 | image_id) +
    (1 | word_id)

```

The results (**Figure 10**) reproduced findings from the planned analysis, with

increases in Predictability associated with more negative (larger) N1 amplitudes for

picture-congruent words, and with less negative (smaller) N1 amplitudes for

picture-incongruent words. The Congruency-Predictability interaction of interest

remained negative, and thus in the opposite direction to that hypothesised, throughout

the N1.

Figure 10

Time-course of fixed effects from the sample-level analysis of the left-lateralised occipitotemporal region of interest.

(**a**) Time-course of fixed effects estimates, with blue-shaded regions depicting 95% confidence intervals. The model intercept (reflecting average amplitudes at the lowest level of Predictability) is depicted as a grey line on each panel to provide a reference for timing and magnitude of effects. (**b**) Fixed-effect predictions for picture-congruent and -incongruent words at levels of Predictability from 10 to 100%, in steps of 10%. (**c**) Same data as (**b**), but split by Predictability rather than Congruency. The rapid change in amplitude after 650 ms was likely elicited by the stimulus colour change at 500 ms, as shown more clearly in **Figure 12**.

The sample-level analysis additionally suggested that the difference was largest

in the N1's offset period (succeeding the peak). A later Congruency-Predictability

interaction was also observed, peaking at around 400 ms (possibly resulting from effects

in the N400 component) in the opposite direction to that observed for the N1's offset. To

better understand the time-course of the Congruency-Predictability interaction, we

examined the time-course of the effect of Predictability for picture-congruent and

-incongruent words separately (i.e., simple effects; **Figure 11**). This showed more clearly

that Predictability reduced amplitudes in the N1 for picture-incongruent words, but

increased amplitudes for picture-congruent words. This difference peaked around 225

ms, but reversed in direction after 300 ms. It is of note that the peak of the observed

effects in the N1 was later than originally anticipated (the planned analysis was limited to

$\leq$200 ms). Nevertheless, the model intercept (**Figure 10a**) clearly shows that these

effects peaked during the N1's offset period.

Figure 11
Time-course of the effect of Predictability for picture-congruent and -incongruent words.

Central lines depict effect estimates, derived from sample-level models that were coded such that the model intercept lay at the respective levels of picture-word Congruency. Estimates reflect occipitotemporal ERPs for words at the maximum level of Predictability, minus those at the minimum level of Predictability. Shaded areas depict 95% confidence intervals of model estimates.

Exploratory Scalp-Wide Analysis

Finally, we examined how the full topography of effects changed over time

(**Figure 12**). Specifically, we fit a linear mixed-effects model to data from each time-point

and electrode separately, with variables coded as described in the section on the

time-course analysis of the region of interest. As in that analysis, we again excluded

random slopes for feasibility:

```
amplitude ~ 1 + congruency * predictability +
    (1 | participant_id) +
    (1 | image_id) +
    (1 | word_id)
```

Results confirmed that the Congruency-Predictability interaction at left

occipitotemporal sites was the earliest fixed effect to emerge, and that the effect was

small relative to that observed at later time points. It additionally showed that the switch

in direction of the Predictability-Congruency interaction shown to peak at around 400 ms

in **Figure 11** exhibits a frontocentral topography. This effect was sustained until around

475 ms. Interestingly, if this effect captures changes in an N400 component, then the

direction of the N400 modulation was, as was the case for the effect on the N1, arguably

inconsistent with a simple predictive coding account. This is because the direction of

effects suggests that prediction-congruent words elicited the most negative-going N400

amplitudes at the lowest level of predictability. As predictability increased, N400

amplitudes elicited by picture-congruent words became less extreme, increasingly

approaching the N400 amplitudes elicited by picture-incongruent words (**Supplementary**

Materials J). The modulation observed in the opposite direction at occipitotemporal sites

in **Figure 10** at around 400 ms likely results from the use of average reference.

The scalp-wide analysis also revealed that the main effect of picture-word

Congruency shown in **Figure 10** indeed peaks at around 400 ms, with a centroparietal

topography. Interpreting this as a modulation of the N400 would mean that, at the lowest

Figure 12

Time-course of scalp-wide fixed-effects estimates.

The first dashed vertical line (0 ms) indicates stimulus (word) onset. The second dashed vertical line (500 ms) indicates the time-point at which the word changed colour to green. Topographic plots of fixed effects are highlighted at key time-points. Model intercepts (reflecting average amplitudes at the lowest level of Predictability) are depicted as grey lines on each panel to provide a reference for timing and magnitude of effects.

level of predictability, picture-congruent words elicited more negative-going N400s

overall than picture-incongruent words did.

Finally, this analysis covered an extended period of time, which revealed a clear

negative-going posterior component at around 650 ms. This component peaked around

150 ms after the stimulus changed colour to indicate that participants could respond.

Given the timing and topography of this component, this is likely to reflect an N1

response to the colour change.

739   **Discussion**

In the present study, we tested whether a simple predictive coding account could

explain online prediction effects on the amplitude of N1 ERP components elicited by

words in biasing contexts. We biased expectations for upcoming words via images of

varying predictability. Based on a predictive coding framework, we hypothesised that

there would be an interaction between picture-word Predictability and Congruency in

which N1 amplitude scales with prediction error. Planned analyses failed to find

evidence for this hypothesis, and exploratory analyses revealed, despite strong evidence

for prediction effects in the N1, that the direction of the interaction was opposite to that

expected under the hypothesis. Specifically, increases in Predictability were associated

with greater-amplitude N1s for picture-congruent words, and smaller-amplitude N1s for

picture-incongruent words. On this basis, we conclude that a simple predictive coding

explanation of the N1 cannot explain predictability effects observed in the picture-word

verification task used here.

In recent years, predictive coding models have been increasingly applied to

explain neural phenomena observed during language processing. This includes

predictive coding perspectives on the N1 specifically (e.g., Gagl et al., 2020; Huang

et al., 2022; Zhao et al., 2019), or its likely generator, vOT (Price & Devlin, 2011), and

other areas of language processing. For example, consider the well-researched N400

ERP component, generally recognised since its initial identification as capturing activity

related to semantic processes (Kutas & Federmeier, 2011; Kutas & Hillyard, 1980). The

N400 shows sensitivity to word- and sentence-level surprise or predictability

(Delaney-Busch et al., 2019; Lau et al., 2013; Lindborg et al., 2023; Mantegna et al.,

2019; Van Petten & Kutas, 1990), in a manner that may be consistent with predictive

coding (Bornkessel-Schlesewsky & Schlesewsky, 2019; Eddine et al., 2023; Rabovsky &

McRae, 2014). Similar interpretations have been made of other signals, as capturing

prediction errors for phonological, semantic, or syntactic representations (Fitz & Chang,

2019; Gagnepain et al., 2012; Van Petten & Luka, 2012; Ylinen et al., 2016, 2017).

Indeed, emerging evidence is beginning to support the broader contention that

naturalistic language comprehension utilises a predictive coding hierarchy spanning the

language network (Caucheteux et al., 2023; Schuster et al., 2021; Shain et al., 2020;

L. Wang et al., 2023). In this way, evidence for predictive coding in language reflects the

growing, although not definitive, empirical evidence for predictive coding models in

perception more generally (Clark, 2013; Heilbron & Chait, 2018; Hodson et al., 2024;

Walsh et al., 2020).

We do not believe our findings refute the existence of predictive coding

mechanisms during the N1. This is informed by our review of the literature outlined in the

Introduction, in which we found evidence broadly consistent with a predictive coding

interpretation of the N1. Instead, we argue that a simple predictive coding account of the

N1, in which the component's amplitude straightforwardly indexes prediction error in a

manner dependent on prediction certainty, is insufficient to explain the pattern of effects

we observed in the picture-word verification task we used here. For a predictive coding

model to better account for these data, it would require elaboration. One feature that

may be relevant is the nature of the task. We elected to use a picture-word verification

task as it encourages explicit prediction of word forms from non-linguistic contexts.

However, this task paradigm may alter predictive processing of word forms in two key

ways. First, participants will have soon learned that the observed word form only

matches its preceding image 50% of the time, which could have interacted with the effect of Predictability (prediction certainty) in unexpected ways. Second, the requirement for explicit verification of prediction congruency may have encouraged artificial processing strategies that are not representative of naturalistic word recognition and reading processes. To better understand whether and how such factors influence any possible predictive coding effects on the N1, we could manipulate prediction error magnitude and precision while the participant's task instructions do not explicitly require processing of the cue. For instance, we could use a picture-word priming design (Sperber et al., 1979; Vanderwart, 1984), presenting picture-word pairs, as in the current study, but ask participants to respond with lexical decisions. Here, prediction error magnitude could be operationalised as the orthographic distance between the string (whether word or non-word), and precision as the predictability of a word given its picture. We believe that such an approach could provide insight into whether, and which, features of the paradigm we used could have resulted in the unexpected pattern of results. Finally, it is possible that dynamics of predictive processing were influenced by the slow presentation rate employed in the present study, relative to more naturalistic reading paradigms. Indeed, previous research has highlighted the importance of presentation rate in prediction effects during reading (e.g., Dambacher et al., 2012), and recent findings have shown that unpredictability in stimulus presentation timing (e.g., with jittered inter-stimulus intervals) may interfere with predictive processes, as indexed by the mismatch negativity component (Tsogli et al., 2022). This explanation of our results could be tested by study designs examining how the congruency-predictability interaction varies over stimulus onset asynchronies of different durations. In sum, while predictive coding mechanisms may ultimately underlie the pattern of effects we observed, the simple account we have tested requires elaboration, informed by insights from other paradigms, for it to explain why our current pattern of effects is opposite to that expected.

Our study is not the first to identify patterns in evoked responses that seemingly

run counter to a simple predictive coding model (e.g., Bowman et al., 2013; Eisenhauer

et al., 2022; Mangun & Hillyard, 1991; Vidal-Gran et al., 2020). One suggested

elaboration to a simple predictive coding model that could allow expected stimuli to elicit

greater evoked responses than unexpected stimuli supposes that, in such cases,

expected stimuli may benefit from greater precision than is allotted to deviant stimuli

(Bowman et al., 2023; Heilbron & Chait, 2018; Kok et al., 2012). In our experiment,

matched picture-congruent and -incongruent words followed the same pictures, such

that predictability, which we used as a measure of top-down prediction precision, should

have been identical prior to word presentation. However, if top-down effects can

penetrate early stages of visual processing that precede the N1, it is conceivable that

processing after word presentation, but prior to the N1, could have up-weighted the

precision of information in picture-congruent words' representations, resulting in the

observed pattern of effects. In simulations, Bowman et al. (2023) recently demonstrated

that precision-modulated predictive coding models can indeed produce "contra-vanilla"

patterns in prediction errors if prediction-congruent stimuli benefit from higher precision,

but that this should be expected to affect the evoked response non-linearly. Specifically,

the latency of the evoked response should be shorter for the prediction-congruent

stimulus. Our findings did indeed reveal a latency difference in the N1 offset period,

between congruent and incongruent words at the highest level of predictability (**Figure**

10), but the direction of this difference was opposite to that predicted by Bowman et al.

(2023), with a shorter offset period for picture-incongruent words. As such, it is unclear

how an elaboration based on differential precision between picture-congruent and

-incongruent words may relate to our findings.

We acknowledge the possibility that the insufficiency of predictive coding

accounts to explain the data we observed may reflect a more fundamental shortcoming.

Indeed, an enduring criticism of predictive coding models is that some evidence for them

may also be explained by alternative models (de Lange et al., 2018; Hodson et al.,

2024). To speculate, predictive coding models may account for activity in the N1 in

previously tested paradigms without accurately describing the underlying neural

processes. For instance, Luthra et al. (2021) showed that, in spoken word recognition,

interactive activation models may provide an alternative account of the ERP amplitude

reduction observed in response to prediction violations, without invoking key features of

predictive coding models. Indeed, effects indicative of predictive processing may emerge

in a system that that lacks any representations of, or mechanisms implementing,

predictions or prediction errors, instead only implementing "pattern completion"

(Falandays et al., 2021). It is tentatively possible that the picture-word verification

paradigm we applied here may be a scenario that employs the same neurocognitive

processes in the N1 as those employed in other paradigms, but elicits cognitive

dynamics whose corresponding neural activity reveals differences from a predictive

coding model. It is possible that processing indexed by the N1 can only be explained by

a model distinct from the predictive coding framework, even though predictive coding

models may correlate with patterns of activity seen in most paradigms. Justifying the

development of such a model, distinct from predictive coding, would require much more

evidence for the shortcomings of a predictive coding account, and we do not believe our

study provides the insights necessary to speculate on the form such a model could take.

Such further insights may be provided by an approach that examines patterns in

the representational content of neural activity, rather than univariate patterns of overall

activity. Such an approach has been exploited previously as a way of comparing

prediction error models, in which neural signals represent unexplained content, with

sharpening models of language processing, in which neural signals contain sharper

representations of predicted content (Desimone, 1996; Grill-Spector et al., 2006). While

these models can account for similar patterns in overall neural activity, they predict

dissociable patterns in corresponding representational content (Blank & Davis, 2016).

For instance, Blank and Davis (2016) employed a Congruency (matching, neutral) ×

Precision (signal quality: 4 or 12 vocoder channels) design in an fMRI experiment on

speech perception. Representational similarity analyses of fMRI activity from the

posterior superior temporal sulcus showed a pattern consistent with the representational

content expected under a prediction error account, and not a sharpening account.

Analyses of EEG signals in a similar paradigm by Sohoglu and Davis (2020) also show

evidence for patterns of representational enhancement and suppression that match a

prediction error account, from 100 ms after stimulus presentation. Further evidence for

prediction error accounts of early speech perception processes is seen in fMRI and MEG

analyses of two-syllable words, where precision is quantified as the predictability of

syllable two, given syllable one (Sohoglu et al., 2023). In contrast, however, an MEG

study on the representation of lexical-semantic information during *visual* word

recognition found evidence more consistent with a sharpening account (Eisenhauer

et al., 2022). Although their use was motivated by a need to disentangle two

explanations of evoked-response patterns that are both consistent with predictive

coding, we believe that such analyses, focusing on representational content, may also

provide an avenue to further investigate the pattern we observed that was seemingly

inconsistent with predictive coding. This could reveal whether the N1's modulation is

accompanied by the representation of more or less stimulus-relevant information, and

may more clearly point to the underlying mechanisms.

Representational content is also of particular importance when testing predictive

coding accounts because it determines the depth in the hierarchy to which top-down

predictions can be conveyed and effectively implemented. This is because in a

hierarchical model of predictive coding, where levels of the hierarchy utilise different

representational formats, the interaction between ascending input and descending

predictions must involve some mapping of higher-level onto lower-level representations.

For instance, if semantic context can influence processing that is closer to sensory input

and indexed by early ERP components (e.g., Enge et al., 2023; Getz & Toscano, 2019;

Segalowitz & Zheng, 2009), then higher-level semantic information must be translated

into predictions of upcoming lower-level sensory signals. In the case of our study's

modulation of the N1, if the N1 is implicated in visual-orthographic processing (Bentin

et al., 1999; Brem et al., 2018; Ling et al., 2019; Maurer, Brandeis, & McCandliss, 2005),

then predictions of upcoming words must be translated into a visual-orthographic code.

Such a mapping could be expected to be very computationally lossy; predictions for

visual-orthographic features of a single word should be expected to also confer

facilitation for words that are orthographically similar, yet picture-incongruent (Kim & Lai,

2012). In contrast, a later ERP more directly implicated in semantic processing, like the

N400, may be expected to be less limited by such mappings.

From one perspective, mapping of predictions to lower-level representations may

be considered a requisite for a phenomenon to be considered top-down modulation

(Rauss et al., 2011). This relates to a long-standing debate on whether prediction effects

at the lexical level of language processing necessitate top-down input informed by

higher-level semantic processes, or could instead result from perhaps more

parsimonious intralexical effects (Fodor, 1983; Forster, 1979). A similar argument could

be made that context effects on the N1 could be interpreted as intra-*orthographic*,

resulting from local interactions in a possible *orthographic module*. As an example, the

orthographic features of the word form *fish* may preactivate features of the word form

chips simply through learned co-occurrence rather than top-down modulation, entirely

within an orthographic processing module that possesses nothing approaching a

semantic representation. Such facilitation could be implemented via an extension to

classic interactive activation models (e.g., McClelland & Rumelhart, 1981) in which there

are excitatory lateral connections between word-level units whose strength is determined

by co-occurrence frequency. We consider this point to highlight an advantage of

paradigms such as ours, that use non-linguistic contexts (e.g., task instructions, images,

etc.) to cue upcoming words and word forms. Effects of context that map across

representations in this way necessitate transfer of information across levels of the processing hierarchy, and may thus be considered stronger evidence for an influence of top-down predictions.

An aspect of the predictive coding account that our design did not fully test also relates to this idea of representational mapping. We dichotomised the variable of congruency (prediction error magnitude), with orthographic Levenshtein distance maximised between picture-congruent and -incongruent word forms. However, prediction error magnitude should also be expected to vary continuously, from unpredicted word forms that are less to more orthographically similar to the predicted word form. This is comparable to Gagl et al.'s (2020) use of a pixel distance metric to calculate the continuous distance between a presented word form and a context-neutral prior. Such an approach could be applied to biasing contexts by instead calculating the orthographic distance between a presented word form and a context-informed prior, where the probability of observing certain pixels (or orthographic features) could be up-weighted proportional to prediction certainty. We believe such an approach could provide useful insights in elucidating the pattern of effects we observed.

We note that exploratory analyses at the typical latency of the N400 revealed a pattern which also appears to run counter to a simple predictive coding account of predictability effects. This is seemingly inconsistent with interpretations of the N400 as indexing prediction error (Bornkessel-Schlesewsky & Schlesewsky, 2019; Eddine et al., 2023; Rabovsky & McRae, 2014). At the lowest level of predictability, we observed greater N400 amplitudes for picture-congruent words, than for picture-incongruent words. As predictability increased, meanwhile, N400 amplitudes became less extreme for picture-congruent words, rather than becoming more extreme for picture-incongruent words. We caution against over-interpreting these results. In addition to these results being entirely exploratory, we used an average EEG reference, rather than the more standard mastoid reference for later centroparietal components like the N400.

Furthermore, when elicited by words in context, such as a sentence or picture, evidence

suggests that the N400 indexes both prediction and integration processes (Nieuwland

et al., 2018). Nevertheless, that our design elicited effects on the N400 that are

seemingly inconsistent with existing findings from more traditional experimental designs

may point to our specific experimental design playing a key role in the pattern of effects

we observed in the N1.

In sum, we tested a simple predictive coding account of the word-elicited N1, but

failed to find evidence in favour of it. Exploratory analyses suggest that the pattern of

effects in the Congruency-Predictability interaction were in the opposite direction to that

expected under a simple predictive coding model. We argue that such a model is

insufficient to explain the pattern of effects we observed, and we have identified avenues

of future research that could better delineate how predictive processes interact with

processing during the N1.

References

Allison, T., Mccarthy, G., Nobre, A., Puce, A., & Belger, A. (1994). Human extrastriate visual cortex and the perception of faces, words, numbers, and colors. *Cerebral Cortex*, *4*(5), 544–554. https://doi.org/10.1093/cercor/4.5.544

Appelbaum, L. G., Liotti, M., Perez, R., Fox, S. P., & Woldorff, M. G. (2009). The temporal dynamics of implicit processing of non-letter, letter, and word-forms in the human visual cortex. *Frontiers in Human Neuroscience*, *3*, 1–11. https://doi.org/10.3389/neuro.09.056.2009

Barr, D. J., Levy, J., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory hypothesis testing: Keep it maximal. *Journal of Memory and Language*, *68*(Supplement), 1–63. https://doi.org/10.1016/j.jml.2012.11.001

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, *67*(1), 1–48. https://doi.org/10.18637/jss.v067.i01

Bentin, S., Mouchetant-Rostaing, Y., Giard, M. H., Echallier, J. F., & Pernier, J. (1999). ERP manifestations of processing printed words at different psycholinguistic levels: Time course and scalp distribution. *Journal of Cognitive Neuroscience*, *11*(3), 235–260. https://doi.org/10.1162/089892999563373

Blank, H., & Davis, M. H. (2016). Prediction Errors but Not Sharpened Signals Simulate Multivoxel fMRI Patterns during Speech Perception [Publisher: Public Library of Science]. *PLOS Biology*, *14*(11), e1002577. https://doi.org/10.1371/journal.pbio.1002577

Bornkessel-Schlesewsky, I., & Schlesewsky, M. (2019). Toward a neurobiologically plausible model of language-related, negative event-related potentials. *Frontiers in Psychology*, *10*(Article 298). https://doi.org/10.3389/fpsyg.2019.00298

Bowman, H., Collins, D. J., Nayak, A. K., & Cruse, D. (2023). Is predictive coding falsifiable? *Neuroscience & Biobehavioral Reviews*, *154*, 105404. https://doi.org/10.1016/j.neubiorev.2023.105404

Bowman, H., Filetti, M., Janssen, D., Su, L., Alsufyani, A., & Wyble, B. (2013). Subliminal Salience Search Illustrated: EEG Identity and Deception Detection on the Fringe of Awareness [Publisher: Public Library of Science]. *PLOS ONE*, *8*(1), e54258. https://doi.org/10.1371/journal.pone.0054258

Branzi, F. M., Martin, C. D., & Paz-Alonso, P. M. (2022). Task-relevant representations and cognitive control demands modulate functional connectivity from ventral occipito-temporal cortex during object recognition tasks. *Cerebral Cortex*, *32*(14), 3068–3080. https://doi.org/10.1093/cercor/bhab401

Brem, S., Halder, P., Bucher, K., Summers, P., Martin, E., & Brandeis, D. (2009). Tuning of the visual word processing system: Distinct developmental ERP and fMRI effects. *Human Brain Mapping*, *30*(6), 1833–1844. https://doi.org/10.1002/hbm.20751

Brem, S., Hunkeler, E., Mächler, M., Kronschnabel, J., Karipidis, I. I., Pleisch, G., & Brandeis, D. (2018). Increasing expertise to a novel script modulates the visual N1 ERP in healthy adults. *International Journal of Behavioral Development*, *42*(3), 333–341. https://doi.org/10.1177/0165025417727871

Brodeur, M. B., Guérard, K., & Bouras, M. (2014). Bank of Standardized Stimuli (BOSS) phase ii: 930 new normative photos. *PLoS ONE*, *9*(9), 1–10. https://doi.org/10.1371/journal.pone.0106953

Brothers, T., Swaab, T. Y., & Traxler, M. J. (2015). Effects of prediction and contextual support on lexical processing: Prediction takes precedence. *Cognition*, *136*, 135–149. https://doi.org/10.1016/j.cognition.2014.10.017

Bürkner, P.-C. (2017). Brms: An R package for Bayesian multilevel models using Stan. *Journal of Statistical Software*, *80*(1), 1–28. https://doi.org/10.18637/jss.v080.i01

Caucheteux, C., Gramfort, A., & King, J.-R. (2023). Evidence of a predictive coding

hierarchy in the human brain listening to speech. *Nature Human Behaviour*, 1–12.

https://doi.org/10.1038/s41562-022-01516-2

Chang, C. Y., Hsu, S. H., Pion-Tonachini, L., & Jung, T. P. (2020). Evaluation of Artifact

Subspace Reconstruction for automatic artifact components removal in

multi-channel EEG recordings. *IEEE Transactions on Biomedical Engineering*,

67(4), 1114–1121. https://doi.org/10.1109/TBME.2019.2930186

Cheimariou, S., Farmer, T. A., & Gordon, J. K. (2019). Lexical prediction in the aging

brain: The effects of predictiveness and congruency on the N400 ERP

component. *Aging, Neuropsychology, and Cognition*, *26*(5), 781–806.

https://doi.org/10.1080/13825585.2018.1529733

Chen, Y., Davis, M. H., Pulvermüller, F., & Hauk, O. (2013). Task modulation of brain

responses in visual word recognition as studied using EEG/MEG and fMRI.

Frontiers in Human Neuroscience, *7*, 1–14.

https://doi.org/10.3389/fnhum.2013.00376

Chen, Y., Davis, M. H., Pulvermüller, F., & Hauk, O. (2015). Early visual word processing

is flexible: Evidence from spatiotemporal brain dynamics. *Journal of Cognitive

Neuroscience*, *27*(9), 1738–1751. https://doi.org/10.1162/jocn_a_00815

Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of

cognitive science. *Behavioral and Brain Sciences*, *36*(3), 181–204.

https://doi.org/10.1017/S0140525X12000477

Cohen, L., Dehaene, S., Naccache, L., Lehéricy, S., Dehaene-Lambertz, G.,

Hénaff, M.-A., & Michel, F. (2000). The visual word form area: Spatial and

temporal characterization of an initial stage of reading in normal subjects and

posterior split-brain patients. *Brain*, *123*, 291–307.

Compton, P. E., Grossenbacher, P., Posner, M. I., & Tucker, D. M. (1991). A
    cognitive-anatomical approach to attention in lexical access. *Journal of Cognitive Neuroscience*, *3*(4), 304–312. https://doi.org/10.1162/jocn.1991.3.4.304

Dale, A. M., Liu, A. K., Fischl, B. R., Buckner, R. L., Belliveau, J. W., Lewine, J. D., &
    Halgren, E. (2000). Dynamic statistical parametric mapping: Combining fMRI and
    MEG for high-resolution imaging of cortical activity. *Neuron*, *26*(1), 55–67.
    https://doi.org/10.1016/S0896-6273(00)81138-1

Dambacher, M., Dimigen, O., Braun, M., Wille, K., Jacobs, A. M., & Kliegl, R. (2012).
    Stimulus onset asynchrony and the timeline of word recognition: Event-related
    potentials during sentence reading. *Neuropsychologia*, *50*(8), 1852–1870.
    https://doi.org/10.1016/j.neuropsychologia.2012.04.011

Delaney-Busch, N., Morgan, E., Lau, E., & Kuperberg, G. R. (2019). Neural evidence for
    Bayesian trial-by-trial adaptation on the N400 during semantic priming. *Cognition*,
    187, 10–20. https://doi.org/10.1016/j.cognition.2019.01.001

de Lange, F. P., Heilbron, M., & Kok, P. (2018). How Do Expectations Shape Perception?
    Trends in Cognitive Sciences, *22*(9), 764–779.
    https://doi.org/10.1016/j.tics.2018.06.002

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of
    single-trial EEG dynamics including independent component analysis. *Journal of
    Neuroscience Methods*, *134*, 9–21.
    https://doi.org/10.1016/j.jneumeth.2003.10.009

Desimone, R. (1996). Neural mechanisms for visual memory and their role in attention.
    Proceedings of the National Academy of Sciences, *93*(24), 13494–13499.
    https://doi.org/10.1073/pnas.93.24.13494

Dikker, S., & Pylkkänen, L. (2011). Before the N400: Effects of lexical-semantic violations
    in visual cortex. *Brain and Language*, *118*(1-2), 23–28.
    https://doi.org/10.1016/j.bandl.2011.02.006

Eaton, J. W., Bateman, D., Hauberg, S., & Wehbring, R. (2020). *GNU Octave version 6.1.0 manual: A high-level interactive language for numerical computations*. https://www.gnu.org/software/octave/doc/v6.1.0/

Eberhard-Moscicka, A. K., Jost, L. B., Fehlbaum, L. V., Pfenninger, S. E., & Maurer, U. (2016). Temporal dynamics of early visual word processing - Early versus late N1 sensitivity in children and adults. *Neuropsychologia*, *91*, 509–518. https://doi.org/10.1016/j.neuropsychologia.2016.09.014

Eddine, S. N., Brothers, T., Wang, L., Spratling, M., & Kuperberg, G. R. (2023, April). A predictive coding model of the N400. https://doi.org/10.1101/2023.04.10.536279

Eisenhauer, S., Gagl, B., & Fiebach, C. J. (2022). Predictive pre-activation of orthographic and lexical-semantic representations facilitates visual word recognition. *Psychophysiology*, *59*(3), 1–26. https://doi.org/10.1111/psyp.13970

Enge, A., Süß, F., & Rahman, R. A. (2023). Instant effects of semantic information on visual perception. *Journal of Neuroscience*. https://doi.org/10.1523/JNEUROSCI.2038-22.2023

Falandays, J. B., Nguyen, B., & Spivey, M. J. (2021). Is prediction nothing more than multi-scale pattern completion of the future? *Brain Research*, *1768*, 147578. https://doi.org/10.1016/j.brainres.2021.147578

Federmeier, K. D. (2007). Thinking ahead: The role and roots of prediction in language comprehension. *Psychophysiology*, *44*(4), 491–505. https://doi.org/10.1111/j.1469-8986.2007.00531.x

Feldman, H., & Friston, K. (2010). Attention, uncertainty, and free-energy. *Frontiers in Human Neuroscience*, *4*. https://doi.org/10.3389/fnhum.2010.00215

Fitz, H., & Chang, F. (2019). Language ERPs reflect learning through prediction error propagation. *Cognitive Psychology*, *111*, 15–52. https://doi.org/10.1016/j.cogpsych.2019.03.002

Fodor, J. (1983). Input systems as modules. In *The Modularity of Mind* (pp. 47–101). MIT Press.

Forster, K. I. (1979). Levels of processing and the structure of the language processor. In W. Cooper & E. Walker (Eds.), *Sentence Processing: Psycholinguistic essays presented to Merrill Garrett* (pp. 27–85). Erlbaum.

Friston, K. (2010). The free-energy principle: A unified brain theory? *Nature Reviews Neuroscience*, *11*(2), 127–138. https://doi.org/10.1038/nrn2787

Gagl, B., Sassenhagen, J., Haan, S., Gregorova, K., Richlan, F., & Fiebach, C. J. (2020). An orthographic prediction error as the basis for efficient visual word recognition. *NeuroImage*, *214*(August 2019), 116727. https://doi.org/10.1016/j.neuroimage.2020.116727

Gagnepain, P., Henson, R. N., & Davis, M. H. (2012). Temporal predictive codes for spoken words in auditory cortex. *Current Biology*, *22*(7), 615–621. https://doi.org/10.1016/j.cub.2012.02.015

Garrido, M. I., Kilner, J. M., Stephan, K. E., & Friston, K. J. (2009). The mismatch negativity: A review of underlying mechanisms. *Clinical Neurophysiology*, *120*(3), 453–463. https://doi.org/10.1016/j.clinph.2008.11.029

Getz, L. M., & Toscano, J. C. (2019). Electrophysiological evidence for top-down lexical influences on early speech perception. *Psychological Science*, *30*(6), 830–841. https://doi.org/10.1177/0956797619841813

Grill-Spector, K., Henson, R., & Martin, A. (2006). Repetition and the brain: Neural models of stimulus-specific effects. *Trends in Cognitive Sciences*, *10*(1), 14–23. https://doi.org/10.1016/j.tics.2005.11.006

Groppe, D. M., Makeig, S., & Kutas, M. (2009). Identifying reliable independent components via split-half comparisons. *NeuroImage*, *45*(4), 1199–1211. https://doi.org/10.1016/j.neuroimage.2008.12.038

Hauk, O., Coutout, C., Holden, A., & Chen, Y. (2012). The time-course of single-word
        reading: Evidence from fast behavioral and brain responses. *NeuroImage*, *60*(2),
        1462–1477. https://doi.org/10.1016/j.neuroimage.2012.01.061

Heilbron, M., & Chait, M. (2018). Great Expectations: Is there Evidence for Predictive
        Coding in Auditory Cortex? *Neuroscience*, *389*, 54–73.
        https://doi.org/10.1016/j.neuroscience.2017.07.061

Hodson, R., Mehta, M., & Smith, R. (2024). The empirical status of predictive coding and
        active inference. *Neuroscience & Biobehavioral Reviews*, *157*, 105473.
        https://doi.org/10.1016/j.neubiorev.2023.105473

Huang, Z., Yang, S., Xue, L., Yang, H., Lv, Y., & Zhao, J. (2022). Level of orthographic
        knowledge helps to reveal automatic predictions in visual word processing.
        Frontiers in Neuroscience, *15*. https://doi.org/10.3389/fnins.2021.809574

Hyvärinen, A., & Oja, E. (1997). A fast fixed-point algorithm for independent component
        analysis. *Neural Computation*, *9*(7), 1483–1492.
        https://doi.org/10.1162/neco.1997.9.7.1483

Kanai, R., Komura, Y., Shipp, S., & Friston, K. (2015). Cerebral hierarchies: Predictive
        processing, precision and the pulvinar. *Philosophical Transactions of the Royal
        Society B: Biological Sciences*, *370*(1668). https://doi.org/10.1098/rstb.2014.0169

Kherif, F., Josse, G., & Price, C. J. (2011). Automatic top-down processing explains
        common left occipito-temporal responses to visual words and objects. *Cerebral
        Cortex*, *21*, 103–114. https://doi.org/10.1093/cercor/bhq063

Kim, A. E., & Gilley, P. M. (2013). Neural mechanisms of rapid sensitivity to syntactic
        anomaly. *Frontiers in Psychology*, *4*, 1–15.
        https://doi.org/10.3389/fpsyg.2013.00045

Kim, A. E., & Lai, V. (2012). Rapid interactions between lexical semantic and word form
        analysis during word recognition in context: Evidence from ERPs. *Journal of
        Cognitive Neuroscience*, *24*(5), 1104–1112. https://doi.org/10.1162/jocn_a_00148

Knolle, F., Schröger, E., & Kotz, S. A. (2013). Prediction errors in self- and
externally-generated deviants. *Biological Psychology*, *92*(2), 410–416.
https://doi.org/10.1016/j.biopsycho.2012.11.017

Kok, P., Rahnev, D., Jehee, J. F. M., Lau, H. C., & de Lange, F. P. (2012). Attention
reverses the effect of prediction in silencing sensory signals. *Cerebral Cortex
(New York, N.Y.: 1991)*, *22*(9), 2197–2206. https://doi.org/10.1093/cercor/bhr310

Kretzschmar, F., Schlesewsky, M., & Staub, A. (2015). Dissociating word frequency and
predictability effects in reading: Evidence from coregistration of eye movements
and EEG. *Journal of Experimental Psychology : Learning, Memory, and
Cognition*, *41*(6), 1648–1662. https://doi.org/10.1037/xlm0000128

Kuperberg, G. R., & Jaeger, T. F. (2016). What do we mean by prediction in language
comprehension? *Language, Cognition and Neuroscience*, *31*(1), 32–59.
https://doi.org/10.1080/23273798.2015.1102299

Kutas, M., & Federmeier, K. D. (2011). Thirty years and counting: Finding meaning in the
N400 component of the event related brain potential (ERP). *Annual review of
psychology*, *62*, 621–647. https://doi.org/10.1146/annurev.psych.093008.131123

Kutas, M., & Hillyard, S. A. (1980). Reading senseless sentences: Brain potentials reflect
semantic incongruity. *Science*, *207*, 203–205.
https://doi.org/10.1126/science.7350657

Lau, E. F., Holcomb, P. J., & Kuperberg, G. R. (2013). Dissociating N400 effects of
prediction from association in single-word contexts. *Journal of Cognitive
Neuroscience*, *25*(3), 484–502. https://doi.org/10.1162/jocn_a_00328

Lau, E. F., Namyst, A., Fogel, A., & Delgado, T. (2016). A Direct Comparison of N400
Effects of Predictability and Incongruity in Adjective-Noun Combination. *Collabra*,
2(1), 13. https://doi.org/10.1525/collabra.40

Lin, S. E., Chen, H. C., Zhao, J., Li, S., He, S., & Weng, X. C. (2011). Left-lateralized
N170 response to unpronounceable pseudo but not false Chinese characters -

the key role of orthography. *Neuroscience*, *190*, 200–206.

https://doi.org/10.1016/j.neuroscience.2011.05.071

Lindborg, A., Musiolek, L., Ostwald, D., & Rabovsky, M. (2023). Semantic surprise

predicts the N400 brain potential. *Neuroimage: Reports*, *3*(1), 100161.

https://doi.org/10.1016/j.ynirp.2023.100161

Ling, S., Lee, A. C. H., Armstrong, B. C., & Nestor, A. (2019). How are visual words

represented? Insights from EEG-based visual word decoding, feature derivation

and image reconstruction. *Human Brain Mapping*, *40*(17), 5056–5068.

https://doi.org/10.1002/hbm.24757

Luke, S. G., & Christianson, K. (2016). Limits on lexical prediction during reading.

Cognitive Psychology, *88*, 22–60. https://doi.org/10.1016/j.cogpsych.2016.06.002

Luthra, S., Li, M. Y. C., You, H., Brodbeck, C., & Magnuson, J. S. (2021). Does signal

reduction imply predictive coding in models of spoken word recognition?

Psychonomic Bulletin & Review, *28*(4), 1381–1389.

https://doi.org/10.3758/s13423-021-01924-x

Mangun, G. R., & Hillyard, S. A. (1991). Modulations of sensory-evoked brain potentials

indicate changes in perceptual processing during visual-spatial priming. *Journal of

Experimental Psychology: Human Perception and Performance*, *17*(4),

1057–1074. https://doi.org/10.1037/0096-1523.17.4.1057

Mantegna, F., Hintz, F., Ostarek, M., Alday, P. M., & Huettig, F. (2019). Distinguishing

integration and prediction accounts of ERP N400 modulations in language

processing through experimental design. *Neuropsychologia*, *134*, 107199.

https://doi.org/10.1016/j.neuropsychologia.2019.107199

MATLAB. (2022). *MATLAB Version 9.13.0 (R2022b)*. The MathWorks Inc.

Maurer, U., Brandeis, D., & McCandliss, B. D. (2005). Fast, visual specialization for

reading in English revealed by the topography of the N170 ERP response.

Behavioral and Brain Functions, *1*, 1–12. https://doi.org/10.1186/1744-9081-1-13

Maurer, U., Brem, S., Bucher, K., & Brandeis, D. (2005). Emerging neurophysiological specialization for letter strings. *Journal of Cognitive Neuroscience*, *17*(10), 1532–1552. https://doi.org/10.1162/089892905774597218

Maurer, U., Rossion, B., & McCandliss, B. D. (2008). Category specificity in early perception: Face and word N170 responses differ in both lateralization and habituation properties. *Frontiers in Human Neuroscience*, *2*, 1–7. https://doi.org/10.3389/neuro.09.018.2008

McClelland, J. L., & Rumelhart, D. E. (1981). An interactive activation model of context effects in letter perception: Part 1. An acccount of basic findings. *Psychological Review*, *88*(5), 375–407. https://doi.org/10.1037/0033-295X.88.5.375

Nieuwland, M. S. (2019). Do 'early' brain responses reveal word form prediction during language comprehension? A critical review. *Neuroscience and Biobehavioral Reviews*, *96*, 367–400. https://doi.org/10.1016/j.neubiorev.2018.11.019

Nieuwland, M. S., Barr, D. J., Bartolozzi, F., Busch-Moreno, S., Darley, E., Donaldson, D. I., Ferguson, H. J., Fu, X., Heyselaar, E., Huettig, F., Husband, E. M., Ito, A., Kazanina, N., Kogan, V., Kohút, Z., Kulakova, E., Mézière, D., Politzer-Ahles, S., Rousselet, G. A., … Von Grebmer Zu Wolfsthurn, S. (2018). Dissociable effects of prediction and integration during language comprehension: Evidence from a large-scale study using brain potentials, 1–23. https://doi.org/10.1101/267815

Nobre, A. C., Allison, T., & McCarthy, G. (1994). Word recognition in the human inferior temporal lobe. *372*, 260–263. https://doi.org/10.1038/372260a0

Pastore, M., & Calcagnì, A. (2019). Measuring distribution similarities between samples: A distribution-free overlapping index. *Frontiers in Psychology*, *10*(1089), 1–8. https://doi.org/10.3389/fpsyg.2019.01089

Peirce, J. W. (2007). PsychoPy - Psychophysics software in Python. *Journal of Neuroscience Methods*, *162*(1-2), 8–13. https://doi.org/10.1016/j.jneumeth.2006.11.017

Penolazzi, B., Hauk, O., & Pulvermüller, F. (2007). Early semantic context integration and lexical access as revealed by event-related brain potentials. *Biological Psychology*, *74*(3), 374–388. https://doi.org/10.1016/j.biopsycho.2006.09.008

Pickering, M. J., & Gambi, C. (2018). Predicting while comprehending language: A theory and review. *Psychological Bulletin*, *144*(10), 1002–1044. https://doi.org/10.1037/bul0000158

Pickering, M. J., & Garrod, S. (2013). An integrated theory of language production and comprehension. *Behavioral and Brain Sciences*, *36*(4), 329–347. https://doi.org/10.1017/S0140525X12001495

Pion-Tonachini, L., Kreutz-Delgado, K., & Makeig, S. (2019). ICLabel: An automated electroencephalographic independent component classifier, dataset, and website. *NeuroImage*, *198*, 181–197. https://doi.org/10.1016/j.neuroimage.2019.05.026

Pleisch, G., Karipidis, I. I., Brem, A., Röthlisberger, M., Roth, A., Brandeis, D., Walitza, S., & Brem, S. (2019). Simultaneous EEG and fMRI reveals stronger sensitivity to orthographic strings in the left occipito-temporal cortex of typical versus poor beginning readers. *Developmental Cognitive Neuroscience*, *40*, 1–13. https://doi.org/10.1016/j.dcn.2019.100717

Powell, M. (2009). The BOBYQA algorithm for bound constrained optimization without derivatives. *Cambridge NA Report NA2009/06, University of Cambridge, Cambridge*, 26–46. https://doi.org/10.1.1.443.7693

Price, C. J., & Devlin, J. T. (2011). The Interactive Account of ventral occipitotemporal contributions to reading. *Trends in Cognitive Sciences*, *15*(6), 246–253. https://doi.org/10.1016/j.tics.2011.04.001

R Core Team. (2021). *R: A language and environment for statistical computing*. R

Foundation for Statistical Computing. https://www.r-project.org/

Rabovsky, M., & McRae, K. (2014). Simulating the N400 ERP component as semantic

network error: Insights from a feature-based connectionist attractor model of word

meaning. *Cognition*, *132*(1), 68–89.

https://doi.org/10.1016/j.cognition.2014.03.010

Rao, R. P., & Ballard, D. H. (1999). Predictive coding in the visual cortex: A functional

interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*,

2(1), 79–87. https://doi.org/10.1038/4580

Rauschecker, A. M., Bowen, R. F., Parvizi, J., & Wandell, B. A. (2012). Position sensitivity

in the visual word form area. *Proceedings of the National Academy of Sciences of

the United States of America*, *109*(24). https://doi.org/10.1073/pnas.1121304109

Rauss, K., Schwartz, S., & Pourtois, G. (2011). Top-down effects on early visual

processing in humans: A predictive coding framework. *Neuroscience and

Biobehavioral Reviews*, *35*(5), 1237–1253.

https://doi.org/10.1016/j.neubiorev.2010.12.011

Rayner, K., Slattery, T. J., Drieghe, D., & Liversedge, S. P. (2011). Eye movements and

word skipping during reading: Effects of word length and predictability. *Journal of

Experimental Psychology: Human Perception and Performance*, *37*, 514–528.

https://doi.org/10.1037/a0020990

Rodrigues, A. P., Rebola, J., Pereira, M., Van Asselen, M., & Castelo-Branco, M. (2019).

Neural responses of the anterior ventral occipitotemporal cortex in developmental

dyslexia: Beyond the visual word form area. *Investigative Ophthalmology and

Visual Science*, *60*(4), 1063–1068. https://doi.org/10.1167/iovs.18-26325

Rousselet, G. A. (2012). Does filtering preclude us from studying ERP time-courses?

Frontiers in Psychology, *3*, 1–9. https://doi.org/10.3389/fpsyg.2012.00131

Schuster, S., Himmelstoss, N. A., Hutzler, F., Richlan, F., Kronbichler, M., & Hawelka, S. (2021). Cloze enough? Hemodynamic effects of predictive processing during natural reading. *NeuroImage*, *228*, 117687. https://doi.org/10.1016/j.neuroimage.2020.117687

Segalowitz, S. J., & Zheng, X. (2009). An ERP study of category priming: Evidence of early lexical semantic access. *Biological Psychology*, *80*(1), 122–129. https://doi.org/10.1016/j.biopsycho.2008.04.009

Sereno, S. C., Brewer, C. C., & O'Donnell, P. J. (2003). Context effects in word recognition: Evidence for early interactive processing. *Psychological Science*, *14*(4), 328–333. https://doi.org/10.1111/1467-9280.14471

Sereno, S. C., Hand, C. J., Shahid, A., Mackenzie, I. G., & Leuthold, H. (2019). Early EEG correlates of word frequency and contextual predictability in reading. *Language, Cognition and Neuroscience*, *35*(5), 625–640. https://doi.org/10.1080/23273798.2019.1580753

Sereno, S. C., Rayner, K., & Posner, M. I. (1998). Establishing a time-line of word recognition: Evidence from eye movements and event-related potentials. *NeuroReport*, *9*(10), 2195–2200. https://doi.org/10.1097/00001756-199807130-00009

Shain, C., Blank, I. A., van Schijndel, M., Schuler, W., & Fedorenko, E. (2020). fMRI reveals language-specific predictive coding during naturalistic sentence comprehension. *Neuropsychologia*, *138*, 107307. https://doi.org/10.1016/j.neuropsychologia.2019.107307

Sohoglu, E., Beckers, L., & Davis, M. H. (2023, October). Convergent neural signatures of speech prediction error are a biological marker for spoken word recognition [Pages: 2023.10.03.560649 Section: New Results]. https://doi.org/10.1101/2023.10.03.560649

Sohoglu, E., & Davis, M. H. (2020). Rapid computations of spectrotemporal prediction error support perception of degraded speech (A. J. King, P. Kok, P. Kok, C. Press, & E. C. Lalor, Eds.). *eLife*, *9*, e58077. https://doi.org/10.7554/eLife.58077

Sperber, R. D., McCauley, C., Ragain, R. D., & Weil, C. M. (1979). Semantic priming effects on picture and word processing. *Memory & Cognition*, *7*(5), 339–345. https://doi.org/10.3758/BF03196937

STAN Development Team. (2023). Stan Modeling Language Users Guide and Reference Manual, 2.32. https://mc-stan.org

Strijkers, K., Bertrand, D., & Grainger, J. (2015). Seeing the same words differently: The time course of automaticity and top-down intention in reading. *Journal of Cognitive Neuroscience*, *27*(8), 1542–1551. https://doi.org/10.1162/jocn_a_00797

Taha, H., Ibrahim, R., & Khateb, A. (2013). How does arabic orthographic connectivity modulate brain activity during visual word recognition: An ERP study. *Brain Topography*, *26*(2), 292–302. https://doi.org/10.1007/s10548-012-0241-2

Tanner, D., Morgan-Short, K., & Luck, S. J. (2015). How inappropriate high-pass filters can produce artifactual effects and incorrect conclusions in ERP studies of language and cognition. *Psychophysiology*, *52*(8), 997–1009. https://doi.org/10.1111/psyp.12437

Taylor, J. E., Beith, A., & Sereno, S. C. (2020). LexOPS: An R package and user interface for the controlled generation of word stimuli. *Behavior Research Methods*, *52*, 2372–2382. https://doi.org/10.3758/s13428-020-01389-1

Thaler, L., Schütz, A. C., Goodale, M. A., & Gegenfurtner, K. R. (2013). What is the best fixation target? The effect of target shape on stability of fixational eye movements. *Vision Research*, *76*, 31–42. https://doi.org/10.1016/j.visres.2012.10.012

Tsogli, V., Jentschke, S., & Koelsch, S. (2022). Unpredictability of the "when" influences prediction error processing of the "what" and "where". *PLOS ONE*, *17*(2), e0263373. https://doi.org/10.1371/journal.pone.0263373

Van Petten, C., & Kutas, M. (1990). Interactions between sentence context and word frequency in event-related brain potentials. *Memory & Cognition*, *18*(4), 380–393. https://doi.org/10.3758/BF03197127

Van Petten, C., & Luka, B. J. (2012). Prediction during language comprehension: Benefits, costs, and ERP components. *International Journal of Psychophysiology*, *83*(2), 176–190. https://doi.org/10.1016/j.ijpsycho.2011.09.015

Vanderwart, M. (1984). Priming by pictures in lexical decision. *Journal of Verbal Learning and Verbal Behavior*, *23*(1), 67–83. https://doi.org/10.1016/S0022-5371(84)90509-7

VanRullen, R. (2011). Four common conceptual fallacies in mapping the time course of recognition. *Frontiers in Psychology*, *2*, 1–6. https://doi.org/10.3389/fpsyg.2011.00365

Veale, J. F. (2014). Edinburgh Handedness Inventory - Short Form: A revised version based on confirmatory factor analysis. *Laterality*, *19*(2), 164–177. https://doi.org/10.1080/1357650X.2013.783045

Vidal, C., Content, A., & Chetail, F. (2017). BACS: The Brussels Artificial Character Sets for studies in cognitive psychology and neuroscience. *Behavior Research Methods*, *49*(6), 2093–2112. https://doi.org/10.3758/s13428-016-0844-8

Vidal-Gran, C., Sokoliuk, R., Bowman, H., & Cruse, D. (2020). Strategic and Non-Strategic Semantic Expectations Hierarchically Modulate Neural Processing. *eNeuro*, *7*(5). https://doi.org/10.1523/ENEURO.0229-20.2020

Walsh, K. S., McGovern, D. P., Clark, A., & O'Connell, R. G. (2020). Evaluating the neurophysiological evidence for predictive processing as a model of perception. *Annals of the New York Academy of Sciences*, *1464*(1), 242–268. https://doi.org/10.1111/nyas.14321

Wang, F., & Maurer, U. (2017). Top-down modulation of early print-tuned neural activity

      in reading. *Neuropsychologia*, *102*, 29–38.

      https://doi.org/10.1016/j.neuropsychologia.2017.05.028

Wang, F., & Maurer, U. (2020). Interaction of top-down category-level expectation and

      bottom-up sensory input in early stages of visual-orthographic processing.

      Neuropsychologia, *137*, 107299.

      https://doi.org/10.1016/j.neuropsychologia.2019.107299

Wang, J., Deng, Y., & Booth, J. R. (2019). Automatic semantic influence on early visual

      word recognition in the ventral occipito-temporal cortex. *Neuropsychologia*, *133*,

      107188. https://doi.org/10.1016/j.neuropsychologia.2019.107188

Wang, L., Schoot, L., Brothers, T., Alexander, E., Warnke, L., Kim, M., Khan, S.,

      Hämäläinen, M., & Kuperberg, G. R. (2023). Predictive coding across the left

      fronto-temporal hierarchy during language comprehension. *Cerebral Cortex*,

      33(8), 4478–4497. https://doi.org/10.1093/cercor/bhac356

White, A. L., Palmer, J., Boynton, G. M., & Yeatman, J. D. (2019). Parallel spatial

      channels converge at a bottleneck in anterior word-selective cortex. *Proceedings*

      of the National Academy of Sciences of the United States of America, *116*(20),

      10087–10096. https://doi.org/10.1073/pnas.1822137116

Woolnough, O., Donos, C., Rollo, P. S., Forseth, K. J., Lakretz, Y., Crone, N. E.,

      Fischer-Baum, S., Dehaene, S., & Tandon, N. (2021). Spatiotemporal dynamics of

      orthographic and lexical processing in the ventral visual pathway. *Nature Human*

      Behaviour, *5*(3), 389–398. https://doi.org/10.1038/s41562-020-00982-w

Yeatman, J. D., Rauschecker, A. M., & Wandell, B. A. (2013). Anatomy of the visual word

      form area: Adjacent cortical circuits and long-range white matter connections.

      Brain and Language, *125*(2), 146–155.

      https://doi.org/10.1016/j.bandl.2012.04.010

Ylinen, S., Bosseler, A., Junttila, K., & Huotilainen, M. (2017). Predictive coding
    accelerates word recognition and learning in the early stages of language
    development. *Developmental Science*, *20*(6), e12472.
    https://doi.org/10.1111/desc.12472

Ylinen, S., Huuskonen, M., Mikkola, K., Saure, E., Sinkkonen, T., & Paavilainen, P.
    (2016). Predictive coding of phonological rules in auditory cortex: A mismatch
    negativity study. *Brain and Language*, *162*, 72–80.
    https://doi.org/10.1016/j.bandl.2016.08.007

Zhao, J., Kipp, K., Gaspar, C., Maurer, U., Weng, X., Mecklinger, A., & Li, S. (2014). Fine
    neural tuning for orthographic properties of words emerges early in children
    reading alphabetic script. *Journal of Cognitive Neuroscience*, *26*(11), 2431–2442.
    https://doi.org/10.1162/jocn_a_00660

Zhao, J., Maurer, U., He, S., & Weng, X. (2019). Development of neural specialization for
    print: Evidence for predictive coding in visual word recognition. *PLoS Biology*,
    17(10), 1–17. https://doi.org/10.1371/journal.pbio.3000474