1
2
3
4 # Benchmarking informatics approaches for virus discovery:
5 ## Caution is needed when combining *in silico* identification methods

11 **Authors**
12
Bridget Hegarty[1*+]
James Riddell V[2*]
Eric Bastien[3]
Kathryn Langenfeld[4]
Morgan Lindback[3]
Jaspreet S. Saini[5]
Anthony Wing[3]
Jessica Zhang[6]
Melissa Duhaime[3+]
[1] Department of Civil and Environmental Engineering, Case Western Reserve University, Cleveland, OH
[2] Department of Microbiology, The Ohio State University, Columbus, OH
[3] Department of Ecology and Evolutionary Biology, University of Michigan, Ann Arbor, MI
[4] Department of Civil and Environmental Engineering, Stanford University, Palo Alto, CA
[5] Laboratory for Environmental Biotechnology, Ecole Polytechnique Fédérale de Lausanne, Lausanne,
Switzerland
[6] Department of Civil and Environmental Engineering, University of Michigan, Ann Arbor, MI
36
37 [*] BH and JR contributed equally to this manuscript
38
39 [+] corresponding authors
40

Abstract

Background

The identification of viruses from environmental metagenomic samples using informatics tools has offered critical insights in microbiome studies. However, it remains difficult for researchers to know for their specific study which tool(s) and settings are best suited to maximize capture of viruses while minimizing false positives. Studies are increasingly combining multiple tool outputs attempting to recover more viruses, but no combined approach has been benchmarked for accuracy. Here, we benchmarked 63 viral identification 'rulesets' against mock metagenomes composed of publicly available viral, bacterial, archaeal, fungal, and protist sequences. These rulesets are based on combinations of four single-tool rules and two multi-tool tuning rules. We applied these rulesets to various aquatic metagenomes and filtering strategies to evaluate the impact of habitat and viral enrichment on individual and combined tool performance. We provide a packaged pipeline for researchers that want to replicate our process.

Results

We found that combining rules increased viral recall, but at the expense of increased false positives. Six of the 63 combinations tested had equivalent accuracies to the highest one (MCC=0.77, $p_{adj} \geq 0.05$). All of the six high accuracy rulesets included VirSorter2, five included our "tuning removal" rule, and no high performing rulesets used more than four of our six rules. DeepVirFinder, VIBRANT, and VirSorter were each found once in these high accuracy rulesets, but never in combination with each other. Our validation suggests that the MCC plateau at 0.77 is caused by inaccurate labeling of the data that viral identification tools rely on for training and validation. In the aquatic metagenomes, our "highest MCC" ruleset identified a higher proportion of viral sequences in the virus-enriched samples (44-46%) than the non-enriched, cellular metagenomes (7-19%).

Conclusion

While improved algorithms may lead to more accurate viral identification tools, this should be done in tandem with curating accurately labeled viral gene and sequence databases. For most applications, we

66   recommend the use of the ruleset that uses VirSorter2 and our empirically derived tuning removal rule.

67   By providing a rigorous overview of the behavior of *in silico* viral identification strategies, our findings

68   guide the use of existing viral identification tools and offer a blueprint for feature engineering of new

69   tools that will lead to higher-confidence viral discovery in microbiome studies.

Background

Viruses are an essential component of microbial ecosystems: they influence nutrient cycling and

microbial community dynamics[1], account for 20-40% of microbial mortality per day[2], reprogram their

hosts' metabolism,[3,4] and horizontally transfer genes between host populations.[5,6] The primary approach

used to discover and describe viral diversity is culture-independent metagenomic sequencing. However,

viral sequences remain challenging to differentiate from non-viral ones because viruses have no universal

marker gene,[7] high mutation rates,[8,9] and relatively small reference databases relative to the magnitude of

their diversity.[10] Additionally, current environmental sample collection and sequencing methods recover

predominantly short contigs. Short sequences are challenging to classify correctly because they often do

not contain enough information (e.g., too few genes) to leverage our knowledge of what makes viral

sequences distinct.[11,12]

The challenge of identifying viral sequences in metagenomic datasets has driven the development of

many viral identification tools over the past decade that aim to differentiate viral sequences from non-

viral sequences.[13] Tools differ in the types of viruses they identify, what sequence lengths they are

optimized for, and the training data and algorithms underlying them. To be confidently applied to

environmental data, viral identification tools must be trained on sequences representative of the

microbiota being studied to ensure the tool has seen enough of the sequence space to correctly classify

viral sequences. Sequence types commonly found in environmental metagenomes include bacteria,

viruses, plasmids, archaea, protists, and fungi. Some tools, such as VirSorter2[12] and VIBRANT,[14] include

these diverse sequence types, as well as representative diversity within each sequence type, expanding the

classification accuracy of each tool. Other tools like DeepVirFinder and VirSorter do not include as

diverse sequences: DeepVirFinder does not include non-prokaryotic references and VirSorter is only built

on bacterial and archaeal virus references. Further, the performance of viral identification tools depends

on the interaction between the tool algorithm and the sample type. In a comparison of the viruses

recovered by different viral identification tools across 13 environmental samples, differences were found

in the number of sequences called viral between environments.[14]

While many viral identifications tools have comparable accuracy, their underlying algorithms differ and

may capture different sets of viruses from the same sample. With so many tools available, it can be

difficult to choose the most appropriate tool for a given study. Rather than choose one tool, a number of

studies have combined the outputs of multiple tools to classify viral sequences to capture a greater portion

of the viral signal.[15–21] This approach assumes that combining multiple tools will improve overall

accuracy by discovering more viruses without greatly increasing non-viral contamination (non-viral

sequences called viral by the approach), but this assumption has not been rigorously evaluated. In

particular, it remains unknown whether or not these multi-tool strategies significantly increase

contamination (e.g., by each tool returning non-overlapping false positive viral sequences).

Here, we benchmarked whether multi-tool approaches can distill a more complete and accurate set of

viral sequences. From our analysis, we recommend pipelines specific to short and long-read sequences, as

well as cellular metagenomes and virus-enriched samples. By returning more viral sequences with less

non-viral contamination, these pipelines will enable new and more accurate insights into the ways viruses

impact microbial ecosystem functions, with far-reaching implications for human and environmental

health.

Methods

Creation of sequence testing set

To create a testing set for benchmarking multi-tool pipelines, we downloaded viral, bacterial, fungal, plasmid,

protist, and archaeal genome sequences from the NCBI reference sequence database (RefSeq), as well as a

unique set of non-RefSeq virus genomes compiled by the VirSorter2 tool developers, herein 'VirSorter2

database'[22] (Figure 1A). These non-RefSeq virus genomes represent a comprehensive validated set of viruses.

We originally created nine testing sets by randomly sampling sequences with replacement from these

sources to create datasets that mimicked metagenomic environmental data. As the variability between

testing sets plateaued at five datasets (Figure S1), five datasets were used for subsequent. The testing sets

were designed to contain approximately 68% bacteria, 10% archaea, 10% virus (not proviruses), 5%

plasmid, 5% protist, and 2% fungi sequences, totaling ~8k sequences (Figure 1B). The proportion of

sequences was chosen to be representative of cellular-enriched metagenomic data, which are dominated

by bacterial sequences, and reportedly contain ~10% viral sequences.[15,23] The non-viral portion was

randomly sampled from 5.3M bacteria, 55.1k archaea, 6.6k plasmid, 69.6k fungi, and 216.5k protist

sequences from the NCBI database (accessed Nov 2019 for bacteria and archaea, April 2022 for others).

The viral portion of the testing set was generated by random sampling from 13.8k viral sequences from

the NCBI database and 370.153k viral sequences from the VirSorter2 database. As DeepVirFinder

requires sequences to be less than 2,100 kb, a custom python script was written to trim the testing set

sequences to meet this length cutoff. We did not expect trimming to impact results since the largest phage

genome reported is smaller than this length cutoff (735 kb).[24] Further, only sequences longer than 3 kb

were used because it has been previously shown that tool accuracy significantly decreases below 3 kb.[12]

Figure 1. Overview of study workflow. (A) A set of sequences > 3 kb were randomly downloaded from
NCBI and a curated Non-RefSeq viral genomes database ('VirSorter2 database') to (B) generate five
mock environmental metagenomes, where the donut chart represents the proportion of each sequence type
in each mock metagenome. (C) Mock metagenomes were run through six viral identification tools; (D)
where score cutoffs were defined based on each tool's outputs to maximize their accuracy. (E) Accuracy
was then assessed for each tool combination to guide the development of defined "rulesets." (F) Rulesets
were then used to classify sequences from six real-world aquatic metagenomes: three cell-enriched
metagenomes and three virus-enriched metagenomes.

Selection of viral identification tools

27 viral identification tools[12,14,25,25–49] were found through literature search and assessed to determine their

suitability for inclusion in this study (Table S1). Tools were included if they met the following criteria:

the tool (1) identifies viruses that infect prokaryotes (i.e., bacteria and archaea), (2) is suitable for

application to multiple environments (e.g., not only the human gut), (3) is designed to target viral

sequences of lengths greater than 3 kb, (4) can classify millions of sequences within a few days on high

performance computing clusters (i.e., not only available on a web server), (5) developers actively respond

to user issues, (6) performs well in previous comparative studies of viral identification tools,[12,14,50] (7) is

not specific to prophages, and (8) was published before June 2022.

Four of the 29 viral identification tools met the above criteria: DeepVirFinder,[27] VIBRANT,[14] VirSorter,[46]

and VirSorter2.[12] While not designed strictly as viral identification tools, Kaiju[51] and CheckV[26] were used

to tune the viral predictions in our test sets. All six are referred to as "viral identification tools" or simply

"tools" in this manuscript (Table 1, Figure 1C).

Table 1 - Overview of viral identification tools selected for inclusion in this study.

Tool name (version)	Tool Description	Algorithmic Approach	Why we included the tool
CheckV[26]	CheckV is an automated pipeline that identifies closed viral genomes, estimates the completeness of genome fragments, and removes host regions from proviruses.	HMM virus and host marker genes, virus-host boundary prediction, AAI based estimation of genome completeness	Not a viral identification tool, but provides benchmarking information for refining predictions from other tools
DeepVirFinder[27]	DeepVirFinder uses a multi-layered deep learning algorithm trained on a positive set of viral sequences from viral RefSeq data and a negative set of prokaryotic ones.	K-mer based deep learning convolutional neural network	Recent and increasingly commonly used tool based on a neural network
VIBRANT[14]	VIBRANT is a hybrid tool that uses both machine learning and protein similarity to classify viruses as either high, medium, low quality, or non-viral.	Neural network of protein annotations of HMMs	Recent and commonly used tool, provides gene annotation information
VirSorter[46]	VirSorter uses probabilistic models with reference and non-reference dependencies, as well as detecting hallmark viral genes.	Probabilistic modeling using HMMs	Commonly used, high quality predictions
VirSorter2[12]	VirSorter2 uses a neural network classifier built on top of the existing VirSorter infrastructure of reference based viral identification.	A multi-classifier combining a Random Forest model and expert knowledge of viral features	Recent and increasingly commonly used tool that is more inclusive of viral diversity than most other tools
Kaiju[51]	Kaiju is a taxonomic classifier that compares metagenomic sequences to NCBI reference databases at the protein level and assigns a near or exact taxon match if one is found.	A taxonomic classifier that uses protein-level classifications to assign reads to taxon from NCBI databases	Not a viral identification tool, but extremely fast method of taxonomic identification based on NCBI releases

160 The testing sets were run through each of the viral identification tools (CheckV (v0.9.0), DeepVirFinder

161 (v1.0), Kaiju (v1.9.0), VIBRANT (v1.2.1), VirSorter (v1.0.6), and VirSorter2 (v2.2.3)) using the

162 University of Michigan Great Lakes Supercomputing Cluster. The Kaiju nr_euk database (updated from

163 NCBI 05-23-2022) was used for Kaiju taxonomic classification. All tools were run with default

164 parameters except for specifying a 3 kb contig length cutoff.

Design of viral identification rules

Viral identification tools generate scores that indicate how confident they are that a given sequence is of

viral origin, but users are often faced with the dilemma of setting their own score cutoff to decide which

sequences to call "viral." To aid in the process of choosing rules and cutoffs for predicting viral

sequences, we designed six rules (Figure 1D, Figure 2). Each rule includes at least two *subrules* that use

outputs from the six selected tools. These subrules were designed through two processes:

(1) *Evaluation of existing recommendations for tool cutoffs and application*: the recommended

cutoffs for distinguishing viral and non-viral sequences in each tool's protocol were used as an initial set

of rules.[12,15,16,52]

(2) *Curation and evaluation of biological features:* some viral identification tools generate

information describing biological features for each sequence, e.g., VirSorter2 reports the number of viral

hallmark genes identified, CheckV reports the completeness of a sequence and relative percentage of viral

versus non-viral genes, VIBRANT identifies virus orthologous genes (VOGs). These biological features

were used to create classification criteria (Figure 2) to distinguish viral and non-viral sequences.

179
Figure 2. Diagram of approach details. (A) Sequences are first processed by each (B) viral
identification tool. Next, (C) the tool outputs are programmatically post-processed to generate a *viral*
score based on both (D) single-tool rules and the data-driven creation of (E) tuning addition and (F)
tuning removal processes. (G) This combined post-processing generates a *viral score* that indicates
whether each sequence input is predicted as "Virus" or "Not Virus." Subrules are scored based on the
confidence of the prediction: low-confidence = ±0.5, confident = ±1, highly confident not viral = -3.
186

The developers' recommendations for calling a sequence viral served as a baseline for assigning a given

sequence a *'viral score'* that captured the relative likelihood that a given sequence was viral. The cutoffs

were then adjusted to maximize the number of true viral sequences being classified as viral (true

positives) and minimize the number of non-viral sequences being classified as viral (false positives) in the

mock environmental microbial communities. We first defined four single-tool rules (Figure 2A-D)

derived from four viral identification tools (i.e., VIBRANT, VirSorter, VirSorter2, DeepVirFinder). Next,

we defined two sets of tuning rules derived from outputs of different tools that indicated a strongly viral

or non-viral signal (Figure 2E-F). These included: (1) a "tuning removal" rule that decreases the *viral*

score based on distinctly non-viral sequence features and (2) a "tuning addition" rule that increases the

viral score based on distinctly viral sequence features.

Each putative viral sequence is assigned a numerical value by each rule; these are combined to give a

value that comprises the sequence's *viral score* (Figure 2G). Sequences with a final *viral score* $\geq$ 1 were

considered viral, and scores < 1 non-viral (Figure 2G).

Evaluation of viral identification rulesets

Ultimately, 63 combinations (rulesets) of these six rules were evaluated by comparing the viral score of

each sequence to the classification assigned by the database (Figure 1E). From these values, precision (the

number of true viruses in our test set called viral divided by all contigs called viral), recall (the number of

true viruses in our test set called viral divided by all true viruses), and Matthews Correlation Coefficient

(MCC, considers the relative proportion of false positives, false negatives, true positives, and true

negatives)[53] were calculated.

Application of rulesets to environmental metagenomes

All rulesets were used to identify viruses from five previously published environmental datasets

representing different aquatic environments and size fractions (Figure 1F, Table S2). Three environments

(drinking water, global ocean water, and eutrophic lake water) contained metagenomic assemblies (>2

μm), and three environments (wastewater, eutrophic lake water, oligotrophic lake water) contained

213 virome assemblies (<0.2 and <0.45 µm), meaning samples were enriched for viruses by filtering through

214 a small pore to remove most cellular organisms before DNA extraction.

216 The default tool settings were used except for the oligotrophic lake and wastewater virus-enriched

217 samples, where the `-virome` flag was used for VIBRANT and VirSorter to reduce sensitivity, as

218 recommended by the developers of those tools given that a greater fraction of total sequences are

219 expected to be viral in virus-enriched samples. The '-virome' flag was not used for the eutrophic lake

220 water virome assemblies due to all eutrophic lake water assemblies being processed together, but the

221 eutrophic lake water virome still was most similar to the other virus-enriched samples (Figure 7). All

222 tools were run with a 3 kb cutoff to remove small sequences.

Code availability

224 The scripts to run the full testing pipeline presented above, including those to identify viral contigs from

225 these tool outputs, example runs, and classifier outputs on the environmental metagenomic samples, are

226 freely available at https://github.com/DuhaimeLab/VSTE.

Results and Discussion

228 Viral identification tools use algorithms based on knowledge of viral sequences and machine learning to

229 separate viral and non-viral sequences. In this study, we test the hypothesis that combining viral

230 identification tools with different underlying algorithms will improve accuracy. Performance of 63

231 combinations (rulesets) of the six rules were evaluated using five mock metagenomes of known

232 composition (Figure 3B, S1). The six rules are as follows: four single-tool rules derived from four viral

233 identification tools (i.e., VIBRANT, VirSorter, VirSorter2, DeepVirFinder; Figure 2A-D) and two

234 additional tuning rules: tuning removal (which removes predictions using Kaiju, CheckV, VirSorter2,

235 VirSorter, and VIBRANT outputs) and tuning addition (which adds predictions using Kaiju, CheckV, and

236 VirSorter2 outputs; Figure 2E-F). In this section, we compare the performance of our rulesets, elaborate

237 on their strengths and weaknesses, and provide recommendations for use.

238
239 **Figure 3. Comparison of different rulesets.** (A) Distribution of *viral scores* assigned to mock
240 metagenome sequences for our 6 rules: 4 single-tool and 2 tuning rules. (B) Viral scores of all sequences
241 across six mock metagenomes classified by each ruleset. Ruleset rows are colored based on whether or
242 not each rule was used to attain the *viral score* result for a given sequence. In both A and B, *viral scores* ≥
243 1 are classified as viral; and < 1 as not viral. All sequences are grouped by their assigned taxonomy.

More tools are better… to a point

Across the 63 rulesets, MCC, our metric for overall performance ('accuracy', herein), ranges from 0.05

(DeepVirFinder) to 0.77 (VirSorter2 + Tuning Removal). With the exception of VirSorter2 (MCC=0.75),

single-rule rulesets (i.e., viral identification tools run on their own) either missed most of the viruses in

the benchmarking dataset or misclassified such a large number of non-viruses that the viral signal was

heavily contaminated (Figure 3A). Of the single-rule rulesets, VIBRANT performs second best (MCC of

0.55), followed by VirSorter (MCC of 0.16) and DeepVirFinder (MCC of 0.05). Previous studies have

reported higher accuracy for these tools, but those studies used a testing set composed of 50% or more

viruses compared to our 10% viral sequences and/or did not include taxonomically diverse sequences

compared to the taxonomically diverse training data used here.[14,27,46,52] Using testing datasets

representative of environmental metagenomic datasets is important. We found that our MCCs increased

when using a testing set with a more similar composition to other studies (50% viral and 50% non-viral;

max MCC=0.91); and, in their validation of DeepVirFinder, Ren et al.[27] demonstrated that the relative

proportion of viral to non-viral sequences in a dataset can have a strong effect on AUROC (area under

receiver operating characteristic; a performance metric). Given the observed taxonomic distribution of

environmental cellular metagenomic sequences,[15,23] users likely need to be more conservative (higher

classification score cutoffs) in viral calling and assume lower accuracy than previous studies have

reported.

Combining rules generally increased the average MCC (Figure 4). This is driven by a statistically

significant increase in recall for multi-rule rulesets compared to single-rule rulesets and for three or more

rule rulesets compared to two-rule rulesets (Table S3). While average precision is constant as rules are

combined (Figure 4A, Table S4), the precision of higher precision rules (precision > 0.7, five right-most

points Figure S2A; the VIBRANT and VirSorter2 rules) decreases as they are combined with lower

precision rules (precision < 0.5; the DeepVirFinder and VirSorter rules). Accuracy is maximized by the

VirSorter2 and tuning removal ruleset, and is not improved by adding more rules (Figure 4B).

Figure 4. Performance of the 63 rulesets. (A) - Box and whisker plots of the performance scores representing variation in MCC, precision, and recall of different rulesets based on the number of rules used for prediction. (B) Ruleset accuracy (MCC) ordered by increasing MCC and colored based on the ruleset's type according to statistically equivalent ($p_{adj} \geq 0.05$) rulesets. For A and B, the middle line represents the group mean; boxes above and below the middle line represent the top and bottom quartiles, respectively; whiskers above and below the boxes represent 1.5 times the interquartile range (roughly the 95% confidence interval), outliers are represented by circles beyond the whiskers. The boxplots in A are overlaid with points that represent each testing set's MCC.

The VirSorter2-based and tuning removal rules are the most critical for accurate virus identification in our testing. When rulesets were ranked by increasing MCC, top performing "high MCC" rulesets were identified as those that did not demonstrate a statistically significant decrease relative to the highest MCC ruleset ($p_{adj} > 0.05$; Figure 4B). VirSorter2's rule ('vs2') was in all six of these high MCC rulesets (Figure 4B) and tuning removal ('tnv') was in five of them. For comparison, the other single-tool rules (i.e., VirSorter, DeepVirFinder, and VIBRANT) were each only in one of the high MCC rulesets, where they always co-occurred with VirSorter2 and the tuning removal rule (Figure 4B). None of the high MCC

rulesets have more than four rules. In the same way, "high precision" (three rulesets; Fig S2A) and "high

recall" (four rulesets; Fig S2B) rulesets were defined.

There is a high degree of overlap in the viruses predicted by the different rulesets (Figure 5). 68% of the

comparisons between rulesets (Figure 5, green and yellow cells) were more than 50% identical to each

other; and 30 rulesets were at least 90% identical to at least one other ruleset (Figure 5, yellow cells),

representing 4% of the total comparisons between rulesets. Rulesets with VirSorter, DeepVirFinder, and

VIBRANT all have more sequences in common as the number of rules in the compared sets increases, but

this trend is much less pronounced for VirSorter2 (Figure S3). This suggests that our observed increase in

recall through combining rules is being driven by a subset of rules that give more tool-specific viral

predictions (i.e., VirSorter, DeepVirFinder, and VIBRANT), leading to the question: "how confident

should users be of their tool-specific predictions?".

One assumption made during *in silico* virus identification by previous studies is that sequences with low-

confidence predictions by multiple tools are more likely to be viral (i.e., called viral by multiple +0.5

subrules). For example, if one tool predicts a sequence as viral with low confidence, it may be

disregarded. But if multiple tools each provide low confidence predictions for a given sequence, many

studies have presumed the sequence is more likely to be viral, thereby combining low quality predictions

to arrive at the set of predicted viruses.[15,16,18] However, we found this was not a safe strategy as it did not

increase the number of true-positives . Rulesets using multiple low-quality prediction subrules in the

single-tool rules did not significantly increase MCC (p-value=0.19) or recall (p-value=0.18); and in fact,

slightly decreased precision (0.54 vs 0.59, p-value=$2.5*10^{-5}$) when compared to rulesets that did not use

low-quality prediction subrules (Figure S4). This pattern is likely due to the rulesets being similarly

uncertain about sequences that are unlikely to be viral; thus, introducing a significant amount of non-viral

contamination. The additive uncertainty did not create certainty. We recommend being cautious of

sequences classified as viral by multiple low-quality predictions and manually inspecting them before

viral assignment.

314
Figure 5 - Proportion of viruses in common between rulesets. Heatmap values calculated by dividing
the intersection (called viral by both rulesets) by the union (called viral by at least one) of the viruses
found by both rulesets, which represents the proportion in common between the tools (scale bar on right:
dark purple: 0-0.1, blue: 0.1-0.5, green: 0.5-0.9, yellow: 0.9-1). The bar to the left of the heatmap
represents the total number of viruses identified by each tool combination (scalebar to its left). The bars
above the heatmap indicate the tool(s) used in the rulesets, as well as the ruleset type.

321
As metagenomes frequently have a high proportion of short sequence fragments and the correct

identification of short fragments with only a few genes is particularly challenging,[26] we tested the rulesets

on 3-5 kb fragments from our original testing sets. Like the >3 kb testing sets, many rulesets performed

similarly for the 3-5 kb fragments (Figure S6). Unlike in the >3 kb testing sets where the VirSorter2

single-rule ruleset was in the high MCC set (Figure 4B), no single-rule ruleset was in the high MCC

rulesets for the short fragments (Figure S6). Also in contrast with the >3 kb testing sets, the six-rule

ruleset was identified as a high MCC ruleset and DeepVirFinder is in 8 of the 12 high MCC rulesets. In

part due to our newly defined viral tuning rules, the accuracy of the viral predictions reported here for

these short fragments is greater than previously published.[12] This increase in accuracy suggests that

datasets where short fragments abound may particularly benefit from our tuning rules. Further, while

researchers with only 3-5 kb fragments may consider using more tools, equally accurate predictions can

still be achieved from the VirSorter2 and tuning removal ruleset.

Tuning rules increase confidence of viral predictions

To leverage expert knowledge of the differences between viral and non-viral sequences, we designed

tuning addition and removal rules (Figure 2E-F; see Figure S6 for subrule performance). These rules were

designed based on specific outputs from multiple tools that distinguish between viral and non-viral

sequences, such as sequence length and the number of host genes. In general, tuning addition improved

MCC and recall, while tuning removal improved MCC and precision (Figure S7). 7 of the 10 highest

MCC rulesets have both tuning addition and removal rules (Figure 4B), demonstrating the importance of

the tuning rulesets for accurate classification. The tuning *removal* rule was able to identify 89% of the

testing set's non-viral sequences and only (mis)identified 2% of testing set's viral sequences as non-viral

(*viral score* < 0 when only the tuning removal rule was applied). The tuning *addition* rule accurately

identified 74% of the viral sequences and only misidentified 4% of non-viral sequences in the testing set

as viral (*viral score* ≥ 1 when only the tuning addition rule was applied). Overall, the tuning rules

increased our prediction accuracy beyond that of the rulesets composed of the single-tool rules. As such,

we demonstrated the value of automating the refinement of viral identification tool predictions, a task

that, if done at all, is currently a laborious manual process.

Even with the tuning rules, we could not improve both precision and recall beyond 0.77 (Figure S8).

Building a more accurate classifier means overcoming barriers such as imperfect gene reference datasets,

overlap between viral and host sequences, and underrepresentation of viral types. This is because to

recover more viruses, it becomes necessary to rely more on genes of unknown origin. These may include

non-viral genes, particularly of eukaryotes, which were not represented in the reference datasets of

DeepVirFinder, VirSorter or CheckV (Figure S9-16). Further, many true viral features overlap with non-

viral features (Figure S9-16) due to our imperfect knowledge of what distinguishes viruses and non-

viruses (and homologous sequences shared by both viruses and cellular organisms), leading non-viruses

with virus-like features to be misclassified as viruses. This challenge is particularly acute when trying to

accurately classify both short sequences (<5 kb)[12,27] and viral types underrepresented in our testing data

(e.g., the accuracy of the "high MCC" ruleset is highest for dsDNAphages compared to other viral

sequence types, Figure S17).

Mislabeled sequences within databases hinder tool accuracy and validation

To improve upon the maximum MCC of 0.77, we looked for patterns in the types of sequences being

misclassified that could aid future tool design. To our surprise, the "false positive" sequences labeled as

bacteria by the NCBI database, but classified as viral by our high MCC ruleset, looked more "viral" than

the viruses themselves. Specifically, the proportion of the sequence's genes identified as viral orthologous

genes (VOGs) was higher in the misclassified bacteria than the known viruses (p-value $< 2.2*10^{-16}$;

Figure 6A). The plasmids misclassified as viral have a similar proportion of viral genes as the viruses (p-

value = 0.63). For all three sequence types, the proportion of sequences represented by VOGs increases

with the number of VOGs in that sequence (Figure 6B). If these highly viral sequences are not actually

viruses, viral identification tools can be improved by removing these genes from viral gene databases. On

the contrary, if these sequences are actually viruses, viral identification tools can be improved by

relabeling these sequences in sequence databases because tools rely on accurate database classification for

training and testing.

Figure 6 - Mislabeled sequences. (A) Box and whisker plot of the proportion of genes on a sequence
with a VOG annotation by VIBRANT broken down by sequence type (for the high MCC rules). (B)
Proportion of a sequence's genes with a VOG annotation versus the number of genes with a VOG
annotation faceted by sequence type. Because VIBRANT is the only tool that provided VOG annotation,
only sequences classified as viral by VIBRANT are included in panels A and B (which only included
bacteria, viruses, and plasmids). (C) Sequence synteny plots indicating sequence similarity between a
representative bacterial "false positive": NZ_LLFE01000196 (NCBI label: bacteria) versus Salmonella
phage SSU5. All genes of the testing set sequences are colored by their gene identity.

Manual inspection of a subset of these misclassified sequences revealed them to be viral sequences

(Figure 6C, S18). These false positives represented two types of mislabeled sequences: (1) viruses (either

extracellular virions or intracellular extrachromosomal viral genomes) co-sequenced when a host isolate

was sequenced (Figure 6C and S18A) and (2) prophages integrated into their hosts' genome (Figure

S18B). We also screened for ΦX contamination, as it is a known problem for NCBI database sequences

using Illumina library preparation due to its use in Illumina libraries.[54] Only 19 ΦX sequences were

taxonomically identified by Kaiju; and, thus do not explain our high degree of false positives. These

findings support the known problem of phage sequences not being removed before being deposited on

NCBI,[54] and lead to phages being misclassified as bacteria, archaea, plasmids, and cellular and satellite

chromosomes. Mislabeled sequences in public databases make it difficult to produce accurate viral

identification tools because developers rely on accurately labeled datasets to train and test their classifiers.

We recommend that before uploading sequences to public databases that non-viral sequences are screened

for viral contamination.

Sample preparation and viral identification tool choice affects viral sequence recovery

To compare our rulesets across environments, we evaluated the proportion of sequences classified as viral

for five publicly available aquatic metagenomic assemblies (Table S2, Figure S19). We found that viral

sequence recovery varied greatly based on sample preparation (e.g., virus-enriched or not) and viral

identification tool(s) used (Figure 7). The highest MCC ruleset identified a higher proportion of viral

sequences in the virus-enriched samples (44-46%) compared to the non-enriched metagenomes (7-19%).

The proportion of viruses recovered across rulesets for the environmental datasets mimics the behavior of

the testing data: the "high recall" rulesets classified the most sequences as viral (with presumably the

greatest non-viral contamination, given the results on our testing sets), while the "high precision" rulesets

labeled the fewest sequences as viral (with presumably the least non-viral contamination, given the results

on the testing sets) (Figure 7, and Table S2). Previous metagenomic studies of biomass collected on a 0.2

μm filter have found viral sequences to be less than 16% of the total metagenome,[15,23] which is in line

with our results. Further, these ranges in cellular-enriched samples (>0.2 μm fraction) is consistent with

the ~10% that one would expect, given that viral genomes tend to be 1-2 orders of magnitude smaller than

their microbial hosts and are on average an order of magnitude more abundant.[15]

Figure 7 - **Proportion of viruses predicted by each tool combination** across (A) our testing sets and
(B) environmental datasets. Rulesets are grouped based on the accuracy type on the testing set shown in
the highlighted rulesets from Figure 5.

For the virus-enriched samples, nearly all sequences were called viral by the "high recall" rulesets (Figure

7, S18). It is likely that some of these sequences are false positives because the tuning removal rule

reduces the number of sequences called viral by 14.9% (1 SD = 2.1%) when comparing the "all" to the

"highest recall" rulesets; and our benchmarking demonstrated that the tuning removal rule effectively

removed the contaminating non-viral sequences without removing true viruses. Further, one of the few

studies to report the proportion of viral sequences found that 30-60% of the sequences with known

taxonomy were similar to at least one viral sequence.[55] Even if all unknown sequences were viruses in

this study, the proportion of viruses would not exceed 92%, which is still lower than the proportions we

found in two of our three virus-enriched samples; and, further suggests the importance of tuning removal

even for viral-enriched metagenomes. We present this "high recall" example to caution readers against

using the "high recall" rulesets on virus-enriched metagenomes. It may be tempting to assume virus-

enrichment removes nearly all non-viral sequence contamination, but even for virus-enriched fragments

we instead recommend using the tuning removal rule unless the number of sequences is small enough to

be manually inspected.

Recommendations and Future Work

In silico prediction of viral sequences is a critical first step to any metagenomic study that aims to resolve viral ecology and virus-microbe interactions. As downstream analyses and conclusions are predicated on accurate viral prediction, it is paramount to choose the most suitable tool(s) (and know how to interpret its output(s)) among the rapidly increasing number of *in silico* viral prediction tools available. Through the above benchmarking, we demonstrated that specific two-rule rulesets provide the highest precision viral identification with only minor sacrifices in recall, whereas the worse performance of combining all tools may lead to erroneous biological conclusions. For this reason, we urge caution when using recent automated pipelines for sequence identification that combine the output of multiple tools.[17,19–21]

Our recommendations based on this study vary depending on research question and experimental design (Figure 8). For a typical study investigating viral diversity and functional potential from a mixed metagenome, we recommend our "high MCC" ruleset (VirSorter2 with tuning removal). If the majority of eukaryotes were filtered out of the sample (e.g., <3 µm fraction was sequenced), the tuning additional rule may increase recall. For researchers seeking to minimize the number of tools they use, we recommend using VirSorter2 with our CheckV-based tuning subrules. VirSorter2 has a comparable MCC to multitool rules (Figure 4), though its high recall comes at the cost of more false positives when used in isolation (Figure S2). While VIBRANT's high precision with and without our tuning removal rule (Figure 4, Figure S2), as well as convenient information about the viruses (e.g., their metabolic potential), are attractive, we found that its recall was much worse than our other recommendations on the environmental datasets. In general, however, we do not recommend researchers to use any of the tools in isolation, based on the poor accuracy of the single-rule sets on the short sequences (3-5 kb testing set, Figure S5).

Figure 8. Recommendations. Flowcharts are based on (A) sample type and (B) study goals when looking to minimize the number of tools used.

One limitation of this work is that the available testing data included sequences that were part of the tools'

original training and testing data: all tools included in this study were trained in part using NCBI

sequences that overlap with our testing data, and some were trained using the VirSorter2 non-RefSeq

genome set. These datasets also happen to harbor a large number of mislabeled sequences, making it

difficult to assess the accuracy of the benchmarking results. As additional curated viral sets are

published,[56] other researchers can test our rules against the new datasets providing further information

about the limitations and scope of our rules.

We focused on tools that were developed primarily for bacteriophage identification, as these are most

commonly used by microbial ecologists and microbiome researchers. We did not evaluate tools that were

specifically for prophages, human viral pathogens, eukaryotic viruses, or archaeal viruses more broadly

(Table S1). Future integration of new tools for plasmid and eukaryotic sequence identification[54,57] is likely

to improve viral identification tool pipelines.

Conclusions

With the rapid development of new viral identification tools, this paper offers a blueprint for intentional, data-driven validation of tool combinations. We found that the highest accuracy resulted from rulesets with four or fewer rules. For most applications, we recommend a combination of VirSorter2 and tuning rules based on features of viral and non-viral sequences; and caution against simply combining viral identification tools expecting higher quality virus sets. By increasing the proportion of high-confidence viruses identified from mixed metagenomic datasets through intentional, data-driven combination of tools, this study enables more accurate ecological analyses by decreasing contamination of the viral signal, particularly from eukaryotic sequences.

Acknowledgements

This work was supported by the Blue Sky Initiative of the University of Michigan College of Engineering (B.H., M.B.D.), National Science Foundation award #2055455 (M.B.D., E.B., M.L.), the National Science Foundation Graduate Research Fellowship Program under Grant No. DGE-134012 (J.R.) and DGE-1256260 (M.L.), and the National Oceanic and Atmospheric Administration Great Lakes Omics program distributed through the UM Cooperative Institute for Great Lakes Research NA17OAR4320152 (M.B.D, A.W.).

References

(1) Guidi, L.; Chaffron, S.; Bittner, L.; Eveillard, D.; Larhlimi, A.; Roux, S.; Darzi, Y.; Audic, S.; Berline, L.; Brum, J. R.; Coelho, L. P.; Espinoza, J. C. I.; Malviya, S.; Sunagawa, S.; Dimier, C.; Kandels-Lewis, S.; Picheral, M.; Poulain, J.; Searson, S.; Stemmann, L.; Not, F.; Hingamp, P.; Speich, S.; Follows, M.; Karp-Boss, L.; Boss, E.; Ogata, H.; Pesant, S.; Weissenbach, J.; Wincker, P.; Acinas, S. G.; Bork, P.; de Vargas, C.; Iudicone, D.; Sullivan, M. B.; Raes, J.; Karsenti, E.; Bowler, C.; Gorsky, G. Plankton Networks Driving Carbon Export in the Oligotrophic Ocean. *Nature* **2016**, *532* (7600), 465–470. https://doi.org/10.1038/nature16942.
(2) Wilhelm, S. W.; Suttle, C. A. Viruses and Nutrient Cycles in the Sea: Viruses Play Critical Roles in the Structure and Function of Aquatic Food Webs. *BioScience* **1999**, *49* (10), 781–788.

https://doi.org/10.2307/1313569.

(3) Howard-Varona, C.; Lindback, M. M.; Bastien, G. E.; Solonenko, N.; Zayed, A. A.; Jang, H.;
Andreopoulos, B.; Brewer, H. M.; Glavina del Rio, T.; Adkins, J. N.; Paul, S.; Sullivan, M. B.;
Duhaime, M. B. Phage-Specific Metabolic Reprogramming of Virocells. *ISME J.* **2020**, *14* (4),
881–895. https://doi.org/10.1038/s41396-019-0580-z.

(4) Hurwitz, B. L.; U'Ren, J. M. Viral Metabolic Reprogramming in Marine Ecosystems. *Curr. Opin.*
Microbiol. **2016**, *31*, 161–168. https://doi.org/10.1016/j.mib.2016.04.002.

(5) Beumer, A.; Robinson, J. B. A Broad-Host-Range, Generalized Transducing Phage (SN-T)
Acquires 16S RRNA Genes from Different Genera of Bacteria. *Appl. Environ. Microbiol.* **2005**, *71*
(12), 8301–8304. https://doi.org/10.1128/AEM.71.12.8301-8304.2005.

(6) Göller, P. C.; Elsener, T.; Lorgé, D.; Radulovic, N.; Bernardi, V.; Naumann, A.; Amri, N.;
Khatchatourova, E.; Coutinho, F. H.; Loessner, M. J.; Gómez-Sanz, E. Multi-Species Host Range of
Staphylococcal Phages Isolated from Wastewater. *Nat. Commun.* **2021**, *12* (1), 6965.
https://doi.org/10.1038/s41467-021-27037-6.

(7) Sullivan, M. B. Viromes, Not Gene Markers, for Studying Double-Stranded DNA Virus
Communities. *J. Virol.* **2015**, *89* (5), 2459–2461. https://doi.org/10.1128/JVI.03289-14.

(8) Drake, J. W. The Distribution of Rates of Spontaneous Mutation over Viruses, Prokaryotes, and
Eukaryotes. *Ann. N. Y. Acad. Sci.* **1999**, *870* (1), 100–107. https://doi.org/10.1111/j.1749-
6632.1999.tb08870.x.

(9) Peck, K. M.; Lauring, A. S. Complexities of Viral Mutation Rates. *J. Virol.* **2018**, *92* (14), e01031-
17. https://doi.org/10.1128/JVI.01031-17.

(10) O'Leary, N. A.; Wright, M. W.; Brister, J. R.; Ciufo, S.; Haddad, D.; McVeigh, R.; Rajput, B.;
Robbertse, B.; Smith-White, B.; Ako-Adjei, D.; Astashyn, A.; Badretdin, A.; Bao, Y.; Blinkova, O.;
Brover, V.; Chetvernin, V.; Choi, J.; Cox, E.; Ermolaeva, O.; Farrell, C. M.; Goldfarb, T.; Gupta,
T.; Haft, D.; Hatcher, E.; Hlavina, W.; Joardar, V. S.; Kodali, V. K.; Li, W.; Maglott, D.; Masterson,
P.; McGarvey, K. M.; Murphy, M. R.; O'Neill, K.; Pujar, S.; Rangwala, S. H.; Rausch, D.; Riddick,
L. D.; Schoch, C.; Shkeda, A.; Storz, S. S.; Sun, H.; Thibaud-Nissen, F.; Tolstoy, I.; Tully, R. E.;
Vatsan, A. R.; Wallin, C.; Webb, D.; Wu, W.; Landrum, M. J.; Kimchi, A.; Tatusova, T.; DiCuccio,
M.; Kitts, P.; Murphy, T. D.; Pruitt, K. D. Reference Sequence (RefSeq) Database at NCBI: Current
Status, Taxonomic Expansion, and Functional Annotation. *Nucleic Acids Res.* **2016**, *44* (Database
issue), D733–D745. https://doi.org/10.1093/nar/gkv1189.

(11) Ponsero, A. J.; Hurwitz, B. L. The Promises and Pitfalls of Machine Learning for Detecting Viruses
in Aquatic Metagenomes. *Front. Microbiol.* **2019**, *10*.

(12) Guo, J.; Bolduc, B.; Zayed, A. A.; Varsani, A.; Dominguez-Huerta, G.; Delmont, T. O.; Pratama, A.
A.; Gazitúa, M. C.; Vik, D.; Sullivan, M. B.; Roux, S. VirSorter2: A Multi-Classifier, Expert-
Guided Approach to Detect Diverse DNA and RNA Viruses. *Microbiome* **2021**, *9* (1), 37.
https://doi.org/10.1186/s40168-020-00990-y.

(13) Andrade-Martínez, J. S.; Camelo Valera, L. C.; Chica Cárdenas, L. A.; Forero-Junco, L.; López-
Leal, G.; Moreno-Gallego, J. L.; Rangel-Pineros, G.; Reyes, A. Computational Tools for the
Analysis of Uncultivated Phage Genomes. *Microbiol. Mol. Biol. Rev.* **2022**, *86* (2), e00004-21.
https://doi.org/10.1128/mmbr.00004-21.

(14) Kieft, K.; Zhou, Z.; Anantharaman, K. VIBRANT: Automated Recovery, Annotation and Curation
of Microbial Viruses, and Evaluation of Viral Community Function from Genomic Sequences.
Microbiome **2020**, *8* (1), 90. https://doi.org/10.1186/s40168-020-00867-0.

(15) Hegarty, B.; Dai, Z.; Raskin, L.; Pinto, A.; Wigginton, K.; Duhaime, M. A Snapshot of the Global
Drinking Water Virome: Diversity and Metabolic Potential Vary with Residual Disinfectant Use.
Water Res. **2022**, *218*, 118484. https://doi.org/10.1016/j.watres.2022.118484.

(16) Gregory, A. C.; Zayed, A. A.; Conceição-Neto, N.; Temperton, B.; Bolduc, B.; Alberti, A.; Ardyna,
M.; Arkhipova, K.; Carmichael, M.; Cruaud, C.; Dimier, C.; Domínguez-Huerta, G.; Ferland, J.;
Kandels, S.; Liu, Y.; Marec, C.; Pesant, S.; Picheral, M.; Pisarev, S.; Poulain, J.; Tremblay, J.-É.;
Vik, D.; Acinas, S. G.; Babin, M.; Bork, P.; Boss, E.; Bowler, C.; Cochrane, G.; de Vargas, C.;

Follows, M.; Gorsky, G.; Grimsley, N.; Guidi, L.; Hingamp, P.; Iudicone, D.; Jaillon, O.; Kandels-
Lewis, S.; Karp-Boss, L.; Karsenti, E.; Not, F.; Ogata, H.; Pesant, S.; Poulton, N.; Raes, J.; Sardet,
C.; Speich, S.; Stemmann, L.; Sullivan, M. B.; Sunagawa, S.; Wincker, P.; Babin, M.; Bowler, C.;
Culley, A. I.; de Vargas, C.; Dutilh, B. E.; Iudicone, D.; Karp-Boss, L.; Roux, S.; Sunagawa, S.;
Wincker, P.; Sullivan, M. B. Marine DNA Viral Macro- and Microdiversity from Pole to Pole. *Cell*
2019, *177* (5), 1109-1123.e14. https://doi.org/10.1016/j.cell.2019.03.040.

(17) Rocha, U. N. da; Kasmanas, J. C.; Kallies, R.; Saraiva, J. P.; Toscan, R. B.; Štefanič, P.; Bicalho,
M. F.; Correa, F. B.; Baştürk, M. N.; Fousekis, E.; Barbosa, L. M. V.; Plewka, J.; Probst, A. J.;
Baldrian, P.; Stadler, P. F.; Consortium, C.-T. MuDoGeR: Multi-Domain Genome Recovery from
Metagenomes Made Easy. bioRxiv August 11, 2022, p 2022.06.21.496983.
https://doi.org/10.1101/2022.06.21.496983.

(18) Vik, D.; Gazitúa, M. C.; Sun, C. L.; Zayed, A. A.; Aldunate, M.; Mulholland, M. R.; Ulloa, O.;
Sullivan, M. B. Genome-Resolved Viral Ecology in a Marine Oxygen Minimum Zone. *Environ.*
Microbiol. **2021**, *23* (6), 2858–2874. https://doi.org/10.1111/1462-2920.15313.

(19) Zhou, Z.; Martin, C.; Kosmopoulos, J. C.; Anantharaman, K. ViWrap: A Modular Pipeline to
Identify, Bin, Classify, and Predict Viral–Host Relationships for Viruses from Metagenomes. *iMeta*
n/a (n/a), e118. https://doi.org/10.1002/imt2.118.

(20) Pandolfo, M.; Telatin, A.; Lazzari, G.; Adriaenssens, E. M.; Vitulo, N. MetaPhage: An Automated
Pipeline for Analyzing, Annotating, and Classifying Bacteriophages in Metagenomics Sequencing
Data. *mSystems* **2022**, *7* (5), e00741-22. https://doi.org/10.1128/msystems.00741-22.

(21) Ru, J.; Khan Mirzaei, M.; Xue, J.; Peng, X.; Deng, L. ViroProfiler: A Containerized Bioinformatics
Pipeline for Viral Metagenomic Data Analysis. *Gut Microbes* **2023**, *15* (1), 2192522.
https://doi.org/10.1080/19490976.2023.2192522.

(22) Guo, J. VirSorter 2 Database, 2022. https://doi.org/10.5281/zenodo.4297575.

(23) DeLong, E. F.; Preston, C. M.; Mincer, T.; Rich, V.; Hallam, S. J.; Frigaard, N.-U.; Martinez, A.;
Sullivan, M. B.; Edwards, R.; Brito, B. R.; Chisholm, S. W.; Karl, D. M. Community Genomics
Among Stratified Microbial Assemblages in the Ocean's Interior. *Science* **2006**, *311* (5760), 496–
503. https://doi.org/10.1126/science.1120250.

(24) Al-Shayeb, B.; Sachdeva, R.; Chen, L.-X.; Ward, F.; Munk, P.; Devoto, A.; Castelle, C. J.; Olm, M.
R.; Bouma-Gregson, K.; Amano, Y.; He, C.; Méheust, R.; Brooks, B.; Thomas, A.; Lavy, A.;
Matheus-Carnevali, P.; Sun, C.; Goltsman, D. S. A.; Borton, M. A.; Sharrar, A.; Jaffe, A. L.;
Nelson, T. C.; Kantor, R.; Keren, R.; Lane, K. R.; Farag, I. F.; Lei, S.; Finstad, K.; Amundson, R.;
Anantharaman, K.; Zhou, J.; Probst, A. J.; Power, M. E.; Tringe, S. G.; Li, W.-J.; Wrighton, K.;
Harrison, S.; Morowitz, M.; Relman, D. A.; Doudna, J. A.; Lehours, A.-C.; Warren, L.; Cate, J. H.
D.; Santini, J. M.; Banfield, J. F. Clades of Huge Phages from across Earth's Ecosystems. *Nature*
2020, *578* (7795), 425–431. https://doi.org/10.1038/s41586-020-2007-4.

(25) Tisza, M. J.; Belford, A. K.; Domínguez-Huerta, G.; Bolduc, B.; Buck, C. B. Cenote-Taker 2
Democratizes Virus Discovery and Sequence Annotation. *Virus Evol.* **2021**, *7* (1), veaa100.
https://doi.org/10.1093/ve/veaa100.

(26) Nayfach, S.; Camargo, A. P.; Schulz, F.; Eloe-Fadrosh, E.; Roux, S.; Kyrpides, N. C. CheckV
Assesses the Quality and Completeness of Metagenome-Assembled Viral Genomes. *Nat.*
Biotechnol. **2021**, *39* (5), 578–585. https://doi.org/10.1038/s41587-020-00774-7.

(27) Ren, J.; Song, K.; Deng, C.; Ahlgren, N. A.; Fuhrman, J. A.; Li, Y.; Xie, X.; Poplin, R.; Sun, F.
Identifying Viruses from Metagenomic Data Using Deep Learning. *Quant. Biol.* **2020**, *8* (1), 64–77.
https://doi.org/10.1007/s40484-019-0187-4.

(28) Czeczko, P.; Greenway, S. C.; de Koning, A. P. J. EzMap: A Simple Pipeline for Reproducible
Analysis of the Human Virome. *Bioinforma. Oxf. Engl.* **2017**, *33* (16), 2573–2574.
https://doi.org/10.1093/bioinformatics/btx202.

(29) Amgarten, D.; Braga, L. P. P.; da Silva, A. M.; Setubal, J. C. MARVEL, a Tool for Prediction of
Bacteriophage Sequences in Metagenomic Bins. *Front. Genet.* **2018**, *9*.

(30) Antipov, D.; Raiko, M.; Lapidus, A.; Pevzner, P. A. MetaviralSPAdes: Assembly of Viruses from

Metagenomic Data. *Bioinformatics* **2020**, *36* (14), 4126–4129.
https://doi.org/10.1093/bioinformatics/btaa490.

(31) *MetaPhinder—Identifying Bacteriophage Sequences in Metagenomic Data Sets | PLOS ONE*.
https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0163111 (accessed 2023-05-08).

(32) Deaton, J.; Yu, F. B.; Quake, S. R. Mini-Metagenomics and Nucleotide Composition Aid the
Identification and Host Association of Novel Bacteriophage Sequences. *Adv. Biosyst.* **2019**, *3* (11),
1900108. https://doi.org/10.1002/adbi.201900108.

(33) Arndt, D.; Grant, J. R.; Marcu, A.; Sajed, T.; Pon, A.; Liang, Y.; Wishart, D. S. PHASTER: A
Better, Faster Version of the PHAST Phage Search Tool. *Nucleic Acids Res.* **2016**, *44* (W1), W16–
W21. https://doi.org/10.1093/nar/gkw387.

(34) Starikova, E. V.; Tikhonova, P. O.; Prianichnikov, N. A.; Rands, C. M.; Zdobnov, E. M.; Ilina, E.
N.; Govorun, V. M. Phigaro: High-Throughput Prophage Sequence Annotation. *Bioinformatics*
2020, *36* (12), 3882–3884. https://doi.org/10.1093/bioinformatics/btaa250.

(35) Fang, Z.; Tan, J.; Wu, S.; Li, M.; Xu, C.; Xie, Z.; Zhu, H. PPR-Meta: A Tool for Identifying Phages
and Plasmids from Metagenomic Fragments Using Deep Learning. *GigaScience* **2019**, *8* (6),
giz066. https://doi.org/10.1093/gigascience/giz066.

(36) Liu, F.; Miao, Y.; Liu, Y.; Hou, T. RNN-VirSeeker: A Deep Learning Method for Identification of
Short Viral Sequences From Metagenomes. *IEEE/ACM Trans. Comput. Biol. Bioinform.* **2022**, *19*
(3), 1840–1849. https://doi.org/10.1109/TCBB.2020.3044575.

(37) Auslander, N.; Gussow, A. B.; Benler, S.; Wolf, Y. I.; Koonin, E. V. Seeker: Alignment-Free
Identification of Bacteriophage Genomes by Deep Learning. *Nucleic Acids Res.* **2020**, *48* (21),
e121. https://doi.org/10.1093/nar/gkaa856.

(38) Li, Y.; Wang, H.; Nie, K.; Zhang, C.; Zhang, Y.; Wang, J.; Niu, P.; Ma, X. VIP: An Integrated
Pipeline for Metagenomics of Virus Identification and Discovery. *Sci. Rep.* **2016**, *6*, 23774.
https://doi.org/10.1038/srep23774.

(39) Tampuu, A.; Bzhalava, Z.; Dillner, J.; Vicente, R. ViraMiner: Deep Learning on Raw DNA
Sequences for Identifying Viral Genomes in Human Samples. *PLOS ONE* **2019**, *14* (9), e0222271.
https://doi.org/10.1371/journal.pone.0222271.

(40) Ren, J.; Ahlgren, N. A.; Lu, Y. Y.; Fuhrman, J. A.; Sun, F. VirFinder: A Novel k-Mer Based Tool
for Identifying Viral Sequences from Assembled Metagenomic Data. *Microbiome* **2017**, *5* (1), 69.
https://doi.org/10.1186/s40168-017-0283-5.

(41) Garretto, A.; Hatzopoulos, T.; Putonti, C. VirMine: Automated Detection of Viral Sequences from
Complex Metagenomic Samples. *PeerJ* **2019**, *7*, e6695. https://doi.org/10.7717/peerj.6695.

(42) Zheng, T.; Li, J.; Ni, Y.; Kang, K.; Misiakou, M.-A.; Imamovic, L.; Chow, B. K. C.; Rode, A. A.;
Bytzer, P.; Sommer, M.; Panagiotou, G. Mining, Analyzing, and Integrating Viral Signals from
Metagenomic Data. *Microbiome* **2019**, *7* (1), 42. https://doi.org/10.1186/s40168-019-0657-y.

(43) Abdelkareem, A. O.; Khalil, M. I.; Elaraby, M.; Abbas, H.; Elbehery, A. H. A. VirNet: Deep
Attention Model for Viral Reads Identification. In *2018 13th International Conference on Computer*
Engineering and Systems (ICCES); 2018; pp 623–626.
https://doi.org/10.1109/ICCES.2018.8639400.

(44) Wommack, K. E.; Bhavsar, J.; Polson, S. W.; Chen, J.; Dumas, M.; Srinivasiah, S.; Furman, M.;
Jamindar, S.; Nasko, D. J. VIROME: A Standard Operating Procedure for Analysis of Viral
Metagenome Sequences. *Stand. Genomic Sci.* **2012**, *6* (3), 421–433.
https://doi.org/10.4056/sigs.2945050.

(45) Rampelli, S.; Soverini, M.; Turroni, S.; Quercia, S.; Biagi, E.; Brigidi, P.; Candela, M. ViromeScan:
A New Tool for Metagenomic Viral Community Profiling. *BMC Genomics* **2016**, *17*, 165.
https://doi.org/10.1186/s12864-016-2446-3.

(46) Roux, S.; Enault, F.; Hurwitz, B. L.; Sullivan, M. B. VirSorter: Mining Viral Signal from Microbial
Genomic Data. *PeerJ* **2015**, *3*, e985. https://doi.org/10.7717/peerj.985.

(47) Miao, Y.; Liu, F.; Hou, T.; Liu, Y. Virtifier: A Deep Learning-Based Identifier for Viral Sequences
from Metagenomes. *Bioinformatics* **2022**, *38* (5), 1216–1222.

https://doi.org/10.1093/bioinformatics/btab845.

(48) Zhao, G.; Wu, G.; Lim, E. S.; Droit, L.; Krishnamurthy, S.; Barouch, D. H.; Virgin, H. W.; Wang, D. VirusSeeker, a Computational Pipeline for Virus Discovery and Virome Composition Analysis. *Virology* **2017**, *503*, 21–30. https://doi.org/10.1016/j.virol.2017.01.005.

(49) Glickman, C.; Hendrix, J.; Strong, M. Simulation Study and Comparative Evaluation of Viral Contiguous Sequence Identification Tools. *BMC Bioinformatics* **2021**, *22* (1), 329. https://doi.org/10.1186/s12859-021-04242-0.

(50) Ho, S. F. S.; Wheeler, N. E.; Millard, A. D.; van Schaik, W. Gauge Your Phage: Benchmarking of Bacteriophage Identification Tools in Metagenomic Sequencing Data. *Microbiome* **2023**, *11* (1), 84. https://doi.org/10.1186/s40168-023-01533-x.

(51) Menzel, P.; Ng, K. L.; Krogh, A. Fast and Sensitive Taxonomic Classification for Metagenomics with Kaiju. *Nat. Commun.* **2016**, *7* (1), 11257. https://doi.org/10.1038/ncomms11257.

(52) Guo, J.; Vik, D.; Pratama, A. A.; Roux, S.; Sullivan, M. Viral Sequence Identification SOP with VirSorter2. **2021**.

(53) Chicco, D.; Jurman, G. The Advantages of the Matthews Correlation Coefficient (MCC) over F1 Score and Accuracy in Binary Classification Evaluation. *BMC Genomics* **2020**, *21*, 6. https://doi.org/10.1186/s12864-019-6413-7.

(54) Camargo, A. P.; Roux, S.; Schulz, F.; Babinski, M.; Xu, Y.; Hu, B.; Chain, P. S. G.; Nayfach, S.; Kyrpides, N. C. You Can Move, but You Can't Hide: Identification of Mobile Genetic Elements with GeNomad. bioRxiv March 6, 2023, p 2023.03.05.531206. https://doi.org/10.1101/2023.03.05.531206.

(55) Roux, S.; Enault, F.; Robin, A.; Ravet, V.; Personnic, S.; Theil, S.; Colombet, J.; Sime-Ngando, T.; Debroas, D. Assessing the Diversity and Specificity of Two Freshwater Viral Communities through Metagenomics. *PloS One* **2012**, *7* (3), e33641. https://doi.org/10.1371/journal.pone.0033641.

(56) Elbehery, A. H. A.; Deng, L. Insights into the Global Freshwater Virome. *Front. Microbiol.* **2022**, *13*.

(57) Gabrielli, M.; Dai, Z.; Delafont, V.; Timmers, P. H. A.; van der Wielen, P. W. J. J.; Antonelli, M.; Pinto, A. J. Identifying Eukaryotes and Factors Influencing Their Biogeography in Drinking Water Metagenomes. *Environ. Sci. Technol.* **2023**, *57* (9), 3645–3660. https://doi.org/10.1021/acs.est.2c09010.