Pretrainable Geometric Graph Neural Network for Antibody Affinity Maturation

Huiyu Cai[1,2,3†], Zuobai Zhang[2,3†], Mingkai Wang[5,6†], Bozitao Zhong[2,3†], Quanxiao Li[5,6], Yuxuan Zhong[5,6], Yanling Wu[5,6*], Tianlei Ying[5,6*] and Jian Tang[1,2,4*]

[1]BioGeometry, Office 1505, 8 Haidianbeierjie St., Beijing, 100083, China.

[2]Mila - Québec AI Institute, 6666 St-Urbain, Montréal, H2S 3H1, Québec, Canada.

[3]Department of Computer Science and Operations Research, Université de Montréal, 2920 chemin de la Tour, Montréal, H3T 1J4, Québec, Canada.

[4]Department of Decision Sciences, HEC Montréal, 3000 chemin de la Côte-Sainte-Catherine, Montréal, H3T 2A7, Québec, Canada.

[5]Shanghai Engineering Research Center for Synthetic Immunology, Fudan University, 131 Dong'an Street, Shanghai, 200032, China.

[6]MOE/NHC/CAMS Key Laboratory of Medical Molecular Virology, Shanghai Frontiers Science Center of Pathogenic Microorganisms and Infection, Shanghai Institute of Infectious Disease and Biosecurity, School of Basic Medical Sciences, Fudan University, 131 Dong'an Street, Shanghai, 200032, China.

*Corresponding author(s). E-mail(s): yanlingwu@fudan.edu.cn; tlying@fudan.edu.cn; tangjian@biogeom.com;
Contributing authors: huiyu.cai@mila.quebec; zuobai.zhang@mila.quebec; 20111010061@fudan.edu.cn; bozitao.zhong@mila.quebec; 20111010055@fudan.edu.cn; 20301030072@fudan.edu.cn;
†These authors contributed equally to this work.

Abstract

Increasing the binding affinity of an antibody to its target antigen is a crucial task in antibody therapeutics development. This paper presents a pretrainable geometric graph neural network, GearBind, and explores its potential in *in silico* affinity maturation. Leveraging multi-relational graph construction, multi-level geometric message passing and contrastive pretraining on mass-scale, unlabeled protein structural data, GearBind outperforms previous state-of-the-art approaches on SKEMPI and an independent test set. We then derive a powerful ensemble model based on GearBind and use it to optimize the affinity of two antibodies with distinct formats and target antigens. The affinity of CR3022 against the spike (S) protein of the SARS-CoV-2 Omicron strain is increased by up to 17-fold, and the affinity of a fully human single-domain antibody (UdAb) against 5T4 by up to 5.6-fold. These promising results underscore the utility of geometric deep learning and effective pretraining in macromolecule interaction modeling tasks.

Keywords: GearBind, Geometric Deep Learning, Contrastive pretraining, Antibody Affinity Maturation, Computational Biology

1 Introduction

Antibody plays a crucial role in the human immune system and serves as a powerful diagnostic and therapeutic tool, due to its ability to bind selectively and specifically to target antigens with high affinity. *In vivo*, antibodies go through affinity maturation, where the target-binding affinity gradually increases as a result of somatic hypermutation and clonal selection [1]. When a new antigen surfaces, therapeutic antibody leads repurposed from known antibodies or screened from a natural or *de novo* designed library often require *in vitro* affinity maturation to enhance their binding affinity to a desired, usually sub-nanomolar, level.

Wet lab experimental methods for *in vitro* antibody affinity maturation usually involve constructing mutant libraries and screening with display technology [2–5]. These methods, while significantly improved during the past few years, are still labor-intensive and costly in general, taking 2-3 months or more to complete the process. Let's consider the combinatorial search space of possible mutations. There are usually 50-60 residues on the complementarity-determining region (CDR) of an antibody, which are hypervariable *in vivo* and contribute to the majority of the binding free energy ΔG_{bind} [6]. Previous works show that multiple point mutations are often needed for successful affinity maturation [7, 8]. Performing experiments on all combinations of the $\sim$1000 possible point mutations in CDR region per antibody (60 residues $\times$ 19 residues per residue) is difficult if not prohibitive. Therefore, a fast and accurate computational method for narrowing down the search space is much desired.

Nevertheless, it is nontrivial for computational affinity maturation methods to balance speed and accuracy. Molecular dynamics methods based on empirical force fields [9–12] rely on human knowledge and abstractions to evaluate binding free energy changes after mutations. However, accurate models are often too slow to be used for ranking thousands of mutations (let alone their combinations). In recent years, machine learning, and particularly deep learning, has been demonstrated as a powerful tool capable of tackling this dilemma. Many machine learning methods [13–18] formulate the affinity maturation problem as a structure-based binding free energy change ($\Delta\Delta G_{\text{bind}} := \Delta G_{\text{bind}}^{(\text{mt})} - \Delta G_{\text{bind}}^{(\text{wt})}$, where *wt* is short for *wild type* and *mt* denotes *mutant*) prediction problem. However, despite the importance of protein side-chain conformation to protein-protein interaction, most existing methods either disregard atom-level geometric information or model it indirectly. These approaches inadequately address the intricate interplay between side-chain atoms. Another critical problem is the massive amount of paired data required by machine learning models for them to become accurate and reliable. To the best of our knowledge, the largest publicly available protein-protein binding free energy change dataset, Structural Kinetic and Energetic database of Mutant Protein Interactions (SKEMPI) v2.0 [19], contains only 7085 $\Delta\Delta G_{\text{bind}}$ measurements on 348 protein complexes, a tiny amount compared to the training set sizes of foundational deep learning models such as AlphaFold2 [20] and ESM2 [21].

To tackle the aforementioned challenges, we introduce GearBind, a deep neural network that leverages multi-level geometric message passing to model the nuanced protein-protein interactions. We also utilize contrastive pretraining techniques on large-scale protein structural dataset to incorporate vital structural insights into the model (Fig. 1). *In silico* experiments on SKEMPI and an independent test set demonstrate the superior performance of GearBind and the benefit of pretraining. We combine the GearBind models with previous state-of-the-art methods to create an ensemble model that achieves state-of-the-art performance on all metrics. Ablation study confirms the importance of key design choices within GearBind and the crucial role it played in the ensemble. We then use the GearBind-based ensemble to perform in silico affinity maturation for two antibodies with distinct formats and target antigens. ELISA binding assays indicate an up to 17-fold increase in CR3022 binding to the spike (S) protein of the Omicron SARS-CoV-2 variant, after synthesizing and testing only 20 antibody candidates. Binding of the single-domain antibody UdAb against the oncofetal antigen 5T4 is increased up to 5.6 fold after testing 12 candidates. These results underscore the importance of geometric deep learning and effective pretraining on antibody affinity maturation and, more generally, macromolecule interaction modeling.

2 Results

2.1 GearBind: a pretrainable $\Delta\Delta G_{\mathrm{bind}}$ predictor

The GearBind framework is designed to extract geometric representations from wild-type and mutant structures via multi-level and multi-relational message passing to predict the binding free energy change $\Delta\Delta G_{\mathrm{bind}}$. GearBind leverages information within a protein complex at three different levels with complementary insights, namely, atom-level information holding precise spatial and chemical characteristics, edge-level information capturing angular relationships, and residue-level information highlighting broader context within the protein complex. Merging these distinct yet interconnected tiers of information allows for a more holistic view of protein complexes and has the potential to substantially enhance the predictive capabilities of binding affinity change.

More formally, when a protein complex structure is input to GearBind, a multi-relational interface atom graph is first constructed to model the detailed interactions within the complex. The relations defined cover both sequential proximity (for atoms on the same chain) and spatial proximity (which includes k-nearest-neighbor and within-r-radius relations). Atom-level representations are obtained by applying a geometric relational graph neural network (Gear-Net [22]) on the interface graph. On top of that, a line graph is constructed by treating each edge in the atom graph as a line node, connecting adjacent line nodes, and encoding the angular information as line edge features. Edge-level interactions are then captured by performing message passing on the line graph, similar to a sparse version of AlphaFold's triangle attention [20]. Finally, after aggregating atom and edge representations for each residue, a geometric graph attention layer is applied to pass messages between residues. This *multi-level message passing* scheme injects multi-granularity structural information into the learned representations, making it highly useful for the task of $\Delta\Delta G_{\mathrm{bind}}$ prediction.

Although GearBind can be trained from scratch on labeled $\Delta\Delta G_{\mathrm{bind}}$ datasets, it could suffer from overfitting or poor generalization if the training data size is limited. To address this problem, we propose a self-supervised pre-training task to exploit large-scale unlabeled protein structures in CATH [22, 23]. In the pretraining stage, the encoder is trained to model the distribution of the native protein structures via noise contrastive estimation [24]. Specifically, we maximize the probability (*i.e.* push down the energy) of native CATH proteins while minimizing the probability of mutant structures (Fig. 1c) generated by randomly mutating residues and sampling side-chain torsional angles from a rotamer library [25]. Distinguishing native, stable protein structures from sampled mutant structures pushes the model to understand side-chain interaction patterns, which are crucial to protein-protein binding. Through this process, meaningful knowledge from single-chain protein structural data could be transferred to benefit protein-protein binding modelling.

2.2 Cross Validation on SKEMPI

We validated GearBind performance via a split-by-complex, five-fold validation on SKEMPI v2.0. This splitting strategy dictates that each test set share no common PDB complex with its corresponding training set, which is more realistic than the split-by-mutation strategy, where the wild-type protein complexes and even the mutation sites in the test set could appear during training. We compared GearBind and GearBind+P (pretrained GearBind fine-tuned on SKEMPI) to state-of-the-art physics-based tools FoldX [9], Flex-ddG [10] and deep learning method Bind-ddG [8]. The results (Table 1) show that GearBind, with its multi-relational graph construction and multi-level message passing schemes, outperforms the baselines in terms of MAE, RMSE and PearsonR, while seconds FoldX in terms of SpearmanR. Adding contrastive pretraining to GearBind brings further improvements in performance, resulting in +5.4% SpearmanR, +2.6% PearsonR, −2.4% MAE and −1.7% RMSE, highlighting the effective knowledge transfer from mass-scale, unlabelled protein structural data.

To understand the contributions of key architectural design choices in GearBind, we benchmarked the performance of 5 GearBind variants on SKEMPI. As shown in 2e, the tested GearBind variants perform worse than GearBind on all four metrics. The exclusion of edge- and residue-level message passing from GearBind brings a 13% and 3% SpearmanR drop, highlighting the benefits of combining multi-level information during feature extraction. The exclusion of side-chain atoms from the interface graph hurts performance even more (15% SpearmanR drop), showing the importance of explicitly modeling the full-atom structure. Notably, replacing the multi-relational interface graph with a KNN graph results in a severe 23% SpearmanR decline, while training a simple RGCN model on the multi-relational graphs results in performance on par with Bind-ddG (−9% SpearmanR compared to GearBind, +2% compared to Bind-ddG). This suggests that the multi-relational graph construction strategy is a key ingredient in GearBind.

Table 1: Cross validation performance of different methods on SKEMPI ($n = 5729$). For each metric, we report the mean and standard error of the mean. "+P" means "with geometric pretraining". MAE: Mean average error. RMSE: root mean square error.

Model	MAE↓	RMSE↓	PearsonR↑	SpearmanR↑
FoldX [9]	1.364 ± 0.134	2.027 ± 0.170	0.491 ± 0.007	$\mathbf{0.526 \pm 0.011}$
Flex-ddG [10]	1.236 ± 0.101	1.849 ± 0.150	0.497 ± 0.034	0.484 ± 0.020
Bind-ddG [8]	1.255 ± 0.096	1.759 ± 0.125	0.581 ± 0.037	0.443 ± 0.041
GearBind	$\underline{1.143 \pm 0.088}$	$\underline{1.639 \pm 0.103}$	$\underline{0.659 \pm 0.030}$	0.498 ± 0.033
GearBind+P	$\mathbf{1.115 \pm 0.072}$	$\mathbf{1.611 \pm 0.075}$	$\mathbf{0.676 \pm 0.041}$	$\underline{0.525 \pm 0.046}$
Ensemble	$\mathbf{1.028 \pm 0.080}$	$\mathbf{1.503 \pm 0.101}$	$\mathbf{0.729 \pm 0.016}$	$\mathbf{0.643 \pm 0.030}$

2.3 A GearBind-based ensemble for in silico affinity maturation

To understand the behavior of the benchmarked models on SKEMPI, we binned the SKEMPI dataset by the target difficulty and plotted the PearsonR and SpearmanR of each model on targets with different difficulty levels. PDB codes in SKEMPI are categorized into "easy" (50+ similar data points in training set), "medium" (1-50), and "hard" (0) targets based on the number of training data points having a high structural similarity (TM-score [26] > 0.8) to it. Deep learning models, namely Bind-ddG, GearBind and GearBind+P, enjoys superior performance compared to physics-based methods such as FoldX and Flex-ddG on easy targets, but the table turns when we move to the hard targets (Fig. 2a,b), showing room for improvement in their generalization capabilities. We also studied the performance on mutations that cause low (< 0.5), medium ($0.5 - 2$) and high (> 2) absolute changes in binding free energy. As Fig. S9 shows, all models perform better when the binding level changes more drastically. GearBind achieves outstanding performance in this region, with a PearsonR value of 0.707, compared to FoldX's 0.411, showing its potential of identifying mutations that could significantly increase the binding affinity. When the $|\Delta\Delta G_{\text{bind}}|$ is small, predictions from all methods have very low correlation with experimental $\Delta\Delta G_{\text{bind}}$ values. This could be due to the noises in data or a deficiency of current tools in modeling weaker interactions.

To combine the advantages of both physics-based and deep learning methods, we used the ensemble of all benchmarked methods to perform subsequent *in silico* affinity maturation. The prediction of the ensemble model is the simple average of prediction values from FoldX, Flex-ddG, GearBind, GearBind+P and Bind-ddG. The proposed ensemble model outperforms each individual model in all four evaluation metrics (Table 1). We evaluated the contribution of individual models to the ensemble by excluding each of them and evaluating performance on SKEMPI. The results (Fig. 2f) show that excluding GearBind and GearBind+P hurts overall performance the most. Specifically, for the PearsonR metric, the exclusion of FoldX, Flex-ddG and Bind-ddG individually results in a marginal (less than 0.01) decrease, but the removal of GearBind causes a significant (more than 0.08) decline. We also note that, while FoldX is not the best-performing model when used in isolation, removing it from the ensemble results in the biggest SpearmanR drop. This shows that FoldX plays an important role in complementing the deep learning models and forging a robust and accurate ensemble model.

2.4 Evaluation on the HER2 binders test set

With the models built and trained (on SKEMPI), we tested their performance on the HER2 binders test set, which we collected from [27]. This dataset contains high-quality binding affinity data, measured by surface plasmon resonance (SPR) on 419 HER2 binders with *de novo* designed CDR loops. The antibodies in the dataset are variants of Trastuzumab but have high edit

distance (7.6 on average), making them potentially challenging for $\Delta\Delta G_{\text{bind}}$ predictors trained on low-edit-distance data. Among the benchmarked methods (Flex-ddG is not benchmarked due to its high time cost), GearBind+P achieve the best PearsonR and SpearmanR (Fig. 2c). We then averaged the predictions of all benchmarked models to form an ensemble model, and excluded each model from the ensemble to measure the performance change. Similarly, we found that excluding GearBind(+P) hurts PearsonR the most, and excluding FoldX hurts SpearmanR the most, with GearBind(+P) closely following (Fig. 2d).

2.5 Affinity Maturation of CR3022 and anti-5T4 UdAb

To validate the efficacy of our methodology, two antibodies, CR3022 and anti-5T4 UdAb, were selected as subjects for affinity maturation. The CR3022 antibody, originally isolated from a convalescent SARS patient [28], has been subsequently identified to bind to SARS-CoV-2 [29, 30]. This binding affinity towards the SARS-CoV-2 receptor-binding domain (RBD) remains consistently robust and largely unaffected by prevalent RBD mutations. Meanwhile, a fully human single-domain antibody (UdAb) directed against the oncofetal antigen 5T4, is characterized by its exceptional stability [31]. Through this selection strategy we aim to comprehensively evaluate the applicability of the proposed pipeline across distinct formats and target antigens. Note that both antigens have only one structurally similar protein chain (TM-score > 0.8) with a different binding site in SKEMPI, making them decently challenging targets for our pipeline (Fig. S14, S15).

For CR3022, a total of 12 mutants were picked out in the first round experimental validation according to the ensemble prediction of their binding affinity against the RBDs of the wild-type, BA.1.1, and BA.4 SARS-CoV-2 strains. We note that the wild-type and Delta RBDs share the same amino acids at the epitope region. In the pre-experiment, we tested the binding affinity of these mutants to the RBD of SARS-CoV-2 Delta strain with the antigen concentration at 100 nM. 9 of the 12 candidates exhibited improved binding affinities than the wild-type CR3022 (Fig. S16a). In the further validation with reduced RBD concentration at 10 nM, the EC_{50} values for all 9 candidates were lower than the wild-type CR3022 (Fig. 3a, b). Based on the results, we combined the well-performed CR3022 mutations and synthesized 8 candidates with double or triple mutations as our second round designs. Seven of the eight designed multi-point mutants exhibited enhanced binding ability against the Delta RBD, with 1.8 to 3.4 fold stronger binding compared to the wild-type (via indirect ELISA as a proxy for binding affinities). The triple mutant SH100D+SH103Y+SL33R has the lowest EC_{50} at 0.06 nM (Fig. 3c, d). Against the Omicron Spike protein, the above seven multi-point mutants again displayed 7.6 to 17.0 fold binding increase with sub-nanomolar EC_{50} values, among which the SH100D+SH103Y+SL33R triple mutant still exhibited the best performance (Fig. 3e, f). We next tested the binding of the mutants designed in the second-round against RBD of SARS-CoV, the original target

of CR3022, to examine if optimization of binding against SARS-CoV-2 RBDs caused a drastic change in binding to SARS-CoV RBD. Experiment results show that 7 out of 8 mutants did not exhibit a significant change in the binding affinity against SARS-CoV RBD (Fig. 3g, h). In summary, the above results demonstrate the success of our GearBind-based pipeline in CR3022 antibody affinity optimization.

To demonstrate the generalizability of our method, we extended our experimental validation to encompass a fully-human single-domain antibody, UdAb, which targets the oncofetal antigen 5T4 [31]. We developed 12 single-point mutants using the GearBind-based pipeline and employed ELISA to verify their binding affinity to 5T4. The highest binding of UdAb improved by 5.6-fold with S57W mutation. This substantial improvement highlights the potential of our approach in enhancing antibody affinity, making it a promising tool for therapeutic antibody development.

2.6 Structural Characteristics of Optimized Antibodies

Understanding the sequence-structure-function relationship of mutations designed using deep learning not only advances our modeling capabilities but also aids in interpreting their biological significance, shedding light on the underlying principles governing antibody-antigen binding. To explore this, we carried out molecular dynamics simulations and structural analyses on both the wild-type and mutant antibodies with the highest binding affinities. As detailed in the experimental results in Section 2.5, we focused on the triple mutant CR3022 antibody with mutations SH100D, SH103Y, SL33R, which demonstrated the highest binding affinity for both the Delta and Omicron variants. For the anti-5T4 UdAb, we selected the S57W mutant, which exhibited the highest binding affinity. We conducted a 300 ns all-atom molecular dynamics simulation at room temperature for each system, including their respective wild-type counterparts (see Methods for details).

Based on the simulation results, we discovered that new interactions from the mutated residues to the target antigen likely contribute to the increased binding affinity. Of the four mutations, three demonstrated an increased number of hydrogen bonds with the target: SH100D and SL33R from CR3022, and S57W from UdAb (Fig. 4g, h). These three mutations in CR3022 also stabilize the antibody and its binding residues in the receptor-binding domain (RBD), as evidenced by reduced fluctuations in the corresponding residues' Cα atoms (Fig. S20). Although the S103Y mutation in the heavy chain of CR3022 does not increase polar contacts, it potentially enhances hydrophobic interactions between the antibody and antigen by excluding more solvent due to the larger size of tyrosine. We also observe changes in the local dihedral angle distributions, especially for mutation S100D (Fig. S22). In summary, the mutations designed by our pipeline likely achieve higher binding affinity through the formation of new interactions. We also observed stabilized binding residues and altered structural properties in the mutated structures.

Interestingly, GearBind's contribution as displayed in the corresponding figure further provided insight into the formation of potential contacts for these designed mutations (Fig. S24). The contribution obtained using the GearBind tool was found to be consistent with our deductions based on the protein structure, thereby corroborating our findings. The possible hydrophobic interaction in S103Y was also presented in the contributions, providing further validation to our findings and aligning well with our deductions based on protein structure (Fig. S24c).

Our findings underscore the importance of understanding the structural and functional relationships of mutations in the antibody-antigen binding process. This knowledge could prove valuable in the development of more effective therapeutic strategies.

3 Discussion

This study reports an *in silico* antibody maturation pipeline based on a pretrainable geometric graph neural network, GearBind, and the efficient and successful application of the pipeline on two distinct antibodies, CR3022 and anti-5T4 UdAb. Substantial *in silico* experiments were done to evaluate model performance and understand their strengths and limitations. The technical strengths of the proposed GearBind model can be summarized as follows: (1) In the graph construction phase, a multi-relational graph is built upon all heavy atoms on the interface. The relations defined cover both sequential proximity (for atoms on the same chain) and spatial proximity (which includes k-nearest-neighbor and within-r-radius relations). Replacing the all-atom graph to backbone-atom-only graph, or replacing the multi-relational graph to a simple kNN graph both cause severe performance decline. (2) In the feature extraction phase, a multi-level message passing scheme is employed to obtain a comprehensive view on the intricate interactions at protein interfaces. (3) A unique pretraining algorithm based on contrastive learning is proposed, which harnesses the abundant, unlabeled single-chain protein structures in CATH, distills knowledge about side-chain torsion angles and native protein structures into the model to further boost its performance.

We challenged our GearBind-based pipeline with two real-world antibody affinity maturation projects. ELISA binding assays showed that CR3022 mutations proposed by the pipeline have led to successful enhancements in binding against both the Delta RBD and the Omicron Spike protein. Notably, 7 out of 10 single-point mutations and 9 out of 10 multiple mutations showed a significant increase in binding, with up to 3.8-fold binding increase for the Delta RBD and 17.0-fold for the Omicron Spike protein. Another trial involving the anti-5T4 UdAb demonstrated that, utilizing GearBind designs, we engineered 12 single-point mutants which achieved a maximum increase in binding affinity of 5.6 times. Thus, GearBind proves to be an efficient and powerful tool for the design of antibodies with enhanced binding affinities. Based on the molecular dynamics simulations of the top-performing mutants identified by

GearBind, we observed that GearBind-designed mutations enhanced binding affinity by creating new interactions or strengthening existing contacts, particularly hydrogen bonds. This provides insight into how GearBind learns from data and designs mutations that increase binding affinity.

While we mainly focus on structure-based methods in this work, others have explored purely sequence-based models for affinity maturation [32]. Our evaluation of the employed ESM-1b and ESM-1v models on SKEMPI (Table S4 and Fig. S12) suggests that zero-shot prediction of large-scale protein language models can enhance affinity and stability in some cases, but it is not yet a generally reliable method for ranking the binding affinity of protein complexes. These findings underscore the crucial role that structure plays in building a reliable model for protein-protein interaction.

Looking ahead, the potential applications of GearBind reach beyond protein-protein binding optimization. The model can be readily adapted to tackle protein-peptide and protein-ligand docking challenges, thereby opening up possibilities for its use in minibinder and enzyme design.

Despite these promising prospects, we acknowledge certain limitations in our current methodology and discuss potential directions for future work. Firstly, the prerequisite for structure-based $\Delta\Delta G_{\mathrm{bind}}$ prediction is an accurate complex structure, which is not easily available for most antibody-antigen pairs. To address this problem, homology modeling tools [33] can be used to build the complex structure from a template structure. This is how we built the complex structure of CR3022 binding to the Omicron RBDs. A more aggressive approach is to directly predict the complex structure from the sequence. As multimer structure prediction methods become more and more accurate [34], they might one day become reliable as the starting point of structure-based affinity maturation. Secondly, the reliance on external tools for mutant structure generation increases the time cost, and limits our action space to substitutions only. Future efforts can focus on training end-to-end models that directly predict the $\Delta\Delta G_{\mathrm{bind}}$, and models that can account for amino acid insertion and deletion. We also call for better pretraining strategy and architecture design to improve the generalization capabilities of deep learning models, making them more robust on proteins they have not seen before. All in all, we believe our work is a solid step towards building a reliable, robust and efficient *in silico* affinity maturation pipeline that would bring tremendous opportunities to research and drug discovery applications.

4 Methods

4.1 Datasets

SKEMPI

We used the SKEMPI v2 [19] dataset for training and validation. The dataset contains 7,085 $\Delta\Delta G_{\text{bind}}$ measurements on 348 complexes. We performed pre-processing following [13, 18], discarding data with ambiguous $\Delta\Delta G_{\text{bind}}$ values (e.g. the mutant is a non-binder without exact K_D measurements) or high $\Delta\Delta G_{\text{bind}}$ variance across multiple measurements ($> 1 \, \text{kcal/mol}$), and arrived at 5,729 distinct mutations, with their $\Delta\Delta G_{\text{bind}}$ measurements, on 340 complexes. For each mutation, we sampled the mutant structure with FoldX 4 [9] based on the wild-type crystal structure. We used PDBFixer v1.8 [35] to fix the PDB structures beforehand if the raw structure could not be processed by FoldX. These FoldX-derived SKEMPI structures are used to train deep learning models, including Bind-ddG, GearBind and GearBind+P. The resulting dataset was split into five subsets with roughly the same size using a split-by-PDB strategy, in order to perform cross validation.

CATH

For pretraining, we use a non-redundant subset of CATH v4.3.0 domains, which contains 30,948 experimental protein structures with less than 40% sequence identity. We also remove proteins that exceed 2,000 AAs in length for efficiency. During pretraining, we randomly truncate long sequences into 150 AAs for efficiency. It is important to note that, currently, our pretraining exclusively utilizes single-chain proteins. The information learned by single-chain pretraining can be transferred to downstream tasks on protein complexes and we have found that this approach alone is sufficient to yield improvement.

HER2 binders

The HER2 binders test set was collected from [27]. The raw data include SPR data for 758 binders and 1097 non-binders. As all benchmarked methods only support amino acid substitutions, we filter out the binders that have different lengths compared to the wild-type antibody (Trastuzumab), leaving 419 Trastuzumab mutants. $\Delta\Delta G_{\text{bind}}$ values are calculated by $\Delta\Delta G_{\text{bind}} = -RT \ln \left(K_D^{(\text{mt})} / K_D^{(\text{wt})} \right)$ based on the SPR-measured binding affinity. Note that we only use this dataset as a test set to evaluate physics-based models (FoldX, Flex-ddG) and deep learning models (Bind-ddG, GearBind and GearBind+P) trained on SKEMPI.

4.2 GearBind implementation

Given a pair of wild-type and mutant structures, GearBind predicts the binding free energy change $\Delta\Delta G_{\text{bind}}$ by building a geometric encoder on a multi-relational graph, which is further enhanced by self-supervised pre-training. Note that the key feature that makes the neural network *geometric* is

434 that it considers the spatial relationship between entities, *i.e.*, nodes in a graph.
435 In the following sections, we will discuss the construction of multi-relational
436 graphs, multi-level message passing and pre-training methods.

4.2.1 Constructing relational graphs for protein complex structures

Given a protein-protein complex, we construct a multi-relational graph for
its interface and discard all other atoms. Here a residue is considered on the
interface if its Euclidean distance to the nearest residue from the binding
partner is no more than 6Å. Each atom on the interface is regarded as a node
in the graph. We add three types of edges to represent different interactions
between these atoms. For two atoms with a sequential distance lower than 3, we
add a **sequential edge** between them, the type of which is determined by their
relative position in the protein sequence. For two atoms with spatial distance
lower than 5Å, we add a **radial edge** between them. Besides, each atom is
also linked to its **10-nearest neighbors** to guarantee the connectivity of the
graph. Spatial edges that connect two atoms adjacent in the protein sequence
are not interesting and thus discarded. The relational graph is denoted as
$(\mathcal{V}, \mathcal{E}, \mathcal{R})$ with $\mathcal{V}$, $\mathcal{E}$, $\mathcal{R}$ denoting the sets of nodes, edges and relation types,
respectively. We use the tuple (i, j, r) to denote the edge between atom i and j
with type r. We use one-hot vectors of residues types and atom types as node
features for each atom and further include sequential and spatial distances in
edge features for each edge.

4.2.2 Building geometric encoder by multi-level message passing

On top of the constructed interface graph, we now perform multi-level message
passing to model interactions between connected atoms, edges and residues. We
use $\boldsymbol{a}_i^{(l)}$ and $\boldsymbol{e}_{(j,i,r)}^{(l)}$ to denote the representations of node i and edge (j, i, r) at
the l-th layer. Specially, we use $\boldsymbol{a}_i^{(0)}$ to denote the node feature for atom i and
$\boldsymbol{e}_{(j,i,r)}^{(0)}$ to denote the edge feature for edge (j, i, r). Then, the representations
are updated by the following procedures:

$$\boldsymbol{a}_i^{(l)} \leftarrow \text{AtomMP}(\boldsymbol{a}_i^{(l-1)}), \tag{1}$$

$$\boldsymbol{e}_{(j,i,r)}^{(l)} \leftarrow \text{EdgeMP}(\boldsymbol{e}_{(j,i,r)}^{(l-1)}), \tag{2}$$

$$\boldsymbol{a}_i^{(l)} \leftarrow \boldsymbol{a}_i^{(l)} + \text{AGGR}(\boldsymbol{e}_{(j,i,r)}^{(l)}), \tag{3}$$

$$\boldsymbol{a}_{\text{C}\alpha(i)}^{(l)} \leftarrow \boldsymbol{a}_{\text{C}\alpha(i)}^{(l)} + \text{ResAttn}(\boldsymbol{a}_{\text{C}\alpha(i)}^{(l)}). \tag{4}$$

458 First, we perform atom-level message passing (AtomMP) on the atom graph.
459 Then, a line graph is constructed for the message passing between edges
460 (EdgeMP) so as to learn effective representations between atom pairs. The

edge representations are used to update atom representations via an aggregation function (AGGR). Finally, we take the representations $\boldsymbol{a}^{(l)}_{\text{C}\alpha(i)}$ of the alpha carbon as residue representation and perform a residue-level attention mechanism (ResAttn), which can be seen as a special kind of message passing on a fully-connected graph. In the following paragraphs, we will discuss these components in details.

Atom-level message passing

Following GearNet [22], we use a relational graph neural network (RGCN) [36] to pass messages between atoms. In a message passing step, each node aggregates messages from its neighbors to update its own representation. The message is computed as the output of a relation (edge type)-specific linear layer when applied to the neighbor representation. Formally, the message passing step is defined as:

$$\text{AtomMP}(\boldsymbol{a}^{(l-1)}_i) = \boldsymbol{a}^{(l-1)}_i + \sigma\left(\text{BN}\left(\sum\nolimits_{r\in\mathcal{R}} \boldsymbol{W}^{(a)}_r \sum\nolimits_{(j,i,r)\in\mathcal{E}} \boldsymbol{a}^{(l-1)}_j\right)\right),$$

where $\text{BN}(\cdot)$ denotes batch norm and $\sigma(\cdot)$ is the ReLU activation function.

Edge-level message passing and aggregation

Modeling sequential proximity or spatial distance alone is not enough for capturing the complex protein-protein interactions (PPI) contributing to binding. Multiple works have demonstrated the benefits of incorporating angular information using edge-level message passing [20, 22, 37]. Here we construct a line graph [38], *i.e.* a relational graph among all edges of the above atom-level graph. Two edges are connected if and only if they share a common end node. The relations, or edge types, are defined as the angle between the atom-level edge pair, discretized into 8 bins. We use $(\mathcal{V}', \mathcal{E}', \mathcal{R}')$ to denote the constructed line graph. Then, relational message passing is used on the line graph:

$$\text{EdgeMP}(\boldsymbol{e}^{(l-1)}_x) = \sigma\left(\text{BN}\left(\sum\nolimits_{r'\in\mathcal{R}'} \boldsymbol{W}^{(e)}_{r'} \sum\nolimits_{(y,x,r')\in\mathcal{E}'} \boldsymbol{e}^{(l-1)}_y\right)\right),$$

where x and y denote edge tuples in the original graph for abbreviation.

Once we updated the edge representations, we aggregate them into its end nodes. These representations are fed into a linear layer and multiplied with the edge type-specific kernel matrix $\boldsymbol{W}^{(a)}_r$ in AtomMP:

$$\text{AGGR}(\boldsymbol{e}^{(l)}_{(j,i,r)}) = \sigma\left(\text{BN}\left(\sum\nolimits_{r\in\mathcal{R}} \boldsymbol{W}^{(a)}_r \sum\nolimits_{(j,i,r)\in\mathcal{E}} \text{Linear}(\boldsymbol{e}^{(l)}_{(j,i,r)})\right)\right),$$

which will be used to update the representation for atom i as in equation 3.

Residue-level message passing

Constrained by the computational complexity, atom and edge-level message passing only consider sparse interactions while ignoring global interactions between all pairs of residues. By modeling a coarse-grained view of the interface at the residue level, we are able to perform message passing between all pairs of residues. To do this, we design a geometric graph attention mechanism, which takes the representations of the alpha carbon of residues as input and updates their representations with the output as in equation 4. Here we follow the typical definition of self-attention to calculate attention logits with query and key vectors and apply the probability on the value vectors to get residue representations $\boldsymbol{r}_i$:

$$\alpha_{ij} = \mathrm{Softmax}_j\left(\frac{1}{d}\cdot\mathrm{Linear}_q(\boldsymbol{a}^{(l)}_{\mathrm{C}\alpha(i)})\cdot\mathrm{Linear}_k(\boldsymbol{a}^{(l)}_{\mathrm{C}\alpha(j)})\right),$$

$$\boldsymbol{r}^{(l)}_i = \sum_j \alpha_{ij}\cdot\mathrm{Linear}_v(\boldsymbol{a}^{(l)}_{\mathrm{C}\alpha(i)}),$$

where d is the hidden dimension of the representation $\boldsymbol{a}^{(l)}_{\mathrm{C}\alpha(i)}$ and the Softmax function is taken over all j.

Besides traditional self-attention, we also include geometric information in the attention mechanism, which should be invariant to roto-translational transformations on the global complex structure. Therefore, we construct a local frame for each residue with coordinates of its Nitrogen, Carbon and alpha Carbon atoms:

$$\boldsymbol{v}_{i1} = \boldsymbol{x}_{\mathrm{N}(i)} - \boldsymbol{x}_{\mathrm{C}\alpha(i)},$$

$$\boldsymbol{v}_{i2} = \boldsymbol{x}_{\mathrm{C}(i)} - \boldsymbol{x}_{\mathrm{C}\alpha(i)},$$

$$\boldsymbol{u}_{i1}, \boldsymbol{u}_{i2} = \mathrm{GramSchmidt}(\boldsymbol{v}_{i1}, \boldsymbol{v}_{i2})$$

$$\boldsymbol{R}_i = \left[\frac{\boldsymbol{u}_{i1}}{\|\boldsymbol{u}_{i1}\|}, \frac{\boldsymbol{u}_{i2}}{\|\boldsymbol{u}_{i2}\|}, \frac{\boldsymbol{u}_{i1}}{\|\boldsymbol{u}_{i1}\|} \times \frac{\boldsymbol{u}_{i2}}{\|\boldsymbol{u}_{i2}\|}\right],$$

where we use $\boldsymbol{x}$ to denote the coordinate of an atom and GramSchmidt($\cdot$) refers to the Gram–Schmidt process for orthogonalization. Then, the geometric attention is designed to model the relative position of beta carbons of all residues j in the local frame of residue i:

$$\boldsymbol{p}^{(l)}_i = \sum_j \alpha_{ij}\boldsymbol{R}^\top_i(\boldsymbol{x}_{\mathrm{C}\alpha(i)} - \boldsymbol{x}_{\mathrm{C}\beta(j)}),$$

where $\boldsymbol{p}^{(l)}_i$ is the spatial representations for the residue i. When the complex structure is rotated, the frame $\boldsymbol{R}_i$ and relative position $\boldsymbol{x}_{\mathrm{C}\alpha(i)} - \boldsymbol{x}_{\mathrm{C}\beta(j)}$ are rotated accordingly and the effects will be counteracted, which guarantees the rotation invariance of our model.

The final output is the concatenation of residue representations $\boldsymbol{r}_i^{(l)}$ and spatial representations $\boldsymbol{p}_i^{(l)}$:

$$\text{ResAttn}(\boldsymbol{a}_{\text{C}\alpha(i)}^{(l)}) = \text{Concat}(\boldsymbol{r}_i^{(l)}, \boldsymbol{p}_i^{(l)}).$$

After obtaining representations for each atom, we apply a mean pooling layer over representations of all alpha carbons $\boldsymbol{a}_{\text{C}\alpha(i)}$ to get protein representations $\boldsymbol{h}$. An anti-symmetric prediction head is then applied to guarantee that back mutations would have the exact opposite predicted $\Delta\Delta G_{\text{bind}}$ values:

$$\widetilde{\Delta\Delta G_{\text{bind}}} = \text{MLP}(\boldsymbol{h}^{(\text{wt})}, \boldsymbol{h}^{(\text{mt})}) - \text{MLP}(\boldsymbol{h}^{(\text{mt})}, \boldsymbol{h}^{(\text{wt})}), \tag{5}$$

where $\boldsymbol{h}^{(\text{wt})}$ and $\boldsymbol{h}^{(\text{mt})}$ denote the representations for wild type and mutant complexes and $\widetilde{\Delta\Delta G_{\text{bind}}}$ is the predicted $\Delta\Delta G_{\text{bind}}$ from our GearBind model.

4.2.3 Modeling energy landscape of proteins via noise contrastive estimation.

As paired binding free energy change data is of relatively small size, it would be beneficial to pretrain GearBind with massive protein structural data. The high-level idea of our pretraining method is to model the distribution of native protein structures, which helps identify harmful mutations yielding unnatural structures. Denoting a protein structure as $\boldsymbol{x}$, its distribution can be modeled with Boltzmann distribution as:

$$p(\boldsymbol{x};\boldsymbol{\theta}) = \frac{\exp(-E(\boldsymbol{x};\boldsymbol{\theta}))}{A(\boldsymbol{\theta})}, \ A(\boldsymbol{\theta}) = \int \exp(-E(\boldsymbol{x};\boldsymbol{\theta}))d\boldsymbol{x}, \tag{6}$$

where $\boldsymbol{\theta}$ denotes learnable parameters in our encoder, $E(\boldsymbol{x};\boldsymbol{\theta})$ denotes the energy function for the protein x and $A(\boldsymbol{\theta})$ is the partition function to normalize the distribution. The energy function is predicted by applying a linear layer on the GearBind representations $\boldsymbol{h}(\boldsymbol{x})$ of protein $\boldsymbol{x}$:

$$E(\boldsymbol{x};\boldsymbol{\theta}) = \text{Linear}(\boldsymbol{h}(\boldsymbol{x})). \tag{7}$$

Given the observed dataset $\{\boldsymbol{x}_1, ..., \boldsymbol{x}_T\}$ from PDB, our objective is to maximize the probability of these samples:

$$\text{maximize} \ \ \frac{1}{2T}\sum_t \log p(\boldsymbol{x}_t;\boldsymbol{\theta}). \tag{8}$$

However, direct optimization of this objective is intractable, since calculating the partition function requires integration over the whole protein structure space. To address this issue, we adopt a popular method for learning energy-based models called noise contrastive estimation [24]. For each observed structure $\boldsymbol{x}_t$, we sample a negative structure $\boldsymbol{y}_t$ and then the problem can be

transformed to a binary classification task, *i.e.*, whether a sample is observed in the dataset or not.

$$\text{minimize} \quad \frac{1}{2T} \sum_t \log\left[\sigma(E(\boldsymbol{x}_t;\ \boldsymbol{\theta}) - E(\boldsymbol{y}_t;\ \boldsymbol{\theta}))\right], \tag{9}$$

where $\sigma(\cdot)$ denotes the sigmoid function for calculating the probability for a sample $\boldsymbol{x}_t$ belonging to the positive class. We could see that the above training objective tries to push down the energy of the positive examples (*i.e.* the observed structures) while pushing up the energy of the negative samples (*i.e.* the mutant structures.

For negative sampling, we perform random single-point mutations on the corresponding positive samples and then generate its conformation by keeping the backbone unchanged and sampling side-chain torsional angles at the mutation site from a backbone-dependent rotamer library [25]. Besides, to further enhance the model's capability to distinguish structural noises, we randomly choose 30% residues to randomly rotate torsional angles when generating negative samples.

After pretraining on the CATH database, we finetune the GearBind encoder on downstream tasks for prediction to avoid overfitting.

4.3 Cross Validation on SKEMPI.

During cross validation, a model is trained and tested five times, each time using a different subset as the test set and the remaining four subsets as the training set. Results are calculated for each test set, and their mean and standard error of mean are reported as the final cross validation performance. During the process of cross-validation, each individual data point is incorporated into the test set precisely once. This ensures that a comprehensive "test result table" is compiled, which includes predictive values for each data point when it is part of the test set. Subsequent performance analysis are done by splitting this table by various criteria and evaluate performance on each subset.

After cross validation on SKEMPI, we obtain five sets of model parameters. During inference, we use the mean of the predicted values of these five checkpoints as the model prediction result.

4.4 Baseline implementation details.

FoldX.

In this work, we use FoldX 4 [9] for mutant structure generation. First, each PDB file is processed with the RepairPDB command for structural corrections. Then, the wild-type, mutant structure pair is built using the BuildModel command. We use the AnalyseComplex command to get the FoldX $\Delta\Delta G_{\text{bind}}$ prediction based on the wild-type and mutant structures.

Flex-ddG.

We run Flex-ddG with its official implementation at https://github.com/Kortemme-Lab/flex_ddG_tutorial. Each PDB file is processed with PDBFixer v1.8 [35]. Using the default parameters, we sample 35 structure models for each mutation, with the number of backrub trails set to 35000 and the energy function set to fa_talaris2014. The final $\Delta\Delta G_{\mathrm{bind}}$ values are predicted with a generalized additive model that reweights the score terms.

GearBind(+P).

We implement GearBind with the TorchDrug library [39]. For message passing, we employed a 4-layer GearBind model with a hidden dimension of 128. Regarding edge message passing, the connections between edges are categorized into 8 bins according to the angles between them. To predict the $\Delta\Delta G_{\mathrm{bind}}$ value from graph representations, we utilized a 2-layer MLP.

The model was trained using the Adam optimizer with a learning rate of 1e-4 and a batch size of 8. The training process is performed on 1 A100 GPU for 40 epochs. For pretraining, we use the same architecture with 4-layer GearBind model with a hidden dimension of 128. The pretraining was conducted using the Adam optimizer with a learning rate of 5e-4 and a batch size of 8, employing 4 A100 GPUs for 10 epochs.

Bind-ddG.

To ensure a fair comparison, we re-implement and re-train the Bind-ddG model on our SKEMPI splits. We following the configuration of the original implementation to set the dimensions of hidden and pair representations at 128 and 64, respectively. Our validation performance indicates that the optimal configuration for our setup includes a two-layer geometric attention mechanism and a four-layer MLP predictor. We trained the model using an Adam optimizer with a learning rate of 1e-4 and a batch size of 8, on a single A400 GPU, for a total of 40 epochs.

4.5 In silico affinity maturation of CR3022 and anti-5T4 UdAb

PDB 6XC3 [40], in which chains H and L comprise antibody CR3022 and chain C is the SARS-CoV-2 RBD, was chosen as the starting complex for CR3022 affinity maturation. To better simulate the CR3022 interaction with Omicron RBD, we constructed the complex structures for BA.4 and BA.1.1 mutants with SWISS-MODEL [33]. We then performed saturation mutagenesis on the CDRs of CR3022 and generated mutant structures using FoldX [9] and Flex-ddG [10]. Specifically, residues 26-35, 50-66, 99-108 from the heavy chain H and residues 24-40, 56-62, 95-103 from the light chain L are mutated. This totals 1400 single-point mutations (if we count the self-mutations). We use our ensemble model to rank the mutations and select the top-ranked mutants for synthesis and subsequent experimental validation. Mutations are ranked by

the modified z-score (where values are subtracted by the median rather than the mean to be less sensitive to outliers) averaged across multiple $\Delta\Delta G_{\text{bind}}$ prediction methods.

An unpublished complex structure was used to optimize anti-5T4 UdAb. As the single-domain antibody binding two distinct epiopes on 5T4 (Fig. 4b), anti-5T4 UdAb has a larger interface region compared to traditional antibodies. After analyzing its interface with 5T4, we decided to perform saturation mutagenesis on residues 1,3,25,27-30,31-33,39-45,52-57,59,91-93,95,99,100-102,103,105,110,112,115-117. This totals 780 single-point mutations (if we count the self-mutations) that goes through the same ranking and selection strategies as described above.

4.6 Antigen preparation

The gene encoding SARS-CoV RBD was synthesized by Genscript (Nanjing, China) and subcloned into pSectag 2B vector with C-terminal human IgG1 Fc fragment and AviTag. The recombinant vector was transfected to Expi 293 cells and cultured at 37°C for 5 days, followed by centrifugation at 4,000 rpm for 20 minutes. The supernatant was harvested and filtered through a 0.22 μm vacuum filter. The protein G resin (Genscript) was loaded into the column, washed by PBS, and flow the supernatant through to fully combine the resin. Then the targeted protein was eluted with 0.1 M glycine (pH 3.0) and neutralized with 1 M Tris-HCL (pH 9.0), followed by buffer-exchanged and concentrated with phosphate buffered saline (PBS) using an Amicon ultra centrifugal concentrator (Millipore) with a molecular weight cut-off of 3 kDa. Protein concentration was measured using the NanoDrop 2000 spectrophotometer (Thermo Fisher), and protein purity was examined by sodium dodecyl sulfate-polyacrylamide gel electrophoresis (SDS-PAGE). The Delta RBD protein was purchased from Vazyme (Nanjing, China) and Omicron S protein was purchased from ACROBiosystems (Beijing, China). The human TPBG/5T4-Fc antigen was purchased from ACROBiosystems (Beijing, China).

4.7 Preparation for mutant and wild-type CR3022 antibodies

The heavy chain and light chain genes of different CR3022 antibodies were synthesized and subcloned into expression vector pcDNA 3.4 in IgG1 format. These constructed vectors were transfected into CHO cells and purified by Protein A. All antibodies were produced by Biointron Biological Inc. (Shanghai, China).

4.8 Generation of mutant and wild-type anti-5T4 UdAbs

The pComb3x vector encoding the gene of wild-type anti-5T4 UdAb was constructed in previous work and preserved in our laboratory. All anti-5T4 UdAb mutants with single-point mutation were constructed with QuickMutation™

Site-directed Gene Mutagenesis Kit (Beyotime, Shanghai, China) following the manufacturer's protocol. The expression of different mutant and wild-type anti-5T4 UdAbs were performed in *E. coli* HB2151 bacterial culture at 30°C for 16 h accompanied by 1 mM isopropyl b-D-1-thiogalactopyranoside (IPTG). The cells were harvested and lysed by polymyxin B at 30°C for 0.5 h, followed by centrifugation at 8,000 rpm for 10 minutes. The supernatant was collected, filtered through 0.8 μm polyethersulphone membranes by sterile syringes and purified by Ni-NTA (Smart Lifesciences) following the manufacturer's instructions. Briefly, the filtered supernatant was loaded over the column with Ni-NTA. The resin was washed by washing buffer (10 mM Na2HPO4, 10 mM NaH2PO4 [pH 7.4], 500 mM NaCl, and 20 mM imidazole), and proteins were eluted in elution buffer (10 mM Na2HPO4, 10 mM NaH2PO4 [pH 7.4], 500 mM NaCl, and 250 mM imidazole). The collected pure fractions were immediately buffer exchanged into PBS and concentrated with Amicon ultra centrifugal concentrators (Millipore). Protein concentration was measured using the NanoDrop 2000 spectrophotometer (Thermo Fisher), and protein purity was examined by SDS-PAGE.

4.9 Enzyme-linked immunosorbent assay (ELISA)

For comparison of different CR3022 mutants, the receptor-binding domain (RBD) of Delta (B.1.617.2) strain and spike (S) protein of Omicron (B.1.1.529) strain at 100 ng per well was coated in 96 wells half area microplates (Corning #3690) overnight at 4 °C. The antigen coated plate was washed by three times with PBST (PBS with 0.05% Tween-20) and blocked with 3% MPBS (PBS with 3% skim milk) at 37 °C for 1 h. Following three times washing with PBST, 50 μL of three-fold serially diluted antibody in 1% MPBS was added and incubated at 37 °C for 1.5 h. The HRP-conjugated anti-Fab and anti-Fc (Sigma-Aldrich) secondary antibodies were used for the detection of different tested antibodies. After washing with PBST for 5 times, the enzyme activity was measured after the addition of ABTS substrate (Invitrogen) for 15 min. The data was acquired by measuring the absorbance at 405 nm using a Microplate Spectrophotometer (Biotek) and the EC_{50} (concentration for 50% of maximal effect) was calculated by GraphPad Prism8.0 software. To verify different UdAb mutants, the same experimental protocol as mentioned above was adopted. Briefly, the human TPBG/5T4-Fc antigen was coated in 96 wells half area microplates, then blocked with 3% MPBS and added serial diluted antibodies. The HRP-conjugated anti-Flag (Sigma-Aldrich) secondary antibody was used, followed by adding ABTS substrate and detected at 405 nm. The reported EC_{50} value is the mean value from three duplicates on a single experiment.

4.10 Protein structure analysis

Protein structure analysis is conducted by python scripts. The antibody-antigen complex structure after mutation was obtained from Rosetta Flex-ddG

relaxation [10]. The relaxed protein structure can provide more accurate side chain conformations, which are critical for accurate contact and conformational analysis. The improved accuracy of such analyses enables a deeper understanding of the underlying binding mechanisms and can facilitate the identification of key characteristics involved in protein-protein interactions. The attribution scores are derived by using Integrated Gradients (IG) [41], a model-agnostic attribution method, on our model to obtain residue-level interpretation following [22]. All protein structure figures are created with PyMOL v3.0.

4.11 Molecular dynamics simulation

For antibody mutation structural analysis, we conducted molecular dynamics simulation of wild type and mutant antibody-antigen complex. Initial structures were taken from the Rosetta Flex-ddG relaxed structures used by GearBind. The LEaP module in the AMBER 22 suite was used for build starting structures and adding ions and solvent for simulation [42]. All systems were neutralized and solvated in boxes of water with TIP4P-Ew [43] solvent model. All bonds involving hydrogen atoms were constrained with the SHAKE algorithm [44]. The particle mesh Ewald (PME) algorithm was used to calculate long-range electrostatic interactions [45]. Initial structures were relaxed with maximum 10,000 steps of minimization before convergence, then subjected to heating for 20 ps and equilibration for 10 ps in the NPT ensemble with PMEMD. The CUDA version of PMEMD was used to accelerate the simulations [46]. The simulation temperature were set to room temperature 298K. All systems were simulated for 300 ns production MD, and samples in the first 50 ns were not used for analysis. CPPTRAJ module in AMBERTools were used to analysis the simulation results, including calculating root mean square deviation (RMSD), room mean square fluctuation (RMSF), hydrogen bonding, and dihedral angle [47].

4.12 Data & Code Availability

The raw SKEMPI database can be accessed via https://life.bsc.es/pid/skempi2. The CSV file of the processed SKEMPI dataset can be downloaded from Supplementary Material 2. The CATH database can be accessed via https://www.cathdb.info/. The raw HER2 binders data can be accessed via https://github.com/AbSciBio/unlocking-de-novo-antibody-design/blob/main/spr-controls.csv. We plan to make the code along with the trained model checkpoints publicly available upon acceptance of this paper.

References

[1] Victora, G.D., Nussenzweig, M.C.: Germinal centers. Annual review of immunology **40**, 413–442 (2022)

[2] Gram, H., Marconi, L.-A., Barbas 3rd, C., Collet, T.A., Lerner, R.A., Kang, A.S.: In vitro selection and affinity maturation of antibodies from a naive combinatorial immunoglobulin library. Proceedings of the National Academy of Sciences **89**(8), 3576–3580 (1992)

[3] Jackson, J.R., Sathe, G., Rosenberg, M., Sweet, R.: In vitro antibody maturation. improvement of a high affinity, neutralizing antibody against il-1 beta. Journal of immunology (Baltimore, Md.: 1950) **154**(7), 3310–3319 (1995)

[4] Li, B., Fouts, A.E., Stengel, K., Luan, P., Dillon, M., Liang, W.-C., Feierbach, B., Kelley, R.F., Hötzel, I.: In vitro affinity maturation of a natural human antibody overcomes a barrier to in vivo affinity maturation. In: MAbs, vol. 6, pp. 437–445 (2014). Taylor & Francis

[5] Wang, J., An, L., Zhao, Y., Zhang, C., Li, S., Ye, C., Jing, S., Hang, H.: In vitro affinity maturation of antibody against membrane-bound gpcr molecules. Applied microbiology and biotechnology **103**, 7703–7717 (2019)

[6] Murphy, K., Weaver, C.: Janeway's Immunobiology. Garland science, ??? (2016)

[7] Sulea, T., Hussack, G., Ryan, S., Tanha, J., Purisima, E.O.: Application of assisted design of antibody and protein therapeutics (adapt) improves efficacy of a clostridium difficile toxin a single-domain antibody. Scientific reports **8**(1), 2260 (2018)

[8] Shan, S., Luo, S., Yang, Z., Hong, J., Su, Y., Ding, F., Fu, L., Li, C., Chen, P., Ma, J., *et al.*: Deep learning guided optimization of human antibody against sars-cov-2 variants with broad neutralization. Proceedings of the National Academy of Sciences **119**(11), 2122954119 (2022)

[9] Delgado, J., Radusky, L.G., Cianferoni, D., Serrano, L.: Foldx 5.0: working with rna, small molecules and a new graphical interface. Bioinformatics **35**(20), 4168–4169 (2019)

[10] Barlow, K.A., Ó Conchúir, S., Thompson, S., Suresh, P., Lucas, J.E., Heinonen, M., Kortemme, T.: Flex ddg: Rosetta ensemble-based estimation of changes in protein–protein binding affinity upon mutation. The Journal of Physical Chemistry B **122**(21), 5389–5399 (2018)

[11] Park, H., Bradley, P., Greisen Jr., P., Liu, Y., Mulligan, V.K., Kim, D.E., Baker, D., DiMaio, F.: Simultaneous optimization of biomolecular energy functions on features from small molecules and macromolecules. Journal of chemical theory and computation **12**(12), 6201–6212 (2016)

[12] Frenz, B., Lewis, S.M., King, I., DiMaio, F., Park, H., Song, Y.: Prediction of protein mutational free energy: benchmark and sampling improvements increase classification accuracy. Frontiers in bioengineering and biotechnology **8**, 558247 (2020)

[13] Rodrigues, C.H., Myung, Y., Pires, D.E., Ascher, D.B.: mcsm-ppi2: predicting the effects of mutations on protein–protein interactions. Nucleic acids research **47**(W1), 338–344 (2019)

[14] Myung, Y., Rodrigues, C.H., Ascher, D.B., Pires, D.E.: mcsm-ab2: guiding rational antibody design using graph-based signatures. Bioinformatics **36**(5), 1453–1459 (2020)

[15] Petukh, M., Dai, L., Alexov, E.: Saambe: webserver to predict the charge of binding free energy caused by amino acids mutations. International journal of molecular sciences **17**(4), 547 (2016)

[16] Huang, X., Zheng, W., Pearce, R., Zhang, Y.: Ssipe: accurately estimating protein–protein binding affinity change upon mutations using evolutionary profiles in combination with an optimized physical energy function. Bioinformatics **36**(8), 2429–2437 (2020)

[17] Jiang, Y., Quan, L., Li, K., Li, Y., Zhou, Y., Wu, T., Lyu, Q.: Dgcddg: Deep graph convolution for predicting protein-protein binding affinity changes upon mutations. IEEE/ACM Transactions on Computational Biology and Bioinformatics (2023)

[18] Liu, X., Luo, Y., Li, P., Song, S., Peng, J.: Deep geometric representations for modeling effects of mutations on protein-protein binding affinity. PLoS computational biology **17**(8), 1009284 (2021)

[19] Jankauskaitė, J., Jiménez-García, B., Dapkūnas, J., Fernández-Recio, J., Moal, I.H.: SKEMPI 2.0: an updated benchmark of changes in protein–protein binding energy, kinetics and thermodynamics upon mutation. Bioinformatics **35**(3), 462–469 (2018) https://academic.oup.com/bioinformatics/article-pdf/35/3/462/27700009/bty635.pdf. https://doi.org/10.1093/bioinformatics/bty635

[20] Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K., Bates, R., Žídek, A., Potapenko, A., *et al.*: Highly accurate protein structure prediction with alphafold. Nature

596(7873), 583–589 (2021)

[21] Lin, Z., Akin, H., Rao, R., Hie, B., Zhu, Z., Lu, W., Smetanin, N., Verkuil,
R., Kabeli, O., Shmueli, Y., *et al.*: Evolutionary-scale prediction of atomic-
level protein structure with a language model. Science **379**(6637), 1123–
1130 (2023)

[22] Zhang, Z., Xu, M., Jamasb, A., Chenthamarakshan, V., Lozano, A.,
Das, P., Tang, J.: Protein representation learning by geometric structure
pretraining. arXiv preprint arXiv:2203.06125 (2022)

[23] Zhang, Z., Xu, M., Lozano, A., Chenthamarakshan, V., Das, P., Tang,
J.: Physics-inspired protein encoder pre-training via siamese sequence-
structure diffusion trajectory prediction. arXiv preprint arXiv:2301.12068
(2023)

[24] Gutmann, M., Hyvärinen, A.: Noise-contrastive estimation: A new esti-
mation principle for unnormalized statistical models. In: Proceedings
of the Thirteenth International Conference on Artificial Intelligence
and Statistics, pp. 297–304 (2010). JMLR Workshop and Conference
Proceedings

[25] Shapovalov, M.V., Dunbrack, R.L.: A smoothed backbone-dependent
rotamer library for proteins derived from adaptive kernel density estimates
and regressions. Structure **19**(6), 844–858 (2011)

[26] Zhang, Y., Skolnick, J.: Scoring function for automated assessment of
protein structure template quality. Proteins: Structure, Function, and
Bioinformatics **57**(4), 702–710 (2004)

[27] Shanehsazzadeh, A., Bachas, S., McPartlon, M., Kasun, G., Sutton,
J.M., Steiger, A.K., Shuai, R., Kohnert, C., Rakocevic, G., Gutierrez,
J.M., et al.: Unlocking de novo antibody design with generative artificial
intelligence. bioRxiv, 2023–01 (2023)

[28] Ter Meulen, J., Van Den Brink, E.N., Poon, L.L.M., Marissen, W.E.,
Leung, C.S.W., Cox, F., Cheung, C.Y., Bakker, A.Q., Bogaards, J.A.,
Van Deventer, E., *et al.*: Human monoclonal antibody combination
against sars coronavirus: synergy and coverage of escape mutants. PLoS
medicine **3**(7), 237 (2006)

[29] Tian, X., Li, C., Huang, A., Xia, S., Lu, S., Shi, Z., Lu, L., Jiang, S.,
Yang, Z., Wu, Y., Ying, T.: Potent binding of 2019 novel coronavirus
spike protein by a SARS coronavirus-specific human monoclonal antibody.
Emerg Microbes Infect **9**(1), 382–385 (2020)

[30] Yuan, M., Wu, N.C., Zhu, X., Lee, C.-C.D., So, R.T.Y., Lv, H., Mok,

C.K.P., Wilson, I.A.: A highly conserved cryptic epitope in the receptor binding domains of SARS-CoV-2 and SARS-CoV. Science **368**(6491), 630–633 (2020)

[31] Wu, Y., Li, Q., Kong, Y., Wang, Z., Lei, C., Li, J., Ding, L., Wang, C., Cheng, Y., Wei, Y., *et al.*: A highly stable human single-domain antibody-drug conjugate exhibits superior penetration and treatment of solid tumors. Molecular Therapy **30**(8), 2785–2799 (2022)

[32] Hie, B.L., Shanker, V.R., Xu, D., Bruun, T.U., Weidenbacher, P.A., Tang, S., Wu, W., Pak, J.E., Kim, P.S.: Efficient evolution of human antibodies from general protein language models. Nature Biotechnology **42**(2), 275–283 (2024)

[33] Waterhouse, A., Bertoni, M., Bienert, S., Studer, G., Tauriello, G., Gumienny, R., Heer, F.T., de Beer, T.A.P., Rempfer, C., Bordoli, L., *et al.*: Swiss-model: homology modelling of protein structures and complexes. Nucleic acids research **46**(W1), 296–303 (2018)

[34] Google DeepMind AlphaFold team and Isomorphic Labs team: Performance and structural coverage of the latest, in-development AlphaFold model. Accessed: 2024-02-01 (2023). https://storage.googleapis.com/deepmind-media/DeepMind.com/Blog/a-glimpse-of-the-next-generation-of-alphafold/alphafold_latest_oct2023.pdf

[35] Eastman, P.: PDBFixer. GitHub (2013)

[36] Schlichtkrull, M., Kipf, T.N., Bloem, P., Van Den Berg, R., Titov, I., Welling, M.: Modeling relational data with graph convolutional networks. In: European Semantic Web Conference, pp. 593–607 (2018). Springer

[37] Gasteiger, J., Groß, J., Günnemann, S.: Directional message passing for molecular graphs. In: International Conference on Learning Representations (ICLR) (2020)

[38] Harary, F., Norman, R.Z.: Some properties of line digraphs. Rendiconti del Circolo Matematico di Palermo **9**(2), 161–168 (1960). https://doi.org/10.1007/BF02854581

[39] Zhu, Z., Shi, C., Zhang, Z., Liu, S., Xu, M., Yuan, X., Zhang, Y., Chen, J., Cai, H., Lu, J., et al.: Torchdrug: A powerful and flexible machine learning platform for drug discovery. arXiv preprint arXiv:2202.08320 (2022)

[40] Yuan, M., Liu, H., Wu, N.C., Lee, C.-C.D., Zhu, X., Zhao, F., Huang, D., Yu, W., Hua, Y., Tien, H., *et al.*: Structural basis of a shared antibody response to sars-cov-2. Science **369**(6507), 1119–1123 (2020)

[41] Sundararajan, M., Taly, A., Yan, Q.: Axiomatic attribution for deep networks. In: International Conference on Machine Learning, pp. 3319–3328 (2017). PMLR

[42] Case, D.A., Cheatham III, T.E., Darden, T., Gohlke, H., Luo, R., Merz Jr, K.M., Onufriev, A., Simmerling, C., Wang, B., Woods, R.J.: The amber biomolecular simulation programs. Journal of computational chemistry **26**(16), 1668–1688 (2005)

[43] Horn, H.W., Swope, W.C., Pitera, J.W., Madura, J.D., Dick, T.J., Hura, G.L., Head-Gordon, T.: Development of an improved four-site water model for biomolecular simulations: Tip4p-ew. The Journal of chemical physics **120**(20), 9665–9678 (2004)

[44] Ryckaert, J.-P., Ciccotti, G., Berendsen, H.J.: Numerical integration of the cartesian equations of motion of a system with constraints: molecular dynamics of n-alkanes. Journal of computational physics **23**(3), 327–341 (1977)

[45] Darden, T., York, D., Pedersen, L.: Particle mesh ewald: An nlog (n) method for ewald sums in large systems. The Journal of chemical physics **98**(12), 10089–10092 (1993)

[46] Salomon-Ferrer, R., Gotz, A.W., Poole, D., Le Grand, S., Walker, R.C.: Routine microsecond molecular dynamics simulations with amber on gpus. 2. explicit solvent particle mesh ewald. Journal of chemical theory and computation **9**(9), 3878–3888 (2013)

[47] Roe, D.R., Cheatham III, T.E.: Ptraj and cpptraj: software for processing and analysis of molecular dynamics trajectory data. Journal of chemical theory and computation **9**(7), 3084–3095 (2013)

Fig. 1: **GearBind-based *in silico* antibody affinity maturation pipeline.** (a) Pipeline Overview: The pipeline features the geometric neural encoder, GearBind, which undergoes self-supervised pretraining on CATH and supervised learning on SKEMPIv2. The GearBind-based ensemble model is employed to perform *in silico* affinity maturation on a target antibody, given its bound structure to the native antigen. Guided by the model predictions, antibodies with improved binding affinity can be found after testing one or two dozen mutant candidates. NN: neural network. Ab: Antibody. CDR: Complementarity-determining region. (b) GearBind Model: GearBind employs a shared graph neural network to encode both the wild-type and mutant complex structures. For each structure, a relational interface graph is constructed. A geometric graph neural network, GearNet, then performs multi-relational and multi-level message passing on the graph to extract rich interface representations. The mutational effect $\Delta\Delta G_{\text{bind}}$ is predicted by an antisymmetric predictor given the GearNet-extracted representations of the two complexes. (c) Self-supervised Pretraining: GearBind+P leverages mass-scale unlabeled protein structures via self-supervised, contrastive pretraining. The model is trained to contrast between native structures and randomly mutated structures with side-chain torsion angles sampled from a rotamer library. Pretraining helps GearBind+P explore the energy landscape of native protein structures and results in improved performance in $\Delta\Delta G_{\text{bind}}$ prediction.

Fig. 2: *In silico* **evaluation on SKEMPI and the HER2 binders test set.** Comparative analysis of Per-PDB Spearman (a) and Pearson (b) correlations between predictions of various models and experimental data across SKEMPI subsets with varying difficulty levels. PDB codes in SKEMPI are categorized into "easy" (50+ similar data points in training set), "medium" (1-50), and "hard" (0) targets based on the number of training data points having a high structural similarity (TM-score > 0.8) to it. Outliers are determined by $1x$ inter-quartile range. (c) Benchmark results on the HER2 binders test set ($n = 419$) show Pearson and Spearman correlations for various models. The deep learning models are trained on SKEMPI. (d) Change of performance metrics in HER2 binders test set when excluding various models from the FoldX + Bind-ddG + GearBind(+P) ensemble. (e) Change of performance when changing GearBind architecture design, as quantified by cross validation performance on SKEMPI ($n = 5729$). (f) Change of performance on SKEMPI ($n = 5729$) when excluding different models from the FoldX + Flex-ddG + Bind-ddG + GearBind(+P) ensemble.

Fig. 3: **ELISA binding assay results for CR3022 and anti-5T4 UdAb mutants designed with a GearBind-based pipeline.** On the left panels (a, c, e, g, i), the concentration-response curves alongside with EC_{50} values evaluated from ELISA assays are displayed, with error bars indicating the standard error. On the right panels (b, d, f, h, j), the fold changes in binding affinity calculated as $EC_{50}^{(wt)}/EC_{50}^{(mt)}$ are plotted, with error bars indicating 95% CI. EC_{50} values are highlighted in white or gray, with binding fold changes marked in blue, green, and orange for different batches of antibodies tested. Tested systems include the first-round CR3022 designs binding to Delta RBD (a, b); the second-round CR3022 designs binding to Delta RBD (c, d), Omicron S protein (e, f) and SARS-RBD (g, h); and single point mutants of anti-5T4 UdAb (i, j) binding to 5T4.

Fig. 4: **Structural analysis of optimized CR3022 and anti-5T4 UdAbs.** (a) Complex structure of antibody CR3022 and the SARS-CoV-2 RBD used for affinity maturation. Target antigen is colored in red, and antibody in blue. Mutation sites S100D, S103Y in heavy chain and S33R in light chain are marked in orange. (b) Complex structure of the single-domain antibody UdAb and its target oncofetal antigen 5T4. Mutation site S57W is marked in orange. (c-e) Three mutation sites in the CR3022 triple-mutant, namely S100D (c), S103Y (d) in heavy chain and S33R (e) in light chain. (f) The S57W mutation site in the UdAb single-point mutant. (g) Depicts the number of hydrogen bonds between the mutation sites and target antigen in the molecular dynamics simulation of CR3022 and RBD complex. (h) Depicts the number of hydrogen bonds between mutation site and target antigen in the molecular dynamics simulation of UdAb and 5T4 complex. In (g,h), hydrogen bond distributions from wild types are colored in orange, and mutants are colored in green.