Whole-Brain Causal Discovery Using fMRI

Fahimeh Arab[1], AmirEmad Ghassami[2], Hamidreza Jamalabadi[3], Megan A. K. Peters[4,5,6], and Erfan Nozari[1,7,8,*]

[1]Department of Electrical and Computer Engineering, University of California, Riverside, USA
[2]Department of Mathematics and Statistics, Boston University, USA
[3]Department of Psychiatry and Psychotherapy, Phillips University of Marburg, Germany
[4]Department of Cognitive Sciences, University of California, Irvine, USA
[5]Center for the Neurobiology of Learning & Memory, University of California, Irvine, USA
[6]Program in Brain, Mind, & Consciousness, Canadian Institute for Advanced Research, Canada
[7]Department of Mechanical Engineering, University of California, Riverside, USA
[8]Department of Bioengineering, University of California, Riverside, USA
[*]Corresponding author (email: erfan.nozari@ucr.edu)

Abstract

Despite decades of research, discovering causal relationships from observational neuroimaging data such as fMRI remains a challenge. Popular algorithms such as Multivariate Granger Causality and Dynamic Causal Modeling fall short in handling complex aspects of data such as contemporaneous effects and latent common causes. Decades of research on causal structure learning have developed alternative algorithms that address these limitations, but they often scale poorly with the number of variables and rely heavily on the lack of cycles in the underlying graph. In this work, we first provide a detailed theoretical and numerical analysis of existing methods and compare their accuracy and efficiency on simulated fMRI from simple graph topologies, demonstrating the pressing need for more accurate and scalable algorithms. To address this gap, we propose Causal discovery for Large-scale Low-resolution Time-series with Feedback (CaLLTiF). CaLLTiF is based on Runge et al's PCMCI [1] and improves upon it in terms of computational efficiency, cyclic contemporaneous connections, and statistical type I error control. Using simulated fMRI from whole-brain macaque connectome, we show that CaLLTiF achieves significantly higher accuracy compared to existing algorithms in recovering the ground-truth connectivity. When applied to resting-state human fMRI ($n = 200$, Human Connectome Project), CaLLTiF learns causal connectomes that are highly consistent across individuals, show clear top-down flow of causal effect from attention and default mode networks to sensorimotor cortices, exhibit Euclidean distance-dependence in causal interactions, are highly dominated by contemporaneous effects, and demonstrate statistically significant laterality and gender differences. Overall, this work takes a major step forward in improving the accuracy and scalability of causal discovery from whole-brain fMRI and defines a new standard for future investigations into causal discovery from neuroimaging data. Python codes for all the analyses in the paper are publicly available at `https://github.com/nozarilab/2023Arab_CaLLTiF`.

Keywords: fMRI, causal discovery, brain networks, statistical algorithms, cognitive neuroscience

Introduction

A major step in the global drive for understanding the brain [2–6] is to move beyond correlations and understand the causal relationships among internal and external factors – a process often referred to as *causal discovery* [7,8]. When possible, causal discovery can be greatly simplified by intervening in one variable and observing the effect in others. However, such interventions are often costly and/or infeasible, necessitating the significantly more challenging task of causal discovery from purely observational data. A particularly rich set of observational data for the brain comes from functional MRI (fMRI) [9,10]. The whole-brain coverage allowed by fMRI is valuable for causal discovery not only because it allows for purely data-driven and unbiased discovery of potentially unexpected causal relationships [11–13], but also because of the great extent to which the presence of unobserved variables can complicate delineating causal adjacencies and orientations [14–

17]. Nevertheless, many characteristics of fMRI also make causal discovery challenging, including its large dimensionality, low temporal resolution, and indirect reflection of underlying neural processes [18]. This has motivated a large and growing body of literature on causal discovery from fMRI. A common approach for causal discovery using neuroimaging and neurophysiology data is Granger Causality (GC) [19]. GC has a long history in neuroscience [19, 20], but also has well-known limitations, including its lack of ability to account for contemporaneous causal relationships and the presence of latent nodes. The former is particularly important for fMRI. The temporal resolution in fMRI is typically within a few hundred milliseconds to several seconds [21], which is about one order of magnitude slower than the time that it takes for neural signals to travel across the brain [22–24]. Therefore, from one fMRI sample to the next, there is enough time for causal effects to flow between almost all pairs of nodes in the network (cf. a related in-depth discussion in [25, Appendix A]). Such fast sub-TR interactions demonstrate themselves as causal effects that appear to be "contemporaneous" and can even be cyclic, making causal discovery significantly more challenging (Supplementary Note 1). Similar to GC, Dynamic Causal Modeling (DCM) has also been widely used with fMRI data [26–29] and fundamentally relies on the temporal order of a generative dynamical model to infer causation from correlations, making it similarly unable to account for contemporaneous causal relationships [30–32].

Discovering causal relationships without reliance on time has been the subject of extensive research in the causal inference literature [7, 33–37]. A wide range of algorithmic solutions have been proposed [7, 18, 36, 38–45], which are often classified based on their methodology into constraint-based [33, 34, 46], noise-based [43, 47], and score-based [48, 49]. Nevertheless, which of these algorithms are suitable for whole-brain fMRI causal discovery and how they compare against each other in terms of accuracy and scalability have remained largely unknown.

In this study, we first discuss and compare existing causal discovery algorithms for their suitability for whole-brain fMRI analysis based on their theoretical characterizations and numerical performance on multiple simulated fMRI benchmarks. This discussion demonstrates a large gap between what causal discovery for fMRI needs and what existing algorithms can achieve. To address this gap, we propose the design of a new algorithm called *Causal discovery for Large-scale Low-resolution Time-series with Feedback (CaLLTiF)*. We demonstrate the higher accuracy of CaLLTiF against state-of-the-art algorithms in simulated fMRI and provide a case study of its performance on resting-state fMRI data from the Human Connectome Project (HCP) [50].

Results

A Taxonomy of Causal Discovery for Whole-Brain fMRI

A vast array of algorithmic solutions exist for learning causal graphs from observational data, but not all are suitable for fMRI data. We selected a subset of state-of-the-art algorithms suitable for whole-brain fMRI data based on four criteria: (1) ability to learn cycles, (2) ability to learn contemporaneous effects, (3) assuming complete coverage of relevant variables in observed data, and (4) linearity (see Discussions). Table 1 shows several state-of-the-art methods that satisfy criteria (1)-(4). Multivariate Granger Causality (MVGC) [20, 51] does not satisfy criteria (2), but we still included it in our subsequent analyses due to its popularity in neuroscience [52–55]. On the other hand, we excluded LiNG [56] from further analysis since it is considered by its proposers as generally inferior to the hybrid FASK algorithm [57]. We also chose FASK for implementation over GANGO [58], a similarly hybrid method with the additional caveat of not having a unified publicly available code distribution.

We compared the accuracy of the resulting list of algorithms (MVGC, PCMCI, PCMCI$^+$, VARLiNGAM, DYNOTEARS, FASK, and DGlearn) using simulated fMRI data from a benchmark of simple (5-10 nodes) networks introduced in [57]. The ground truth graphs are shown in Figure 1a, and details on the fMRI time series generation for each node in these graphs are provided under Methods. To evaluate the success of each algorithm, we treated the causal discovery problem as a binary classification problem for each directed edge and calculated the resulting F1 score, both for the directed graphs as well as their undirected skeletons (see Methods for details). Figure 1b illustrates the distribution of F1 scores for all algorithms, combined across nine simple networks. The results show that the PCMCI algorithm achieved significantly higher median F1 score compared to all other algorithms over the directed graphs (all Cohen's d > 0.23 and $p < 10^{-4}$, pairwise

(a)

(b)   **(c)**

Figure 1: **Results of comparing several state-of-the-art causal discovery algorithms over a benchmark of simulated fMRI [57] generated from simple networks with 5-10 nodes each.** **(a)** Ground truth graphs of the simple networks in the benchmark. Despite all being small-scale, the graphs vary widely in their density, number of cycles, etc. **(b)** F1 scores of seven state-of-the-art algorithms (six from Table 1 and MVGC) for correctly identifying the full (directed) graphs. All methods are evaluated using optimized values of their respective hyperparameters (see Methods). The benchmark data includes 60 repetitions of fMRI data from each of the 9 graphs, so each violin plot is based on 540 F1 score samples. The PCMCI method achieves the highest median F1 score, both directed and undirected (see Supplementary Figure 3). **(c)** The mean execution time (averaged over all 60 repetitions) of different algorithms as a function of network size. Note the logarithmic scaling of the vertical axis. Error bars, though hardly visible, show 1 s.e.m.

one-sided Wilcoxon signed-rank test) and compared to all but DYNOTEARS over the undirected skeletons (Supplementary Figure 3, all Cohen's d > 0.44 and $p < 10^{-29}$, pairwise one-sided Wilcoxon signed-rank test. Also see Supplementary Figures 4 and 5 for precision and recall). The PCMCI algorithm also has the smallest computational complexity on simple networks, as seen from Figure 1c. Furthermore, our results indicate that FASK, DGlearn, and PCMCI$^+$ (at their best values of hyperparameters) do not scale well with network size, forcing us to exclude them from further analysis as we move on to larger networks (see Supplementary Figures 13, 14, and 15).

Next, we compared the remaining four algorithms (PCMCI, MVGC, DYNOTEARS, and VARLiNGAM) on a larger-scale, more realistic simulated benchmark. The graph shown in Figure 2a, called the 'Small-Degree Macaque' network, consists of a complete macaque anatomical connectome with 28 nodes and 52 directed edges [57] but the generative model used to simulate fMRI data from this graph remains the same (see Methods for details). The distributions of F1 scores are shown in Figure 2b. PCMCI and MVGC achieved very similar success in learning both the full graph and its undirected skeleton, while significantly outperforming DYNOTEARS and VARLiNGAM. A similar result is obtained when comparing adjacency F1 scores for detecting the network's undirected skeleton (Supplementary Figure 16, also see Supplementary Figures 17 and 18 for precision and recall). As far as execution time is concerned, however, MVGC showed a significant advantage over PCMCI (Figure 2c). Therefore, despite its simplistic nature, MVGC was found most successful in causal discovery from *medium-sized* simulated macaque fMRI data (but also see Figure 3).

Table 1: List of causal discovery methods suitable for use with whole-brain fMRI, divided by methodological category (constraint-, noise-, and score-based). All these methods (1) allow for cycles, (2) allow for contemporaneous effects, (3) assume complete coverage of relevant variables in observed data, and (4) learn linear relationships. The FASK algorithm is fundamentally hybrid and therefore listed as both constraint-based and noise-based.

Category / Type	Constraint-based	Noise-based	Score-based
Time-series	PCMCI [1], PCMCI$^+$ [59]	VARLiNGAM [60]	DYNOTEARS [61]
Cross-sectional with cycles	FASK [57]	FASK [57], LiNG [62]	DGlearn [63]

Figure 2: Comparing the scalable subset of algorithms from Figure 1 over simulated fMRI data from the Small Degree Macaque benchmark [57]. (a) ground-truth Small Degree Macaque network. **(b)** F1 scores of identifying the full (directed) graph. Each distribution consists of 10 F1 scores calculated based on 10 repetitions of simulated data from the same underlying graph. **(c)** Mean execution times for each method (error bars show one standard deviation).

CaLLTiF: A New Causal Discovery Algorithm for Whole-Brain fMRI

The best-performing algorithms on Small-Degree Macaque, i.e., PCMCI and MVGC, suffer from three main drawbacks: (1) poor scalability (only for PCMCI), (2) inability to learn directed contemporaneous effects (PCMCI only learns undirected contemporaneous effects while MVGC learns none), and (3) having sparsity-controlling hyperparameters that are subjectively selected in the absence of ground-truth graphs. In this section, we describe the design of a new algorithm based on PCMCI that mitigates these drawbacks and demonstrate its superior performance over existing methods.

Our first modification to PCMCI is with regard to scalability and computational complexity. The computational complexity of PCMCI depends heavily on the value of its 'PC Alpha' hyperparameter, which controls the sparsity of the set of potential common causes on which the algorithm conditions when checking the conditional independence of each pair of nodes (Extended Data Figure 1a). Higher values of PC Alpha make these sets denser and accordingly decrease statistical power in the subsequent conditional independence tests, *ultimately conditioning on all other nodes (and all of their lags) when PC Alpha = 1.* Nevertheless, interestingly, our experiments on the Small-Degree Macaque data show that the maximum achievable accuracy of PCMCI (i.e., F1 score maximized over Alpha Level for each fixed value of PC Alpha) monotonically increases with PC Alpha, reaching its maximum at PC Alpha = 1 (Extended Data Figures 1b and 1c). Therefore, while this may seem to cause a trade-off between accuracy and scalability, it is in fact an opportunity for maximizing both. At PC Alpha = 1, the PC part of PCMCI (a.k.a. the S1 algorithm in [1]) is theoretically guaranteed to return a complete conditioning set for all pairs of nodes, and can thus be skipped entirely. The PC part is further responsible for the poor scalability of PCMCI. Thus its removal significantly improves the computational efficiency of the resulting algorithm *without compromising accuracy* (cf. Discussions for a potential explanation of why conditioning on all other nodes may improve accuracy despite lowering statistical power).

Our second modification addresses the lack of directed contemporaneous causal effects (see Introduction for why these effects are particularly important in fMRI). By default, MVGC returns no contemporaneous edges and PCMCI returns ∘–∘ ones which only indicate the presence of significant partial correlations but does not resolve between →, ←, or ⇆. However, we know from decades of tract tracing studies that reciprocal connections are significantly more common than unidirectional connections in the primate brain [64–66]. Therefore, we replace all ∘–∘ edges returned by PCMCI by the more likely choice of ⇆. The only exception comes from (the often minority of) pairs of nodes that have a *lagged* directed edge between them, in which case we leave the direction of the contemporaneous effect between them the same as their lagged effect.

Figure 3 shows how the resulting CaLLTiF algorithm performs on a synthetic fMRI dataset generated from the significantly larger full macaque structural connectome with 91 nodes and 1,615 ground-truth edges (Figure 3a, see also Methods). CaLLTiF has a significantly higher F1 score compared to PCMCI, VARLiNGAM, DYNOTEARS, and MVGC in its discovery of the complete directed graph (Figure 3b, all Cohen's $d > 15$, $p < 10^{-6}$, one-sided Wilcoxon signed-rank test) as well as its undirected adjacency skeleton (Figure 3c, all Cohen's $d > 7$, $p < 10^{-6}$, one-sided Wilcoxon signed-rank test). Precisions and recalls are also shown in Supplementary Figures 24 and 25. We also compared CaLLTiF (and PCMCI) against a middle-ground 'Mixed-PCMCI' variant where the ∘–∘ edges returned by PCMCI are used only in the

Figure 3: Comparisons between the proposed algorithm (CaLLTiF) and state-of-the-art alternatives over simulated fMRI from the Full Macaque connectome. (a) ground-truth Full Macaque network. **(b,c)** Distributions of F1 scores for CaLLTiF and state-of-the-art alternatives in discovering the full (directed) graph (b) and its undirected adjacency skeleton (c). For all repetitions, the best performance of MVGC occurs at $\alpha = 0.5$ which returns a complete graph, hence the point distributions for MVGC. *** denotes $p < 0.001$. All statistical comparisons are performed using a one-sided Wilcoxon signed-rank test. In all boxplots, the center line represents the median, the box spans the interquartile range (IQR), and the whiskers extend up to 1.5 times the IQR from the box limits.

computation of adjacency F1 score (Supplementary Figures 26-28, see also Methods). Mixed-PCMCI benefits from contemporaneous effects as much as CaLLTiF in terms of adjacency F1 score, but not so in terms of full F1 score, further motivating the inclusion of directed contemporaneous connections as done in CaLLTiF. Detailed performances of all compared algorithms are provided in Supplementary Figures 27-34.

Finally, the third aspect in which CaLLTiF departs from PCMCI is the choice of sparsity-controlling hyperparameter 'Alpha Level'. Most, if not all, algorithms for causal discovery have at least one hyperparameter (often a threshold) that controls the sparsity of the resulting graphs. Different from PC Alpha described earlier, Alpha Level in PCMCI is the standard type-I error bound in determining statistical significance in *each* partial correlation test (cf. Extended Data Figure 1). By default, Alpha Level is selected subjectively, based on domain knowledge and expected level of sparsity. However, in CaLLTiF, we select Alpha Level objectively based on a novel method for correction for multiple comparisons (see Methods) that occur when collapsing a time-series graph over lagged variables into a final summary graph. This step is critical, particularly in the absence of ground-truth connectivity, to ensure that we have statistical confidence in every edge of the final summary graph returned by CaLLTiF.

In summary, CaLLTiF starts by constructing an extended time-lagged graph among all the variables $X_i(t - \tau), i = 1, \ldots, n$ and all lags $\tau = 0, 1, \ldots, \tau_{\max}$. To establish a causal link between any pair of variables $X_i(t - \tau)$ and $X_j(t)$, CaLLTiF performs a conditional independence test (using linear partial correlation) between $X_i(t - \tau)$ and $X_j(t)$, conditioned on all other *lagged* variables ($X_k(t - s), s = 1, \ldots, \tau_{\max}$). A causal link is established if the null hypothesis of conditional independence is rejected at a significance threshold 'Alpha Level'. By default, 'Alpha Level' is selected based on CaLLTiF's type I error control, but it can also be optimized in simulated data using ground-truth knowledge. If $\tau > 0$, the direction of the edge is clearly $X_i(t - \tau) \to X_j(t)$. When $\tau = 0$, CaLLTiF returns $X_i(t) \leftrightarrows X_j(t)$ if no other edges exist between X_i and X_j at higher lags, and places the edge(s) consistent with the corresponding lagged direction(s) otherwise. Finally, the extended time-lagged graph is collapsed into a summary graph by taking an OR operation for each edge across all lags (cf. Methods for details).

Causal Discovery from Resting-State Human fMRI

We next applied CaLLTiF on resting-state fMRI from 200 subjects from the Human Connectome Project (HCP) (See Methods). Each scan from each subject was parcellated into 100 cortical and 16 subcortical regions. CaLLTiF was then performed on all four resting-state scans for each subject, resulting in one causal graph per individual.

Learned causal graphs are highly consistent across subjects. Despite individual differences, a remarkably common causal connectome emerged across subjects. Figure 4a shows the average causal graph among the subjects and Figure 4b shows the intersection graph that contained the edges *common across all subjects.* Due to the binary nature of individual graphs, the former can also be viewed as a matrix of probabilities, where entry (i, j) shows the probability of region i causing region j across all subjects. As a result of the significant commonalities that exist in the causal graphs among subjects, the average graph has a bimodal distribution, with the vast majority of average weights being close to either 0 or 1. These extreme values of average weights can also be seen as a measure of the confidence of the algorithm in the presence or lack of most edges, and have a clear contrast with the weights of the average of randomized surrogate graphs generated *independently* across subjects (Supplementary Figure 41). In the absence of a ground truth causal connectivity for direct comparison, such strong commonalities among subjects serve as an alternative measure of validation and provide insights into the general patterns and characteristics of the causal relationships in a resting brain.

Nodal centralities also show strong consistency among the subjects. Figure 4c shows the nodal degrees for all subjects (gray lines) as well as its mean across subjects (black line, also depicted in Figure 4d). Statistically significant differences exist between the degree distributions of many pairs of nodes (about 90% of the pairs have $p < 0.001$, two-sided Wilcoxon signed-rank test, computed between nodal degrees of each pair of parcels), while significant correlations exist between nodal degrees for all pairs of subjects (all pairs have $0.56 \leq r \leq 0.96$, $p < 10^{-10}$, Pearson Correlation Coefficient, computed based on the nodal degrees of each pair of subjects separately). Similar consistency for in-degree, out-degree, betweenness, and eigenvector centralities can be observed among subjects (Supplementary Figures 42-45). Consistently across subjects, medial ventral attention regions, cingulate cortices, and lateral primary sensorimotor areas show particularly low nodal degrees across both hemispheres, whereas bilateral default mode areas, particularly the left ventromedial prefrontal cortex, show notably strong nodal degrees. Bilateral anterior thalami are particularly causally connected compared to other subcortical regions, even though subcortical areas have significantly lower degrees than cortical areas in general, with bilateral posterior thalami, nuclei accumbens, and globus pallidi showing the least causal connections across the whole brain at rest.

Causal graphs are also sparser and more consistent across subjects compared to functional connectivity. A major motivation for building causal connectomes is the removal of spurious connections in functional connectivity (FC) profiles that reflect mere correlation but no causation. For causal graphs learned by CaLLTiF, we indeed observed significantly lower edge density compared to FC graphs (see Methods for details on the computation of FC graphs) (Supplementary Figures 40a,40b, no overlap existing between the support of the two distributions). In fact, FC graphs included approximately 95% of CaLLTiF's discovered causal edges (Supplementary Figure 40c), while only about half of all functional connectivity edges are also causal (Supplementary Figure 40d). Interestingly, among the approximately 5% of causal edges that were not in the FC graphs, the majority came from non-zero lags. This is remarkable, given that causal edges from non-zero lags are significantly fewer in general (cf. Figure 6a), but are fundamentally not discoverable by FC which only measures contemporaneous co-fluctuations. Moreover, causal connectomes are significantly more consistent across subjects compared to FC connectomes (Supplementary Figure 40e, Cohen'd > 2, $p < 0.001$, one-sided Wilcoxon signed-rank test), further reinforcing the expectation that causal edges are "pruned" and more reliable compared to functional edges.

Net resting-state causal effect flows from attention and default mode to sensorimotor networks. One of the main advantages of directed causal connectomes over undirected functional and structural connectomes is the former's ability to show the directed flow of causal effect between brain regions. In graphs learned by CaLLTiF, nodal causal flows (outflow minus inflow, see Methods) are also highly consistent across subjects (Figure 5c,5d), even though the two notions of centrality are generally dissociated across parcels

Figure 4: Learned causal graphs are highly consistent across subjects. (a) Average causal graph, computed as the mean of all the causal graphs of 200 subjects. The color of the (i, j) entry in this matrix shows how likely it is for node i to cause node j. A clear distinction can be seen in the causal links among cortical regions (colored labels) and subcortical ones (black labels). **(b)** The shared causal graph, containing only the edges that are present in all 200 subjects. This graph is dominated by diagonal elements (self- and within-subnetwork causation) and links among symmetrically located regions across the two hemispheres. **(c)** Distribution of nodal degree, computed separately for each node in the causal graph and each subject. Gray colors correspond to different subjects and the black line shows the average nodal degrees across subjects. **(d)** Average cortical nodal degree (black line in (c)) shown over the brain cortical surface.

(Figure 5b and Supplementary Figure 50). On average across all subjects, we observed particularly high causal flows (source-ness) in several regions of bilateral medial ventral attention networks, specific dorsal attention areas (ventral precentral, ventral frontal cortices, and frontal eye fields), and bilateral hippocampi, even though subcortical areas are much less connected to the rest of the network in general. In contrast, bilateral visual areas show the strongest negative causal flow (sink-ness) across all subjects. There is also notable variability among parcels within a subnetwork, such as the notable bilateral contrast between the strongly positive and weakly negative causal flows of frontal and posterior parts of the dorsal attention network, respectively.

To better assess the overall net causal effects between different functional networks, we computed an average "subnetwork graph" in which each node represents a functional cortical network and edges denote thresholded average directed connectivity from one functional network to another (see Methods for detailed computations). The result is illustrated in Figure 5a. Ventral attention and visual networks are clearly the strongest source and sink of causal flow, respectively. The dorsal attention and somatomotor networks are also a clear (though weaker) source and sink, respectively. The default mode network (DMN) is also a net source of causal flow, even though its outflows and inflows are nearly balanced. Similarly, the control and limbic networks have near-zero causal flows (near-balanced inflow and outflow). Several directed paths, however, can be seen from both attention and default mode networks to sensorimotor networks through the limbic and control networks. Therefore, in summary, causal graphs learned by CaLLTiF show the strongest net resting state causal effect to flow from the ventral and dorsal attention as well as the default mode networks, through control and limbic networks, towards sensorimotor networks, with the DMN serving both as a hub and a weak source of causal flow (cf. Discussion for a more detailed summary).

Casual graphs are strongly dominated by contemporaneous and lag-1 connections. Given that the final causal graph returned by CaLLTiF is a union over subgraphs at different lags (cf. Methods), we can go back and ask how much causal effects in each lag have contributed to the final graph. Figure 6a shows the percentage of edges in the final graph that exist *only* in one lag (including lag 0, or contemporaneous edges). Increasing the lag order resulted in significantly sparser single-lag subgraphs, which contributed less to the end result. In particular, approximately 70% of the end graphs came from lag 0 alone, a pattern that appears consistently across all subjects (Supplementary Figure 54). Even further, such contemporaneous edges are substantially stronger than edges from lags 1-3 (Figure 6b). This further confirms that the contemporaneous effects are particularly important for fMRI, where most neural dynamics occur at timescales shorter than 1 TR (typically shorter than 1-2 seconds). This is even the case in HCP data, with TR = 0.72s which is among the shortest TRs currently available in fMRI research. That being said, all lags had a non-zero (and significant by construction) contribution to the end graph in all subjects. Even lag 3 had a median of approximately 0.2% unique contributions to the final graph across subjects. We also found very small intersections among lags. This not only highlights the importance of considering multiple lags rather than just the first one or two but also demonstrates that it is incorrect to assume that if one region causes another, that causation will appear continuously across all lags. In summary, we found contemporaneous effects dominant in the final causal graphs of CaLLTiF, even though all lags had significantly non-zero and mostly unique contributions.

Causal connections are weakly modulated by pairwise Euclidean distance. As one would expect from a network learned over a set of nodes embedded in physical space, the causal graphs learned by CaLLTiF are modulated in a number of ways by the Euclidean distance between pairs of nodes. First, we found degree similarity (correlation coefficient between nodal degrees of two parcels over all subjects) to decay statistically significantly, though weakly in effect size, with parcel distance (Pearson $r = -0.12$, $p = 10^{-43}$, 95% confidence interval $(-0.14, -0.1)$) as shown in Figure 7a (See Supplementary Figures 51 and 52 for separate maps of degree similarities and pairwise nodal distances). This relationship is stronger among intra-hemispheric parcels (Pearson $r = -0.27$, $p = 10^{-82}$, 95% confidence interval $(-0.29, -0.24)$) where connections are denser and shorter-distance, compared to inter-hemispheric parcels (Pearson $r = -0.09$, $p = 10^{-5}$, 95% confidence interval $(-0.13, -0.05)$). Thus, in summary, nodes that are physically closer to each other also have more similar causal connections to the rest of the network, particularly if they belong to the same hemisphere.

The strength of CaLLTiF edges is also modulated by the Euclidean distance between edge endpoints, even though we observed that there are approximately as many long-distance edges as short ones (See

Figure 5: Patterns of causal flow across subjects. **(a)** The average subnetwork graph, computed as the mean of subnetwork graphs of all the subjects. In the subnetwork graph of each subject, the weight of an edge from subnetwork i to j is the number of nodes in subnetwork i that connect to nodes in subnetwork j, normalized by the number of all possible edges between these subnetworks. Edges with weights less than 0.5 are removed for better visualizations. To further ease the visual inspection of causal flows, if two networks are bidirectionally coupled we have shown the stronger edge with a thicker line (see Supplementary Figures 48, 49 for the weight matrix before thresholding and the corresponding nodal degrees and causal flows.) **(b)** The joint distributions of causal flow and degree for each "node" of the subnetwork graphs across all subjects. **(c)** Distribution of nodal causal flow, computed separately for each node in the causal graph and each subject. Gray colors correspond to different subjects and the black line shows the average nodal degrees across subjects. **(d)** Average cortical nodal causal flows (black line in (c)) shown over the brain cortical surface.

(a)

(b)

Figure 6: The contributions of each lag to the final causal graph in CaLLTiF. (a) For each lag, the box plot shows the distribution of the percentage of edges that come only from that lag across subjects. In all boxplots, the center line represents the median, the box spans the interquartile range (IQR), the whiskers extend up to 1.5 times the IQR from the box limits, and individual points beyond the whiskers indicate outliers. **(b)** The strength (statistical significance) of edges across lags. For each edge within the subgraph of each lag, we define its strength as the p-value of the partial correlation test that was used to conclude the presence of that edge (see Methods) even though all edges have a statistically significant p-value by definition, edges in larger lags are significantly closer to the threshold for significance than those in smaller lags. *** = $p < 0.001$, one-sided Wilcoxon rank-sum test.

Supplementary Figures 53). We define the strength of each edge in the final graph (union over lags) as the *minimum* p-value of respective partial correlation tests across all lags (cf. Methods). As seen from Figure 7b, the mean strength of causal edges (black solid line) initially increases with the Euclidean length of the edge until about 20mm and then decays with Euclidean edge length thereafter.

Finally, we found no major differences between the Euclidean distances of edges contributed by different lags. Given that causal effects take time to spread along axonal fibers throughout the brain, one might expect physically-closer pairs of nodes to be connected by lower-lag edges and more distant pairs of nodes to be connected by larger-lag edges. However, as seen in Supplementary Figure 55, this is not quite the case. Given the slow sampling of fMRI, even the most distant regions can causally affect each other in time scales shorter than 1 TR. Thus, the observation that the physical distance of pairs of nodes was not related to edge lag should not be taken as an indication that such relationships would – or would not – be observed when sampling with higher temporal precision.

Degree, but not casual flow, shows significant laterality and gender differences. We observed that nodal degrees were statistically significantly higher in the right hemisphere (Figure 8a, Cohen's d = 0.07 and $p = 10^{-48}$, one-sided Wilcoxon signed-rank test), even though no such laterality was found in nodal causal flows (Figure 8b, Cohen's d = 0.02 and $p = 0.23$, one-sided Wilcoxon signed-rank test). To understand which subnetworks might be playing a stronger role in the hemispheric asymmetry observed in the distribution of nodal degrees, Figure 8c shows the mean degrees of corresponding pairs of regions in the left and right hemispheres, color-coded by functional subnetworks (cf. Supplementary Figures 46 for separate plots per subnetwork). The ventral attention, dorsal attention, and executive control networks show clearly larger causal degrees in the right hemisphere, whereas the limbic network and DMN have larger causal degrees in the left hemisphere. A similar plot for causal flows (Figure 8d, Supplementary Figure 47) shows a lot more symmetry, except for the limbic network which shows exceptionally higher causal flows (i.e., source-ness) in the right compared to the left hemispheres. The DMN also shows some asymmetry in its causal flow, where right DMN nodes are mostly sources of causal flow whereas left DMN causal flows are more evenly distributed around zero. Thus, in summary, various functional subnetworks show laterality in degree distributions, culminating in a net increase in right vs. left nodal degrees. Causal flows, however, are mostly symmetric, except for the limbic network which shows a strong flow from the right to the left hemisphere.

Similarly, degree, but not casual flow, shows a small but statistically significant difference between men and women. In causal connectomes learned by CaLLTiF, we found nodal degrees to be statistically significantly higher in women compared to men (Figure 8e, Cohen's d > 0.05, $p < 10^{-5}$, one-sided Wilcoxon rank-sum test). Nodal causal flows, on the other hand, where statistically indistinguishable between men and women (Figure 8f, Cohen's d = -3.77×10^{-18}, $p = 0.81$, one-sided Wilcoxon rank-sum test). These result

Figure 7: Effect of Euclidean distance on edge attributes. (a) Degree similarity (correlation coefficient between nodal degrees of two parcels over all subjects) as a function of the Euclidean distance between the parcels. Parcel pairs in the same hemisphere (intra-hemispheric) and parcels in two different hemispheres (inter-hemispheric) are shown in blue and red, respectively. Degree similarity decays statistically significantly with parcel distance (Pearson $r = -0.12$, $p = 10^{-43}$, 95% confidence interval $(-0.14, -0.1)$), much more so among intra-hemispheric parcels (Pearson $r = -0.27$, $p = 10^{-82}$, 95% confidence interval $(-0.29, -0.24)$) than inter-hemispheric ones (Pearson $r = -0.09$, $p = 10^{-5}$, 95% confidence interval $(-0.13, -0.05)$). **(b)** Edge strength (as in Figure 6b) as a function of Euclidean distance between edge endpoints (note the inverted vertical axis). The solid line shows the corresponding moving average of $\log(p)$ with 10mm window size and 8mm window overlap. The upper limit of the vertical axis is limited to -30 for better visualization.

demonstrate that nodal degrees in causal connectomes are generally more heterogeneous and sensitive while causal flows tend to be more homogeneous and stereotyped across individuals and hemispheres. Further research is needed to pinpoint the root causes of these differences (and lacks thereof) as well as potential implications of them in health and disease.

Discussion

Summary. In this study, we investigated the problem of whole-brain causal discovery from fMRI. We first comprehensively compared existing causal discovery techniques suitable for whole-brain fMRI by examining both theoretical properties and numerical outcomes on simulated fMRI. To address the shortcomings of existing methods, we proposed the Causal discovery for Large-scale Low-resolution Time-series with Feedback (CaLLTiF) algorithm that improves upon the state of the art in terms of computational efficiency, discovering contemporaneous effects, and correction for temporal multiple comparisons. We demonstrated the accuracy of CaLLTiF against several state-of-the-art approaches using simulated fMRI and then used it to estimate causal connectomes from resting-state HCP data [50, 67, 68]. On human fMRI data, CaLLTiF was able to learn causal graphs that (1) are highly consistent across subjects, (2) are consistent with known resting-state dynamics, (3) are sparser and more consistent across subjects compared to functional connectivity graphs, (4) properly reflect the presence of contemporaneous relationships due to the low temporal resolution of fMRI, (5) capture Euclidean distance-dependence in causal interactions, and (6) demonstrate statistically significant laterality and gender differences in degree distributions (but not causal flows). Overall, our results validate the power of CaLLTiF in detecting causal interactions from resting-state fMRI and open myriad avenues for future investigations of causal discovery from the task and stimulation-induced neuroimaging data.

Criteria for causal discovery from whole-brain fMRI. As noted in the Results, we used four criteria to narrow down the list of existing causal discovery methods based on their suitability for whole-brain fMRI. First, we focused our analysis on algorithms that can learn graphs with cycles. In the field of causal

Figure 8: Hemispheric laterality and gender differences in causal connectomes. (a) Distributions of nodal degree in the right and left hemispheres, combined across all subjects. (b) Similar to (a) but for causal flows. (c) Nodal degrees, averaged across subjects and color-coded by functional subnetwork, for pairs of corresponding parcels within the right and left hemispheres. To properly pair nodes across the two hemispheres, degrees of all the parcels with the same label in the Schaefer/Tian atlas were averaged and then paired. Deviations from the dashed y = x line indicate laterality. (d) Similar to (c) but for causal flows. (e) Distributions of nodal degrees in female and male subjects, combined across all brain regions. (f) Similar to (e), but for causal flows.

discovery, most methods assume that the underlying causal structure of a system can be represented by a Directed Acyclic Graph (DAG) [7, 36, 38–43]. In studying the brain, however, cycles and feedback are inevitable and pervasive [65, 66, 69–72]. This significantly limits the range of methods that are suitable for causal discovery from neuroimaging data, primarily to two categories: time-series methods that still learn a DAG over lagged variables (often via vector autoregressive models [73, 74]), and cross-sectional methods that allow for cycles even among contemporaneous variables (Table 1). We included algorithms from both categories but found the latter to generally have higher computational complexity and not scale well for whole-brain analysis. This is critical as even with a TR of 720ms, we found a strong majority of edges coming from contemporaneous effects. Moving to TRs of 2s or greater, which are still very common, will likely make contemporaneous effects almost all that remains detectable. CaLLTiF provides a first step in developing scalable algorithms that can learn cycles also among contemporaneous variables, but only learns symmetric contemporaneous subgraphs. More research is therefore needed to design algorithms that can learn accurate, potentially asymmetric causal graphs among lagged and contemporaneous variables while scaling well to hundreds of variables.

Second, neural signals are known to travel across the brain in much less than one fMRI repetition time (TR) [23, 24]. Such fast sub-TR interactions in fact account for a significant portion of neural dynamics and demonstrate themselves as "contemporaneous" effects in fMRI. Therefore, we further pruned algorithms based on their ability to learn contemporaneous effects. For a detailed discussion on how we theoretically define contemporaneous edges and their practical significance for fMRI, see Supplementary Note 1. Third, we only selected algorithms that do *not* allow for latent nodes. This is due to a nuanced trade-off between theoretical generality and practical utility. Allowing for latent nodes is in theory a capability and an advantage, but it comes at the cost of significantly expanding the set of graphs consistent with observational data. In turn, allowing for latent nodes *lowers* an algorithm's ability to detect unambiguous causal links. The possibility of whole-brain coverage and measuring all cortical and subcortical areas in fMRI provides a unique opportunity to avoid such costs and use simpler algorithms that assume a complete coverage of relevant variables in the observed data. Finally, we selected methods designed to capture linear causal relationships. This is mainly motivated by our recent empirical [75] and analytical [76, 77] works demonstrating the macroscopic linearity of resting-state dynamics, particularly those captured by fMRI. Nevertheless, we also tested a state-of-the-art nonlinear causal discovery method [14, 78] and found it to indeed have a lower F1 score compared to linear methods in synthetic fMRI (Supplementary Figure 35).

Dimensions of improvement over state of the art. To address the limitations of existing algorithms, we proposed CaLLTiF which improves upon the state of the art in three main dimensions: learning contemporaneous edges and cycles, type I error control, and scalability. A core aspect of CaLLTiF is its treatment of contemporaneous effects. Our results with the HCP data (Figures 6a and 6b) confirmed the importance of being able to reveal such "contemporaneous" effects, where these effects accounted for the majority and strongest of network edges. Further, the distributions of edges with different Euclidean distances at each lag (Supplementary Figure 55) demonstrates how broadly neural signals can propagate across the brain in one TR interval, even with the relatively fast sampling (TR = 0.72s) in the HCP dataset.

Second, in interpreting CaLLTiF's outputs, it is important to note its by-design conservative method of correction for temporal multiple comparisons. In simulated Full Macaque data where the ground truth is known, we found Alpha Level = 0.01 to maximize the F1 score, while CaLLTiF's correction for temporal multiple comparisons would have suggested $0.01/32 = 0.0003$ (cf. Equation (4)) and thus would have obtained sparser graphs. Similarly, we obtained causal graphs from human fMRI that are about 30-55% dense across all subjects and 40-60% dense among cortical nodes (Supplementary Figure 40a). These are generally consistent with, but sparser than, the near-66% cortical density found using tract-tracing results in non-human primates [66]. In other words, graphs returned by CaLLTiF are likely to have higher precision but lower recall than what would maximize the F1 score. This conservativeness is by design and desirable *in the absence of a ground-truth causal graph*, ensuring that we have strong confidence in all discovered edges (at least 99% confidence in every detected edge in our experiments with human fMRI). Nevertheless, CaLLTiF's level of conservativeness can also be tuned as needed by tuning its pre-correction significance threshold (q in Equation (4)).

An unexpected finding of our study was the higher accuracy of causal discovery when conditioning pairwise independence tests (see Equation (1)) on all other nodes in the network, as done in CaLLTiF,

compared to using a more restricted parent set found by PCMCI (cf. Extended Data Figure 1). The approach taken by PCMCI increases statistical power (cf. the trend of optimal 'Alpha Level' values in Extended Data Figure 1b), but can significantly increase type I error in the presence of contemporaneous effects. Even further, we found that even using the (lagged) ground-truth parent sets for each node leads to a lower F1 score compared to using complete conditioning sets (Supplementary Figure 37-39). This is likely because CaLLTiF's conditioning on the *past* of all variables serves as a proxy for the missing contemporaneous parents that should have been conditioned on. On the other hand, one may wonder if this issue could have been better resolved by conditioning on contemporaneous variables themselves. However, this can result in spurious statistical dependence if conditioning on all contemporaneous variables (consider, e.g., testing $X_i \not\perp\!\!\!\perp X_j | X_k$ with the ground-truth causal graph $X_i \rightarrow X_k \leftarrow X_j$). For a detailed discussion on this see Supplementary Note 3. Finally, using PC-like methods for conditioning on carefully-chosen subsets of contemporaneous variables (as done, e.g., in PCMCI$^+$ [59]) requires an assumption of contemporaneous acyclicity and often increases computational complexity. Therefore, despite its heuristic nature, we found the conditioning in CaLLTiF to provide a desirable balance between precision and recall for the particular application of causal discovery from fMRI.

The third core aspect of CaLLTiF is its scalability. In the context of causal discovery, ROI-based analysis allows for a more targeted discovery among a few variables of interest, makes it easier to validate obtained results against the available literature, and alleviates scalability concerns. Algorithms such as FASK [57] and DGlearn [63], e.g., have shown great promise when applied to small graphs. However, ROI-based analysis has two main limitations. The first limitation is an inherent bias towards already established networks and ROIs, limiting the power of causal 'discovery' to detect relationships not otherwise expected or hypothesized. The latter is increasingly possible using the power of emerging ever-larger datasets, but requires algorithmic solutions capable of handling big data efficiently. The second limitation is that ROI-based analysis mandates careful consideration of potential latent confounders. This significantly limits the range of algorithms one can use as well as the power and specificity of statistical methods in detecting unambiguous causal relationships in the presence of latent confounders. A significant need therefore exists for scalable algorithms such as CaLLTiF that can learn potentially cyclic, potentially contemporaneous causal relationships from whole-brain fMRI.

Causal connectivity during resting state. When applying CaLLTiF to resting state human fMRI, we found the strongest causal effect to flow from attention to sensorimotor networks. The strongest sources and sinks were the ventral attention and visual networks, followed by dorsal attention and somatomotor networks, respectively. Despite the lack of "ground-truth" connectivity as in simulated data, we can still evaluate these findings based on their agreement with prior findings on the roles of resting state networks. The dorsal attention network (involving regions in the intraparietal and superior frontal cortex) is commonly believed to handle top-down selection processes and is only modulated by stimulus detection, while the ventral attention network (including areas such as the temporoparietal and inferior frontal cortex) specializes in detecting behaviorally relevant stimuli, particularly those that are salient or unexpected, and directing attention to them [79]. These networks exhibit internally correlated activity patterns (particularly during the task) [80] and their flexible interaction facilitates dynamic attentional control aligned with both top-down goals and bottom-up sensory inputs [81]. Nonetheless, the ventral attention network is more strongly involved in the "reorientation" of attention, namely, interrupting one thought process and orienting attention towards something salient, while the dorsal attention network is more strongly implicated in focused and guided attentional tasks such as visual search under high short-term memory load [81].

Arguably, resting state activity is more aligned with the former (salience-based reorientation) than the latter (goal-driven focused attention). Despite a lack of sensory salience, attention is frequently reoriented during periods of rest by endogenously-salient thoughts and memories. Intermittent periods of focused attention can also arise, particularly given the long durations of each resting-state scan ($\sim$ 15min). Our findings thus confirm and corroborate the existing hypotheses about the roles of attention networks and how they jointly but unevenly drive brain dynamics during rest. Furthermore, due to the lack of meaningful sensory (particularly visual) input during a resting state scan, sensory areas receive more top-down influence from higher-order cortices than they provide bottom-up information to them. As such, the sink-ness of sensorimotor areas in graphs learned by CaLLTiF is arguably more consistent with the nature of resting state activity compared to a contrasting, sensory-driven flow found, e.g., in [58]. Finally, we found the DMN

to be both a hub and a weak source of causal flow, which is consistent with its well-known role in resting state dynamics [82–84].

Resting-state causal graphs learned by CaLLTiF are also notably aligned with the literature in terms of the laterality of different functional subnetworks (Figure 8c and Supplementary Figure 46). Several studies have found the ventral attention system to be predominantly lateralized to the right hemisphere [79–81, 85]. Similarly, the degree distribution of ventral attention nodes in graphs learned by CaLLTiF is strongly right-lateralized. We found the dorsal attention network to also be right-lateralized, but not as strongly as the ventral network. Similarly, The dorsal attention network is found by prior studies to be organized mostly bilaterally, except for specific regions (Intraparietal sulcus and frontal eye field) in the right dorsal network that show stronger involvement in the attentional control of both hemispheres compared to their left counterparts [85]. Also similar is alignment in the lateralization of the default mode network, where both CaLLTiF several past studies have found it to be left lateralized [86–89]. Sensorimotor cortices, on the other hand, were found to be highly symmetric and not particularly lateralized to either hemisphere in causal graphs learned by CaLLTiF, a finding that is also consistent with the generally symmetric involvement of primary sensory and motor areas in contralateral processing [86]. Finally, research on the laterality of the control and limbic networks is ongoing and, to the best of our knowledge, inconclusive (see, e.g., [90]). In graphs learned by CaLLTiF, however, we observe strong left lateralization of the limbic and right lateralization of the control networks, respectively. Thus, in summary, we observe clear laterality in all but sensorimotor cortical networks which either corroborate the existing literature or clarify previously inconclusive observations.

When applying CaLLTiF to resting-state HCP data, we also found a significant effect of Euclidean distance on causal connections, both in terms of their strength and their end-point degree similarity (Figure 7). This finding is in line with several prior studies that have shown distance-dependence in structural and functional connections [91–93], and provides new evidence for the presence of a similar distance dependence in *causal* connections. Since causal connections are more mechanistically meaningful than functional connections, our findings also open the door to potentially more accurate investigations of how variations in distance-dependent patterns of connectivity can relate to different states of health and disease [91].

Assumptions. Similar to most causal discovery algorithms, CaLLTiF relies on an assumption of stationarity in order to treat the recorded time series across different time points as samples from a (single) underlying distribution. For $N = 116$ nodes and $\tau_{\max} = 3$ lags, this assumption requires approximately $2 \cdot 3 \cdot 116 \simeq 700$ continuously recorded samples while the subject is in relatively stationary conditions. This is often feasible for resting-state recordings but can become challenging for task data. In the case of the latter, at least two approaches can be pursued. First, one can reduce $\tau_{\max}$ which would proportionately reduce the length of stationary recordings needed. We tested this approach on 30 of our HCP subjects and found the final graphs to only vary by about %5 as we reduced $\tau_{\max}$ from 3 to 1 (Supplementary Figure 56). A second approach involves comparing causal graphs obtained from large blocks of task with those obtained from equally-long blocks of rest, or between two or more blocks of task. This comparative analysis helps mitigate the need to break task blocks into smaller intervals of task performance, inter-trial intervals, etc. Such temporal partitioning leads to a significant loss in the number of continuously-recorded windows around the beginning and end of each partition, and avoiding it is almost imperative when using lag-based methods with a large number of variables and slow sampling, as is the case with whole-brain fMRI.

Because the blood-oxygen-level-dependent (BOLD) signal measured by fMRI provides only an indirect measure of neural activity through the hemodynamic response function (HRF), one may first seek to estimate the underlying neural activations by deconvolving fMRI from the HRF and then use the estimated neural activations for causal discovery. We, however, did not find such deconvolution beneficial. Using the simulated Full Macaque data and standard Wiener deconvolution [94] with the generic SPM HRF [95], we compared the CaLLTiF, Mixed-PCMCI, and PCMCI methods when applied directly to the BOLD data or after HRF deconvolution (Supplementary Figure 36). While PCMCI and Mixed-PCMCI exhibited slightly higher F1 scores when applied to the deconvolved signals, the highest F1 scores were achieved by CaLLTiF over the BOLD signal. This is in line with our earlier findings regarding *decreased* dynamics signal to noise ratio after HRF deconvolution [75], and motivated using the BOLD signal itself in the rest of our analyses.

Limitations. The present study has a number of limitations. The TR value of 720ms in the HCP data limits the precision of causal discovery. As we saw from Supplementary Figure 55, edges of all lengths are

observed even at lag 0. This indicates the possibility that some of the edges discovered by CaLLTiF may be polysynaptic paths but resemble a direct monosynaptic connection at low temporal resolution. The lack of a ground-truth *causal* connectome further makes the validation of obtained graphs challenging. Unlike structural connectivity, a causal connectome is directed, dynamic, and task-specific. As such, once an algorithm is sufficiently validated on simulated data, its outcomes on real data must be 'trusted' to some extent. Our conservative method for correction for temporal multiple comparisons seeks to serve this purpose and ensure a certain level of statistical confidence in each edge of the resulting graphs. Finally, similar to most constraint-based methods, the causal graphs returned by CaLLTiF are not tied to a generative dynamical model (as is the case with VARLiNGAM, DYNOTEARS, DCM, etc). If such generative models are needed, VAR models based on CaLLTiF's extended time-lagged graph constitute a natural choice, but further research is needed to compare the dynamic predictive accuracy of such models against potential alternatives [96].

Conclusions. Overall, this study demonstrates the interplay between the theoretical challenges of causal discovery and the practical limitations of fMRI, and the design of an algorithmic solution that can bridge this gap. This work motivates several follow-up studies, including the application of the proposed CaLLTiF method to task fMRI and comparing its outcomes against structural connectivity. Structural connectivity can also be used as a prior for causal discovery and augment functional data. Complementary to our focus on learning separate causal graphs for each subject, one can also learn one causal graph from a group of subjects and use that group-level graph to improve the estimation of each causal graph [97, 98]. Multimodal discovery, combining, e.g., fMRI and EEG, is also highly warranted given the complementary spatial and temporal resolutions of different imaging modalities. We leave these exciting possibilities to future studies.

Material and methods

Simulated fMRI Data

When comparing different causal discovery algorithms or different hyperparameters of the same algorithm, we used several benchmarks of simulated fMRI data with known ground truth connectivity from [57]. In general, this dataset included two groups of networks, one consisting of 9 simple small-scale synthetic graphs and one consisting of two graphs extracted from the macaque connectome. From the latter group, we only used the smallest ('Small-Degree Macaque') and the largest ('Full Macaque').

The details of generating BOLD signals from each graph are detailed in [57]. In brief, the same simulation procedure was used for simple and macaque-based graphs, where the authors used the model proposed in [45] which is itself based on the DCM architecture of [26]. Underlying neural dynamics are simulated using the linear differential equation $dz/dt = \sigma Az + Cu$, where A denotes the ground-truth connectivity. To simulate resting-state data, the u input was modeled using a Poisson process for each of the regions ($C = I$). The neuronal signals z were then passed through the Balloon-Windkessel model [45, 99] to obtain simulated BOLD data.

Resting-State fMRI from the Human Connectome Project

For the real fMRI analysis, we used ICA-FIX resting-state data from the Human Connectome Project S1200 release [50, 67, 68]. Resting-state fMRI images were collected with the following parameters: TR = 720 ms, TE = 33.1 ms, flip angle = 52 deg, FOV = 208x108 mm, matrix = 104x90, slice thickness = 2.0 mm, number of slices = 72 (2.0 mm isotropic), multi-factor band = 8, and echo spacing = 0.58 ms. Brains were normalized to fslr32k via the MSM-AII registration and the global signal was removed. We removed subjects from further analysis if any of their four resting state scans had excessively large head motion, defined by having frames greater than 0.2 mm frame-wise displacement or a derivative root mean square (DVARS) above 75. Also, subjects listed in [100] under "3T Functional Preprocessing Error of all 3T RL fMRI runs in 25 Subjects" or "Subjects without Field Maps for Structural scans" were removed. Among the remaining 700 subjects, the 200 with the smallest head motion (DVARS) were selected for analysis. For all subjects, we parcellated the brain into 100 cortical regions (Schaefer 100x7 atlas [101]) and 16 subcortical ones (Melbourne Scale I atlas [102]). The Human Connectome Project experiments were carried out by the

WU-Minn consortium and its adherence to ethical standards was approved by the by the Internal Review Board of the respective institutions. Explicit informed consent was acquired from all participants involved in the study [50].

Causal discovery methods

One aim of causal inference is to construct a causal graph based on observational data. The relationship between a probability distribution and its depiction as a graph plays a significant role in this process. Nevertheless, it is not always feasible to deduce a causal graph solely from observational data. Further assumptions are therefore required. Here, we briefly summarize the main assumptions and principles underlying the list of causal discovery methods studied in this work (cf. Table 1).

PCMCI. PCMCI was proposed in [1] as a constraint-based causal discovery method designed to work with time-series data. The algorithm is composed of two main steps. In the first step, the algorithm selects relevant variables using a variant of the skeleton discovery part of the PC algorithm [38]. This step removes irrelevant variables for conditioning and therefore increases statistical power. In the second step, the algorithm uses the momentary conditional independence (MCI) test, which measures the independence of two variables conditioned on the set of their parents identified in step 1. The MCI test helps to reduce the false positive rate, even when the data is highly correlated. PCMCI assumes that the data is stationary, has time-lagged dependencies, and has causal sufficiency. Even when the stationarity assumption is violated, PCMCI was shown to perform better than Lasso regression or the PC algorithm [1]. However, PCMCI is considered not suitable for highly predictable (almost deterministic) systems with little new information at each time step [1]. The Python implementation of PCMCI is available in the Tigramite package at `https://github.com/jakobrunge/tigramite`.

As noted earlier, PCMCI only returns ∘—∘ edges among contemporaneous variables. While this allows PCMCI to relax the common DAG assumption and allow for cycles, it results in a mixed summary graph, where multiple types of edges ($\leftarrow$, $\rightarrow$, and/or ∘—∘) can exist between two nodes. In contrast, we require all algorithms to output a directed graph. Therefore, when reporting F1 scores for PCMCI, we only include directed edges coming from lagged relationships and exclude the contemporaneous ∘—∘ edges. The only exception is what we call 'Mixed PCMCI' (See Supplementary Figures 26- 28), where the contemporaneous ∘—∘ edges are also included in the computation of *adjacency* F1 scores.

PCMCI$^+$. PCMCI$^+$ is an extension of the PCMCI method which incorporates directed contemporaneous links in addition to the lagged ones [59]. The approach revolves around two key concepts. First, it divides the skeleton edge removal phase into separate lagged and contemporaneous conditioning phases, thereby reducing the number of conditional independence tests required. Second, it incorporates the idea of momentary conditional independence (MCI) tests from PCMCI [1] specifically in the contemporaneous conditioning phase. PCMCI$^+$ also outputs a time-series graph with different types of contemporaneous edges, including directed edges ($\rightarrow$ and $\leftarrow$), unoriented edges (∘—∘), and conflicting edges ($\times - \times$). Consistent with our requirement of a regular digraph at the end, we disregarded the unoriented and conflicting edges and retained only the directed ones. Similar to most other causal discovery algorithms, PCMCI$^+$ does not permit cycles in the contemporaneous links, which could potentially account for its relatively underwhelming performance over fMRI data. The Python implementation of PCMCI+ is also available in the Tigramite package `https://github.com/jakobrunge/tigramite`.

VARLiNGAM. VARLiNGAM is a causal discovery method that combines non-Gaussian instantaneous models with autoregressive models. This method, proposed in [60], builds on the fact that in the absence of unobserved confounders, linear non-Gaussian models can be identified without prior knowledge of the network structure. VARLiNGAM is capable of estimating both contemporaneous and lagged causal effects in models that belong to the class of structural vector autoregressive (SVAR) models and provides ways to assess the significance of the estimated causal relations. These models are a combination of structural equation models (SEM) and vector autoregressive (VAR) models. In addition, VARLiNGAM emphasizes the importance of considering contemporaneous influences, as neglecting them can lead to misleading interpretations of causal effects. Nevertheless, VARLiNGAM does not permit cycles in the contemporaneous links either, which could

potentially account for its relatively poor performance over brain fMRI data with many feedback loops. The VARLiNGAM method is available from `https://github.com/cdt15/lingam` and a tutorial can be found at `https://lingam.readthedocs.io/en/latest/tutorial/var.html`.

DYNOTEARS. Dynamic NOTEARS (DYNOTEARS) method, proposed in [61], is a score-based method designed to discover causal relationships in dynamic data. It simultaneously estimates relationships between variables within a time slice and across different time slices by minimizing a penalized loss function while ensuring that the resulting directed graph is acyclic (including acyclicity of contemporaneous connections). The goal is to identify the best set of conditional dependencies that are consistent with the observed data. DYNOTEARS builds on the original NOTEARS method proposed in [103], which uses algebraic properties to characterize acyclicity in directed graphs for static data. Python implementations are available from the CausalNex library (`https://github.com/quantumblacklabs/causalnex`) as well as `https://github.com/ckassaad/causal_discovery_for_time_series`.

DGlearn. DGlearn is a score-based method for discovering causal relationships from observational data. Importantly, it is one of few algorithms that can learn cyclic structures from cross-sectional data. The method, introduced in [63], is based on a novel characterization of equivalence for potentially cyclic linear Gaussian directed graphical models. Two structures are considered equivalent if they can generate the same set of data distributions. DGlearn utilizes a greedy graph modification algorithm to return a graph within the equivalence class of the original data-generating structure. The Python implementation of DGlearn is available at `https://github.com/syanga/dglearn`.

FASK. The Fast Adjacency Skewness (FASK) method, proposed in [57], is a hybrid method for causal discovery from cross-sectional data, combining constraint-based and noise-based elements. It leverages (and needs) non-Gaussianity in the data and allows for cycles. This algorithm is composed of two main steps. The first step, called FAS-Stable, outputs an undirected graph G_0 by iteratively performing conditional independence tests under the increasing size of the conditioning set and using the Bayesian information criterion (BIC) to compare the conditioning sets. In the second step, assuming i.i.d. non-Gaussian data, each of the $X - Y$ adjacencies in G_0 are oriented as a 2-cycle ($\leftrightarrows$) if the difference between $corr(X, Y)$ and $corr(X, Y | X > 0)$, and $corr(X, Y)$ and $corr(X, Y | Y > 0)$, are both significantly nonzero, and as a unidirectional edge otherwise. The pseudo-code for FASK can be found in Supporting Information A of [57] and Java source code for it is available at `http://github.com/cmu-phil/tetrad`.

MVGC. In [51], Granger introduced a statistical version of Hume's regularity theory, stating that X_p Granger-causes X_q, if past values of X_p provide unique, statistically significant information about future values of X_q [8]. While this allows for optimal forecasting of an effect and has been extended to multivariate systems [20], MVGC cannot account for contemporaneous effects and the presence of unobserved confounders can result in spurious edges. Python implementation of MVGC is available at `https://github.com/ckassaad/causal_discovery_for_time_series`.

NTS-NOTEARS. NTS-NOTEARS is a nonlinear causal discovery method designed for time-series data [78]. It employs 1-D convolutional neural networks to capture various types of relationships, including linear, nonlinear, lagged, and contemporaneous connections among variables. The method ensures that the resulting causal structure forms a directed acyclic graph. It builds upon the NOTEARS approach [103], and is similarly based on continuous optimization. Similar to other algorithms above, it assumes the presence of no hidden confounding factors and stationarity of the data-generating process. In our analysis, we compare NTS-NOTEARS as a state-of-the-art nonlinear method against the aforementioned linear algorithms in synthetic fMRI (cf. Supplementary Figure 35). A Python implementation of NTS-NOTEARS is available at `https://github.com/xiangyu-sun-789/NTS-NOTEARS`

CaLLTiF (proposed method). The proposed CaLLTiF method builds upon PCMCI [1] but, instead of using a PC-type approach in the first step to estimate the set of parents for lagged variables, it starts from a complete conditioning set including all lagged variables. This choice dramatically decreases computational

cost, but surprisingly, it is also optimal, as shown in Extended Data Figure 1, because as mentioned in the discussion section, the approach of PCMCI discards contemporaneous effects. Using a complete conditioning set, CaLLTiF then performs Momentary Conditional Independence (MCI) partial correlation tests between all pairs of variables. Specifically, for any pair $X_i(t - \tau), X_j(t)$ with $i, j \in 1, \ldots, N$ and time delays $\tau \in 0, 1, \ldots, \tau_{max}$, a causal link is established ($X_i(t - \tau) \rightarrow X_j(t)$ if $\tau > 0$ and $X_i(t) \circ\!\!-\!\!\circ X_j(t)$ if $\tau = 0$), if and only if:

$$\text{Cond. Ind. Test} : X_i(t - \tau) \not\perp\!\!\!\perp X_j(t) \mid \{X_k(t - s) : k = 1, \ldots, N, s = 1, \ldots, \tau_{\max}\} \setminus \{X_i(t - \tau)\}. \quad (1)$$

Note that, despite being complete, the conditioning sets only include variables from *prior* time lags. As noted earlier, to test a conditional independence of the form $X \not\perp\!\!\!\perp Y|Z$, we compute the partial correlation coefficient $\rho(X, Y|Z)$ between X and Y conditioned on the set of variables in Z and the corresponding p-value for the null hypothesis that $\rho(X, Y|Z) = 0$. An edge is placed between $X_j(t)$ and $X_i(t - \tau)$ if this p-value is less than the hyperparameter 'Alpha Level'. The value of this threshold was selected optimally in simulated fMRI and using temporal correction for multiple comparisons (see below) in real data. Finally, for contemporaneous pairs ($\tau = 0$), each $\circ\!\!-\!\!\circ$ edge is replaced with $\leftrightarrows$ if there are no other edges between those two variables at other lags, and is replaced with a directed edge or a $\leftrightarrows$ based on the lagged direction(s) otherwise. For a more detailed summary of the partial correlation-based edge discovery in CaLLTiF, see Supplementary Note 2.

Finally, it is imperative to acknowledge the possibility that some of the directed edges detected by our methodology do not possess a strictly causal connotation. As previously indicated, the orientation method relies on the widely accepted premise that bidirectional connections hold notably greater prevalence than unidirectional links. Thus, we believe that the presented approach shall yield a proximate representation of the true causal graph, concurrently accommodating cyclic structures and circumventing computational barriers.

Construction of summary causal graphs from causal graphs over lagged variables

Causal discovery algorithms designed for time series data often return a causal graph among the lagged variables

$$\begin{aligned}
&X_1(t - \tau_{\max}), \ldots, X_1(t - 1), X_1(t) \\
&X_2(t - \tau_{\max}), \ldots, X_2(t - 1), X_2(t) \\
&\vdots \\
&X_n(t - \tau_{\max}), \ldots, X_n(t - 1), X_n(t)
\end{aligned} \quad (2)$$

From this, we extract a final *summary* graph among the variables $X_1, \ldots, X_n$ by placing an edge from X_i to X_j if there exists any $\tau \geq 0$ for which there is an edge from $X_i(t - \tau)$ to $X_j(t)$. This is equivalent to an OR operation among binary edges (as opposed, e.g., to a majority vote) and must be taken into account when interpreting the obtained summary graphs.

Correction for multiple comparisons across lags in CaLLTiF

As noted above, CaLLTiF places an edge from X_i to X_j in its summary graph if there exists at least one $\tau \geq 0$ for which there is an edge from $X_i(t - \tau)$ to $X_j(t)$. Therefore, the decision to place an edge from X_i to X_j depends on the outcomes of $\tau_{\max} + 1$ statistical tests, and to maintain a desired bound on the probability of type I error for each edge in the *summary* graph, we need to account for multiple comparisons across lags.

Formally, for each edge $X_i \rightarrow X_j$ in the final graph, the null hypothesis (i.e., lack of a direct causal effect from X_i to X_j) can be formulated as

$$H_0 = H_{0,0} \cap H_{0,1} \cap \cdots \cap H_{0,\tau_{\max}} = \bigcap_{\tau=0}^{\tau_{\max}} H_{0,\tau},$$

$$H_{0,\tau} = \{X_i(t - \tau) \not\rightarrow X_j(t)\}.$$

Let p_τ denote the p-value of the partial correlation test between $X_i(t - \tau)$ and $X_j(t)$ and q denote the significance threshold for each partial correlation test. Then, the probability of type I error is

$$\text{P(Type I Error)} = P\Big(\bigcup_{\tau=0}^{\tau_{\max}} \{p_\tau < q\} \,\Big|\, \bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big)$$

Note that this is different from the family-wise error rate (FWER, bounded by the Bonferroni method and its extensions) or the false discovery rate (FDR). In particular, this is different from FWER in that only one decision is made and the probability of error is computed for that single decision only. So, for instance, if in reality any subset (even one) of $\{H_{0,\tau}\}$ is false and the algorithm rejects any subset (even all) of $\{H_{0,\tau}\}$, there is no type I error, as an edge exists from X_i to X_j both in the data-generating process and in the final summary graph.

The type I error can then be bounded as

$$
\begin{aligned}
P\text{(Type I Error)} &= P\Big(\bigcup_{\tau=0}^{\tau_{\max}} \{p_\tau < q\} \,\Big|\, \bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big) \leq \sum_{\tau=0}^{\tau_{max}} P\Big(\{p_\tau < q\} \,\Big|\, \bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big) \\
&= \sum_{\tau=0}^{\tau_{max}} \frac{P\Big(\{p_\tau < q\} \cap \bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big)}{P\big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \big)} \leq \sum_{\tau=0}^{\tau_{max}} \frac{P\Big(\{p_\tau < q\} \cap H_{0,\tau} \Big)}{P\big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \big)} \\
&= \sum_{\tau=0}^{\tau_{max}} \frac{P(H_{0,\tau})}{P\big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \big)} \frac{P\Big(\{p_\tau < q\} \cap H_{0,\tau} \Big)}{P(H_{0,\tau})} = q \sum_{\tau=0}^{\tau_{max}} \frac{P(H_{0,\tau})}{P\big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \big)}
\end{aligned}
\tag{3}
$$

The last expression has no dependence on the data and depends only on the prior distribution we consider on graphs. Assuming a uniform prior, $P(H_{0,\tau}) = 1/2$. Further,

$$P\Big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big) = P(H_{0,0}|H_{0,1} \cap \cdots \cap H_{0,\tau_{\max}}) \cdots P(H_{0,\tau_{\max}-1}|H_{0,\tau_{\max}}) \cdot P(H_{0,\tau_{\max}})$$

We assume a prior where knowledge of the lack of an edge from X_i to X_j at one lag either increases the probability of lack of an edge between them at other lags or, at least, does not decrease it (independence across lags). Then,

$$P\Big(\bigcap_{\sigma=0}^{\tau_{\max}} H_{0,\sigma} \Big) \geq P(H_{0,0}) \cdots P(H_{0,\tau_{\max}-1}) \cdot P(H_{0,\tau_{\max}}) = \Big(\frac{1}{2} \Big)^{\tau_{\max}+1}$$

Putting everything together, we get

$$P\text{(Type I Error)} \leq q \frac{(\tau_{\max} + 1)/2}{(1/2)^{\tau_{\max}+1}} = q(\tau_{\max} + 1)2^{\tau_{\max}}.$$

Note, for analogy, that the correction factor $(\tau_{\max} + 1)2^{\tau_{\max}}$ takes place of the factor $(\tau_{\max} + 1)$ in a corresponding Bonferroni correction. To have P(Type I Error) less than a prescribed threshold α, we choose

$$q = \frac{\alpha}{(\tau_{\max} + 1)2^{\tau_{\max}}} \tag{4}$$

In our experiments with the HCP data, we have $\tau_{max} = 3$ and $\alpha = 0.01$, giving a per-lag significance threshold of approximately 0.0003. This is notably smaller than the Alpha Level values that maximized F1 scores in simulated Full Macaque data (0.1 for adjacency F1 score and 0.01 for F1 score), and is due to the conservative nature of this correction for temporal multiple comparisons.

Computing Functional Graphs

In order to calculate the functional graphs for each subject, we consolidated the data from the four sessions of each subject in the HCP and computed the pairwise correlations among all pairs of parcels. To form a binary functional graph, we placed an edge between any two parcels displaying a statistically significant correlation coefficient ($p < 0.01$, t-test for Pearson correlation coefficient).

Hyperparameter Selection

All the methods we described in Table 1 have at least one main hyperparameter that significantly affects the end result, particularly in terms of edge density. These include 'PC Alpha' and 'Alpha Level' for PCMCI, 'PC Alpha' for PCMCI$^+$, 'Alpha' for VARLINGAM, DYNOTEARS, and MVGC, and FASK, and 'BIC Coefficient' for DGlearn. These hyperparameters were swept over (simultaneously for PCMCI) using the simulated data and selected such that the F1 score with the ground truth graph is maximized in each case. This process was repeated for all algorithms and all experiments (simple graphs, Small-Degree Macaque, Full Macaque). Performance metrics such as Recall, Precision, and F1 scores of each method for a range of their hyperparameters are shown in Supplementary Figures 6-12 for the simulated Simple Network graphs, in Supplementary Figures 19-23 for the simulated Small-Degree Macaque data, and in Supplementary Figures 29-35 for the simulated Full Macaque data.

Time-series algorithms (PCMCI, PCMCI$^+$, VARLiNGAM, DYNOTEARS) also have a hyperparameter controlling the number of lags used for causal discovery. Based on our prior work [75], we set this value to 3 for the HCP data (TR = 0.72s), and confirmed its sufficiency based on the contributions of higher-order lags (Figure 6a). For the simulated data, (TR = 1.2s), we used a maximum lag of 2 to match its slower sampling.

Computing F1 Scores, Degrees, and Causal Flows

In our experiments using simulated fMRI data, access to ground truth graphs allows for evaluating the performance of causal discovery methods. In this work, we evaluate causal discovery algorithms as binary classifiers deciding the presence or lack of n^2 edges among n nodes. This allows us to evaluate algorithms using standard classification metrics such as precision, recall, and F1 score [104–108]. Given that the F1 score provides a balanced trade-off between precision and recall, we use it as our measure of accuracy. We define two separate metrics, (full) F1 score and adjacency F1 score. For the former, each of the n^2 edges (including any self-loops due to dampening autocorrelation for each node) in the graph is considered as one test sample for classification. In the latter, the ground-truth and learned graphs are first transformed into an undirected skeleton, placing an edge between two nodes if a directed edge existed in at least one direction. The resulting $\binom{n}{2}$ possible edges are then treated as test samples for classification and computation of adjacency F1 score.

To determine the degree and causal flow of a node i in a *binary* directed graph, its in-degree (number of edges pointing toward node i) and out-degree (number of edges originating from node i) are first computed and normalized by the total number of nodes in the graph. The degree of node i is then computed as the sum of the out-degree and in-degree, while the causal flow is obtained by subtracting the in-degree from the out-degree. The same process is followed for weighted graphs except that the calculation of in-degree and out-degree involves a weighted mean. Mathematically,

$$Causal\ Flow\ (i) = \frac{1}{N}\sum_{j=1}^{N} G(i,j) - \frac{1}{N}\sum_{j=1}^{N} G(j,i)\ \ ,\ \ i = 1, 2, ..., N$$

$$Degree\ (i) = \frac{1}{N}\sum_{j=1}^{N} G(i,j) + \frac{1}{N}\sum_{j=1}^{N} G(j,i)\ \ ,\ \ i = 1, 2, ..., N$$

where G denotes the graph's (binary or weighted) adjacency matrix.

Computing Subnetwork Graphs from Parcel-Level Graphs

Subnetwork graphs were computed by aggregating parcel-level binary graphs into graphs between 16 subnetworks. These subnetworks consist of the standard 7 resting-state subnetworks [109] plus one subcortical subnetwork, separately for the left and right hemispheres. A subnetwork-level graph is then computed for each subject, whereby the weight of an edge from subnetwork i to j is the number of nodes in subnetwork i that connect to nodes in subnetwork j, normalized by the number of all possible edges between these subnetworks. The results are then averaged over the subject, as depicted in Supplementary Figure 48.

Computing

All the computations reported in this study were performed on a Lenovo P620 workstation with AMD 3970X 32-Core processor, Nvidia GeForce RTX 2080 GPU, and 512GB of RAM.

Additional Information

Author Contributions

EN and AG designed and supervised the study; FA performed the research; HJ and MAKP assisted in the analyses of human fMRI data; FA and EN drafted and all authors edited the manuscript.

Acknowledgments

The research conducted in this study was partially supported by NSF Award #2239654 to EN and by the Canadian Institute for Advanced Research (fellowship awarded to MAKP).

Competing financial interests

The authors declare no competing financial interests.

Data Availability Statement

All the fMRI data used in this work is publicly available. The simulated fMRI benchmarks can be downloaded from `https://github.com/cabal-cmu/Feedback-Discovery` and the human fMRI data can be accessed via the HCP S1200 Release at `https://www.humanconnectome.org/study/hcp-young-adult/document/1200-subjects-data-release`.

Code Availability Statement

The Python code for this study is publicly available at `https://github.com/nozarilab/2023Arab_CaLLTiF`.

References

[1] J. Runge, P. Nowack, M. Kretschmer, S. Flaxman, D. Sejdinovic, Detecting and quantifying causal associations in large nonlinear time series datasets, Science Advances 5 (11) (2019) eaau4996. `doi:10.1126/sciadv.aau4996`.

[2] L. A. Jorgenson, W. T. Newsome, D. J. Anderson, C. I. Bargmann, E. N. Brown, K. Deisseroth, J. P. Donoghue, K. L. Hudson, G. S. Ling, P. R. MacLeish, et al., The brain initiative: developing technology to catalyse neuroscience discovery, Philosophical Transactions of the Royal Society B: Biological Sciences 370 (1668) (2015) 20140164.

[3] K. Amunts, C. Ebell, J. Muller, M. Telefont, A. Knoll, T. Lippert, The human brain project: creating a european research infrastructure to decode the human brain, Neuron 92 (3) (2016) 574–581.

[4] A. Adams, S. Albin, K. Amunts, T. Asakawa, A. Bernard, J. G. Bjaalie, K. Chakli, J. O. Deshler, Y. De Koninck, C. J. Ebell, et al., International brain initiative: an innovative framework for coordinated global brain research efforts, Neuron 105 (2) (2020) 212–216.

[5] M.-m. Poo, J.-l. Du, N. Y. Ip, Z.-Q. Xiong, B. Xu, T. Tan, China brain project: basic neuroscience, brain diseases, and brain-inspired computing, Neuron 92 (3) (2016) 591–596.

[6] H. Okano, A. Miyawaki, K. Kasai, Brain/minds: brain-mapping project in japan, Philosophical Transactions of the Royal Society B: Biological Sciences 370 (1668) (2015) 20140310.

[7] C. Glymour, K. Zhang, P. Spirtes, Review of causal discovery methods based on graphical models, Frontiers in genetics 10 (2019) 524.

[8] C. K. Assaad, E. Devijver, E. Gaussier, Survey and evaluation of causal discovery methods for time series, Journal of Artificial Intelligence Research 73 (2022) 767–819.

[9] J. B. Goense, N. K. Logothetis, Neurophysiology of the bold fmri signal in awake monkeys, Current Biology 18 (9) (2008) 631–640. doi:https://doi.org/10.1016/j.cub.2008.03.054.

[10] Z. Q. Winder AT, Echagarruga C, D. PJ, Weak correlations between hemodynamic signals and ongoing neural activity during the resting state, Nature Neuroscience 18 (2017) 17611769–640. doi:10.1038/s41593-017-0007-y.

[11] S. L. Bressler, V. Menon, Large-scale brain networks in cognition: emerging methods and principles, Trends in Cognitive Sciences 14 (6) (2010) 277–290. doi:https://doi.org/10.1016/j.tics.2010.04.004.
URL https://www.sciencedirect.com/science/article/pii/S1364661310000896

[12] E. Bullmore, O. Sporns, The economy of brain network organization, Nature Reviews Neuroscience 13 (5) (2012) 336–349.

[13] A. Fornito, E. T. Bullmore, Connectomics: A new paradigm for understanding brain disease, European Neuropsychopharmacology 25 (5) (2015) 733–748, advances in neuroscience for improved mental health: an ECNP analysis of progress and prospects. doi:https://doi.org/10.1016/j.euroneuro.2014.02.011.

[14] U. Hasan, E. Hossain, M. O. Gani, A survey on causal discovery methods for temporal and non-temporal data, arXiv preprint arXiv:2303.15027 (2023).

[15] A. Gerhardus, J. Runge, High-recall causal discovery for autocorrelated time series with latent confounders, in: H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, H. Lin (Eds.), Advances in Neural Information Processing Systems, Vol. 33, Curran Associates, Inc., 2020, pp. 12615–12625.

[16] D. Malinsky, P. Spirtes, Causal structure learning from multivariate time series in settings with unmeasured confounding, in: T. D. Le, K. Zhang, E. Kıcıman, A. Hyvärinen, L. Liu (Eds.), Proceedings of 2018 ACM SIGKDD Workshop on Causal Disocvery, Vol. 92 of Proceedings of Machine Learning Research, PMLR, 2018, pp. 23–47.

[17] D. Entner, P. O. Hoyer, On causal discovery from time series data using fci, Probabilistic graphical models (2010) 121–128.

[18] J. D. Ramsey, S. J. Hanson, C. Hanson, Y. O. Halchenko, R. A. Poldrack, C. Glymour, Six problems for causal inference from fmri, Neuro]mage 223 (2010) 1545–1558. doi:https://doi.org/10.1016/j.neuroimage.2009.08.065.

[19] A. K. Seth, A. B. Barrett, L. Barnett, Granger causality analysis in neuroscience and neuroimaging, Journal of Neuroscience 35 (8) (2015) 3293–3297.

[20] L. Barnett, A. K. Seth, The mvgc multivariate granger causality toolbox: A new approach to granger-causal inference, Journal of Neuroscience Methods 223 (2014) 50–68. doi:https://doi.org/10.1016/j.jneumeth.2013.10.018.

[21] S. A. Huettel, A. W. Song, G. McCarthy, Functional Magnetic Resonance Imaging, 2nd Edition, Sinauer Associates, 2009.

[22] P. L. Nunez, R. Srinivasan, Electric Fields of the Brain: The Neurophysics of EEG, Oxford University Press, 2006.

[23] S. Sutton, M. Braren, J. Zubin, E. John, Evoked-potential correlates of stimulus uncertainty, Science 150 (3700) (1965) 1187–1188.

[24] S. Sutton, H. Begleiter, Evoked brain potentials and behavior (1979).

[25] E. Nozari, F. Pasqualetti, J. Cortés, Heterogeneity of central nodes explains the benefits of time-varying control scheduling in complex dynamical networks, Journal of Complex Networks 7 (5) (2019) 659–701.

[26] K. Friston, L. Harrison, W. Penny, Dynamic causal modelling, NeuroImage 19 (4) (2003) 1273–1302. doi:https://doi.org/10.1016/S1053-8119(03)00202-7.

[27] K. J. Friston, J. Kahan, B. Biswal, A. Razi, A dcm for resting state fmri, NeuroImage 94 (2014) 396–407. doi:https://doi.org/10.1016/j.neuroimage.2013.12.009.
URL https://www.sciencedirect.com/science/article/pii/S1053811913012135

[28] K. Friston, K. H. Preller, C. Mathys, H. Cagnan, J. Heinzle, A. Razi, P. Zeidman, Dynamic causal modelling revisited, NeuroImage 199 (2019) 730–744. doi:https://doi.org/10.1016/j.neuroimage.2017.02.045.

[29] K. E. Stephan, A. Roebroeck, A short history of causal modeling of fmri data, Neuroimage 62 (2) (2012) 856–863.

[30] K. J. Friston, Functional and effective connectivity: A review, Brain Connectivity 1 (1) (2011) 13–36.

[31] K. Friston, R. Moran, A. K. Seth, Analysing connectivity with granger causality and dynamic causal modelling, Current opinion in neurobiology 23 (2) (2013) 172–178.

[32] N. K. Logothetis, What we can do and what we cannot do with fmri, Nature 453 (7197) (2008) 869–878.

[33] J. Pearl, Causality: Models, Reasoning, and Inference, Cambridge University Press, 2009.

[34] J. Pearl, Probabilistic reasoning in intelligent systems: networks of plausible inference, Morgan kaufmann, 1988.

[35] P. Spirtes, C. N. Glymour, R. Scheines, Causation, prediction, and search, MIT press, 2000.

[36] J. Pearl, Causal inference in statistics: An overview (2009).

[37] P. Spirtes, K. Zhang, Causal discovery and inference: concepts and recent methodological advances, in: Applied informatics, Vol. 3, Springer, 2016, pp. 1–28.

[38] P. Spirtes, C. Glymour, An algorithm for fast recovery of sparse causal graphs, Social Science Computer Review 9 (1) (1991) 62–72.

[39] P. Spirtes, C. Meek, T. Richardson, Causal inference in the presence of latent variables and selection bias, in: Proceedings of the Eleventh Conference on Uncertainty in Artificial Intelligence, 1995, pp. 499–506.

[40] C. Meek, Graphical models: selecting causal and statistical models, Ph.D. thesis, Carnegie Mellon University (1997).

[41] C. Meek, Causal inference and causal explanation with background knowledge, in: Conference on Uncertainty in Artificial Intelligence, 1995.

[42] D. M. Chickering, Learning equivalence classes of bayesian-network structures, The Journal of Machine Learning Research 2 (2002) 445–498.

[43] S. Shimizu, P. O. Hoyer, A. Hyvärinen, A. Kerminen, A linear non-gaussian acyclic model for causal discovery, Journal of Machine Learning Research 7 (2006) 2003–2030.

[44] T. R. Henry, K. M. Gates, Causal search procedures for fmri: review and suggestions, Behaviormetrika 44 (2017) 193–225.

[45] S. M. Smith, K. L. Miller, G. Salimi-Khorshidi, M. Webster, C. F. Beckmann, T. E. Nichols, J. D. Ramsey, M. W. Woolrich, Network modelling methods for fmri, NeuroImage (2011) 875–891 doi: https://doi.org/10.1016/j.neuroimage.2010.08.063.

[46] A. P. Dawid, Conditional independence in statistical theory, Journal of the Royal Statistical Society Series B: Statistical Methodology 41 (1) (1979) 1–15.

[47] S. Shimizu, Lingam: Non-gaussian methods for estimating causal structures, Behaviormetrika 41 (2014) 65–98.

[48] D. Heckerman, D. Geiger, D. M. Chickering, Learning bayesian networks: The combination of knowledge and statistical data, Machine learning 20 (1995) 197–243.

[49] D. M. Chickering, Optimal structure identification with greedy search, Journal of machine learning research 3 (Nov) (2002) 507–554.

[50] D. C. V. Essen, S. M. Smith, D. M. Barch, T. E. Behrens, E. Yacoub, K. Ugurbil, The wu-minn human connectome project: an overview, NeuroImage 80 (2013) 62–79. doi:doi:10.1016/j.neuroimage.2013.05.041.

[51] C. W. J. Granger, Investigatinag causal relations by econometric models and cross-spectral methods, Econometrica 37 (3) (1969) 424–438.

[52] A. Roebroeck, E. Formisano, R. Goebel, Mapping directed influence over the brain using granger causality and fmri, Neuroimage 25 (1) (2005) 230–242.

[53] R. Goebel, A. Roebroeck, D.-S. Kim, E. Formisano, Investigating directed cortical interactions in time-resolved fmri data using vector autoregressive modeling and granger causality mapping, Magnetic resonance imaging 21 (10) (2003) 1251–1261.

[54] W. Liao, D. Mantini, Z. Zhang, Z. Pan, J. Ding, Q. Gong, Y. Yang, H. Chen, Evaluating the effective connectivity of resting state networks using conditional granger causality, Biological cybernetics 102 (2010) 57–69.

[55] M. Ding, Y. Chen, S. L. Bressler, Granger causality: basic theory and application to neuroscience, Handbook of time series analysis: recent theoretical developments and applications (2006) 437–460.

[56] J. D. Ramsey, K. Zhang, M. Glymour, R. S. Romero, B. Huang, I. Ebert-Uphoff, S. Samarasinghe, E. A. Barnes, C. Glymour, Tetrad—a toolbox for causal discovery, in: 8th international workshop on climate informatics, 2018, pp. 1–4.

[57] R. Sanchez-Romero, J. Ramsey, K. Zhang, M. Glymour, B. Huang, C. Glymour, Estimating feed-forward and feedback effective connections from fmri time series: Assessments of statistical methods, Network Neuroscience 86 (2019) 274–306. doi:doi:10.1162/netn_a_00061.

[58] E. Rawls, E. Kummerfeld, B. A. Mueller, S. Ma, A. Zilverstand, The resting-state causal human connectome is characterized by hub connectivity of executive and attentional networks, Neuroimage 255 (2022) 119211.

[59] J. Runge, Discovering contemporaneous and lagged causal relations in autocorrelated nonlinear time series datasets, in: Conference on Uncertainty in Artificial Intelligence, PMLR, 2020, pp. 1388–1397.

[60] A. Hyvärinen, K. Zhang, S. Shimizu, P. O. Hoyer, Estimation of a structural vector autoregression model using non-gaussianity, Journal of Machine Learning Research 11 (56) (2010) 1709–1731. URL http://jmlr.org/papers/v11/hyvarinen10a.html

[61] R. Pamfil, N. Sriwattanaworachai, S. Desai, P. Pilgerstorfer, P. Beaumont, K. Georgatzis, B. Aragam, Dynotears: Structure learning from time-series data, ArXiv abs/2002.00498 (2020).

[62] G. Lacerda, P. Spirtes, J. Ramsey, P. Hoyer, Discovering cyclic causal models by independent components analysis, in: Proceedings of the 24th Conference on Uncertainty in Artificial Intelligence, 2008.

[63] A. Ghassami, A. Yang, N. Kiyavash, K. Zhang, Characterizing distribution equivalence and structure learning for cyclic and acyclic directed graphs, in: International Conference on Machine Learning, PMLR, 2020, pp. 3494–3504.

[64] J. Tigges, W. Spatz, M. Tigges, Reciprocal point-to-point connections between parastriate and striate cortex in the squirrel monkey (saimiri), Journal of Comparative Neurology 148 (4) (1973) 481–489.

[65] D. J. Felleman, D. C. Van Essen, Distributed hierarchical processing in the primate cerebral cortex., Cerebral cortex (New York, NY: 1991) 1 (1) (1991) 1–47.

[66] N. T. Markov, M. M. Ercsey-Ravasz, A. Ribeiro Gomes, C. Lamy, L. Magrou, J. Vezoli, P. Misery, A. Falchier, R. Quilodran, M.-A. Gariel, et al., A weighted and directed interareal connectivity matrix for macaque cerebral cortex, Cerebral cortex 24 (1) (2014) 17–36.

[67] D. M. Barch, Resting-state functional connectivity in the human connectome project: Current status and relevance to understanding psychopathology, Harvard Review of Psychiatry 25 (5) (2017) 209–217. doi:10.1097/HRP.0000000000000166.

[68] G. Burgess, S. Kandala, D. Nolan, T. Laumann, J. Power, B. Adeyemo, M. Harms, S. Petersen, D. Barch, Evaluation of denoising strategies to address motion-correlated artifacts in resting-state functional magnetic resonance imaging data from the human connectome project, Brain Connectivity 6 (9) (2016) 669–680. doi:10.1089/brain.2016.0435.

[69] N. T. Markov, M. Ercsey-Ravasz, D. C. Van Essen, K. Knoblauch, Z. Toroczkai, H. Kennedy, Cortical high-density counterstream architectures, Science 342 (6158) (2013) 1238406.

[70] K. J. Friston, B. Li, J. Daunizeau, K. E. Stephan, Network discovery with dcm, Neuroimage 56 (3) (2011) 1202–1221.

[71] R. Kötter, K. E. Stephan, Network participation indices: characterizing component roles for information processing in neural networks, Neural Networks 16 (9) (2003) 1261–1275.

[72] S. Zeki, S. Shipp, The functional logic of cortical connections, Nature 335 (6188) (1988) 311–317.

[73] P. A. Valdes-Sosa, Spatio-temporal autoregressive models defined over brain manifolds, Neuroinformatics 2 (2004) 239–250.

[74] A. Moneta, N. Chlass, D. Entner, P. Hoyer, Causal search in structural vector autoregressive models, in: F. Popescu, I. Guyon (Eds.), Proceedings of the Neural Information Processing Systems Mini-Symposium on Causality in Time Series, Vol. 12 of Proceedings of Machine Learning Research, PMLR, Vancouver, Canada, 2011, pp. 95–114. URL https://proceedings.mlr.press/v12/moneta11.html

[75] E. Nozari, M. A. Bertolero, J. Stiso, L. Caciagli, E. J. Cornblath, X. He, A. S. Mahadevan, G. J. Pappas, D. S. Bassett, Macroscopic resting-state brain dynamics are best described by linear models, Nature Biomedical Engineering (2023).

[76] S. Ahmed, E. Nozari, On the linearizing effect of spatial averaging in large-scale populations of homogeneous nonlinear systems, in: 2022 IEEE 61st Conference on Decision and Control (CDC), IEEE, 2022, pp. 641–648.

[77] S. Ahmed, E. Nozari, On the linearizing effect of temporal averaging in nonlinear dynamical systems, in: 2023 American Control Conference (ACC), 2023, pp. 4185–4190.

[78] X. Sun, G. Liu, P. Poupart, O. Schulte, Nts-notears: Learning nonparametric temporal dags with time-series data and prior knowledge, arXiv e-prints (2021) arXiv–2109.

[79] M. Corbetta, G. L. Shulman, Control of goal-directed and stimulus-driven attention in the brain, Nature reviews neuroscience 3 (3) (2002) 201–215.

[80] M. Corbetta, G. Patel, G. L. Shulman, The reorienting system of the human brain: from environment to theory of mind, Neuron 58 (3) (2008) 306–324.

[81] S. Vossel, J. J. Geng, G. R. Fink, Dorsal and ventral attention systems: distinct neural circuits but collaborative roles, The Neuroscientist 20 (2) (2014) 150–159.

[82] M. E. Raichle, A. M. MacLeod, A. Z. Snyder, W. J. Powers, D. A. Gusnard, G. L. Shulman, A default mode of brain function, Proceedings of the national academy of sciences 98 (2) (2001) 676–682.

[83] M. D. Greicius, B. Krasnow, A. L. Reiss, V. Menon, Functional connectivity in the resting brain: a network analysis of the default mode hypothesis, Proceedings of the national academy of sciences 100 (1) (2003) 253–258.

[84] J. R. Andrews-Hanna, J. Smallwood, R. N. Spreng, The default network and self-generated thought: Component processes, dynamic control, and clinical relevance, Annals of the new York Academy of Sciences 1316 (1) (2014) 29–52.

[85] P. Mengotti, A.-S. Käsbauer, G. R. Fink, S. Vossel, Lateralization, functional specialization, and dysfunction of attentional networks, Cortex 132 (2020) 206–222.

[86] O. Agcaoglu, R. Miller, A. R. Mayer, K. Hugdahl, V. D. Calhoun, Lateralization of resting state networks and relationship to age and gender, Neuroimage 104 (2015) 310–325.

[87] J. A. Nielsen, B. A. Zielinski, M. A. Ferguson, J. E. Lainhart, J. S. Anderson, An evaluation of the left-brain vs. right-brain hypothesis with resting state functional connectivity magnetic resonance imaging, PloS one 8 (8) (2013) e71275.

[88] N. Swanson, T. Eichele, G. Pearlson, K. Kiehl, Q. Yu, V. D. Calhoun, Lateral differences in the default mode network in healthy controls and patients with schizophrenia, Human brain mapping 32 (4) (2011) 654–664.

[89] S. J. Banks, X. Zhuang, E. Bayram, C. Bird, D. Cordes, J. Z. Caldwell, J. L. Cummings, A. D. N. Initiative, et al., Default mode network lateralization and memory in healthy aging and alzheimer's disease, Journal of Alzheimer's Disease 66 (3) (2018) 1223–1234.

[90] B. E. Morton, Brain executive laterality and hemisity, Personality Neuroscience 3 (2020) e10.

[91] A. F. Alexander-Bloch, P. E. Vértes, R. Stidd, F. Lalonde, L. Clasen, J. Rapoport, J. Giedd, E. T. Bullmore, N. Gogtay, The anatomical distance of functional connections predicts brain network topology in health and schizophrenia, Cerebral cortex 23 (1) (2013) 127–138.

[92] M. Shinn, A. Hu, L. Turner, S. Noble, K. H. Preller, J. L. Ji, F. Moujaes, S. Achard, D. Scheinost, R. T. Constable, et al., Functional brain networks reflect spatial and temporal autocorrelation, Nature Neuroscience (2023) 1–12.

[93] M. Straathof, M. R. Sinke, T. J. Roelofs, E. L. Blezer, R. A. Sarabdjitsingh, A. van der Toorn, O. Schmitt, W. M. Otte, R. M. Dijkhuizen, Distinct structure-function relationships across cortical regions and connectivity scales in the rat brain, Scientific Reports 10 (1) (2020) 56.

[94] N. Wiener, Extrapolation, interpolation, and smoothing of stationary time series: with engineering applications, MIT press, 1949.

[95] K. J. Friston, P. Fletcher, O. Josephs, A. Holmes, M. Rugg, R. Turner, Event-related fmri: characterizing differential responses, Neuroimage 7 (1) (1998) 30–40.

[96] L. Ljung, System identification: theory for the user, PTR Prentice Hall, Upper Saddle River, NJ (1999) 1–14.

[97] K. M. Gates, P. C. Molenaar, Group search algorithm recovers effective connectivity maps for individuals in homogeneous and heterogeneous samples, NeuroImage 63 (1) (2012) 310–319.

[98] B. Huang, K. Zhang, J. Zhang, J. Ramsey, R. Sanchez-Romero, C. Glymour, B. Schölkopf, Causal discovery from heterogeneous/nonstationary data, The Journal of Machine Learning Research 21 (1) (2020) 3482–3534.

[99] R. B. Buxton, E. C. Wong, L. R. Frank, Dynamics of blood flow and oxygenation changes during brain activation: the balloon model, Magnetic resonance in medicine 39 (6) (1998) 855–864.

[100] J. Elam, Hcp Data Release Updates: Known Issues and Planned Fixes, `https://wiki.humanconnectome.org/display/PublicData/HCP+Data+Release+Updates%3A+Known+Issues+and+Planned+fixes`, last accessed May 13, 2020 (May 2020).

[101] A. Schaefer, R. Kong, E. M. Gordon, T. O. Laumann, X.-N. Zuo, A. J. Holmes, S. B. Eickhoff, B. T. T. Yeo, Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity mri, Cerebral cortex 28 (9) (2018) 3095–3114. `doi:10.1093/cercor/bhx179`.

[102] Y. Tian, D. S. Margulies, M. Breakspear, A. Zalesky, Hierarchical organization of the human subcortex unveiled with functional connectivity gradients, bioRxiv (2020). `doi:10.1101/2020.01.22.916357`.

[103] X. Zheng, B. Aragam, P. K. Ravikumar, E. P. Xing, Dags with no tears: Continuous optimization for structure learning, in: S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, R. Garnett (Eds.), Advances in Neural Information Processing Systems, Vol. 31, Curran Associates, Inc., 2018.

[104] D. M. Powers, Evaluation: from precision, recall and f-measure to roc, informedness, markedness and correlation, arXiv preprint arXiv:2010.16061 (2020).

[105] A. Tharwat, Classification assessment methods, Applied Computing and Informatics 17 (1) (2020) 168–192.

[106] T. Fawcett, An introduction to roc analysis, Pattern recognition letters 27 (8) (2006) 861–874.

[107] J. Davis, M. Goadrich, The relationship between precision-recall and roc curves, in: Proceedings of the 23rd international conference on Machine learning, 2006, pp. 233–240.

[108] M. Sokolova, G. Lapalme, A systematic analysis of performance measures for classification tasks, Information processing & management 45 (4) (2009) 427–437.

[109] T. Yeo, F. M. Krienen, J. Sepulcre, M. R. Sabuncu, D. Lashkari, M. Hollinshead, J. L. Roffman, J. W. Smoller, L. Zöllei, J. R. Polimeni, B. Fischl, H. Liu, R. L. Buckner, The organization of the human cerebral cortex estimated by intrinsic functional connectivity, Journal of neurophysiology 106 (3) (2011) 1125–1165.

(a)

(b)

(c)

Extended Data Figure 1: The effect of the 'PC Alpha' hyperparameter of PCMCI on its performance over simulated Small-Degree Macaque fMRI. (a) Mean Execution time for different values of PC Alpha, showing a super-exponential growth. (b,c) F1 scores for varying values of PC Alpha and Alpha Level. Alpha Level denotes a second hyperparameter that controls the sparsity of the returned graph (the higher the Alpha Level the denser the resulting graphs). Best F1 scores are achieved for PC Alpha = 1. In all graphs, the error bars depict the standard error of the mean.