Title: Human EEG and artificial neural networks reveal disentangled representations of object real-world size in natural images

Abbreviated title: Real-World Size Representations in Natural Images

Authors: Zitong Lu (路子童) & Julie D. Golomb

Affiliations: Department of Psychology, The Ohio State University, Columbus, OH 43212 USA

Corresponding author: Zitong Lu (路子童), email: lu.2637@osu.edu

Acknowledgments: This work was supported by research grants from the National Institutes of Health (R01-EY025648) and from the National Science Foundation (NSF 1848939) to JDG.

Conflict of interest statement: The authors declare no competing financial interests

Number of pages: 38
Number of figures: 9
Number of tables: 2
Abstract – Number of words: 161
Introduction - Number of words: 586
Discussion – Number of words: 1298

Abstract

Human brains have the ability to accurately perceive and process the real-world size of objects, despite vast differences in distance and perspective, which is a remarkable feat of cognitive processing. While previous studies have delved into this phenomenon, our study uses an innovative approach to disentangle neural representations of object real-world size from visual size and perceived real-world depth in a way that was not previously possible. Our multi-modal approach incorporates computational modeling and the THINGS EEG2 dataset, which offers both high time-resolution human brain recordings and more ecologically valid naturalistic stimuli. Leveraging this state-of-the-art dataset, our EEG representational similarity results revealed a pure representation of object real-world size in human brains. We report a representational timeline of visual object processing: pixel-wise differences appeared first, then real-world depth and visual size, and finally, real-world size. Furthermore, representational comparisons with different artificial neural networks reveal real-world size as a stable and higher-level dimension in object space incorporating both visual and semantic information.

Keywords: real-world size, depth perception, RSA, artificial neural networks, object recognition

Significance Statement

Humans possess a remarkable ability to perceive an object's real-world size, regardless of its distance or our viewpoint. Distinguishing this ability from other visual perceptions, like depth, has been challenging. Using advanced EEG datasets with real-world images, our study uniquely separated real-world size perception from other visual cues. We discovered a specific sequence in visual processing, culminating in accurate size perception. Additionally, by comparing with artificial neural networks, we demonstrated that this perception involves both what we see (visual) and what we know (semantic). Our findings offer valuable insights into the human visual process, with implications for both cognitive science and artificial intelligence.

Introduction

Imagine you are viewing an apple tree while walking around an orchard: the visual (retinal) size of the apple changes as your perspective and distance shifts, yet your perception of the apple's real-world size remains constant. How do our brains extract this consistent real-world size information? Behavioral studies have demonstrated that perceived real-world size is represented as an object physical property, revealing same-size priming effects (Setti et al., 2008), familiar-size stroop effects (Konkle & Oliva, 2012a; Long & Konkle, 2017), and canonical visual size effects (Chen et al., 2022; Konkle & Oliva, 2011). Neuroimaging studies support this, suggesting that real-world size is a fundamental dimension of object representation (Huang et al., 2022; S.-M. Khaligh-Razavi et al., 2018; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b; Luo et al., 2023; Quek et al., 2023; Wang et al., 2022).

However, perception of object size is closely related to perception of its distance in depth. For instance, imagine you are looking at two photos: a zoomed in photo of the apple, and a photo of a basketball that fills the same visual (photo) size. You simultaneously infer that the apple is physically smaller and thus located closer to you than the basketball. In previous neuroimaging studies of perceived real-world size (Huang et al., 2022; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b), researchers presented images of familiar objects zoomed and cropped such that they occupied the same visual image size, finding that neural responses in ventral temporal cortex reflected the perceived real-world size (e.g. an apple smaller than a car). However, while they controlled the visual image size of objects, the nature of the stimuli did not allow them to also control for perceived real-world depth. Moreover, the stimuli used in these studies were cropped object stimuli against a plain white or grey background, which are not particularly

naturalistic. More and more studies and datasets have highlighted the important role of naturalistic context in object recognition (Allen et al., 2022; Gifford et al., 2022; Grootswagers et al., 2022; Hebart et al., 2019; Stoinski et al., 2023). In ecological contexts, inferring the real-world size/distance of an object likely relies on a combination of bottom-up visual information and top-down knowledge about canonical object sizes for familiar objects. Incorporating naturalistic background context in experimental stimuli can yield a more nuanced understanding of visual object processing.

In the current study, we aimed to used computational methods to distinguish the neural representations of object real-world size and other size and depth features based on THINGS EEG2 dataset (Gifford et al., 2022), a more ecologically representative dataset with variations in object real-world size, depth, and visual size. This dataset paves the way for an innovative exploration of visual object processing, offering a chance to understand the timeline of how the brain processes perceived object real-world size compared to perceived depth. Furthermore, artificial neural networks (ANNs) have emerged as invaluable tools in cognitive computational neuroscience, with their similar representations to human visual systems (Cichy et al., 2016; Güçlü & van Gerven, 2015; Yamins et al., 2014; Yamins & DiCarlo, 2016). Although a recent study found that ANNs also represent real-world size (Huang et al., 2022), the datasets used had limitations similar to those of previous human studies. We aim to unravel the internal representations in both human brains and ANNs, which provides us deeper approach to not only explore whether both biological and artificial systems represent object real-world size, along with and independent of other size and depth features, but to also investigate possible mechanisms of object real-world size representations.

Materials and Methods

Experimental design and EEG data:

We utilized the open dataset from THINGS EEG2 (Gifford et al., 2022), which includes EEG data from 10 healthy human subjects (age=28.5±4, 8 female and 2 male) in a rapid serial visual presentation (RSVP) paradigm with an orthogonal target detection task to ensure participants paid attention to the visual stimuli. For each trial, subjects viewed one image (sized 500 × 500 pixels) for 100ms. Each subject viewed 16740 images of objects on a natural background for 1854 object concepts from THINGS dataset (Hebart et al., 2019). For the current study, we used the 'test' dataset portion, which includes 16000 trials per subject corresponding to 200 images (200 object concepts, one image per concept) with 80 trials per image. Before inputting the images to the ANNs, we reshaped image sizes to 224 x 224 pixels and normalized the pixel values of images to ImageNet statistics.

EEG data were collected using a 64-channel EASYCAP and a BrainVision actiCHamp amplifier. We used already pre-processed data from 17 channels (O1, Oz, O2, PO7, PO3, POz, PO4, PO8, P7, P5, P3, P1, Pz, P2) overlying occipital and parietal cortex. We re-epoched EEG data ranging from 100ms before stimulus onset to 500ms after onset with a sample frequency of 100Hz. Thus the shape of our EEG data matrix for each trial was 17 channels × 60 time points.

ANN models:

We applied two pre-trained ANN models: one visual model (ResNet-101 (He et al., 2016) pretrained on ImageNet), and one multi-modal (visual+semantic) model (CLIP with a ResNet-101 backbone (Radford et al., 2021) pretrained on YFCC-15M). We used THINGSvision

(Muttenthaler & Hebart, 2021) to obtain low- and high-level feature vectors of ANN activations from early and late layers (early layer: second convolutional layer; late layer: last visual layer) for the images.

Word2Vec model:

To approximate the non-visual, pure semantic space of objects, we also applied a Word2Vec model, a natural language processing model for word embedding, pretrained on Google News corpus (Mikolov et al., 2013), which contains 300-dimensional vectors for 3 million words and phrases. We input the words for each image's object concept (pre-labeled in THINGS dataset: Hebart et al., 2019), instead of the visual images themselves. We used Gensim (Řehůřek & Sojka, 2010) to obtain Word2Vec feature vectors for the objects in images.

Representational dissimilarity matrices (RDMs):

To conduct RSA across human EEG, artificial models, and our hypotheses corresponding to different visual features, we first computed representational dissimilarity matrices (RDMs) for different modalities (Figure 2). The shape of each RDM was 200 × 200, corresponding to pairwise dissimilarity between the 200 images. We extracted the 19900 cells from the upper half of the diagonal of each RDM for subsequent analyses.

Neural RDMs. From the EEG signal, we constructed timepoint-by-timepoint neural RDMs for each subject with decoding accuracy as the dissimilarity index (Figure 2A). We first conducted timepoint-by-timepoint classification-based decoding for each subject and each pair of images (200 images, 19900 pairs in total). We applied linear Support Vector Machine (SVM) to train and test a two-class classifier, employing a 5-time 5-fold cross-validation method, to obtain an

independent decoding accuracy for each image pair and each timepoint. Therefore, we ultimately acquired 60 (1 per timepoint) EEG RDMs for each subject.

Hypothesis-based RDMs. We constructed four hypothesis-based RDMs reflecting the different types of visual object properties in the naturalistic images (Figure 2B): Real-World Size RDM, Visual Size RDM, Real-World Depth RDM, and Pixel-Wise Difference RDM. We constructed these RDMs as follows:

(1) For Real-World Size RDM, we obtained human behavioral real-world size ratings of each object concept from the THINGS+ dataset (Stoinski et al., 2022). In the THINGS+ dataset, 2010 participants (different from the subjects in THINGS EEG2) did an online size rating task and completed a total of 13024 trials corresponding to 1854 object concepts. The range of possible size ratings was from 0 to 519, with the actual mean ratings ranging from 100.03 ('sand') to 423.09 ('subway'). We used these ratings as the perceived real-world size measure of the object concept pre-labeled in THINGS dataset (Hebart et al., 2019) for each image. We then constructed the representational dissimilarity matrix by calculating the difference between perceived real-world size ratings for each pair of images.

(2) For Visual Size RDM, we applied Adobe Photoshop (Adobe Inc., 2019) to crop objects corresponding to object labels from images manually, obtaining a rectangular region that precisely contains a single object, then measured the diagonal length of the segmented object in pixels as the visual size measure. Due to our calculations being at the object level, if there were more than one same objects in an image, we cropped the

most complete one to get more accurate visual size. We then constructed the RDM by calculating the difference between measured visual size for each pair of images.

(3) For Real-World Depth RDM, we calculated the perceived depth based on the measured visual size index and behavioral real-world size ratings, such that real-world depth / visual image depth = real-world size / visual size. Since visual image depth (viewing distance) is held constant across images in the task, real-world depth is proportional to real-world size / visual size. We then constructed the RDM by calculating the difference between real-world depth index for each pair of images.

(4) For Pixel-Wise Difference RDM, we flattened each color image ($3 \times 500 \times 500$) into a vector containing 750000 values and then calculated pixel-wise correlations between image pairs. The dissimilarity index for the RDM was one minus the correlation coefficient.

ANN (and Word2Vec) model RDMs. We constructed a total of five model-based RDMs (Figure 2C). Our primary analyses used four ANN RDMs, corresponding to the early and late layers for both ResNet and CLIP (Figure S1). We also calculated a single Word2Vec RDM for the pure semantic analysis (Figure S2). For each RDM, we got the dissimilarities by calculating 1 – Pearson correlation coefficient between each pair of two vectors of the model features corresponding to two input images.

Representational similarity analyses (RSA) and statistical analyses:

We conducted cross-modal representational similarity analyses between the three types of RDMs (Figure 2). All decoding and RSA analyses were implemented using NeuroRA (Lu & Ku, 2020).

EEG × ANN (or W2V) RSA. To measure the representational similarity between human brains and ANNs and confirm that ANNs have significantly similar representations to human brains, we calculated the Spearman correlation between the 60 timepoint-by-timepoint EEG neural RDMs and the 4 ANN RDMs corresponding to the representations of ResNet early layer, ResNet late layer, CLIP early layer, CLIP late layer, respectively. We also calculated temporal representational similarity between human brains (EEG RDMs) and the Word2Vec model RDM. Cluster-based permutation tests were conducted to determine the time windows of significant representational similarity. First, we performed one-sample t-tests (one-tailed testing) against zero to get the t-value for each timepoint, and extracted significant clusters. We computed the clustering statistic as the sum of t-values in each cluster. Then we conducted 1000 permutations of each subject's timepoint-by-timepoint similarities to calculate a null distribution of maximum clustering statistics. Finally, we assigned cluster-level p-values to each cluster of the actual representational timecourse by comparing its cluster statistic with the null distribution. Time-windows were determined to be significant if the p-value of the corresponding cluster was <0.05.

EEG × HYP RSA. To evaluate how human brains temporally represent different visual features, we calculated the timecourse of representational similarity between the timepoint-by-timepoint EEG neural RDMs and the four hypothesis-based RDMs. To avoid correlations between hypothesis-based RDMs (Figure S3) influencing comparison results, we calculated partial correlations with one-tailed test against the alternative hypothesis that the partial correlation was positive (greater than zero). Cluster-based permutation tests were performed as described above to determine the time windows of significant representational similarity. In addition, we conducted peak latency analysis to determine the latency of peak representational similarity for each type of visual information with the EEG signal. We restricted the time-window to the significant partial

correlation time-window for real-world size, visual size, and real-world depth, and got the individual peak timepoint corresponding to the highest partial correlation. Paired t-tests (two-tailed) were conducted to assess the statistical differences in peak latencies between different visual features.

ANN (or W2V) × HYP RSA. To evaluate how different visual information is represented in ANNs, we calculated representational similarity between the ANN RDMs and hypothesis-based RDMs. As in the EEG × HYP RSA, we calculated partial correlations to avoid correlations between hypothesis-based RDMs. We also calculated the partial correlations between hypothesis-based RDMs and the Word2Vec RDM. To determine statistical significance, we conducted a bootstrap test. We shuffled the order of the cells above the diagonal in each ANN (or Word2Vec) RDM 1000 times. For each iteration, we calculated partial correlations corresponding to the four hypothesis-based RDMs. This produced a 1000-sample null distribution for each HYP x ANN (or W2V) RSA. We hypothesized that if the real similarity was higher than the 95% confidence interval of the null distribution, it indicated that ANN (or W2V) features validly encoded the corresponding visual feature.

Additionally, to explore how the naturalistic background present in the images might influence object real-world size and other size and depth representations, we conducted another version of the analysis by inputting cropped object images without background into ANN models to obtain object-only ANN RDMs (Figure S4). Then we performed the same ANN x HYP similarity analysis to calculate partial correlations between the hypothesis-based RDMs and object-only ANN RDM. (We didn't conduct the similarity analysis between timepoint-by-timepoint EEG neural RDMs with subjects viewing natural images and object-only ANN RDMs due to the input differences.)

Data and code accessibility:

EEG data and images from THINGS EEG2 data are publicly available on OSF (https://osf.io/3jk45/). All Python analysis scripts will be available post-publication on GitHub (https://github.com/ZitongLu1996/RWsize).

Results

We conducted a cross-modal representational similarity analysis (Figures 1-2, see Method section for details) comparing the patterns of human brain activation (timepoint-by-timepoint decoding of EEG data) while participants viewed naturalistic object images, the output of different layers of artificial neural networks and semantic language models fed the same stimuli (ANN and Word2Vec models), and hypothetical patterns of representational similarity based on behavioral and mathematical measurements of different visual image properties (perceived real-world object size, displayed visual object size, perceived real-world object depth, and pixel-wise image similarity).

Dynamic representations of object size and depth in human brains

To explore if and when human brains contain distinct representations of perceived real-world size, visual size, and real-world depth, we constructed timepoint-by-timepoint EEG neural RDMs (Figure 2A), and compared these to four hypothesis-based RDMs corresponding to different visual image properties (Figure 2B). Figure 3A shows the timecourse of representational similarity between the EEG and each hypothesis-based RDM, computed using

partial Spearman correlations. The neural signal showed significant representational similarity with Real-World Size from 170-240ms after stimulus onset. Critically, the partial correlation technique suggests that this reflects a pure representation of object real-world size in the human brain, independent from visual size and real-world depth, which showed significant representational similarity at different time windows (visual size from 90 to 200ms, and real-world depth from 60 to 130ms and 270 to 330ms). These representations of object size and depth are also independent from low-level visual features, as captured by the pixel-wise difference information, which was also included in the partial correlation RSA and significant from 0 to 290ms and 360 to 440ms.

Peak latency results showed that neural representations of real-world size, visual size and real-world depth reached their peaks at different latencies after stimulus onset (real-world depth: ~87ms, visual size: ~143ms, real-world size: ~206ms, Figure 3A left). The representation of real-word size had a significantly later peak latency than that of both visual size (t=3.7347, p=.0047) and real-world depth (t=18.58, p<.001). And visual size representation had a significantly later peak latency than real-world depth (t=3.8501, p=.0039). These varying peak latencies imply an encoding order for distinct visual features, transitioning from real-world depth through visual size, and then to real-world size.

Artificial neural networks also reflect distinct representations of object size and depth

To test how ANNs process these visual properties, we input the same stimulus images into ANN models and got their latent features from early and late layers (Figure 2C), and then conducted comparisons between the ANN RDMs and hypothesis-based RDMs. Parallel to our

findings of dissociable representations of real-world size, visual size, and real-world depth in the human brain signal, we also found dissociable representations of these visual features in ANNs (Figure 3B). Our partial correlation RSA analysis showed that early layers of both ResNet and CLIP had primarily real-world depth and visual size representations, and there was also visual size representation in the late layer of ResNet and real-world depth representation in the late layer of CLIP. However, real-world size was only represented in the late layers of two ANNs. These representations were independent of pixel-wise difference information, also included in the partial correlations. The detailed statistical results are shown in Table S1.

Thus, ANNs provide another approach to understand the formation of different visual features, offering convergent results with the EEG representational analysis, where visual (image) size was reflected most in the early layers of ANNs, while object real-world size representations didn't emerge until late layers of ANNs, consistent with a potential role of higher-level visual information, such as the semantic information of object concepts.

Finally, we directly compared the timepoint-by-timepoint EEG neural RDMs and the ANN RDMs (Figure 3C). The early layer representations of both ResNet and CLIP were significantly correlated with early representations in the human brain (early layer of ResNet: 40-280ms, early layer of CLIP: 50-130ms and 160-260ms), while the late layer representations of two ANNs were significantly correlated with later representations in the human brain (late layer of ResNet: 80-500ms, late layer of CLIP: 70-500ms). This pattern of early-to-late correspondence aligns with previous findings that convolutional neural networks exhibit similar hierarchical representations to those in the brain visual cortex (Cichy et al., 2016; Güçlü & van Gerven, 2015; Kietzmann et al., 2019; Yamins & DiCarlo, 2016): that both the early stage of brain processing and the early layer of the ANN encode lower-level visual information, while the

late stage of the brain and the late layer of the ANN encode higher-level visual information. Also, human brain representations showed a higher similarity to the early layer representation of the visual model (ResNet) than to the visual-semantic model (CLIP) at an early stage. Conversely, human brain representations showed a higher similarity to the late layer representation of the visual-semantic model than visual model at a late stage. Interestingly, the peaks of significant time windows for the EEG × HYP RSA also correspond with the peaks of the EEG × ANN RSA timecourse (Figure 3A,C).

Real-world size as a stable and higher-level dimension in object space

An important aspect of the current study is the use of naturalistic visual images as stimuli, in which objects were presented in their natural contexts, as opposed to cropped images of objects without backgrounds. In natural images, background can play an important role in object perception. How dependent are the above results on the presence of naturalistic background context? To investigate how image context influences object size and depth representations, we next applied a reverse engineering method, feeding the ANNs with modified versions of the stimulus images containing cropped objects without background, and evaluating the ensuing ANN representations compared to the same original hypothesis-based RDMs. If the background significantly contributes to the formation of certain feature representations, we may see some encoding patterns in ANNs disappear when the input only includes the pure object but no background.

Compared to results based on images with background, the ANNs based on cropped-object modified images showed weaker overall representational similarity for all features (Figure

4). In the early layers of both ANNs, we now only observed significantly preserved visual size representations (which is a nice validity check, since visual size measurements were based purely on the physical object dimensions in the image, independent of the background). Real-world depth representations were almost totally eliminated, with only a small effect in the late layer of ResNet. However, we still observed a preserved pattern of real-world size representations, with significant representational similarity in the late layers of both ResNet and CLIP, and not in the early layers. The detailed statistical results are shown in Table S2. Even though the magnitude of representational similarity for object real-world size decreased when we removed the background, this high-level representation was not entirely eliminated. This finding suggests that background information does indeed influence object processing, but the representation of real-world size seems to be a relatively stable higher-level feature. On the other hand, representational formats of real-world depth changed when the input lacked background information. The deficiency of real-world depth representations in early layers, compared to when using full-background images, might suggest that the human brain typically uses background information to estimate object depth, though the significant effect in the late layer of ResNet in background-absent condition might also suggest that the brain (or at least ANN) has additional ability to integrate size information to infer depth when there is no background.

The above results reveal that real-world size emerges with later peak neural latencies and in the later layers of ANNs, regardless of image background information. Is this because real-world size is a more conceptual-level dimension in object semantic space? If so, we might expect it to be driven not only by higher-level visual information, but also potentially by purely semantic information about familiar objects. To test this, we extracted object names from each image and input the object names into a Word2Vec model to obtain a Word2Vec RDM (Figure

S2A), and then conducted a partial correlation RSA comparing the Word2Vec representations with the hypothesis-based RDMs (Figure 5A). The results showed a significant real-world size representation (r=0.1856, p<0.001) but no representation of visual size (r=-0.0061, p=0.8035) or real-world depth (r=-0.0046, p=.7412) from Word2Vec. Also, the significant time-window (90-500ms) of similarity between Word2Vec RDM and EEG RDMs (Figure 5B) contained the significant time-window of EEG x real-world size representational similarity (Figure 3A).

Both the reverse engineering manipulation and Word2Vec findings corroborate that object real-world size representation, unlike visual size and real-world depth, emerges in both image- and semantic-level in object space.

Discussion

Our study applied computational methods to distinguish the representations of object real-world size and other size and depth features in both human brains and ANNs. Consistent with prior studies reporting real-world size representations (Huang et al., 2022; S.-M. Khaligh-Razavi et al., 2018; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b; Luo et al., 2023; Quek et al., 2023; Wang et al., 2022), we found that both human brains and ANNs contain significant information about real-world size. Critically, compared to the prior studies, our study offers several important theoretical and methodological advances: (a) we eliminated the confounding impacts of both visual size and perceived real-world depth on the real-world size representation; (b) we conducted analyses based on more ecologically valid naturalistic images; (c) we obtained precise feature values for each object in every image, instead of simply dividing objects into 2 or 8 categories based on a certain dimension; and (d) we used multi-modal, partial correlation RSA combining

EEG, hypothesis-based models, and ANNs to investigate representational time courses and reverse engineering manipulations.

Using EEG we uncovered a representational timeline for visual object processing, with pixel-wise difference information represented first, followed by real-world depth and visual size, and finally real-world size. While size and depth are highly correlated to each other, our results suggest that the human brain indeed has dissociated time courses and mechanisms to process them. The later representation time-window for object real-world size may suggest that the brain requires more sophisticated, higher-level information to form this representation, perhaps incorporating semantic and/or memory information about familiar objects, which was corroborated by our ANN and Word2Vec analyses. These findings also align with a recent fMRI study (Luo et al., 2023) using natural images to explore the neural selectivity for real-world size, finding that low-level visual information could hardly account for neural size preferences, although that study did not consider covariables like visual size and real-world depth. In general, very few studies discuss the relationship between real-world size and real-world depth, and the possible confounding influence of depth has been generally overlooked in studies investigating real-world size representations (Huang et al., 2022; S.-M. Khaligh-Razavi et al., 2018; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b). One recent behavioral study (Quek et al., 2023) attempted to explore the impact of the relationship of two objects' depths on real-world size representations. Although they didn't directly distinguish the representations between size and depth of the same object, they provided evidence that perceived real-world depth could influence real-world size representation. This further illustrates the necessity of investigating pure real-world size representations in human brains and ANNs.

In contrast to the later-emerging real-world size representations, it makes sense that visual size representations could be processed more quickly based on more fundamental, lower-level information such as shape and edge discrimination. The intermediate latency for real-world depth processing suggests that this feature may precede real-world size processing. Intriguingly, there was also a secondary, albeit substantially later, significant depth representation time-window, which might indicate that our brains also have the ability to apply higher-level information or incorporate real-size information to form the final representation of real-world depth. Our comparisons between human brains and artificial models and explorations on ANNs and Word2Vec offer further insights and suggest that although real-world object size and depth are closely related, object real-world size appears to be a more stable and higher-level dimension.

The concept of 'object space' in cognitive neuroscience research is crucial for understanding how various visual features of objects are represented. Historically, various visual features have been considered important dimensions in constructing object space, including animate-inanimate (Kriegeskorte et al., 2008; Naselaris et al., 2012), spikiness (Bao et al., 2020; Coggan & Tong, 2023), and physical appearance (Edelman et al., 1998). In this study, we focus on one particular dimension, real-world size (Huang et al., 2022; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b). How we generate neural distinctions of different object real-world size and where this ability comes from remain uncertain. Some previous studies found that object shape rather than texture information could trigger neural size representations (Huang et al., 2022; Long et al., 2016, 2018; Wang et al., 2022). Our results attempt to further advance their findings, that object real-world size is a stable and higher-level dimension substantially driven by object semantics in object space.

Increasingly, research has been beginning to use ANNs to study the mechanisms of object recognition (Ayzenberg et al., 2023; Cichy & Kaiser, 2019; Doerig et al., 2022; Kanwisher et al., 2023). We can explore how the human brain processes information at different levels by comparing brain activity with models (Cichy et al., 2016; S. M. Khaligh-Razavi & Kriegeskorte, 2014; Kuzovkin et al., 2018; Xie et al., 2020), and we can also analyze the representation patterns of the models with some specific manipulations and infer potential processing mechanisms in the brain (Golan et al., 2020; Huang et al., 2022; Lu & Ku, 2023; Xu et al., 2021). In current study, our comparisons result between EEG signals and different ANNs showed that the visual model's early layer had a higher similarity to the brain in the early stage, while the visual-semantic model's late layer had a higher similarity to the brain in the late stage. However, for the representation of objects, partial correlation results for different ANNs didn't demonstrate the superiority of the multi-modal model at late layers. This might be due to models like CLIP, which contain semantic information, learning more complex image descriptive information (like the relationship between object and the background in the image). Real-world size might be a semantic dimension of the object itself, and its representation does not require overall semantic descriptive information of the image. In contrast, visual size and real-world depth could rely on image background information for estimation, thus their representations in the CLIP late layer disappeared when input images had only pure object but no background.

Building on the promising findings of our study, future work may further delve into the detailed processes of object processing and object space. One important problem to solve is how real-world size interacts with other object dimensions in object space. In addition, our approach could be used with future studies investigating other influences on object processing, such as how different task conditions impact and modulate the processing of various visual features.

Moreover, we must also emphasize that in this study, we were concerned with perceived real-world size and depth reflecting a perceptual estimation of our world, which are slightly different from absolute physical size and depth. The differences in brain encoding between perceived and absolute physical size and depth require more comprehensive measurements of an object's physical attributes for further exploration. Also, we focused on perceiving depth and size from 2D images in this study, which might have some differences in brain mechanism compared to physically exploring the 3D world. Nevertheless, we believe our study offers a valuable contribution to object recognition, especially the encoding process of object real-world size in natural images.

In conclusion, we used computational methods to distinguish the representations of real-world size and other size and depth features of objects in ecologically natural images in both human brains and ANNs. We found an unconfounded representation of object real-world size, which emerged at later time windows in the human EEG signal and at later layers of artificial neural networks compared to real-world depth, and which also appeared to be preserved as a stable dimension in object space. Thus, although size and depth properties are closely correlated, the processing of perceived object size and depth may arise through dissociated time courses and mechanisms. Our research provides a detailed and clear characterization of the object processing process, which offers further advances and insights into our understanding of object space and the construction of more brain-like visual models.

References

Allen, E. J., St-Yves, G., Wu, Y., Breedlove, J. L., Prince, J. S., Dowdle, L. T., Nau, M., Caron,

B., Pestilli, F., Charest, I., Hutchinson, J. B., Naselaris, T., & Kay, K. (2022). A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature Neuroscience*, *25*(1), 116–126.

Ayzenberg, V., Blauch, N., & Behrmann, M. (2023). Using deep neural networks to address the how of object recognition. *PsyArXiv*.

Bao, P., She, L., McGill, M., & Tsao, D. Y. (2020). A map of object space in primate inferotemporal cortex. *Nature*, *583*(7814), 103–108.

Chen, Y. C., Deza, A., & Konkle, T. (2022). How big should this object be? Perceptual influences on viewing-size preferences. *Cognition*, *225*, 105114.

Cichy, R. M., & Kaiser, D. (2019). Deep Neural Networks as Scientific Models. *Trends in Cognitive Sciences*, *23*(4), 305–317.

Cichy, R. M., Khosla, A., Pantazis, D., Torralba, A., & Oliva, A. (2016). Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. *Scientific Reports*, *6*(1), 1–13.

Coggan, D. D., & Tong, F. (2023). Spikiness and animacy as potential organizing principles of human ventral visual cortex. *Cerebral Cortex*, *33*(13), 8194–8217.

Doerig, A., Sommers, R., Seeliger, K., Richards, B., Ismael, J., Lindsay, G., Kording, K., Konkle, T., Van Gerven, M. A. J., Kriegeskorte, N., & Kietzmann, T. C. (2022). *The neuroconnectionist research programme*. *24*(July).

Edelman, S., Grill-Spector, K., Kushnir, T., & Malach, R. (1998). Toward direct visualization of

the internal shape representation space by fMRI. *Psychobiology*, *26*(4), 309–321.

Gifford, A. T., Dwivedi, K., Roig, G., & Cichy, R. M. (2022). A large and rich EEG dataset for modeling human visual object recognition. *NeuroImage, 264*, 119754.

Golan, T., Raju, P. C., & Kriegeskorte, N. (2020). Controversial stimuli: Pitting neural networks against each other as models of human cognition. *Proceedings of the National Academy of Sciences of the United States of America*, *117*(47), 29330–29337.

Grootswagers, T., Zhou, I., Robinson, A. K., Hebart, M. N., & Carlson, T. A. (2022). Human EEG recordings for 1,854 concepts presented in rapid serial visual presentation streams. *Scientific Data*, *9*(1), 1–7.

Güçlü, U., & van Gerven, M. A. J. (2015). Deep Neural Networks Reveal a Gradient in the Complexity of Neural Representations across the Ventral Stream. *Journal of Neuroscience*, *35*(27), 10005–10014.

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep Residual Learning for Image Recognition. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770–778.

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Van Wicklin, C., & Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more than 26,000 naturalistic object images. *PLoS ONE*, *14*(10), 1–24.

Huang, T., Song, Y., & Liu, J. (2022). Real-world size of objects serves as an axis of object space. *Communications Biology*, *5*(1), 1–12.

Kanwisher, N., Khosla, M., & Dobs, K. (2023). Using artificial neural networks to ask 'why' questions of minds and brains. *Trends in Neurosciences*, *46*(3), 240–254.

Khaligh-Razavi, S.-M., Cichy, R. M., Pantazis, D., & Oliva, A. (2018). Tracking the Spatiotemporal Neural Dynamics of Real-world Object Size and Animacy in the Human Brain. *Journal of Cognitive Neuroscience*, *30*(11), 1559–1576.

Khaligh-Razavi, S. M., & Kriegeskorte, N. (2014). Deep Supervised, but Not Unsupervised, Models May Explain IT Cortical Representation. *PLoS Computational Biology*, *10*(11), e1003915.

Kietzmann, T. C., Spoerer, C. J., Sörensen, L. K. A., Cichy, R. M., Hauk, O., & Kriegeskorte, N. (2019). Recurrence is required to capture the representational dynamics of the human visual system. *Proceedings of the National Academy of Sciences of the United States of America*, *116*(43), 21854–21863.

Konkle, T., & Caramazza, A. (2013). Tripartite Organization of the Ventral Stream by Animacy and Object Size. *Journal of Neuroscience*, *33*(25), 10235–10242.

Konkle, T., & Oliva, A. (2011). Canonical Visual Size for Real-World Objects. *Journal of Experimental Psychology: Human Perception and Performance*, *37*(1), 23–37.

Konkle, T., & Oliva, A. (2012a). A familiar-size Stroop effect: Real-world size is an automatic property of object representation. *Journal of Experimental Psychology: Human Perception and Performance*, *38*(3), 561.

Konkle, T., & Oliva, A. (2012b). A Real-World Size Organization of Object Responses in

Occipitotemporal Cortex. *Neuron*, *74*(6), 1114–1124.

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., &
Bandettini, P. A. (2008). Matching Categorical Object Representations in Inferior Temporal
Cortex of Man and Monkey. *Neuron*, *60*(6), 1126–1141.

Kuzovkin, I., Vicente, R., Petton, M., Lachaux, J. P., Baciu, M., Kahane, P., Rheims, S., Vidal, J.
R., & Aru, J. (2018). Activations of deep convolutional neural networks are aligned with
gamma band activity of human visual cortex. *Communications Biology*, *1*(1), 1–12.

Long, B., & Konkle, T. (2017). A familiar-size Stroop effect in the absence of basic-level
recognition. *Cognition*, *168*, 234–242.

Long, B., Konkle, T., Cohen, M. A., & Alvarez, G. A. (2016). Mid-level perceptual features
distinguish objects of different real-world sizes. *Journal of Experimental Psychology:
General*, *145*(1), 95–109.

Long, B., Yu, C. P., & Konkle, T. (2018). Mid-level visual features underlie the high-level
categorical organization of the ventral stream. *Proceedings of the National Academy of
Sciences of the United States of America*, *115*(38), E9015–E9024.

Lu, Z., & Ku, Y. (2020). NeuroRA: A Python Toolbox of Representational Analysis From Multi-
Modal Neural Data. *Frontiers in Neuroinformatics*, *14*, 61.

Lu, Z., & Ku, Y. (2023). Facial representation comparisons between human brain and deep
convolutional neural network reveal a fatigue repetition suppression. *BioRxiv*.

Luo, A. F., Wehbe, L., Tarr, M. J., & Henderson, M. M. (2023). Neural Selectivity for Real-

World Object Size In Natural Images Abbreviated title : Neural Selectivity for Real-World Size. *BioRxiv*.

Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). Efficient Estimation of Word Representations in Vector Space. *Proceedings of the International Conference on Learning Representations (ICLR)*.

Muttenthaler, L., & Hebart, M. N. (2021). THINGSvision: A Python Toolbox for Streamlining the Extraction of Activations From Deep Neural Networks. *Frontiers in Neuroinformatics*, *15*, 45.

Naselaris, T., Stansbury, D. E., & Gallant, J. L. (2012). Cortical representation of animate and inanimate objects in complex natural scenes. *Journal of Physiology Paris*, *106*(5–6), 239–249.

Quek, G., Theodorou, A., & Peelen, M. V. (2023). Better together : Objects in familiar constellations evoke high-level representations of real-world size. *BioRxiv*.

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning Transferable Visual Models From Natural Language Supervision. *Proceedings of the International Conference on Machine Learning (ICML)*.

Řehůřek, R., & Sojka, P. (2010). Software framework for topic modelling with large corpora. *Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks*, 45–50.

Setti, A., Caramelli, N., & Borghi, A. M. (2008). Conceptual information about size of objects in

nouns. *European Journal of Cognitive Psychology*, *21*(7), 1022–1044.

Stoinski, L. M., Perkuhn, J., & Hebart, M. N. (2023). THINGSplus: New norms and metadata for
the THINGS database of 1854 object concepts and 26,107 natural object images. *Behavior
Research Methods*, 1–21.

Wang, R., Janini, D., & Konkle, T. (2022). Mid-level feature differences support early animacy
and object size distinctions: Evidence from electroencephalography decoding. *Journal of
Cognitive Neuroscience*, *34*(9), 1670–1680.

Xie, S., Kaiser, D., & Cichy, R. M. (2020). Visual Imagery and Perception Share Neural
Representations in the Alpha Frequency Band. *Current Biology*, *30*(13), 2621-2627.e5.

Xu, S., Zhang, Y., Zhen, Z., & Liu, J. (2021). The Face Module Emerged in a Deep
Convolutional Neural Network Selectively Deprived of Face Experience. *Frontiers in
Computational Neuroscience*, *15*, 1–12.

Yamins, D. L. K., & DiCarlo, J. J. (2016). Using goal-driven deep learning models to understand
sensory cortex. *Nature Neuroscience*, *19*(3), 356–365.

Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014).
Performance-optimized hierarchical models predict neural responses in higher visual cortex.
Proceedings of the National Academy of Sciences of the United States of America, *111*(23),
8619–8624.

Figure 1 Overview of our analysis pipeline including constructing three types of RDMs and conducting comparisons between them.

Figure 2 Methods for calculating neural (EEG), hypothesis-based (HYP), and artificial neural network (ANN) & semantic language processing (Word2Vec, W2V) model-based representational dissimilarity matrices (RDMs). (A) Steps of computing the neural RDMs from EEG data. EEG analyses were

performed in a time-resolved manner on 17 channels as features. For each time t, we conducted pairwise cross-validated SVM classification. The classification accuracy values across different image pairs resulted in each 200 × 200 RDM for each time point. (B) Calculating the four hypothesis-based RDMs: Real-World Size RDM, Visual Size RDM, Real-World Depth RDM, and Pixel-Wise Difference RDM. Real-world size, visual size, and real-world depth were calculated for the primary object in each of the 200 stimulus images. The number in the bracket represents the rank (out of 200, in ascending order) based on each feature corresponding to the object in each stimulus image. The connection graph to the right of each RDM represents the relative representational distance of three stimuli in the corresponding feature space. (C) Steps of computing the ANN and Word2Vec RDMs. For ANNs, the inputs were the resized images, and for Word2Vec, the inputs were the words of object concepts.

Figure 3 Cross-modal RSA results. (A) Temporal representational similarity results between EEG neural RDMs and hypothesis-based RDMs; the partial correlation technique reveals representations of real-world depth, visual size, and real-world size unconfounded by each other and pixel-wise image similarity. Left: Temporal latencies for peak similarity between EEG and the 3 types of object information. Error bars indicate ±SEM. Asterisks indicate significant differences across conditions (p<.05); Right: Full representational similarity time courses (partial Spearman correlations) between EEG neural RDMs and hypothesis-based RDMs. Color-coded small dots at the top indicate significant timepoints (cluster-based permutation test, p<.05). Shaded area reflects ±SEM. (B) Representational similarities (partial Spearman correlations) between the four ANN RDMs and hypothesis-based RDMs of real-world depth, visual size, and real-world size. Asterisks indicate significant partial correlations (bootstrap test, p<.05). (C) Representational similarity time courses (Spearman correlations) between EEG neural RDMs and ANN RDMs. Color-coded small dots at the top indicate significant timepoints (cluster-based permutation test, p<.05). Shaded area reflects ±SEM.

Figure 4 Contribution of image backgrounds to object size and depth representations. Representational similarity results (partial Spearman correlations) between ANNs fed inputs of cropped object images without backgrounds and the hypothesis-based RDMs. Stars above bars indicate significant partial correlations (bootstrap test, p<.05).

Figure 5 Representation similarity with a non-visual semantic language processing model (Word2Vec) fed word inputs corresponding to the images' object concepts. (A) Representational similarity results (partial Spearman correlations) between Word2Vec RDM and hypothesis-based RDMs. Stars above bars indicate significant partial correlations (bootstrap test, p<.05). (B) Representational similarity time course (Spearman correlations) between EEG RDMs (neural activity while viewing images) and Word2Vec RDM (fed corresponding word inputs). Color-coded small dots at the top indicate significant timepoints (cluster-based permutation test, p<.05). Line width reflects ±SEM.

Supplementary materials

Figure S1. Four ANN RDMs of ResNet early layer, ResNet late layer, CLIP early layer, and CLIP late later.

Figure S2. Word2Vec RDMs.

Figure S3. Similarities (Spearman correlations) between four hypothesis-based RDMs. Asterisks indicate a significant similarity, p<.05.

Figure S4. Four ANN RDMs with inputs of cropped object images without background of ResNet early layer, ResNet late layer, CLIP early layer, and CLIP late later.

Table S1 Statistical results of similarities (partial Spearman correlations) between four ANN RDMs and four hypothesis-based RDMs.

ANN × HYP	*ResNet (early)*	*CLIP (early)*	*ResNet (late)*	*CLIP (late)*
Pixel-wise Difference	**r=.3871, p<.001**	**r=.1291, p<.001**	**r=.0720, p<.001**	**r=.0932, p<.001**
Real-World depth	**r=.0297, p<.001**	**r=.0245, p<.001**	r=-.0524, p=1	**r=.0265, p<.001**
Visual Size	**r=.0703, p<.001**	**r=.0746, p<.001**	**r=.0227, p<.001**	r=.0065, p=.1788
Real-World Size	r=-.0530, p=1	r=-.0080, p=.8710	**r=0.2474, p<.001**	**r=0.2351, p<.001**

Table S2 Statistical results of similarities (partial Spearman correlations) between four ANN RDMs with inputs of cropped object images without background and four hypothesis-based RDMs.

ANN (obj-only imgs) × HYP	ResNet (early)	CLIP (early)	ResNet (late)	CLIP (late)
Pixel-wise Difference	r=-.0255, p=.9998	r=-.0343, p=1	r=.0109, p=.0621	**r=.0265, p<.001**
Real-World depth	r=-.0105, p=.9315	r=-.0081, p=.8720	**r=.0182, p=.0052**	r=-.0180, p=.9944
Visual Size	**r=.0322, p<.001**	**r=.0312, p<.001**	r=-.0031, p=.6681	r=-.0029, p=.6598
Real-World Size	r=.0032, p=.3236	r=.0098, p=.0843	**r=.0397, p<.001**	**r=.0143, p=.0217**