Human EEG and artificial neural networks reveal disentangled representations and processing timelines of object real-world size and depth in natural images

10   Zitong Lu & Julie D. Golomb

11   Department of Psychology, The Ohio State University, Columbus, OH 43212 USA

Please address correspondence to:
Zitong Lu
Department of Psychology
The Ohio State University
Columbus, OH, 43210
Email: lu.2637@osu.edu

Abstract

Remarkably, human brains have the ability to accurately perceive and process the real-world size of objects, despite vast differences in distance and perspective. While previous studies have delved into this phenomenon, distinguishing the processing of real-world size from other visual properties, like depth, has been challenging. Using the THINGS EEG2 dataset with human EEG recordings and more ecologically valid naturalistic stimuli, our study combines human EEG and representational similarity analysis to disentangle neural representations of object real-world size from retinal size and perceived depth, leveraging recent datasets and modeling approaches to address challenges not fully resolved in previous work. We report a representational timeline of visual object processing: object real-world depth processed first, then retinal size, and finally, real-world size. Additionally, we input both these naturalistic images and object-only images without natural background into artificial neural networks. Consistent with the human EEG findings, we also successfully disentangled representation of object real-world size from retinal size and real-world depth in all three types of artificial neural networks (visual-only ResNet, visual-language CLIP, and language-only Word2Vec). Moreover, our multi-modal representational comparison framework across human EEG and artificial neural networks reveals real-world size as a stable and higher-level dimension in object space incorporating both visual and semantic information. Our research provides a temporally resolved characterization of how certain key object properties – such as object real-world size, depth, and retinal size – are represented in the brain, which offers further advances and insights into our understanding of object space and the construction of more brain-like visual models.

Keywords: real-world size, depth perception, RSA, artificial neural networks, object recognition

Introduction

Imagine you are viewing an apple tree while walking around an orchard: as you change your perspective and distance, the retinal size of the apple you plan to pick varies, but you still perceive the apple as having a constant real-world size. How do our brains extract object real-world size information during object recognition to allow us to understand the complex world? Behavioral studies have demonstrated that perceived real-world size is represented as an object physical property, revealing same-size priming effects (Setti et al., 2008), familiar-size stroop effects (Konkle & Oliva, 2012a; Long & Konkle, 2017), and canonical visual size effects (Chen et al., 2022; Konkle & Oliva, 2011). Human neuroimaging studies have also found evidence of object real-world size representation (Huang et al., 2022; S.-M. Khaligh-Razavi et al., 2018; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b; Luo et al., 2023; Quek et al., 2023; R. Wang et al., 2022). These findings suggest real-world size is a fundamental dimension of object representation.

However, previous studies on object real-world size have faced several challenges. Firstly, the perception of an object's real-world size is closely related to the perception of its real-world distance in depth. For instance, imagine you are looking at photos of an apple and a basketball: if the two photos were zoomed in such that the apple and the basketball filled the same exact retinal (image) size, you could still easily perceive that the apple is the physically smaller real-world object. But, you would simultaneously infer that the apple is thus located closer to you (or the camera) than the basketball. In previous neuroimaging studies of perceived real-world size (Huang et al., 2022; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b), researchers presented images of familiar objects zoomed and cropped such that they occupied the

same retinal size, finding that neural responses in ventral temporal cortex reflected the perceived

real-world size (e.g. an apple smaller than a car). However, while they controlled the retinal size

of objects, the intrinsic correlation between real-world size and real-world depth in these images

meant that the influence of perceived real-world depth could not be entirely isolated when

examining the effects of real-world size. This makes it difficult to ascertain whether their results

were driven by neural representations of perceived real-world size and/or perceived real-world

depth. MEG and EEG studies focused on temporal processing of object size representations (S.-

M. Khaligh-Razavi et al., 2018; R. Wang et al., 2022) have been similarly susceptible to this

limitation. Indeed, one recent study (Quek et al., 2023) provided evidence that perceived real-

world depth could influence real-world size representations, further illustrating the necessity of

investigating pure real-world size representations in the brain. Secondly, the stimuli used in these

studies were cropped object stimuli against a plain white or grey background, which are not

particularly naturalistic. More and more studies and datasets have highlighted the important role

of naturalistic context in object recognition (Allen et al., 2022; Gifford et al., 2022;

Grootswagers et al., 2022; Hebart et al., 2019; Stoinski et al., 2023). In ecological contexts,

inferring the real-world size/distance of an object likely relies on a combination of bottom-up

visual information and top-down knowledge about canonical object sizes for familiar objects.

Incorporating naturalistic background context in experimental stimuli may produce more

accurate assessments of the relative influences of visual shape representations (Bracci et al.,

2017; Bracci & Op de Beeck, 2016; Proklova et al., 2016) and higher-level semantic information

(Doerig et al., 2022; Huth et al., 2012; A. Y. Wang et al., 2022). Furthermore, most previous

studies have tended to categorize size rather broadly, such as merely differentiating between big

and small objects (S.-M. Khaligh-Razavi et al., 2018; Konkle & Oliva, 2012b; R. Wang et al.,

2022) or dividing object size into seven levels from small to big. To more finely investigate the

representation of object size in the brain, it may be necessary to obtain a more continuous

measure of size for a more detailed characterization.

Certainly, a minority of fMRI studies have attempted to utilize natural images and also

engaged in more detailed size measurements to more precisely explore the encoding of object

real-world size in different brain areas (Luo et al., 2023; Troiani et al., 2014). However, no study

has yet comprehensively overcome all the challenges and unfolded a clear processing timeline

for object retinal size, real-world size, and real-world depth in human visual perception.

In the current study, we overcome these challenges by combining human EEG recordings,

naturalistic stimulus images, artificial neural networks, and computational modeling approaches

including representational similarity analysis (RSA) and partial correlation analysis to

distinguish the neural representations of object real-world size, retinal size, and real-world depth.

We applied our integrated computational approach to an open EEG dataset, THINGS EEG2

(Gifford et al., 2022). Firstly, the visual image stimuli used in this dataset are more naturalistic

and include objects that vary in real-world size, depth, and retinal size. This allows us to employ

a multi-model representational similarity analysis to investigate relatively unconfounded

representations of object real-world size, partialing out – and simultaneously exploring – these

confounding features. Secondly, we are able to explore the neural dynamics of object feature

processing in a more ecological context based on natural images in human object recognition.

Thirdly, instead of categorizing object size into discrete levels, we applied a more continuous

measure based on detailed behavioral measurements from an online size rating task, allowing us

to more finely decode the representation of object size in the brain.

We first focus on unfolding the neural dynamics of statistically isolated object real-world

size representations. The temporal resolution of EEG allows us the opportunity to investigate the

representational timecourse of visual object processing, asking whether processing of perceived

object real-world size precedes or follows processing of perceived depth, if these two properties

are in fact processed independently.

We then attempt to further explore the underlying mechanisms of how human brains

process object size and depth in natural images by integrating artificial neural networks (ANNs).

In the domain of cognitive computational neuroscience, ANNs offer a complementary tool to

study visual object recognition, and an increasing number of studies support that ANNs exhibit

representations similar to human visual systems (Cichy et al., 2016; Güçlü & van Gerven, 2015;

Yamins et al., 2014; Yamins & DiCarlo, 2016). Indeed, a recent study found that ANNs also

represent real-world size (Huang et al., 2022); however, their use of a fixed retinal size image

dataset with the same cropped objects as described above makes it similarly challenging to

ascertain whether the results reflected real-world size and/or depth. Additionally, some recent

work indicates that artificial neural networks incorporating semantic embedding and multimodal

neural components might more accurately reflect human visual representations within visual

areas and even the hippocampus, compared to vision-only networks (Choksi, Mozafari, et al.,

2022; Choksi, Vanrullen, et al., 2022; Conwell et al., 2022; Doerig et al., 2022; Jozwik et al.,

2023; A. Y. Wang et al., 2022). Given that perception of real-world size may incorporate both

bottom-up visual and top-down semantic knowledge about familiar objects, these models offer

yet another novel opportunity to investigate this question. Utilizing both visual and visual-

semantic models, as well as different layers within these models, ANNs provide us the approach

to extract various image features, low-level visual information from early layers and higher-level

information including both visual and semantic features from late layers.

The integrated computational approach by cross-modal representational comparisons we

take with the current study allows us to compare how representations of perceived real-world

size and depth emerge in both human brains and artificial neural networks. Unraveling the

internal representations of object size and depth features in both human brains and ANNs enables

us to investigate how distinct spatial properties—retinal size, real-world depth, and real-world

size—are encoded across systems, and to uncover the representational mechanisms and temporal

dynamics through which real-world size emerges as a potentially higher-level, semantically

grounded feature.

Materials and Methods

Experimental design, stimuli images and EEG data:

We utilized the open dataset from THINGS EEG2 (Gifford et al., 2022), which includes EEG

data from 10 healthy human subjects (age=28.5±4, 8 female and 2 male) participating in a rapid

serial visual presentation (RSVP) paradigm with an orthogonal target detection task to ensure

participants paid attention to the visual stimuli. All participants were seated at a fixed distance of

0.6 meters from the screen throughout the experiment. For each trial, subjects viewed one image

(sized 500×500 pixels) for 100ms. Each subject viewed 16740 images of objects on a natural

background for 1854 object concepts from THINGS dataset (Hebart et al., 2019). For the current

study, we used the 'test' dataset portion, which includes 16000 trials per subject corresponding to

200 images (200 object concepts, one image per concept) with 80 trials per image, providing high trial counts per condition necessary for reliable EEG decoding. In contrast, images in the training set were only shown four times each. This design choice ensured higher decoding reliability and greater signal quality for RSA. Before inputting the images to the ANNs, we reshaped image sizes to 224 x 224 pixels and normalized the pixel values of images to ImageNet statistics.

EEG data were collected using a 64-channel EASYCAP and a BrainVision actiCHamp amplifier. The EEG data were originally sampled at 1000Hz and online-filtered between 0.1 Hz and 100 Hz during acquisition, with recordings referenced to the Fz electrode. For preprocessing, no additional filtering was applied. Baseline correction was performed by subtracting the mean signal during the 100 ms pre-stimulus interval from each trial and channel separately. We used already pre-processed data from 17 channels with labels beginning with "O" or "P" (O1, Oz, O2, PO7, PO3, POz, PO4, PO8, P7, P5, P3, P1, Pz, P2) ensuring full coverage of posterior regions typically involved in visual object processing. The epoched data were then down-sampled to 100 Hz. We re-epoched EEG data ranging from 100ms before stimulus onset to 300ms after onset with a sample frequency of 100Hz. Thus the shape of our EEG data matrix for each trial was 17 channels $\times$ 40 time points.

ANN models:

We applied two pre-trained ANN models: one visual model (ResNet-101 (He et al., 2016) pretrained on ImageNet), and one multi-modal (visual+semantic) model (CLIP with a ResNet-101 backbone (Radford et al., 2021) pretrained on YFCC-15M). Our motivation for selecting ResNet-50 and CLIP ResNet-50 was not to make a definitive comparison between model classes,

but rather to include two widely used representatives of their respective categories—one trained purely on visual information (ResNet-50 on ImageNet) and one trained with joint visual and linguistic supervision (CLIP ResNet-50 on image–text pairs). These models are both highly influential and commonly used in computational and cognitive neuroscience, allowing for relevant comparisons with existing work (Choksi, Mozafari, et al., 2022; Choksi, Vanrullen, et al., 2022; Conwell et al., 2024; Song et al., 2024; A. Y. Wang et al., 2022). We used THINGSvision (Muttenthaler & Hebart, 2021) to obtain low- and high-level feature vectors of ANN activations from early and late layers (early layer: second convolutional layer; late layer: last visual layer) for the images.

Word2Vec model:

To approximate the non-visual, pure semantic space of objects, we also applied a Word2Vec model, a natural language processing model for word embedding, pretrained on Google News corpus (Mikolov et al., 2013), which contains 300-dimensional vectors for 3 million words and phrases. We input the words for each image's object concept (pre-labeled in THINGS dataset: Hebart et al., 2019), instead of the visual images themselves. We used Gensim (Řehůřek & Sojka, 2010) to obtain Word2Vec feature vectors for the objects in images.

Representational dissimilarity matrices (RDMs):

To conduct RSA across human EEG, artificial models, and our hypotheses corresponding to different visual features, we first computed representational dissimilarity matrices (RDMs) for different modalities (Figure 2). The shape of each RDM was 200×200, corresponding to pairwise dissimilarity between the 200 images. We extracted the 19900 cells from the upper half of the diagonal of each RDM for subsequent analyses.

Neural RDMs. From the EEG signal, we constructed timepoint-by-timepoint neural

RDMs for each subject with decoding accuracy as the dissimilarity index (Figure 2A). Since

EEG has a low SNR and includes rapid transient artifacts, Pearson correlations computed over

very short time windows yield unstable dissimilarity estimates (Kappenman & Luck, 2010;

Luck, 2014) and may thus fail to reliably detect differences between images. In contrast,

decoding accuracy - by training classifiers to focus on task-relevant features - better mitigates

noise and highlights representational differences. We first conducted timepoint-by-timepoint

classification-based decoding for each subject and each pair of images (200 images, 19900 pairs

in total). We applied linear Support Vector Machine (SVM) to train and test a two-class

classifier, employing a 5-time 5-fold cross-validation method, to obtain an independent decoding

accuracy for each image pair and each timepoint. Therefore, we ultimately acquired 40 (1 per

timepoint) EEG RDMs for each subject.

Hypothesis-based (HYP) RDMs. We constructed three hypothesis-based RDMs

reflecting the different types of visual object properties in the naturalistic images (Figure 2B):

Real-World Size RDM, Retinal Size RDM, and Real-World Depth RDM. We constructed these

RDMs as follows:

(1) For Real-World Size RDM, we obtained human behavioral real-world size ratings of

each object concept from the THINGS+ dataset (Stoinski et al., 2022). In the

THINGS+ dataset, 2010 participants (different from the subjects in THINGS EEG2)

did an online size rating task and completed a total of 13024 trials corresponding to

1854 object concepts using a two-step procedure. In their experiment, first, each

object was rated on a 520-unit continuous slider anchored by familiar reference

objects (e.g., "grain of sand," "microwave oven," "aircraft carrier") representing a

228 logarithmic size range. Participants were not shown numerical values but used

229 semantic anchors as guides. In the second step, the scale zoomed in around the

230 selected region to allow for finer-grained refinement of the size judgment. Final size

231 values were derived from aggregated behavioral data and rescaled to a range of 0–519

232 for consistency across objects, with the actual mean ratings across subjects ranging

233 from 100.03 ('grain of sand') to 423.09 ('subway'). We used these ratings as the

234 perceived real-world size measure of the object concept pre-labeled in THINGS

235 dataset (Hebart et al., 2019) for each image. We then constructed the representational

236 dissimilarity matrix by calculating the absolute difference between perceived real-

237 world size ratings for each pair of images.

238 (2) For Retinal Size RDM, we applied Adobe Photoshop (Adobe Inc., 2019) to crop

239 objects corresponding to object labels from images manually. All cropping and

240 measurement were conducted by one of the authors to ensure consistency across the

241 dataset. The cropped object images have been made publicly available at

242 https://github.com/ZitongLu1996/RWsize to facilitate future reuse and

243 reproducibility. For each image, we obtained a rectangular region that precisely

244 contains a single object, then measured the diagonal length of the segmented object in

245 pixels as the retinal size measure (Konkle & Oliva, 2011). Due to our calculations

246 being at the object level, if there were more than one same objects in an image, we

247 cropped the most complete one to get more accurate retinal size. We then constructed

248 the RDM by calculating the absolute difference between measured retinal size for

249 each pair of images.

(3) For Real-World Depth RDM, we calculated the perceived depth based on the

measured retinal size index and behavioral real-world size ratings, such that real-

world depth / visual image depth = real-world size / retinal size. Since visual image

depth (viewing distance) is held constant across images in the task, inferred real-

world depth is proportional to real-world size / retinal size. We then constructed the

RDM by calculating the absolute difference between inferred real-world depth index

for each pair of images.

ANN (and Word2Vec) model RDMs. We constructed a total of five model-based RDMs

(Figure 2C). Our primary analyses used four ANN RDMs, corresponding to the early and late

layers for both ResNet and CLIP (Figure S1). The early layer in ResNet refers to

ResNet.maxpool layer, and the late layer in ResNet refers to ResNet.avgpool layer. The early

layer in CLIP refers to CLIP.visual.avgpool layer, and the late layer in CLIP refers to

CLIP.visual.attnpool layer. We also calculated a single Word2Vec RDM for the pure semantic

analysis (Figure S2). For each RDM, we got the dissimilarities by calculating 1 – Pearson

correlation coefficient between each pair of two vectors of the model features corresponding to

two input images.

Representational similarity analyses (RSA) and statistical analyses:

We conducted cross-modal representational similarity analyses between the three types of RDMs

(Figure 2). All decoding and RSA analyses were implemented using NeuroRA (Lu & Ku, 2020).

EEG × ANN (or W2V) RSA. To measure the representational similarity between human

brains and ANNs and confirm that ANNs have significantly similar representations to human

brains, we calculated the Spearman correlation between the 40 timepoint-by-timepoint EEG

neural RDMs and the 4 ANN RDMs corresponding to the representations of ResNet early layer,

ResNet late layer, CLIP early layer, CLIP late layer, respectively. We also calculated temporal

representational similarity between human brains (EEG RDMs) and the Word2Vec model RDM.

Cluster-based permutation tests were conducted to determine the time windows of significant

representational similarity. First, we performed one-sample t-tests (one-tailed testing) against

zero to get the t-value for each timepoint, and extracted significant clusters. We computed the

clustering statistic as the sum of t-values in each cluster. Then we conducted 1000 permutations

of each subject's timepoint-by-timepoint similarities to calculate a null distribution of maximum

clustering statistics. Finally, we assigned cluster-level p-values to each cluster of the actual

representational timecourse by comparing its cluster statistic with the null distribution. Time-

windows were determined to be significant if the p-value of the corresponding cluster was <0.05.

EEG × HYP RSA. To evaluate how human brains temporally represent different visual

features, we calculated the timecourse of representational similarity between the timepoint-by-

timepoint EEG neural RDMs and the three hypothesis-based RDMs. To avoid correlations

between hypothesis-based RDMs (Figure 3A) influencing comparison results, we calculated

partial correlations and used a one-tailed test against the null hypothesis that the partial

correlation was less than or equal to zero, testing whether the partial correlation was significantly

greater than zero. In EEG × HYP partial correlation (Figure 3D), we correlated EEG RDMs with

one hypothesis-based RDM (e.g., real-world size), while controlling for the other two (e.g.,

retinal size and real-world depth). Cluster-based permutation tests were performed as described

above to determine the time windows of significant representational similarity. In addition, we

conducted peak latency analysis to determine the latency of peak representational similarity for

each type of visual information with the EEG signal. To assess the stability of peak latency

estimates for each subject, we performed a bootstrap procedure across stimulus pairs. At each

time point, the EEG RDM was vectorized by extracting the lower triangle (excluding the

diagonal), resulting in 19,900 unique pairwise values. For each bootstrap sample, we resampled

these 19,900 pairwise entries with replacement to generate a new pseudo-RDM of the same size.

We then computed the partial correlation between the EEG pseudo-RDM and a given hypothesis

RDM (e.g., real-world size), controlling for other feature RDMs, and obtained a time course of

partial correlations. Repeating this procedure 1000 times and extracting the peak latency within

the significant time window yielded a distribution of bootstrapped latencies, from which we got

the bootstrapped mean latencies per subject. Paired t-tests (two-tailed) were conducted to assess

the statistical differences in peak latencies between different visual features.

<u>ANN (or W2V) × HYP RSA.</u> To evaluate how different visual information is represented

in ANNs, we calculated representational similarity between the ANN RDMs and hypothesis-

based RDMs. As in the EEG × HYP RSA, we calculated partial correlations to avoid correlations

between hypothesis-based RDMs. In ANN (or W2V) × HYP partial correlation (Figure 3E and

Figure 5A), we correlated ANN (or W2V) RDMs with one hypothesis-based RDM (e.g., real-

world size), while partialling out the other two. We also calculated the partial correlations

between hypothesis-based RDMs and the Word2Vec RDM. To determine statistical significance,

we conducted a bootstrap test. We shuffled the order of the cells above the diagonal in each

ANN (or Word2Vec) RDM 1000 times. For each iteration, we calculated partial correlations

corresponding to the three hypothesis-based RDMs. This produced a 1000-sample null

distribution for each HYP x ANN (or W2V) RSA. We hypothesized that if the real similarity

was higher than the 95% confidence interval of the null distribution, it indicated that ANN (or

W2V) features validly encoded the corresponding visual feature.

Additionally, to explore how the naturalistic background present in the images might

influence object real-world size, retinal size, and real-world depth representations, we conducted

another version of the analysis by inputting cropped object images without background into

ANN models to obtain object-only ANN RDMs (Figure S3). Then we performed the same ANN

x HYP similarity analysis to calculate partial correlations between the hypothesis-based RDMs

and object-only ANN RDM. (We didn't conduct the similarity analysis between timepoint-by-

timepoint EEG neural RDMs with subjects viewing natural images and object-only ANN RDMs

due to the input differences.)

Data and code accessibility:

EEG data and images from THINGS EEG2 data are publicly available on OSF

(https://osf.io/3jk45/). All Python analysis scripts will be available post-publication on GitHub

(https://github.com/ZitongLu1996/RWsize).

Figure 1 Overview of our analysis pipeline including constructing three types of RDMs and conducting comparisons between them. We computed RDMs from three sources: neural data (EEG), hypothesized object features (real-world size, retinal size, and real-world depth), and artificial models (ResNet, CLIP, and Word2Vec). Then we conducted cross-modal representational similarity analyses between: EEG × HYP (partial correlation, controlling for other two HYP features), ANN (or W2V) × HYP (partial correlation, controlling for other two HYP features), and EEG × ANN (correlation).

Figure 2 Methods for calculating neural (EEG), hypothesis-based (HYP), and artificial neural network

(ANN) & semantic language processing (Word2Vec, W2V) model-based representational dissimilarity

matrices (RDMs). (A) Steps of computing the neural RDMs from EEG data. EEG analyses were

performed in a time-resolved manner on 17 channels as features. For each time t, we conducted pairwise

cross-validated SVM classification. The classification accuracy values across different image pairs

resulted in each 200 × 200 RDM for each time point. (B) Calculating the three hypothesis-based RDMs:

Real-World Size RDM, Retinal Size RDM, and Real-World Depth RDM. Real-world size, retinal size,

and real-world depth were calculated for the object in each of the 200 stimulus images. The number in the

bracket represents the rank (out of 200, in ascending order) based on each feature corresponding to the

object in each stimulus image (e.g. "ferry" ranks 197[th] in real-world size from small to big out of 200

objects). The connection graph to the right of each RDM represents the relative representational distance

of three stimuli in the corresponding feature space. (C) Steps of computing the ANN and Word2Vec

RDMs. For ANNs, the inputs were the resized images, and for Word2Vec, the inputs were the words of

object concepts. For clearer visualization, the shown RDMs were separately histogram-equalized

(percentile units).

Results

We conducted a cross-modal representational similarity analysis (Figures 1-2, see Method

section for details) comparing the patterns of human brain activation while participants viewed

naturalistic object images (timepoint-by-timepoint decoding of EEG data), the output of different

layers of artificial neural networks and semantic language models fed the same stimuli (ANN

and Word2Vec models), and hypothetical patterns of representational similarity based on

behavioral and mathematical measurements of different visual image properties (perceived real-

world object size, displayed retinal object size, and inferred real-world object depth).

Dynamic representations of object size and depth in human brains

To explore if and when human brains contain distinct representations of perceived real-world

size, retinal size, and real-world depth, we constructed timepoint-by-timepoint EEG neural

RDMs (Figure 2A), and compared these to three hypothesis-based RDMs corresponding to

different visual image properties (Figure 2B). Firstly, we confirmed that the hypothesis-based

RDMs were indeed correlated with each other (Figure 3A), and without accounting for the

confounding variables, Spearman correlations between the EEG and each hypothesis-based

RDM revealed overlapping periods of representational similarity (Figure 3B). In particular,

representational similarity with real-world size (from 90 to 120ms and from 170 to 240ms)

overlapped with the significant time-windows of other features, including retinal size from 70 to

210ms, and real-world depth from 60 to 130ms and from 180 to 230ms. But critically, with the

partial correlations, we isolated their independent representations. The partial correlation results

reveal a relatively unconfounded representation of object real-world size in the human brain

from 170 to 240ms after stimulus onset, independent from retinal size and real-world depth,

which showed significant representational similarity at different time windows (retinal size from

90 to 200ms, and real-world depth from 60 to 130ms and 270 to 300ms) (Figure 3D).

Figure 3 Cross-modal RSA results. (A) Similarities (Spearman correlations) between three hypothesis-based RDMs. Asterisks indicate a significant similarity, p<.05. (B) Representational similarity time courses (full Spearman correlations) between EEG neural RDMs and hypothesis-based RDMs. (C) Temporal latencies for peak similarity (partial Spearman correlations) between EEG and the 3 types of object information. Error bars indicate ±SEM. Asterisks indicate significant differences across conditions (p<.05); (D) Representational similarity time courses (partial Spearman correlations) between EEG neural RDMs and hypothesis-based RDMs. (E) Representational similarities (partial Spearman correlations)

between the four ANN RDMs and hypothesis-based RDMs of real-world depth, retinal size, and real-

world size. Asterisks indicate significant partial correlations (bootstrap test, p<.05). (F) Representational

similarity time courses (Spearman correlations) between EEG neural RDMs and ANN RDMs. Color-

coded small dots at the top indicate significant timepoints (cluster-based permutation test, p<.05). Shaded

area reflects ±SEM across the 10 subjects.

Peak latency results showed that neural representations of real-world size, retinal size and

real-world depth reached their peaks at different latencies after stimulus onset (real-world depth:

~87ms, retinal size: ~138ms, real-world size: ~206ms, Figure 3C). The representation of real-

word size had a significantly later peak latency than that of both retinal size, $t(9)=4.30$, $p=.002$,

and real-world depth, $t(9)=18.58$, $p<.001$. And retinal size representation had a significantly later

peak latency than real-world depth, $t(9)=3.72$, $p=.005$. These varying peak latencies imply an

encoding order for distinct visual features, transitioning from real-world depth through retinal

size, and then to real-world size.

Artificial neural networks also reflect distinct representations of object size and depth

To test how ANNs process these visual properties, we input the same stimulus images

into ANN models and got their latent features from early and late layers (Figure 2C), and then

conducted comparisons between the ANN RDMs and hypothesis-based RDMs. Parallel to our

findings of dissociable representations of real-world size, retinal size, and real-world depth in the

human brain signal, we also found dissociable representations of these visual features in ANNs

(Figure 3E). Our partial correlation RSA analysis showed that early layers of both ResNet and

CLIP had significant real-world depth and retinal size representations, whereas the late layers of

both ANNs were dominated by real-world size representations, though there was also weaker

retinal size representation in the late layer of ResNet and real-world depth representation in the

late layer of CLIP (additional results of the extended analysis of multiple layers in ResNet and

CLIP are shown in Figure S4). The detailed statistical results are shown in Table S1.

Thus, ANNs provide another approach to understand the formation of different visual

features, offering convergent results with the EEG representational analysis, where retinal size

was reflected most in the early layers of ANNs, while object real-world size representations

didn't emerge until late layers of ANNs, consistent with a potential role of higher-level visual

information, such as the semantic information of object concepts.

Representational similarity between human EEG and artificial neural networks

To directly examine the representational similarity between ANNs and human EEG

signals, we compared the timepoint-by-timepoint EEG neural RDMs and the ANN RDMs. This

analysis allowed us to assess how different stages of visual processing in the human brain align

temporally with hierarchical representations in ANNs. As shown in Figure 3F, the early layer

representations of both ResNet and CLIP (ResNet.maxpool layer and CLIP.visual.avgpool)

showed significant correlations with early EEG time windows (early layer of ResNet: 40-280ms,

early layer of CLIP: 50-130ms and 160-260ms), while the late layers (ResNet.avgpool layer and

CLIP.visual.attnpool layer) showed correlations extending into later time windows (late layer of

ResNet: 80-300ms, late layer of CLIP: 70-300ms). Although there is substantial temporal

overlap between early and late model layers, the overall pattern suggests a rough correspondence

between model hierarchy and neural processing stages.

We further extended this analysis across intermediate layers of both ResNet and CLIP

models (from early to late, ResNet: ResNet.maxpool, ResNet.layer1, ResNet.layer2,

ResNet.layer3, ResNet.layer4, ResNet.avgpool; from early to late, CLIP: CLIP.visual.avgpool,

CLIP.visual.layer1, CLIP.visual.layer2, CLIP.visual.layer3, CLIP.visual.layer4,

CLIP.visual.attnpool). The results, now included in Figure S5, show a consistent trend: early

layers exhibit higher similarity to early EEG time points, and deeper layers show increased

similarity to later EEG stages. This pattern of early-to-late correspondence aligns with previous

findings that convolutional neural networks exhibit similar hierarchical representations to those

in the brain visual cortex (Cichy et al., 2016; Güçlü & van Gerven, 2015; Kietzmann et al., 2019;

Yamins & DiCarlo, 2016): that both the early stage of brain processing and the early layer of the

ANN encode lower-level visual information, while the late stage of the brain and the late layer of

the ANN encode higher-level visual information. Notably, early brain responses showed stronger

similarity to early ResNet layers than to CLIP layers, consistent with prior work suggesting that

early visual processing is more closely aligned with purely visual models (Greene & Hansen,

2020). In contrast, at later time windows, brain activity more closely resembled late CLIP layers,

possibly reflecting the integration of visual and semantic information. However, it is also

possible that these differences between ResNet and CLIP reflect differences in training data scale

and domain.

To contextualize how much of the shared variance between EEG and ANN

representations is driven by the specific visual object features we tested above, we conducted a

partial correlation analysis between EEG RDMs and ANN RDMs controlling for the three

hypothesis-based RDMs (Figure S6). The EEG×ANN similarity results remained largely

unchanged, suggesting that ANN representations capture much more additional rich

representational structure beyond these features. Similarly, a supplemental EEG noise ceiling

analysis (Figure S7) shows that the observed EEG–HYP similarity values are substantially below

a theoretical upper bound of explainable variance. This outcome is fully expected: Each of our

HYP RDMs captures only a specific aspect of the neural representational structure, rather than

attempting to account for the totality of the EEG or ANN signal. Our goal is not to optimize

model performance or maximize fit, but to probe if these different components of object

information are reflected – and dissociated – in the temporal dynamics and processing stages of

the brain's responses. In parallel, these supplemental findings help to situate our hypothesis-

driven analysis within the broader representational capacity of the brain and the models.

Real-world size as a stable and higher-level dimension in object space

An important aspect of the current study is the use of naturalistic visual images as stimuli, in

which objects were presented in their natural contexts, as opposed to cropped images of objects

without backgrounds. In natural images, background can play an important role in object

perception. How dependent are the above results on the presence of naturalistic background

context? To investigate how image context influences object size and depth representations, we

next applied a reverse engineering method, feeding the ANNs with modified versions of the

stimulus images containing cropped objects without background, and evaluating the ensuing

ANN representations compared to the same original hypothesis-based RDMs. If the background

significantly contributes to the formation of certain feature representations, we may see some

encoding patterns in ANNs disappear when the input only includes the pure object but no

background.

Compared to results based on images with background, the ANNs based on cropped-

object modified images showed weaker overall representational similarity for all features (Figure

4). In the early layers of both ANNs, we now only observed significantly preserved retinal size

representations (which is a nice validity check, since retinal size measurements were based

purely on the physical object dimensions in the image, independent of the background). Real-

world depth representations were almost totally eliminated, with only a small effect in the late

layer of ResNet. However, we still observed a preserved pattern of real-world size

representations, with significant representational similarity in the late layers of both ResNet and

CLIP, and not in the early layers. The detailed statistical results are shown in Table S2. Even

though the magnitude of representational similarity for object real-world size decreased when we

removed the background, this high-level representation was not entirely eliminated. This finding

suggests that background information does indeed influence object processing, but the

representation of real-world size seems to be a relatively stable higher-level feature. On the other

hand, representational formats of real-world depth changed when the input lacked background

information. The deficiency of real-world depth representations in early layers, compared to

when using full-background images, might suggest that the human brain typically uses

background information to estimate object depth, though the significant effect in the late layer of

ResNet in background-absent condition might also suggest that the brain (or at least ANN) has

additional ability to integrate size information to infer depth when there is no background. These

results show that real-world size emerges in the later layers of ANNs regardless of image

background information, and – based on our prior EEG results – although we could not test

object-only images in the EEG data, we hypothesize that a similar temporal profile would be

observed in the brain, even for object-only images.

Figure 4 Contribution of image backgrounds to object size and depth representations. Representational

similarity results (partial Spearman correlations) between ANNs fed inputs of cropped object images

without backgrounds and the hypothesis-based RDMs. Stars above bars indicate significant partial

correlations (bootstrap test, p<.05).

The relative robustness of real-world size representations – even in the absence of

background – raises an important question: might real-world size be encoded as a more abstract,

conceptual-level dimension in the brain's object representation space? If so, we might expect it

to be driven not only by higher-level visual information, but also potentially by purely semantic

information about familiar objects. To test this, we extracted object names from each image and

input the object names into a Word2Vec model to obtain a Word2Vec RDM (Figure S2), and

then conducted a partial correlation RSA comparing the Word2Vec representations with the

hypothesis-based RDMs (Figure 5A). The results showed a significant real-world size

representation (r=0.1871, p<0.001) but no representation of retinal size (r=-0.0064, p=0.8148) or

real-world depth (r=-0.0040, p=.7151) from Word2Vec. Also, the significant time-window (90-

300ms) of similarity between Word2Vec RDM and EEG RDMs (Figure 5B) contained the

significant time-window of EEG x real-world size representational similarity (Figure 3B).

Figure 5 Representation similarity with a non-visual semantic language processing model (Word2Vec)

fed word inputs corresponding to the images' object concepts. (A) Representational similarity results

(partial Spearman correlations) between Word2Vec RDM and hypothesis-based RDMs. Stars above bars

indicate significant partial correlations (bootstrap test, p<.05). (B) Representational similarity time course

(Spearman correlations) between EEG RDMs (neural activity while viewing images) and Word2Vec

RDM (fed corresponding word inputs). Color-coded small dots at the top indicate significant timepoints

(cluster-based permutation test, p<.05). Line width reflects ±SEM across the 10 subjects.

To further probe the relationship between real-world size and semantic information, and

to examine whether Word2Vec captures variances in EEG signals beyond that explained by

visual models, we conducted two additional analyses. First, we performed a partial correlation

between EEG RDMs and the Word2Vec RDM, while regressing out four ANN RDMs (early and

late layers of both ResNet and CLIP) (Figure S8). We found that semantic similarity remained

significantly correlated with EEG signals across sustained time windows (100-190ms and 250-

300ms), indicating that Word2Vec captures neural variance not fully explained by visual or

visual-language models. Second, we conducted a variance partitioning analysis, in which we

decomposed the variance in EEG RDMs explained by three hypothesis-based RDMs and the

semantic RDM (Word2Vec RDM), and we still found that real-world size explained unique

variance in EEG even after accounting for semantic similarity (Figure S9). And we also observed

a substantial shared variance jointly explained by real-world size and semantic similarity and a

unique variance of semantic information. These results suggest that real-world size is indeed

partially semantic in nature, but also has independent neural representation not fully explained by

general semantic similarity.

Both the reverse engineering manipulation and Word2Vec findings corroborate that

object real-world size representation, unlike retinal size and real-world depth, emerges in both

image- and semantic-level in object space.

Discussion

Our study applied computational methods to distinguish the representations of objects' perceived

real-world size, retinal size, and inferred real-world depth features in both human brains and

ANNs. Consistent with prior studies reporting real-world size representations (Huang et al.,

2022; S.-M. Khaligh-Razavi et al., 2018; Konkle & Caramazza, 2013; Konkle & Oliva, 2012b;

Luo et al., 2023; Quek et al., 2023; R. Wang et al., 2022), we found that both human brains and

ANNs contain significant information about real-world size. Critically, our study goes beyond

the contributions of prior studies in several key ways, offering both theoretical and

methodological advances: (a) we eliminated the confounding impact of perceived real-world depth (in addition to retinal size) on the real-world size representation; (b) we conducted analyses based on more ecologically valid naturalistic images; (c) we obtained precise feature values for each object in every image, instead of simply dividing objects into 2 or 7 coarse categories; and (d) we utilized a multi-modal, partial correlation RSA that combines EEG, hypothesis-based models, and ANNs. Our approach allowed us to investigate representational time courses and reverse engineering manipulations in unparalleled detail. By integrating EEG data with hypothesis-based models and ANNs, this method offers a powerful tool for dissecting the neural underpinnings of object size and depth perception in more ecological contexts, which enriches our comprehension of the brain's representational mechanisms.

Using EEG we uncovered a representational timeline for visual object processing, with object real-world depth information represented first, followed by retinal size, and finally real-world size. While size and depth are highly correlated to each other, our results suggest that the human brain indeed has dissociated time courses and mechanisms to process them. The later representation time-window for object real-world size may suggest that the brain requires more sophisticated, higher-level information to form this representation, perhaps incorporating semantic and/or memory information about familiar objects, which was corroborated by our ANN and Word2Vec analyses. These findings also align with a recent fMRI study (Luo et al., 2023) using natural images to explore the neural selectivity for real-world size, finding that low-level visual information could hardly account for neural size preferences, although that study did not consider covariables like retinal size and real-world depth.

In contrast to the later-emerging real-world size representations, it makes sense that retinal size representations could be processed more quickly based on more fundamental, lower-

level information such as shape and edge discrimination. Interestingly, real-world depth

representations emerged even earlier than retinal size, suggesting that depth feature may precede

real-world size processing. This early emergence might reflect the role of depth cues in

facilitating object segmentation, as proposed in classical theories of vision (Marr, 1982), where

depth helps delineate object boundaries from complex backgrounds. Additionally, there was a

secondary, albeit substantially later, significant depth representation time-window, which might

indicate that our brains also have the ability to integrate object retinal size and higher-level real-

size information to form the final representation of real-world depth. Our comparisons between

human brains and artificial models and explorations on ANNs and Word2Vec offer further

insights and suggest that although real-world object size and depth are closely related, object

real-world size appears to be a more stable and higher-level dimension.

The concept of 'object space' in cognitive neuroscience research is crucial for

understanding how various visual features of objects are represented. Historically, various visual

features have been considered important dimensions in constructing object space, including

animate-inanimate (Kriegeskorte et al., 2008; Naselaris et al., 2012), spikiness (Bao et al., 2020;

Coggan & Tong, 2023), and physical appearance (Edelman et al., 1998). In this study, we focus

on one particular dimension, real-world size (Huang et al., 2022; Konkle & Caramazza, 2013;

Konkle & Oliva, 2012b). How we generate neural distinctions of different object real-world size

and where this ability comes from remain uncertain. Some previous studies found that object

shape rather than texture information could trigger neural size representations (Huang et al.,

2022; Long et al., 2016, 2018; R. Wang et al., 2022). Our results attempt to further advance their

findings, that object real-world size is a stable and higher-level dimension substantially driven by

object semantics in object space.

Increasingly, research has begun to use ANNs to study the mechanisms of object

recognition (Ayzenberg et al., 2023; Cichy & Kaiser, 2019; Doerig et al., 2023; Kanwisher et al.,

2023). We can explore how the human brain processes information at different levels by

comparing brain activity with models (Cichy et al., 2016; S. M. Khaligh-Razavi & Kriegeskorte,

2014; Kuzovkin et al., 2018; Xie et al., 2020), and we can also analyze the representation

patterns of the models with some specific manipulations and infer potential processing

mechanisms in the brain (Golan et al., 2020; Huang et al., 2022; Lu & Ku, 2023; Xu et al., 2021).

In the current study, our comparisons result between EEG signals and different ANNs showed

that the visual model's early layer had a higher similarity to the brain in the early stage, while the

visual-semantic model's late layer had a higher similarity to the brain in the late stage. In

addition, to assess whether this EEG-ANN similarity pattern generalizes to more biologically

inspired architectures, we conducted the same analyses and found that CORnet show similar

patterns to those observed for ResNet and CLIP, providing converging evidence across models

(Figure S10). However, for the representation of objects, partial correlation results for different

ANNs didn't demonstrate the superiority of the multi-modal model at late layers. This might be

due to models like CLIP, which contain semantic information, learning more complex image

descriptive information (like the relationship between object and the background in the image).

Real-world size might be a semantic dimension of the object itself, and its representation does

not require overall semantic descriptive information of the image. In contrast, retinal size and

real-world depth could rely on image background information for estimation, thus their

representations in the CLIP late layer disappeared when input images had only pure object but no

background.

Although our study does not directly test specific models of visual object processing, the

observed temporal dynamics provide important constraints for theoretical interpretations. In

particular, we find that real-world size representations emerge significantly later than low-level

visual features such as retinal size and depth. This temporal profile is difficult to reconcile with a

purely feedforward account of visual processing (e.g., DiCarlo et al., 2012), which posits that

object properties are rapidly computed in a sequential hierarchy of increasingly complex visual

features. Instead, our results are more consistent with frameworks that emphasize recurrent or

top-down processing, such as the reverse hierarchy theory (Hochstein & Ahissar, 2002), which

suggests that high-level conceptual information may emerge later and involve feedback to earlier

visual areas. This interpretation is further supported by representational similarities with late-

stage artificial neural network layers and with a semantic word embedding model (Word2Vec),

both of which reflect learned, abstract knowledge rather than low-level visual features. Taken

together, these findings suggest that real-world size is not merely a perceptual attribute, but one

that draws on conceptual or semantic-level representations acquired through experience. While

our EEG analyses focused on posterior electrodes and thus cannot definitively localize cortical

sources, we see this study as a step toward linking low-level visual input with higher-level

semantic knowledge. Future work incorporating broader spatial coverage (e.g., anterior sensors),

source localization, or complementary modalities such as MEG and fMRI will be critical to

adjudicate between alternative models of object representation and to more precisely trace the

origin and flow of real-world size information in the brain. Moreover, building on the promising

findings of our study, future work may further delve into the detailed processes of object

processing and object space. One important problem to solve is how real-world size interacts

with other object dimensions in object space. In addition, our approach could be used with future

studies investigating other influences on object processing, such as how different task conditions

impact and modulate the processing of various visual features.

Moreover, we must also emphasize that in this study, we were concerned with perceived

real-world size and depth reflecting a perceptual estimation of our world, which are slightly

different from absolute physical size and depth. The differences in brain encoding between

perceived and absolute physical size and depth require more comprehensive measurements of an

object's physical attributes for further exploration. Also, we focused on perceiving depth and

size from 2D images in this study, which might have some differences in brain mechanism

compared to physically exploring the 3D world. Nevertheless, we believe our study offers a

valuable contribution to object recognition, especially the encoding process of object real-world

size in natural images. Additionally, we acknowledge that our metric for real-world depth was

derived indirectly as the ratio of perceived real-world size to retinal size. While this formulation

is grounded in geometric principles of perspective projection and served the purpose of

analytically dissociating depth from size in our RSA framework, it remains a proxy rather than a

direct measure of perceived egocentric distance. Future work incorporating behavioral or

psychophysical depth ratings would be valuable for validating and refining this metric.

In conclusion, we used computational methods to distinguish the representations of real-

world size, retinal size, and real-world depth features of objects in ecologically natural images in

both human brains and ANNs. We found an unconfounded representation of object real-world

size, which emerged at later time windows in the human EEG signal and at later layers of

artificial neural networks compared to real-world depth, and which also appeared to be preserved

as a stable dimension in object space. Thus, although size and depth properties are closely

correlated, the processing of perceived object size and depth may arise through dissociated time

courses and mechanisms. Our research provides a temporally resolved characterization of how

certain key object properties – such as object real-world size, depth, and retinal size – are

represented in the brain, which advances our understanding of real-world size encoding as a

stable and semantically grounded dimension in object space, and contributes to the development

of more brain-like visual models.

Acknowledgments

678 This work was supported by research grants from the National Institutes of Health (R01-

679 EY025648) and from the National Science Foundation (NSF 1848939) to JDG. The authors

680 declare no competing financial interests.

References

Allen, E. J., St-Yves, G., Wu, Y., Breedlove, J. L., Prince, J. S., Dowdle, L. T., Nau, M., Caron,

B., Pestilli, F., Charest, I., Hutchinson, J. B., Naselaris, T., & Kay, K. (2022). A massive 7T

fMRI dataset to bridge cognitive neuroscience and artificial intelligence. *Nature*

Neuroscience, *25*(1), 116–126.

Ayzenberg, V., Blauch, N., & Behrmann, M. (2023). Using deep neural networks to address the

how of object recognition. *PsyArXiv*.

Bao, P., She, L., McGill, M., & Tsao, D. Y. (2020). A map of object space in primate

inferotemporal cortex. *Nature*, *583*(7814), 103–108.

Bracci, S., Daniels, N., & Op de Beeck, H. (2017). Task Context Overrules Object- and

Category-Related Representational Content in the Human Parietal Cortex. *Cerebral Cortex*,

27(1), 310–321.

Bracci, S., & Op de Beeck, H. (2016). Dissociations and associations between shape and

category representations in the two visual pathways. *Journal of Neuroscience*, *36*(2), 432–

444.

Chen, Y. C., Deza, A., & Konkle, T. (2022). How big should this object be? Perceptual

influences on viewing-size preferences. *Cognition*, *225*, 105114.

Choksi, B., Mozafari, M., VanRullen, R., & Reddy, L. (2022). Multimodal neural networks

better explain multivoxel patterns in the hippocampus. *Neural Networks*, *154*, 538–542.

Choksi, B., Vanrullen, R., & Reddy, L. (2022, August 25). Do multimodal neural networks better

explain human visual representations than vision-only networks? *Conference on Cognitive*

Computational Neuroscience 2022.

Cichy, R. M., & Kaiser, D. (2019). Deep Neural Networks as Scientific Models. *Trends in*

Cognitive Sciences, *23*(4), 305–317.

Cichy, R. M., Khosla, A., Pantazis, D., Torralba, A., & Oliva, A. (2016). Comparison of deep

neural networks to spatio-temporal cortical dynamics of human visual object recognition

reveals hierarchical correspondence. *Scientific Reports*, *6*(1), 1–13.

Coggan, D. D., & Tong, F. (2023). Spikiness and animacy as potential organizing principles of

human ventral visual cortex. *Cerebral Cortex*, *33*(13), 8194–8217.

Conwell, C., Prince, J. S., Alvarez, G. A., & Konkle, T. (2022). Large-Scale Benchmarking of

Diverse Artificial Vision Models in Prediction of 7T Human Neuroimaging Data. *BioRxiv*.

Conwell, C., Prince, J. S., Kay, K. N., Alvarez, G. A., & Konkle, T. (2024). A large-scale

examination of inductive biases shaping high-level visual representation in brains and

machines. *Nature Communications*, *15*(1), 1–18.

DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How does the brain solve visual object

recognition? *Neuron*, *73*(3), 415–434.

Doerig, A., Kietzmann, T. C., Allen, E., Wu, Y., Naselaris, T., Kay, K., & Charest, I. (2022).

Semantic scene descriptions as an objective of human vision. *ArXiv*.

Doerig, A., Sommers, R., Seeliger, K., Richards, B., Ismael, J., Lindsay, G., Kording, K., Konkle,

T., Van Gerven, M. A. J., Kriegeskorte, N., & Kietzmann, T. C. (2023). The

neuroconnectionist research programme. *Nature Reviews Neuroscience*, *24*, 431–450.

Edelman, S., Grill-Spector, K., Kushnir, T., & Malach, R. (1998). Toward direct visualization of

the internal shape representation space by fMRI. *Psychobiology*, *26*(4), 309–321.

Gifford, A. T., Dwivedi, K., Roig, G., & Cichy, R. M. (2022). A large and rich EEG dataset for

modeling human visual object recognition. *NeuroImage*, *264*, 119754.

Golan, T., Raju, P. C., & Kriegeskorte, N. (2020). Controversial stimuli: Pitting neural networks

against each other as models of human cognition. *Proceedings of the National Academy of*

Sciences of the United States of America, *117*(47), 29330–29337.

Greene, M. R., & Hansen, B. C. (2020). Disentangling the Independent Contributions of Visual and Conceptual Features to the Spatiotemporal Dynamics of Scene Categorization. *Journal of Neuroscience*, *40*(27), 5283–5299.

Grootswagers, T., Zhou, I., Robinson, A. K., Hebart, M. N., & Carlson, T. A. (2022). Human EEG recordings for 1,854 concepts presented in rapid serial visual presentation streams. *Scientific Data*, *9*(1), 1–7.

Güçlü, U., & van Gerven, M. A. J. (2015). Deep Neural Networks Reveal a Gradient in the Complexity of Neural Representations across the Ventral Stream. *Journal of Neuroscience*, *35*(27), 10005–10014.

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep Residual Learning for Image Recognition. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770–778.

Hebart, M. N., Dickter, A. H., Kidder, A., Kwok, W. Y., Corriveau, A., Van Wicklin, C., & Baker, C. I. (2019). THINGS: A database of 1,854 object concepts and more than 26,000 naturalistic object images. *PLoS ONE*, *14*(10), 1–24.

Hochstein, S., & Ahissar, M. (2002). View from the top: Hierarchies and reverse hierarchies in the visual system. *Neuron*, *36*(5), 791–804.

Huang, T., Song, Y., & Liu, J. (2022). Real-world size of objects serves as an axis of object space. *Communications Biology*, *5*(1), 1–12.

Huth, A. G., Nishimoto, S., Vu, A. T., & Gallant, J. L. (2012). A Continuous Semantic Space

Describes the Representation of Thousands of Object and Action Categories across the

Human Brain. *Neuron*, *76*(6), 1210–1224.

Jozwik, K. M., Kietzmann, T. C., Cichy, R. M., Kriegeskorte, N., & Mur, M. (2023). Deep

Neural Networks and Visuo-Semantic Models Explain Complementary Components of

Human Ventral-Stream Representational Dynamics. *Journal of Neuroscience*, *43*(10),

1731–1741.

Kanwisher, N., Khosla, M., & Dobs, K. (2023). Using artificial neural networks to ask 'why'

questions of minds and brains. *Trends in Neurosciences*, *46*(3), 240–254.

Kappenman, E. S., & Luck, S. J. (2010). The effects of electrode impedance on data quality and

statistical significance in ERP recordings. *Psychophysiology*, *47*(5), 888–904.

Khaligh-Razavi, S.-M., Cichy, R. M., Pantazis, D., & Oliva, A. (2018). Tracking the

Spatiotemporal Neural Dynamics of Real-world Object Size and Animacy in the Human

Brain. *Journal of Cognitive Neuroscience*, *30*(11), 1559–1576.

Khaligh-Razavi, S. M., & Kriegeskorte, N. (2014). Deep Supervised, but Not Unsupervised,

Models May Explain IT Cortical Representation. *PLoS Computational Biology*, *10*(11),

e1003915.

Kietzmann, T. C., Spoerer, C. J., Sörensen, L. K. A., Cichy, R. M., Hauk, O., & Kriegeskorte, N.

(2019). Recurrence is required to capture the representational dynamics of the human visual

system. *Proceedings of the National Academy of Sciences of the United States of America*,

116(43), 21854–21863.

Konkle, T., & Caramazza, A. (2013). Tripartite Organization of the Ventral Stream by Animacy

and Object Size. *Journal of Neuroscience*, *33*(25), 10235–10242.

Konkle, T., & Oliva, A. (2011). Canonical Visual Size for Real-World Objects. *Journal of*

Experimental Psychology: Human Perception and Performance, *37*(1), 23–37.

Konkle, T., & Oliva, A. (2012a). A familiar-size Stroop effect: Real-world size is an automatic

property of object representation. *Journal of Experimental Psychology: Human Perception*

and Performance, *38*(3), 561.

Konkle, T., & Oliva, A. (2012b). A Real-World Size Organization of Object Responses in

Occipitotemporal Cortex. *Neuron*, *74*(6), 1114–1124.

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., &

Bandettini, P. A. (2008). Matching Categorical Object Representations in Inferior Temporal

Cortex of Man and Monkey. *Neuron*, *60*(6), 1126–1141.

Kubilius, J., Schrimpf, M., Kar, K., Rajalingham, R., Hong, H., Majaj, N. J., Issa, E. B.,

Bashivan, P., Prescott-Roy, J., Schmidt, K., Nayebi, A., Bear, D., Yamins, D. L. K., &

Dicarlo, J. J. (2019). Brain-Like Object Recognition with High-Performing Shallow

Recurrent ANNs. *Advances in Neural Information Processing Systems (NeurIPS)*, *32*.

Kuzovkin, I., Vicente, R., Petton, M., Lachaux, J. P., Baciu, M., Kahane, P., Rheims, S., Vidal, J.

R., & Aru, J. (2018). Activations of deep convolutional neural networks are aligned with

gamma band activity of human visual cortex. *Communications Biology*, *1*(1), 1–12.

Long, B., & Konkle, T. (2017). A familiar-size Stroop effect in the absence of basic-level

recognition. *Cognition*, *168*, 234–242.

Long, B., Konkle, T., Cohen, M. A., & Alvarez, G. A. (2016). Mid-level perceptual features

distinguish objects of different real-world sizes. *Journal of Experimental Psychology:*

General, *145*(1), 95–109.

Long, B., Yu, C. P., & Konkle, T. (2018). Mid-level visual features underlie the high-level

categorical organization of the ventral stream. *Proceedings of the National Academy of*

Sciences of the United States of America, *115*(38), E9015–E9024.

Lu, Z., & Ku, Y. (2020). NeuroRA: A Python Toolbox of Representational Analysis From Multi-

Modal Neural Data. *Frontiers in Neuroinformatics*, *14*, 61.

Lu, Z., & Ku, Y. (2023). Bridging the gap between EEG and DCNNs reveals a fatigue

mechanism of facial repetition suppression. *IScience*, *26*(12), 108501.

Luck, S. J. (2014). An Introduction to the Event-Related Potential Technique. In *An introduction*

to the event-related potential technique (Second Edi). MIT Press.

Luo, A. F., Wehbe, L., Tarr, M. J., & Henderson, M. M. (2023). Neural Selectivity for Real-

World Object Size In Natural Images Abbreviated title：: Neural Selectivity for Real-World

Size. *BioRxiv*.

Marr, D. (1982). *Vision：: a computational investigation into the human representation and*

processing of visual information. The MIT Press.

Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). Efficient Estimation of Word

Representations in Vector Space. *Proceedings of the International Conference on Learning*

Representations (ICLR).

Muttenthaler, L., & Hebart, M. N. (2021). THINGSvision: A Python Toolbox for Streamlining

the Extraction of Activations From Deep Neural Networks. *Frontiers in Neuroinformatics*,

15, 45.

Naselaris, T., Stansbury, D. E., & Gallant, J. L. (2012). Cortical representation of animate and

inanimate objects in complex natural scenes. *Journal of Physiology Paris*, *106*(5–6), 239–

249.

Proklova, D., Kaiser, D., & Peelen, M. V. (2016). Disentangling Representations of Object

Shape and Object Category in Human Visual Cortex: The Animate–Inanimate Distinction.

Journal of Cognitive Neuroscience, *28*(5), 680–692.

Quek, G., Theodorou, A., & Peelen, M. V. (2023). Better together□: Objects in familiar

constellations evoke high-level representations of real-world size. *BioRxiv*.

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A.,

Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning Transferable Visual

Models From Natural Language Supervision. *Proceedings of the International Conference*

on Machine Learning (ICML).

Řehůřek, R., & Sojka, P. (2010). Software framework for topic modelling with large corpora.

Proceedings of the LREC 2010 Workshop on New Challenges for NLP Frameworks, 45–50.

Setti, A., Caramelli, N., & Borghi, A. M. (2008). Conceptual information about size of objects in

nouns. *European Journal of Cognitive Psychology*, *21*(7), 1022–1044.

Song, Y., Liu, B., Li, X., Shi, N., Wang, Y., & Gao, X. (2024). Decoding Natural Images from

EEG for Object Recognition. *International Conference on Learning Representations (ICLR)*.

Stoinski, L. M., Perkuhn, J., & Hebart, M. N. (2023). THINGSplus: New norms and metadata for

the THINGS database of 1854 object concepts and 26,107 natural object images. *Behavior*

Research Methods, 1–21.

Troiani, V., Stigliani, A., Smith, M. E., & Epstein, R. A. (2014). Multiple object properties drive

scene-selective regions. *Cerebral Cortex*, *24*(4), 883–897.

Wang, A. Y., Kay, K., Naselaris, T., Tarr, M. J., & Wehbe, L. (2022). Incorporating natural

language into vision models improves prediction and understanding of higher visual cortex.

BioRxiv.

Wang, R., Janini, D., & Konkle, T. (2022). Mid-level feature differences support early animacy

and object size distinctions: Evidence from electroencephalography decoding. *Journal of*

Cognitive Neuroscience, *34*(9), 1670–1680.

Xie, S., Kaiser, D., & Cichy, R. M. (2020). Visual Imagery and Perception Share Neural

Representations in the Alpha Frequency Band. *Current Biology*, *30*(13), 2621-2627.e5.

Xu, S., Zhang, Y., Zhen, Z., & Liu, J. (2021). The Face Module Emerged in a Deep

Convolutional Neural Network Selectively Deprived of Face Experience. *Frontiers in*

Computational Neuroscience, *15*, 1–12.

Yamins, D. L. K., & DiCarlo, J. J. (2016). Using goal-driven deep learning models to understand

sensory cortex. *Nature Neuroscience*, *19*(3), 356–365.

Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014).

Performance-optimized hierarchical models predict neural responses in higher visual cortex.

Proceedings of the National Academy of Sciences of the United States of America, *111*(23),

8619–8624.

Supplementary materials

Figure S1. Four ANN RDMs of ResNet early layer, ResNet late layer, CLIP early layer, and CLIP late

later.

863   **Figure S2**. Word2Vec RDMs.

866 **Figure S3**. Four ANN RDMs with inputs of cropped object images without background of ResNet early

867 layer, ResNet late layer, CLIP early layer, and CLIP late later.

Figure S4. Representational similarities (partial Spearman correlations) between ANN RDMs from

multiple layers in ResNet and CLIP and hypothesis-based RDMs of real-world depth, retinal size, and

real-world size (as extended results of Figure 3E). Asterisks indicate significant partial correlations

(bootstrap test, p<.05).

Figure S5. Representational similarity time courses (Spearman correlations) between EEG neural RDMs

and ANN RDMs from multiple layers (as extended results of Figure 3F). (A) Similarity between EEG and

ResNet's multiple layers (from early layer to late layer: ResNet.maxpool layer, ResNet.layer1 layer,

ResNet.layer2 layer, ResNet.layer3 layer, ResNet.layer4 layer, ResNet.avgpool). (B) Similarity between

EEG and CLIP's multiple layers (from early layer to late layer: CLIP.visual.avgpool layer,

CLIP.visual.layer1 layer, CLIP.visual.layer2 layer, CLIP.visual.layer3 layer, CLIP.visual.layer4 layer,

CLIP.visual.attnpool). Color-coded small dots at the top indicate significant timepoints (cluster-based

permutation test, p<.05). Shaded area reflects ±SEM across the 10 subjects.

Figure S6. Representational similarity time courses (partial Spearman correlations) between EEG neural

RDMs and ANN RDMs controlling for the three hypothesis-based RDMs. Color-coded small dots at the

top indicate significant timepoints (cluster-based permutation test, p<.05). Shaded area reflects ±SEM

across the 10 subjects.

Figure S7. Noise ceiling of representational similarity analysis based on EEG neural RDMs. Shaded area
reflects the lower and upper bound.

 Figure S8. Representational similarity time courses (partial Spearman correlations) between EEG neural

 RDMs and the Word2Vec RDM controlling for four ANN RDMs (ResNet early/late and CLIP early/late

 layers). Color-coded small dots at the top indicate significant timepoints (cluster-based permutation test,

 $p<.05$). Shaded area reflects $\pm$SEM across the 10 subjects.

Figure S9. Unique and shared variance of real-world size and semantic information (from Word2Vec) in

EEG neural representations using variance partitioning analysis while controlling retinal size and real-

world depth. Color-coded small dots at the top indicate significant timepoints (cluster-based permutation

test, p<.05). Shaded area reflects ±SEM across the 10 subjects.

Figure S10. RSA results based on CORnet. (A) Representational similarities (partial Spearman

correlations) between the five CORnet RDMs from multiple layers (from early layer to late layer:

CORnet.V1, CORnet.V2, CORnet.V4, CORnet.IT, and CORnet.decoder.avgpool) and hypothesis-based

RDMs of real-world depth, retinal size, and real-world size. Asterisks indicate significant partial

correlations (bootstrap test, p<.05). (B) Representational similarity time courses (Spearman correlations)

between EEG neural RDMs and the five CORnet RDMs. Color-coded small dots at the top indicate

significant timepoints (cluster-based permutation test, p<.05). Shaded area reflects ±SEM across the 10

subjects.

Table S1 Statistical results of similarities (partial Spearman correlations) between four ANN RDMs and

three hypothesis-based RDMs.

ANN × HYP	*ResNet (early)*	*CLIP (early)*	*ResNet (late)*	*CLIP (late)*
Real-World depth	**r=.0330, p<.001**	**r=.0262, p<.001**	r=-.0513, p=1	**r=.0278, p<.001**
Retinal Size	**r=.0618, p<.001**	**r=.0730, p<.001**	**r=.0221, p<.001**	r=.0058, p=.1788
Real-World Size	r=-.0330, p=1	r=-.0027, p=.8710	**r=0.2497, p<.001**	**r=0.2378, p<.001**

923
924

925 **Table S2** Statistical results of similarities (partial Spearman correlations) between four ANN RDMs with

926 inputs of cropped object images without background and three hypothesis-based RDMs.

ANN (obj-only imgs) $\times$ HYP	ResNet (early)	CLIP (early)	ResNet (late)	CLIP (late)
Real-World depth	r=-.0109, p=.9382	r=-.0086, p=.8862	**r=.0183, p=.0049**	r=-.0176, p=.9934
Retinal Size	**r=.0323, p<.001**	**r=.0315, p<.001**	r=-.0032, p=.6725	r=-.0031, p=.6705
Real-World Size	r=.0022, p=.3781	r=.0084, p=.1193	**r=.0402, p<.001**	**r=.0154, p=.0149**