Flexible neural representations of abstract structural knowledge in the human Entorhinal Cortex

*Mark S[2]., Schwartenbeck P.[1,2], Hahamy A[1], Samborska V[2], **Baram AB.[1], **Behrens TEJ[1,2,3].

1. Wellcome Centre for Integrative Neuroimaging, University of Oxford, Oxford, UK.

2. Wellcome Centre for Human Neuroimaging, University College London, London, UK.

3. Sainsbury Wellcome Centre for Neural Circuits and Behaviour, University College London, London, UK

*:corresponding author

**: Equal contribution

Abstract

Humans' ability for generalisation is outstanding. It is flexible enough to identify cases where knowledge from prior tasks is relevant, even when many features of the current task are different, such as the sensory stimuli or the size of the task state space. We have previously shown that in abstract tasks, humans can generalise knowledge in cases where the only cross-task shared feature is the statistical rules that govern the task's state-state relationships. Here, we hypothesized that this capacity is associated with generalisable representations in the entorhinal cortex (EC). This hypothesis was based on the EC's generalisable representations in spatial tasks and recent discoveries about its role in the representation of abstract tasks. We first develop an analysis method capable of testing for such representations in fMRI data, explain why other common methods would have failed for our task, and validate our method through a combination of electrophysiological data analysis, simulations and fMRI sanity checks. We then show with fMRI that EC representations generalise across complex non-spatial tasks that share a hexagonal grid structural form but differ in their size and sensory stimuli, i.e. their only shared feature is the rules governing their statistical structure. There was no clear evidence for such generalisation in EC for non-spatial tasks with clustered, as opposed to planar, structure.

Introduction

If you grew up in a small town, arriving in a big city might come as a shock. However, you'll still be able to make use of your previous experiences, despite the difference in the size of the environment: When trying to navigate the busy city streets, your knowledge of navigation in your hometown is crucial. For example, it's useful to know the constraints that a 2D topological structure exerted on distances between locations. When trying to make new friends, it's useful to remember how people in your hometown tended to cluster in groups, with popular individuals perhaps belonging to several groups. Indeed, the statistical rules (termed "structural form", (Kemp and Tenenbaum 2008)) that govern the relationships between elements (states) in the environment are particularly useful for generalisation to novel situations, as they do not depend on the size, shape or sensory details of the environment (Mark *et al.* 2020). Such generalisable features of environments are proposed to be part of the "cognitive map" encoding the relationships between their elements (Tolman 1948; Behrens *et al.* 2018; Mark *et al.* 2020).

The most studied examples of such environments are spatial 2D tasks. In all spatial
environments, regardless of their size or shape, the relations between states (in this case
locations) are subject to the same Euclidean statistical constraints. The spatial example is
particularly useful because neural spatial representations are well-characterised. Indeed,
one of the most celebrated of these - grid cells in the entorhinal cortex (EC) - has been
suggested as (part of) a neural substrate for spatial generalisation (Behrens *et al.* 2018;
Whittington *et al.* 2022). This is because (within a grid module) grid cells maintain their
coactivation structure across different spatial environments (Fyhn *et al.* 2007; Yoon *et al.*
2013). In other words, the information embedded in grid cells generalises across 2D spatial
environments (including environments of different shapes and sizes). Following a surge of
studies showing that EC spatial coding principles are also used in non-spatial domains
(Constantinescu, O'Reilly and Behrens 2016; Garvert, Dolan and Behrens 2017; Bao *et al.*
2019; Park *et al.* 2020), we have recently shown that EC also generalises over non-spatial
environments that share the same statistical structure (Baram *et al.* 2021). Importantly, in
that work the graphs that described the same-structured environments were isomorphic -
i.e. there was a one-to-one mapping between states across same-structure environments.

What do we mean when we say the EC has "generalisable representations" in spatial tasks?
and how can we probe these representations in complex non-spatial tasks? Between
different spatial environments, each grid cell realigns: its firing fields might rotate and shift
(Fyhn *et al.* 2007). Crucially, this realignment is synchronized within a grid module
population (Yoon *et al.* 2013; Gardner *et al.* 2022), such that the change in the grid angle
and phase of all cells is the same. This means that cells that have neighboring firing fields in
one environment will also have neighboring firing fields in another environment- the
coactivation structure is maintained (Yoon *et al.* 2013; Gardner *et al.* 2022). A mathematical
corollary is that grid cells' activity lies in the same low-dimensional subspace (manifold,
(Yoon *et al.* 2013; Gardner *et al.* 2022)) in all spatial environments. This subspace remains
even during sleep, meaning the representation is stably encoded (Burak and Fiete 2009;
Gardner *et al.* 2019; Trettel SG et al. 2019).

We have recently developed an analysis method, referred to as "subspace generalisation",
which allows for the quantification of the similarities between linear neural subspaces, and
used it to probe generalisation in cell data (Samborska *et al.* 2022). Unlike other
representational methods for quantifying the similarity between activity patterns (like RSA,
used in Baram et al. (Kriegeskorte, Mur and Bandettini 2008; Diedrichsen and Kriegeskorte
2017)), this method has the ability to isolate the shared features underlying tasks that do
not necessarily have a straightforward cross-task mapping between states, such as when the
sizes of tasks underlying graphs are different. Here, we use it to quantify generalisation in
such a case, but on fMRI data of humans solving complex abstract tasks rather than on cell
data. We designed an abstract associative-learning task in which visual images were
assigned to nodes on a graph and were presented sequentially, according to their relative
ordering on the graph. The graphs belonged to two different families of graphs, each
governed by a different set of statistical regularity rules (structural forms (Kemp and
Tenenbaum 2008)) – hexagonal (triangular) lattice graphs, and community structure graphs.

There were two graphs of each structural form. Crucially, the graph size and embedded
images differed within a pair of graphs with the same structural form (Figure 3b), allowing
us to test generalisation due to structural form across both environment size and sensory
information.

We first validate our approach by showing that subspace generalisation detects the known
generalisation properties of entorhinal grid cells and hippocampal place cells when rodents
free-forage in two different spatial environments – properties that have inspired our study's
hypothesis. Next, we propose that our method can capture these properties even in low-
resolution data such as fMRI. We provide twofold support for this conjecture: through
sampling and averaging of the rodent data to create low resolution version of the data, and
through simulations of grid cells grouped into simulated voxels to account for the very low
resolution of the BOLD signal. We use these simulations to discuss how the sensitivity of our
method depends on various characteristics of the signal. Next, we validate the method for
real fMRI signals by showing it detects known properties of visual encoding in the visual
cortex in our task. Finally, and most importantly, we show that EC generalises its voxelwise
correlation patterns over abstract, discrete hexagonal graphs of different size and stimuli,
exactly as grid cells do in space. This result, however, did not hold for the community graph
structures. We discuss some possible experimental shortcomings that might have led to this
null result.

Theory – "subspace generalisation"

How can we probe the neural correlates of generalisation of abstract tasks in the human
brain? Popular representational analysis methods such as Representational Similarity
Analysis (RSA) (Kriegeskorte, Mur and Bandettini 2008; Diedrichsen and Kriegeskorte 2017)
and Repetition Suppression (Grill-Spector, Henson and Martin 2006; Barron, Garvert and
Behrens 2016) have afforded some opportunities in this respect (Baram *et al.* 2021).
However, because these methods rely on similarity measures between task states, they
require labeling of a hypothesized similarity between each pair of states across tasks. Such
labeling is not possible when we do not know which states in one task align with which
states in another task. In the spatial example where states are locations, the mapping of
each location in room A to locations in room B doesn't necessarily exist - particularly when
the rooms differ in size or shape. This makes labeling of hypothesized similarity between
each pair of locations impossible. How can we look for shared activity patterns in such a
case?

We have recently proposed this can be achieved by studying the correlation of different
neurons across states (Samborska *et al.* 2022) (as opposed to RSA - which relies on the
correlation of different states across neurons). If two tasks contain similar patterns of neural
activity (regardless of when these occurred in each task), then the *neuron X neuron*
correlation matrix (across states within-task) will look similar in both tasks. This correlation
matrix can be summarised by its eigenvectors, which are patterns across neurons - akin to
"cell assemblies" - and their eigenvalues, which indicate how much each pattern contributes
to the overall variance in the data. If representations generalise across tasks, then patterns

that explain a lot of variance in task 1 will also explain a lot of variance in task 2. We can
compute the task 2 variance explained by each of the eigenvectors of task 1:

$$\Sigma_{12} = diag(U_1^T B_2 B_2^T U_1)$$

Where U_1 is a matrix with all task 1 eigenvectors as its columns, ordered by their
eigenvalues, and B_2 is the *neurons* X *states* task 2 data. These eigenvectors are ordered
according to the variance explained in task 1. Hence, if the same eigenvectors explain
variance across tasks, early eigenvectors will explain more variance in task 2 than late
eigenvectors. The cumulative sum of Σ_{12} will be a concave function and the area under this
concave function is a measure of how well neuronal patterns generalise across tasks (Figure
4d). We refer to this measure as subspace generalisation.

As validation and demonstration of our method, we first use it to recover differences in
generalisation between grid cells and place cells in the rodent brain that have been shown
previously with other methods. Next, we demonstrate the feasibility of our method in
capturing this difference in generalization properties even after we manipulate the data and
reduce its resolution. To complete the logical bridge from cells to voxels, we address the
limitation of this demonstration: the low number of cells recorded. We simulate voxels from
synthetic grid cells and show how our method's power depends on various characteristics of
the signal. These analyses show that theoretically (and under reasonable conditions) our
method could still detect medial temporal lobe generalisation properties in fMRI BOLD
signal. Finally, and most importantly, we use our method to analyse fMRI data, testing for
generalisation of the covariance between voxel representations in human EC across
complex non-spatial graphs with common regularities – analogous to the generalisation of
grid cells in physical space. Crucially, in this task other representational methods common in
fMRI analysis such as RSA or repetition suppression would not be applicable (due to lack of
one-to-one mapping between states across graphs), highlighting the usefulness of our
method.

Results

Subspace generalization captures known generalisation properties of grid and place cells

Grid cells and place cells differ in their generalisation property. When an animal moves from
one environment to another, place cells "remap": they change their correlation structure
such that place cells that are neighbours in environment 1 need not be neighbors in
environment 2. By contrast grid cells do not remap**:** the correlation structure between grid
cells is preserved across environments, such that pairs of grid cells (within the same module)
that have neighboring fields in environment 1 will also have neighboring fields in
environment 2 (Fyhn *et al.* 2007). This is true even though each grid cell shifts and rotates
its firing fields across environments - the grid cell population within a module realigns in
unison (Gardner *et al.* 2022; Waaga *et al.* 2022). Crucially, the angle and phase of this
realignment can't be predicted in advance, meaning it is not possible to create hypotheses
to test regarding the similarity between representations at a given location in environment

1 and a given location in environment 2 - a requirement for fMRI-compatible methods such

as RSA or repetition suppression. In this section we demonstrate how subspace

generalisation - which can also be useful in fMRI - captures the generalisation properties of

grid and place cells that have previously been shown only with traditional analysis methods

that require access to firing maps of single cells.

We computed subspace generalisation for grid and place cells recorded with

electrophysiology in a previous study (Chen *et al.* 2018), in which mice freely-foraged in two

square environments: a real physical and a virtual reality (VR) (see Methods for more

details). For our purposes, this dataset is useful because large numbers of both place cells

and grid cells were recorded (concurrently within a cell type) in two different environments

- rather than because of the use of a VR environment.

We compared two different situations: one where "task 1" and "task 2" were actually from

the same environment, Figure 1a - solid line, within-environment) and one where "task 1"

and "task 2" were from different environments (Figure 1a - dotted line, across-

environments).

As predicted, across environments grid cells' subspaces generalised: eigenvectors that were

calculated using activity in one environment explained the activity variance in the other

environment just as well as the within-environment baseline (Figure 1a, compare dotted

and solid black lines, plots show the average of the projections of activity from one

environment on EVs from the other environment and vice versa). The difference between

the area under the curve (AUC) of the two lines was significantly smaller than chance

(p<0.001 using a permutation test, see Methods and supplementary Figure S1). Importantly,

grid cells generalized much better between the environments than place cells; the

difference in AUCs between the solid and dotted lines is significantly smaller for grid cells

compared to place cells (Figure 1b, p<0.001, for both permutation test and 2 sample t-test,

see Methods and supplementary material). Interestingly, the difference in AUCs was also

significantly smaller than chance for place cells (Figure 1a, compare dotted and solid green

lines, p<0.05 using permutation tests, see statistics and further examples in supplementary

material Figure S2), consistent with recent models predicting hippocampal remapping that is

not fully random (Whittington et al. 2020).

From neurons to voxels

So far, we have validated our method when applied to neurons. However, our primary

interest in this manuscript is to apply it to fMRI data. To illustrate the efficacy of this

approach in revealing generalisable neuronal subspaces within low resolution data like

fMRI, we applied our method to such data – both from manipulated electrophysiology and

simulations. We first examined our method on low-resolution versions of the Chen et al.

rodent MTL data, obtained by grouping and averaging cells. We show that our method can

still detect subspace generalization even on the supra-cellular level. However, due to the

small number of recorded cells, this analysis does not fully replicate a voxel's BOLD signal,

which corresponds to the average activity of thousands of cells. To address this, we

simulated many grid cells and grouped them into voxels, with each voxel's activity

corresponding to the average activity of its cells. We then applied subspace generalisation
to the simulated pseudo-voxels, and examined how the results depend on various signal
characteristics.

Using Chen et al electrophysiology dataset, we first normalised each cell's firing rate maps,
and then created bootstrapped low-resolution data: for each sampling iteration we sampled
7 cells (with repeats) into 2 groups within each animal and averaged the activities of cells
within each group. This results in a 2-long vector for each animal. We then concatenate
these vectors across animals. Note that for grid cells, this pooling over independent groups
of neurons is reminiscent of pooling over different grid modules in a single subject. For each
sample we calculated the difference in the area under the curve (AUC) between within and
across environments projections as above (averaged over the projections on both
environments, Figure 1c). We repeat this bootstrapping step to create a distribution of the
differences in AUC for place cells and grid cells (Figure 1d). The difference in AUC was
smaller for grid cells than for place cells (p<0.001 Kolmogorov Simonov test), as is expected
from the single cells' analysis above.

FIgure 1. Subspace generalisation across environments in grid and place cells in data from
Chen et al. 2018.

a. The cumulative variance explained by the eigenvectors (EVs) calculated using the activity
of the grid (black) or place (green) cells, within (solid lines) and across (dotted lines)
environments. Subspace generalization is calculated as the difference between the area

under the curve (AUC) of two lines. The difference between the black lines is small,
indicating generalisation of grid cells across environments. The difference between the
green lines is larger, indicating remapping of place cells (p<0.001, permutation test, see
Methods).

b. The difference between the within and across (solid and dashed lines in a., respectively)
environments AUCs of the cumulative variance explained by grid or place cells (black or
green lines in a., respectively). Data shown for all mice with enough grid or place cells
(>10 recorded cells of the same type, each bar is a mouse and a specific projection (i.e.
projecting on environment one or two)). The differences between the grid cells AUCs are
significantly smaller than the place cells (p < 0.001 permutation test, see supplementary
for more statistical analyses and specific examples).

c. An example of the cumulative variance explained by the eigenvectors, calculated using
the constructed low-resolution version of grid and place cells data. The solid and dotted
lines are average over 10 samples and the shaded areas represent the standard error of
the mean across samples. Here, as above, the solid lines are projection within
environment and the dotted lines are projections between environments.

d. Subspace generalization in the low resolution version of the data captures the same
generalization properties of grid vs place cells. The distributions were created via
bootstrapping over cells from the same animal, averaging their activity, concatenating
the samples across all animals and calculating the AUC difference between within and
across environments projections (p<<0.001 Kolmogorov Simonov test).

The required number of cells to simulate a voxel's activity (let alone multiple voxels) far
exceeds the number of cells in the Chen et al. dataset. To overcome this limitation and
support our conjecture that our method can detect subspace-generalization even in fMRI
BOLD signal, we next used simulated data. We simulated grid cells (see methods) organized
into four grid modules, each composed of more than 10000 cells. We organized the cells in
each module into four groups (pseudo-voxels) and averaged the activity within each group
(see supplementary info for an example of our analysis using different number of groups
within each module, and how our results are affected by the number of voxels per module,
Figure S3). We concatenated the pseudo-voxels from all modules into one vector and
calculated the difference in subspace-generalization measure (i.e. the AUC of within and
between environments). We explored how two characteristics of the data affect subspace
generalization: whether the grouping into voxels (within each module) was organized
according to grid phase, and the level of noise in the data.

We first grouped the cells into voxels randomly, i.e. without any a-priori assumption on the
relationship between the physical proximity of cells within the cortical layer and their firing
rate maps. Examples of the resulted "pseudo-voxels" activity maps can be seen in Figure 2a.
However, recent work has suggested there is a relationship between grid cells' physical
proximity and their grid phases (Gu et al. 2018). We therefore also simulated "pseudo
voxels" by grouping grid cells, within each module, according to their grid phase (Figure 2b).

The pseudo-voxel's signal in the latter case is substantially stronger (compare color bar
scales a between Figure 2a and 2b).

How does the difference between the signal variances affect the subspace generalization
measure? If the BOLD signal had no noise and all the cells within a voxel were indeed grid
cells, the actual variance of the signal would not affect our measure (Figure 2c, the solid and
dashed black lines are similar in both panels; i.e. the eigenvectors that explain the activity
variance while the agent is in environment one explain the activity variance of environment
two similarly well, no matter how the cells are sampled into voxels). However, this is, of
course, unrealistic; the BOLD signal is noisy, and it is likely that voxel activity reflects non-
grid cells activity as well. To address this, we incorporated noise into our simulated voxel's
activity map. Figure 2c shows that increasing signal variance by grouping according to the
grid phase, leads to higher subspace generalization measure (AUC) compared to random
sampling; random sampling results in small AUC ($AUC \approx 0.5$) which is close to the expected
AUC following projections on random vectors (solid and dash blue lines in Figure 2c, left, see
supplementary info Figure S3 for further analysis). Predictably, as the fraction of randomly
sampled grid cells increases the ability to detect subspace generalization in the presence of
noise decreases (Figure 2d, Figure S3). Furthermore, sampling of grid cells according to
phase increases the statistical power of the subspace generalization method when the
amplitude of the noise increases (Figure 2e, Figure S3). To conclude, this shows under noisy
conditions, if nearby grid cells have similar phase tuning, as has been shown (Gu et al. 2018),
our method can in principle detect the generalization properties of grid cells, even in a very
low-resolution data, akin to the fMRI BOLD signal. It can in principle work to detect
generalization properties of any representation where nearby cells have similar tuning (such
as orientation tuning in V1).

Figure 2: simulated voxels from simulated grid modules

a. Examples of simulated voxels activity map in the two environments, without noise. upper: higher frequency module, lower: lower frequency module. Cells are grouped into voxels randomly.

b. Same as a. but with cells grouped into voxels according to the grid phase. Note the different scale of the color-bar between a. and b.

c. Subspace generalization plot for the 16 simulated voxels, where the grouping into voxels is either random (left) or according to phase (right). Legend as in d.

d. Left: AUCs of the subspace generalisation plots in c. as a function of the ratio of random vs phase-organised cells in the voxels, with no noise (black) or with high amplitude of noise (blue). Without noise (black lines), subspace generalization measure (AUC) remains high even when the fraction of randomly sampled cells increases. However, in the presence of noise, subspace generalization measure decreases with the fraction of randomly sampled cells. Right: p-value of the effect according to the permutation distribution (see methods,

shaded area: standard error of the mean). In the presence of noise and when the cells are sampled randomly, $AUC_{within-between}$ becomes non-significant, see supplementary info Figure S3 for the dependency of the permutation distributions on the presence of noise and sampling.

e. Same as d., except the continuous X-axis variable is the noise amplitude, for either of phase-organized (black) or randomly organized voxels (red). AUC decreases sharply with noise amplitude when the cells are sampled randomly, while it decreases more slowly when the cells are sampled according to phase. The decrease in AUC to chance level (i.e. AUC = 0.5) with the increase in noise amplitude results in insignificant difference in subspace generalization measure ($AUC_{within-between}$). See supplementary info Figure S3 for the permutation distributions.

Probing generalisation across abstract tasks with shared statistical rules – task design and behaviour

In human neuroimaging, the success of multivariate pattern analysis (MVPA, (Haxby *et al.* 2001)) and RSA (Kriegeskorte, Mur and Bandettini 2008; Diedrichsen and Kriegeskorte 2017)) tells us that, as with cells, the covariance between fMRI voxel activity contains information about the external world. It is therefore conceivable that we can measure the generalisation of fMRI patterns across related tasks using the same measure of subspace generalisation, but now applied to voxels rather than to cells. This will give us a measure of generlisation in humans that can be used across tasks with no state-to-state mapping – e.g. when the size of the state space is different across tasks. In this section, we first describe the experimental paradigm we used to test whether, as in physical space, EC 1) generalises over abstract tasks governed by the same statistical rules; and 2) does so in a manner that is flexible to the size of the environment. In the next section we use known properties of visual encoding as a sanity check for the use of subspace generalisation on fMRI data in this task. Finally, we describe how the fMRI subspace generalisation results in EC depend on the statistical rules (structural forms) of tasks.

We designed an associative-learning task (Figure 3A and 3B, similar to the task in (Mark *et al.* 2020)) where participants learned pairwise associations between images. The images can be thought of as nodes in a graph (unseen by participants), where the existence of an edge between nodes translates to an association between their corresponding images (Figure 3A). There were two kinds of statistical regularities governing graph structures: a hexagonal/triangular structural form and a community structure. There were also two mutually exclusive image sets that could be used as nodes for a graph, meaning that each structural form had two different graphs with different image sets, resulting in a total of four graphs per participant. Importantly, two graphs of the same structural form were also of different sizes (36 and 42 nodes for the hexagonal structure; 35 and 42 nodes for the community structure - 5 or 6 communities of 7 nodes per community, respectively), meaning states could not be aligned even between graphs of the same structural form. The pairs of graphs with the (approximately) same sizes across structural forms used the same visual stimuli set (Figure 3B). This design allowed us to test for subspace generalisation

between tasks with the same underlying statistical regularities, controlling for the tasks'
stimuli and size.

Participants were trained on the graphs for four days and graph knowledge was assessed in
each of the days using a battery of tests described previously (Mark et al. 2020 and
methods). Some tests probed knowledge of pairwise (neighboring) associations (Figure 3C-
D) and others probed "a sense of direction" in the graph, beyond the learned pairwise
associations of neighboring nodes (Figure 3 E-F). In all tests, the performance of participants
improved with learning and was significantly better than chance by the end of training
(Figure 3 C-F), suggesting that participants were able to learn the graphs and developed a
sense of direction even though they were never exposed to the graphs beyond pairwise
neighbors. Note that while all participants performed well on tests of neighboring
associations, the variance across participants for tests of non-neighboring nodes was high,
with some participants performing almost perfectly and others close to chance (compare
panels C-D to panels E-F). At the end of the training days, we asked participants whether
they noticed how the images are associated with each other, 26 out of 28 participants
recognized that in two sets, the pictures were grouped.

Figure 3. Experimental design and behavior. A. Example of an associative graph. Participants were never exposed to this top-down view of the graph - they learned the graph by viewing a series of pairs of neighboring images, corresponding to a walk on the graph. To aid memorisation, we asked participants to internally invent stories that connect the images. **B.** Each participant learned 4 graphs: two with a hexagonal lattice structure (both learned on days 1 and 2) and two with a community structure (both learned on days 3 and 4). For each structural form, there was one larger graph and one smaller graph. The nodes of graphs with approximately the same size were drawn from the same set of images.

C-F. In each day of training we used four tests to probe the knowledge of the graphs, as well
as to promote further learning. In all tests, participants performed above chance level on all
days and improved their performance between the first and second days of learning a
graph. **C.** Participants were asked whether an image X can appear between images Y and Z
(one sided t-test against chance level (50%): hex day1 $t(27) = 31.2$, $p < 10^{-22}$; hex day2
$t(27) = 35.5$, $p < 10^{-23}$; comm day3 $t(27) = 26.9$, $p < 10^{-20}$; comm day4 $t(27) = 34.2$, $p <$
10^{-23} ; paired one sided t-test between first and second day for each structural form: hex
$t(27) = 4.78$, $p < 10^{-5}$; comm $t(27) = 3.49$, $p < 10^{-3}$). **D.** Participants were shown two 3-
long image sequences, and were asked whether a target image can be the fourth image in
the first, second or both of the sequences (one sided t-test against chance level (33.33%):
hex day1 $t(27) = 39.9$, $p < 10^{-25}$; hex day2 $t(27) = 42.3$, $p < 10^{-25}$; comm day3 $t(27) =$
44.8 , $p < 10^{-26}$; comm day4 $t(27) = 44.2$, $p < 10^{-26}$; paired one sided t-test between
first and second day for each structural form: hex $t(27) = 3.97$, $p < 10^{-3}$; comm $t(27) = 2.81$
, $p < 10^{-2}$). **E.** Participants were asked whether an image X is closer to image Y or image Z, Y
and Z are not neighbors of X on the graph (one sided t-test against chance level (50%): hex
day1 $t(27) = 12.6$, $p < 10^{-12}$; hex day2 $t(27) = 12.5$, $p < 10^{-12}$; comm day3 $t(27) = 5.06$,
$p < 10^{-4}$; comm day4 $t(27) = 7.42$, $p < 10^{-07}$; paired one sided t-test between first and
second day for each structural form: hex $t(27) = 3.44$, $p < 10^{-3}$; comm $t(27) = 2.88$, $p <$
10^{-2}). **F.** Participants were asked to navigate from a start image X to a target image Y. In
each step, the participant had to choose between two (randomly selected) neighbors of the
current image. The participant repeatedly made these choices until they arrived at the
target image (paired one sided t-test between number of steps taken to reach the target in
first and second day for each structural form. Left: trials with initial distance of 2 edges
between start and target images: hex $t(27) = 2.57$, $p < 10^{-2}$; comm $t(27) = 2.41$, $p < 10^{-2}$;
MIddle: initial distance of 3 edges: hex $t(27) = 2.58$, $p < 10^{-2}$; comm $t(27) = 4.67$, $p < 10^{-}$
2; Right: trials with initial distance of 4 edges: hex $t(27) = 3.02$, $p < 10^{-2}$; comm $t(27) = 3.69$
, $p < 10^{-3}$). Note that while feedback was given for the local tests in panels C and D, no
feedback was given for the tests in panels E-F to ensure that participants were not directly
exposed to any non-local relations. The location of different options on the screen was
randomised for all tests. Hex: hexagonal lattice graphs. Comm: community structure graphs.

FMRI task and analysis

On the fifth day participants performed a task in the fMRI scanner. Each block of the scan
included one of the four graphs the participant has learned and started with a self-paced
image-by-image random walk on the graph to allow inference of the currently relevant
graph (Figure 4a, data not used in this manuscript). The second part of the block had two
crucial differences. First, images were arranged into sequences of 3 images that were
presented in rapid succession, corresponding to a walk of length 3 on the graph (Figure 4b
and Figure S5 for the partitioning the graphs into 3 images sequences). The time between

two successive sequences was 800ms (Figure 4c). Second, while the order within each 3-
images sequence was dictated by the graph, the order across the sequences was pseudo-
random. We needed this second manipulation to ensure coverage of the graph in every
block and to eliminate the possibility of spurious temporal correlations between
neighboring sequences. However, if we had presented images individually in this random
order, graphs with the same stimuli set would have been identical, making it difficult for
subjects to maintain a representation of the current graph across the block. Whilst the
images were the same across 2 graphs, the sequences of neighboring images uniquely
identified each graph, inducing a sensation of "moving" through the graph. To encourage
attention to the neighborhood of the sequence in the graph, in 12.5% of trials the sequence
was followed by a single image ("catch trial" in Figure 4c), and participants had to indicate
whether it was associated with the last image in the sequence (Figure 4c). Participants
answered these questions significantly better than chance (Figure S6), indicating that they
indeed recognize the correct graph and maintain the correct representation during the
block (t-test, p<<0.001 for both structures, $t[27]_{hex}$=11.3, $t[27]_{comm}$=10.6). At the end of
each block participants were asked whether they recognised which images set they
currently observed (see Method and supplementary for more details). Participants
answered these questions significantly better than chance (t-test, p<0.001 for both
structures, $t[27]_{hex}$ = 3.8, $t[27]_{comm}$ = 9.96, see supplementary Figure S6), again indicating
that they correctly recognised the current graph in the scanner.

To analyze this data, we used the subspace generalisation method as described for the
rodent data but replacing the firing of neurons at different spatial locations with the activity
of fMRI voxels for different 3-images sequences. To do this, we first performed a voxelwise
GLM where each regressor modeled all appearances of a particular 3-images sequence in a
given run, together with several nuisance regressors (see Methods). This gave us the activity
of each voxel for each sequence. For each voxel, in each run, we extracted the 100 nearest
voxels and formed a matrix of sequence X voxels. These are analogous to the data matrices,
B, in equation 1. We then computed subspace generalisation using the eigenvectors of the
voxel X voxel covariance matrix instead of the cell X cell covariance matrix (Figure 4d).

We then employed a leave-one-out cross-validation by repeatedly averaging the activation
matrices from three runs of graph X, calculating the eigenvectors from this average
representation, and then projecting the activation matrix of the held out run of control
graph X (or a test graph Y) on these eigenvectors. This ensures that the "eigenvector" and
"data" graphs are always from different runs. We then calculated the subspace
generalisation between each pair of graphs resulting in a 4x4 matrix at each voxel of the
brain (Figure 4d).

We refer to the elements of this 4x4 matrix in the following notation: we denote by H/C
graphs of either hexagonal or community structure, and by s/l either small or large stimuli
sets (matched across graphs of different structures). For example, HsCs denotes the

element of the matrix corresponding to activity from the small hexagonal graph projected on eigenvectors calculated from the small (same image-set) community-structure graph.

Figure 4. fMRI experiment and analysis method (subspace generalisation)

a. Each fMRI block starts with 70s of random walk on the graph: a pair of pictures appears on the screen, each time a participant presses enter a new picture appears on the screen and the previous picture appears behind (similar to the three pictures sequence, sell below). During this phase participants are instructed to infer which

464    "pictures set" (i.e graph) they are currently playing with. Note that fMRI data from
465    this phase of the task is not included in the current manuscript.
466   b. The three pictures sequence: three pictures appear one after the other, while
467    previous picture/s still appear on the screen.
468   c. Each block starts with the random walk (panel a). Following the random walk,
469    sequences of three pictures appear on the screen. Every few sequences there was a
470    catch trial in which we ask participants to determine whether the questioned picture
471    can appear next on the sequence.
472   d. Subspace generalisation method on fMRI voxels. Each searchlight extracts a beta X
473    voxels' coefficients (of 3-images sequences) matrix for each graph in each run
474    (therefore, there are four such matrices). Then, using cross-validation across runs,
475    the left out run matrix of one graph is projected on the EVs from the (average of 3
476    runs of the) other graph. Following the projections, we calculate the cumulative
477    percentage of variance explained and the area under this curve for each pair of
478    graphs. This leads to a 4 X 4 subspace generalization matrix that is then being
479    averaged over the four runs (see main text and methods for more details). The colors
480    of this matrix indicate our original hypothesis for the study: that in EC, graphs with
481    the same structure would have larger (brighter) AUCs than graphs with different
482    structures (darker).

484 **Testing subspace generalisation on visual representations**

485 To verify our analysis approach is indeed valid when used on our fMRI data, we first tested it
486 on the heavily studied object encoding representations in lateral occipital cortex (LOC,
487 Malach 1995 PNAS, Grill-Spector). Recall that our stimuli in the scanner were concurrently
488 presented sequences of three images of objects. We reasoned that these repeated
489 sequences would induce correlations between object representations that should be
490 observable in the fMRI data and detectable by our method. This would allow us to identify
491 visual representations of the objects without ever specifying when the stimuli (i.e. 3-images
492 sequences) were presented.

493 To this end we compared subspace generalization computed between different runs that
494 included the same stimuli (3-images sequences, with different order across sequences
495 between runs) with subspace generalization computed between runs of different stimuli
496 while controlling for the graph structure. This led to the contrast [HlHl + ClCl + HsHs +CsCs] -
497 [HlHs + HsHl + ClCs + CsCl], which had a significant effect in LOC (Figure 5a , peak MNI [-44,-
498 86,-8], $t(27)\_peak$ = 4.96, P_tfce < 0.05 based on a FWE-corrected nonparametric
499 permutation test, corrected in bilateral LOC mask (Harvard-Oxford atlas, Desikan 2006,
500 Neuroimage). In an additional exploratory analysis, we tested the significance of the same
501 contrast in a whole-brain searchlight. While this analysis did not reach significance once
502 corrected for multiple comparisons, the strongest effect was found in LOC (Figure 5a). Note
503 that in this contrast we intentionally ignored the elements of the 4x4 matrix where the data
504 and the eigenvectors came from graphs with the same images set and a different structure

505 (HlCl, HsCs, ClHl, CsHs), because they did not share the exact same visual stimuli (the 3-
506 images sequence). In these cases, we did not have a hypothesis about the subspace
507 generalization in LOC. These results suggest that we can detect the correlation structure
508 induced by stimuli without specifying when each stimulus was presented.

EC generalizes a low-dimensional representation across hexagonal graphs of different stimuli and sizes

Having established that the subspace generalization method can detect meaningful
correlations between fMRI voxels, we next aimed to test whether EC will represent the
statistical structure of abstract graphs with generalisable low-dimensional representations.
We first tested this for discretized 2D (hexagonal) graphs, using the community structure
graphs as controls: We tested whether the EC subspaces from hexagonal graphs blocks were
better aligned with the eigenvectors of other hexagonal blocks, than with the eigenvectors
from community graphs blocks, i.e. ([HlHl + HlHs + HsHl + HsHs] - [HlCl + HlCs + HsCl + HsCs],
Figure 5b). This contrast was significant in the right EC (peak MNI [28, -10, -40], $t(27)\_peak =$
4.2, $P\_tfce < 0.01$ based on a FWE-corrected nonparametric permutation test, corrected in a
bilateral EC mask (Figure 5b) (Julich atlas, Eickoff 2007). We obtained a null result for the
equivalent analysis for community structure graphs ([ClCl + ClCs + CsCl + CsCs] - [ClHl + ClHs
+ CsHl + CsHs]). This was particularly due to low subspace generalization across different
runs of the same community structure graphs (bottom two diagonal elements in Figure 5b
right, compare to our original hypothesis subspace generalization matrix in Figure 4d). See
the Discussion for possible interpretations of this null result.

To ensure the robustness of the hexagonal graphs result we next tested the same effect in
an orthogonal ROI from our previous study. In (Baram *et al.* 2021) we have shown that EC
generalises over different reinforcement learning tasks with the exact same structure. We
therefore tested the same effect in that ROI (all voxels in the green cluster in Figure 3d in
Baram 2021 et al., peak MNI: [25, -5, -28]), and indeed the [HlHl + HlHs + HsHl + HsHs] - [HlCl
+ HlCs + HsCl + HsCs] contrast was significant (one sided t-test, $t(27) = 3.6$, $p < 0.001$, Figure
5c).

Taken together, these results suggest that as in physical space, different abstract hexagonal
graphs are being represented on the same EC low-dimensional subspace. This is consistent
with a view where the same EC cell assembly represents both hexagonal graphs, and that
these cells covary together - even when the underlying size of the graph is different.

Figure 5: subspace generalisation in visual and structural representations.

a. Subspace generalisation of visual representations in LOC. Left: difference in subspace generalization was computed between different blocks that included the same stimuli with subspace generalization computed between blocks of different stimuli while controlling for the graph structure, i.e [HlHl + ClCl + HsHs +CsCs] - [HlHs + HsHl + ClCs + CsCl]. t(27)_peak = 4.96, P_tfce < 0.05 over LOC. Right: visualization of the subspace generalisation matrix (averaged over all LOC voxels with t>2 for the [HlHl + ClCl + HsHs +CsCs] - [HlHs + HsHl + ClCs + CsCl] contrast, i.e. green minus red entries.

b. EC generalises over the structure of hexagonal graphs. Left: the effect for the contrast [HlHl + HlHs + HsHl + HsHs] - [HlCl + HlCs + HsCl + HsCs], i.e. the difference between subspace generalisation of hexagonal graphs data, when projected on eigenvectors calculated from (cross-validated) hexagonal graphs (green elements in right panel) vs community structure graphs (red elements). t(27)_peak = 4.2, P_tfce <0.01 over EC. Right: Same as in a. right but for the [HlHl + HlHs + HsHl + HsHs] - [HlCl + HlCs + HsCl + HsCs] contrast in EC.

c. The average effect in an ROI from Baram et al. (green cluster in figure 3d of Baram et al.) for each participant. Star denotes the mean, error bars are SEM.

Discussion

The contributions of this manuscript are two-fold: first, we show that EC representations generalize over hexagonal abstract graphs of different sizes, highlighting the importance of the statistical properties of the environment to generalization. This expands our previous work (both experimental (Baram *et al.* 2021) and theoretical (Whittington *et al.* 2020)), suggesting EC plays an important role in generalization over abstract tasks, to the case where the tasks are governed by the same statistical rules but are not governed by the exact underlying graph (transition structure). This view builds on the known generalization properties of EC in physical space (Fyhn *et al.* 2007; Gardner *et al.* 2022) and on recent literature highlighting parallels between medial temporal lobe representations in spatial and non-spatial environments (Behrens *et al.* 2018; Whittington *et al.* 2022). Second, we present an fMRI analysis method ("subspace generalization"), adapted from related work in electrophysiology analysis (Samborska *et al.* 2022), to quantify generalization in cases where a mapping between states across environments is not available (though see (Hahamy and Behrens 2019) for our previous fMRI application of this method in the visual domain).

Exploiting previous knowledge while making decisions in new environments is a hard challenge that humans and animals face regularly. To enable generalization from loosely related previous experiences, knowledge should be represented in an abstract and flexible manner that does not depend on the particularities of the current task. Understanding the brain's solution to this computational problem requires a definition of a "generalisable representation", and a way of quantifying it. Here, we define generalization as sharing of neuronal manifold across representations of related tasks. The particular assumption here is that in the EC, such manifolds encode the relevant information about the particular structural form of the task.

An example of such generalization has previously been observed in the spatial domain, in grid cells recordings across different physical environments, regardless of shape or size (Fyhn *et al.* 2007; Gardner *et al.* 2022). This was usually done through direct comparison of the pairwise activity patterns of cells (Fyhn *et al.* 2007; Yoon *et al.* 2013; Gardner *et al.* 2022). However, this is not possible to do in fMRI, rendering the examination of EC generalization in complex abstract tasks difficult. "Subspace generalization" relies on the idea that similarity in activity patterns across tasks implies similarity of the within-task correlations between neurons. These are summarized in the similarity between the (low dimensional) linear subspaces where the activity of the neurons/voxels representing the two tasks lies. For fMRI purposes, this similarity between within-task neuronal correlations should be reflected in the similarity between within-task correlations across voxels, as long as the relevant neurons anatomically reside across a large enough number of voxels. Importantly, comparing similarity in neuronal correlations structures rather than similarity in states representations patterns (as in RSA) allows us to examine flexible knowledge representations when a mapping between states in the two tasks does not exist. We present three validations of this method: in cells, we show it captures all expected properties of grid and place cells, even if we reduce the data resolution by averaging over the activity of group of cells. In simulation, we show that calculating subspace generalization

using simulated voxels from simulated grid cells results in significant generalization effect
under realistic condition. In fMRI, we show it captures the expected correlations induced by
the visual properties of a task in LOC.

Our main finding of subspace generalization in EC across hexagonal graphs with different
sizes and stimuli significantly strengthens the suggestion that EC flexibly represents all
'spatial- like' tasks, such as discretized 2D hexagonal graphs. Recently, we presented a
theoretical framework for this idea: a neural network trained to predict future states, that
when trained on 2D graphs displayed known spatial EC representations (the Tolman
Eichenbaum Machine (TEM) (Whittington *et al.* 2020)). However, 'spatial-like' structures are
not the only prevalent structures in natural tasks. The relations between task states often
follow other structural forms (such as periodicities, hierarchies or community structures),
inference of which can aid behavior (Mark *et al.* 2020). Representations of non-Euclidian
task structures have been found in EC (Garvert, Dolan and Behrens 2017; Baram *et al.* 2021)
and these generalize over different reinforcement learning tasks that are exactly the same
except for their sensory properties (Baram *et al.* 2021). Indeed, when TEM was trained on
non-Euclidean structures like hierarchical trees, it learned representations that were
generalisable to novel environments with the same structure (Whittington *et al.* 2020).
Further, we have previously shown that representing each family of graphs of the same
structural form with the relevant stable representation (i.e. basis set) allows flexible transfer
of the graph structure and therefore inference of unobserved transitions (relations between
task's states) (Mark *et al.* 2020). Together these studies suggest that flexible representation
of structural knowledge may be encoded in the EC.

Based on these, we hypothesized that EC representations will also generalize over non-
'spatial-like' tasks (here, community-structure) of different sizes. However, we could not
find conclusive evidence for such a representation: the relevant contrast ([ClCl + ClCs + CsCl
+ CsCs] - [ClHl + ClHs + CsHl + CsHs]) did not yield a statistically significant effect in EC (or
elsewhere, in an exploratory analysis corrected across the whole brain). This is despite clear
behavioral evidence that participants use the community structure of the graph to inform
their behavior: participants have a strong tendency to choose to move to the connecting
nodes (nodes that connect two different communities) over non-connecting nodes ((Mark *et*
al. 2020), and Figure S4a). Moreover, in the post-experiment debriefing, participants could
verbally describe the community structure of the graphs (26 out of 28 participants). This was
not true for the hexagonal graphs. Why, then, did we not detect any neural generalization
signals for the community structure graphs? There are both technical and psychological
differences between the community structure and the hexagonal graphs that might have
contributed to the difference in the results between the two structures. First, we have
chosen a particular nested structure in which communities are organized on a ring.
Subspace generalisation may not be suitable for the detection of community structure: for
example, a useful generalisable representation of such structure is composed of a binary
'within-community nodes' vs 'connecting nodes' representation. If this is the representation
used by the brain, it means all "community-encoding" voxels are similarly active in response
to all stimuli (as all 3-images sequences contain at least two non-connecting node images),

and only "connecting nodes encoding" voxels change their activation during stimuli
presentation. Therefore, there is very little variance to detect.

Though this manuscript has focused on EC, it is worth noting that there is evidence for
structural representations in other brain areas. Perhaps the most prominent of these is
mPFC, where structural representations have been found in many contexts (Klein-Flügge *et*
al. 2019; Baram *et al.* 2021; Klein-Flügge, Bongioanni and Rushworth 2022). Indeed, the
strongest grid-like signals in abstract 2D tasks are often found in mPFC (Constantinescu,
O'Reilly and Behrens 2016; Bao *et al.* 2019; Park *et al.* 2020; Bongioanni *et al.* 2021) and task
structure representations have been suggested to reside in mOFC (Wilson *et al.* 2014;
Schuck *et al.* 2016; Xie and Padoa-Schioppa 2016). The difference and interaction between
PFC and MTL representations is a very active topic of research. One such suggested
dissociation that might be of relevance here is the preferential contribution of MTL and PFC
to latent and explicit learning, respectively. A related way of discussing this dissociation is to
think of mPFC signals as closer to the deliberate actions subjects are taking. Circumstantial
evidence from previous studies in our lab (tentatively) suggest the existence of such
dissociation also for structural representations: when participants learnt a graph structure
without any awareness of it, this structure was represented in MTL but not mPFC (Garvert,
Dolan and Behrens 2017). On the other hand, when participants had to navigate on a 2D
abstract graph to locations they were able to articulate, we observed much stronger grid-
like signals in mPFC than MTL (though a signal in EC was also observed,(Constantinescu,
O'Reilly and Behrens 2016)). In addition, Baram et al. found that while the abstract structure
of a reinforcement learning task was represented in EC, the structure-informed learning
signals that inform trial-by-trial behavior with generalisable information were found in
mPFC. Taken together, these results suggest that here, it is reasonable to expect
generalisation signals of community structure graphs (of which participants were aware) in
PFC, as well as the signals reported in EC for hexagonal graphs (of which participants were
unaware). Indeed, when we tested for subspace generalisation of community structure
graphs in the same ROI in vmPFC where Baram et al. found generalisable learning signals,
we obtained a significant result (though this is a weak effect, and we hence report it with
caution in the supplementary material, Figure S4b).

To summarize, we have extended the understanding of EC representations and showed that
EC represents hexagonal graph structures of different sizes, similarly to grid cells
representation of spatial environments. We did this by using an analysis method which we
believe will prove useful for the study of generalisable representations in different neural
recording modalities. More work is needed to verify whether this principle of EC
representations extends to other, non-''spatial-like' structural forms.

Methods

Rodent cells analysis

Cells electrophysiology data were taken from (Chen *et al.* 2018). In short, cells (place cells from CA1
and grid cells from dmEC) were recorded while the animals foraged in two different square arenas;
one real arena and one virtual reality (VR) arena, real arena is 60x60 and the VR arena is 60x60 or
90x90 cm. The VR system restrained head-movements to horizontal rotations, and included an air-
suspended ball on which the mice could run and turn. A virtual environment reflecting the mouse's
movements on the ball was projected on screens in all horizontal directions and on the floor. Mice
were implanted with custom-made microdrives (Axona, UK), loaded with 17mm platinum-iridium
tetrodes, and providing buffer amplification. We analyzed grid cells data from three animals; two
animals had only grid cells data and one animal had both place cells and grid cells data. We analyzed
place cells data from three more animals that had only place cells data (mouse 1 had 14 grid cells,
mouse 2 and 3 had 21 grid cells, mouse 1, 4, 5 had 25 place cells). This experimental design results in
two different firing rate maps, one for each arena. After preprocessing (calculate the firing rate map
using on 64X64 bins matrix and smoothing of the firing rate maps with 5 bins boxcar), we calculated
the 'subspace generalisation' score, as follows:

          a. Calculate the neuron X neuron correlation matrix from the first firing rate map (one
694 695   of the environments) and its principal components (PCs).
696   b. Project the firing rate maps from this environment and the other environment on
697   these PCs.
698   c. Calculate the cumulative variance explained as a function of PCs (that are organized
699   according to their corresponding eigenvalues)
d. Calculate the area under the curve (AUC).

*Permutation tes*t 1 (within cell type): Our hypothesis is that the neuron X neuron correlation
structure is preserved while the animals forage in the two different arenas, i.e. that the active cells'
assemblies remain the same. Therefore, the null hypothesis is that the cells' assemblies are random
and did not remain the same while animals forage in the two arenas. We therefore calculated the
eigenvectors (EV) using the firing rate map while the animal foraged in one environment and
permuted the cells' identity of the firing rate maps correspond to the second environment. We then
calculated the difference between the 'subspace generalisation' score within and across
environments. This creates our null distribution, which we compare to the subspace generalisation
score of the non-permuted data.

permutation test 2 (between cell types): Our hypothesis is that grid cells generalise better than place
cells, i.e. that the difference between the AUC of within arena projection to across arenas projection
is smaller in grid cells compared to place cells. To this end, we created AUC-differences distribution
using place cells activity as our null distribution; we sample place cells from each animal, such that
the number of grid cells and place cells was equal (mouse 1 had 14 grid cells, mouse 2 and 3 had 21
grid cells, mouse 1, 4, 5 had 25 place cells). Then, for each sample, we calculated the difference in
AUC (same arena - different arenas), as before. We calculated the distribution of these AUC-
differences values from all three animals. We then checked whether the AUC-differences in grid
cells, for all three animals, is significantly smaller than those predicted by the sampled place cells
distribution (Figure S1).

<u>Reducing the resolution of the electrophysiological data</u>

We first normalized all firing rate maps. Then, for each animal we randomly sampled (with repeats)
seven cells into two groups and averaged the cells' activity within each group, separately for each
environment. We then concatenated the resulted size-2 vectors from all animals into one vector and
used this vector as above to calculate the AUC differences between within and across environments.
The number of bootstraps was 400, therefore we had 800 repetitions to calculate the distribution
(for each sample we project on both environments therefore getting two AUC - difference values).
The plots in Figure.1d were smoothed with smoothing window of 9, the number of bins to calculate
the distribution was 50.

Simulating pseudo voxels

Grid cells are simulated as a thresholded sum of three 2D cosines (Burgess et al. 2007). Each module
is simulated by shifting the grid cells within a grid that spans the rhombus of the hexagonal grid,
such that the average over all grid cells within a module is a constant across the box (note that due
to numerical issues this is almost constant).
We simulated 13456 cells per module (116*116 in the x-y plane, i.e. covering the grid's rhombus).
The box is simulated with 50*50 resolution (the size of the "box" is 10*10). We simulated four
different modules that differ in their grid spacing and phases. Each environment was simulated by a
different phase and shift of the grid fields such that the relationships between the cells remain the
same across environments.
Voxels were simulated by averaging cells within a module. Each module was segregated into four
groups of cells (therefore there are 3364 cells within each voxel, see supplementary for different
segregations). Each voxel is an average over the cells' firing rate map within the group. The
averaging was done in two stages:
a.   sampling grid cells randomly - i.e. not related to their grid phase
b.   The remaining cells were segregated into four groups according to their phase.
The above process was repeated for different fractions of random/(according to phase) ratio
(*ratio_random* = [0,1], 0: only segregated according to phase, 1: only segregated randomly). We
further added spatial white noise to each voxel, noise std ranging from 0 to 0.1.
748

FMRI experiment

Participants: 60 UCL students were originally recruited. As the training is long and hard, for each scan
we recruited two participants for the training sessions, and chose the better performing of the two
to be scanned. Overall, we scanned 34 participants and excluded 6 participants from the analysis
because of severe movement or sleepiness in the scanner.
The study was approved by the University College London Research Ethics Committee (Project ID
11235/001). Participants gave written informed consent before the experiment.
756

Behavioural training for fMRI training task

To ensure that participants understood the instructions, the first training day was performed in the
lab while the other three training days were performed from the participant's home.

Graphs. One hexagonal graph consisted of 36 nodes and the other 42 nodes as shown in Figure 3b.
One community structured graph consisted of 5 communities and the other 6 communities, with 7
nodes each. Within a community, each node was connected to all other nodes except for the two
connecting nodes that were not connected to each other but were each connected to a connecting

node of a neighboring community (Figure 3b). Therefore, all nodes had a degree of six, similarly to
the hexagonal graphs (except the nodes on the hexagonal graphs border, which had degree less than
six). Our community structure graph had a hierarchical structure, wherein communities were
organized on a ring.
768
Training procedures. In each of the training days, participants learned two graphs with the same
underlying structure but different stimuli. During the first two days participants learned the
hexagonal graphs, while during the third and fourth days participants learned the community
structured graphs. During the fifth day, before the fMRI scan, participants were reminded of all four
graphs, with two repetitions of each hexagonal graph and one repetition of each community
structured graph. Stimuli were selected randomly, for each participant, from a bank of stimuli (each
pair of graphs, one hexagonal and one of a community structured graph shared the same bank).
Each graph was learnt during four blocks (Figure. 3b; 4 blocks for graph 1 followed by 4 blocks for
graph 2 in each training day). Participants could take short resting breaks during the blocks. They
were instructed to take a longer resting break after completing the four blocks of the first graph of
each learning day.
780
Block structure. Each block during training was made of the following tasks: 1) Learning phase 2)
Extending pictures sequences 3) Can it be in the middle 4) Navigation 5) Distance estimation (see
Figure 3). Next, we elaborate the various components of each block.
Learning phase (Figure 3a): Participants learned associations between graph nodes by observing a
sequence of pairs of pictures which were sampled from a random walk on the graph (successive
pairs of pictures shared a common picture). Participants were instructed to 'say something in their
head' in order to remember the associations. Hexagonal graphs included 120 steps of the random
walk per block and community-structured graphs included 180 steps per block (we introduced more
pictures in the community graph condition as random walks on such graphs result in high sampling
of transitions within a certain community and low sampling of transitions between communities).
Extending pictures sequences (Figure 3d): Given a target picture, which of two sequences of three
pictures can be extended by that picture (a sequence can be extended by a picture only if it is a
neighbor of the last picture in the sequence, the correct answer can be sequence 1/sequence 2/both
sequences): Sixteen questions per block. (note that a picture could not appear twice in the same
sequence, i.e. if the target picture is already in the sequence the correct answer was necessarily the
other sequence).
Can it be in the middle (Figure 3c): Determine whether a picture can appear between two other
pictures, the answer is yes if and only if the picture is a neighbor of the two other pictures. Sixteen
questions per block.
Navigation (Figure 3e): The aim—navigate to a target picture (appears at the right of the screen).
The task was explained as a card game. Participants are informed that they currently have the card
of the picture that appears on the left of the screen. They were asked to choose between two
pictures that are associated with their current picture. They could also skip and sample again two
pictures that are associated with the current picture, if they thought their two current options did
not get them closer to the target (skipping was counted as a step). In each step participants were
instructed to choose a picture that they thought had a smaller number of steps to the target picture
(according to their memory). Following choice, the chosen picture appeared on the left and two new

pictures, that correspond to states that are neighbors of the chosen picture, appear as new choices.
After a participant selected a neighbor of the target picture, that target picture itself could appear as
one of the new options for choice. The game terminated when either the target was reached or 200
steps were taken (without reaching the target). In the latter case a message 'too many steps' was
displayed. On the first block, for each step, the number of links from the current picture to the target
picture was shown on the screen. Participants played three games (i.e. navigation until the target
was reached or 200 steps passed) in each block, where the starting distance (number of links)
between the starting picture to the target was 2, 3 and 4.
<u>Distance estimation:</u> Which of two pictures has the smallest number of steps to a target picture: 45
questions per block (none of the 2 pictures was a direct neighbor on the graph, i.e. the minimal
distance was 2 and no feedback was given).
819
fMRI scanning task
The task consisted of four runs. Each run was divided into five blocks (one block for each graph and
one more repetition for one of the hexagonal graphs; the repetition was not used in the analyses in
this manuscript). On each block participants observed pictures that belong to one of the graphs. A
block started with 70sec in which participants observed, at their own pace, a random walk on the
graph; two neighboring pictures appeared on the screen and when participants pressed 'enter' a
new picture appeared on the screen (similar to the training learning phase). The new picture
appeared in the middle of the screen and the old picture appeared on its left. Participants were
instructed to infer which 'pictures set' they are currently observing. No information about the graph
was given. This random walk phase was not used in any analyses in this manuscript.
830
Next, sequences of three pictures appeared on the screen, one after the other (note the first and
second pictures did not disappear from the screen until after the third picture in the sequence was
presented - all three pictures disappeared together, prior to the next trial, Figure 4b). To keep
participants engaged, once in a while (5 out of 45 sequences) a fourth picture appeared and
participants had to indicate whether this picture can appear next on the sequence ('catch trials',
Figure 4c). Before starting the fMRI scan participants were asked whether they found any
differences between the picture sets during the first two days (when the hexagonal graphs were
learnt) and the last two days (when the community graphs were learnt). Most participants (26 out of
28) could indicate that there were groups of pictures (i.e. communities) in the last two days, and that
this was not the case during the first two days. At the end of each block in the scanner participants
answered whether or not there are groups in the current picture set (participants that were not
aware of the groups were asked whether this set belongs to the first two training days or not).
Participants were given a bonus for answering correctly, such that 100% correct results in a ten
pounds bonus.
845
fMRI data acquisition
FMRI data was acquired on a 3T Siemens Prisma scanner using a 32 channels head coil. Functional
scans were collected using a T2*-weighted echo-planar imaging (EPI) sequence with a multi-band
acceleration factor of 4 (TR = 1.450 s, TE = 35ms, flip angle = 70 degrees, voxel resolution of 2x2x2mm).
A field map with dual echo-time images (TE1 = 10ms, TE2 = 12.46ms, whole-brain coverage, voxel size
2x2x2mm) was acquired to correct for geometric distortions due to susceptibility-induced field

inhomogeneities. Structural scans were acquired using a T1-weighted MPRAGE sequence with
1x1x1mm voxel resolution. We discarded the first six volumes to allow for scanner equilibration.

Pre-processing

Pre-processing was performed using tools from the fMRI Expert Analysis Tool (FEAT, Woolrich MW
et al. 2001; Woolrich MW et al. 2004), part of FMRIB's Software Library (FSL, Smith et al. 2004). Data
from each of the four scanner runs was preprocessed separately. Each run was aligned to a
reference image using the motion correction tool MCFLIRT. Brain extraction was performed using
the automated brain extraction tool BET (Smith, 2002). All data were temporally high-pass filtered
with a cut-off of 100s. Registration of EPI images to high-resolution structural images and to
standard (MNI) space was performed using FMRIB's Linear Registration Tool (FLIRT (Jenkinson et al.,
2002; Jenkinson and Smith, 2001)). No spatial smoothing was performed during pre-processing (see
below for different smoothing protocols for each analysis). Because of the notable breathing- and
susceptibility-related artifacts in the entorhinal cortex, we cleaned the data with FMRIB's ICA tool,
FIX (Griffanti *et al.* 2014; Salimi-Khorshidi *et al.* 2014).

Univariate analysis

Due to incompatibility of FSL with the MATLAB RSA toolbox (Nili *et al.* 2014) used in subsequent
analyses, we estimated all first-level GLMs and univariate group-level analyses using SPM12
(Wellcome Trust Centre for Neuroimaging, https://www.fil.ion.ucl.ac. uk/spm).

For estimating subspace generalization, we constructed a GLM to estimate the activation as a result
of each three images' sequence (a 'pile' of pictures). The GLM includes the following regressors:
mean CSF regressor and 6 motion parameters as nuisance regressors, bias term modeling the mean
activity in each fMRI run, a regressor for the 'start' message (as a delta function), a regressor for the
self- paced random walk on each graph (a delta function for each new picture that appears on the
screen), a regressor for each pile in each graph (duration of a pile: 1.4sec), regressor for the catch
trial onset (delta) and the pile that corresponds to the catch (pile duration). All regressors beside the
6 motion regressors and CSF regressor were convolved with the HRF. The GLM was calculated using
non-normalized data.

Multivariate analysis

Quantifying subspace generalization:

We calculated noise normalized GLM betas within each searchlight using the RSA toolbox. For each
searchlight and each graph, we had a nVoxels (100) by nPiles (10) activation matrix ($B_{voxel \times pile}$) that
describes the activation of a voxel as a result of a particular pile (three pictures' sequence). We
exploited this matrix to quantify the manifold alignment within each searchlight.

To account for fMRI auto-correlation we used Leave One Out (LOO) approach; For each fMRI scanner
run and graph, we calculated the mean activation matrix over the three others scanner runs ($\hat{B}^{\sim j}$).
We then calculated the left Principles Component (PCs) of that matrix ($U_{voxel \times voxel}^{\sim j}$). To quantify the
alignment, we projected the excluded scanner run graph activation matrix (B^j) of each graph on
these PCs and calculated the accumulated variance explained as a function of PCs, normalized by the
total variance of each graph within each run. Therefore, for each run and graph we calculated:

$$P^{a,b} = U_a^{\sim j} \cdot B_b^j$$

$$M_k^{a,b} = \frac{\sum_{l=1}^{10}\left(P_{a,b}^{l,k}\right)^2}{S^j}$$

$$\Sigma^j = U^{j^T} B^{j^T} B^j U^j$$

Where $P^{a,b}$ is the projection matrix of dimensions $voxel \times pile$ of graph 'b' on the PCs of graph 'a', $M_k^{a,b}$ is the normalized variance explained on the 'k' direction, S^j is the summation of the diagonal of Σ^j, the total variance as a result of the graph piles (three images sequence). We then calculated the cumulative variance explained over all 'k' PCs directions. As a summary statistic we calculated the area under this curve. This gives us a 4x4 alignment matrix, for each run, such that each entry (*a, b*) in this matrix is a measure of the alignment of voxels patterns as a result of the two graphs *a&b* *(Figure 4d)*. We then averaged over the four runs and calculated different contrasts over this matrix.

The above calculations were performed in subject space, we therefore normalized the searchlight results and then smoothed with a kernel of 6mm FWHM using FSL FLIRT and FNIRT before performing group level statistics.

For group level we calculated the t-stat over participants of each contrast:

Visual contrast was [HlHl + ClCl + HsHs +CsCs] - [HlHs + HsHl + ClCs + CsCl], i.e. same exact sequences controlled by the same structure.

Structural contrast was [HlHl + HlHs + HsHl + HsHs] - [HlCl + HlCs + HsCl + HsCs], i.e. the difference between subspace generalisation of hexagonal graphs data, when projected on eigenvectors calculated from (cross-validated) hexagonal graphs (yellow elements in middle panel) vs community structure graphs (red elements).

Multiple comparisons correction

Multiple comparison correction was performed using the permutation tests machinery (Nichols and Holmes 2002) in PALM (Winkler *et al.* 2014): within the mask we used for multiple comparisons correction (details in main text), we first measured the TFCE statistic for the current contrast. We then repeated this procedure for each of the 10000 random sign-flip iterations (each participant's contrast sign was randomly flipped and the statistic over participants was calculated). Using these values we then created a null distribution of TFCE statistics by saving only the voxel with the highest TFCE in each iteration. Comparing the true TFCE to the resulting null distributions results in FWE-corrected TFCE P-values.

Author contributions

S.M and T.B conceive the research, S.M and P.S design and perform the experiment, S.M and A.B analyzed the data. A.H and V.S provided consultation with analysis. S.M, A.B and T.B wrote the manuscript.

Acknowledgements

T.B. is supported by a Wellcome Principal Research Fellowship (219525/Z/19/Z), a Wellcome Collaborator award (214314/Z/18/Z), a JS McDonnell Foundation award (JSMF220020372), and by the Jean Francois and Marie-Laure de Clermont Tonerre Foundation. The Wellcome Centre for Integrative

Neuroimaging and Wellcome Centre for Human Neuroimaging are each supported by core funding
from the Wellcome Trust (203139/Z/16/Z, 203147/Z/16/Z). The Sainsbury-Wellcome centre is
supported by core funding from the Wellcome Trust (219627/Z/19/Z) and the Gatsby Charitable
Foundation (GAT3755).

A.H. was supported by the European Molecular Biology Organization nonstipendiary Long-Term
Fellowship (848–2017), Human Frontier Science Program (LT000444/2018), Israeli National
Postdoctoral Award Program for Advancing Women in Science, and the European Union's Horizon
2020 research and innovation programme under the Marie Skłodowska-Curie Grant Agreement No.
789040.

References

Bao X, Gjorgieva E, Shanahan LK *et al.* Grid-like Neural Representations Support Olfactory Navigation
of a Two-Dimensional Odor Space. *Neuron* 2019;**102**:1066-1075.e5.
Baram AB, Muller TH, Nili H *et al.* Entorhinal and ventromedial prefrontal cortices abstract and
generalize the structure of reinforcement learning problems. *Neuron* 2021;**109**:713–23.
Barron HC, Garvert MM, Behrens TE. Repetition suppression: a means to index neural
representations using BOLD? *Philos Trans R Soc B Biol Sci* 2016;**371**:20150355.
Behrens TE, Muller TH, Whittington JC *et al.* What is a cognitive map? Organizing knowledge for
flexible behavior. *Neuron* 2018;**100**:490–509.
Bongioanni A, Folloni D, Verhagen L *et al.* Activation and disruption of a neural mechanism for novel
choice in monkeys. *Nature* 2021;**591**:270–4.
Burak Y, Fiete IR. Accurate path integration in continuous attractor network models of grid cells.
PLoS Comput Biol 2009;**5**:e1000291.
Burgess N, Barry C, O'keefe J. An oscillatory interference model of grid cell firing. Hippocampus
2007; 801-812, 17(9).
Chen G, King JA, Lu Y *et al.* Spatial cell firing during virtual navigation of open arenas by head-
restrained mice. *Elife* 2018;**7**:e34789.
Constantinescu AO, O'Reilly JX, Behrens TE. Organizing conceptual knowledge in humans with a
gridlike code. *Science* 2016;**352**:1464–8.
Diedrichsen J, Kriegeskorte N. Representational models: A common framework for understanding
encoding, pattern-component, and representational-similarity analysis. *PLOS Comput Biol*
2017;**13**:e1005508.
Fyhn M, Hafting T, Treves A *et al.* Hippocampal remapping and grid realignment in entorhinal cortex.
Nature 2007;**446**:190–4.
Gardner RJ, Hermansen E, Pachitariu M *et al.* Toroidal topology of population activity in grid cells.
Nature 2022;**602**:123–8.
Gardner RJ, Lu L, Wernle T *et al.* Correlation structure of grid cells is preserved during sleep. *Nat
Neurosci* 2019;**22**:598–608.
Garvert MM, Dolan RJ, Behrens TE. A map of abstract relational knowledge in the human
hippocampal–entorhinal cortex. *elife* 2017;**6**:e17086.
Griffanti L, Salimi-Khorshidi G, Beckmann CF *et al.* ICA-based artefact removal and accelerated fMRI
acquisition for improved resting state network imaging. *NeuroImage* 2014;**95**:232–47.
Grill-Spector K, Henson R, Martin A. Repetition and the brain: neural models of stimulus-specific
effects. *Trends Cogn Sci* 2006;**10**:14–23.
Gu Yi, Lewallen S, Kinkhabwala A, Domnisoru C, Yoon K, Gauthier JL, Fiete IR, and Tank DW. Cell
2018; 175, 735-750.Hahamy A, Behrens TE. Measuring the spatial scale of brain
representations. *2019 Conference on Cognitive Computational Neuroscience*. 2019, 2019–
1174.
Haxby JV, Gobbini MI, Furey ML *et al.* Distributed and overlapping representations of faces and
objects in ventral temporal cortex. *Science* 2001;**293**:2425–30.

Kemp C, Tenenbaum JB. The discovery of structural form. *Proc Natl Acad Sci* 2008;**105**:10687–92.

Klein-Flügge MC, Bongioanni A, Rushworth MFS. Medial and orbital frontal cortex in decision-making
and flexible behavior. *Neuron* 2022;**110**:2743–70.

Klein-Flügge MC, Wittmann MK, Shpektor A *et al.* Multiple associative structures created by
reinforcement and incidental statistical learning mechanisms. *Nat Commun* 2019;**10**:4835.

Kriegeskorte N, Mur M, Bandettini P. Representational similarity analysis - connecting the branches
of systems neuroscience. *Front Syst Neurosci* 2008;**2**.

Mark S, Moran R, Parr T *et al.* Transferring structural knowledge across cognitive maps in humans
and models. *Nat Commun* 2020;**11**:4783.

Nichols TE, Holmes AP. Nonparametric permutation tests for functional neuroimaging: A primer with
examples. *Hum Brain Mapp* 2002;**15**:1–25.

Nili H, Wingfield C, Walther A *et al.* A Toolbox for Representational Similarity Analysis. *PLOS Comput
Biol* 2014;**10**:e1003553.

Park SA, Miller DS, Nili H *et al.* Map Making: Constructing, Combining, and Inferring on Abstract
Cognitive Maps. *Neuron* 2020;**107**:1226-1238.e8.

Salimi-Khorshidi G, Douaud G, Beckmann CF *et al.* Automatic denoising of functional MRI data:
Combining independent component analysis and hierarchical fusion of classifiers.
NeuroImage 2014;**90**:449–68.

Samborska V, Butler JL, Walton ME *et al.* Complementary task representations in hippocampus and
prefrontal cortex for generalizing the structure of problems. *Nat Neurosci* 2022;**25**:1314–26.

Schuck NW, Cai MB, Wilson RC *et al.* Human Orbitofrontal Cortex Represents a Cognitive Map of
State Space. *Neuron* 2016;**91**:1402–12.

Smith SM, Jenkinson M, Woolrich MW, Beckmann CF, Behrens TEJ, Johansen-Berg H, Bannister
PR, De Luca M, Drobnjak I, Flitney DE, Niazy RK, Saunders J, Vickers J, Zhang Y, De Stefano N, Brady
JM, Matthews PM. Advances in functional and structural MR image analysis and implementation as
FSL. NeuroImage 2004; 23: S208-S219.

Tolman EC. Cognitive maps in rats and men. *Psychol Rev* 1948;**55**:189–208.

Trettel SG, Trimper JB, Hwaun E, Fiete IR, Colgin LL. Grid cell co-activity patterns during sleep reflect
spatial overlap of grid fields during active behaviors. Nature Neuroscience 2019; 22: 609-617.

Waaga T, Agmon H, Normand VA *et al.* Grid-cell modules remain coordinated when neural activity is
dissociated from external sensory cues. *Neuron* 2022;**110**:1843-1856.e6.

Whittington JC, McCaffary D, Bakermans JJ *et al.* How to build a cognitive map. *Nat Neurosci*
2022;**25**:1257–72.

Whittington JC, Muller TH, Mark S *et al.* The Tolman-Eichenbaum machine: unifying space and
relational memory through generalization in the hippocampal formation. *Cell*
2020;**183**:1249–63.

Wilson RC, Takahashi YK, Schoenbaum G *et al.* Orbitofrontal Cortex as a Cognitive Map of Task
Space. *Neuron* 2014;**81**:267–79.

Winkler AM, Ridgway GR, Webster MA *et al.* Permutation inference for the general linear model.
NeuroImage 2014;**92**:381–97.

Woolrich M W, Ripley BD, Brady M, & Smith, SM. (2001). Temporal Autocorrelation in Univariate
Linear Modeling of FMRI Data. NeuroImage, 14(6), 1370–1386

Woolrich MW, Behrens TEJ, Beckmann CF, Jenkinson M, Smith SM. Multilevel linear
modelling for FMRI group analysis using Bayesian inference. NeuroImage 2004; 21:
1732-1747.

Xie J, Padoa-Schioppa C. Neuronal remapping and circuit persistence in economic decisions. *Nat
Neurosci* 2016;**19**:855–61.

Yoon K, Buice MA, Barry C *et al.* Specific evidence of low-dimensional continuous attractor dynamics
in grid cells. *Nat Neurosci* 2013;**16**:1077–84.