Medial temporal cortex supports compositional visual inferences

Tyler Bonnen,* Anthony D. Wagner, and Daniel L.K. Yamins

Stanford University

Perception unfolds across multiple timescales. For humans and other primates, many object-centric visual attributes can be inferred 'at a glance' (i.e., with <200ms of visual information), an ability supported by ventral temporal cortex (VTC). Other perceptual inferences require more time; to determine a novel object's identity, we might need to represent its unique configuration of visual features, requiring multiple 'glances.' Here we evaluate whether medial temporal cortex (MTC), downstream from VTC, supports object perception by integrating over such visuospatial sequences. We first compare human visual inferences directly to electrophysiological recordings from macaque VTC. While human performance 'at a glance' is approximated by a linear readout of VTC, participants radically outperform VTC given longer viewing times (i.e., >200ms). Next, we demonstrate the causal role of MTC in these temporally extended visual inferences: just as time restricted performance can be approximated by a linear readout of VTC, the performance of (time unrestricted) MTC-lesioned humans resembles a computational proxy for VTC. Finally, we characterize these visual abilities through a series of eyetracking experiments. With extended viewing times participants sequentially sample task-relevant features via multiple saccades—visuospatial patterns that are reliable across participants and necessary for performance. From these data, we suggest that MTC transforms visuospatial sequences into 'compositional' representations that support visual object perception.

1   Introduction

There is temporal structure in how we perceive the world. Many visual attributes can be inferred 'at a glance' (Potter, 1975). Given just 100ms of visual information, for example, humans and other primates can determine behaviorally relevant stimulus properties, such as object shape and category membership (Greene and Oliva, 2009; Potter and Levy, 1969). Ventral temporal cortex (VTC) supports these rapid visual inferences through successive, hierarchical transformations over retinal inputs (DiCarlo et al., 2012; Grill-Spector and Weiner, 2014). However, not all visual inferences are possible 'at a glance' (Findlay and Gilchrist, 2003; Henderson, 2003). This is due, in part, to biological constraints on the primate visual system (Van Essen and Anderson, 1990). High-acuity visual information is only maintained at the central visual field (i.e., the fovea) and, as a consequence, we shift the location of our gaze roughly three times per second as we attend to different visual features (Hirsch and Curcio, 1989; Liversedge and Findlay, 2000). It has been proposed that this gaze dependent strategy enables us to 'compose' flexible representations of objects using a finite set of visual representations (Ullman, 1987). While a great deal is known about visual information processing within the first 200ms of stimulus onset, less is known about the neural substrates that enable us to integrate across visuospatial sequences.

Neuroanatomical structures within medial temporal cortex (MTC) may play a critical role in visual inferences that rely on sequential integration. These structures, such as perirhinal cortex (PRC), are situated at the apex of VTC (Suzuki and Amaral, 2004) and receive input from high-level visual cortex (Fig. 1, top). Decades of lesion studies in humans and monkeys have demonstrated that MTC enables visual inferences not supported by VTC alone (e.g., Barense et al., 2007; Bussey and Saksida, 2002; Lee et al., 2005; Murray and Bussey, 1999). Theoretical (Murray and Wise, 2012) and computational (Cowell, 2012) accounts of MTC function have centered on the anatomical relationship between MTC and VTC (i.e., 'representational-hierarchical' accounts, Saksida and Bussey, 2010). More recent data highlight the temporal dynamics of MTC-dependent visual inferences; the divergence between human accuracy and VTC supported performance scales linearly with reaction time (Bonnen et al., 2021) and there are reliable patterns in MTC-dependent gaze behaviors (Erez et al., 2013). Considering these lesion and behavioral data, as well as the neuroanatomical relationship between VTC and MTC, it is possible that MTC enables supra-VTC performance by integrating over the sequential outputs from high-level visual cortex. That is, MTC might support visual inferences not possible 'at a glance.'

Here we characterize the complementary roles that VTC and MTC play in visual object perception using a combination of lesion, electrophysiological, computational, and psychophysics data. By comparing human performance to electrophysiological responses from high-level visual cortex, we first demonstrate that rapid visual inferences reflect VTC supported performance. However, with increased viewing time participants radically outperform VTC. These temporal relationships are also evident when comparing human performance to 'VTC-like' computational models: our rapid visual inferences are approximated by task-optimized convolutional neural networks (CNNs), but we radically outperform these models with more time. This enables us to use these models as proxies for VTC in subsequent

---

Anatomical relationship between ventral and medial temporal cortex

VTC matches human performance 'at a glance' but not longer timescales

Estimated from macaque electrophysiological recordings

Estimated from deep learning models of vision (CNNs)

Figure 1: **VTC matches human performance 'at a glance,' but not at longer timescales**. Ventral temporal cortex (VTC) is a hierarchical network of neural structures on the lateral and ventral surface of the temporal lobe (top; green). These structures have been shown to support rapid visual inferences through (largely) feedforward processing of retinal inputs. Medial temporal cortex (MTC) is situated on the medial surface of the temporal lobe and is composed of numerous structures. Here, we visualize perirhinal cortex (purple), a MTC structure situated at the apex of VTC—i.e., it receives inputs from high-level visual cortex. MTC structures, such as PRC, have also been implicated in object perception. We estimate 'VTC supported performance' (bottom, left; x axis) from electrophysiological responses collected from high-level visual cortex in the macaque (Majaj et al., 2015). We determine human performance (bottom, left; y axis) by administering the same stimuli to participants online. Using a zero-delay match-to-sample paradigm, we find that when participants are only able to encode the 'sample' image for 100 ms, human visual inferences are predicted by VTC supported performance (bottom, left; green). When participants can visual the same stimuli with unrestricted viewing times, using a simultaneous visual discrimination (i.e., 'oddity') task, human visual inferences radically exceed VTC supported performance (left; purple). We demonstrate the same pattern in relationship to a computational proxy for VTC (bottom, right): time restricted human visual inferences are predicted by a VTC-like model (bottom, right; green), while time unrestricted visual inferences radically exceed VTC model performance (bottom, right; purple). Results from all experiments are normalized such that chance performance is plotted at zero.

 experiments. Next, we implicate MTC in temporally extended visual behaviors by evaluating MTC-
 lesioned and -intact performance. We first validate our previous findings in this novel dataset, observing

that human accuracy corresponds with VTC model performance at restricted viewing times, but exceeds VTC model performance with longer viewing times. Critically, we find that time restricted/unrestricted performance mirrors the differences between MTC-lesioned/-intact participants: neurologically intact 'time restricted' participant behaviors resemble the performance of MTC-lesioned participants. Finally, we use a series of eye-tracking experiments to reveal the sequential nature of information processing during these temporally extended, MTC-dependent visual inferences.

2 Results

2.1 VTC matches human performance 'at a glance,' but not at longer timescales

We examine human performance in two temporal regimes: 'time restricted' (i.e., 'at a glance', given less than 200ms of visual information), and 'time unrestricted' (i.e., 'self-paced'). We draw this partition at 200ms because this is roughly the amount of time needed to initiate an eye movement (i.e., a saccade) in response to a stimulus (Leigh and Zee, 2015). When a stimulus is presented for just 100ms, for example, participants are unable to sequentially sample the image; performance must rely on visually processing 'at a glance.' Conversely, when stimuli are presented for longer durations (e.g., 1000ms) participants are able to collect high-acuity visual information from multiple locations via eye movements. We leverage two experimental designs to examine these temporal dynamics. First, we use a 3-way concurrent visual discrimination task (schematized in Fig. S5) commonly used to evaluate the role of MTC in perception (e.g., Barense et al., 2007; Buckley et al., 2001; Bussey et al., 2002). This design enables us to determine visual inferences that are possible with unlimited viewing time: on each trial, participants are presented with three images and must identify the image that does not match the other two in terms of object identity (i.e., the 'oddity'). To evaluate the effect of time restriction on performance, we use a match-to-sample visual discrimination paradigm (schematized in Fig. S5), common in experiments used to evaluate VTC function (DiCarlo and Cox, 2007; DiCarlo et al., 2012; Majaj et al., 2015). In each match-to-sample trial, participants first view a 'sample' image, which disappears after 100ms, then two images are presented on the subsequent screen. Participants are instructed to select the image that 'matches' the previous image on the sample screen. We administer these experiments to human participants online ($N = 474$). We note that are many differences between these two designs; we address these issues with control experiments later in this section.

We compare time restricted and unrestricted human visual inferences directly to electrophysiological recordings collected from the macaque. This dataset (Majaj et al., 2015) contains neural responses from high-level visual cortex (i.e., inferior temporal cortex, within VTC in the macaque) to stimuli from semantic categories (e.g., Animals, Chairs, Planes, Faces; examples in Fig. S6). With a subset of these images (Methods: Generating a novel stimulus set from Majaj et al., 2015) we use a modified leave-one-out cross validation strategy, enabling us to estimate the item-level ($N = 32$) performance supported by a linear readout of high-level visual cortex (Methods: Estimating VTC supported performance on stimuli from Majaj et al., 2015). We administer these same stimuli to human participants (Methods: Online human data collection). We observe a striking correspondence between time restricted human performance ($N = 107$) and a linear readout of VTC on this zero-delay match-to-sample paradigm (item-level analysis, $\beta = 0.87$, $F(1, 30) = 8.34$, $P = 3\text{x}10^{-9}$; (Fig. 1, bottom left (green)). There is not a significant difference between human accuracy and VTC supported performance (item-level paired ttest $\beta = -0.02$, $t(31) = -0.85$, $P = 0.40$). However, with unrestricted viewing time, participants ($N = 297$) substantially outperform a linear readout of VTC (Fig. 1, bottom left (purple): item-level paired ttest $\beta = .24$, $t(31) = 9.50$, $P = 1\text{x}10^{-10}$). We observe a significant interaction between human and VTC supported performance as a function of stimulus presentation time ($\beta = 0.54$, $F(3, 60) = 5.25$, $P = 2 \text{ x } 10^{-6}$). These data indicate that human performance 'at a glance' reflects a linear readout of VTC, while humans substantially outperform VTC given longer viewing times.

Next, we estimate 'VTC Model Performance' with the same leave-one-out cross-validation strategy used above: we pass the same images which were presented to non-human primates in the Majaj et al., 2015 to a task-optimized convolutional neural network, extract model representations to each image, and then use the same protocol developed to estimate VTC supported performance (Methods: Determining VTC model performance on Majaj et al., 2015). This approach results in a single estimate of VTC Model Performance on each item ($N = 32$). This computational proxy for VTC predicts neural responses in high-level visual cortex ($\beta = .81$, $F(1, 30) = 13.33$, $P = 4\text{x}10^{-14}$; Fig. 1, bottom right (green)), and is outperformed by MTC-intact participants ($\beta = .16$, $t(31) = 5.38$, $P = 7\text{x}10^{-6}$; Fig. 1, bottom right (purple)). Critically, just as with the relation to VTC supported performance, the relationship between human performance and VTC model performance is evident in the temporal interaction term ($\beta = 0.51$, $F(3, 60) = 6.17$, $P = 6 \text{ x } 10^{-8}$). These data validate the use of these computational models as proxies for VTC and, notably, demonstrate that they display the same pattern of accuracy in relation to time restricted/unrestricted human visual inferences.

Finally, we demonstrate that the divergence between time restricted and unrestricted performance is not driven by the difference in experimental designs (i.e., oddity vs. match-to-sample). That is, the difference between time restricted and time unrestricted performance might be a consequence of design

changes that do not necessarily relate to the time permitted to encode each stimulus; e.g., by keeping all stimulus present for the duration of each trial, the oddity design might simply alleviate working memory demands that are present in the match-to-sample task. To evaluate this possibility, we administer a 'self-paced' match-to-sample task where participants are given unrestricted time to encode the stimulus, before the choose to move on to the match screen. This task retains all of the cognitive demands of the 100ms match-to-sample design, while permitted participants more time to encode the 'sample' image. Just as in the oddity task, we find that participants ($N = 60$) in the time unrestricted match-to-sample experiment substantially exceed the performance of time restricted participants (paired ttest $t(30) = 12.01, P = 5.44$ x 10^{-13}; Fig. S7): increasing the time participants can encode the stimulus on the sample screen leads to substantial performance enhancement over time restricted visual inferences. We note that participants in the simultaneous visual discrimination task do outperform participants in the self-paced match-to-sample task ($t(30) = 3.71, P = 0.0008$), suggesting that there are other cognitive factors in the oddity design that may contribute to supra-VTC performance (e.g., less working memory demands). These data make clear that humans are able to significantly outperform VTC given longer encoding times, revealing a striking contrast between the perceptual inferences that are possible at different timescales.

Figure 2: **Temporally extended visual inferences rely on MTC and visuospatial sequences.** We leverage a dataset that enables us to make causal claims about the neural substrates that enable temporally extended visual inferences: Barense et al., 2007 revealed profound impairments of MTC-lesioned human participants performing a visual discrimination ('oddity') task. Here we administer these experimental stimuli to human participants to evaluate the temporal demands of these MTC-dependent stimuli, and situate their performance in relation to a stimulus-computable proxy for VTC. First, we evaluate the performance of human participants in a zero-delay match-to-sample task. Behavior of time restricted human participants online tracks performance resembles VTC model performance (left, green). Time unrestricted performance substantially exceeds time restricted/VTC model performance (left, purple). Next, we evaluate the role of longer viewing times, independent from eye movements, through a series of in-lab eye tracking studies. When participants are gaze restricted (i.e., required to maintain fixation on a single object location) but given unrestricted viewing time, their performance resembles VTC modeled accuracy (center, green). Only when participants are allowed to freely move their eyes can they achieve supra-VTC performance emblematic of MTC-dependent visual inferences (center, purple). These data demonstrate that both temporally and foveally restricted behaviors resemble VTC model performance and, by proxy, MTC-lesioned performance (right, green). Notably, human participants with selective lesions to the hippocampus (HPC) exhibit no impairment on these visual discrimination tasks, indicating that these behaviors rely on cortical structures surrounding the HPC, such as perirhinal cortex (PRC). Taken together, these data suggest that MTC-supported performance relies on gaze dynamics that are only possible with temporally extended viewing times. Results from all experiments are normalized such that chance performance is plotted at zero.

2.2 Temporally extended visual inferences rely on MTC

To investigate the neural substrates that enable these temporally extended visual inferences, we leverage a dataset that contains the performance of MTC-lesioned and -intact human participants (Barense et al., 2007). These stimuli have been shown to reveal profound MTC-related deficits on visual inferences. As such, this dataset enables us to evaluate the effects time restriction alongside the effects of MTC lesions. Before describing the experimental data, we briefly outline the rationale behind these experimental stimuli. First, this stimulus set (example stimuli can be seen in Fig. S6) contains both 'familiar' objects that belong to semantically familiar object categories (e.g. common animate and inanimate objects such as cars and animals) and 'novel' objects that are not semantically familiar to experimental participants (e.g., 'greebles'). These 'familiar' and 'novel' objects are further grouped into two experimental conditions: 'low-ambiguity' stimuli serve as control trials, intended to evaluate the

relative integrity of VTC structures in these MTC-lesioned participants, as well as the cognitive control systems that are needed to perform the task, while 'high-ambiguity' trials are designed to evaluate MTC involvement in visual perception. MTC-lesioned participants have been shown to be selectively impaired on the 'high ambiguity' condition while exhibiting no impairment on 'low ambiguity' trials, with more pronounced deficits for 'novel' stimuli (Barense et al., 2007). Originally, these stimuli were administered via a concurrent visual discrimination (i.e., 'oddity') task, with each trail containing 4 images (i.e., 3 'typicals' and 1 'oddity') presented in a 2x2 choice arrays. Here, we administered all four conditions of these stimuli to human participants online (N=105) and in lab (n=58) using the same experimental designs used in the previous time restricted/unrestricted protocols. While our experiments used the same stimuli, we note that the number of stimuli presented in each trial has been modified to be standardized across the oddity and match-to-sample experiments: we use minimal number of images necessary for each trial, which is 3 (i.e., 2 'typicals' and 1 'oddity').

When evaluating performance on all experimental conditions, we situate human behavior in relation to a computational proxy for the primate VTC (Methods: Determining VTC model performance on stimuli from Barense et al., 2007). We employ a method similar to representational similarity analyses common in the neuroscientific literature (Kriegeskorte et al., 2008; Mehrer et al., 2020). For each trial, in each available experiment, the stimulus screen containing N objects is segmented into N object-centered images. Given that each trial in Barense et al., 2007 contains 4 independent images, we pass each image to the model, then extracted model responses from a layer that approximates high-level visual cortex (i.e., a layer that fits electrophysiological responses collected from IT cortex, in the macaque). These layer responses were flattened into vectors, and we use the pairwise Pearson's correlation between items to generate a 4x4 (item-by-item) correlation matrix. The item with the lowest mean off-diagonal correlation was the model-selected oddity (i.e., the item least like the others) which we then labeled as either correct or incorrect, depending on its correspondence with ground truth. After repeating this protocol for each trial in the experiment, we computed the average accuracy across all trials. This single value represents the performance that would be expected from a uniform readout of high-level visual cortex. Thus, we are able to compare visual abilities across all our experimental designs/datasets within a common metric space: VTC model performance.

One this stimulus set designed to evaluate MTC involvement in perception, we find that time restricted human performance is predicted by VTC modeled performance (subject-by-condition level correlation with VTC model performance: $r = 0.77$, $\beta = 0.57$, $F(1,195) = 16.92$, $P = 4 \times 10^{-40}$; Fig. 2 left, green). Time unrestricted performance diverges from and exceeds time restricted performance (unpaired ttest between the average performance of time restricted/unrestricted condition-level accuracy for all participants: $t(327) = 5.67$, $P = 3.04 \times 10^{-8}$; Fig. 2 left, purple). Critically, when predicting human accuracy from model performance, we observe a significant interaction with stimulus presentation time ($\beta = -0.17$, $F(3,325) = -3.47$, $P = 6 \times 10^{-4}$). As in the experiments above, using stimuli from Majaj et al., 2015, we note that the time restricted/unrestricted comparison using stimuli from Barense et al., 2007 was conducted using two distinct experimental designs. As with the comparison between human and VTC supported performance, we again administer a 'self-paced' match-to-sample task where participants are given unrestricted time to encode the stimulus, before the choose to move on to the match screen. We find that participants (n=20) in the time unrestricted match-to-sample experiment substantially exceed the performance of time restricted participants (paired ttest $t(275) = 4.56$, $P = 7.17 \times 10^{-6}$; Fig. S8), and that there is again an interaction between human and VTC model performance, as a function of stimulus presentation time ($\beta = -0.16$, $F(3,273) = -2.76$, $P = 0.006$). These results demonstrate that the temporal pattern of human visual inferences, previously observed on stimuli from Majaj et al., 2015, is also evident in these experiments using stimuli from Barense et al., 2007.

Just as time restricted human performance is approximated by VTC model performance, and time unrestricted human performance exceeds it, MTC-lesioned performance is approximated by VTC model performance and MTC-intact performance exceeds it (Fig. 2 right). Given the low sample size, we refer here only to the qualitative similarity between time restriction and MTC lesions (for statistical analyses comparing MTC-intact/-lesioned performance in relation to VTC model performance, see Bonnen et al., 2021). Additionally, we note that restricting the time course of visual information processing to <200ms affects multiple systems downstream of VTC—including, but not limited to, MTC. For example, MTC-lesioned participants are known to be unimpaired on rotational invariance (Barense et al., 2007). Time restricted performance of neurotypical participants, however, is significantly impaired even on 'low ambiguity' (i.e., control) stimuli, when compared to MTL-lesioned patient performance (Fig. 2, left, beneath the diagonal; $t(13) = -6.40$, $P = 2 \times 10^{-5}$), presumably because these stimuli are rotated. Indeed, when these stimuli are presented in their canonical orientations in a novel online experiment ($N = 19$), there is no longer a significant difference between time restricted/-unrestricted neurotypical participants (Fig. 2 right, purple, $t(18) = -2.05$, $P = 0.055$). That is, restricting viewing times on the sample screen disrupts abilities that appear to be intact in a MTC-lesioned state, as well as those that appear to depend on MTC. As such, time restricted visual inferences do not necessarily reflect *selective* disruption of MTC-dependent processes.

2.3 MTC-dependent visual inferences rely on visuospatial integration

To evaluate MTC-dependent perceptual dynamics, we conduct a series of in-lab eye tracking experiments (Methods: Eye tracking data collection). Participants' ($N = 97$) gaze was continuously monitored while they completed an hour-long zero-delay match-to-sample experiment, similar to those conducted online. We first sought to determine whether supra-VTC performance is dependent on longer viewing times per se, or the ability to sequentially sample the visual stimulus via multiple saccades. To evaluate this question, we allow participants to view each stimulus on the sample screen for an unrestricted amount of time (i.e., 'self-paced'), but restrict their gaze movements: participants must maintain fixation on a single location at the center of each sample image. On the match screen, participants are free to move their gaze, as in previous experiments. Gaze restricted human participants, even with unrestricted viewing time, are significantly impaired relative to participants who could freely view the stimulus on the sample screen ($t(106) = -4.13, P = 7.14$ x 10^{-5}). Moreover, the performance of gaze restricted human participants is better approximated by VTC-like models than gaze unrestricted abilities (Fig. 2 center), as is evident in the canonical interaction between human performance and VTC model performance, as a function of gaze restriction ($F(3, 104) = 5.15, P = 1$ x 10^{-6}). Thus, when participants are gaze restricted—because they do not have sufficient time to move their eyes, or because their gaze is fixed— their accuracies resemble the performance supported by a linear readout of VTC. We note that these temporally and foveally restricted accuracies resemble the pattern of impairments following lesions to MTC in human participants (Fig. 2 right, green). Inversely, these data suggest that MTC-supported performance relies on gaze dynamics that are only possible with temporally extended viewing times.

Given the critical role of foveal dynamics in MTC-dependent visual inferences, we next characterize the gaze behaviors at encoding (i.e., viewing the stimulus on the sample screen). First, we evaluate the relationship between encoding time and the number of sequential samples taken by experimental participants, which is given by the number of unique 'fixations' on each trial (Methods: Eye tracking data collection). As expected, the duration of time that participants choose to encode the stimulus on the sample screen relates directly to the number of fixations taken on each trial (across all trials $r = 0.93, beta = 2.65, F(1, 5803) = 195.35, P = 0.000$) with a median time spent on each sample screen of 2.77 s, a median number of fixations on each trial of 8, and a median fixation length on each trial of .358 s. We note that, at encoding, there is not a significant difference in the time (across all trials $t(5803) = 0.90, P = 0.36$) or number of fixations ($t(5803) = .80, P = 0.42$) that participants allocate for trials that rely on MTC from those trials that do not (Fig. 3 left, overlapping box plots). That is, this sequential match-to-sample experimental design enables us to isolate stimulus encoding behaviors from subsequent visual/cognitive operations, such as stimulus-stimulus comparison—as intended. Moving on to the match screen, there continues to be a direct relationship between the time participants view an image and the number of fixations on each trial ($r = 0.94 \beta = 2.93, F(1, 6179) = 224.92, P = 0.000$), with a median time spent on each sample screen of 2.13 s, a median number of fixations on each trial of 5, and a median fixation length on each trials of 0.45 s. On the match screen, unlike the gaze behavior at encoding, there is a significant difference in the time ($t(6179) = 38.28, P = 5.75$ x 10^{-288}) or number of fixations ($t(6179) = 36.84, P = 9.97$ x 10^{-269}) that participants allocate for trials that rely on MTC from those trials that do not. That is, participants spend more time on MTC-dependent trials (i.e., those conditions were MTC-lesioned participants are impaired, relative to controls; 'high-ambiguity' semantically familiar and novel objects; evident in the non overlapping box plots for 'high' and 'low' ambiguity conditions for both semantically novel and familiar stimuli Fig. 3 right). More explicitly, we note that trials that exhibit greater MTC-lesioned deficits require more time on the match screen (e.g., 'high ambiguity familiar objects' vs 'low ambiguity familiar objects'; $t(208) = -20.70, P = 2.10$ x 10^{-52}; Fig. 3 left, purple) and more sequential visual sampling (e.g., 'high ambiguity familiar objects' vs 'low ambiguity familiar objects'; $t(208) = -20.06, P = 1.62$ x 10^{-50}; Fig. 3 left, orange). That is, MTC-lesioned deficits are greater for those trials where participants required more time and fixations. We note that this relationship is evident also in computational proxies of VTC (Fig. 3 right).

Finally, we determine whether these gaze behaviors are reliable across participants. We estimate the split-half reliability of these gaze dynamics using the following protocol (Methods: Estimating gaze reliability). First, for each trial, a participant-level salience map is generated from the raw gaze behaviors, smoothed with a Gaussian kernel (example data from a single trial visualized in Fig. S9). For each image, all participant-level salience maps are collected, then randomly partitioned into two splits. The salience maps in each of these random splits are averaged (i.e., across participants), then we determine the correlation between the two (random split-half) salience maps associated with each image. This results in a single numerical value for the random shuffle of participant maps to this image. For each image we repeat this protocol across 100 iterations, storing the correlation across random splits. This results in a distribution of random split-half correlations for each image. To establish an empirical null we compute the correlation between random splits corresponding to the different images within the same trial. Additionally, we estimate the bottom-up salience of each image using standard image processing pipelines (Itti et al., 1998) and also compute the correlation between this bottom-up salience map and the average participant salience maps. Thus, for each image, have three distributions: the split-half correlations between participants' salience maps, an empirical null (i.e., the correlation between the split half of this image and the split half of another image), and the correlation between

Longer viewing times enable sequential sampling of visual stimuli

Stimuli that require more sequential sampling reveal MTC-related deficits

Figure 3: **Gaze dynamics of human participants during a MTC-dependent visual task.** We administer a sequential match-to-sample task to human participants in lab during a novel eye tracking study. We visualize the relationship between reaction time, number of fixations, and stimulus type, for both the sample (top, left) and match (top, right) screens. As intended, on the sample screen, participants are not differentiating between stimulus categories; it is not yet clear what the difficulty of the subsequent match screen will be, and so all images are encoded for roughly the same amount of time (evident in the overlapping box plots between 'high' and 'low' ambiguity conditions). On the match screen, by comparison, there is a clear distinction between reaction time and number of fixations as a function of stimulus category with the 'high-ambiguity' (i.e., MTC-dependent) stimuli requiring substantially more time (non-overlapping boxplots between 'high' and 'low' ambiguity conditions). That is, this sequential match-to-sample design enables us to isolate stimulus encoding behaviors from subsequent visual/cognitive operations, such as stimulus-stimulus comparison—as intended. We relate these gaze behaviors more explicitly to MTC dependence: trials that exhibit greater MTC-lesioned deficits in Barense et al., 2007 require more time on the match screen, in order for participants to sequentially sample the visual stimulus (e.g., 'high ambiguity familiar objects' vs 'low ambiguity familiar objects'; bottom, left). That is, MTC-lesioned deficits are greater for those trials where participants required more time and fixations. We note that this relationship is evident also in computational proxies of VTC (bottom, right).

participants' salience maps and a bottom-up salience map. We repeat this process for all images and find that gaze behaviors on each image are remarkably reliable across participants (Fig. 4; purple, median split-half correlation across images of 0.86, STD of 0.095). These image-level reliability scores (Fig. 4 purple, all panels) are significantly greater that the empirical null (unpaired ttest $t(1258) = 35.97, P = 1.90$ x 10^{-195}; Fig. 4 grey, all panels) as well as the fit to bottom-up salience maps (unpaired ttest $t(835) = 26.38, P = 4.58$ x 10^{-112}; Fig. 4 black, all panels), indicating that these gaze behaviors are reliable and not simply driven by bottom-up salience.

Figure 4: **Pattern of spatial attention for each object is reliable across participants.** Here we estimate the reliability of item-level gaze behaviors across participants during encoding (i.e., during the sample screen). For each participant, we generate a salience map from the raw gaze behaviors. This yields a salience map for each image a participant observed during the experiment. We can collect all the salience maps for all participants, for a given image, and randomly partitioned these salience maps into two splits. We then averaged across participants in each random split, resulting in two averaged salience maps for this random split. We correlate these two maps, resulting in a single numerical value. We repeat this protocol for each image, storing the correlation values across 100 random splits, resulting in a distribution of random split-half correlations for each image (purple, all plots). We compare this correlation to both an empirically estimated null distribution (light grey, all plots) and the bottom-up salience map of each image (dark grey, all plots). We find that gaze behaviors on each image are reliable across participants. Remarkably, the image-level reliability is greater than the correlation between salience maps and the bottom-up salience estimated from each image. These data indicating that these gaze behaviors are reliable and not simply driven by bottom-up salience.

3 Discussion

Our findings suggest that there are complementary neural systems supporting visual object perception. VTC provides a basis space for visual inferences (Jagadeesh and Gardner, 2022): features that are useful for many downstream behaviors emerge within 100ms of stimulus presentation (DiCarlo and Cox, 2007), enabling rich visual inferences 'at a glance' (Potter and Levy, 1969). However, not all visual inferences are easily (i.e., linearly) separable in this basis space. To overcome this limitation, humans sequentially sample visual stimuli via multiple saccades, collecting high-acuity visual information from task-relevant features. MTC integrates over these visuospatial sequences, enabling supra-VTC performance on visual inferences. We support this multiple-systems account of object perception with several sources of evidence. When human participants are time restricted, their performance tracks with a linear readout of VTC. Given sufficient viewing time, however, MTC-intact human participants are able to radically outperform a linear readout of VTC. It is not time, per se, that enables this supra-VTC performance: increased viewing time enables participants to sequentially sample visual stimuli via multiple saccades, visuospatial patterns that are reliable across participants and not simply a reflection of bottom-up salience. Conversely, when participants are given unlimited viewing time, but unable to move their eyes, their performance continues to reflect VTC levels of performance. Critically, MTC-lesioned human performance resembles the accuracy supported by a stimulus-computable proxy for VTC, even with unrestricted viewing time. These data provide causal evidence that MTC enables supra-VTC performance by integrating over visuospatial sequences.

The sequential nature of information processing within MTC is well recognized in the neuroscientific literature (Buzsáki and Tingley, 2018; Dusek and Eichenbaum, 1997). These sequences are increasingly understood for their 'compositional' role in cognitive function (McNamee et al., 2021; Schwartenbeck et al., 2021), enabling animals to flexibly combine distinct representations to support novel inferences. The compositional operations of MTC have historically been studied in relation to memory-related functions, where the to-be-composed elements are sequentially sampled from prior experience (e.g., Kurth-Nelson et al., 2023). Anatomically, these studies have centered on MTC structures such as hippocampal and entorhinal cortex (HPC and ERC, respectively). Our work extends these findings to the domain of perceptual functions, where the to-be-composed elements are sequentially sampled directly from the environment (i.e., the visual stimulus)—or, more concretely, from VTC responses elicited by the environment. These data provide implementation-level support for longstanding theories of visual perception (e.g., Marr, 1982; Ullman, 1987), demonstrating how a finite set of visual features, supported by VTC, can be flexibly repurposed to represent an unbounded set of possible objects, supported by MTC. More precisely, we note that bilateral damage to HPC results in no impairment on the object-centric visual inferences studied here (Barense et al., 2007). For this reason, as well as its anatomical relationship to VTC, the literature on MTC involvement in object perception has centered on perirhinal cortex (PRC). However, the available data do not enable us to isolate the role of PRC from ERC, leaving open the possibility that both ERC and PRC contribute to these perceptual functions.

These data highlight the computational advantage of integrating neural systems that operate over

different timescales (McClelland et al., 1995). The stimulus properties that VTC can represent are sculpted by the cumulative experience of the organism (Arcaro et al., 2017; Gomez et al., 2019; Nordt et al., 2021; Rajalingham et al., 2020; Srihasam et al., 2012). As such, human performance 'at a glance' draws from these amortized visual representations (Dasgupta et al., 2018). This provides a powerful, if limited, basis space of features to represent ongoing experience. MTC-dependent representations enable zero-shot performance visual inferences 'out of distribution' visual inferences—i.e., not present in the information consolidated within VTC, nor possible 'at a glance.' However, consolidating these representations into earlier stages of visual processing provides significant behavioral advantages when these challenges are common occurrences (Goldstone, 1998; Miyashita et al., 1998). That is, visual representations that initially depend on MTC are, over time, consolidated throughout VTC (Erez et al., 2016; Liang et al., 2020; Miyashita et al., 1993). In turn, this enables the elemental features that MTC operates over to be increasingly 'complex,' enabling more sophisticated zero-shot visual inferences.

The representational dynamics outlined above present challenges for experimentalists that aim to understand MTC involvement in perception. Historically, isolating MTC function has focused on manipulating stimulus-level visual attributes, such as stimulus 'complexity' (Cowell et al., 2010) or 'feature ambiguity' (Barense et al., 2007). Yet there has not been a reliable way to elicit MTC-dependent representational demands across experiments (Bonnen et al., 2021) or across species (Bonnen and Eldridge, 2023). This was due, in part, to reliance on qualitative accounts of experimental variables to characterize the representational demands in a given stimulus set. We suggest that isolating MTC supported behaviors requires manipulating both the representational and temporal demands in these experimental designs. First, time unrestricted human performance should exceed VTC supported performance, evidence of the representational challenge resolved by MTC. In lieu of direct neural recordings, VTC-like models can serve as computational proxies for VTC; these models, such as convolutional neural networks, provide a powerful, tractable framework to approximate VTC supported performance, directly from the experimental stimulus presented to participants. Second, supra-VTC performance must rely on the sequential processing of visual stimuli, evidence of the algorithmic approach needed to resolves this representational challenge. This is not to suggest that all temporally extended visual inferences—nor all supra-VTC performance—relies on MTC. Many neural systems transform VTC responses to support downstream behaviors, including prefrontal structures (Birman and Gardner, 2019; Kar and DiCarlo, 2020). Nonetheless, manipulating both temporal and representational demands can help isolate VTC supported behaviors from those that depend on downstream structures, such as MTC.

Our work provides algorithmic and architectural constraints for biologically plausible models of human vision. Deep learning methods already used throughout the neurosciences (e.g., convolutional neural networks) account for one component of this system; these models have been shown to approximate neural responses and behaviors that depend on VTC, but fail to achieve human-level performance on many visual inferences (Alcorn et al., 2019; Baker et al., 2018; Geirhos et al., 2018; Reizenstein et al., 2021). The divergence between these 'VTC-like' models and human performance is often used to critique these computational approaches. Our data support an alternative interpretation: the divergence between humans and 'VTC-like' models highlight the multi-system nature of perception. As such, biologically plausible models of human vision should be designed to reflect the algorithmic and architectural constraints we have identified here. Recent developments in computer science may prove useful for this purpose. For example, vision transformers (ViTs) use a sequential strategy to process visual inputs (Dosovitskiy et al., 2020; Liu et al., 2021) and have been adapted to reflect the foveal dynamics of primate vision (e.g., Jonnalagadda et al., 2021; Min et al., 2022; Wang et al., 2021; Yang et al., 2022) with architectural variants that (incidentally) resemble the hierarchical relationship between MTC and VTC (Hatamizadeh et al., 2023; Pan et al., 2023; Wu et al., 2021). However, we note that these models suffer from the same failures modes widely observed in prior methods (Abbas and Deny, 2023; Madan et al., 2021). While other frameworks have been proposed to address these shortcomings (e.g., Yu et al., 2021), each comes with its unique limitations. Nonetheless, we believe designing models that embody the biological constraints identified here provide a promising approach to characterize—and perhaps approximate—the complementary neural systems that underlie human visual abilities.

Acknowledgements

This work is supported by the National Institute of Neurological Disorders and Stroke of the National Institutes of Health (Award Number F99NS125816) and Stanford's Center for Mind Brain Behavior and Technology. We thank Dhruv Kapadia for collecting the in-lab eyetracking data.

References

Abbas, A., & Deny, S. (2023). Progress and limitations of deep networks to recognize objects in unusual poses. *Proceedings of the AAAI Conference on Artificial Intelligence, 37*(1), 160–168.

Alcorn, M. A., Li, Q., Gong, Z., Wang, C., Mai, L., Ku, W.-S., & Nguyen, A. (2019). Strike (with) a pose: Neural networks are easily fooled by strange poses of familiar objects. *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 4845–4854.

Arcaro, M. J., Schade, P. F., Vincent, J. L., Ponce, C. R., & Livingstone, M. S. (2017). Seeing faces is necessary for face-domain formation. *Nature neuroscience*, *20*(10), 1404.

Baker, N., Lu, H., Erlikhman, G., & Kellman, P. J. (2018). Deep convolutional networks do not classify based on global object shape. *PLoS computational biology*, *14*(12), e1006613.

Barense, M. D., Gaffan, D., & Graham, K. S. (2007). The human medial temporal lobe processes online representations of complex objects. *Neuropsychologia*, *45*(13), 2963–2974.

Birman, D., & Gardner, J. L. (2019). A flexible readout mechanism of human sensory representations. *Nature communications*, *10*(1), 3500.

Bonnen, T., & Eldridge, M. A. (2023). Inconsistencies between human and macaque lesion data can be resolved with a stimulus-computable model of the ventral visual stream. *Elife*, *12*, e84357.

Bonnen, T., Yamins, D. L., & Wagner, A. D. (2021). When the ventral visual stream is not enough: A deep learning account of medial temporal lobe involvement in perception. *Neuron*.

Buckley, M. J., Booth, M. C., Rolls, E. T., & Gaffan, D. (2001). Selective perceptual impairments after perirhinal cortex ablation. *Journal of Neuroscience*, *21*(24), 9824–9836.

Bussey, T. J., & Saksida, L. M. (2002). The organization of visual object representations: A connectionist model of effects of lesions in perirhinal cortex. *European Journal of Neuroscience*, *15*(2), 355–364.

Bussey, T. J., Saksida, L. M., & Murray, E. A. (2002). Perirhinal cortex resolves feature ambiguity in complex visual discriminations. *European Journal of Neuroscience*, *15*(2), 365–374.

Buzsáki, G., & Tingley, D. (2018). Space and time: The hippocampus as a sequence generator. *Trends in cognitive sciences*, *22*(10), 853–869.

Cowell, R. A. (2012). Computational models of perirhinal cortex function. *Hippocampus*, *22*(10), 1952–1964.

Cowell, R. A., Bussey, T. J., & Saksida, L. M. (2010). Components of recognition memory: Dissociable cognitive processes or just differences in representational complexity? *Hippocampus*, *20*(11), 1245–1262.

Dasgupta, I., Schulz, E., Goodman, N. D., & Gershman, S. J. (2018). Remembrance of inferences past: Amortization in human hypothesis generation. *Cognition*, *178*, 67–81.

De Leeuw, J. R. (2015). Jspsych: A javascript library for creating behavioral experiments in a web browser. *Behav. Res. Methods.*, *47*(1), 1–12. 10.3758/s13428-014-0458-y

Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., & Fei-Fei, L. (2009). Imagenet: A large-scale hierarchical image database. *2009 IEEE conference on computer vision and pattern recognition*, 248–255.

DiCarlo, J. J., & Cox, D. D. (2007). Untangling invariant object recognition. *Trends in cognitive sciences*, *11*(8), 333–341.

DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How does the brain solve visual object recognition? *Neuron*, *73*(3), 415–434.

Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., et al. (2020). An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*.

Dusek, J. A., & Eichenbaum, H. (1997). The hippocampus and memory for orderly stimulus relations. *Proceedings of the National Academy of Sciences*, *94*(13), 7109–7114.

Erez, J., Cusack, R., Kendall, W., & Barense, M. D. (2016). Conjunctive coding of complex object features. *Cerebral Cortex*, *26*(5), 2271–2282.

Erez, J., Lee, A. C., & Barense, M. D. (2013). It does not look odd to me: Perceptual impairments and eye movements in amnesic patients with medial temporal lobe damage. *Neuropsychologia*, *51*(1), 168–180.

Findlay, J. M., & Gilchrist, I. D. (2003). *Active vision: The psychology of looking and seeing*. Oxford University Press.

Geirhos, R., Rubisch, P., Michaelis, C., Bethge, M., Wichmann, F. A., & Brendel, W. (2018). Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. *arXiv preprint arXiv:1811.12231*.

Goldstone, R. L. (1998). Perceptual learning. *Annual review of psychology*, *49*(1), 585–612.

Gomez, J., Barnett, M., & Grill-Spector, K. (2019). Extensive childhood experience with pokémon suggests eccentricity drives organization of visual cortex. *Nature human behaviour*, *3*(6), 611–624.

Greene, M. R., & Oliva, A. (2009). The briefest of glances: The time course of natural scene understanding. *Psychological science*, *20*(4), 464–472.

Grill-Spector, K., & Weiner, K. S. (2014). The functional architecture of the ventral temporal cortex and its role in categorization. *Nature Reviews Neuroscience*, *15*(8), 536–548.

Hatamizadeh, A., Heinrich, G., Yin, H., Tao, A., Alvarez, J. M., Kautz, J., & Molchanov, P. (2023). Fastervit: Fast vision transformers with hierarchical attention. *arXiv preprint arXiv:2306.06189*.

Henderson, J. M. (2003). Human gaze control during real-world scene perception. *Trends in cognitive sciences*, *7*(11), 498–504.

Hirsch, J., & Curcio, C. A. (1989). The spatial resolution capacity of human foveal retina. *Vision research*, *29*(9), 1095–1101.

Itti, L., Koch, C., & Niebur, E. (1998). A model of saliency-based visual attention for rapid scene analysis. *IEEE Transactions on pattern analysis and machine intelligence*, *20*(11), 1254–1259.

Jagadeesh, A. V., & Gardner, J. (2022). Texture-like representation of objects in human visual cortex. *bioRxiv*.

Jonnalagadda, A., Wang, W. Y., Manjunath, B., & Eckstein, M. P. (2021). Foveater: Foveated transformer for image classification. *arXiv preprint arXiv:2105.14173*.

Kar, K., & DiCarlo, J. J. (2020). Fast recurrent processing via ventral prefrontal cortex is needed by the primate ventral stream for robust core visual object recognition. *Available at SSRN 3606801*.

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis-connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, 4.

Kurth-Nelson, Z., Behrens, T., Wayne, G., Miller, K., Luettgau, L., Dolan, R., Liu, Y., & Schwartenbeck, P. (2023). Replay and compositional computation. *Neuron*, *111*(4), 454–469.

Lee, A. C., Bussey, T. J., Murray, E. A., Saksida, L. M., Epstein, R. A., Kapur, N., Hodges, J. R., & Graham, K. S. (2005). Perceptual deficits in amnesia: Challenging the medial temporal lobe 'mnemonic'view. *Neuropsychologia*, *43*(1), 1–11.

Leigh, R. J., & Zee, D. S. (2015). *The neurology of eye movements*. Contemporary Neurology.

Liang, J. C., Erez, J., Zhang, F., Cusack, R., & Barense, M. D. (2020). Experience transforms conjunctive object representations: Neural evidence for unitization after visual expertise. *Cerebral Cortex*, *30*(5), 2721–2739.

Liu, Z., Lin, Y., Cao, Y., Hu, H., Wei, Y., Zhang, Z., Lin, S., & Guo, B. (2021). Swin transformer: Hierarchical vision transformer using shifted windows. *Proceedings of the IEEE/CVF international conference on computer vision*, 10012–10022.

Liversedge, S. P., & Findlay, J. M. (2000). Saccadic eye movements and cognition. *Trends in cognitive sciences*, *4*(1), 6–14.

Madan, S., Sasaki, T., Li, T.-M., Boix, X., & Pfister, H. (2021). Small in-distribution changes in 3d perspective and lighting fool both cnns and transformers. *arXiv preprint arXiv:2106.16198*.

Majaj, N. J., Hong, H., Solomon, E. A., & DiCarlo, J. J. (2015). Simple learned weighted sums of inferior temporal neuronal firing rates accurately predict human core object recognition performance. *Journal of Neuroscience*, *35*(39), 13402–13418.

Marr, D. (1982). Vision: A computational investigation into the human representation and processing of visual information.

McClelland, J. L., McNaughton, B. L., & O'Reilly, R. C. (1995). Why there are complementary learning systems in the hippocampus and neocortex: Insights from the successes and failures of connectionist models of learning and memory. *Psychological review*, *102*(3), 419.

McNamee, D. C., Stachenfeld, K. L., Botvinick, M. M., & Gershman, S. J. (2021). Flexible modulation of sequence generation in the entorhinal–hippocampal system. *Nature neuroscience*, *24*(6), 851–862.

Mehrer, J., Spoerer, C. J., Kriegeskorte, N., & Kietzmann, T. C. (2020). Individual differences among deep neural network models. *Nature communications*, *11*(1), 5725.

Min, J., Zhao, Y., Luo, C., & Cho, M. (2022). Peripheral vision transformer. *Advances in Neural Information Processing Systems*, *35*, 32097–32111.

Miyashita, Y., Date, A., & Okuno, H. (1993). Configurational encoding of complex visual forms by single neurons of monkey temporal cortex. *Neuropsychologia*, *31*(10), 1119–1131.

Miyashita, Y., Kameyama, M., Hasegawa, I., & Fukushima, T. (1998). Consolidation of visual associative long-term memory in the temporal cortex of primates. *Neurobiology of learning and memory*, *70*(1-2), 197–211.

Murray, E. A., & Bussey, T. J. (1999). Perceptual–mnemonic functions of the perirhinal cortex. *Trends in cognitive sciences*, *3*(4), 142–151.

Murray, E. A., & Wise, S. P. (2012). Why is there a special issue on perirhinal cortex in a journal called hippocampus? the perirhinal cortex in historical perspective. *Hippocampus*, *22*(10), 1941–1951.

Nordt, M., Gomez, J., Natu, V. S., Rezai, A. A., Finzi, D., Kular, H., & Grill-Spector, K. (2021). Cortical recycling in high-level visual cortex during childhood development. *Nature human behaviour*, *5*(12), 1686–1697.

Nyström, M., & Holmqvist, K. (2010). An adaptive algorithm for fixation, saccade, and glissade detection in eyetracking data. *Behavior research methods*, *42*(1), 188–204.

Pan, X., Ye, T., Xia, Z., Song, S., & Huang, G. (2023). Slide-transformer: Hierarchical vision transformer with local self-attention. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2082–2091.

Potter, M. C. (1975). Meaning in visual search. *Science*, *187*(4180), 965–966.

Potter, M. C., & Levy, E. I. (1969). Recognition memory for a rapid sequence of pictures. *Journal of experimental psychology*, *81*(1), 10.

Rajalingham, R., Kar, K., Sanghavi, S., Dehaene, S., & DiCarlo, J. J. (2020). The inferior temporal cortex is a potential cortical precursor of orthographic processing in untrained monkeys. *Nature communications*, *11*(1), 3886.

Reizenstein, J., Shapovalov, R., Henzler, P., Sbordone, L., Labatut, P., & Novotny, D. (2021). Common objects in 3d: Large-scale learning and evaluation of real-life 3d category reconstruction. *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 10901–10911.

Saksida, L. M., & Bussey, T. J. (2010). The representational–hierarchical view of amnesia: Translation from animal to human. *Neuropsychologia*, *48*(8), 2370–2384.

Schwartenbeck, P., Baram, A., Liu, Y., Mark, S., Muller, T., Dolan, R., Botvinick, M., Kurth-Nelson, Z., & Behrens, T. (2021). Generative replay for compositional visual understanding in the prefrontal-hippocampal circuit. *bioRxiv*, 2021–06.

Simonyan, K., & Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*.

Srihasam, K., Mandeville, J. B., Morocz, I. A., Sullivan, K. J., & Livingstone, M. S. (2012). Behavioral and anatomical consequences of early versus late symbol training in macaques. *Neuron*, *73*(3), 608–619.

Suzuki, W. A., & Amaral, D. G. (2004). Functional neuroanatomy of the medial temporal lobe memory system. *Cortex: A Journal Devoted to the Study of the Nervous System and Behavior*.

Ullman, S. (1987). Visual routines. In *Readings in computer vision* (pp. 298–328). Elsevier.

Van Essen, D. C., & Anderson, C. H. (1990). Information processing strategies and pathways in the primate retina and visual cortex. In *An introduction to neural and electronic networks* (pp. 43–72).

Wang, B., Mayo, D., Deza, A., Barbu, A., & Conwell, C. (2021). On the use of cortical magnification and saccades as biological proxies for data augmentation. *arXiv preprint arXiv:2112.07173*.

Wu, H., Xiao, B., Codella, N., Liu, M., Dai, X., Yuan, L., & Zhang, L. (2021). Cvt: Introducing convolutions to vision transformers. *Proceedings of the IEEE/CVF international conference on computer vision*, 22–31.

Yang, J., Li, C., Dai, X., & Gao, J. (2022). Focal modulation networks. *Advances in Neural Information Processing Systems*, *35*, 4203–4217.

Yu, A., Ye, V., Tancik, M., & Kanazawa, A. (2021). Pixelnerf: Neural radiance fields from one or few images. *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 4578–4587.

4 Methods

4.1 Estimating VTC supported performance on stimuli from Majaj et al., 2015

In order to estimate the performance supported by VTC and compare to human visual inferences, we utilize stimuli and electrophysiological data from a previous experiment (Majaj et al., 2015). This stimulus set consists of 5760 unique black and white images. Every black and white image contains one of 64 objects, each belonging to one of eight categories, rendered in different orientations and projected onto random backgrounds. This results in 90 images per object. For each image, the original study collected population-level electrophysiological responses recorded from primate V4 and IT. To estimate VTC supported performance on the stimuli above, we use a modified leave-one-out cross validation strategy. For a given sample$_{ij}$ trial we construct a random combination of three-way oddity tasks to be used as training data; we sample without replacement from the pool of all images of object$_i$ and object$_j$, excluding only those three stimuli that were present in sample$_{ij}$. This yields 'pseudo oddity experiments' where each trial contains two typical objects and one oddity that have the same identity as the objects in sample$_{ij}$ and are randomly configured (different viewpoints, different backgrounds, different orders). These 'pseudo oddity experiments' are used as training data. For each of these images, we identify neural responses from high-level visual cortex. We then train an L2 regularized linear classifier to identify the oddity across all ($N = 52$) trials in this permutation of pseudo oddity experiments generated for sample$_{ij}$. After learning this weighted, linear readout, we evaluate the classifier on the neural responses to sample$_{ij}$. This results in a prediction which is binarized into a single outcome $\{0 \mid 1\}$, either correct or incorrect. We repeat this protocol across 100 random sample$_{ij}$s, and average across them, resulting in a single estimate of VTC supported performance for each pair$_{ij}$.

4.2 Determining VTC model performance on Majaj et al., 2015

To estimate VTC model performance we use the same protocol as above, but use a task-optimized convolutional neural network instead of neural recordings. We use a task-optimized convolutional neural network (VGG16, Simonyan and Zisserman, 2014), implemented in tensorflow and pre-trained to perform object classification on a large-scale object classification dataset (Imagenet, Deng et al., 2009). For every image in the Majaj et al., 2015 dataset, we convert this stimulus from greyscale to RGB, then resize it to accommodate model input dimensions (224x224x3). We pass each image to the model and extract responses from a penultimate layer (fc6). Then we repeat the protocol outlined above for estimating VTC supported performance. For each object, we generate a suite of 'pseudo oddity experiments,' train L2 regularized linear classifier to predict the oddity in each of these pseudo random trails, and evaluate this linear transform of model responses on the test data.

4.3 Generating a novel stimulus set from Majaj et al., 2015

To generate human behavioral experiments we subsample stimuli from Majaj et al., 2015. We reconfigure stimuli from four categories into sets that can be used for both within-category oddity tasks as well as match-to-sample tasks. Each trial is designed to have the minimal configuration of objects ($n = 3$) for these two experimental designs: two of the three objects share an identity (two images of the 'typical' object$_i$, presented from two different viewpoints and projected onto different random backgrounds) and the other is of a different identity (one image of the 'oddity', object$_j$, e.g., two animals, where 'elephant' and 'hedghog' are object$_i$ and object$_j$, respectively). We generate a sample trial$_{ij}$ for the pair$_{ij}$ of objects i and j by randomly sampling two different objects from the same category, then sampling two images of object$_i$ (without replacement) and one image of the oddity of object$_j$, all with random orientations and backgrounds. We create trials composed of stimuli containing 224 objects. We use this protocol for each of the 224 pair$_{ij}$s: we generate 5 random combination of trials from each pair$_{ij}$ and fix these trials across all experiments (i.e., trial$_{ij_1}$, trial$_{ij_2}$, ..., trial$_{ij_5}$), resulting in (224 x 5) 1120 unique trials. We administer a randomized subset ($N = 100$) of these oddity trials to 297 human participants using a browser-based experimental paradigm implemented in jsPsych (De Leeuw, 2015). We note that, given the truly random experimental generation protocol—and, subsequently, the highly variable nature of the stimuli that comprise each trial—there is no guarantee that a given trial$_{ij_n}$ will contain the information sufficient for a correct response. For example, all the faces in a trial might be rotated out of view, such that the correct oddity can not be determined. To address this, of the 5 stimuli presented, for each of the 224 pair$_{ij}$s, we restrict our analysis to 1 trial$_{ij}$ which is identified empirically. We select this exemplar for each pair$_{ij}$ using a single criterion: the item whose average accuracy (across participants) is closest to the average accuracy measured across all trials (across participants) belonging to other categories. This procedure enables us to exclude outliers (due to, for example, the objects not being fully visible on the viewing screen) while not biasing the results in future analyses. Performance estimates are computed across the population of human participants. In this pooled population of behavior, we compute the reliability by determining the averaged correlation over 1000 randomly shuffled split halves: accuracy was reliable at the category (averaging across all oddity trials in a given category, $r = .97 \pm .03$), object (averaging over all oddity objects for a given typical object, $r = .69 \pm .07$), and image level (average performance on a given trial, averaged across participants, $r = .24 \pm .05$). This effect was even more prominent in the estimates of reaction time at the category ($r = .99 \pm .01$), object ($r = .91 \pm .02$), and image level ($r = .76 \pm .02$).

4.4 Determining VTC model performance on stimuli from Barense et al., 2007

For each trial, in each available experiment, the stimulus screen containing 4 objects was segmented into 4 object-centered images. Stimuli for each trial were only available in the form presented to experimental participants, as a single image containing multiple objects. For both 'novel' experiments (i.e., low ambiguity novel and high ambiguity novel), for each trial, the stimulus screen was segmented using a K-means clustering approach that automatically identified the centroid of each object, defined a bounding box around each of these centroids, and extracted each object from the coordinates of each bounding box. For both 'familiar' experiments, which had images with more irregular dimensions, these stimuli were segmented by splitting the original stimulus screen into quadrants of equal size. For all segmentation protocols, we passed each trial's 4 object-centered images to the model, then extracted model responses from an 'IT like' layer. These layer responses were flattened into length F vectors, resulting in an Fx4 response matrix for each trail. To identify the item-by-item similarity between objects in this trial, were used Pearson's correlation between items in this Fx4 response matrix, generating an 4x4 (item-by-item) correlation matrix. The item with the lowest mean off-diagonal correlation was the model-selected oddity (i.e., the item least like the others) which we then labeled as either correct or incorrect, depending on its correspondence with ground truth. After repeating this protocol for each trial in the experiment, we computed the average accuracy across all trials. This single value, 'model performance', represents the performance that would be expected from a uniform readout of IT. We normalize model performance to fall within the range of 0 (chance) to 1 (ceiling) so that we can compare results from these original oddity decisions (i.e., 4-way, with chance at 25%) with current experiments (which were either 3-way oddity decisions, or 2-way match-to-sample decision, with chance at either 33% or 50%, respectively.

4.5 Online human data collection

Human experimental data were collected online via Amazon Mechanical Turk and Prolific via experiments were implemented in JsPsych (De Leeuw, 2015). Each experiment began with an instruction phase, which introduced them to the task as well as provided 5 practice trials. This provided an opportunity for participants to acclimate themselves to the task and the controls. Once the experiment began, participants initiated the beginning of each trial with a button press (spacebar), such that they can (effectively) pause the experiment whenever they deem appropriate. This was designed to reduce environmental interference in the experiment. Experiments were designed to be completed in 10 minutes

and participants were payed at a rate of roughly $16/hour. In addition, participants were awarded a bonus commensurate with their performance, enabling them to earn up to twice the base pay. In order to ensure that participants were fairly compensated for their time, even in the case of a crowdsourcing platform errors, trial-by-trial data were collected throughout the experiment and stored on a custom server built from a Digital Ocean 'droplet.'

We administer two related experimental designs. First, we use a 3-way concurrent visual discrimination task commonly used to evaluate the role of MTC in perception (Barense et al., 2007; Buckley et al., 2001; Bussey et al., 2002). This design enables us to determine visual inferences that are possible with unlimited viewing time, as all stimuli remain on the screen for the duration of the trial. On each trial, participants are presented with three images and must identify the image that does not match the other two in terms of object identity (i.e., the 'oddity'). Participants are given upwards of ten seconds to complete each trial. At any point in this duration participants can select the oddity with a button press (right arrow, left arrow, or down arrow) corresponding to those location on the oddity array. After this button press, participants are given feedback related to their performance on that trial, indicating whether their choice was correct or incorrect. If participants do no press a button in these ten seconds, the trial is marked as incorrect, feedback is given on the screen encouraging them to complete each trial within the allotted time.

To evaluate the effect of time restriction on performance, we use a match-to-sample visual discrimination paradigm common among tasks designed to evaluate VTC supported performance (DiCarlo and Cox, 2007; DiCarlo et al., 2012; Majaj et al., 2015). In each match-to-sample trial, participants first view a 'sample' image. After 100 ms of stimulus presentation, this sample image disappears, a noise mask is presented for around 30 ms, then two images are presented on the subsequent screen. Participants are instructed to select the image that 'matches' the previous image on the sample screen. Participants again have ten seconds to complete each trial, which is a relatively unrestricted amount of time to complete each trial. If participants do no press a button in these ten seconds, the trial is marked as incorrect, with feedback given on the screen encouraging them to complete each trial within the allotted time. Additionally, we administer 'self-paced' match to sample experiments. In these experiments, participants determine how long to view the stimulus on the sample screen (up to 10 seconds). After they press a button to move on, the sample image disappears, a noise mask is briefly presented, and then they make their choice on the match screen in a manner identical to the match-to-sample design introduced above.

4.6 Eye tracking data collection

Eye tracking was performed using an infrared video-based eye-tracker at 1000 Hz (Eyelink 1000; SR Research). Stimuli were displayed on a 22.5 inch VIEWPixx LCD display (resolution of 1900×1200, refresh rate of 120 Hz) and responses collected via keyboard. Other sources of light were minimized during data collection. The stimulus on the sample screen was presented at the central field of view and spanned up to 10 degrees of visual angle. This stimulus size was selected such that in order to collect high-acuity visual information from various stimulus locations, participants had to move their eyes (i.e., make a saccade). Stimuli on the match screen were the same size, but presented side by side, offset from the horizontal midpoint of the screen by 10 degrees of visual angle. Each experiment began with gaze calibration, then 5 practice trials to acclimate participants to the experimental setup. Each trial was initiated by the participants and began with participants maintaining fixation at the center of the screen (to perform drift correction at the beginning of each trial). Participants completed each trial at their own pace and there was a brief rest period every 5 minutes. This duration of this rest period was at the discretion of each participant. After this rest period, there was another gaze calibration, after which participants again completed a series of trials at their own pace as described above. For all gaze analyses (e.g., evaluating gaze reliability) we estimate gaze-related events (e.g. fixations) directly from the raw gaze data using a standard python library (REMoDNaV; Nyström and Holmqvist, 2010).

4.7 Estimating gaze reliability

We estimate the split-half reliability of in-lab gaze dynamics using the following protocol. First, for each trial, a subject-level salience map is generated from the raw gaze behaviors: a 2D histogram is generated from the raw time series, which is then smoothed with a Gaussian kernel. We note that the results reported in this manuscript are robust to the resolution of the 2D histogram and size of the smoothing kernel. This protocol yields a salience map for each image for each subject. We then generate a random split of subjects and partition the salience maps for a given image using this random subject split. We then average across participants in each random split, which results in two salience maps, each corresponding to the random split of participants allotted to that half. We then estimate the correlation between the two (random split-half) salience maps associated with this image. We repeat this protocol for 100 random split-half permutations (i.e., generating a new shuffle of participants each iteration). For each image, we then have a distribution of split-half correlations which enables us to evaluate how similar participants viewed each image. To establish an empirical null we compute the correlation between random splits corresponding the different images within the same trial. Additionally,

692 we estimate the bottom-up salience of each image (Itti et al., 1998) and compute the correlation between 692
693 this bottom-up salience map and the random splits associated with each permutation of each image. 693

Supplemental Information

Barense et al. 2007

"High ambiguity" (i.e., MTC dependent) sets   *"Low ambiguity" (i.e., not MTC dependent) sets*

"Familiar" objects   *"Novel" objects*   *"Familiar" objects*   *"Novel" objects*

Majaj et al. 2015

"Animals"   *"Chairs"*   *"Planes"*   *"Faces"*

Figure S5: Example stimuli from Barense et al., 2007 & Majaj et al., 2015

Time unrestricted

Figure S6: Visualization of experimental designs used throughout manuscript

Figure S7: Self-paced match-to-sample performance on stimuli from Majaj et al., 2015

Figure S8: Self-paced match-to-sample performance on stimuli from Barense et al., 2007

Figure S9: Examples of trial-level gaze data, alongside group average to this same image.