Independent allocentric and egocentric reference frame encoding of person knowledge within the brains of social groups

Robert S. Chavez, Taylor D. Guthrie, and Jack M. Kaptuska

Department of Psychology, University of Oregon, Eugene, Oregon, USA

Humans spontaneously infer information about others to perceive the similarity in behaviors and traits among people in our social environments. However, evaluating the similarity among people can be achieved through multiple frames of reference: other-to-other differences (allocentric similarity) or self-to-other differences (egocentric similarity), which are difficult to dissociate with behavioral measures alone. Here, we use functional magnetic resonance imaging to test whether the similarity of brain response patterns when thinking of others and the self is predicted by models of allocentric and egocentric similarity in the trait-judgments of well-acquainted peers from 20 independent groups of people (total N = 108; within-subject design). Results show that both allocentric and egocentric similarity during person representation are reflected in brain response similarity patterns when thinking of others but do so differentially and in non-overlapping brain systems. Specifically, allocentric similarity was positively related to brain similarity patterns in distributed regions involved in social cognition as well as in regions involved in general non-social spatial reference frame encoding. Egocentric similarity was inversely related to brain response similarity but only within dorsal regions of the medial prefrontal cortex and anterior cingulate, suggesting that activation within this region is important for dissociating self-representation from that of similar others. These results suggest that the brain processes both kinds of reference frames independently to encode trait information about conspecifics that we use to represent person knowledge about other people within real-world social networks.

person knowledge | fMRI | reference frames | social cognition

Correspondence: *rchavez@uoregon.edu*

NOTE: The current manuscript is a preprint and may not fully reflect the final version of the paper.

Humans live, work, and play among people with a variety of dispositions and reputations within our social environments. Understanding the traits, behaviors, and individual characteristics of other people—a process of generating what is called person knowledge (Anzellotti & Young, 2020)—within our social networks is important for establishing friendships (Byrne, 1969), reducing conflict and uncertainty (Kets & Sandroni, 2019), and promoting cooperation (Schroeder et al., 2015) and collaboration towards shared goals. Despite relying on a variety of high-level information processing, human social cognition is fast and spontaneous. Within seconds (Ambady & Rosenthal, 1993), people can automatically ascribe trait characteristics to others that

are highly correlated with independent judgements at longer timescales and predict real-world outcomes (Todorov et al., 2005) without explicit impression formation goals (Winter & Uleman, 1984). These capacities form the basis of our ability to encode person knowledge that we use to maintain lasting impressions of the people with whom we interact regularly and have the potential to significantly impact our daily lives.

When using person knowledge to represent information about other people in social contexts, it is useful to know the similarity among individuals within a group. For instance, if two coworkers share many of the same traits or characteristics (e.g., both are quiet but hard working), it may be cognitively efficient to mentally represent information about them more similarly than we would if they did not share these characteristics (Macrae et al., 1994). Likewise, if we perceive someone as being similar to ourselves, we will anchor on our own attitudes when considering the preferences of others (Tamir & Mitchell, 2010) which simplifies elements of social judgment and decision making (Tamir & Mitchell, 2012). Thus, previous research indicates that we use information about a person's similarity to others as well as their similarity to ourselves when we are generating a mental representation of their traits and behaviors. However, it is unclear whether these two ways of representing person knowledge are processed independently of one another or if they are just different operations of the same social cognitive system.

To better understand whether these two processes represent fundamentally distinct models of how we represent information about others, it is useful to consider an analogous framework from the study of distance processing in spatial cognition. Here, researchers use the concept of reference frames to describe the location of objects in physical space. Put simply, reference frames are means of describing the structure of the location of entities in space based on their relationships to other entities (Klatzky, 1998). In research on spatial perception, the two most commonly used reference frames are allocentric distance and egocentric distance. Allocentric distance describes the distances between each pair of objects within a given set. Egocentric distance identifies a particular object as the reference point origin and describes the distance between that object and each of the other objects within a set. Spatial reference frames have been a fruitful framework for studying navigation (Gramann et al., 2010), memory (Byrne et al., 2007), and computer vision

(Henriques & Vedaldi, 2018). Moreover, because allocentric and egocentric reference frames have a formal mathematical distinction, this framework has been useful in modeling brain activity for identifying shared and distinct systems for processing allocentric and egocentric distance in the underlying neurobiological mechanisms supporting each of these processes in humans (Wang, 2012; Zaehle et al., 2007) and non-human animals (Poulter et al., 2018; Rinaldi et al., 2020).

The utility of allocentric and egocentric reference frames can be directly applied to the study of social cognition where there is quantitative information about both the self and others within a group of people. Applying this framework to the domain of person knowledge, subjective ratings of the traits and characteristics of others and the self can serve as the basis of the coordinate systems where allocentric similarity describes the other-to-other differences and egocentric similarity describes self-to-other differences among a group of people. However, unlike spatial cognition, there is no objective ground-truth in person knowledge measures which are typically assessed through self-report ratings. Instead, researchers studying accuracy and agreement interpersonal perception have made progress by aggregating responses among a set of raters to generate consensus-like judgments across participants (Kolar et al., 1996; McCrae & Costa, 1987). Previous research has demonstrated that consensus judgments of targets are better predictors of brain activity patterns than individual ratings (Knutson & Genevsky, 2018) in some domains (e.g. affective responses during decision making) responses but less accurate in others (e.g. face-selective cortical areas; Kanwisher, 2017; Saygin et al., 2012). As such, it remains an open question whether an individual's within-perceiver judgements or aggregated group-consensus responses are a better model of how person knowledge is represented in the brains of individuals when they are considering the thoughts and behaviors of other people within their social groups.

The current study is designed to identify brain systems that represent information about other people based on either allocentric or egocentric reference frames of person knowledge within real-world social groups of well-acquainted others. Here, we successfully recruited 108 individuals from 20 independent groups of peers to make ratings about themselves and each other group using a round-robin design in which every person was both a perceiver and target for every other member of the group. Specifically, participants rated themselves and others on questions related to dimensions of warmth and competence from the stereotype content model (Fiske et al., 2002)—a robust and widely adopted theory of person perception of groups and individuals (Fiske, 2018) and their neural correlates (Thornton & Mitchell, 2018). These ratings were then used to calculate within-perceiver allocentric and egocentric similarity measures among everyone in the group. Furthermore, group-consensus models of allocentric and egocentric similarity were calculated by averaging ratings across all members of the group. In a separate experimental session, the same participants were then scanned using functional magnetic resonance imaging (fMRI) while they completed a round-robin version of a standard trait-judgment task used to elicit mental representations of the self and others. Both subjective and consensus versions of each reference frame were then used as models of representational similarity that were compared against similarity of fMRI multivoxel brain responses patterns within the brains of participants when they were thinking of each other member of their group (see Fig. 1 for a general schematic of the approach). These analyses provide a means of identifying both shared and distinct neural systems in which representations of fellow group members are captured, simultaneously, by each reference frame of person knowledge during interpersonal perception, informing our understanding of reference frames for person perception and the brian systems that support these processes.

Methods

Participants.
A total of 120 right-handed participants were recruited from 20 independent real-world social groups in the University of Oregon and local Eugene community, including student organizations, local business employees, and friend groups. Participants ranged in age from 18 to 51 (M = 23.5, SD = 7.2). A majority of participants identified as White or Caucasian (77.9%), 4.4% identified as Black or African American, 2.7% identified as Asian, 1.8% identified as American Indian or Alaska Native, 1.8% identified as Native Hawaiian or Pacific Islander, 9.7% identified as more than one race, and 1.8% chose not to identify their race. A majority of participants identified as non-Hispanic (84.1%). Six people were recruited from each of the 20 groups, and all participants within each group were familiar with one another. Across all groups, five participants failed to fulfill scheduled experimental session appointments, two subjects were excluded due to poor quality imaging data, and five subjects were excluded for missing or incomplete behavioral data. This left a final N = 108 subjects in the final sample used for all analyses. All participants were screened for magnetic resonance imaging contraindications and had normal or corrected-to-normal vision. Each participant in the study participated in two sessions. The first was a behavioral ratings session in which participants filled out a series of questionnaires for themselves and their group members. The second session consisted of a scanning session in which participants completed trait judgments for themselves and their peers while undergoing fMRI . Participants gave informed consent in both sessions in accordance with the guidelines set by the Internal Review Board at the University of Oregon and were compensated for their participation following each session of the study.

Behavioral Rating Task.
All reference frame models were calculated using item-wise responses of warmth and competence ratings of every target (including self ratings) per participant within each group. To this end, target ratings were flattened into one-dimensional

Fig. 1. Design and analytic framework. A schematic of the approach used in the current study. A) Participants were recruited from twenty independent social groups of six people in a round-robin design in which every participant is both a perceiver and target for every other member of their group. This round-robin design was used for both collecting behavioral ratings as well as measuring brain responses to each target. **B)** Allocentric similarity describes the distance in behavioral ratings among other members of a perceiver's group. Egocentric similarity describes the distance in behavioral ratings between the perceiver and every other member of their group. Allocentric and egocentric reference frames were calculated using euclidean distances in behavioral ratings of measures of warmth and competence of others and the self within each group. **C)** Brain activity for each target and the self were measured using functional magnetic resonance imaging within each participant. Multivoxel response patterns for each target and the self were then used to calculate within 600 cortical parcels to estimate the brain response similarity among each target. Behavioral models of allocentric and egocentric similarity were then compared to brain response similarity using a multilevel model representational similarity analysis to identify regions that were significantly associated with each reference frame within each participant.

response vectors that were then used to calculate the total euclidean distance among ratings for each target within each participant. Euclidean distance was used for behavioral measures because it captures both the direction and magnitude of the similarity among items, akin to spatial reference frames. For ease of interpretation, we use the term 'similarity' to describe the inverse of the euclidean distance metrics, such that smaller distances are equivalent to greater similarity. Unlike spatial reference frames which have an objective criterion to establish distances among objects, reference frames of person knowledge are subjective and can be calculated according to judgements within the perceiver or via aggregated group consensus ratings. The round-robin design used in the current study allows for reference frame calculation both within-perceivers (i.e. within the person whose brain activity is being measured) and those averaged across fellow group members. This provides a means by which to know if group-consensus ratings provide a better model of a participant's brain representation of target similarities than those based on the participant's own subjective ratings, which may be biased or less accurate.

For the allocentric reference frame, within-perceiver similarity among targets was calculated based on that par-

ticipants own ratings of the targets (i.e. the other members of their group) to generate a similarity matrix among all other members of the group. Group-consensus target similarity was calculated by averaging scores across items per target and recalculating distances among people within each group. Importantly, neither the perceiver's trait ratings nor the individual target's self-judgements were included in the aggregated results to avoid contaminating aggregated results with bias from either the target or perceiver.

Egocentric reference frames were calculated as the distance between ratings of the self and ratings of others. As with the allocentric reference frame, within-perceiver similarity was calculated using the ratings of the self from each participant against their ratings of all of their fellow group members. Unlike the allocentric reference frames, there are two different ways to calculate group-consensus responses for egocentric similarity. The first calculates the similarity participant's ratings of the self against group-aggregated responses of each target. The second calculates both group-aggregated ratings of the perceiver and group-aggregated ratings of the target. As with the allocentric reference frame, neither the perceiver's trait ratings nor the individual target's self-ratings were included in the group-aggregated calcula-

tions.

Reference Frame Calculation.

All reference frame models were calculated using item-wise responses of warmth and competence ratings of every target (including self ratings) per participant within each group. To this end, target ratings were flattened into one-dimensional response vectors that were then used to calculate the total euclidean distance among ratings for each target within each participant. Euclidean distance was used for behavioral measures because it captures both the direction and magnitude of the similarity among items, akin to spatial reference frames. For ease of interpretation, we use the term 'similarity' to describe the inverse of the euclidean distance metrics, such that smaller distances are equivalent to greater similarity. Unlike spatial reference frames which have an objective criterion to establish distances among objects, reference frames of person knowledge are subjective and can be calculated according to judgements within the perceiver or via aggregated group consensus ratings. The round-robin design used in the current study allows for reference frame calculation both within-perceivers (i.e. within the person whose brain activity is being measured) and those averaged across fellow group members. This provides a means by which to know if group-consensus ratings provide a better model of a participant's brain representation of target similarities than those based on the participant's own subjective ratings, which may be biased or less accurate.

For the allocentric reference frame, within-perceiver similarity among targets was calculated based on that participants own ratings of the targets (i.e. the other members of their group) to generate a similarity matrix among all other members of the group. Group-consensus target similarity was calculated by averaging scores across items per target and recalculating distances among people within each group. Importantly, neither the perceiver's trait ratings nor the individual target's self-judgements were included in the aggregated results to avoid contaminating aggregated results with bias from either the target or perceiver.

Egocentric reference frames were calculated as the distance between ratings of the self and ratings of others. As with the allocentric reference frame, within-perceiver similarity was calculated using the ratings of the self from each participant against their ratings of all of their fellow group members. Unlike the allocentric reference frames, there are two different ways to calculate group-consensus responses for egocentric similarity. The first calculates the similarity participant's ratings of the self against group-aggregated responses of each target. The second calculates both group-aggregated ratings of the perceiver and group-aggregated ratings of the target. As with the allocentric reference frame, neither the perceiver's trait ratings nor the individual target's self-ratings were included in the group-aggregated calculations.

Neuroimaging Data Acquisition.

Magnetic resonance imaging was conducted with a Siemens 3T Skyra scanner using a 32-channel phased array coil.

Structural images were acquired using a T1-weighted MP-RAGE protocol (175 sagittal slices; TR: 2500 ms; TE: 3.43 ms; flip angle: 7°; 1 mm isotropic voxels). Functional images were acquired using a T2*-weighted echo planar sequence (TR: 2000 ms; 72 axial slices; TE: 25 ms; flip angle: 90°; 2 mm isotropic voxels). For each participant, we collected five runs of the round-robin task (188 whole brain volumes per run). In order to correct for distortion due to B0 inhomogeneity we also acquired a field map (TR: 6390 ms; TE: 47.8 ms; effective echo spacing: 0.345 ms). The total length of time for the entire scanning session was approximately 75 minutes and each functional run was approximately 6 minutes long.

Neuroimaging Trait Judgement Task.

In a separate session, participants were brought back to the lab to complete the fMRI portion of the experiment. While in the scanner, participants were asked to complete a standard trait-judgment task widely used in the study of self and other processing (Chavez et al., 2017; Kelley et al., 2002; Mitchell et al., 2011). As with the behavioral ratings, we employed a round-robin design in which each participant in the study was both a perceiver and target stimulus for every other participant within their group. Participants were presented with a screen containing two words arranged vertically consisting of white text on a black background. For each trial, the top word displayed either "Self" or the name of one of the other five group members from the same group that the perceiver belonged to. Each perceiver indicated during the behavioral session what name they used most frequently when referring to each of their group members (e.g. "Robert" may have been changed to "Rob" or the nickname "Bean" for the fMRI portion). These names were then used in the fMRI portion to avoid confusion about which person each perceiver was making trait-judgements about for each trial. The bottom word displayed one of 60 valence-balanced trait adjectives (e.g. "Happy", "Clumsy", "Smart"; Anderson, 1968) for 2000 ms followed by 2000 ms of fixation and intermittent passive fixation trials (2000-12000 ms). Jittered trials were optimized using Opseq2 (Dale, 1999). Participants were asked to make either a "yes" or "no" response using a button box in their right hand as to whether or not the trait adjective described either themselves or one of their group members. All targets were presented in each run, and there were a total of twelve trials per target per run in which each target was presented with the same 12 trait-adjectives per run. The same targets were then used in each subsequent run but were then paired with a new set of 12 trait-adjectives in each one resulting in all targets being paired with all 60 trait-adjectives. Individual traits were only presented once per target randomly across all runs in the experiment. No two participants were presented with the same target/trait-adjective order across the experiment to account for potential order effects.

Neuroimaging Preprocessing and Response Pattern Estimation.

Functional imaging data for the fMRI task were preprocessed and voxel responses estimated using FSL (Smith et

al., 2004). Data were processed using mean-based intensity normalization, high pass filtering (Gaussian-weighted least-squares straight line fitting, with sigma = 100s), and spatially smoothed with a 4mm FWHM Gaussian smoothing kernel. A multi-step normalization procedure was used to register results to standard space. First, functional data were corrected for spatial distortion using a field map unwarping before aligning functional data to each participant's anatomical scan using boundary-based registration (Greve & Fischl, 2009) in conjunction with a linear registration with FSL's FLIRT tool. These images were then warped to a 2mm MNI template using nonlinear registration with FSL's FNIRT tool and a 10mm warp field. All first level task-based analyses were performed in native space before being warped into standard space for final analyses. Parameter estimates were calculated for each participant's five group members in each of the five runs. These responses were then combined in a second-level within-subject fixed-effects analysis to produce parameter estimates for each of the five group members' "target" conditions. Normalized (i.e. z-score) voxel responses for each condition were extracted from each parcel of the 600 regions in the Schaefer parcellation atlas (Schaefer et al., 2018). Consistent with previous studies using fMRI to estimate multivariate similarity patterns (Kriegeskorte, 2008; Thornton & Mitchell, 2018), we used Spearman rank correlation distance metric (e.g., 1 - Spearman-rho) to compute the dissimilarity between neural response patterns during trials among each of the conditions (i.e. the self and each of the other people in the group) using tools from the nilearn package in Python (Abraham et al., 2014). These values were used as the estimates of neural similarity in each brain parcel that was then compared against the behavioral reference frame models (Figure 1c).

Statistical Modeling.
Behaviorally measured allocentric and egocentric reference frame similarity models were related to neural similarity measures at every parcel within each participant using a representational similarity analysis (Kriegeskorte, 2008). Allocentric similarity was modeled based on both within-perceiver and group-consensus ratings for targets. Egocentric similarity was modeled using within-perceiver ratings, group-consensus ratings for the target, and group-consensus ratings of both the perceiver and targets. For each reference frame, we fit a nested multilevel model using each behavioral similarity as a predictor of brain responses similarity within nested random intercepts for each participant within each group using the lme4 package in R (Bates et al., 2015). Significance of each model was calculated using Satterthwaite estimated p-values for every parcel (Kuznetsova et al., 2017). Finally, whole-brain significance tests were corrected for multiple comparisons using false discovery rate (FDR) across all parcels.

Results

Allocentric Similarity.
To increase the interpretability and transparency of the re-sults, distributions of the behavioral measures and unthresholded statistical maps for the allocentric similarity analyses are shown in Figure 2a. There was a greater degree and wider distribution of allocentric distance values for within-perceiver effects (M = 4.82, SD = 1.89) than group-consensus for targets values (M = 3.45 , SD = 1.11). Across the brain, within-perceiver models showed more consistent brain-behavior associations than group-consensus models. Unthresholded results were most pronounced in lateral prefrontal cortex and cortical midline structures from the default mode network.

Egocentric Similarity.
As with the allocentric reference frame results, behavioral distributions and unthresholded statistical maps from each of the egocentric similarity analyses are shown in Figure 2b. Unlike the allocentric reference frame results, distributions of ratings were similar between within-perceiver (M =4.82 , SD = 1.78) and group-consensus for targets (M = 4.87, SD = 1.10). Group-consensus for targets and perceivers distance ratings were generally lower than the other two models (M = 3.30, SD = 1.23). Consistent with the results from the allocentric similarity analyses, only the within-perceiver effects showed brain-behavioral associations in multiple regions. In general, the results from the egocentric reference frame analyses were less distributed than the allocentric results and were mostly found in dorsal medial prefrontal cortical regions as well as some lateral prefrontal areas.

Non-overlapping Neural Representations of Person Knowledge Reference Frames.
Results for the within-perceiver ratings after correcting for multiple comparisons for both allocentric and egocentric reference frames are shown in Figure 3. From these results, we found a positive relationship between multivoxel similarity patterns and behavioral allocentric similarity in parts of the brain areas previously implicated in social cognition such as the posterior cingulate cortex, ventromedial prefrontal cortex, and lateral orbitofrontal cortex. There were also significant results found in areas previously implicated in spatial allocentric references frame encoding (Zaehle et al., 2007), such as the inferior and superior frontal gyri and lateral occipital cortex. A table of all significant regions from the allocentric reference frame analysis can be found in Supplementary Table 1. There were no significant regions from the allocentric reference frame analysis that showed an inverse relationship to the behavioral similarity measures.

From the egocentric reference frames results, we found a significant relationship between multivoxel similarity patterns and behavioral egocentric similarity primarily within medial prefrontal regions including the dorsal medial prefrontal cortex and dorsal anterior cingulate cortex. A table of all significant regions from the egocentric reference frame analysis can be found in Supplementary Table 2. Importantly, all of the significant regions from the egocentric reference frame analysis showed an inverse relationship to the behavioral measures, such that greater egocentric similarity was related to less similar neural representations in these regions.

Fig. 2. Unthresholded brain maps of reference frame representation. The distribution of behaviorally measured distance values for each reference frame and their associated unthresholded p-values from the fMRI representational similarity analysis. **A)** Allocentric distances among targets were calculated using both within-perceiver ratings and aggregated group-consensus ratings. Across the brain, within-perceiver ratings of allocentric similarity showed better model fit against neural similarity measures than the group-consensus ones, including within the default mode network and other areas implicated in social cognition. **B)** Egocentric distances were calculated using within-perceiver ratings, aggregated group-consensus ratings of only the targets against self-reported ratings from the perceiver, and aggregated group-consensus ratings of both the targets and the perceiver. Consistent with the allocentric results, the within-perceiver model of egocentric similarity showed better model fit against the neural similarity measures than either group-consensus models, particularly within prefrontal cortical regions.

Finally, there were no significant results found after correcting for multiple comparisons for any of the group-consensus results across both reference frames. This suggests that subjective ratings from each participant were a better match to their own brain representations of group members than were ratings aggregated across fellow group members.

Discussion

There are multiple ways humans can represent information about others that contribute to how we think of and interact with people in our social environments. In the current study, we adapted the notion of spatial allocentric and egocentric reference frames to measures of person knowledge to study how the brain represents information about other-to-other similarities and self-to-other similarities. To this end, we used a novel round-robin design for both behavioral and fMRI paradigms to relate models of person knowledge similarity to neural similarity during interpersonal perception within multiple real-world social groups. Our results show that both allocentric similarity and egocentric similarity are related to measures of neural similarity, but that they did so separately with no overlap in the regions implicated for each reference frame. This suggests that reference frames for per-

son knowledge are processed independently and concurrently and not as two different modes of a single social cognitive system.

The results from the allocentric reference frame implicated a variety of brain regions involved both social cognition as well as in areas that have been associated with spatial reference processing. Our results are consistent with a large body of work has implicated areas within the default mode network, including the ventral medial prefrontal context and posterior cingulate cortex in processing information about other people (Denny et al., 2012; Wagner et al., 2012) and in representing similarities among famous individuals (Thornton & Mitchell, 2018). Our results build on these previous findings to show the similarity of brain responses between real-world group members track with similarity major dimensions of person perception, namely assessments of warmth and competence among peers. Furthermore, our findings overlap with previous research that has also shown that brain regions such as the lateral occipital cortex, inferior frontal gyrus, and precuneus are involved in processing spatial allocentric distances (Galati et al., 2010; Zaehle et al., 2007). Together with these previous findings, our results are consistent with the idea that these regions which are engaged in

allocentric similarity   egocentric similarity

Fig. 3. Non-overlapping regions reflecting reference frames of person knowledge. Thresholded FDR-corrected p-value maps of the significant areas from the within-perceiver allocentric similarity and egocentric similarity analyses. Brain and behavior allocentric similarity showed a positive relationship across a variety of regions involved in distance perception and social cognition, including the precuneus and ventral medial prefrontal cortex. Brain and behavior egocentric similarity showed an inverse relationship in regions of the the dorsal medial prefrontal cortex and anterior cingulate. There were no significant regions in which both allocentric similarity and egocentric similarity showed a significant relationship to the behavioral models of either reference frame.

spatio-temporal processes compute context general information that can be repurposed within social contexts (Parkinson & Wheatley, 2015). Overall, the results of this study suggest that allocentric similarity is computed across broadly distributed cortical regions involved both in both person perception and general distance processing.

The results from the egocentric reference frame analyses were different from the allocentric ones in a few important ways. First, brain regions related to egocentric reference frames were much less distributed, with results primarily located within the dorsal medial prefrontal cortex and anterior cingulate cortex but also within the rostrolateral orbitofrontal cortex. These regions have been implicated in a variety of social cognitive tasks that involve social comparisons in close-others (Hughes & Beer, 2012), self/other anchoring during mentalizing (Tamir & Mitchell, 2010), and thinking of others with similar preferences (Mitchell et al., 2006) and were based on standard univariate responses magnitude metrics. Critically, our findings also showed that multivariate similarity of neural and behavioral measures for the egocentric similarity were inversely related to one another, such that the more similar a participant rated one of their peers, the more dissimilar their neural representation of that person was using our multivariate framework. This suggests that when people are using these brain systems to reflect person knowledge about similar others, part of what these systems are doing is engaging processes that also allow people to maintain a differentiation between others and the self. This interpretation

is consistent with the view that a heightened or more distinguishable view of conspecifics from the self may allow a person to think about the mental states of others without confusing the source of those thoughts and feelings (de Waal, 2008), which may be critical for processes related to empathy in primates (de Waal & Preston, 2017). Thus, at least when it comes to dissociating person knowledge of the self from similar others, these parts of the brain may be engaged not to underscore the shared aspects of those representations but instead to ensure that we can maintain a cognitive separation of the self from group members with whom we have much in common.

The round-robin design used in the current study uniquely allowed us to measure each reference frame model based on subjective within-perceiver ratings of behavioral similarity as well as group-consensus ratings aggregated among fellow participants. This allowed us to test the possibility that group-consensus reference frames would predict neural similarity within each perceiver differentially than within-perceiver ones. These analyses are critical because, unlike spatial reference frames, there is no objective way to define person knowledge similarity, and there may be potential issues with relating brain response similarity patterns to behavioral similarity metrics based on ratings that can be prone to self-serving or otherwise biased reporting. However, across both reference frames, we found no evidence that group-consensus behavioral ratings of any kind showed a superior relationship to the neural similarity measures. To the

degree that within-perceiver ratings are prone to reporting biases, our results suggest that these biases are more consistent with how their brain is representing information about person knowledge than are those based on others' ratings of the same target. Put differently, even if self-reports can be biased against an agreed upon social landscape, they may be reflecting honest interpretations of subjective similarities among people within our social groups within our own brains.

Conclusions.

By integrating an interdisciplinary set of well-supported empirical models and methodological approaches, this study has theoretical implications for both cognitive neuroscience and social psychology. The results from our fMRI analysis indicate that independent regions known to be involved in various aspects of social cognition also process information about the differences among others as well as the differences between ourselves and others. Additionally, for the allocentric reference frame, we show that brain regions that are involved in more general cognitive distance processing also compute relevant information to person knowledge. For the egocentric reference frame, our results challenge assumptions about what information is being computed within brain regions when engaged in processing information concerning the differences between the self and others. Furthermore, our results inform social psychological theorizing by suggesting that our perception of other-to-other differences and self-to-other differences rely on independent social cognitive systems that may operate under different rules. To the degree that a social psychological theory posits that a manipulation or change in one reference frame implies a change in the other, our results suggest that this may not be the case and may offer a model for future investigations.

In summary, our results show that the brain independently processes both allocentric and egocentric reference frames of person knowledge among real-world groups of people. These findings contribute to our understanding of how the brain processes information about the self in social contexts which is central to our lives as richly sentient members of a fundamentally social species.

ACKNOWLEDGEMENTS
Research funded by University of Oregon.

OPEN SCIENCE PRACTICES
Data, materials, and code used to generate the findings in this study will be available prior to peer review via the Open Science Framework.

References

Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J., Gramfort, A., Thirion, B., & Varoquaux, G. (2014). Machine learning for neuroimaging with scikit-learn. Frontiers in Neuroinformatics, 8. https://doi.org/10.3389/fninf.2014.00014

Ambady, N., & Rosenthal, R. (1993). Half a minute: Predicting teacher evaluations from thin slices of nonverbal behavior and physical attractiveness. Journal of Personality and Social Psychology, 64(3), 431–441. https://doi.org/10.1037/0022-3514.64.3.431

Anderson, N. H. (1968). Likableness ratings of 555 personality-trait words. Journal of Personality and Social Psychology, 9(3), 272–279.

Anzellotti, S., & Young, L. L. (2020). The Acquisition of Person Knowledge. Annual Review of Psychology, 71(1), 613–634. https://doi.org/10.1146/annurev-psych-010419-050844

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models Using lme4. Journal of Statistical Software, 67, 1–48. https://doi.org/10.18637/jss.v067.i01

Byrne, D. (1969). Attitudes and Attraction. In L. Berkowitz (Ed.), Advances in Experimental Social Psychology (Vol. 4, pp. 35–89). Academic Press. https://doi.org/10.1016/S0065-2601(08)60076-3

Byrne, P., Becker, S., & Burgess, N. (2007). Remembering the past and imagining the future: A neural model of spatial memory and imagery. Psychological Review, 114(2), 340–375. https://doi.org/10.1037/0033-295X.114.2.340

Chavez, R. S., Heatherton, T. F., & Wagner, D. D. (2017). Neural Population Decoding Reveals the Intrinsic Positivity of the Self. Cerebral Cortex, 27(11), 5222–5229. https://doi.org/10.1093/cercor/bhw302

Dale, A. M. (1999). Optimal experimental design for event-related fMRI. Human Brain Mapping, 8(2–3), 109–114. https://doi.org/10.1002/(SICI)1097-0193(1999)8:2/3<109::AID-HBM7>3.0.CO;2-W

de Waal, F. B. M. (2008). Putting the Altruism Back into Altruism: The Evolution of Empathy. Annual Review of Psychology, 59(1), 279–300. https://doi.org/10.1146/annurev.psych.59.103006.093625

de Waal, F. B. M., & Preston, S. D. (2017). Mammalian empathy: Behavioural manifestations and neural basis. Nature Reviews Neuroscience, 18(8), Article 8. https://doi.org/10.1038/nrn.2017.72

Denny, B. T., Kober, H., Wager, T. D., & Ochsner, K. N. (2012). A meta-analysis of functional neuroimaging studies of self- and other judgments reveals a spatial gradient for mentalizing in medial prefrontal cortex. Journal of Cognitive Neuroscience, 24(8), 1742–1752. https://doi.org/10.1162/jocn$_a$0233

Fiske, S. T. (2018). Stereotype Content: Warmth and Competence Endure. Current Directions in Psychological Science, 27(2), 67–73. https://doi.org/10.1177/0963721417738825

Fiske, S. T., Cuddy, A. J. C., Glick, P., & Xu, J. (2002). A model of (often mixed) stereotype content: Competence and warmth respectively follow from perceived status and competition. Journal of Personality and Social Psychology, 82(6), 878–902. https://doi.org/10.1037/0022-3514.82.6.878

Galati, G., Pelle, G., Berthoz, A., & Committeri, G. (2010). Multiple reference frames used by the human brain for spatial perception and memory. Experimental Brain Research, 206(2), 109–120. https://doi.org/10.1007/s00221-010-2168-8

Gramann, K., Onton, J., Riccobon, D., Mueller, H. J., Bardins, S., & Makeig, S. (2010). Human Brain Dynamics Accompanying Use of Egocentric and Allocentric Reference Frames during Navigation. Journal of Cognitive Neuroscience, 22(12), 2836–2849. https://doi.org/10.1162/jocn.2009.21369

Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-based registration. NeuroImage, 48(1), 63–72. https://doi.org/10.1016/j.neuroimage.2009.06.060

Guthrie, T. D., Benadjaoud, Y. Y., & Chavez, R. S. (2022). Social Relationship Strength Modulates the Similarity of Brain-to-Brain Representations of Group Members. Cerebral Cortex, 32(11), 2469–2477. https://doi.org/10.1093/cercor/bhab355

Henriques, J. F., & Vedaldi, A. (2018). MapNet: An Allocentric Spatial Memory for Mapping Environments. 8476–8484.

Hughes, B. L., & Beer, J. S. (2012). Orbitofrontal Cortex and Anterior Cingulate Cortex Are Modulated by Motivated Social Cognition. Cerebral Cortex, 22(6), 1372–1381. https://doi.org/10.1093/cercor/bhr213

Kanwisher, N. (2017). The Quest for the FFA and Where It Led. Journal of Neuroscience, 37(5), 1056–1061. https://doi.org/10.1523/JNEUROSCI.1706-16.2016

Kelley, W. M., Macrae, C. N., Wyland, C. L., Caglar, S., Inati, S., & Heatherton, T. F. (2002). Finding the self? An event-related fMRI study. Journal of Cognitive Neuroscience, 14(5), 785–794.

Kets, W., & Sandroni, A. (2019). A belief-based theory of homophily. Games and Economic Behavior, 115, 410–435. https://doi.org/10.1016/j.geb.2019.04.002

Klatzky, R. L. (1998). Allocentric and Egocentric Spatial Representations: Definitions, Distinctions, and Interconnections. In C. Freksa, C. Habel, & K. F. Wender (Eds.), Spatial Cognition: An Interdisciplinary Approach to Representing and Processing Spatial Knowledge (pp. 1–17). Springer. https://doi.org/10.1007/3-540-69342-4_1

Knutson, B., & Genevsky, A. (2018). Neuroforecasting Aggregate Choice. Current Directions in Psychological Science, 27(2), 110–115. https://doi.org/10.1177/0963721417737877

Kolar, D. W., Funder, D. C., & Colvin, C. R. (1996). Comparing the accuracy of personality judgements by the self and knowledgeable others. Journal of Personality, 64(2), 311–337.

Kriegeskorte, N. (2008). Representational similarity analysis – connecting the branches of systems neuroscience. Frontiers in Systems Neuroscience. https://doi.org/10.3389/neuro.06.004.2008

Kuznetsova, A., Brockhoff, P. B., & Christensen, R. H. B. (2017). lmerTest Package: Tests in Linear Mixed Effects Models. Journal of Statistical Software, 82, 1–26. https://doi.org/10.18637/jss.v082.i13

Macrae, C. N., Milne, A. B., & Bodenhausen, G. V. (1994). Stereotypes as energy-saving devices: A peek inside the cognitive toolbox. Journal of Personality and Social Psychology, 66(1), 37–47. https://doi.org/10.1037/0022-3514.66.1.37

McCrae, R. R., & Costa, P. T. (1987). Validation of the Five-Factor Model of Personality Across Instruments and Observers. Journal of Personality and Social Psychology, 52(1), 81–90. https://doi.org/10.1037/0022-3514.52.1.81

Mitchell, J. P., Macrae, C. N., & Banaji, M. R. (2006). Dissociable Medial Prefrontal Contributions to Judgments of Similar and Dissimilar Others. Neuron, 50(4), 655–663. https://doi.org/10.1016/j.neuron.2006.03.040

Mitchell, J. P., Schirmer, J., Ames, D. L., & Gilbert, D. T. (2011). Medial prefrontal cortex predicts intertemporal choice. Journal of Cognitive Neuroscience, 23(4), 857–866. https://doi.org/10.1162/jocn.2010.21479

Parkinson, C., & Wheatley, T. (2015). The repurposed social brain. Trends in Cognitive Sciences, 19(3), 133–141. https://doi.org/10.1016/j.tics.2015.01.003

Peirce, J., Gray, J. R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., & Lindeløv, J. K. (2019). PsychoPy2: Experiments in behavior made easy. Behavior Research Methods, 51(1), 195–203. https://doi.org/10.3758/s13428-018-01193-y

Poulter, S., Hartley, T., & Lever, C. (2018). The Neurobiology of Mammalian Navigation. Current Biology, 28(17), R1023–R1042. https://doi.org/10.1016/j.cub.2018.05.050

Rinaldi, A., De Leonibus, E., Cifra, A., Torromino, G., Minicocci, E., De Sanctis, E., López-Pedrajas, R. M., Oliverio, A., & Mele, A. (2020). Flexible use of allocentric and egocentric spatial memories activates differential neural networks in mice. Scientific Reports, 10(1), Article 1. https://doi.org/10.1038/s41598-020-68025-y

Saygin, Z. M., Osher, D. E., Koldewyn, K., Reynolds, G., Gabrieli, J. D. E., & Saxe, R. R. (2012). Anatomical connectivity patterns predict face selectivity in the fusiform gyrus. Nature Neuroscience, 15(2), Article 2. https://doi.org/10.1038/nn.3001

Schaefer, A., Kong, R., Gordon, E. M., Laumann, T. O., Zuo, X.-N., Holmes, A. J., Eickhoff, S. B., & Yeo, B. T. T. (2018). Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic Functional Connectivity MRI. Cerebral Cortex, 28(9), 3095–3114. https://doi.org/10.1093/cercor/bhx179

Schroeder, K. B., Nettle, D., & McElreath, R. (2015). Interactions between personality and institutions in cooperative behaviour in humans. Philosophical Transactions of the Royal Society B: Biological Sciences, 370(1683), 20150011. https://doi.org/10.1098/rstb.2015.0011

Smith, S. M., Jenkinson, M., Woolrich, M. W., Beckmann, C. F., Behrens, T. E. J., Johansen-Berg, H., Bannister, P. R., De Luca, M., Drobnjak, I., Flitney, D. E., Niazy, R. K., Saunders, J., Vickers, J., Zhang, Y., De Stefano, N., Brady, J. M., & Matthews, P. M. (2004). Advances in functional and structural MR image analysis and implementation as FSL. NeuroImage, 23, S208–S219.

https://doi.org/10.1016/j.neuroimage.2004.07.051

Tamir, D. I., & Mitchell, J. P. (2010). Neural correlates of anchoring-and-adjustment during mentalizing. Proceedings of the National Academy of Sciences of the United States of America, 107(24), 10827–10832. https://doi.org/10.1073/pnas.1003242107

Tamir, D. I., & Mitchell, J. P. (2012). Anchoring and Adjustment During Social Inferences. Journal of Experimental Psychology. General. https://doi.org/10.1037/a0028232

Thornton, M. A., & Mitchell, J. P. (2018). Theories of Person Perception Predict Patterns of Neural Activity During Mentalizing. Cerebral Cortex, 28(10), 3505–3520. https://doi.org/10.1093/cercor/bhx216

Todorov, A., Mandisodza, A. N., Goren, A., & Hall, C. C. (2005). Inferences of Competence from Faces Predict Election Outcomes. Science, 308(5728), 1623–1626. https://doi.org/10.1126/science.1110589

Wagner, D. D., Haxby, J. V., & Heatherton, T. F. (2012). The representation of self and person knowledge in the medial prefrontal cortex. WIREs Cognitive Science, 3(4), 451–470. https://doi.org/10.1002/wcs.1183

Wang, R. F. (2012). Theories of spatial representations and reference frames: What can configuration errors tell us? Psychonomic Bulletin & Review, 19(4), 575–587. https://doi.org/10.3758/s13423-012-0258-2

Winter, L., & Uleman, J. S. (1984). When are social judgments made? Evidence for the spontaneousness of trait inferences. Journal of Personality and Social Psychology, 47(2), 237–252. https://doi.org/10.1037//0022-3514.47.2.237

Zaehle, T., Jordan, K., Wüstenberg, T., Baudewig, J., Dechent, P., & Mast, F. W. (2007). The neural basis of the egocentric and allocentric spatial frame of reference. Brain Research, 1137, 92–103. https://doi.org/10.1016/j.brainres.2006.12.044

Supplementary Information

Independent allocentric and egocentric reference frame encoding of person knowledge within the

brains of social groups

Robert S. Chavez, Taylor D. Guthrie, & Jack M. Kaptuska

Supplementary Table 1

Significant FDR-Corrected Allocentric Reference Frame Parcels

Region	L/R	FDR p-value	Effect	SE
PCC	L	0.00002	0.01280958	0.00231078
dLPFC	R	0.00123156	0.0104022	0.00224668
lateral occipital cortex	R	0.00241534	0.00703432	0.0015997
supramarginal gyrus	L	0.00324419	0.01242147	0.00294669
precuneus	R	0.00324419	0.0112704	0.00266203
caudal lateral OFC	L	0.00692512	0.00979808	0.00247596
lateral frontal pole	R	0.00692512	0.00866058	0.00217094
vMPFC	R	0.00859926	0.00968684	0.00250201
vMPFC	L	0.00879096	0.0073769	0.00192259
dLPFC	L	0.01830332	0.00648131	0.0017889
PCC	L	0.02152272	0.00838311	0.00235813
lateral frontal pole	L	0.02479095	0.00879045	0.00254657
middle frontal gyrus	R	0.02479095	0.00936137	0.00268535
middle frontal gyrus	R	0.02479095	0.00703897	0.00203792
dLPFC	R	0.0277588	0.00663957	0.00195165
motor cortex	L	0.03026941	0.00404952	0.00120523
somatosensory cortex	L	0.03983793	0.00466168	0.00143857
motor cortex	R	0.03983793	0.00871393	0.00269361
mid cingulate cortex	R	0.03983793	0.01100814	0.0034048
lateral inferior frontal gyrus	L	0.04843058	0.00508123	0.00162166
lateral frontal pole	L	0.04843058	0.00796335	0.00253142
lateral frontal pole	R	0.04843058	0.0070218	0.00223053

Supplementary Table 2

Significant FDR-corrected Egocentric Reference FrameParcels

Region	L/R	FDR p-value	Effect	SE
rostral lateral OFC	L	0.01715338	-0.0106508	0.00252199
dMPFC	L	0.04438308	-0.0096417	0.00252184
medial superior frontal cortex	L	0.04684022	-0.0144149	0.00397196
dACC	L	0.04684022	-0.0142081	0.00388152