# Algebraic Invariants for Inferring 4-leaf Semi-Directed Phylogenetic Networks

Samuel Martin[1,2,*], Niels Holtgrefe[3], Vincent Moulton[4], and Richard M. Leggett[2]

[1] European Bioinformatics Institute (EMBL-EBI), Wellcome Genome Campus, Hinxton, Cambridge, CB10 1SD, United Kingdom

[2] Earlham Institute, Norwich Research Park, Norwich, NR4 7UZ, United Kingdom

[3] Delft Institute of Applied Mathematics, Delft University of Technology, Mekelweg 4, 2628CD, Delft, The Netherlands

[4] School of Computing Sciences, University of East Anglia, Norwich Research Park, Norwich, NR4 7TJ, United Kingdom

* To whom correspondence should be addressed. Email: samuel.martin@ebi.ac.uk

**Abstract** A core goal of phylogenomics is to determine the evolutionary history of a set of species from biological sequence data. Phylogenetic networks are able to describe more complex evolutionary phenomena than phylogenetic trees but are more difficult to accurately reconstruct. Recently, there has been growing interest in developing methods to infer semi-directed phylogenetic networks. As computing such networks can be computationally intensive, one approach to building such networks is to puzzle together smaller networks. Thus, it is essential to have robust methods for inferring semi-directed phylogenetic networks on small numbers of taxa. In this paper, we investigate an algebraic method for performing phylogenetic network inference from nucleotide sequence data on 4-leaf semi-directed phylogenetic networks by analysing the distribution of leaf-pattern probabilities. On simulated data, we found that we can correctly identify with high accuracy the

undirected phylogenetic network for sequences of length at least 10kbp. We found

that identifying the semi-directed network is more challenging and requires

sequences of length approaching 10Mbp. We are also able to use our approach to

identify tree-like evolution and determine the underlying tree. Finally, we employ our

method on a real dataset from *Xiphophorus* species and use the results to build a

phylogenetic network.

**Keywords** Phylogenetic network, semi-directed network, phylogenetic invariants,

**1. Introduction**

Phylogenetic networks describe the evolutionary history of taxa where reticulate

evolution events, such as hybridisation and horizontal gene transfer, have occurred

(Bapteste et al. 2013). Biologists are becoming increasingly aware that such events

are common in the evolutionary histories of many species, and so the development

of methods for constructing phylogenetic networks from biological data is an active

area of research.

Over the past decades many methods of phylogenetic network reconstruction

have been suggested. One approach is to infer implicit networks that do not aim to

represent specific biological processes. For example, distance-based methods such

as Neighbor-Net (Bryant, Moulton, 2004) construct split networks directly from a

distance matrix without the need for sequence data. Other methods construct

networks by analysing gene trees (Than et al. 2008), concordance factors (Allman et

al. 2019), or quartets (Grünewald et al. 2013) and attempt to find the "best" network

that displays these. Several maximum parsimony algorithms have also been

developed for phylogenetic networks (Kanna, Wheeler, 2012). An alternative

approach is to place an evolutionary model on an explicit network (where each

vertex in the network represents a biological event or ancestral species), thereby

creating a rooted, directed phylogenetic network. Methods such as maximum

likelihood e.g. (Wen et al. 2018, Lutteropp et al. 2022) or Bayesian inference e.g.

(Zhang et al. 2018) can then be used to determine how well a set of data fits a

certain model and thereby construct a phylogenetic network.

Recently, there has been increasing interest in inferring semi-directed

phylogenetic networks for evolutionary analysis (e.g. (Solís-Lemus, Ané, 2016; Solís-

Lemus, Bastide, 2017; Allman et al. 2019; Gross et al. 2021; Linz, Wicke, 2023)).

These are networks in which only some of the edges are directed, and these

directed edges usually indicate reticulate events (see e.g., Figure 1). Semi-directed

phylogenetic networks can be inferred from sequencing data by maximising a

likelihood function, but for larger networks, performing a full search of the parameter

space of a semi-directed model to determine the parameters that maximise a

likelihood function is often too computationally intensive to be practical. One solution

to this problem is to use pseudolikelihood, which is based on the likelihood formulas

of the 4-taxon subnetworks, as in (Solís-Lemus, Ané, 2016). Another approach is to

build such networks from knowledge of the networks displayed by a small number of

taxa. This approach has been used in the past for trees (e.g., (Schmidt et al. 2002))

as well as explicit networks (Oldman et al. 2016) and more recently for semi-directed

networks (Huebler et al. 2019; Allman et al. 2024; Frohn et al. 2025; Holtgrefe et al.

2025). One of the key challenges to this approach is to accurately determine each

subnetwork displayed by small numbers of taxa. Here, we attempt to address this

challenge.

**Figure 1**. A semi-directed network with eight leaves, labelled by *Xiphophorus*

species, constructed from Figure 10 of (Solís-Lemus, Ané, 2016).

For phylogenetic trees, algebraic techniques based on phylogenetic invariants

have been used for both the understanding of evolutionary models and for methods

of phylogenetic tree inference, e.g. (Casanellas, Fernández-Sánchez, 2007;

Chifman, Kubatko, 2014). Recently, algebraic methods have also been used to

determine when hybridisation between species is likely to have occurred (Blischak et

al. 2018) and combined with statistical learning techniques to infer small semi-

directed networks (Barton et al. 2022). In this paper, we investigate a method for

determining 4-leaf semi-directed networks that uses algebraic invariants for "group-

based" models of evolution, namely, the Jukes-Cantor (JC) model, and the Kimura 2-

parameter (K2P) model. By identifying the state space of the four nucleic acids with

a mathematical structure called a group, group-based models enable a Fourier

transformation of the parameter space that simplifies the equations defining the

model. This, and their low number of parameters, makes them amenable to the

algebraic methods we use here. Furthermore, these models are commonly used to

model nucleotide substitution in the presence of reticulate evolution (for example

(Kong et al. 2024; Burbrink and Gehara 2018)).

As well as performing extensive simulations to understand the performance of the

method, we show that it can be used to distinguish between tree-like and non-

treelike evolution. We also compare our method with the QNR-SVM method (Barton

et al. 2022) and employ our method on a real data set that has been previously

analysed using semi-directed networks in (Solís-Lemus, Ané, 2016) and separately

in (Blischak et al. 2018) to compare its performance with these methods.

**2. Materials and Methods**

***2.1 Background***

For a rooted phylogenetic network, its *semi-directed network* is the mixed

graph obtained by unrooting the network and undirecting all edges except for the

reticulation edges. For the nucleotide substitution models we define on rooted

phylogenetic networks, only the semi-directed network is identifiable from the leaf-

pattern distribution (also called the marginal character distribution), that is, the

distribution of nucleotides observed at the leaves (Gross et al. 2021). This is

analogous for the case for phylogenetic trees, where, under the nucleotide

substitution models we use, only the unrooted tree topology is identifiable from the

leaf-pattern distribution. Here, we only consider *level-1* phylogenetic networks.

These are phylogenetic networks in which the reticulation vertices are sufficiently far

away from each other. More precisely, they are phylogenetic networks in which the

undirected cycles do not overlap.

We place a model of nucleotide substitution on a rooted phylogenetic network

in the form of a directed graphical model, by assigning a transition matrix to each

edge in the network (where each entry in the matrix is the probability of a particular

nucleotide substitution occurring along that edge), a distribution of nucleotides at the

root of the network (for us this will be the equilibrium distribution of the model), and

for each reticulation vertex, the probability that a particular position is inherited along

either reticulation edge. We refer to this final parameter as the "tree-ratio", because

when it is either 0 or 1, the model becomes that of an unrooted tree. From this model

we can obtain expressions for the probability of observing the leaf-patterns (or

marginal characters) of the network. Each leaf-pattern is a sequence of nucleotides

that can be observed at the leaves of the network at a single position in a sequence

alignment.

By considering the numerical parameters of the model as free variables, we

think of the distribution of leaf-patterns as a multi-dimensional polynomial function.

These functions are complicated, but they can be simplified if we use certain

evolutionary models called "group-based" models (see e.g., Chapter 15 of Sullivant,

2018 for further details). For 4-state nucleotide models, there are three well known

group-based models: the Jukes Cantor model (JC), the Kimura 2-parameter model

(K2P), and the Kimura 3-parameter model (K3P). In each case, a Fourier

transformation can be applied to the model that makes the transformed expressions

for the distribution of marginal characters much simpler, although it is no longer

probabilistic. These transformations were first described for phylogenetic trees in

(Evans, Speed 1993) and (Hendy, Penny, 1996), where the transformed distribution

functions are monomial (a polynomial with a single term), which makes them

especially amenable for algebraic study, and indeed, these models have been well

studied from an algebraic perspective (e.g., Sturmfels, Sullivant, 2005; Allman et al.

2011).

142           From an algebraic perspective, we view the phylogenetic tree or network and

substitution model as an algebraic variety (see e.g. Cox et al. 2007 for an

introduction). This object can be thought of as a high-dimensional surface, and

consists of all possible distributions of leaf-patterns that can be observed from the

model. Recent study of these objects has given identifiability results. For the JC

model, it was shown that the semi-directed network topology of large cycle networks

is generically identifiable from the distribution of leaf-patterns (Gross, Long, 2018).

Analogous results have been proven for the K2P and K3P evolutionary models

(Hollering, Sullivant, 2021), and for all three evolutionary models on level-1, triangle-

free phylogenetic networks (Gross et al. 2021). Further algebraic properties have

been determined for any triangle-free level-1 network under any group-based model

(Gross et al. 2024). In particular, for group-based evolutionary models, it is not

possible to identify the reticulation vertex in a 3-cycle from the leaf-pattern

distribution (Gross et al. 2021).

156           Algebraic invariants (also called phylogenetic invariants) are polynomial

functions that evaluate to 0 on all points of an algebraic variety given by a fixed

phylogenetic network and model of evolution. (Note that the term "phylogenetic

invariants" is sometimes used to mean only those algebraic invariants that belong to

exactly one tree or network, as in (Casanellas, Fernández-Sánchez, 2007)) They

can be used to determine whether a set of data could have been produced by a

given network without the need for parameter estimation. One of the most well-

known examples of algebraic invariants are the edge invariants (Allman, Rhodes,

2007). These encode the set of splits in a phylogenetic tree from which the full tree

can be reconstructed and give rank conditions on certain matrices called flattening

matrices. This method was employed in the software SVDQuartets (Chifman,

Kubatko, 2014) and has been extended to phylogenetic networks in (Casanellas,

Fernández-Sánchez, 2021).

Algebraic invariants have also been used to infer 4-leaf trees from simulated

data under the K3P model (Casanellas, Fernández-Sánchez, 2007), and 4-leaf

networks under the JC model (Barton et al. 2022). Used as a method of inferring tree

or network topologies from aligned sequence data, they have several advantages.

First, finding the invariants for a fixed phylogenetic tree or phylogenetic network and

model of evolution need only be done once. For small trees, many invariants have

already been calculated and are available online (Casanellas, Garcia, Sullivant,

2005). Second, using invariants is a statistically consistent method to infer an

unrooted phylogenetic tree or semi-directed network topology, provided that an

appropriate set of invariants are used. Third, once the invariants have been

calculated, applying the method to a dataset is simply a case of evaluating a fixed

number of polynomials, and so can be performed quicker than many other

statistically consistent methods, such as maximum likelihood.

Here, we investigate the *practical identifiability* of semi-directed networks and

the effectiveness of using algebraic invariants for network inference under the JC

and K2P nucleotide substitution models. We present a new algorithm to infer the 4-

leaf, 4-cycle network (also called a 4-*sunlet* network, a directed example of which is

depicted in Figure 2) from aligned sequence data using algebraic invariants. The

algorithm is based on that developed for 4-leaf trees in (Casanellas, Fernández-

Sánchez, 2007). The 4-leaf, 4-cycle network has particular biological relevance in

that it can represent the evolutionary relationship between two species, their hybrid,

and an outgroup; and it is generically identifiable from leaf-pattern data. Furthermore,

knowledge of all the networks restricted to 4-taxa subsets, called 'quarnets', is

sufficient to rebuild a (level-1) phylogenetic network. When the network is assumed

to be triangle-free, we need only 4-cycles and 4-leaf trees to rebuild the network

(Huber et al. 2024; Frohn et al. 2025).

**Figure 2**. A directed cycle network with cycle of length 4. Dashed edges represent

reticulation edges. The root vertex is highlighted in orange. This topology could

represent the evolutionary history between taxa where $a$ is a hybrid species resulting

from a hybridisation event between taxa $b$ and $d$, whilst $c$ is an outgroup.

***2.2 Algorithm to Infer Phylogenetic Network Topology from Aligned Sequence Data***

We developed an algorithm that utilises phylogenetic invariants to infer the

correct 4-leaf, 4-cycle network from a multiple sequence alignment (MSA) of 4 taxa.

We use the notation $(abcd)$ to denote the 4-leaf 4-cycle network with taxon "$a$" at the

leaf below the reticulation vertex and taxa "$b$", "$c$", and "$d$" at the leaves going anti-

clockwise from "$a$" (as in Figure 2). There are $12 = {4!}/{2}$ possible 4-leaf 4-cycle

networks, since $(abcd)$ and $(adcb)$ represent the same 4-cycle. Note that for each

network the underlying semi-directed graph is the same, but the taxa labels at the

leaves are permuted.

Each of the 4-leaf, 4-cycle networks is represented by a "surface" giving the

leaf-pattern distributions that can be obtained from that network and substitution

model. From an MSA from 4 taxa we obtain an empirical leaf-pattern distribution,

and we use algebraic invariants to determine how close this is to each of the

surfaces. A depiction of this process is given in Figure 3.

First, using the software Macaulay2 (Grayson, Stillman), we calculated

invariants for the 4-leaf, 4-cycle phylogenetic network depicted in Figure 2, for the JC

and K2P models. Full details on how these were calculated and which invariants

were chosen are given in the supplementary materials.We now briefly describe our

algorithm for inferring a phylogenetic network topology from aligned sequence data.

Further details and a full description are given in the supplementary materials. For a

given MSA, we score each of the twelve semi-directed network topologies by

permuting the sequences in the MSA, applying the Fourier transform to the

corresponding leaf-pattern distribution, and then applying invariants to the result. The

first step is to read the alignment and count the number of columns that occur for

each leaf-pattern. This gives us an empirical leaf-pattern distribution which we store

as a single vector $p$. The next step is to transform $p$ using the Fourier transformation,

giving us a new vector $q$.

Our algorithm next reads in a file of invariants that have undergone the

Fourier transformation as above, and we evaluate each invariant at the vector $q$. This

gives us a list of numbers from which a score for the corresponding network is given.

As in (Casanellas, Fernández-Sánchez, 2007) we found that scoring using the 1-

Norm gave us the best results. In this case, the score for network $\mathcal{N}$ is given by the

formula

234
$$S_{\mathcal{N}} = \sum_{f \in G} |f(q)|,$$

where $G$ is a set of invariants, and $q$ is the transformed data point obtained from the

permuted MSA. Once each network has been scored, the networks are ordered by

score in ascending order, and the network with the smallest score is chosen as the

one most likely to have generated the data.

**Figure 3**. **A.** Each leaf-labelled, semi-directed network is converted into a high-

dimensional "surface" in a high-dimensional space (depicted here as a 2D surface in

a 3D space), representing all leaf-pattern distributions possible from the model. **B.**

An MSA is converted into a point $q$ in this space, and this lies exactly on the surface

(i.e., the alignment could have been generated by the model) if and only if $f(q) = 0$

for all invariants $f$. Since each $f$ is a continuous polynomial, for points $q$ close to the

surface, $f(q)$ will be close to 0. Depiction of the surface was created using

CalcPlot3D available at https://c3d.libretexts.org/CalcPlot3D/index.html.

It is common to infer phylogenetic trees or networks from a single MSA. In this

case, it is desirable to have an idea of the confidence a tool has in its inference.

Bootstrap support (Felsenstein, 1985) is a popular method of providing confidence

intervals for phylogenetic inferences. Here, we sample with replacement many times

from the original data to create new datasets with similar properties. In our case, we

expect the new datasets will have leaf-pattern distributions close to that of the

original dataset. We implemented a separate version of our script with inbuilt support

for parallelised bootstrapping. We applied our bootstrap method to real transcriptome

data from 24 swordtail fish and platyfish species (genus *Xiphophorus*) and two

outgroups (*Pseudoxiphophorus jonesii* and *Priapella compressa*), by independently

assessing each subset of 4 taxa. The transcriptome data was generated in (Cui et al.

2013) and alignments were kindly provided to us by the authors of (Blischak et al.

2018).

We implemented our inference algorithm in a python script `evaluate.py`, (and

with bootstrap in `evaluate_bootstrap.py`) along with a python library for

reading, writing, and evaluating phylogenetic invariants. These are available from the

GitHub repository https://github.com/SR-Martin/4cycle_invariants.

**3. Results**

In this section we evaluate our method on data simulated according to the JC and

K2P models on 4-leaf, 4-cycle networks. All data was simulated using the simulation

scripts available on the GitHub page. The results in this section are obtained using

invariants from the appropriate model, as described in the supplementary materials.

*3.1 Simulated 4-leaf 4-cycle data*

We generated MSA data from each of the twelve distinct leaf permutations of the

directed network depicted in Figure 2, each of which has a semi-directed network

identifiable from leaf-pattern data. For each network we generated 100 MSAs of

lengths 1kbp, 10kbp, 100kbp, 1Mbp, and 10Mbp under both the JC and K2P models.

For each edge, substitution rates were generated uniformly at random in the interval

$(0, 0.1)$ for JC, and $(0, 0.15)$ for K2P. The tree ratio $(\gamma)$ was fixed at 0.5. Each MSA

was assessed using the algorithm described in Section 2.2, and in each case the 4-

cycle topology with the lowest score was taken as the "inferred network". Figure 4.A

shows the confusion matrices for these datasets for the JC model, and Figure 4.B

shows the confusion matrices for the K2P model. In both cases we see that we

approach 100% true positive and 0% false positive rates as the sequence length

approaches 10Mbp. Furthermore, we can see the set of 4-leaf 4-cycle networks is

partitioned into three sets, where in each set the circular order is the same (e.g., the

first set is given by (0123), (1032), (2103), and (3012)). Figures 4.A and 4.B show

that at lengths of 1kbp, we can identify the correct circular order with close to 100%

true positive rate. In this case, identifying the circular order is equivalent to identifying

the *undirected phylogenetic network*.

**Figure 4**. **A.** Confusion matrices for inference of 4-leaf, 4-cycle networks from data

simulated under the JC model. **B.** Confusion matrices for inference of 4-leaf, 4-cycle

networks from data simulated under the K2P model. **C.** Distribution of scores from

data generated by the network (0123) under the JC model. **D**. Distribution of scores

from data generated by the network (0123) under the K2P model

We found a clear distinction between scores for the true network, and scores for the

other networks. Figure 4.C and D show the distribution of scores obtained for each

network when the true network was (0123), under the JC and K2P models

respectively. Again, we can see that scores for networks with the correct circular

order are smaller than scores for all others from 1kbp. At each alignment length we

see that the mean score of the true network is smaller than the mean scores of all

others, suggesting a bootstrap approach might be beneficial (see Section 3.5). At

1Mbp there is no overlap between the interquartile range of scores for the true

network and the interquartile range of scores for all other networks. By 10Mbp, this

effect is more pronounced, and the score for the true network is smaller than the

scores for other networks with the same circular order.

### 3.2 Varying the tree ratio

We generated further datasets where the 4-leaf, 4-cycle network was fixed and

the tree ratio $\gamma$ was varied from 0.0 to 1.0 in intervals of 0.05. As before, we

generated 100 MSAs of length 1kbp, 10kbp, 100kbp, 1Mbp, and 10Mbp for both JC

and K2P models. Figure 5 shows the number of correctly inferred networks in each

case for the JC model (5.A) and K2P model (5.B). Observe that when $\gamma = 0$ or 1 we

obtain a low percent of correctly identified networks regardless of MSA length,

because in this case the data is from a phylogenetic tree, and there is not a unique

semi-directed phylogenetic network that could have produced it.

**Figure 5**. **A.** Percent of tree-ratio datasets where the network was correctly identified (left) and average score over all datasets that the correct network achieved (right) for JC. **B.** Analogous plots for K2P datasets.

### 3.3    Identification of Treelike versus Non-treelike Evolution

In many cases, it may not be known whether a set of taxa has undergone reticulate evolution or not. In this section, we focus on using our method to determine whether data from four taxa has been generated from a tree (treelike) or a 4-leaf, 4-cycle network (non-treelike).

To do this, we make the following observation: for a fixed model of evolution, the model for a 4-leaf unrooted tree is contained in the models of the eight 4-leaf, 4-

cycle networks that display the tree, and is not contained in the remaining four.

Therefore, if a set of data is generated by a tree, we expect the score that this data

obtains via our invariants method to be low for 8 of the networks, and high for the

remaining 4 networks. Furthermore, from the partition of the networks by their scores

we can determine which unrooted tree generated the data.

We found that this signature is identifiable even for short alignment lengths

(see Figure 6.C). In this case, when $\gamma = 0$, evolution has been treelike, along a tree

which we refer to as tree 1. When $\gamma = 1$, evolution has also been treelike, along a

different tree which we refer to as tree 2. In all other cases evolution has been non-

treelike. Figure 6.A shows that for the data simulated under the JC model, we

approach a 100% true positive rate and 0% false positive rate for alignments of

length 10Mbp. Figure 6.B shows a similar picture for the data simulated under the

K2P model.

**Figure 6. A.** Percent of JC datasets identified as evolving along either tree 1 or tree 2. **B.** Percent of K2P datasets identified as evolving along either tree 1 or tree 2. **C.** Scores assigned to networks generated along tree 1 (i.e. $\gamma = 0$) under the JC model. The low scores of eight of the networks are clearly identifiable. **D**. Scores assigned to networks generated along tree 1 under the K2P model.

### 3.4 *Assessment against QNR-SVM*

We assessed our method against the QNR-SVM method presented in Barton et al. (2022). This method uses a support vector machine to analyse the residuals from a set of phylogenetic invariants, one for each identifiable semi-directed phylogenetic network topology on 4 leaves. In particular, the method can identify undirected 3-cycles (that is, quarnets that contain 3-cycles in which the reticulation

vertex is not identified). We assessed our method on the simulated data available in

Barton et al. 2022, from the three unrooted 4-leaf tree topologies (networks 1,2, and

3 in Barton et al. 2022), the twelve 4-cycle topologies (networks 10-22), the six

topologies with a single 3-cycle (networks 4-9), and the 3 topologies with two 3-

cycles (networks 22-24). The data was simulated under a JC model with branch

lengths of cycle and cycle-adjacent edges chosen uniformly at random between 0.05

and 0.2, and branch lengths of all other edges chosen uniformly at random between

0.05 and 0.4. The tree-ratio parameter $\gamma$ was chosen uniformly at random between

0.25 and 0.75, and the alignment length was 1Mbp. The results of our method on

this data are displayed in Figure 7.

**Figure 7. A.** Confusion matrix for analysis of datasets from Barton et al. (2022). The
373
first three columns are datasets simulated from phylogenetic trees. The next 12
374
columns are from 4-leaf 4-cycle networks. The next 6 columns, labelled network 4 to
375
9 are 3-cycle networks. The final 3 columns are double 3-cycle networks. (See
376
Figure 5 of Barton et al. 2022). Each column represents 200 datasets. **B.** Scores for
377
each 4-cycle network on data from (left) a single 3-cycle (network 4) and (right) a
378
double 3-cycle (network 22).
379

We found that on trees and 4-cycles, our method gives very similar results to

those in Barton et al. (2022) (see Figure 5 therein), with all topologies being

identified at close to 100% true positive rate. In particular, here we are able to

correctly identify a higher proportion of the 4-leaf trees (lower left box in Figure 7)

than in Barton et al. 2022. However, we note that here we do not attempt to identify

phylogenetic networks containing 3-cycles, and these accounted for many of the

false-positives for the 4-leaf tree data in Barton et al. (2022). Observe that the

convergence of our method on this data is an order of magnitude better than the

simulated data in Section 3.1.

We do not attempt to identify topologies with 3-cycles, since the placement of

the reticulation vertex is not identifiable. However, it is helpful to know how our

method performs in these cases. In most cases we infer the 4-leaf tree obtained by

collapsing the 3-cycle to a single point (Figure 7.A). Inspection of the scores reveals

a similar situation to the scores on tree topologies in Section 3.3, where particular

topologies consistently score lower than others (Figure 7.B).

**3.5    *Inference of networks from real datasets with many taxa***

We used our method to evaluate aligned transcriptome data from 24 swordtail

fish and platyfish species (genus *Xiphophorus*) and two outgroups

(*Pseudoxiphophorus jonesii* and *Priapella compressa*), generated in (Cui et al.

2013). Each of the *Xiphophorus* species belongs to one of three distinct clades;

southern swordtails, northern swordtails, and platyfishes (split further into southern

platyfishes and northern platyfishes). Since our method is restricted to four taxa, we

looked at each subset of four taxa individually, giving a total of 14,950 subsets. The

data consists of 10,999 alignments, each of length at least 500bp, for a total

alignment length of 16.85Mbp. Since we do not use positional information, we

concatenated all alignments into a single alignment. Next, we extracted the

concatenated alignment for each subset of four taxa. Each of these subsequent

alignments was analysed by our bootstrap method, with 100 bootstrap replicates in

each case. Here, we ignore columns in the alignment containing the gap character "-

".  Without gaps, alignments between subsets of four taxa ranged between 180kbp

and 3.37Mbp.

We then used the software Squirrel (Holtgrefe et al. 2025) to create a level-1

phylogenetic network displaying the relationships between all 24 Xiphophorus

species. Squirrel is a new approach that can take as input the quarnets computed

using the method presented here to build larger level-1 (triangle-free) phylogenetic

networks on many taxa.

Of the 14,950 4-taxa subsets, 7,028 (47%) had 100% bootstrap support for a

particular tree (6,175) or 4-cycle (853) topology, and 8,982 (60.1%) had at least 90%

support for a particular tree (6,325) or 4-cycle (2,657) topology. Almost all (14,561)

had at least 50% support for a particular tree (6,459) or 4-cycle (8,102) topology,

consistent with widespread hybridisation between Xiphophorus species, as

demonstrated in previous analyses of this dataset (Cui et al. 2013; Solís-Lemus and

Ané 2016; Blischak et al. 2018). The bootstrap results show that the inference of 4-

cycles is less certain than the inference of trees, likely due to the difficulty in placing

the reticulation vertex, which we observed in Section 3.1. The full results for all 4-

subsets are available in the Supplementary data.

Next, we created a level-1 phylogenetic network using an adapted version of

the software Squirrel. For input, we gave Squirrel the highest-supported tree or 4-

cycle network from each 4-subset, and these were weighted by the corresponding

support value. Squirrel allows exactly one taxon to be designated the outgroup in

order to root the network. We designated *P. compressa* as the outgroup, and

therefore excluded all subsets containing *Ps. jonesii*. The network produced by

Squirrel is displayed in Figure 8. It shows clear separation between the clades

(although the Southern Swordtails do not form a monophyletic group) and is in

agreement with that produced in (Solís-Lemus and Ané 2016, see Figure 10 therein).

In particular, we find a reticulation event between *Xiphophorus xiphidium* and the

Northern Swordtail clade, exactly as described in (Solís-Lemus and Ané 2016) and

also reported in (Blischak et al. 2018). We also find further reticulation within the

Northern Swordtail clade, in line with the results of Cui et al. (2013). For example,

they constructed two trees that placed *Xiphophorus nezahualcoyotl* as sister to

*Xiphophorus cortezi* and *Xiphophorus montezumae* respectively. Here, we find a

reticulation event enabling both placements.

**Figure 8.** The level-1 phylogenetic network produced by Squirrel, using the bootstrap-supported quarnets from Xiphophorus data. Dashed red lines indicate reticulation edges.

### 3.6    *Timings*

Figure 9 shows the time taken and maximum memory usage for the analysis of the simulated data from Section 3.1. Each analysis was run on a single CPU with 8GB of RAM. Since each dataset is evaluated on a fixed set of invariants (that have been pre-computed and are stored in a text file), most of the time is taken on reading the alignments and counting leaf patterns to obtain the empirical leaf-pattern distribution, and then performing a Fourier transform of this data. The time therefore

scales with the length of the alignment. Shorter alignments perform quickly

(seconds), but longer alignments can take several minutes. Memory usage scales

with alignment length, as the whole alignment is loaded into memory to calculate the

empirical distribution of leaf-patterns. However, this is not necessary and could be

improved so that memory usage was fixed by reading alignments piecewise.

**Figure 9.** Timings and max memory usage for simulated JC data (Section 3.1) split

463                              by alignment length.

**4   Discussion**

We have developed a novel method for inferring a semi-directed network

topology from aligned sequence data between four taxa. We demonstrate its use in

identifying 4-leaf 4-cycle networks from simulated data, and in identifying whether

reticulate evolution is likely to have occurred. We have shown that we can identify

the undirected network with sequences of length 1kbp but require longer sequences

(up to 10Mbp) to determine which vertex is the reticulation vertex and thereby

identify the semi-directed network. Furthermore, we show that our method can detect

when evolution between taxa has been treelike, converging quickly to a high true

positive rate and low false negative rate as alignment length increases.

On simulated data we observe a rate of convergence that is much less than the

analogous rate for trees. In (Casanellas, Fernández-Sánchez, 2007), the authors

observe almost 100% accuracy for alignments of length 10kbp on 4-leaf trees under

the K3P model. For 4-leaf, 4-cycle networks under the JC and K2P models, we do

not achieve 100% accuracy until alignment lengths are in the order of 10Mbp.

However, for alignments of length at least 1kbp, we were able to infer with high

accuracy the correct circular ordering of 4-leaf 4-cycle networks and thereby

determine the undirected network. There are three circular orderings possible, each

corresponding to a choice of two out of three 4-leaf unrooted trees displayed by the

network. Thus, when restricting to undirected networks, our results are comparable

to those in (Casanellas, Fernández-Sánchez, 2007). Locating the correct reticulation

vertex appears to be the main difficulty. We conjecture that the leaf-pattern

distribution varieties of 4-leaf 4-cycle networks with the same circular ordering are

close together geometrically. The scores displayed in Figure 4.C and 4.D support

this, and this makes inference difficult. The varieties corresponding to any two 4-leaf-

4-cycle networks contain exactly one variety corresponding to a phylogenetic tree in

their intersection, and so for data where the tree ratio is close to 0 or 1, the true

semi-directed network topology will be more difficult to infer. This can be observed in

Figure 6.

We compared our method with the QNR-SVM method in (Barton et al. 2022) and

found the performance of our method comparable with theirs on trees and 4-cycles,

with true positive and false positive rates very similar. Unless it is known that a

dataset is similar to data used in the pretrained QNR-SVM model, to use QNR-SVM

one must first train the model on the data. The method we present has the

advantage that it does not require training and is therefore much quicker to run. We

found that the convergence of our method was an order of magnitude better on the

QNR-SVM data than on our own simulated data sets, with a true positive rate of

almost 100% being achieved on data from alignments of length 1Mbp. The main

difference in the two datasets is that the QNR-SVM 4-leaf 4-cycle networks are less

symmetric, with branch lengths having different ranges depending on the branch. A

better understanding of the geometry and how this corresponds to the parameter

space may enable faster convergence.

Since we do not attempt to identify 3-cycle topologies, we were unable to

identify the correct topology for the data in (Barton et al. 2022) generated from 3-

cycle topologies. Nonetheless, we analysed this data using our method and

inspected the results. In most cases our method inferred the 4-leaf tree obtained by

collapsing the 3-cycle(s) to a single vertex (Figure 7.A). When subsequently building

a phylogenetic network using Squirrel, this will not affect the result, since Squirrel will

collapse 3-cycles to a single vertex on all input quarnets. We found that for each 3-

cycle topology, particular 4-cycles scored consistently lower than others, much like

the case for 4-leaf trees in Section 3.3. For the networks with a single 3-cycle, this is

expected, since, under the JC substitution model, each 3-cycle model is contained in

exactly four of the 4-cycle models (see Figure 10 of (Gross, Long, 2018)). The

distribution of scores in this case lies somewhere between the distribution for 4-

cycles (Figure 4.C) and the distribution for trees (Figure 6.C), which agrees with the

containment results. Thus, a very careful analysis of the scores here may enable us

to determine quarnets containing a single 3-cycle, in a similar way to how we

determine treelike evolution. For the topologies with two 3-cycles however, we do not

have the same containment of models, so the results here are less clear. The

distribution of scores in this case was closer to that of the 4-leaf trees. Further work

is needed to determine whether we can identify these topologies from the 4-cycle

scores.

Our method looked at small networks with 4 taxa. In principle, one can apply the

same method to larger networks with more taxa, but the problem of calculating

invariants for larger networks is currently intractable. Alternatively, one could

construct a larger network by computing networks on smaller numbers of taxa and

puzzling them together to make larger networks (see e.g. (Huber, Moulton, 2013;

Oldman et al. 2016) where directed networks are constructed from 3-leaf networks).

Recently, we made some progress in this direction for semi-directed networks by

developing a new approach that can take as input the quarnets computed using the

method presented here to build larger level-1 (triangle-free) phylogenetic networks

on many taxa, or directly from MSAs using a heuristic based on statistical geometry

(Holtgrefe et al. 2025). This approach is implemented in the software Squirrel. Here.

we applied our new method, combined with bootstrapping, to aligned transcriptome

data from swordfish species and used the results as input for Squirrel to create a

level-1 phylogenetic network. This network displayed previously identified

hybridisation events and was largely consistent with previous analyses.

Bootstrapping enabled us to give confidence intervals to the tree or 4-leaf 4-cycle

networks we inferred, which we then used as weights for the corresponding network

when given to the software Squirrel. However, we are only able to give the single

most supported topology for each 4-subset to Squirrel. This means that information

on other topologies that might be well-supported is lost. Future work on Squirrel will

take alternative topologies into account, and we believe will provide more accurate

phylogenetic network reconstruction.

In our simulations, we found that we were able to identify the circular ordering of

4-cycles with high accuracy from smaller alignments, whereas identifying the position

of the reticulation vertex required longer alignments, However, for constructing larger

level-1 phylogenetic networks, Squirrel only uses the placement of the reticulation

vertex in a 4-cycle quarnet to place the reticulation vertex in 4-cycles in the final

network. For larger cycles in the final network, the circular ordering of the 4-cycle

quarnets are used. Thus, we may still be able to create accurate level-1 phylogenetic

networks even if we are not able to always identify the correct reticulation vertex, as

is the case for shorter alignments.

We developed several python scripts for both simulating and assessing aligned

sequence data. These scripts read in plain-text files containing expressions for the

phylogenetic invariants to use and may therefore be useful for other researchers

assessing other sets of invariants. Our tool performs quickly on all datasets, with

time demand growing with alignment length. The computations that take the most

time are calculating the empirical distribution of leaf-patterns, followed by performing

a linear transformation of these frequencies. Both tasks are parallelisable and

implementing this could increase the speed by up to 12x, although we have not

explored this yet. The remaining time is spent evaluating the polynomial invariants

on the transformed frequency data, and this is also parallelisable. Thus, there is

potential for our tool to be significantly faster. The reason we can perform network

inference relatively quickly is that the most difficult computations (computing the

invariants of the networks) need only be done once. We have already done them

and distribute the results with the tool. The speed at which this tool runs means that

it may be useful for exploratory or initial analyses of large datasets. Indeed, our tool

could be used as a single stage in a larger phylogenetic analysis pipeline,

complementary to other methods. For example, the bootstrap values we obtain could

be used as a fast and efficient way to obtain priors for a deeper Bayesian analysis, in

order to gain further support for a particular topology or for parameter estimation.

One of the biggest challenges of this work was calculating invariants. We used

methods in elimination theory to find a Gröbner basis with the software Macaulay2,

but this does not scale well. Indeed, we were only able to calculate degree 2

invariants for the K3P model. This model is more versatile than K2P and JC, so we

hope our results provide motivation for developing better methods of calculating

invariants in this case. In (Cummings et al. 2024), the authors reduce the

calculations for finding quadratic invariants for 4-leaf, 4-cycle networks under the

Cavender-Farris-Neyman (CFN) 2-state model to finding the kernel of a linear map.

The result is a much faster method of calculating invariants than using Gröbner basis

methods and has been extended to higher degree invariants and other group-based

models in (Cummings, Hollering, 2023), where the authors were able to calculate all

minimal generators of the 4-leaf, 4-cycle network under the K3P model up to degree

3. However, even the K3P model is somewhat simplistic, so we would like to be able

to calculate invariants for more complex substitution models such as the generalised

time reversible (GTR) model, or models that incorporate a molecular clock. Work in

this direction has been recently performed for the CFN model on phylogenetic trees

in (Coons, Sullivant, 2021), and recent theoretical results for the GTR model on

phylogenetic trees (Casanellas et al. 2024) suggest that it may be possible to

compute phylogenetic invariants for those models using similar methods to those we

used here.

We currently do not have an interpretation of the invariants we have found in

terms of the network topology. In the Supplementary Materials, we determine which

of the invariants belong only to a single topology, and which are shared between

different topologies, but we do not know what (if anything) they are telling us of the

topology. Having a greater understanding of the invariants, or determining invariants

that correspond to different topological features may enable faster convergence than

we have observed here, and is the topic of future work.

**References**

[Bapteste et al. 2013] E. Bapteste, L. van Iersel, A. Janke, S. Kelchner, S. Kelk, J.O.

McInerney, D.A. Morrison, L. Nakhleh, M. Steel, L. Stougie, J. Whitfield. Networks:

expanding evolutionary thinking. *Trends Genet.* 29(8):439-441, 2013.

[Bryant, Moulton, 2004] D. Bryant, V. Moulton. Neighbor-Net: An agglomerative

method for the construction of phylogenetic networks. *Mol. Biol. Evol.* 21(2):255-265.

2004.

[Than et al. 2008] C. Than, D. Ruths. L. Nakhleh. PhyloNet: A software package for

analyzing and reconstructing reticulate evolutionary relationships. *BMC*

*Bioinformatics.* 9:32, 2008.

[Allman et al. 2019] E.S. Allman, H. Baños, J.A. Rhodes. NANUQ: A method for

inferring species networks from gene trees under the coalescent model. *Algorithms*

*Mol. Biol.* **14**,24, 2019.

[Grünewald et al. 2013] S. Grünewald, A. Spillner, S. Bastkowski, A. Bogershausen,

V. Moulton. SuperQ: Computing supernetworks from quartets. *IEEE/ACM*

*Transactions on Computational Biology and Bioinformatics.* 10(1):151-160, 2013.

[Kanna, Wheeler, 2012] L. Kannan, W.C. Wheeler. Maximum parsimony on

phylogenetic networks. *Algorithms Mol. Biol.* 7:9, 2012.

[Wen et al. 2018] D. Wen, Y. Yu, J, Zhu, L. Nakhleh. Inferring phylogenetic networks

using PhyloNet. *Syst. Biol.* 67(4):735-740, 2018.

[Lutteropp et al. 2022] S. Lutteropp, C. Scornavacca, A.M. Kozlov, B. Morel, A.

Stamatakis. NetRAX: accurate and fast maximum likelihood phylogenetic network

inference, *Bioinformatics* 38(15):3725–3733, 2022.

[Zhang et al. 2018] C. Zhang, H.A. Ogilvie, A.J. Drummon, T. Stadler. Bayesian

inference of species networks from multilocus sequence data. *Mol. Biol. Evol.*

35(2):504-517, 2018.

[Solís-Lemus, Ané, 2016] C. Solís-Lemus, C. Ané. Inferring phylogenetic networks

with maximum pseudolikelihood under incomplete lineage sorting. *PLoS Genet.*

12(3): e1005896, 2016.

[Solís-Lemus, Bastide, 2017] C. Solís-Lemus, P. Bastide, C. Ané. PhyloNetworks: A

package for phylogenetic networks. *Mol. Biol. Evol.* 34(12):3292-3298, 2017.

[Linz, Wicke, 2023] S. Linz, K. Wicke. Exploring spaces of semi-directed

phylogenetic networks. *arXiv* 2301.10818, 2023.

[Gross et al. 2021] E. Gross, L. van Iersel, R. Janssen, M. Jones, C. Long, Y.

Murakami. Distinguishing Level-1 Phylogenetic Networks on the Basis of Data

Generated by Markov Processes. *J. Math. Biol.* 83:32, 2021.

[Sullivant, 2018] S. Sullivant. Algebraic Statistics. *Graduate Studies in Mathematics*,

Volume 194. American Mathematical Society, 2018.

[Evans, Speed, 1993] S.N. Evans, T.P. Speed. Invariants of some probability models

used in phylogenetic inference. *Ann. Stat.* 21(1):355-377, 1993.

[Hendy, Penny, 1996] M.D. Hendy, D. Penny. Complete families of linear invariants

for some stochastic models of sequence evolution, with and without molecular clock

assumption, *J. Comput. Biol.* 3:19-32, 1996.

[Chifman, Kubatko, 2014] J. Chifman, L. Kubatko. Quartet inference from SNP data

under the coalescent model. *Bioinformatics*. 30(23):3317-3324, 2014.

[Oldman et al. 2016] J. Oldman, T. Wu, L. van Iersel, V. Moulton. TriLoNet: Piecing

together small networks to reconstruct reticulate evolutionary histories. *Mol. Biol.*

*Evol*. 33(8):2151-2162, 2016.

[Schmidt et al. 2002] H.A. Schmidt, K. Strimmer, M. Vingron, A. von Haeseler.

TREE-PUZZLE: maximum likelihood phylogenetic analysis using quartets and

parallel computing. *Bioinformatics.* 18(3):502-504, 2002.

[Huebler et al. 2019] S. Huebler, R. Morris, J. Rusinko, Y. Tao. Constructing semi-

directed level-1 phylogenetic networks from quarnets. *arXiv* 1910.00048, 2019.

[Allman et al. 2024] E.S. Allman, H. Baños, J.A. Rhodes, K. Wicke. NANUQ[+]: A

divide-and-conquer approach to network estimation. bioRxiv 2024.10.30.621146,

2024.

[Holtgrefe et al. 2025] N. Holtgrefe, K.T. Huber, L. van Iersel, M. Jones, S. Martin, V.

Moulton. Squirrel: Reconstructing semi-directed phylogenetic level-1 networks from

four-leaved networks or sequence alignments. *Mol. Biol. Evol*. msaf067, 2025.

[Casanellas, Fernández-Sánchez, 2007] M. Casanellas, J. Fernández-Sánchez.

Performance of a New Invariants Method on Homogeneous and Nonhomogeneous

Quartet Trees. *Mol. Biol. Evol.* 24(1): 288-293, 2007.

[Blischak et al. 2018] P.D. Blischak, J. Chifman, A.D. Wolfe, L.S. Kubatko. HyDe: A

python package for genome-scale hybridization detection. *Systematic Biology.* 67(5):

821-829, 2018.

[Barton et al. 2022] T. Barton, E. Gross, C. Long, J. Rusinko. Statistical learning with

phylogenetic network invariants.  *arXiv* 2211.11919, 2022.

[Kong et al. 2024] S. Kong, D.L. Swofford, L.S. Kubatko. Inference of Phylogenetic

Networks From Sequence Data Using Composite Likelihood, *Syst. Biol.* syae054,

2024.

[Burbrink and Gehara 2018] F.T. Burbrink, M. Gehara. The Biogeography of Deep

Time Phylogenetic Reticulation, *Syst. Biol.* 67(5):743–755, 2018.

[Gross, Long, 2018] E. Gross, C. Long. Distinguishing Phylogenetic Networks. *SIAM

J. Appl. Algebra Geometry.* 2(1):72-93, 2018.

[Sturmfels, Sullivant, 2005] B. Sturmfels, S. Sullivant. Toric ideals of phylogenetic

invariants. *J. Comput. Biol*. 12(4):457-481, 2005.

[Allman et al. 2011] E.S. Allman, S. Petrović, J.A. Rhodes, S. Sullivant. Identifiability

of Two-Tree Mixtures for Group-Based Models. *TCBB.* 8(3)710-722, 2011.

[Cox et al. 2007] D.A. Cox, J. Little, D. O'Shea. Ideals, Varieties, and Algorithms: An

introduction to computational algebraic geometry and commutative algebra.

*Undergraduate Texts in Mathematics.* Springer-Verlag, 2007.

[Hollering, Sullivant. 2021] B. Hollering, S. Sullivant. Identifiability in Phylogenetics

using Algebraic Matroids. *J. Symb. Comput.* 104:142-158, 2021.

[Gross et al. 2024] E. Gross, R. Krone, S. Martin. Dimensions of Level-1 Group-

Based Phylogenetic Networks. *Bull. Math. Biol.* 86:90, 2024*.*

[Allman, Rhodes, 2007] E.S. Allman, J.A. Rhodes. Phylogenetic Invariants, in

Reconstructing Evolution (editors O. Gascuel, M.A. Steel). Oxford University Press,

2007.

[Casanellas, Fernández-Sánchez, 2021] M. Casanellas, J. Fernández-Sánchez.

Rank Conditions on Phylogenetic Networks. *Extended Abstracts GEOMVAP 2019.*

*Trends in Mathematics*, 15. Birkhäuser, Cham, 2021.

[Casanellas, Garcia, Sullivant, 2005] M. Casanellas, L.D. Garcia, S. Sullivant.

Catalog of Small Trees. In: L. Pachter, B. Sturmfels, editors. Algebraic statistics for

computational biology. Chapter 15. Cambridge University Press, 2005.

[Huber et al. 2024] K.T. Huber, L. van Iersel, M. Jones, V. Moulton, L. Veenema-

Nipius. When are quarnets sufficient to reconstruct semi-directed phylogenetic

networks? *arXiv*: 2408.12997, 2024.

[Frohn et al. 2025] M. Frohn, N. Holtgrefe, L. van Iersel, M. Jones, S. Kelk.

Reconstructing semi-directed level-1 networks using few quarnets. *J. Comput. Syst.*

*Sci.* 103655, 2025.

[Grayson, Stillman] D.R. Grayson, M.E. Stillman. Macaulay2, a software system for

research in algebraic geometry. Available at http://www.math.uiuc.edu/Macaulay2/.

[Felsenstein, 1985] J. Felsenstein. Confidence Limits on Phylogenies: An Approach

Using the Bootstrap. *Evolution* 39(4):783-791, 1985.

[Cui et al. 2013] R. Cui, M. Schumer, K. Kruesi, R. Walter, P. Andolfatto, G.G.

Rosenthal. Phylogenomics reveals extensive reticulate evolution in Xiphophorus

fishes. *Evol.* 67(8): 2166-2179, 2013.

[Huber, Moulton, 2013] K.T. Huber, V. Moulton. Encoding and Constructing 1-Nested

Phylogenetic Networks with Trinets. *Algorithmica* 66:714-738, 2013.

S. Martin, N.Holtgrefe, V. Moulton, R.M. Leggett

[Cummings et al. 2024] J. Cummings, B. Hollering, C. Manon. Invariants for level-1

phylogenetic networks under the Cavendar-Farris-Neyman Model. *Adv. Appl. Math.*

135:102633, 2024.

[Cummings, Hollering, 2023] J. Cummings, B. Hollering. Computing Implicitizations

of Multi-Graded Polynomial Maps. *arXiv*:2311.07678, 2023.

[Coons, Sullivant, 2021] J.I. Coons, S. Sullivant. Toric Geometry of the Cavender-

Farris-Neyman model with a molecular clock. *Adv. Appl. Math.* 123:102119, 2021.

[Casanellas et al. 2024] M. Casanellas, R. Homs, A. Torres. A Novel Algebraic

Approach to Time-Reversible Evolutionary Models. *SIAM J. Appl. Math.* 84(4):1845-

1867, 2024.

**Funding**

This work was supported by EPSRC Mathematical Sciences Small Grant

award EP/W007134/1. SM and RL acknowledge the support of the Biotechnology

and Biological Sciences Research Council (BBSRC), part of UK Research and

Innovation; parts of this research were funded by the BBSRC Core Strategic

Programme Grant (Genomes to Food Security) BB/CSP1720/1 and its constituent

work package BBS/E/T/000PR9817 (WP3 Computational Developments). SM is

grateful for further funding from BBSRC (grant number BB/X005186/1). NH was

supported by grant OCENW.M.21.306 of the Dutch Research Council (NWO).

**Acknowledgments**

The authors are grateful to Paul Blischak for providing alignment data of the

*Xiphophorus* species, to NBI's Research Computing group for HPC support in

running the analyses, and to Nick Goldman and Nicola De Maio for their helpful

comments and discussions on this manuscript.

## **Data availability**

741       All scripts used in this project, including scripts for simulating data and

742    Macaulay2 scripts for calculating invariants, are available at the GitHub repository

743    https://github.com/SR-Martin/4cycle_invariants. All simulated data and results

744    presented are available at https://ckan.earlham.ac.uk/dataset/algebraic-invariants.