Dynamic categorization rules alter representations in human visual cortex

Authors: Margaret M. Henderson[1,2], John T. Serences[3,4], Nuttida Rungratsameetaweemana[5,6]

[1] Department of Psychology, Carnegie Mellon University, Pittsburgh, USA
[2] Neuroscience Institute, Carnegie Mellon University, Pittsburgh, USA
[3] Neurosciences Graduate Program, University of California, San Diego, La Jolla, USA
[4] Department of Psychology, University of California, San Diego, La Jolla, USA
[5] The Salk Institute for Biological Studies, La Jolla, USA
[6] Department of Biomedical Engineering, Columbia University, New York, USA

Abstract

Everyday perceptual tasks require sensory stimuli to be dynamically encoded and analyzed
according to changing behavioral goals. For example, when searching for an apple at the
supermarket, one might first find the Granny Smith apples by separating all visible apples into
the categories "green" and "non-green". However, suddenly remembering that your family
actually likes Fuji apples would necessitate reconfiguring the boundary to separate "red" from
"red-yellow" objects. This flexible processing enables identical sensory stimuli to elicit varied
behaviors based on the current task context. While this phenomenon is ubiquitous in nature,
little is known about the neural mechanisms that underlie such flexible computation.
Traditionally, sensory regions have been viewed as mainly devoted to processing inputs, with
limited involvement in adapting to varying task contexts. However, from the standpoint of
efficient computation, it is plausible that sensory regions integrate inputs with current task goals,
facilitating more effective information relay to higher-level cortical areas. Here we test this
possibility by asking human participants to visually categorize novel shape stimuli based on
different linear and non-linear boundaries. Using fMRI and multivariate analyses of
retinotopically-defined visual areas, we found that shape representations in visual cortex
became more distinct across relevant decision boundaries in a context-dependent manner, with
the largest changes in discriminability observed for stimuli near the decision boundary.
Importantly, these context-driven modulations were associated with improved categorization
performance. Together, these findings demonstrate that codes in visual cortex are adaptively
modulated to optimize object separability based on currently relevant decision boundaries.
32
33 Keywords: context-dependent processing, decision making, human visual cortex, decision
34 boundaries, task modulations, neural mechanisms

Introduction

Perceptual categorization is a fundamental cognitive ability that allows us to organize and understand the myriad stimuli encountered in our sensory environment. By forming categories, observers are able to generalize existing knowledge to new incoming inputs, facilitating efficient perception and decision-making (Bruner, 1957; Freedman & Assad, 2016). Within the visual system, categories can capture divisions within the natural structure of a stimulus space (Rosch et al., 1976) or can reflect the learning of arbitrary discrete boundaries along stimulus dimensions that would otherwise be represented continuously (Ashby & Maddox, 2005). At the same time, categorization in the real world is a highly dynamic cognitive process, in which the category membership of stimuli may change over time. For example, when making a categorical decision about produce at the farmer's market, depending on our goals we might think of carrots in the same category as lettuce (vegetables) or the same category as tangerines (orange colored items). Perceptual categorization is thus also tightly connected with flexible prioritization of information based on current task demands (Biederman et al., 1973; McAdams & Maunsell, 1999; Desimone & Duncan, 1995). Within contexts where task goals change dynamically over time, the neural mechanisms supporting categorization of sensory stimuli are not yet understood.

Past work has provided some insight into how category learning impacts representations of sensory stimuli. Behaviorally, learning to categorize stimuli in a continuous feature space can lead to perceptual changes such as an increase in sensitivity to changes along a relevant stimulus dimension, and an increase in perceptual discriminability of stimuli belonging to different categories (Goldstone, 1994; Livingston et al., 1998; Newell & Bülthoff, 2002). Such changes are also reflected in the brain – electrophysiology studies in macaques have demonstrated that after learning of a categorization task, neurons in inferotemporal cortex (ITC) become more strongly selective for diagnostic dimensions of stimuli (Sigala & Logothetis, 2002), and neural populations in ITC also contain information encoding the learned category status of stimuli (Meyers et al., 2008; Tanaka, 1996). In human functional magnetic resonance imaging (fMRI) studies, learning to discriminate object categories has been shown to increase neural responses to objects in extrastriate cortex (Gauthier et al., 2000; Op de Beeck et al., 2006) and lead to sharpening of visual representations as measured with fMRI adaptation (Folstein et al., 2015; Folstein et al., 2013; Jiang et al., 2007). Moreover, recent work has shown that learning a decision boundary can alter representations of orientation in early visual areas, with representations becoming biased away from the decision boundary (Ester et al., 2020). At the same time, other work has suggested that the effects of category status on sensory representations are more prominent in prefrontal cortex (PFC) than visual areas. This suggests that the primary role of visual areas may be restricted to perceptual analysis, rather than decision-related processing (Freedman et al., 2003; McKee et al., 2014; Meyers et al., 2008).

From an efficient processing perspective, it is plausible that visual areas play a more active role in decision-making, potentially encoding decision-related variables, task contexts, choices, or motor outcomes. Such coding would enable visual areas to process sensory inputs in a manner conducive to downstream readout. Emerging evidence from rodent studies

supports this view. For instance, activity that was thought to reflect random fluctuations in neural
representations within sensory areas has been linked to choice-related motor activities and
decision outcomes (Musall et al., 2019; Stringer et al., 2019). Furthermore, recent findings
indicate that early sensory areas robustly encode task context variables, such as expectations
and decision rules, during dynamic decision-making tasks (Ebrahimi et al., 2022; Findling et al.,
2023). Yet, the extent to which human sensory areas similarly code for task-related variables
and adapt their representations based on contextual changes is unclear.

In addition, the mechanisms by which categorical decision-making flexibly shapes neural
representations, particularly in tasks necessitating the switching between distinct decision rules,
are not well understood. Prior work has demonstrated that neural populations in PFC can
dynamically encode different boundaries depending on the currently relevant task rule (Cromer
et al., 2010; Roy et al., 2010), providing one potential neural mechanism for dynamic decision-
making. Similarly, a human neuroimaging study using novel objects suggested that
representations in frontoparietal areas can encode different category distinctions between
objects depending on their task relevance (Jackson et al., 2017). This study also found
evidence for similar (albeit weaker) effects in the lateral occipital complex (LOC), suggesting
that representations in visual areas may also be modified by task-relevance. Thus, it remains an
open question whether and how varying task contexts interact with representations in visual
cortex, as well as how these modulations may contribute to downstream task performance.

Here we address these gaps by investigating how neural responses in human visual
cortex flexibly adapt to dynamic task contexts, as induced by varying categorization rules. We
hypothesized that task context modulates sensory representations such that changes in the
decision boundary are actively integrated during the early analysis of sensory information. To
examine the effects of categorization within an abstract stimulus space, we generated a two-
dimensional space of shape stimuli (Op de Beeck et al., 2001; Zahn & Roskies, 1972) that were
viewed by human participants undergoing fMRI scanning. Participants categorized shapes
according to different rules: linear boundaries (*Linear-1* and *Linear-2* tasks) or a non-linear
boundary (*Nonlinear* task). These task contexts were interleaved across scanning runs,
necessitating real-time cognitive adaptation to distinct categorization requirements applied to
physically identical stimuli. Each task incorporated both "easy" and "hard" trials drawn from
distinct locations in the shape space, enabling us to concurrently examine the influence of
perceptual difficulty on decision processes. Using multivariate decoding methods in
retinotopically-defined visual areas, we measured shape representations in each categorization
task and examined how representations differed across task contexts. We predicted that shape
representations would be more discriminable across a given decision boundary when that
boundary was relevant for the current task. Findings from our neural data are in line with this
account. Importantly, we further show that an increase in neural discriminability is linked to
improved task performance.
114
115

Results

We trained 10 human participants to perform a shape categorization task while in the
fMRI scanner, with each subject participating in 3 scanning sessions that each lasted 2 hours
(Figure 1A). Shape stimuli varied parametrically along two independent axes, generating a two-
dimensional shape space, and each condition of the task required shapes to be categorized
according to either a linear boundary (*Linear-1* and *Linear-2* tasks) or a nonlinear boundary that
required grouping together of non-adjacent quadrants (*Nonlinear* task). These different
categorization tasks were performed during different scanning runs within each session,
meaning that participants needed to flexibly apply different decision rules depending on the task
condition for the current run (see *Methods*). Each task included a mixture of "easy" trials and
"hard" trials. On the "easy" trials, a common set of 16 shapes, making up a 4x4 grid which we
refer to as the main grid (black dots in Figure 1B), were shown in all tasks, while on "hard" trials,
shapes were sampled from portions of the shape space near the active boundary, which made
the current task more challenging (light gray dots in Figure 1B).

To verify the two-dimensional structure of our shape space, we used an image similarity
analysis based on GIST features (Oliva & Torralba, 2001; see *Methods*) to assess the
perceptual similarity between shape stimuli. As expected, a principal components analysis
(PCA) performed on the GIST features revealed a two-dimensional grid structure, with the two
shape space axes oriented roughly orthogonal to one another in PC space (Figure 1C). In
addition, measuring the linear separability (based on between-category versus within-category
Euclidean distances; see *Methods*) of shapes across each category boundary based on GIST
features revealed that shapes were most separable across the *Linear-2* boundary, followed by
the *Linear-1* boundary, with lowest separability for the *Nonlinear* boundary (Figure 1D). A similar
pattern was found when computing separability using features from a self-supervised deep
neural network model (SimCLR; T. Chen et al., 2020; see *Methods*), suggesting that these
relationships held even when considering a broader set of image features. The low separability
of the *Nonlinear* categories relative to the *Linear-1* and *Linear-2* categories is consistent with the
Nonlinear boundary being nonlinear in shape space.

Figure 1. Stimulus set, task design, and behavioral performance. **(A)** Two-dimensional shape space used for categorization tasks in this experiment. Shapes are generated using radial frequency contours (Op de Beeck et al., 2001; Zahn & Roskies, 1972) that vary along two independent dimensions, referred to as axis 1 and axis 2. See *Methods* for more details. **(B)** Illustration of the tasks (*Linear-1, Linear-2, Nonlinear*) performed by participants while in the fMRI scanner. Points in each plot indicate the positions in shape space that were sampled, and dotted lines indicate the relevant categorization boundaries for each task. Black dots represent the 16 positions in the "main grid", which were sampled on "easy" trials in every task, while light gray dots represent positions that were sampled on "hard" trials, which differed depending on the task. Hard trial shape positions were sampled from the region nearest the relevant

categorization boundary. Different tasks were performed during different scan runs. In each
task, every trial consisted of the presentation of a single shape (1s), and participants were
instructed to respond with a button press indicating which category the presented shape fell
into. See *Methods* for more details on task design. **(C-D)** Image similarity analysis: we
computed activations from two computer vision models, GIST (Oliva & Torralba, 2001) and
SimCLR (T. Chen et al., 2020) for each of the 16 main grid shape images. **(C)** Visualization of a
principal components analysis (PCA) performed on the GIST model features, where each
plotted point represents one shape in PC space, colored according to the coordinate value
along axis 1 (left) or axis 2 (right). **(D)** Quantification of the separability of shape categories
within each feature space, computed based on the ratio of between-category to within-category
Euclidean distance values. See *Methods* for more details. **(E)** Behavioral accuracy (left) and
response time (RT; right) in each task. Dots in different colors represent individual participants;
open circles and error bars represent the mean ± SEM across 10 participants. **(F)** Accuracy
(left) and RT (right) for each task separated into "easy" and "hard" trials, where easy refers to
trials sampling the 16 shapes in the main grid (black dots in B), and hard refers to trials
sampling more challenging portions of the shape space for each task (light gray dots in B)**.** Gray
lines represent individual participants, open circles and error bars represent the mean ± SEM
across 10 participants.
178
179
Across participants, behavioral accuracy (Figure 1E) was highest for the *Linear-2* task
(0.86 ± 0.02; mean ± SEM across 10 participants), followed by the *Linear-1* task (0.83 ± 0.01)
and the *Nonlinear* task (0.80 ± 0.01). A repeated measures ANOVA revealed a main effect of
task ($F_{(2,18)}$ = 13.22, p < 0.001; p-values obtained using permutation test; see *Methods*), and
post-hoc tests showed that accuracy was significantly higher for both of the linear tasks versus
the *Nonlinear* task (*Linear-1* vs. *Nonlinear*: $t_{(9)}$ = 2.19, p = 0.024; *Linear-2* vs. *Nonlinear*: $t_{(9)}$ =
4.98, p = 0.002; paired t-tests with permutation; see *Methods*), and higher for the *Linear-2* task
versus the *Linear-1 task* (*Linear-1* vs. *Linear-2*: $t_{(9)}$ = -3.00, p = 0.001). This advantage for the
Linear-2 task is consistent with the high relative separability across the *Linear-2* boundary
based on image features shown in the previous analysis (Figure 1D). In terms of response times
(RTs), a significant main effect of task was also found ($F_{(2,18)}$ = 3.94, p = 0.036; p-values
obtained using permutation test). No difference in RTs between the *Linear-1* and *Linear-2* tasks
was observed, but RTs were significantly slower for the *Nonlinear* task than the *Linear-1* task
($t_{(9)}$ = -3.08, p = 0.012). In addition to these differences across tasks, we also observed a
consistent difference between performance on the easy and hard trials within each task (Figure
1F), which was expected based on the task design. Accuracy was significantly higher on easy
versus hard trials within each task (*Linear 1:* $t_{(9)}$ = 11.05, p = 0.002; *Linear-2:* $t_{(9)}$ = 7.88, p =
0.002; *Nonlinear:* $t_{(9)}$ = 15.37, p = 0.002), and RT was significantly faster on easy versus hard
trials within each task (*Linear 1:* $t_{(9)}$ = -7.48, p = 0.002; *Linear-2:* $t_{(9)}$ = -9.38, p = 0.002; *Nonlinear:*
$t_{(9)}$ = -4.92, p = 0.003).
200
201
202
203

Figure 2. Overall classification accuracy for binary and multinomial classifiers. **(A-C)** A binary logistic regression classifier was trained to predict the category of the shape shown on each trial, according to either the *Linear-1*, *Linear-2*, or *Nonlinear* decision rule. **(D)** A multinomial (16-way) logistic regression classifier was trained to predict the individual shape shown on each trial. In **(A-D)**, classifiers were trained and tested within each task condition separately, training using data from the main grid trials only (i.e. black dots in Figure 1B). Different colors indicate data from different tasks. Plotted values reflect overall prediction accuracy of classifiers for each task and each ROI, computed using trials from the main grid only. Gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants, horizontal line indicates chance decoding accuracy (1/2 for binary classifier, 1/16 for multinomial). All classification accuracy values were above chance at the participant-averaged level (FDR corrected, q < 0.01); see *Methods* for more details.

Next, we examined the neural representations of shape stimuli in each task, under the hypothesis that shape representations would differ across task conditions in accordance with the changing decision boundary. To achieve this we used multivariate classification to analyze single-trial voxel activation patterns from retinotopically defined ROIs (Figure 2). First, we trained a series of binary classifiers to predict the category of the shape shown on each trial, according to each of the three decision boundaries, using data from each task separately (Figure 2A-C). These binary classifiers provide an estimate of the discriminability of shape representations in visual cortex across each of the three decision boundaries, within each task context. Overall, we observed that binary classifier accuracy was highest in early visual areas V1 and V2, and lower in higher visual areas such as LO2 and IPS, although participant-averaged classification accuracy was significantly above chance for every ROI in every task (significance evaluated using a permutation test; FDR corrected; all q < 0.01; see *Methods*). We also observed that accuracy was highest for the *Linear-2* binary classifier (V2 accuracy averaged across tasks: 0.86 ± 0.02; mean ± SEM across 10 participants), followed closely by

the *Linear-1* classifier (V2 accuracy averaged across tasks: 0.80 ± 0.02), with lowest accuracy
for the *Nonlinear* classifier (V2 accuracy averaged across tasks: 0.72 ± 0.02). However, the
overall accuracy of these binary classifiers did not differ significantly across tasks: for each
classifier, we performed a two-way repeated measures ANOVA on the classifier values with
factors of ROI and task, and found significant main effects of ROI, but no main effects related to
task (see Supplementary Table 2 for test statistics).
240
Given that there was no difference in overall binary classifier accuracy across tasks, we
next performed a more targeted analysis, based on the hypothesis that task-related differences
in category discriminability might be limited to a subset of trials, and therefore would not be
measurable when averaging across all trials. Specifically, we predicted stronger effects for
shapes nearer to the category boundary versus shapes further from the boundary. To test this,
we used the same series of binary classifiers from the previous analysis, but we separated test
trials into two groups based on distance to the boundary: "near" trials consisted of the 8 main
grid shapes that were closest to the classifier boundary, while "far" trials consisted of the 8
shapes further from the boundary (Figure 3, see diagrams on right side). Note that the "near"
group does not include the set of trials that are outside the main grid and closest to the active
boundary in each task (i.e., "hard" trials; light gray dots in Figure 1B), but see Figure 8 for
discussion of this trial group. We then computed accuracy within each of these trial subsets,
using data from the *Linear-1* and *Linear-2* tasks only.

Figure 3. Category separability differs across tasks, only for trials near the decision boundary. Using the binary classifiers that were trained to predict category according to either the *Linear-1* or *Linear-2* decision rule (see Figure 2A-B), we separately computed accuracy using test set trials that were either far or near from the classifier boundary. Each panel shows the results for a different binary classifier (trained to predict either the *Linear-1* or *Linear-2* category), and different colors indicate data from different tasks. **(A)** Accuracy for "far" trials, consisting of the 8 main grid shapes furthest from the classifier boundary (see diagrams on right side of panel for illustration). **(B)** Accuracy for "near" trials, consisting of the 8 main grid shapes nearest to the classifier boundary. In (**A**-**B**), the gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants.

As predicted, this analysis revealed a difference between near and far trials. Classifier accuracy was overall higher for far trials versus near trials, which was expected based on the difference in stimulus discriminability on these trial types. Importantly, we also observed that for near trials only, there was an interaction between classifier boundary and task, such that the accuracy of each classifier appeared higher when the classifier matched the boundary that was currently active in the task. This effect was most pronounced in early areas such as V2. We examined this pattern by performing a three-way repeated measures ANOVA on the classifier accuracy values for near trials, which revealed significant main effects of ROI, Task, and Boundary, as well as a Task x Boundary interaction (ROI: $F_{(7,63)} = 65.53$, $p < 0.001$; Task: $F_{(1,9)} = 5.37$, $p = 0.044$; Boundary: $F_{(1,9)} = 9.33$, $p = 0.014$; Task x Boundary: $F_{(1,9)} = 8.99$, $p = 0.011$; p-values obtained using permutation test; see Supplementary Table 3 for complete set of test statistics). We then examined each classifier boundary separately, which showed that across all ROIs, the accuracy of the *Linear-2* classifier for near trials was higher when using data from the

Linear-2 task versus the *Linear-1* task (two-way repeated measures ANOVA; ROI: $F_{(7,63)}$ =
50.00, p < 0.001; Task: $F_{(1,9)}$ = 10.30, p = 0.011; ROI x Task: $F_{(7,63)}$ = 0.83, p = 0.570). At the
single ROI level, this difference was significant in V2 ($t_{(9)}$ = -3.27, p = 0.009; paired t-test with
permutation; see *Methods*), and V3 ($t_{(9)}$ = -2.80, p = 0.024). However, when examining the
accuracy of the *Linear-1* classifier across tasks, no significant difference was observed (two-way
repeated measures ANOVA; ROI: $F_{(7,63)}$ = 42.38, p < 0.001; Task: $F_{(1,9)}$ = 0.05, p = 0.828; ROI x
Task: $F_{(7,63)}$ = 0.75, p = 0.627). Overall, these results support the idea that on near trials, shape
representations may be modified adaptively to become more separable across the task-relevant
boundary, particularly during the *Linear-2* task. Notably, performing the same test on the
classifier accuracy values from far trials showed no significant interaction between task and
classifier boundary (see Supplementary Table 3), suggesting that the modulatory effect of task
on visual representations was limited to trials closer to the decision boundary.
300
To evaluate whether a similar interaction between task, boundary and distance was present for
the *Nonlinear* boundary, we performed a similar analysis for the *Nonlinear* binary classifier
(Figure 4). Specifically, we computed *Nonlinear* classifier accuracy, separately for trials that
were near versus far from the *Nonlinear* decision boundary. In this case, however, we did not
observe any consistent differences in classifier accuracy across tasks, for either near trials (two-
way repeated measures ANOVA; ROI: $F_{(7,63)}$ = 45.99, p < 0.001; Task: $F_{(2,18)}$ = 0.19, p = 0.829;
ROI x Task: $F_{(14,126)}$ = 0.77, p = 0.696), or far trials (two-way repeated measures ANOVA; ROI:
$F_{(7,63)}$ = 59.44, p < 0.001; Task: $F_{(2,18)}$ = 1.01, p = 0.380; ROI x Task: $F_{(14,126)}$ = 0.66, p = 0.804).

Figure 4. Separability of representations across the *Nonlinear* boundary does not differ significantly across tasks. We computed classifier accuracy for the *Nonlinear* classifier (Figure 2C), separately for trials near versus far from the category boundary. **(A)** Accuracy computed using "far" trials, meaning the four points in the main grid that fell furthest from the two category boundaries (i.e., four corners of the shape space grid). **(B)** Accuracy computed using "near" trials, meaning the 12 points in the main grid that fell nearest to either of the two category boundaries. In (**A**-**B**), the gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants.

Next, we investigated visual cortex representations at a finer level of granularity, by training a 16-way multinomial classifier (Figure 2D). In contrast to the binary classifier analysis, which reduces all stimuli to two discrete categories, this multinomial classifier treats each of the individual shapes as a distinct category, and therefore may be able to pick up on more fine-grained changes to the overall representational space that occur across tasks. As before, we trained and tested this classifier using data from each task separately. We observed that overall 16-way classification accuracy was highest in V2 (16-way accuracy averaged across tasks: 0.34 ± 0.04; mean ± SEM across 10 participants), followed by V1 (0.32 ± 0.05) and V3 (0.27 ± 0.03). Participant-averaged classification accuracy was significantly above chance for every ROI in every task (significance evaluated using a permutation test; FDR corrected; all q < 0.01; see *Methods*).

To characterize the neural shape space, we used the output of the 16-way classifier to compute a confusion matrix for each ROI and for each task, which captures how often the classifier assigned each shape label to each shape in the test dataset (Figure 5; see *Methods*). For V1, this confusion matrix revealed that shape confusability was related to distance in shape space, with the classifier tending to make more errors between shapes that were adjacent in shape space (off-diagonal structure in Figure 5A). This relationship with distance can also be seen by plotting the proportion of predictions as a function of the distance between predicted and actual shape space coordinates (Figure 5B). Importantly, the distances between shape space points were not specified in the construction of the classifier, where all 16 points were treated as independent categories. Thus, the emergence of this structure in the classifier confusion matrix provides evidence for a two-dimensional representation of the shape space grid in V1. A similar pattern was seen in all other ROIs tested.

Figure 5. Classifier confusion matrices suggest restructuring of shape representations between the *Linear-1* and *Linear-2* tasks. **(A)** Classifier confusion matrices for V1 in each task, where each row represents the set of trials on which a given shape was actually shown, and the columns represent the proportion of those trials that the classifier predicted as having each of the 16 shape labels (each row sums to 1). Confusion matrices were computed using main grid trials only, and are averaged across 10 participants. **(B)** A simplified view of the classifier confusion data for V1: we computed the proportion of trials on which the actual and predicted shapes were separated by a given distance in shape space. Colored lines and shaded error bars indicate mean ± SEM across 10 participants. **(C)** Template matrices for the *Linear-1* and *Linear-2* tasks, representing the pattern of confusability expected for a perfect binary representation of each decision boundary. In A and C, the axis labels are coordinate pairs which

represent the position of stimuli in shape space: (axis 1 coordinate, axis 2 coordinate). These
are analogous to the x and y coordinates in Figure 1B. The *Linear-1* template distinguishes
stimuli based on their axis 1 coordinate (x), while the *Linear-2* template distinguishes stimuli
based on their axis 2 coordinate (y). **(D)** The similarity (Pearson correlation coefficient, z-
transformed) between actual and template confusion matrices for each task and each ROI. Gray
dots represent individual participants, colored circles and error bars represent the mean ± SEM
across 10 participants. See Supplementary Figure 1 for an analogous analysis using a template
for the *Nonlinear* task.

387
388

Next, we examined how well the neural shape space measured in each task aligned with
each decision rule. To examine this, we first constructed "template" confusion matrices for the
Linear-1 and *Linear-2* boundaries, where each template had 1 for shape pairs that were on the
same side of the category boundary for that task and 0 for shape pairs that were on different
sides (Figure 5C). We then correlated these template matrices with the real confusion matrices
for each task (Figure 5D). This analysis revealed that the similarity of confusion matrices to
each template differed depending on task. A three-way repeated measures ANOVA on the z-
transformed template similarity values showed main effects of ROI and Template, as well as a
significant ROI x Template interaction and a significant Task x Template interaction (ROI: $F_{(7,63)}$
= 46.42, p < 0.001; Task: $F_{(1,9)}$ = 8.06, p = 0.020; Template: $F_{(1,9)}$ = 21.05, p = 0.001; ROI x Task:
$F_{(7,63)}$ = 1.41, p = 0.217; ROI x Template: $F_{(7,63)}$ = 3.25, p = 0.004; Task x Template: $F_{(1,9)}$ = 8.89,
p = 0.015; ROI x Task x Template: $F_{(7,63)}$ = 0.97, p = 0.461; p-values obtained using permutation
test; see *Methods*). Evaluating the similarity values for each template separately, we found that
across all ROIs, the *Linear-2* template was significantly more similar to confusion matrices
computed from the *Linear-2* task versus the *Linear-1* task (two-way repeated measures
ANOVA; ROI: $F_{(7,63)}$ = 31.99, p < 0.001; Task: $F_{(1,9)}$ = 15.62, p = 0.003; ROI x Task: $F_{(7,63)}$ = 0.97,
p = 0.467). Post-hoc tests showed that the difference in similarity to the *Linear-2* template
between the *Linear-2* and *Linear-1* tasks was significant in LO1 ($t_{(9)}$ = -2.93, p = 0.007; paired t-
test with permutation; see *Methods*). These findings suggest that shape representations in LO1
were more aligned with the *Linear-2* template when the *Linear-2* boundary was relevant than
when it was irrelevant for the present task. However, the similarity of confusion matrices to the
Linear-1 template did not differ significantly across tasks (two-way repeated measures ANOVA;
ROI: $F_{(7,63)}$ = 32.57, p < 0.001; Task: $F_{(1,9)}$ = 0.49, p = 0.502; ROI x Task: $F_{(7,63)}$ = 1.53, p =
0.175). Additionally, when we constructed a template for the *Nonlinear* task, we did not observe
a difference in the similarity of confusion matrices to the *Nonlinear* template across tasks
(Supplementary Figure 1). Together, these results suggest that shape representations in visual
cortex during our task may reorganize in a way that reflects the current decision boundary and
shifting cognitive demands.

417
418
419
420

Figure 6. Illustration of how classifier "confidence" was computed with respect to each binary decision boundary. **(A)** *Linear-1* confidence, or confidence with respect to the *Linear-1* category boundary, was computed based on the difference between the total probability assigned by the 16-way classifier to each side of the boundary (see *Methods*). Left and right panels represent data from V1 in the *Linear-1* and *Linear-2* tasks, respectively, averaged across all participants. In each of the plots, each square represents a bin of shape space positions in the test dataset, and the color indicates the average confidence assigned to the correct category for that test trial (red) versus the incorrect category (blue). Arrows labeled "easy" and "hard" indicate the trial types, as in Figure 1B; the "hard" trial group was only used to generate Figure 8. **(B)** Same as A**,** but showing *Linear-2* confidence. An analogous procedure was also used to compute *Nonlinear* confidence; see *Methods.*

As in the binary classifier analysis, we then asked whether these representational changes were more pronounced for shapes nearer to the category boundary than shapes further from the boundary. We again divided the trials into near and far groups based on distance to the boundary. To measure the category separability of shapes in each of these distance bins, we computed a continuous measure we refer to as classifier confidence (Figure 6). Confidence is a single-trial measure, computed with respect to each of the category boundaries separately, and was computed by taking the output of the 16-way classifier described above and comparing the total probability assigned by the classifier to points on each side of each boundary. Larger positive values indicate higher separability of shapes across the boundary of interest. We refer to these measures, with respect to each boundary, as *Linear-1* confidence, *Linear-2* confidence, and *Nonlinear* confidence.

Figure 7. Discriminability of *Linear-1* and *Linear-2* shape categories depends on task and proximity to category boundaries. To obtain a continuous estimate of shape category discriminability, we used our 16-way multinomial classifier (see Figure 2D) to compute classifier confidence toward the correct binary category on each trial (see Figure 6). Confidence was computed with respect to the *Linear-1* categorization boundary (*Linear-1* confidence; left) or the *Linear-2* categorization boundary (*Linear-2* confidence; right). **(A)** Confidence computed using "far" trials, meaning the 8 points in the main grid that fell furthest from the category boundary of interest. **(B)** Confidence computed using "near" trials, meaning the 8 points in the main grid that fell nearest to the boundary of interest. In (**A-B**), the gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants. For an analogous version of this analysis based on a binary classifier, see Supplementary Figure 2.

We then compared *Linear-1* confidence and *Linear-2* confidence across the *Linear-1* and *Linear-2* tasks (Figure 7). Overall, both types of confidence were highest for trials furthest from the boundary (Figure 7A), followed by near trials (Figure 7B). This pattern is expected given that shapes further from the boundary are more distinctive from one another, while shapes nearer to the boundary are more ambiguous. In addition, this analysis revealed effects of task condition that differed for near and far trials. For trials in the far group, a three-way repeated measures ANOVA showed main effects of ROI and confidence boundary (i.e., *Linear-1* confidence versus *Linear-2* confidence), but no main effect of task or interaction between task and boundary (Supplementary Table 4), suggesting that discriminability of shapes across the *Linear-1* and *Linear-2* boundaries did not differ across tasks for this group of trials. For the near

trials, however, there was also a significant interaction between task and boundary
(Supplementary Table 4). When each boundary was examined separately for each of these trial
groups, we found a main effect of task on *Linear-2* confidence for the near trials (two-way
repeated measures ANOVA on near trials; ROI: $F_{(7,63)}$ = 30.05, p < 0.001; Task: $F_{(1,9)}$ = 13.65, p
= 0.005; ROI x Task: $F_{(7,63)}$ = 0.36, p = 0.925), with *Linear-2* confidence showing higher values
for the *Linear-2* task, across all ROIs, than the *Linear-1* task. As with the previous analyses, the
effect of task was larger for the *Linear-2* boundary than for the *Linear-1* boundary – there was
no main effect of task seen for the *Linear-1* confidence values for near trials (ROI: $F_{(7,63)}$ = 23.58,
p < 0.001; Task: $F_{(1,9)}$ = 0.10, p = 0.757; ROI x Task: $F_{(7,63)}$ = 0.62, p = 0.751). As a further test,
we also performed a version of this classifier confidence analysis using the output of the simpler
binary classifiers presented earlier (Supplementary Figure 2). This revealed the same pattern of
results, namely an interaction between the classifier boundary and the task, in which *Linear-2*
confidence values were significantly higher when computed from the *Linear-2* task versus the
Linear-1 task. This indicates that the difference in classifier confidence across tasks is not
dependent on the classifier training method used.
487
488   In addition to comparing confidence across the two linear boundaries, we measured
489   *Nonlinear* confidence for the far and near trials in each task (Supplementary Figure 3). As
490   before, confidence values tracked the distance of shapes from the boundary, with highest
491   overall confidence observed for far trials. In contrast to the results with *Linear-2* confidence,
492   however, *Nonlinear* confidence did not show any significant differences across tasks.
493
Finally, we evaluated whether the discriminability of shape representations across the
relevant category boundary in each task was associated with behavioral performance. To test
this, we compared classifier confidence for correct versus incorrect trials: focusing here on only
the "hard" trials (see light gray points in Figure 1B), because these had the highest rate of
incorrect responses. To ensure a fair comparison across correct and incorrect trials, we used
bootstrap resampling to match the distribution of stimulus positions sampled in each group of
trials; see *Methods* for details. As shown in Figure 8, this analysis revealed a significant
difference in classifier confidence between correct and incorrect trials in both the *Linear-2* and
the *Nonlinear* tasks, with confidence tending to be higher for correct trials than incorrect trials,
particularly in early areas V1, V2, and V3. A two-way repeated measures ANOVA with factors of
ROI and correctness revealed a significant main effect of correctness for both the *Linear-2* and
Nonlinear tasks, and a significant interaction between ROI x correctness for the *Nonlinear* task
(*Linear-2;* ROI: $F_{(7,63)}$ = 10.21, p < 0.001; Correctness: $F_{(1,9)}$ = 6.33, p = 0.031; ROI x
Correctness: $F_{(7,63)}$ = 1.81, p = 0.099; *Nonlinear*; ROI: $F_{(7,63)}$ = 7.55, p < 0.001; Correctness: $F_{(1,9)}$
= 8.68, p = 0.016; ROI x Correctness: $F_{(7,63)}$ = 2.82, p = 0.011; p-values obtained using
permutation test; see *Methods*). At the individual ROI level, confidence was significantly higher
for correct versus incorrect trials in V1 during both the *Linear-2* and the *Nonlinear* tasks (*Linear-
2;* $t_{(9)}$ = 3.62, p = 0.007; *Nonlinear;* $t_{(9)}$ = 3.39, p = 0.008; paired t-test with permutation; see
Methods), and in V2 during the *Linear-2* task ($t_{(9)}$ = 2.91, p = 0.022). The *Linear-1* task showed
no significant differences in confidence for correct versus incorrect trials (ROI: $F_{(7,63)}$ = 4.90, p <
0.001; Correctness: $F_{(1,9)}$ = 0.40, p = 0.543; ROI x Correctness: $F_{(7,63)}$ = 0.98, p = 0.453). These
results indicate that the separability of shape representations in early visual cortex across the

task-relevant category boundary was associated with behavioral performance, at least for two
out of three categorization tasks.
518
519

520
521
Figure 8. Task-relevant shape categories are more discriminable on correct versus incorrect
trials. In each task, classifier confidence was computed with respect to the relevant category
boundary for that task. Confidence was computed using "hard" trials only (those not on the main
grid, and nearest the relevant boundary), separately for trials with correct and incorrect
behavioral responses. The set of shape space positions sampled on correct and incorrect trials
was matched using resampling to ensure that the effect was not driven by stimulus differences;
see *Methods* for details. Gray dots represent individual participants, colored circles and error
bars represent the mean ± SEM across 10 participants.
530

Discussion

Our goal was to determine whether and how human visual cortex representations of
shape stimuli are adaptively modulated when switching between distinct task contexts. To test
this, we trained participants to perform a categorization task on shape silhouette stimuli within a
two-dimensional shape space (Figure 1). Participants categorized shapes according to different
categorization rules (*Linear-1, Linear-2, Nonlinear*) on interleaved fMRI scanning runs, and we
used multivariate decoding to explore how neural representations shift based on decision rules
and the relative positions of shapes within the two-dimensional stimulus space. We showed that
the discriminability of shapes across each linear boundary, as measured by classifier accuracy
and classifier confidence, was higher when that boundary was relevant to the current task.
These effects were most pronounced in early areas V1-V3, and were strongest for shapes
located nearest to the active categorization boundary (Figure 3, Figure 7). We also used a

confusion matrix analysis to show that shape representations became more aligned with the
Linear-2 boundary when participants were performing the *Linear-2* task versus the *Linear-1*
task, with the largest effect observed in LO1 (Figure 5). Finally, we showed that the
discriminability of shapes across relevant category boundaries was higher on correct versus
incorrect trials, indicating a link with behavioral task performance (Figure 8). Together, these
results demonstrate that performance of a categorization task with a dynamically changing task
boundary is accompanied by changes to neural representations in human visual cortex.

The average accuracy of our classifiers, across tasks, was highest in V2 followed by V1
and V3. This high decoding accuracy in early areas is surprising in light of earlier work
suggesting that higher visual areas like ITC and LOC encode shapes similar to ours (i.e., radial
frequency components (RFC)-defined silhouettes) in a way that matches perceptual similarity
(Drucker & Aguirre, 2009; Op de Beeck et al., 2001), and that LOC is critically involved in shape
computations (Vinberg & Grill-Spector, 2008). Work in non-human primates also indicates that
neurons in ITC, as well as in V4, are more strongly tuned for shape and contour than neurons in
V1 (Connor et al., 2007; DiCarlo & Maunsell, 2000; Pasupathy & Connor, 1999; Tanaka, 1993,
1996). One reason for our observation of higher decoding accuracy in early areas is that our
stimuli were silhouettes presented at a fixed size and position, so invariance to size or position
was not required to encode them accurately. As a result, fine-grained retinotopic and orientation
tuning in areas like V1-V3 was likely sufficient to encode the shapes with high accuracy, without
the need for an explicit – or invariant – contour or shape representation. Importantly, the goal of
our experiment was not to measure abstract representations of shape or contour *per se* but to
measure how visual representations change in accordance with dynamically varying decision
boundaries, and our relatively simple stimulus set was appropriate for this goal.

The effects of task context on classifier accuracy and classifier confidence (Figure 3,
Figure 7), as well as association of classifier confidence with behavioral performance (Figure 8),
also tended to be strongest in early visual areas. This advantage for early areas may be due in
part to the higher signal-to-noise ratio (SNR) of decoding accuracy in V1-V3, but it may also
suggest that representations in these areas are particularly important for performance of our
decision task. The findings of strong task-dependent effects in early retinotopic areas align with
recent rodent studies, which show that representations within sensory areas contain information
pertinent to task goals, motor outcomes, and prior knowledge about sensory environments
(Ebrahimi et al., 2022; Findling et al., 2023; Mimica et al., 2023; Niell & Stryker, 2010; Stringer
et al., 2019). Extending these findings, our study demonstrates that human visual areas are
more actively involved with decision-related computation than previously thought. Our results
demonstrate that human sensory areas not only code for temporally varying task contexts but
also dynamically integrate this information with incoming sensory inputs to optimize decision
processes. This observation challenges the traditional view that sensory areas are primarily
dedicated to basic sensory processing, suggesting a more multifaceted role in cognitive
computation.

A plausible mechanism for guiding dynamic task coding and context-dependent
representation of sensory inputs in humans may involve the deployment of selective attention.
By flexibly prioritizing processing of relevant stimulus features based on current task goals,

attention may guide the integration of sensory information with shifting task demands.
Specifically, our observed task-dependent effects in early retinotopic areas are consistent with
the literature on feature-based attention, which has shown that directing attention to simple
visual features can modulate representations in early visual cortex (X. Chen et al., 2012; Foster
& Ling, 2022; Gundlach et al., 2023; Jehee et al., 2011; Liu et al., 2003, 2007; Martinez-Trujillo
& Treue, 2004; Mirabella et al., 2007; Saenz & Boynton, 2003; Serences & Boynton, 2007;
Treue & Maunsell, 1996, 1999; Yoo et al., 2022). By modulating neurons coding for perceptual
features that differentiate between categories, feature-based attention could provide a
mechanism for improving the separability of different stimulus categories (Navalpakkam & Itti,
2007; Scolari et al., 2012; Scolari & Serences, 2009). Our result of early modulations is also
consistent with Ester et al. (2020), who found biases in orientation representations that were
related to categorization, although their paradigm used a single category boundary as opposed
to a dynamically updated boundary.

598   Importantly, however, our experiment differs from typical paradigms for studying feature-
based attention (Martinez-Trujillo & Treue, 2004; Saenz & Boynton, 2003; Treue & Maunsell,
1996; Treue & Maunsell, 1999; Desimone & Duncan, 1995) in that participants were not cued
explicitly to a single elementary feature dimension (such as orientation or motion direction), and
instead were required to categorize stimuli along axes in an abstract shape space. Within the
shape space, simple features like a single orientation or retinotopic position are not sufficient to
determine the category of a shape, so information must be integrated over multiple areas of the
image and multiple low-level feature dimensions in order to solve the task. In this light, one
hypothesis for our observed results is that during each task, a subset of the neurons within early
visual cortex are tuned for feature combinations that are diagnostic of the relevant category
distinction. These subpopulations may be tuned for specific retinotopic regions of the image,
features like orientation or curvature, or combinations of these properties. Top-down
modulations may then selectively target these particular subpopulations, leading to an increase
in shape discriminability at the population level. In this respect, our results go beyond existing
knowledge on selective attention, by showing that a mechanism similar to feature-based
attention, perhaps combined with spatial attention, may operate in visual cortex within the
context of a more complex, abstract decision-making task.

615   Relatedly, other work using more complex stimuli such as three dimensional objects and
human bodies has also shown feature-based attention effects in higher visual areas such as
LOC and the extrastriate body area (EBA), as opposed to early visual cortex (Jackson et al.,
2017; Thorat & Peelen, 2022). As discussed earlier, the fact that we saw larger effects in early
visual areas versus higher areas may be due to the fact that our task did not require position-
invariant representations of shape or contour. Interestingly, Jackson et al. (2017) also examined
early visual areas in their study of three-dimensional object coding, and found that while LOC
encoded more information about a task-relevant object dimension, no such effect was found in
early visual areas. One possible explanation for this is that our stimuli subtended a large portion
of the visual field, with the most category-diagnostic features distributed across a range of
retinotopic positions, while in the stimuli used by Jackson et al., the task-relevant stimulus
features were localized to a small region of the image. This difference in spatial distribution, and
possibly the allocation of spatial attention, may explain why we observed task-related

modulations in early retinotopic cortex while Jackson et al. did not. More generally, these
observations may indicate that attentional modulations in V1-V3 are most important for task
performance when stimuli are relatively simple and require fine-grained spatial detail (e.g.,
oriented gratings, two-dimensional silhouettes in our task), than when stimuli are more complex
and require position invariance. In keeping with this idea of attention adapting dynamically to the
most informative features for a task, a recent behavioral study demonstrated that feature-based
attention is adaptively allocated according to experience with the variance of feature
distributions (Witkowski & Geng, 2022). Our findings extend these prior studies by
demonstrating feature-based attention as a potential mechanism for effectively integrating
sensory information with changing task requirements within human sensory cortex.

Despite the relatively low classifier accuracy values that were observed in higher areas,
we did observe a significant effect of task-relevance in LO1 based on the confusion matrix
analysis in Figure 5. In this analysis, we demonstrated that classifier confusion matrices from
LO1 were more aligned with the *Linear-2* task template during the *Linear-2* task versus the
Linear-1 task. The divergence of this finding from our classifier accuracy and confidence
analyses, in which early areas showed larger task effects than LO1, may indicate that the nature
of representational changes in LO1 across categorization tasks differs from the changes in V1-
V3. Specifically, the confusion matrix analysis tests the hypothesis that shape representations in
each task become more aligned with a binary, categorical code, and tests this hypothesis using
all trials together. The classifier accuracy and confidence analyses, on the other hand, test for
an increase in category discriminability specifically for trials that are near the boundary. In this
light, one interpretation is that context-related changes in early areas reflect subtle changes in
discriminability that are limited to the area near the category boundary. These subtle changes
allow the overall structure of the representational space to be largely maintained across tasks in
a stable sensory code. On the other hand, changes in LO1 may reflect a more dramatic
restructuring of sensory codes into a format that resembles a binary or categorical code for each
task. Such a difference would be consistent with LO1 being a higher visual area more closely
aligned with decision processes than early areas. In addition to this, the confusion matrix
analysis captures changes to the relationship between all 16 shapes in the main shape space
grid, including pairs on the same side of the boundary, while the classifier accuracy and
confidence analyses only capture the discriminability of shapes across the category boundary.
Based on this, another (non-exclusive) hypothesis is that the changes in LO1 from the *Linear-1*
task to the *Linear-2* task are primarily driven by re-structuring of shape representations within a
given category (i.e. "acquired equivalence"; Goldstone, 1994) as opposed to an increase in
discriminability across the boundary. Further experiments will be needed to evaluate these
possibilities.

When classifier accuracy and confidence values were broken down based on proximity
to the category boundary, we observed the largest effects of categorization task on confidence
for stimuli nearest the boundary, and no effect of task for the furthest stimulus positions. This
scaling of categorization effects with proximity to the boundary is consistent with a previous
fMRI experiment (Ester et al., 2020) as well as past behavioral experiments (Ashby & Maddox,
2005; Goldstone, 1994, 1998; Livingston et al., 1998; Newell & Bülthoff, 2002). These
convergent findings suggest that top-down modulatory effects in early visual cortex are

strengthened on trials with higher category ambiguity, facilitating perceptual discrimination of
these challenging stimuli. Importantly, our results also build on these past findings by
demonstrating an increase in the discriminability of representations near the decision boundary
during a task that requires flexible switching between multiple decision boundaries.

Task context had more consistent effects on discriminability with respect to the *Linear*
tasks compared to the *Nonlinear* task, with no significant difference across tasks observed for
Nonlinear classifier accuracy (Figure 4). This difference may be due to the fact that the
Nonlinear task required using a non-linear decision boundary. The non-linear boundary was
more challenging behaviorally, as demonstrated by the slower RTs and lower accuracy
observed in the *Nonlinear* task compared to the *Linear-1* and *Linear-2* tasks, which is also
consistent with a past report showing that a quadrant task with similar stimuli was more
challenging for macaques to learn than a linear rule (Op de Beeck et al., 2001). Notably, our
image similarity analysis (Figure 1D) suggested an even more dramatic difference in difficulty
between the *Nonlinear* task and the *Linear* tasks, compared to the modest difference seen
behaviorally. This may suggest that human observers used a more complex strategy to solve
the *Nonlinear* task, allowing them to do relatively well on the *Nonlinear* task despite the low
separability of the *Nonlinear* categories in image space. For example, they might have first
identified the quadrant each shape belonged to, then mapped this quadrant to a category label
using an abstract rule.

In terms of our classifier results, the non-linearity of the boundary may also explain the
lack of a consistent task-related modulation of *Nonlinear* discriminability in visual cortex. It is
possible that while top-down mechanisms are capable of selectively enhancing representations
along one continuous axis in a perceptual space, such a mechanism does not exist for non-
linear boundaries. Interestingly, although we did not observe a task-related modulation of
Nonlinear confidence, we observed a significant within-task association of *Nonlinear* confidence
with behavioral performance (Figure 8). One explanation for this difference is that a different set
of trials is used for each analysis – the association of confidence with behavioral performance
was computed using hard trials only, while the task-related effect was assessed using easy
trials only. We did not examine task-related effects on classifier confidence for hard trials here,
due to the fact that hard trials sampled different portions of the stimulus space in each task (this
was an intended property of the experimental design; see Figure 1B), which made it challenging
to obtain fair, stable comparisons of confidence across tasks for these trials. However, it is
possible that if sufficient trials had been collected for positions closer to the *Nonlinear* boundary
in each task, a task-related enhancement of *Nonlinear* category coding may have been
measurable. At the same time, the difference in outcomes between these analyses may also
indicate that while discriminability of shapes across the *Nonlinear* boundary does not differ
across task contexts, there is variability in the quality of representations across trials within the
Nonlinear task, and this variability is associated with behavioral performance.

Comparing the two *Linear* tasks, we observed higher SNR for discriminating stimuli
across the *Linear-2* boundary than the *Linear-1* boundary (i.e., higher average accuracy of
binary classifier across the *Linear-2* boundary, and higher values of similarity to *Linear-2*
template, across all tasks). We also observed more consistent effects of task relevance on

Linear-2 accuracy, template similarity, and confidence than the analogous measures with
respect to *Linear-1.* Finally, we did not observe any association of *Linear-1* confidence with
behavioral performance, though such an effect was observed for *Linear-2* and *Nonlinear*
confidence. These findings may be related to the difference in perceptual separability, as
measured by our image similarity analyses, between the *Linear-1* and *Linear-2* categories
(Figure 1D). The *Linear-2* boundary, across which shapes are more perceptually distinctive,
may also be a more effective target of context-dependent processing via selective attention
mechanisms. At the same time, however, we note that several of our analyses also revealed a
significant interaction between task and classifier boundary (Figure 3B, Figure 5D, Figure 7B),
which indicates that there is not simply an increase in signal-to-noise ratio from the *Linear-1* to
Linear-2 task that drives the observed effects, but a specific, task-dependent enhancement of
Linear-2 category separability during the *Linear-2* task. Taken together, these findings may
indicate an asymmetry in the allocation of attention to different dimensions within our shape
space, in a way that reflects physical properties of the stimuli.

Overall, our findings provide evidence for context-dependent modulations of neural
representations in early visual cortex, and show that these effects differ in accordance with
temporally shifting task demands. Shape representations were modified to support
discrimination of currently-relevant shape categories, with effects that were strongest for stimuli
near the decision boundary. Moreover, these effects were associated with task performance.
These results may indicate that visual cortex plays an active computational role in the flexible
categorization of stimuli, providing new insight into how we organize knowledge about visual
stimuli in the face of changing behavioral requirements.

Materials & Methods

Human participants

Ten (10) participants were recruited from the UCSD community, and were adults having normal or corrected-to-normal vision. Participants were between the ages of 24 and 33 (mean = 28.2, std = 3.0), and 7 out of 10 were female. The protocol for this study was approved by the Institutional Review Board at UCSD, and all participants provided written informed consent. As part of this experiment, each participant took part in one behavioral training session lasting approximately 1 hour, for which they were compensated at a rate of $10/hour and three scanning sessions each lasting approximately 2 hours, for which they were compensated at a rate of $20/hour. During each scanning session for this experiment, participants also performed several runs of a n-back (repeat detection) task on the same stimuli used in our main task (see *Main task design*). Data from this task are not analyzed here but are included in our full open dataset (see *Data availability*). Each participant also participated in a separate retinotopic mapping scan session; for eight participants this retinotopic mapping session was performed as part of an earlier experiment and for the remaining two it was performed just prior to the start of the present experiment.

Acquisition of MRI data

All magnetic resonance imaging (MRI) scanning was performed at the UC San Diego Keck Center for Functional Magnetic Resonance Imaging. For the first 7 participants, we used a General Electric (GE) Discovery MR750 3.0T scanner, and for the latter 3 participants, we used a Siemens MAGNETOM Prisma 3.0T scanner. Given that all manipulations were within-subject, we combined data across scanners.

We first discuss the protocols that were used for the GE scans: We used a Nova Medical 32-channel head coil (NMSC075-32-3GE-MR750) to acquire all functional echo-planar imaging (EPI) data, using the Stanford Simultaneous Multislice (SMS) EPI sequence (MUX EPI), with a multiband factor of 8 and 9 axial slices per band (total slices = 72; 2 mm^3 isotropic; 0 mm gap; matrix = 104 x 104; field of view = 20.8 cm; repetition time/time to echo [TR/TE] = 800/35 ms; flip angle = 52°; inplane acceleration = 1). To perform image reconstruction and un-aliasing we used reconstruction code from the Stanford Center for Neural Imaging, on servers hosted by Amazon Web Services. The initial 16 TRs collected at sequence onset were used as reference images in order to transform data from k-space to image space.

For the Siemens scans: We used a Siemens 32-channel head coil (Siemens Medical Solutions, Malvern, PA) to acquire all functional EPI data. Functional runs used a multiband acceleration factor of 4 (slices = 68; 2.5 mm^3 isotropic; 0 mm gap; matrix = 100 x 100; field of view = 25.0 cm; repetition time/time to echo [TR/TE] = 1300/32.60 ms; flip angle = 50°; phase-encoding direction A>>P).

In addition, for both types of scanners, a set of two "topup" datasets (17s each) were collected using forward and reverse phase-encoding directions. For the GE scans, we collected

one set of topups at the halfway point of the session, and for the Siemens scans, we collected
2-3 sets of topups that were evenly distributed through the session. These runs were used to
correct for distortions in the EPI sequences from the same session using topup functionality
(Andersson et al., 2003) in the FMRIB Software Library (FSL; Jenkinson et al., 2012).
In addition to the functional data, we also collected a high-resolution anatomical scan for
each participant as part of that participant's retinotopic mapping session. This anatomical T1
image was used for segmentation, flattening, and delineation of the retinotopic mapping data.
For five out of the ten participants, we acquired this anatomical scan using the same 32 channel
head coil used for functional scanning, and for the remaining five participants, we used an in
vivo eight-channel head coil. Anatomical scans were acquired using accelerated parallel
imaging (GE ASSET on a FSPGR T1-weighted sequence; 1 x 1 x 1 mm^3; 8136 ms TR; 3172 ms
TE; 8° flip angle; 172 slices; 1 mm slice gap; 256 x 192 cm matrix size). When the 32-channel
head coil was used, anatomical scans were corrected for inhomogeneities in signal intensity
using GE's 'phased array uniformity enhancement' (PURE) method.

806 Preprocessing of functional MRI data

Preprocessing of functional data was performed using tools from FSL and FreeSurfer
(available at http://www.fmrib.ox.ac.uk/ fsl and https://surfer.nmr.mgh.harvard.edu). We first
performed cortical surface gray-white matter volumetric segmentation of the anatomical T1
scans for each participant, using the recon-all function in FreeSurfer (Dale et al., 1999). The
segmented T1 data were then used to define cortical meshes on which we defined retinotopic
ROIs (see next section for details). We also used the anatomical T1 data in order to align multi-
session functional data to a common space for each participant. This was performed by using
the first volume of the first scan for each session as a template, and using this template to align
the entire functional session to the anatomical scan for each participant. We used the manual
and automatic boundary-based registration tools in FreeSurfer to perform co-registration
between functional and anatomical data (Greve & Fischl, 2009), then used the resulting
transformation matrix and FSL FLIRT to transform all functional data into a common space
(Jenkinson et al., 2002; Jenkinson & Smith, 2001). Next, we used FSL MCFLIRT to perform
motion correction (Jenkinson et al., 2002), with no spatial smoothing, with a final sinc
interpolation stage, and 12° of freedom. Finally, we performed de-trending to remove slow drifts
in the data using a high-pass filter (1/40 Hz cutoff).
823

Following these initial preprocessing stages, we z-scored the data within each scan run
on a per-voxel basis to correct for differences in mean and variance across runs. This and all
subsequent analyses were performed using Python 3.7.10 (Python Software Foundation,
Wilmington, DE). Next, we obtained a single estimate for each voxel's activation on each trial
by averaging the time series over a window spanning from 3.2-5.6s (4-7 TRs) following image
onset (for subjects S01-S07, who were scanned with a 0.8s TR), or from 2.6-6.5s (2-5 TRs)
following image onset (for subjects S08-S10, who were scanned with a 1.3s TR). See *Main task*
design for more details on task timing and procedure. We then extracted data from voxels within
several regions of interest (ROIs; see next section) that were used for subsequent analyses.

Retinotopic ROI definitions

We defined several retinotopic visual ROIs: V1, V2, V3, V3AB, hV4, LO1, LO2, and IPS, following previously identified retinotopic mapping procedures (Engel et al., 1997; Jerde & Curtis, 2013; Sereno et al., 1995; Swisher et al., 2007; Wandell et al., 2007; Winawer & Witthoft, 2015, Mackey et al., 2017). We combined all intraparietal sulcus (IPS) subregions (IPS0, IPS1, IPS2, IPS3), into a single combined IPS ROI, as this led to improved classifier accuracy relative to the individual sub-regions. For 8 out of 10 participants (all except S08 and S09), retinotopic mapping stimuli consisted of black-and-white contrast reversing checkerboard stimuli that were configured as a rotating wedge (10 cycles, 36 s/cycle), expanding ring (10 cycles, 32 s/cycle), or bowtie shape (8 cycles, 40 s/cycle). During the rotating wedge task, a contrast detection task (detecting dimming events approximately every 7.5 s) was used to encourage covert attention to the stimulus. Average accuracy on this task was 76.75 ± 4.01% (mean ± SEM across 8 participants). The stimulus had a maximum eccentricity of 9.3°. For the remaining participants (S08 and S09), retinotopic mapping stimuli were bars composed of randomly generated moving dots, which participants covertly attended to while performing a motion discrimination task (see Mackey et al., 2017 for details).

After defining retinotopic ROIs using these methods, we further thresholded the ROIs using an independent localizer task to identify voxels that were responsive to the region of space in which shape stimuli could appear (see *Silhouette localizer task* for details on this task). The data from the localizer were analyzed using a general linear model (GLM) implemented in FSL's FMRI Expert Analysis Tool (FEAT; version 6.00). This analysis included performing brain extraction and pre-whitening (Smith, 2002; Woolrich et al., 2001). We generated predicted BOLD responses by convolving each stimulus onset with a canonical gamma hemodynamic response (phase = 0s, s.d. = 3s, lag = 6s), and combined individual runs using a standard weighted fixed effects analysis. We identified voxels that were significantly activated by the stimulus versus baseline ($p < 0.05$, false discovery rate (FDR) corrected). This mask of responsive voxels was then intersected with each ROI definition to obtain the final thresholded ROI definitions. The exception to this was the IPS ROIs, to which we did not apply any additional thresholding; this was because the localizer yielded few responsive voxels in IPS for some participants. See Supplementary Table 1 for the final number of voxels in each ROI, after thresholding.

Shape stimuli

We used a set of shape silhouette stimuli that varied parametrically along two continuous dimensions, generating a 2-dimensional shape space (Figure 1A). Each shape in this space was a closed contour composed of radial frequency components (RFCs; Op de Beeck et al., 2001; Zahn & Roskies, 1972). Each shape was composed of 7 different RFCs, where each component has a frequency, amplitude, and phase. We selected these stimuli because they can be represented in a low-dimensional grid-like coordinate system, but are more complex and abstract relative to simpler stimuli such as oriented gratings. Importantly, the changes along each axis in the shape space involve variability in multiple regions of the image,

so categorizing the shapes correctly required participants to integrate information globally
across the image, rather than focusing on a single part of the shape. To generate the 2-
dimensional shape space, we parametrically varied the amplitude of two RFCs, leaving the
others constant. The manipulation of RFC amplitude was used to define an x/y grid in arbitrary
units that spanned positions between 0-5 a.u., with adjacent grid positions spaced by 0.1 a.u. All
shape space positions on all trials were sampled from this grid of shape space positions. We
also defined a coarser grid of 16 points (a 4x4 grid) which was used to generate the 16 stimuli
that were shown on the majority of trials; this grid is referred to as the "main grid", and included
all x/y combinations of the points [0.1, 1.7, 3.3, 4.9] in shape space coordinates. Stimuli
corresponding to points in shape space that were not part of the main grid were used to make
the tasks more difficult, see *Main task design* for details.
885
We divided the shape space into four quadrants by imposing boundaries at the center
position of the grid (2.5 a.u.) in each dimension. To define the binary categories that were
relevant for each task (see *Main task design)*, we grouped together two quadrants at a time,
with the *Linear-1* task and *Linear-2* tasks grouping quadrants that were adjacent (creating either
a vertical or horizontal linear boundary in shape space), and the *Nonlinear* task grouping
quadrants that were non-adjacent (creating a non-linear boundary). During task training as well
as before each scanning run, we utilized a "prototype" image for each shape space quadrant as
a way of reminding participants of the current categorization rule. The prototype for each
quadrant was positioned directly in the middle of the four main grid positions corresponding to
that quadrant (i.e. the x/y coordinates for the prototypes were combinations of [0.9, 4.1] a.u.).
These prototype images were never shown during the categorization task trials, to prevent
participants from simply memorizing the prototypes. Shapes used in the task were also never
positioned exactly on any quadrant boundary in order to prevent any ambiguity about category.
899

Display parameters

During all scanning runs, stimuli were presented to participants by projecting onto a
screen that was mounted on the inside of the scanner bore, just above the participant's chest.
The screen was visible to the participant via a mirror that was attached to the head coil. The
image projected onto the screen was a rectangle with maximum horizontal eccentricity of 13
degrees (center-to-edge distance) and maximum vertical eccentricity of 10 degrees. In the main
task and silhouette localizer task, the region of the screen in which shapes could appear
subtended a maximum eccentricity of 11 degrees in the horizontal direction, and 9 degrees in
the vertical direction. The fixation point in all tasks was a gray square 0.2 degrees in diameter;
participants were instructed to maintain fixation on this point throughout all experimental runs.
910
In the main task, shapes were displayed as gray silhouettes on a gray background. For
all participants except for the first participant (S01), the shapes were darker than the
background (shape = 31, background = 50; luminance values are in the range 0-255). For S01,
the shapes were lighter than the background (shape = 230, background = 77). The change in
parameters was made because the brighter stimuli shown to S01 led to display artifacts when

scanning subsequent participants, and darker stimuli reduced these artifacts. S01 reported no
artifacts and performed well on the task. No gamma correction was performed.
918

Main task design

The main experimental task consisted of categorizing shape silhouette stimuli (Figure 1)
into binary categories. There were three task conditions: *Linear-1, Linear-2,* and *Nonlinear*, each
of which corresponded to a different binary categorization rule. Shape stimuli were drawn from a
two-dimensional shape space coordinate system (see *Shape stimuli*). The *Linear-1* and *Linear-2*
tasks used a boundary that was linear in this shape space, while the *Nonlinear* task used a
boundary that was non-linear in this shape space (requiring participants to group non-adjacent
quadrants into a single category, see Figure 1 for illustration). Each trial consisted of the
presentation of one shape for 1s, and trials were separated by an inter-trial interval (ITI) that
was variable in length, uniformly sampled from the interval 1-5s. Participants responded on
each trial with a button press (right index or middle finger) to indicate which binary category the
currently viewed shape fell into; the mapping between category and response was counter-
balanced within each scanning session. Participants were allowed to make a response anytime
within the window of 2s from stimulus onset. Feedback was given at the end of each run, and
included the participant's overall accuracy, as well as their accuracy broken down into "easy"
and "hard" trials (see next paragraph for description of hard trials), and the number of trials on
which they failed to respond. No feedback was given after individual trials.
936

Each run in the task consisted of 48 trials and lasted 261s (327 TRs). Of the 48 trials, 32
of these used shapes that were sampled from a grid of 16 points evenly spaced within shape
space ("main grid", see *Shape stimuli*), each repeated twice. These 16 shapes were presented
twice per run regardless of task condition. The remaining 16 trials (referred to as "hard" trials)
used shapes that were variable depending on the current task condition and the difficulty level
set by the experimenter. The purpose of these trials was to allow the difficulty level to be
controlled by the experimenter so that task accuracy could be equalized across all task
conditions, and prevent any single task from being trivially easy for each participant. For each
run of each task, the experimenter selected a difficulty level between 1-13, with each level
corresponding to a particular bin of distances from the active categorization boundary (higher
difficulty denotes closer distance to boundary). These difficulty levels were adjusted on each run
during the session by the experimenter, based on performance on the previous run, with the
goal of keeping the participant accuracy values within a stable range for all tasks (target range
was around 80% accuracy). For the *Nonlinear* task, the distance was computed as a linear
distance to the nearest boundary. The "hard" trials were generated by randomly sampling 16
shapes from the specified distance bin, with the constraint that 4 of the shapes had to come
from each of the four quadrants in shape space. This manipulation ensured that responses were
balanced across categories within each run. For many of the analyses presented here, we
excluded these hard trials, focusing only on the "main grid" trials where the same images were
shown across all task conditions.
957

Participants performed 12 runs of the main task within each scanning session, for a total
of 36 runs across all 3 sessions (with the exception of one participant (S06) for whom 3 runs are
missing due to a technical error). The 12 runs in each session were divided into 6 total "parts"
where each part consisted of a pair of 2 runs having the same task condition and the same
response mapping (3 conditions x 2 response mappings = 6 parts). Each part was preceded by
a short training run, which consisted of 5 trials, each trial consisting of a shape drawn from the
main grid. The scanner was not on during these training runs, and the purpose of these was to
remind the participant of both the currently active task and the response mapping before they
began performing the task runs for that part. The order in which the 6 parts were shown was
counter-balanced across sessions. Before each scan run began, the participant was again
reminded of the current task and response mapping via a display that presented four prototype
shapes, one for each shape space quadrant (see *Shape stimuli* for details on prototype
shapes). The prototypes were arranged with two to the left of fixation and two to the right of
fixation, and the participant was instructed that the two leftmost shapes corresponded to the
index finger button and the two rightmost shapes corresponded to the middle finger button. This
display of prototype shapes was also used during the training runs to provide feedback after
each trial: after each training trial, the four prototype shapes were shown, and the two
prototypes corresponding to the correct category were outlined in green, with accompanying
text that indicated whether the participant's response was correct or incorrect. This feedback
display was not shown during the actual task runs.
978
Before the scan sessions began, participants were trained to perform the shape
categorization tasks in a separate behavioral session (training session took place on average
4.0 days before the first scan session). During this behavioral training session, participants
performed the same task that they performed in the scanner, including 12 main task runs (2
runs for each combination of condition and response mapping; i.e., each of the 6 parts). As in
the scan sessions, each part was preceded by training runs that consisted of 5 trials, each
accompanied by feedback. Participants completed between 1-3 training runs before starting
each part. Average training session accuracy was 0.81 ± 0.02 (mean ± SEM across 10
participants) for the *Linear-1* task, 0.81 ± 0.02 for the *Linear-2* task, and 0.78 ± 0.02 for the
Nonlinear task.
989

Silhouette localizer task

A silhouette localizer task was used to identify voxels that were responsive to all the
regions of retinotopic space where the shape stimuli could appear. For this task, a single
silhouette shape was generated that covered the area spanned by any shape in the main grid.
The silhouette region was rendered with a black-and-white flashing checkerboard (spatial period
= 2 degrees) against a mid-gray background. On each trial, the flashing checkerboard silhouette
stimulus appeared for a total duration of 7s, with trials separated by an ITI that varied between
2-8s (uniformly sampled). During each trial the checkerboard was flashed with a frequency of 5
Hz (1 cycle = on for 100 ms, off for 100 ms). On each cycle, the checkerboard was re-drawn
with a randomized phase. There were 20 trials per run of this task, and participants performed

between 4 and 7 runs of this task across all sessions. During all runs of this task, participants
were instructed to monitor for a contrast dimming event and press a button when the dimming
occurred. Dimming events occurred with a probability of 0.10 on each frame, and were
separated by a minimum of 4 cycles. There were on average 17 dimming events in each run
(minimum 10; maximum 25). Average hit rate (proportion of events correctly detected) was 0.69
± 0.07 (mean ± SEM across 10 participants), and the average number of false alarms per run
was 3.42 ± 1.41 (mean ± SEM across 10 participants).
1007

Image similarity analysis

To estimate the perceptual discriminability of our shape categories, we used two
computer vision models to extract activations in response to each stimulus image. We first used
the GIST model (Oliva & Torralba, 2001), which is based on Gabor filters and captures low-level
spectral image properties. We also extracted features from a pre-trained SimCLR model (T.
Chen et al., 2020), which is a self-supervised model trained using contrastive learning on a
large image database. We selected these two models because the GIST model captures clearly
defined image properties similar to those represented in the early visual system, while the
SimCLR model can capture a wider set of image features, including mid-level and high-level
properties. The GIST model was implemented in Matlab, using a 4x4 spatial grid, 4 spatial
scales, and 4 orientations per spatial scale. The version of SimCLR that we used was
implemented in PyTorch and used a ResNet-50 backbone (pre-trained model downloaded from
https://pypi.org/project/simclr/). We extracted activations from blocks [2,6,12,15] and performed
a max-pooling operation (kernel size = 4, stride = 4) to reduce the size of activations from each
block. We used principal components analysis (PCA) to further reduce the size of activations,
retaining a maximum of 500 components per block, and concatenated the resulting features
across all blocks.
1025

Using these activations, we computed the separability of shape categories across each
of our boundaries (*Linear-1, Linear-2, Nonlinear*) by computing all pairwise Euclidean distances
between main grid shapes in the same category (within-category distances) and main grid
shapes in different categories (between-category distances). We then computed the average of
the within-category distances (w) and between-category distances (b). The separability measure
for each boundary was computed as: (b-w)/(b+w).

Multivariate classifier analysis

We used a multivariate classifier to estimate how well the voxel activation patterns from
each ROI could be used to discriminate different shape stimuli. We performed three different
types of binary classification (*Linear-1, Linear-2, Nonlinear)*, as well as 16-way multinomial
classification, and the following details apply to all classifier types. Classification was performed
within each participant, each ROI, and each task condition separately. Before training the
classifier, we mean-centered the activation patterns on each trial, by subtracting the average
signal across voxels from each trial. We cross-validated the classifier by leaving one run out at a

time during training, looping over held-out test runs so that every run served as the test run
once. During training of the classifier, we used only trials on which main grid shapes were
shown. For the 16-way classifier, we treated each of the 16 unique shapes as distinct classes.
For the binary classifiers, we split the 16 shapes into two classes according to either the *Linear-*
1 category boundary, the *Linear-2* category boundary, or the *Nonlinear* category boundary.
Using these class labels, we then constructed a logistic regression classifier, implemented using
scikit-learn (version 1.0.2) in Python 3.6. We used the 'lbfgs' solver and L2 regularization. To
select the L2 regularization parameter (C), we created a grid of 20 candidate C values that were
logarithmically spaced between 10^{-9} and 1. We then used nested cross-validation on the training
data only to select the C resulting in highest accuracy across folds, and re-fit the model for the
entire training set using the best C parameter. The resulting classifier was then used to predict
the class (1-2, or 1-16) for all trials in the test dataset (note that this included trials where the
viewed shape was not in the main grid, and thus was not included in classifier training). In
addition to a predicted class for each trial, the classifier returned a continuous probability
estimate for each of the classes, obtained using a softmax function.
1055
To evaluate whether the accuracy of the classifier was significantly greater than chance,
we used a permutation test. To do this, we performed 1000 iterations of training and testing the
classifier, constructed in the same way as described above, using shuffled labels for the data.
We always performed shuffling within a given scan run, so that the run labels were kept intact,
and leave-run-out cross-validation was performed as in the original method. To make this
computationally feasible, we did not perform C selection on every shuffling iteration, instead we
used a fixed C value of 0.023 (for the 16-way classifier) or 0.007 (for each of the 2-way
classifiers), which were approximately the median of the C values obtained across all models fit
to the real data. We obtained a p-value for each individual participant, ROI, and task condition
by computing the proportion of shuffle iterations on which shuffled classifier accuracy was
greater than or equal to the real classifier accuracy. To obtain p-values for the participant-
averaged classification accuracy for each ROI and task, we used the same procedure but first
averaged the values across participants, within each shuffle iteration. All reported p-values were
false-discovery-rate (FDR) corrected at q = 0.01 (Benjamini & Hochberg, 1995).

Confusion matrix analysis

For each participant, ROI, and task, we generated a confusion matrix for the 16-way
multinomial classifier. This was a 16 x 16 matrix where each row represents the set of trials on
which a given shape was actually shown, and each column in the row represents the proportion
of those trials that the classifier assigned into each of the 16 classes, and each row sums to 1.
To compute confusion matrices we used only trials in the main grid, and only used trials on
which the participant made a correct behavioral response. To quantify the alignment of
confusion matrices with the representation needed to solve each task, we generated template
confusion matrices for the *Linear-1* and *Linear-2* tasks, where each template matrix had 0 for
pairs of stimuli that were on different sides of the boundary and 1 for pairs of stimuli that were
on the same side of the boundary. We then computed the Pearson correlation coefficient
between each actual confusion matrix and each template confusion matrix. Finally, we applied a

Fisher z-transform to these correlation coefficient values, using the inverse hyperbolic tangent
function (arctanh).

Classifier confidence

To obtain a continuous estimate of the discriminability of shapes belonging to different
binary categories, we computed a measure we term "classifier confidence", which is based on
the continuous probability estimates output by each binary or 16-way classifier. For each
boundary and each individual trial, our measure of classifier confidence was computed as the
difference between the total probability assigned by the classifier to the "correct" binary category
for that trial [p(correct)] and the total probability assigned by the classifier to the "incorrect"
binary category for that trial [p(incorrect)]. For each of the binary classifiers, it is straightforward
to compute p(correct) and p(incorrect) based on the probability assigned to each binary class.
For the 16-way classifier, we obtained p(correct) by summing the probability assigned to the 8
main grid shapes in the same category as the shape on the current trial (based on whichever
category boundary was currently being considered), and p(incorrect) by summing the probability
assigned to the 8 main grid shapes in the other category. This allowed us to compute classifier
confidence from the 16-way classifier, with respect to each of the three category boundaries.
Note that this measure of confidence can be computed even when the test trial shape is not part
of the main grid. To interpret this measure, large positive values of confidence indicate high
discriminability of shapes across a given category boundary, and large negative or zero values
indicate poor discriminability.
1102
For the analyses where confidence values are broken down by "far" and "near" trials, the
far and near trials are always restricted to positions in the main grid. For the *Linear-1* and
Linear-2 tasks, there are 8 total positions counted as far and 8 counted as near. For the
Nonlinear task, we counted the 4 corner positions as far and the 12 other positions as near.
When average confidence values are reported, they are averaged over behaviorally correct
trials only (unless otherwise specified).

Bootstrap resampling procedures

When comparing classifier confidence values between correct and incorrect trials, we
used bootstrap resampling to match the distribution of shape positions sampled on correct
versus incorrect trials. This controls for the possibility that correct and incorrect trials had
different stimulus properties; for example, harder trials would be more likely to be incorrect. The
difference in stimulus properties could have, if not corrected, contributed to a difference in
average confidence between correct and incorrect trials. This analysis was done using only
"hard" trials (i.e., trials close to the boundary and not on the main grid), because these had the
highest rate of incorrect responses. To perform resampling, for each boundary we collapsed the
set of coordinates sampled on the "hard" trials onto a single axis that ran perpendicular to the
boundary of interest. For the *Nonlinear* task, instead of collapsing coordinates onto a single
axis, we computed the distance between each [x,y] coordinate and the nearest linear boundary,
and multiplied by (+1) for coordinates in nonlinear category 1 or (-1) for coordinates in nonlinear

category 2, which results in a single coordinate value that captures distance from the boundary
as well as category sign. We then binned these coordinates into a set of 12 linearly-spaced bins
that spanned the portion of shape space nearest the boundary (from 1.8 to 3.2 in shape space
coordinates; see *Shape stimuli*). For each participant and task, we then identified a subset of
these 12 bins that were sampled on both correct and incorrect trials, and were also symmetric
around the categorization boundary. We then performed 1,000 iterations on which we
resampled with replacement a set of approximately 100 correct trials and approximately 100
incorrect trials that each evenly sampled from all bins, and computed the average classifier
confidence for this resampled set. The final confidence values for each participant reflect the
average across these 1,000 bootstrapping iterations.

Statistical analysis

To perform statistical comparisons of classifier confidence values and template
correlation coefficient values (see previous sections) across ROIs and categorization tasks, we
used repeated measures ANOVA tests, implemented using *statsmodels* in Python 3.6. To
obtain non-parametric p-values for these tests (which are suitable to ensure that any violations of
the assumptions of the parametric tests do not bias the results), we performed permutation tests
where we shuffled the values within each participant 10,000 times, and computed F-statistics for
each effect on the shuffled data. This resulted in a null distribution of F-values for each effect.
The final p-values for each effect were based on the proportion of iterations on which the
shuffled F-statistic was greater than or equal to the real F-statistic. F-statistics reported in the
text reflect those obtained using the real (unshuffled) data. This procedure for obtaining non-
parametric p-values is similar to previous work (e.g., Sprague & Serences, 2013; Sprague,
Ester, & Serences, 2014; Ester, Sprague & Serences, 2015; Rademaker, Chunharas &
Serences, 2019; Henderson et al., 2022); we also observed qualitatively similar results when
using a parametric significance test as this permutation-based approach is more conservative.
1147
To perform post-hoc tests for differences between tasks in each ROI, we used a paired
t-test with permutation. For each ROI, we computed a t-statistic for the true difference between
the conditions across participants, then performed 10,000 iterations where we randomly
swapped the values within each participant across conditions, with 50% probability. This
resulted in a null distribution of t-statistics. The final two-tailed p-value was obtained by
computing the proportion of iterations on which the shuffled t-statistic was greater than or equal
to the real t-statistic and the proportion of iterations on which the real t-statistic was greater than
or equal to the shuffled t-statistic, taking the minimum and multiplying by 2.

Code availability statement

1157   All code required to reproduce our analyses is available at
1158   https://github.com/mmhenderson/shapeDim.

Data availability

All data used in the present study will be deposited as MATLAB-formatted data in Open Science Framework.

Acknowledgments

This work was supported by NEI R01-EY025872 to JS, NIMH Training Grant in Cognitive Neuroscience (T32-MH020002) to MH, the Swartz Foundation Fellowship for Theory in Neuroscience to NR, and the Kavli Institute for Brain and Mind Postdoctoral Award to NR. We thank Stephanie Nelli for helpful discussions during the inception of this project as well as Anna Shafer-Skelton and Julie Eitzen for their help with data collection. We would like to acknowledge Hans Op de Beeck for providing code that was used for stimulus generation.

Author Contributions

MH and JS conceived the research. MH, JS, and NR designed, performed the research, analyzed data, and wrote the manuscript.

Declaration of Interests

The authors declare no competing interests.

References

Andersson, J. L. R., Skare, S., & Ashburner, J. (2003). How to correct susceptibility distortions in spin-echo echo-planar images: Application to diffusion tensor imaging. *NeuroImage*, *20*(2), 870–888. https://doi.org/10.1016/S1053-8119(03)00336-7

Ashby, F. G., & Maddox, W. T. (2005). Human category learning. *Annual Review of Psychology*, *56*, 149–178. https://doi.org/10.1146/ANNUREV.PSYCH.56.091103.070217

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, *57*(1), 289–300. https://doi.org/10.1111/J.2517-6161.1995.TB02031.X

Biederman, I., Glass, A. L., & Stacy, E. W. (1973). Searching for objects in real-world scenes. *Journal of Experimental Psychology*, *97*(1), 22–27. https://doi.org/10.1037/h0033776

Bruner, J. S. (1957). On perceptual readiness. *Psychological Review*, *64*(2), 123–152. https://doi.org/10.1037/h0043805

Chen, T., Kornblith, S., Norouzi, M., & Hinton, G. (2020). *A Simple Framework for Contrastive Learning of Visual Representations*.

Chen, X., Hoffmann, K.-P., Albright, T. D., & Thiele, A. (2012). Effect of feature-selective attention on neuronal responses in macaque area MT. *Journal of Neurophysiology*, *107*(5), 1530–1543. https://doi.org/10.1152/jn.01042.2010

Connor, C. E., Brincat, S. L., & Pasupathy, A. (2007). Transformation of shape information in the ventral pathway. *Current Opinion in Neurobiology*, *17*(2), 140–147. https://doi.org/10.1016/j.conb.2007.03.002

Cromer, J. A., Roy, J. E., & Miller, E. K. (2010). *Representation of Multiple, Independent Categories in the Primate Prefrontal Cortex*. https://doi.org/10.1016/j.neuron.2010.05.005

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis: I. Segmentation

and surface reconstruction. *NeuroImage*, *9*(2), 179–194.

<u>https://doi.org/10.1006/nimg.1998.0395</u>

Desimone, R., & Duncan, J. (1995). Neural Mechanisms of Selective Visual Attention.

Annual Review of Neuroscience, *18*(1), 193–222.

https://doi.org/10.1146/annurev.ne.18.030195.001205

DiCarlo, J. J., & Maunsell, J. H. R. (2000). Form representation in monkey inferotemporal cortex

is virtually unaltered by free viewing. *Nature Neuroscience*, *3*(8), Article 8.

https://doi.org/10.1038/77722

Drucker, D. M., & Aguirre, G. K. (2009). Different spatial scales of shape similarity

representation in lateral and ventral LOC. *Cerebral Cortex (New York, N.Y. : 1991)*,

19(10), 2269–2280. https://doi.org/10.1093/cercor/bhn244

Ebrahimi, S., Lecoq, J., Rumyantsev, O., Tasci, T., Zhang, Y., Irimia, C., Li, J., Ganguli, S., &

Schnitzer, M. J. (2022). Emergent reliability in sensory cortical coding and inter-area

communication. *Nature 2022 605:7911*, *605*(7911), 713–721.

https://doi.org/10.1038/s41586-022-04724-y

Engel, S., Glover, G. H., & Wandell, B. A. (1997). Retinotopic organization in human visual

cortex and the spatial precision of functional MRI. *Cerebral Cortex*, *7*(2), 181–192.

https://doi.org/10.1093/cercor/7.2.181

Ester, E. F., Sprague, T. C., & Serences, J. T. (2015). Parietal and Frontal Cortex

Encode Stimulus-Specific Mnemonic Representations during Visual Working Memory.

Neuron, *87*(4), 893–905. https://doi.org/10.1016/j.neuron.2015.07.013

Ester, E. F., Sprague, T. C., & Serences, J. T. (2020). Categorical biases in human

occipitoparietal cortex. *Journal of Neuroscience*, *40*(4), 917–931.

https://doi.org/10.1523/JNEUROSCI.2700-19.2019

Findling, C., Hubert, F., Laboratory, I. B., Acerbi, L., Benson, B., Benson, J., Birman, D.,

Bonacchi, N., Carandini, M., Catarino, J. A., Chapuis, G. A., Churchland, A. K., Dan, Y., Dewitt, E. E., Engel, T. A., Fabbri, M., Faulkner, M., Fiete, I. R., Freitas-Silva, L., … Pouget, A. (2023). Brain-wide representations of prior information in mouse decision-making. *bioRxiv*, 2023.07.04.547684. https://doi.org/10.1101/2023.07.04.547684

Folstein, J., Palmeri, T. J., Van Gulick, A. E., & Gauthier, I. (2015). Category Learning Stretches Neural Representations in Visual Cortex. *Current Directions in Psychological Science*, *24*(1), 17–23. https://doi.org/10.1177/0963721414550707

Folstein, J. R., Palmeri, T. J., & Gauthier, I. (2013). Category Learning Increases Discriminability of Relevant Object Dimensions in Visual Cortex. *Cerebral Cortex*, *23*(4), 814–823. https://doi.org/10.1093/cercor/bhs067

Foster, J. J., & Ling, S. (2022). Feature-based attention multiplicatively scales the fMRI-BOLD contrast-response function. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *42*(36), 6894–6906. https://doi.org/10.1523/JNEUROSCI.0513-22.2022

Freedman, D. J., & Assad, J. A. (2016). Neuronal Mechanisms of Visual Categorization: An Abstract View on Decision Making. *Annual Review of Neuroscience*, *39*(1), 129–147. https://doi.org/10.1146/annurev-neuro-071714-033919

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2003). A comparison of primate prefrontal and inferior temporal cortices during visual categorization. *The Journal of Neuroscience : The Official Journal of the Society for Neuroscience*, *23*(12), 5235–5246. https://doi.org/23/12/5235 [pii]

Gauthier, I., Skudlarski, P., Gore, J. C., & Anderson, A. W. (2000). Expertise for cars and birds recruits brain areas involved in face recognition. *Nature Neuroscience*, *3*(2), 191–197. https://doi.org/10.1038/72140

Goldstone, R. (1994). Influences of Categorization on Perceptual Discrimination. *Journal of Experimental Psychology: General*, *123*(2), 178–200. https://doi.org/10.1037/0096-

3445.123.2.178

Goldstone, R. (1998). Perceptual learning. *Annual Review of Psychology*, *49*, 585–612.

https://doi.org/10.1146/ANNUREV.PSYCH.49.1.585

Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-

based registration. *NeuroImage*, *48*(1), 63–72.

https://doi.org/10.1016/j.neuroimage.2009.06.060

Gundlach, C., Wehle, S., & Müller, M. M. (2023). Early sensory gain control is dominated by

obligatory and global feature-based attention in top-down shifts of combined spatial and

feature-based attention. *Cerebral Cortex (New York, N.Y.: 1991)*, bhad282.

https://doi.org/10.1093/cercor/bhad282

Henderson, M. M., Rademaker, R. L., Serences, J. T. (2022). Flexible utilization of spatial- and

motor-based codes for the storage of visuo-spatial information. eLife, 11:e75688.

https://doi.org/10.7554/eLife.75688

Jackson, J., Rich, A. N., Williams, M. A., & Woolgar, A. (2017). Feature-selective Attention in

Frontoparietal Cortex: Multivoxel Codes Adjust to Prioritize Task-relevant Information.

Journal of Cognitive Neuroscience, *29*(2), 310–321.

https://doi.org/10.1162/jocn_a_01039

Jehee, J. F. M., Brady, D. K., & Tong, F. (2011). Attention Improves Encoding of Task-Relevant

Features in the Human Visual Cortex. *Journal of Neuroscience*, *31*(22), 8210–8219.

https://doi.org/10.1523/JNEUROSCI.6153-09.2011

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the robust

and accurate linear registration and motion correction of brain images. *NeuroImage*,

17(2), 825–841. https://doi.org/10.1016/S1053-8119(02)91132-8

Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W., & Smith, S. M. (2012). Fsl.

NeuroImage, *62*(2), 782–790. https://doi.org/10.1016/j.neuroimage.2011.09.015

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of

brain images. *Medical Image Analysis*, *5*(2), 143–156. https://doi.org/10.1016/S1361-

8415(01)00036-6

Jerde, T. A., & Curtis, C. E. (2013). Maps of space in human frontoparietal cortex. *Journal of*

Physiology Paris, *107*(6), 510–516. https://doi.org/10.1016/j.jphysparis.2013.04.002

Jiang, X., Bradley, E., Rini, R. A., Zeffiro, T., VanMeter, J., & Riesenhuber, M. (2007).

Categorization Training Results in Shape- and Category-Selective Human Neural

Plasticity. *Neuron*, *53*(6), 891. https://doi.org/10.1016/J.NEURON.2007.02.015

Liu, T., Larsson, J., & Carrasco, M. (2007). Feature-based attention modulates orientation-

selective responses in human visual cortex. *Neuron*, *55*(2), 313–323.

https://doi.org/10.1016/j.neuron.2007.06.030

Liu, T., Slotnick, S. D., Serences, J. T., & Yantis, S. (2003). Cortical mechanisms of feature-

based attentional control. *Cerebral Cortex (New York, N.Y.: 1991)*, *13*(12), 1334–1343.

https://doi.org/10.1093/cercor/bhg080

Livingston, K. R., Andrews, J. K., & Harnad, S. (1998). Categorical perception effects induced

by category learning. *Journal of Experimental Psychology. Learning, Memory, and*

Cognition, *24*(3), 732–753. https://doi.org/10.1037//0278-7393.24.3.732

Mackey, W. E., Winawer, J., & Curtis, C.E. (2017). Visual field map clusters in human

frontoparietal cortex. *eLife,* 6:e22974. https://doi.org/10.7554/eLife.22974

Martinez-Trujillo, J. C., & Treue, S. (2004). Feature-based attention increases the selectivity of

population responses in primate visual cortex. *Current Biology: CB*, *14*(9), 744–751.

https://doi.org/10.1016/j.cub.2004.04.028

McAdams, C. J., & Maunsell, J. H. (1999). Effects of attention on orientation-tuning functions of

single neurons in macaque cortical area V4. *The Journal of Neuroscience: The Official*

Journal of the Society for Neuroscience, *19*(1), 431–441.

https://doi.org/10.1523/JNEUROSCI.19-01-00431.1999

McKee, J. L., Riesenhuber, M., Miller, E. K., & Freedman, D. J. (2014). Task Dependence of

Visual and Category Representations in Prefrontal and Inferior Temporal Cortices. *Journal of Neuroscience*, *34*(48), 16065–16075. https://doi.org/10.1523/JNEUROSCI.1660-14.2014

Meyers, E. M., Freedman, D. J., Kreiman, G., Miller, E. K., & Poggio, T. (2008). Dynamic Population Coding of Category Information in Inferior Temporal and Prefrontal Cortex. *Journal of Neurophysiology*, *100*(3), 1407–1419. https://doi.org/10.1152/jn.90248.2008

Mimica, B., Tombaz, T., Battistin, C., Fuglstad, J. G., Dunn, B. A., & Whitlock, J. R. (2023). Behavioral decomposition reveals rich encoding structure employed across neocortex in rats. *Nature Communications 2023 14:1*, *14*(1), 1–20. https://doi.org/10.1038/s41467-023-39520-3

Mirabella, G., Bertini, G., Samengo, I., Kilavik, B. E., Frilli, D., Della Libera, C., & Chelazzi, L. (2007). Neurons in Area V4 of the Macaque Translate Attended Visual Features into Behaviorally Relevant Categories. *Neuron*, *54*(2), 303–318. https://doi.org/10.1016/j.neuron.2007.04.007

Navalpakkam, V., & Itti, L. (2007). Search goal tunes visual features optimally. *Neuron*, *53*(4), 605–617. https://doi.org/10.1016/j.neuron.2007.01.018

Newell, F. N., & Bülthoff, H. H. (2002). Categorical perception of familiar objects. *Cognition*, *85*(2), 113–143. https://doi.org/10.1016/S0010-0277(02)00104-X

Niell, C. M., & Stryker, M. P. (2010). Modulation of Visual Responses by Behavioral State in Mouse Visual Cortex. *Neuron*, *65*(4), 472–479. https://doi.org/10.1016/J.NEURON.2010.01.033

Oliva, A., & Torralba, A. (2001). Modeling the Shape of the Scene: A Holistic Representation of the Spatial Envelope *. In *International Journal of Computer Vision* (Vol. 42, Issue 3, pp. 145–175).

Op de Beeck, H. P., Baker, C. I., DiCarlo, J. J., & Kanwisher, N. G. (2006). Discrimination Training Alters Object Representations in Human Extrastriate Cortex. *Journal of*

Neuroscience, *26*(50), 13025–13036. https://doi.org/10.1523/JNEUROSCI.2481-06.2006

Op de Beeck, H. P., Wagemans, J., & Vogels, R. (2001). Inferotemporal neurons represent low-dimensional configurations of parameterized shapes. *Nature Neuroscience*, *4*(12), 1244–1252. https://doi.org/10.1038/nn767

Pasupathy, A., & Connor, C. E. (1999). Responses to contour features in macaque area V4. *Journal of Neurophysiology*, *82*(5), 2490–2502. https://doi.org/10.1152/jn.1999.82.5.2490

Rademaker, R. L., Chunharas, C., & Serences, J. T. (2019). Coexisting representations of sensory and mnemonic information in human visual cortex. *Nature Neuroscience*, *22*, 1336–1344. https://doi.org/10.1101/339200

Rosch, E., Mervis, C. B., Gray, W. D., Johnson, D. M., & Boyes-Braem, P. (1976). Basic Objects in Natural Categories. In *COGNITIVE PSYCHOLOGY* (Vol. 8, pp. 382–439).

Roy, J. E., Riesenhuber, M., Poggio, T., & Miller, E. K. (2010). Prefrontal Cortex Activity during Flexible Categorization. *Journal of Neuroscience*, *30*(25), 8519–8528. https://doi.org/10.1523/JNEUROSCI.4837-09.2010

Saenz, M., & Boynton, G. M. (2003). The role of competing stimuli in feature-based attention. *Journal of Vision*, *3*(9), 727. https://doi.org/10.1167/3.9.727

Scolari, M., Byers, A., & Serences, J. T. (2012). Optimal Deployment of Attentional Gain during Fine Discriminations. *Journal of Neuroscience*, *32*(22), 7723–7733. https://doi.org/10.1523/JNEUROSCI.5558-11.2012

Scolari, M., & Serences, J. T. (2009). Adaptive allocation of attentional gain. *The Journal of Neuroscience*, *29*(38), 11933–11942. https://doi.org/10.1523/JNEUROSCI.5642-08.2009

Serences, J. T., & Boynton, G. M. (2007). Feature-Based Attentional Modulations in the Absence of Direct Visual Stimulation. *Neuron*, *55*(2), 301–312. https://doi.org/10.1016/j.neuron.2007.06.015

Sereno, M., Dale, A., Reppas, J., Kwong, K., Belliveau, J., Brady, T., Rosen, B., & Tootell, R.

(1995). Borders of multiple visual areas in humans revealed by functional magnetic

resonance imaging. *Science*, *268*(5212), 889–893.

https://doi.org/10.1126/science.7754376

Sigala, N., & Logothetis, N. K. (2002). Visual categorization shapes feature selectivity in the

primate temporal cortex. *Nature*, *415*(6869), 318–320. https://doi.org/10.1038/415318a

Smith, S. M. (2002). Fast robust automated brain extraction. *Human Brain Mapping*, *17*(3), 143–

155. https://doi.org/10.1002/hbm.10062

Sprague, T. C., Ester, E. F., & Serences, J. T. (2014). Reconstructions of information in

visual spatial working memory degrade with memory load. *Current Biology : CB*, *24*(18),

2174–2180. https://doi.org/10.1016/j.cub.2014.07.066

Sprague, T. C., & Serences, J. T. (2013). Attention modulates spatial priority maps in the

human occipital, parietal and frontal cortices. *Nature Neuroscience*, *16*(12), 1879–1887.

https://doi.org/10.1038/nn.3574

Stringer, C., Pachitariu, M., Steinmetz, N., Reddy, C. B., Carandini, M., & Harris, K. D. (2019).

Spontaneous behaviors drive multidimensional, brainwide activity. *Science*, *364*(6437).

https://doi.org/10.1126/SCIENCE.AAV7893/SUPPL_FILE/AAV7893_STRINGER_SM.P

DF

Swisher, J. D., Halko, M. A., Merabet, L. B., McMains, S. A., & Somers, D. C. (2007). Visual

Topography of Human Intraparietal Sulcus. *Journal of Neuroscience*, *27*(20), 5326–

5337. https://doi.org/10.1523/JNEUROSCI.0991-07.2007

Tanaka, K. (1993). Neuronal mechanisms of object recognition. *Science (New York, N.Y.)*,

262(5134), 685–688.

Tanaka, K. (1996). Inferotemporal cortex and object vision. *Annual Review of Neuroscience*, *19*,

109–139. https://doi.org/10.1146/annurev.ne.19.030196.000545

Thorat, S., & Peelen, M. V. (2022). Body shape as a visual feature: Evidence from spatially-

global attentional modulation in human visual cortex. *NeuroImage*, *255*, 119207.

https://doi.org/10.1016/j.neuroimage.2022.119207

Treue, S., & Maunsell, J. H. (1996). Attentional modulation of visual motion processing in

cortical areas MT and MST. *Nature*, *382*(6591), 539–541.

https://doi.org/10.1038/382539a0

Treue, S., & Maunsell, J. H. (1999). Effects of attention on the processing of motion in macaque

middle temporal and medial superior temporal visual cortical areas. *The Journal of*

Neuroscience: The Official Journal of the Society for Neuroscience, *19*(17), 7591–7602.

https://doi.org/10.1523/JNEUROSCI.19-17-07591.1999

Vinberg, J., & Grill-Spector, K. (2008). Representation of Shapes, Edges, and Surfaces Across

Multiple Cues in the Human Visual Cortex. *Journal of Neurophysiology*, *99*(3), 1380–

1393. https://doi.org/10.1152/jn.01223.2007

Wandell, B. A., Dumoulin, S. O., & Brewer, A. A. (2007). Visual field maps in human cortex.

Neuron, *56*(2), 366–383. https://doi.org/10.1016/j.neuron.2007.10.012

Winawer, J., & Witthoft, N. (2015). Human V4 and ventral occipital retinotopic maps. *Visual*

Neuroscience, *32*, E020. https://doi.org/10.1017/S0952523815000176

Witkowski, P. P., & Geng, J. J. (2022). Attentional priority is determined by predicted feature

distributions. *Journal of Experimental Psychology: Human Perception and Performance*,

48(11), 1201–1212. https://doi.org/10.1037/xhp0001041

Woolrich, M. W., Ripley, B. D., Brady, M., & Smith, S. M. (2001). Temporal autocorrelation in

univariate linear modeling of FMRI data. *NeuroImage*, *14*(6), 1370–1386.

https://doi.org/10.1006/nimg.2001.0931

Yoo, S.-A., Martinez-Trujillo, J. C., Treue, S., Tsotsos, J. K., & Fallah, M. (2022). Attention to

visual motion suppresses neuronal and behavioral sensitivity in nearby feature space.

BMC Biology, *20*(1), 220. https://doi.org/10.1186/s12915-022-01428-7

Zahn, C. T., & Roskies, R. Z. (1972). Fourier descriptors for plane closed curves. *IEEE*

Transactions on Computers. https://doi.org/10.1109/TC.1972.5008949

Supplementary Material

1425

Supplementary Table 1. Number of voxels in each ROI for each participant. Voxel counts are
concatenated across hemispheres, and reflect the final number of voxels in each ROI, after
thresholding each ROI (except for IPS) based on the results of the Silhouette Localizer task; see
Methods. Note that the size of voxels differed for subjects S01-S07 (2 mm^3 isotropic) and
subjects S08-S10 (2.5 mm^3 isotropic), which leads to smaller voxel counts for the last three
subjects; see *Methods* for details on acquisition parameters.
1432
1433

	S01	S02	S03	S04	S05	S06	S07	S08	S09	S10
V1	1866	1956	2216	2464	2156	2373	1520	669	476	422
V2	1236	1834	1866	1584	1424	1570	1098	579	480	334
V3	1109	1929	1200	1548	1430	1228	1710	487	424	383
V3AB	1013	1964	517	708	812	1256	1171	376	254	302
hV4	277	641	484	1080	578	572	636	238	169	199
LO1	369	331	462	465	352	465	768	307	102	251
LO2	152	322	492	304	230	320	420	156	76	156
IPS	3054	2463	2336	2387	3395	2230	2761	1439	1838	1414

1453 **Supplementary Table 2**. Results of two-way repeated measures ANOVA tests on the binary
1454 classifier accuracy values, with factors of ROI x Task, separately for the *Linear-1, Linear-2,* and
1455 *Nonlinear* classifiers (see Figure 2A-C for classifier accuracy values). All p-values were obtained
1456 using a permutation test, see *Methods* for details.
1457
1458

Linear-1 classifier accuracy

	F Value	Num DF	Den DF	p
ROI	70.81	7	63	0.0000
Task	0.83	2	18	0.4505
ROI:Task	2.22	14	126	0.0099

Linear-2 classifier accuracy

	F Value	Num DF	Den DF	p
ROI	87.64	7	63	0.0000
Task	3.17	2	18	0.0672
ROI:Task	0.28	14	126	0.9939

Nonlinear classifier accuracy

	F Value	Num DF	Den DF	p
ROI	53.37	7	63	0.0000
Task	1.65	2	18	0.2180
ROI:Task	0.63	14	126	0.8417

1467   **Supplementary Table 3.** Results of three-way repeated-measures ANOVA tests on the binary
1468   classifier accuracy values for far and near trials, with factors of ROI, task and boundary (i.e.,
1469   comparing *Linear-1* classifier versus *Linear-2* classifier). Classifier accuracy values are shown in
1470   Figure 3. All p-values were obtained using a permutation test, see *Methods* for details.
1471
1472

Far trials

	F Value	Num DF	Den DF	p
ROI	100.81	7	63	0.0000
Task	2.91	1	9	0.1217
Boundary	40.46	1	9	0.0003
ROI:Task	2.61	7	63	0.0205
ROI:Boundary	3.70	7	63	0.0016
Task:Boundary	0.35	1	9	0.5659
ROI:Task:Boundary	1.54	7	63	0.1727

Near trials

	F Value	Num DF	Den DF	p
ROI	65.53	7	63	0.0000
Task	5.37	1	9	0.0438
Boundary	9.33	1	9	0.0135
ROI:Task	0.46	7	63	0.8639
ROI:Boundary	3.48	7	63	0.0020
Task:Boundary	8.99	1	9	0.0113
ROI:Task:Boundary	1.21	7	63	0.3065

1473
1474
1475
1476

1477

1478

Supplementary Figure 1. Classifier confusion matrix alignment with the *Nonlinear* template
does not differ significantly across task conditions. **(A)** Template matrix for the *Nonlinear* task,
representing the pattern of similarity expected for a perfect binary representation of the
Nonlinear categorization scheme. **(B)** The similarity (Pearson correlation coefficient, z-
transformed) between the *Nonlinear* template and the actual confusion matrix for each task and
ROI. Gray dots represent individual participants, colored circles and error bars represent the
mean ± SEM across 10 participants. A two-way repeated measures ANOVA on these similarity
values revealed a main effect of ROI but no main effect of task or ROI x task interaction (ROI:
$F_{(7,63)} = 63.20$, $p < 0.001$; Task: $F_{(2,18)} = 1.19$, $p = 0.329$; ROI x Task: $F_{(14,126)} = 1.29$, $p = 0.222$).

1488

1489

1490

1491

1492

1493

1494

1495

1496

1497

1498

1499

1500

1501

1502

1503

1504

1505

1506

1507

1508

1509 **Supplementary Table 4.** Results of three-way repeated-measures ANOVA tests on the
1510 multinomial classifier confidence values for far and near trials, with factors of ROI, task and
1511 confidence boundary (i.e., comparing *Linear-1* confidence versus *Linear-2* confidence).
1512 Classifier confidence values are shown in Figure 7. All p-values were obtained using a
1513 permutation test, see *Methods* for details.
1514
1515

Far trials

	F Value	Num DF	Den DF	p
ROI	54.44	7	63	0.0000
Task	0.22	1	9	0.6569
Boundary	49.96	1	9	0.0000
ROI:Task	0.82	7	63	0.5706
ROI:Boundary	6.58	7	63	0.0000
Task:Boundary	0.04	1	9	0.8568
ROI:Task:Boundary	1.15	7	63	0.3475

Near trials

	F Value	Num DF	Den DF	p
ROI	30.13	7	63	0.0000
Task	1.88	1	9	0.1975
Boundary	17.03	1	9	0.0011
ROI:Task	0.39	7	63	0.9128
ROI:Boundary	4.69	7	63	0.0002
Task:Boundary	11.05	1	9	0.0075
ROI:Task:Boundary	0.78	7	63	0.6281

1516
1517
1518
1519

Supplementary Figure 2. Task-related differences in classifier confidence are also measurable using binary classifiers. We used binary logistic regression classifiers that were trained to predict the category of each shape according to either the *Linear-1* or *Linear-2* decision rule (see Figure 2A-B), and computed the confidence of these classifiers for each trial as in Figure 6. **(A)** Confidence computed using "far" trials, meaning the 8 points in the main grid that fell furthest from the category boundary of interest. **(B)** Confidence computed using "near" trials, meaning the 8 points in the main grid that fell nearest to the boundary of interest. For the near trials only, we observed a main effect of task on *Linear-2* confidence (two-way repeated measures ANOVA; ROI: $F_{(7,63)} = 33.81$, $p < 0.001$; Task: $F_{(1,9)} = 30.67$, $p < 0.001$; ROI x Task: $F_{(7,63)} = 0.96$, $p = 0.465$). In **(A-B)**, the gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants.

1538
1539

Supplementary Figure 3. Classifier confidence across the *Nonlinear* boundary does not differ significantly across tasks. Similar to Figure 7, we computed the confidence of the classifier toward the correct *Nonlinear* task category for each trial. **(A)** Confidence computed using "far" trials, meaning the four points in the main grid that fell furthest from the two category boundaries (i.e., four corners of the shape space grid). **(B)** Confidence computed using "near" trials, meaning the 12 points in the main grid that fell nearest to either of the two category boundaries. In **(A-B)**, the gray dots represent individual participants, colored circles and error bars represent the mean ± SEM across 10 participants. A two-way repeated measures ANOVA on these similarity values revealed a main effect of ROI but no main effect of task or ROI x task interaction (Far trials; ROI: $F_{(7,63)}$ = 41.70, p < 0.001; Task: $F_{(2,18)}$ = 0.50, p = 0.618; ROI x Task: $F_{(14,126)}$ = 0.67, p = 0.806; Near trials; ROI: $F_{(7,63)}$ = 23.86, p < 0.001; Task: $F_{(2,18)}$ = 0.51, p = 0.620; ROI x Task: $F_{(14,126)}$ = 0.58, p = 0.885).