Revealing principles of autonomous thermal soaring in windy conditions using vulture-inspired deep reinforcement-learning

Yoav Flato,[1, 2, 3] Roi Harel,[4, 5, 6] Aviv Tamar,[7] Ran Nathan,[2] and Tsevi Beatus[1, 2, 3, a)]

[1)]*School of Computer Science and Engineering, The Hebrew University of Jerusalem, Jerusalem, Israel 9190401*

[2)]*Institute of Life Sciences, The Hebrew University of Jerusalem, Jerusalem, Israel 9190401*

[3)]*Center of Bioengineering, The Hebrew University of Jerusalem, Jerusalem, Israel 9190401*

[4)]*Department for the Ecology of Animal Societies, Max Planck Institute of Animal Behavior, Konstanz, Germany 78467*

[5)]*Department of Biology, University of Konstanz, Konstanz, Germany 78457*

[6)]*Centre for the Advanced Study of Collective Behaviour, University of Konstanz, Konstanz, Germany 78457*

[7)]*Department of Electrical and Computer Engineering, Technion, Haifa, Isarel 3200003*

(*Electronic mail: tsevi.beatus@mail.huji.ac.il)

(Dated: Monday 28th August, 2023)

Thermal soaring, a technique used by birds and gliders to utilize updrafts of hot air, presents an attractive model for developing biomimetic autonomous and unmanned aerial vehicles (UAVs) capable of long-endurance flight. Previous studies have employed machine- and deep-learning models to control gliding UAVs in simplified environments without horizontal winds. The resulting neural network models operate as 'black boxes', with little insight into their navigation policy or the structure of the problem. Here, we present a deep reinforcement-learning framework for autonomous glider control in a simulated environment with thermal updrafts and challenging horizontal winds. Compared with vulture flight data, the resulting autonomous agent spontaneously adopted a vulture-like soaring technique that successfully and robustly exploited thermal updrafts under horizontal winds up to 5 m/sec. This system enabled us to reveal the underlying structure of the thermal soaring problem, which consists of two critical bottlenecks that should be solved sequentially: achieving stable flight and flying near the thermal center. Additionally, the agent's neural network divides into functional clusters that correlate with distinct behavioral modes during thermal searching and soaring. Our findings may contribute to the development of biomimetic UAVs with vulture-like efficiency and to understanding the structure and bottlenecks of other motion-based problems.

I. INTRODUCTION

Vultures and other large birds soar by using thermal updrafts, which are localized warm air columns that rise due to their buoyancy. Thermal soaring enables these birds, as well as human glider pilots, to fly for long distances with high energetic efficiency and under challenging wind conditions[1–5]. These impressive capabilities make bird-like thermal soaring an appealing model for imitation in unmanned aerial vehicles (UAVs)[6]. Implementing thermal soaring in autonomous UAVs can improve their flight range and endurance, which will support the growing diversity of UAV applications from surveillance to environmental monitoring. More broadly, thermal soaring is an appealing model-problem for motion control: it has rich dynamics and nontrivial constraints, yet it is relatively simple to model owing to the lack of contact forces.

A pioneering approach for mimicking thermal soaring was developing unmanned gliders with rule-based algorithms. These algorithms estimate the center of the thermal and rely on a set of pre-programmed rules to achieve thermal soaring[7–10]. While this approach succeeded in thermalling even under challenging horizontal winds, rule-based methods are, by definition, limited to their pre-programmed solution-space and cannot explore novel solutions, which might be particularly relevant in complicated motion control and planning tasks.

This limitation can be alleviated by using machine learning (ML) and, particularly, reinforcement learning (RL) methods[11–14]. In RL, an agent operates in an environment to maximize a specific goal function, referred to as a *reward*. The maximization is done via a learning process and as the agent learns, it acquires a policy that determines its behavior. This policy controls the agent's *actions* based on a set of available observations of the environment, which is known as the agent's *state*. Throughout the learning process, actions taken by the agent result in a reward, indicating the quality of its next (or final) state. This setting enables the agent to explore the environment, allowing it to discover its own strategy. Thus, in an ideal learning process, the agent can find an optimal policy whose complexity is limited only by the agent's computational architecture. The agent's policy may even exceed the performance of policies based on human intuition or expertise[15], illustrating an advantage of RL over rule-based algorithms.

The first application of RL to thermal soaring was presented by Reddy *et al.*[16,17], who trained a rule-based RL agent using the SARSA algorithm operating in an environment without significant horizontal winds. The agent is represented by a lookup table, which defines the glider's action as a function of its current state. The action is the glider's bank (roll) angle,

and its state is described by a discrete set of variables, such as discretized vertical acceleration and bank angle. This system achieved successful thermal soaring both in simulations and on a real glider. However, while the policy of rule-based RL can be easily interpreted, it has been shown that this approach is sub-optimal for a wide range of problems[18]. This may indicate that richer agent architectures can achieve better gliding performance, for example, under more challenging environmental conditions such as thermals that are drifted by winds. This particular condition is probably the norm rather than the exception in thermal soaring[1,4]. One agent architecture that can potentially outperform rule-based method is deep neural networks (NN). Combined with state-of-the-art RL algorithms (deep-RL), such as actor-critic and policy-gradient[19–21], these methods have led to numerous successful applications in complicated motion control and planning tasks[11–14]. Deep-RL has been applied also to gliding problems by several authors. Novati *et al.* showed that deep-RL can robustly solve a gliding control problem of a simulated elliptical object, achieving gliding and landing in a complex flow environment[22]. Additionally, Notter *et al.* demonstrated the potential of deep hierarchical-RL to solve complex thermal soaring tasks such as triangle racing[23] but without explicitly handling horizontal winds. Therefore, it appears that the potential of deep-RL to the problem of thermal soaring under challenging winds is yet underfulfilled.

Once a successful deep-RL solution has been found, understanding how it operates may improve our understanding of the problem, reveal new rule-based strategies, and increase our trust in the learned policy. For example, discontinuities in the agent's reward during the learning process may inform us about the underlying structure of the problem and whether it consist of sub-problems, or learning bottlenecks[24]. Revealing these bottlenecks, which must be solved sequentially to achieve the overall learning goal, can improve our solution strategies for problems that appear too difficult to solve directly. Overall, however, deep-NN are often 'black boxes', and interpreting their operation might be challenging, due to their structure and complex input-output relation. Interpreting deep-RL networks[25] can be performed by identifying significant elements of the problem through the NN's performance and learning process, including feature importance techniques, finding groups of correlated state-actions, reward shaping, and optimizing the learning process for better problem understanding. For example, Zahavy *et al.*[26] studied deep-RL solutions for Atari games, and used clustering of the network's neural activation patterns, states, and actions to gain insights into the NN's modes. In another example, from the field of movement ecology of bats, Goldstein *et al.* used an NN model and analyzed its hidden layers, to show that bats may use visual information for navigation[27].

In this paper, we both present a new simulation-based deep-RL solution to the problem of thermal soaring under challenging wind conditions, and apply several interpretation methods to understand the resulting NNs, their learning process and their relation with natural soaring observed in GPS-tracked free-ranging vultures. Our deep-RL environment is a 6 degrees-of-freedom (DOF) simulation of a vulture-like glider that includes both thermal updrafts and horizontal winds. Using gradual curriculum learning[28], reward shaping, and optimizing the state-action representation, our deep-NN model managed to achieve robust thermal soaring under horizontal winds of up to 5m/sec. Then, we defined a new efficiency metric for thermal soaring and use it to analyze several aspects of the resulting NN agents and their learning process. Analyzing the reward dynamics revealed specific bottlenecks in the learning process that we then managed to alleviate using reward-shaping. Analyzing the NN activation revealed distinct neuronal patterns associated with specific behavioral modes. Moreover, we have identified similarities between the learned policy and the soaring technique and learning dynamics observed in free-ranging vultures. Overall, this work poses thermal-soaring as a model-problem for complex motion control. Despite the typically opaque nature of deep-RL solutions, we present ways to interpret the solution and probe the inner structure of the learning problem. These results may be applicable to understanding animal decision-making behavior, developing autonomous UAVs, and to motion control problems in general.

II. MATERIALS AND METHODS

A. Thermal soaring as an RL problem

Reinforcement learning is a type of machine learning in which an agent learns to take actions in an environment to maximize a cumulative reward signal (Fig. 1). The agent observes its state in the environment and chooses an action based on a policy $\pi : S \times A \to p$, where S is the state space and A is the action space. The policy π maps state-action pairs to the probability $p \in [0, 1]$ of taking a particular action in a given state. The policy can be represented in various ways and here we represent it as a NN. The agent receives a reward based on the state resulting from the selected action. The goal of RL is to learn a policy that maximizes the expected cumulative reward. In our thermal soaring environment, the agent is a simulated glider with vulture-like parameters. The agent's kinematic parameters, such as speed and direction, represent its state, while the glider's control parameters, which are the body angles, represent the actions. The reward signal can be designed to incentivize the agent to gain altitude, which in our simulated environment can be achieved by thermal soaring. Through trial and error, the goal of the RL algorithm is to shape the policy π to optimize the agent's behavior in the thermal soaring environment based on the reward received.

B. Simulation Model

In our RL framework, the environment is a 6-DOF simulation of a glider that operates both under rising thermals and horizontal wind. The vulture-like glider model is based on the simplified model of Beeler *et al.*[29], in which the glider is described as a point-mass aircraft in an environment with a spatially varying wind. The glider's parameters, such as

FIG. 1. **Reinforcement learning system for simulation-based thermal soaring.** (a) Overall system layout. (b) The state, action, reward and algorithm settings of our RL system. (c) A representative flight trajectory of the nominal agent configuration, which shows climbing thermalling motion under horizontal wind (blue arrow). The agent's climb rate is color coded along the trajectory. (d) A representative flight trajectory of a free-ranging vulture during thermal soaring[1]. Scale bars are 100 m.

mass, wingspan and aerodynamic coefficients are detailed in Appendix A. The glider model is described in Fig. 2 and its equations of motion are:

$$
\begin{aligned}
\dot{z} &= V \sin\gamma \\
\dot{x} &= V \cos\chi \cos\gamma \\
\dot{y} &= V \sin\chi \cos\gamma \\
\dot{V} &= -\frac{1}{m}D(V,\alpha,\beta) - g\sin\gamma \\
\dot{\gamma} &= \frac{1}{mV}\left(L(V,\alpha)\cos\sigma + C(V,\beta)\sin\sigma\right) - \frac{g}{V}\cos\gamma \\
\dot{\chi} &= \frac{1}{mV\cos\gamma}\left(L(V,\alpha)\sin\sigma - C(V,\beta)\cos\sigma\right).
\end{aligned}
\tag{1}
$$

The dynamic variables are the (x,y,z) coordinates of the glider's center-of-mass, its velocity V, glide (pitch) angle γ, and side (yaw) angle χ. The glider's two control parameters are its bank (roll) angle σ and angle-of-attack α. The

model supports a third control parameter – the sideslip angle β – which, as we verified, is not essential for obtaining robust thermalling. The glider mass is m and gravity acceleration is g. The lift force L, drag force D, and side force C, are calculated by a simplified aerodynamic model based on V, α, and β, which include the effect of the local air motion due to thermals and horizontal wind. Detailed description of the aerodynamic model is given in Appendix A.

The environment's atmospheric model consists of a sum of a horizontal wind and thermal updraft. Horizontal wind is approximated as uniform wind velocity u in the $+x$ direction. This direction is practically randomized with respect to the glider-agent, assuming the agent has no prior information about its heading and its initial heading is randomized. Soaring birds and human glider pilots obviously use more information about the environment[30]. The magnitude of the horizontal wind is constant per each simulation run. We assume that u has no z dependence despite its well-known logarithmic profile $u(z)$ in open landscapes, as gliders and vultures

FIG. 2. **Glider model.** The glider was modeled as a point mass with lift force L, drag force D, side force C and weight W. The glider's orientation is defined by the following angles: the angle-of-attack α; the sideslip angle β between the body axis and the velocity; the glide angle γ; the bank (roll) angle σ and the side angle χ of the velocity with respect to the horizon.

mostly soar at relatively high elevations where the boundary-layer resistance (that shapes the logarithmic profile) is weak and $u(z)$ is nearly uniform. The shape of the updraft velocity vertical profile $w(z)$ is determined by Gedeon's model[31], and its amplitude $w_{\text{core}}(z)$ is given by Lenschow's model[32]. The combined vertical updraft velocity, as described by Bencatel is given in cylindrical coordinates (r,z),[33] is:

$$w(r,z) = w_{\text{core}}(z) e^{-\left(\frac{r}{R(z)}\right)^2} \left[1 - \left(\frac{r}{R(z)}\right)^2\right]$$

$$w_{\text{core}}(z) = w^* \left(\frac{z}{z^*}\right)^{1/3} \left(1 - 1.1\frac{z}{z^*}\right) \qquad (2)$$

$$R(z) = 0.08 \left(\frac{z}{z^*}\right)^{1/3} \left(1 - \frac{1}{4}\frac{z}{z^*}\right) z^*,$$

where w^*=5m/sec is the characteristic updraft amplitude and z^*=2,000m is the characteristic thermal altitude. In the resulting radial updraft profile (Fig. 3a), the thermal radius increases with height z and its velocity peak is surrounded by a ring of downwards velocity. For example, the peak updraft velocity at z=500m is w_{core}=2.3m/sec. To combine the horizontal wind and updraft velocity we use the chimney model[33,34], in which thermal motion may include both horizontal motion and leaning of its centerline. The results presented here use uniform horizontal motion without leaning. We achieved successful RL also with the full chimney model. The overall atmospheric model is, therefore:

$$\mathbf{v}(x,y,z,t) = \begin{pmatrix} u \\ 0 \\ w(r(t),z) \end{pmatrix}, \qquad (3)$$

with $r(t) = \sqrt{(x-ut)^2 + y^2}$, as shown in Fig. 3b.

FIG. 3. **Modelling a thermal updraft with horizontal wind. (a)** Thermal updraft distribution as a function of distance from the thermal center r, for different heights. The thermal parameters are w^*=5, z^*=2000. **(b)** The velocity field of a thermal with horizontal wind. Each arrow represents wind velocity direction and magnitude at a given (x,y,z) position. Arrows are color-coded by the magnitude of v_z. The horizontal wind is u=3m/sec and thermal parameters identical to the thermal in (a).

C. Deep-RL model

The deep-RL agent consists of a neural network that controls the simulated glider in an environment with a single thermal. Each simulation run spans 200sec of flight, divided into 1sec intervals. In each interval, the agent obtains its state

FIG. 4. **The angle from wind, θ during circling motion.** Left: A trajectory of a thermalling vulture taken from data[1]. Right: a scheme of one circle within the thermalling motion that demonstrates the values of θ (the angle between the glider velocity and the wind u in the xy plane) along the circle. $\theta=0$ represents motion against the wind (headwind) and $\theta= \pm 180°$ represents motion in the wind direction (tailwind). θ is defines such that it is increasing during the circling. Here, for example, the glider is rotating clockwise, hence when it goes from headwind to tailwind, θ increases from 0 to $180°$. For counter clockwise rotations, θ is mirrored such that it still increases when transitioning from headwind to tailwind.

and calculates a steering action. The action is implemented in the simulated dynamics of the next 1 sec interval. In a real glider system, this mode of operation would rely on a nested feedback loop that provides orientation control via the aircraft control surfaces. After a full simulation run, the agent gets a reward based on its cumulative performance. The state, action and reward are described below.

State. The agent's state consists of the following parameters:

- Glider's speed V.
- Climb rate v_z.
- Bank angle σ.
- Angle of attack α.
- The magnitude of the horizontal wind u.
- The angle θ between the glider's velocity vector and u (Fig. 4).

Each state entry was normalized to the range $[-1, 1]$. These parameters can be measured by standard sensors, and can probably be sensed by vultures and other soaring birds. Additionally, the agent's state contains a short history of the state parameters, as vultures were found to integrate short-term information on their soaring performance from their current and recent experiences[35]. The length of this history is a hyperparameter of the model. To characterize the robustness of our agents to noise, we tested some of the trained agents with sensor noise, where we added Gaussian noise to their state data (Section III C). To further examine the effect of the state on performance, we tested additional state representations, which included the glider's distance from the thermal center, and the difference of the vertical wind between the two wings.

Actions. The agent's two actions are[23,29]:

- Bank angle change, $\Delta\sigma$. In each 1 sec interval, the agent can change σ by $\Delta\sigma \in [-15°, 15°]$, and σ is limited to the range $[-50°, 50°]$.

- Angle of attack change, $\Delta\alpha$. In each time step the agent can change α by $\Delta\alpha \in [-10°, 10°]$, and α is limited to $[-30°, 30°]$.

We also tested agents that can modulate their sideslip angle and wingspan, and found that these control parameters are not crucial for the current task.

Reward. In analogy to vultures and gliders, the basic reward in our model was the glider's climb rate v_z. To overcome the bottlenecks that we identified in the learning process (section III D), we employed two additional factors in the reward, which can be considered as 'reward shaping'[36]. The first factor is a penalty for instability, P_{stab}: when the agent spins out of control, the simulation is stopped and the agent is penalized proportionally to the remaining simulation time. The second reward shaping factor is a penalty proportional to the glider's horizontal distance from the thermal center, termed P_{center}. Importantly, because this penalty is not part of the state, the agent has no direct information on its distance from the thermal center. This penalty helps in shaping the agent's behavior through the reward, by encouraging the agent to fly closer to the thermal center (Section III D).

Training algorithm. We used the DDPG (Deep Deterministic Policy Gradient) algorithm, which is a state-of-the-art actor-critic policy gradient method designed for continuous control problems[20] (Fig. 5). Actor-critic systems are composed of two neural networks: the actor network and the critic network. The actor determines the agent's action based on the current state, while the critic estimates the value or Q-functions associated with a given state and action. Both the value function and Q-function represent the expected cumulative future reward: the value function's estimate relies on a given state, while the Q-function's estimate relies on a given state and action. The critic network learns to estimate one of these functions by observing trajectories of (state, action, reward) generated by the actor in the environment. Most of the time, the critic's estimate is utilized to calculate the temporal difference (TD) error or advantage function. The TD error quantifies the discrepancy between the current estimate of the state-value and the discounted value estimate of the subsequent state, along with the actual reward obtained by the actor. The advantage function is the expectation of the TD error with respect to the next state, which also quantifies the quality of a certain action given a certain state. The critic's value function serves the dual purpose of updating the critic's value estimation and providing feedback to the actor regarding the quality of its chosen action. In the case of DDPG, the critic network specifically calculates the Q-function rather than the value function. In addition to DDPG, we tested the PPO (Proximal Policy Optimization) algorithm[19], which is another actor-critic policy gradient method. PPO also achieved successful learning, though in longer times.

We use the code implementation of the stable-baselines3 library[37], which includes various deep-RL algorithms based on the PyTorch library. We optimized the learning process by performing a hyper-parameter optimization[38] for the learning rate, learning algorithm (DDPG/PPO), number of NN layers, and layer size (Appendix C).

Overall, in the learning process, we begin with an initial

FIG. 5. **Actor-critic RL architecture.** The actor acts in the environment and the critic learns the environment, by assigning a 'value' to each state (or state-action pair). Critic values are used to update the actor. Together, the RL algorithm operates to obtain maximum cumulative reward.

neural network policy that maps states to actions. This policy is updated using a critic neural network through the policy gradient actor-critic method, which is executed in the thermal environment and uses the rewards obtained from the environment.

In each simulation run during the learning process, the glider was initialized at a random orientation, random horizontal position in (x,y), height of z=500m, velocity of 15 m/sec, and gliding angle of $-5°$. The thermal center was set to (x,y)=$(0,0)$, and the horizontal wind velocity u in the $+x$ direction was set to a random value between $u_{\min}$ and $u_{\max}$, which are the wind speed hyper-parameters. The thermal was, therefore, drifting at velocity u while keeping a vertical structure. These random initialization improved the agent's generalization capacity. On top of this scheme, we used a curriculum learning approach, where the maximum horizontal wind velocity, $u_{\max}$, was gradually increased during the learning process, as further detailed in the Results section.

D. Interpreting and analyzing the deep-RL agents

To understand the agent's policy and performance during and after the learning process, we employed both kinematic analyses of the flight trajectories, and analyzed the NN itself by clustering the neural activation patterns in the network's hidden layers.

The activation of a neuron in the network is the output of its nonlinear activation function, which, in our case, is a non-negative number. At each timestep, we represent the activation of the entire network by concatenating the activations of all neurons in the NN hidden layers into one vector. Prior work has shown that analyzing the hidden layers is useful for interpreting NN in both physical-ecological[27] and RL problems[26]. To perform the clustering, we used the k-means algorithm[39] on the concatenated activation vectors. To de-

termine the number of clusters k, we used the knee locator method[40] based on the sum-of-squared-error (SSE)[41], which finds the k value at which the SSE curve starts to straighten up. We later show that specific clusters can be assigned to distinct flight modes.

E. Experimental data of soaring vultures

In our study, we compared our RL model to vulture flight trajectories collected by Harel *et al.*[1]. The dataset consists of over 4 million GPS location samples, taken at 1Hz rate of 20 vultures of different ages collected over ~3 years. Among these locations, there were almost 1 million samples from thermal soaring in over 6,000 thermal updrafts, with each thermal soaring trajectory lasting more than 100 sec. Further details are given in Appendix D.

III. RESULTS

The next section (III A) describes the soaring performance of the agent resulting from our nominal system configuration. The subsequent sections report on further analyses of this RL system, which also explain the selection of specific aspects of the nominal configuration: the system's state and action representations (Section III B), robustness (Section III C), learning bottlenecks (Section III D) and interpretability (Section III E).

A. Thermal soaring under horizontal wind

The chosen parameters of the system, referred to as the 'nominal' configuration, which resulted in successful learning of thermal soaring, are as follows. The agent's state consisted of the five parameters $\{V, v_z, \sigma, \alpha, \theta\}$ given for the current time and 8 previous 1 sec time steps. The state also included the horizontal wind velocity u. The agent's action was $\{\Delta\sigma, \Delta\alpha\}$. The reward per each simulation step was a sum of two components: the agent's climb rate v_z and a penalty P_{center} equal to $-d/50$, where d is the agent's horizontal distance from the thermal center in meters. Additionally, the agent was penalized in two cases. First, if the agent went unstable, defined as spinning $360°$ in pitch, the simulation was stopped and the agent was penalized by P_{stab}, equal to -1 per each sec left until the end of the run. Second, if the agent crashed ($z = 0$), the simulation was stopped and the agent was penalized by -1000. We used the DDPG algorithm where both actor and critic NNs included two fully connected hidden layers with 200 neurons each (Appendix C).

We found that using curriculum learning was crucial for achieving successful soaring under horizontal winds. To this end, we gradually increased u during the learning process. First, the agent was learning on environments with u randomly selected within the range $0-2$ m/sec. Then, the range of u was increased to $0-4$ m/sec and, finally, to $0-6$ m/sec. Each of these three steps consisted of $3-5\cdot10^6$ sec

FIG. 6. **Thermal soaring of the nominal agent under various horizontal wind speeds (a)** Representative 3D soaring trajectories in winds of 1 m/sec (blue), 3 m/sec (orange) and 5 m/sec (green). The wind is in the +x direction. **(b-d)** The climb rate v_z and the agent's distance from the (moving) thermal center as a function of time, for the same trajectories in (a). The left column is for u=1 m/sec, middle column is for u=3 m/sec, and the right column is for u=5 m/sec. **(e-g)** histograms of the agent's xy position with respect to the the moving thermal center. Each histogram for a given value u was calculated for 100 runs with random initial conditions. The white arrows indicate the direction of circling. **(h-i)** 2D histograms of the climb rate v_z and the angle from wind, θ. The histograms were calculated for the same 100 runs per each u. The white arrows indicate the direction of circling.

of simulated flight.

Agents resulting from the nominal configuration achieved stable thermal soaring under horizontal winds of up to u =

0–6 m/sec (Fig. 6 and Videos 1, 2). Fig. 6a shows representative trajectories of the same agent, soaring under u = 1, 3 and 5 m/sec. As agents were, on average, placed initially close to, but not within, the thermal, the trajectories include a short

(a)

(b)

(c)

FIG. 7. **Thermal soaring performance of the nominal agent at different horizontal wind speeds.** Agent's performance was analyzed over 100 runs with random initial conditions for each value of the horizontal wind speed u. The performance measures are presented in violin plot which show the distribution over all runs with the mean marked by a horizontal line. For reference, each plot shows also the optimal and baseline climb rates (Appendix B). **(a)** The time the agent spent within the thermal as a fraction of its full run of 200 sec. **(b)** The distribution of average climb rates for each u. **(c)** The distribution of the thermal soaring efficiency η for each u (Eq. 4).

searching phase, which took 5–20 sec and consisted of a circling motion. Once the agent located the thermal, it starts thermalling: circling the thermal center and simultaneously tracking it downwind. To track the drifting thermal, the agent decreased its turning radius every time its trajectory is aligned with the wind, *i.e.*, at angle of $\theta \approx \pm 180°$ with respect to the wind, which is along the $+x$ direction. This motion is most evident in the u=5 m/sec trajectory, where the trajectory becomes almost parallel to the x axis. The resulting trajectories are trochoid in the xy plane, which manifests a thermalling technique similar to the techniques of soaring vultures[1] and professional human gliders[4,5]. Each learning session resulted in an agent that consistently rotated either clockwise or anti clockwise; the agent in Fig. 6 is of the clockwise type. While thermalling, the agent keeps itself in a range of 10–50 m from the thermal center, with an average distance of ~25 m (Figs. 6b-g). The agent's climb rate v_z consists of two contributions: the updraft velocity of the thermal (peak velocity ~2 m/sec), and the horizontal wind velocity, which the agent learned to convert to vertical velocity when flying against the wind.

To understand the agent's thermalling policy, we tested the agent on 100 random initial conditions for each of the three horizontal wind values u = 1, 3 and 5 m/sec. Figs. 6e-g show two-dimensional (2D) histograms of the agent's position with respect to the moving thermal center, calculated for each u across all 100 runs. The histograms show that the agent learned to move around the thermal center in a radius of ~25 m. Interestingly, for $u \geq 3$ m/sec, the center of the circling motion does not align with the thermal center, but the peaks of the 2D distributions show that along its circular trajectory, the agent spends more time closer to the thermal center. In addition, in this part of the trajectory, the agent chases the moving thermal ($\theta \approx \pm 180°$, tail wind). Analyzing v_z across the trajectories, shows that the agent gains most of its vertical velocity at angles of $\theta \approx 90°$ with respect to the wind (Figs. 6h-j). For $\theta < 90°$ the agent moves against the wind, and for $\theta > 90°$ it moves along the wind. For u=5 m/sec we see a clear signature of the agent's vertical acceleration as it rotates in θ, through the slope of $v_z(\theta)$. The vertical acceleration is highest between $\theta = -45°$ and $90°$ when the agent mostly flies against the wind, showing it exploits the wind to increase v_z. As u increased, the variability of the agent's σ and α increased, indicating a higher control load. For example, the standard deviation of σ increased from $6°$ in u=0 to $12°$ in u=5 m/sec.

To quantify the agent's soaring performance, we first calculate the fraction of its flight time spent in the thermal, *i.e.*, 80 m from its center, where the thermal updraft is still positive. Fig. 7a shows that under horizontal winds of 0–6 m/sec the agent spends most of its flight time thermalling. To quantify soaring performance in terms of v_z, we define a soaring efficiency measure, η, which consists of two limits for the climb rate: an upper bound v_z^{optimal} and a baseline v_z^{baseline}. The upper bound, v_z^{optimal}, was estimated for a thermal with the parameters used in our environment: w^*=5 m/sec and z^*=2000m. It was derived from the equations of motion (Eq. 1) by characterizing their steady state under constant (σ, α) in the wind frame-of-reference. The steady state radius was then used to calculate the v_z upper bound in a circular trajectory within the

thermal. Under these settings, the upper bound for the climb rate is $v_z^{\text{optimal}}=0.72\,\text{m/sec}$ (see Appendix B for the full derivation, and Appendix D for a comparison with the thermal parameters estimated from vulture data). The second limit of the climb rate $v_z^{\text{baseline}}=-0.75\,\text{m/sec}$ (*i.e.*, a sink), is the maximum climb rate that can be achieved with no thermal updraft. This climb rate is obtained in a straight descending flight with $\sigma=0$ and $\alpha=6°$. Naturally, for gliders, $v_z^{\text{baseline}}<0$, hence, for example, any positive v_z^{agent} indicates positive soaring efficiency. Using these values, we define the soaring efficiency η as:

$$\eta = \frac{v_z^{\text{agent}} - v_z^{\text{baseline}}}{v_z^{\text{optimal}} - v_z^{\text{baseline}}}. \tag{4}$$

Overall, η represents the fraction of the updraft exploited by the agent. An agent with $\eta=1$ uses all the thermal updraft; an agent with $\eta=0$ can be gliding straight at v_z^{baseline}; and an agent with $\eta<0$ is doing worse than v_z^{baseline}.

Fig. 7b shows the distributions of the agent's mean v_z value for different horizontal winds, compared with v_z^{baseline} and v_z^{optimal}, and Fig. 7c plots the corresponding η distributions. The agent achieved $\eta>0$ across the entire range of horizontal wind speeds and performed best in the mid-range $u=1-3\,\text{m/sec}$, with $\eta\approx0.8$. The highest average v_z was $0.42\,\text{m/sec}$ obtained at $u=3\,\text{m/sec}$. For this u, when omitting the first 20 sec of each trajectory, the mean v_z reaches $0.54\,\text{m/sec}$ (maximum of $0.67\,\text{m/sec}$), the mean η reaches 0.88 (maximum of 0.96).

B. Probing the state and action representations

As part of the state optimization process we tested agents with several state representations, whose performance shed light on the importance of specific attributes of the nominal state representation: the horizontal wind speed u and the memory size of previous states. First, we compare the nominal agent to an agent whose state representation excluded u, namely, it included only $\{V, v_z, \sigma, \alpha, \theta\}$. Both agents' state memory included their current state and the state in the previous 8 time steps, and they were trained in the nominal curriculum learning protocol (section III A). Each agent was tested on a range of horizontal winds $u=0-6$ for 100 runs on each value of u. Fig. 8 shows that the agent whose state did not include u was significantly less efficient than the nominal agent which had u in its state. Additionally, we found that agents with no knowledge of u were able to learn to soar under one specific horizontal wind $u_0\leq8\,\text{m/sec}$, when trained in a curriculum learning protocol which gradually increased in $1\,\text{m/sec}$ steps. However, these agents performed poorly on horizontal winds weaker than u_0. Together these results indicate that u is a crucial state parameters.

Next, we compared the nominal agent to a series of agents whose state representations included memory buffers of different sizes, from 1 to 9 previous time steps (nominal is 8), in addition to the current state. These agents were trained under horizontal winds of $1-3\,\text{m/sec}$ and tested on $u=2\,\text{m/sec}$. Fig. 9 shows that for staying mostly in the vicinity of the thermal

FIG. 8. **The horizontal wind u is a crucial state variable.** The thermalling efficiency η was calculated for two agents under the same learning protocol. One agent (orange) had u included in its state, and the other agent (blue) did not. The thermalling efficiency is plots as the mean η on 100 runs in each horizontal wind speed u from 0 to $6\,\text{m/sec}$. For reference, the baseline and optimal values of η are plotted as well.

FIG. 9. **Agent performance as as function of its memory buffer size.** The efficiency (blue) and fraction of time spend within the thermal (red) are plotted for the agents trained under $u=1-3\,\text{m/sec}$ and tested on $u=2\,\text{m/sec}$. These results show that a memory buffer of 3 sec is sufficient for flying within the thermal, but efficient soaring requires a buffer of at least 5 sec.

it is sufficient to have memory of ≥ 2 time steps. However, for exploiting the thermal and soaring efficiently it is required to have memory of ≥ 5 time steps, as measured by η.

In terms of the agent's action, our model allows for three control parameters: $\Delta\sigma$, $\Delta\alpha$, and $\Delta\beta$, which represent modulations the the bank angle, angle-of-attack and sideslip angle, respectively. While the bank angle is crucial for thermalling[4,17,23,42], it is insufficient for stabilizing in strong horizontal winds. As taught in basic gliding courses[4], our system consistently showed that adding $\Delta\alpha$ was sufficient for achieving efficient thermalling, whereas further adding $\Delta\beta$ resulted in slow convergence. Therefore, the actions of the nominal agent we set to $\Delta\sigma, \Delta\alpha$.

FIG. 10. **Climb rate performance in different thermal parameters.** To quantify the system's generalization, the nominal agent was tested on a 15 combinations of thermal parameters (z^*, w^*) different than the values on which it was trained (dark square). For each combination of (z^*, w^*) we averaged over 20 runs in random initial conditions. The plot shows the mean efficiency η in percent (color coded), the mean v_z and $v_z^{optimal}$.

C. Robustness of the nominal agent

To mimic several aspects of the real world, we characterized the robustness of the nominal solution with respect to changes in the parameters of the thermal, as well as with respect to sensor noise.

Thermal parameters. The nominal agent was trained on environments with random horizontal wind and initial condition but with fixed thermal parameters, w^* and z^* (section II B). To evaluate the agent's ability to generalize its technique for different thermal parameters, we tested its performance in a range of w^* and z^* values without further training (Fig. 10). For each combination of w^* and z^* we ran 20 simulations with horizontal wind of u=3 m/sec and random initial conditions. The agent performance was evaluated by the efficiency metric η (section III A) and by calculating its average v_z and optimal v_z under each condition. Fig. 10 shows that for the weaker thermals with w^*=3 m/sec the agent performed quite poorly, but it managed to generalize for all the tested values of $w^* \geq 5$ m/sec and all z^*, where its efficiency was >70%.

Sensor noise. We modeled sensor noise by adding Gaussian noise to the state variables $\{v_z, V, \sigma, \alpha, \theta, u\}$, one variable at a time. Fig. 11a shows the average climb rate of the nominal agent under different noise levels. The noise levels were normalized with respect to the standard deviation of the sensor readout, as a typical scale for its variation. Overall, the climb rate reduced with the noise level, with different performance degradation for noise in different sensors. For example, the most sensitive sensor was θ (angle with respect to the u): rel-

FIG. 11. **Climb rate performance degrade with sensor noise and wind gusts.** **(a)** The average climb rate of the nominal agent under different types of sensor noise and different normalized noise levels. The noise level in each sensor was normalized by the standard deviation of the measured variable. The standard deviations were: std(V)=2.3 m/sec, std(v_z)=2.6 m/sec, std(θ)=116.4 m/sec, std(σ)=11.9 m/sec, std(σ)=5.9 m/sec. **(b)** The orange line describes the agent's average climb rate as a function of noise level in its u sensor, as defined in the main text. The blue line shows the average climb rate as a function of noise in the *environmental* value of u, which represents physics gusts that change over a 20 sec timescale.

ative noise of ~0.65 degraded the agent's performance down to the baseline climb rate, equivalent to gliding with no thermal. The least sensitive sensor was V, for which a similar performance degradation was met for relative noise of ~1.7.

Testing the performance under sensor noise in u (Fig. 11b), shows that the agent's performance degraded to the baseline climb rate at a Gaussian noise with standard deviation of ~7 m/sec, greater than the horizontal wind speed u=3 m/sec used in this trial. This result hints that the agent averages the readouts of u across its memory buffer. Finally, we tested the agent's robustness to environmental noise in u, which simulated a horizontal wind with gusts that change every 20sec and have a Gaussian distribution. The agent performance monotonically degraded to the baseline at gusts with standard deviation of ~3 m/sec, where the mean u was 3 m/sec.

D. Identifying learning bottlenecks via reward shaping

To reveal the underlying structure of the thermal soaring problem and break it into meaningful sub-problems, we tested

FIG. 13. **Learning bottlenecks.** Each circle represent a stages in a successful thermalling technique. The × symbols indicate the staged reached by the agents studied in Fig. 12, using the same color coding. The innermost circle represents the technique with the highest efficiency. The transition from into the outermost circle represents the first learning bottleneck related to stabilization. The transition to the next inner circle corresponds to the second bottleneck: locating and flying near the thermal. The final transition into the innermost circle of "stable thermalling" was achieved via a smooth process facilitated by the v_z reward.

FIG. 12. **The effect of reward shaping on learning dynamics.** The following plots show the gliding performance during the learning process, as a function of simulation time in seconds. The four colors represents agents with different reward functions, as indicated by the legends. **(a)** The fraction of stable flight time as a function of learning timestep for different reward agents. **(b)** The fraction of time spent in thermal area as a function of learning timestep for different reward agents that survived for a significant duration. **(c)** Climb rate as a function of learning timestep for different reward shaping agents that survived for a significant duration.

the nominal agent in a slightly more challenging protocol, in which u was randomly selected between $2.5-3.5$ m/sec, without curriculum learning. We identified that in our system the task of efficient thermal soaring is too difficult for learning when the reward is simply the climb rate v_z. As shown Fig. 12a, an agent with this reward did not manage to stabilize itself and crashed in a very early stage of the simulation. The first sub-problem of thermal soaring is, therefore,

achieving stable flight. Hence, we changed the reward function by adding the penalty P_{stab}, defined above (section III A), which penalizes the agent when it gets unstable. Agents that learned with the reward $v_z + P_{\text{stab}}$ achieved stable flight (Fig. 12a) but did not manage to find the thermal and to spend a significant time in its vicinity (Fig. 12b). This reveals the second sub-problem of thermal soaring – staying closer to the thermal center. Thus, we defined another penalty term, P_{center}, proportional to the agent's distance from the thermal center (section III A). Agents learning with the combined reward $v_z + P_{\text{stab}} + P_{\text{center}}$ managed to fly both stably and near the thermal center, and eventually learned to circle the center to soar efficiently. Interestingly, agents with the reward $v_z + P_{\text{center}}$ did not overcome the stabilization bottleneck (Fig. 12a).

In summary, these results indicate that the problem of thermal soaring, as modeled here, consists of at least two sub-problems that can be manifested as learning bottlenecks (Fig. 13). The first bottleneck identified is achieving stable flight, and the second is locating and flying near the thermal center. Using reward shaping assisted the agent to sequentially funnel its flight technique through those bottlenecks and achieve efficient soaring. Interestingly, while these gliding principles are known by human glider pilots, the current RL system 'rediscovered' them using a neural network of 400 inter-neurons only.

E. Opening the black box: analyzing the NN functional modes

The highly complex and opaque nature of the NN makes it difficult to understand its gliding policy. To address this challenge, we analyzed the NN activity by clustering the neural activation values in the hidden layers, to obtain clusters with similar activation patterns (section II D). Here, we tested this procedure on the nominal agent that was trained in a range of horizontal winds $1-2$ m/sec. The agent performance during the learning process is shown in Fig. 14a. We selected three during the learning process and labeled them 'young', 'intermediate' and 'expert' agents. Representative trajectories of these three stages are show in Fig. 14b. Clustering the NN activation patterns revealed 4 distinct clusters. Then, at any given time within a flight trajectory, we can associate the internal NN activation pattern with its closest cluster. We, thereby, obtain a labeling of each timepoint according to its cluster (Fig. 14b).

Markedly, this cluster labeling can be associated with specific stages of the circling flight in the thermal. The labeling is mostly associated with the angle of the glider with respect to the horizontal wind, which is equivalent to its phase in the circling motion (Fig. 4). Furthermore, this association becomes more apparent with increasing agent's 'age'. Fig. 14c, which plots how the cluster labeling is distributed by θ, shows that as the agent 'matures' the cluster distribution becomes more correlated with θ. For example, in the 'expert' agent, one cluster (red) is correlated with flight against the wind in the range $\theta = -100°$ to $90°$, a second cluster (purple) is correlated with the values from $\theta = 90°$ to $\pm 180°$, and a third cluster (blue), aligns with the range $\theta = \pm 180°$ to $-100°$. A fourth cluster (green) appeared for a brief time in the beginning of each trajectory and is associated with a short thermal searching phase. The changes in the clustering patterns over the agent's 'lifetime' is reminiscent of the differences between the thermal soaring of young and adult vultures, where the climb rate of young vultures is independent of θ and the (significantly higher) climb rate of adult vultures depends on θ[1]. To rule out the possibility that this functional association of the clusters with θ is a trivial outcome of having θ as a state variable, we performed the same analysis on an agent that did not have access to θ in its state (appendix E). While this agent did not perform as well as the nominal agent, it did exhibit neural activation clustering with similar distribution in θ.

IV. DISCUSSION AND CONCLUSIONS

In this study, we developed a simulation-based deep-RL system that learned to thermal soar efficiently under horizontal wind of $0-5$ m/sec. The agent's performance was analyzed using a new efficiency metric, η, which quantifies how well the thermal is exploited by the agent. The nominal agent configuration was obtained by optimizing its state and action representations, as well as the curriculum learning process and reward. To further characterize the agent's performance, we analyzed its robustness to different thermal parameters, wind

gusts and sensor noise, and characterized the reduction in performance with increasing gusts and noise amplitude in each sensor. For example, although the agent trained on a single set of thermal parameters (w^*, z^*) it managed to generalize to a wider range of these parameters, for thermals with core updraft $w_{core} \geq 2$ m/sec ($w^* \geq 5$ m/sec).

Interestingly, modulating the reward function, revealed the underlying structure of the thermal soaring problem in its current formulation. This problem consists of at least two bottlenecks, or sub-problems, that must be solved sequentially to achieve efficient soaring: the first bottleneck is achieving stable flight and the second is flying at the vicinity of the thermal center. The method of reward shaping may be applicable for finding the underlying structure of other complex problems in RL. Like learning to crawl before learning to walk and run, identifying learning bottlenecks and addressing them sequentially during learning can, therefore, improve the solution strategy and convergence time for problems that are too difficult for a direct solution based on a single final goal.

Finally, we analyzed the neural activation patterns of the agent's NN and found it divides into four functional clusters. During the learning process, this clustering became more distinct, and in 'expert' agent the clusters are associated with specific phases of θ during the circling motion around the thermal center. Further analyzing these clusters and their evolution during the learning process may inform us about the inner workings of the NN and may be used to understand the agent's policy by extracting explicit rules, for example, by describing each cluster as a decision tree[43–46].

The control over the environment, state, action and reward offered by such RL system, may be helpful in gaining insights into the limiting factors of complex behaviors such as thermal soaring. This methodology is widely applied for non-NN, models[47] and has recently been applied for deep learning and RL models of the sensory system of bats[27,48]. Here, for example, by testing various action-representations we found that controlling the glider's bank angle alone is insufficient for stable flight under strong horizontal winds, and that the angle-of-attack must be controlled as well. Characterizing the agent's robustness to sensor noise and wind gusts may provide physical limits to the relative importance of different sensory information in soaring birds. Additionally, the insights regarding the learning bottlenecks in the thermal soaring problem as well as the evolution of the agents technique and functional clusters with the agent's 'age', may shed light on the constraints and learning process of soaring birds. These concepts may be tested by long-term motion tracking of individual birds combined with accurate measurement of the local environment.

An obvious future goal of this study is to use a similar deep-RL methodology to achieve robust thermal soaring of a real-world glider under realistically challenging atmospheric conditions. As pioneered by Reddy et al.[17] and Notter et al.[23], going from a simulation model to a real-world system ("sim-to-real") is challenging, mainly because simulations typically do not capture the entire relevant complexity of the real-world and because learning on real-world systems takes much longer than in simulation[49,50]. Several routes to address the sim-to-

FIG. 14. **NN activation clusters through learning process.** **(a)** The evolution of agent performance during the learning process. Dashed vertical lines mark the times at which the "young", "intermediate" and "expert" agents were selected for further analysis. **(b)** Representative trajectories of the three agents colored the active neural cluster at each timestep. **(c)** Distribution of the neural activation clusters as a function θ for each of the three agent. Color coding is identical to (b).

real gap in the thermal soaring problem may be: (a) improving the simulation to better mimic the real world in terms of the atmospheric conditions, noise, glider physics and control parameters, and the glider on-board sensors; (b) using data from a real glider or vultures for imitation learning[51]; (c) apply active learning methods to choose the flight parameters for testing on the real system in order to minimize the number of real-world tests; (d) simplifying the learning problem by dividing it to sub-problems that can be learned independently, for example, estimating the horizontal wind speed and direction, and estimating the distance to the thermal center; and (e) applying domain randomization techniques[52] to train a policy in simulation that is robust to the sim-to-real gap. Mimicking natural thermal soaring in UAVs may also improve our understanding of this complex and graceful behaviour.

ACKNOWLEDGEMENT

This study was supported by a grant from the Center for Interdisciplinary Data Science Research (CIDR) of the Hebrew University of Jerusalem, Israel (joint to TB and RN). The vulture study was funded by the US-Israel Binational Science Foundation (BSF 255/2008) and the special BSF Multiplier Grant Award from the Rosalinde and Arthur Gilbert Foundation (to RN and Wayne Getz). We also acknowledge financial support from the Adelina and Massimo Della Pergola Chair of Life Sciences and the Minerva Center for Movement Ecology (to RN). Finally, we thank Walter Nesser for his ecological insight and for taking us paragliding.

REFERENCES

[1] R. Harel, N. Horvitz, and R. Nathan, "Adult vultures outperform juveniles in challenging thermal soaring conditions," Scientific reports **6**, 1–8 (2016).

[2] E. Nourani and N. M. Yamaguchi, "The effects of atmospheric currents on the migratory behavior of soaring birds: a review," Ornithological Science **16**, 5–15 (2017).

[3] H. J. Williams, E. Shepard, M. D. Holton, P. A. E. Alarcón, R. Wilson, and S. A. Lambertucci, "Physical limits of flight performance in the heaviest soaring bird," Proceedings of the National Academy of Sciences **117**, 17884–17890 (2020).

[4] H. Reichmann, *Cross-Country Soaring* (homson Publications, Santa Monica, CA, 1978).

[5] Z. Ákos, M. Nagy, and T. Vicsek, "Comparing bird and human soaring strategies," Proceedings of the National Academy of Sciences **105**, 4139–4143 (2008).

[6] Z. Ákos, M. Nagy, S. Leven, and T. Vicsek, "Thermal soaring flight of birds and unmanned aerial vehicles," Bioinspiration & biomimetics **5**, 045003 (2010).

[7] M. J. Allen and V. Lin, "Guidance and control of an autonomous soaring uav," Tech. Rep. (2007).

[8] K. Andersson, I. Kaminer, V. Dobrokhodov, and V. Cichella, "Thermal centering control for autonomous soaring; stability analysis and flight test results," Journal of Guidance, Control, and Dynamics **35**, 963–975 (2012).

[9] N. T. Depenbusch, J. J. Bird, and J. W. Langelaan, "The autosoar autonomous soaring aircraft part 2: Hardware implementation and flight results," Journal of Field Robotics **35**, 435–458 (2018).

[10] N. T. Depenbusch, J. J. Bird, and J. W. Langelaan, "The autosoar autonomous soaring aircraft, part 1: Autonomy algorithms," Journal of Field Robotics **35**, 868–889 (2018).

[11] S. Guo, X. Zhang, Y. Zheng, and Y. Du, "An autonomous path planning model for unmanned ships based on deep reinforcement learning," Sensors **20**, 426 (2020).

[12] S. Aradi, "Survey of deep reinforcement learning for motion planning of autonomous vehicles," IEEE Transactions on Intelligent Transportation Systems **23**, 740–759 (2020).

[13] Y. Li, "Deep reinforcement learning: Opportunities and challenges," arXiv preprint arXiv:2202.11296 (2022).

[14] E. Bøhn, E. M. Coates, S. Moe, and T. A. Johansen, "Deep reinforcement learning attitude control of fixed-wing uavs using proximal policy optimization," in *2019 International Conference on Unmanned Aircraft Systems (ICUAS)* (IEEE, 2019) pp. 523–533.

[15] D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, *et al.*, "Mastering the game of go without human knowledge," nature **550**, 354–359 (2017).

[16] G. Reddy, A. Celani, T. J. Sejnowski, and M. Vergassola, "Learning to soar in turbulent environments," Proceedings of the National Academy of Sciences **113**, E4877–E4884 (2016).

[17] G. Reddy, J. Wong-Ng, A. Celani, T. J. Sejnowski, and M. Vergassola, "Glider soaring via reinforcement learning in the field," Nature **562**, 236–239 (2018).

[18] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, *et al.*, "Human-level control through deep reinforcement learning," nature **518**, 529–533 (2015).

[19] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," arXiv preprint arXiv:1707.06347 (2017).

[20] T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra, "Continuous control with deep reinforcement learning," arXiv preprint arXiv:1509.02971 (2015).

[21] K. Arulkumaran, M. P. Deisenroth, M. Brundage, and A. A. Bharath, "Deep reinforcement learning: A brief survey," IEEE Signal Processing Magazine **34**, 26–38 (2017).

[22] G. Novati, L. Mahadevan, and P. Koumoutsakos, "Controlled gliding and perching through deep-reinforcement-learning," Physical Review Fluids **4**, 093902 (2019).

[23] S. Notter, F. Schimpf, G. Müller, and W. Fichter, "Hierarchical reinforcement learning approach for autonomous cross-country soaring," Journal of Guidance, Control, and Dynamics **46**, 114–126 (2023).

[24] G. Reddy, "A reinforcement-based mechanism for discontinuous learning," Proceedings of the National Academy of Sciences **119**, e2215352119 (2022).

[25] A. Alharin, T.-N. Doan, and M. Sartipi, "Reinforcement learning interpretation methods: A survey," IEEE Access **8**, 171058–171077 (2020).

[26] T. Zahavy, N. Ben-Zrihem, and S. Mannor, "Graying the black box: Understanding dqns," in *International conference on machine learning* (PMLR, 2016) pp. 1899–1908.

[27] A. Goldshtein, S. Akrish, R. Giryes, and Y. Yovel, "An artificial neural network explains how bats might use vision for navigation," Communications biology **5**, 1–8 (2022).

[28] S. Narvekar, B. Peng, M. Leonetti, J. Sinapov, M. E. Taylor, and P. Stone, "Curriculum learning for reinforcement learning domains: A framework and survey," The Journal of Machine Learning Research **21**, 7382–7431 (2020).

[29] S. C. Beeler, D. D. Moerder, and D. E. Cox, "A flight dynamics model for a small glider in ambient winds," Tech. Rep. (2003).

[30] R. Harel, O. Spiegel, W. M. Getz, and R. Nathan, "Social foraging and individual consistency in following behaviour: testing the information centre hypothesis in free-ranging vultures," Proceedings of the Royal Society B: Biological Sciences **284**, 20162654 (2017).

[31] J. Gedeon, "Dynamic analysis of dolphin-style thermal cross-country flight: Part ii," Technical Soaring **3**, 17–34 (1973).

[32] D. Lenschow and P. Stephens, "The role of thermals in the convective boundary layer," Boundary-Layer Meteorology **19**, 509–532 (1980).

[33] R. Bencatel, J. T. de Sousa, and A. Girard, "Atmospheric flow field models applicable for aircraft endurance extension," Progress in Aerospace Sciences **61**, 1–25 (2013).

[34] M. Allen, "Updraft model for development of autonomous soaring uninhabited air vehicles," in *44th AIAA Aerospace Sciences Meeting and Exhibit* (2006) p. 1510.

[35] R. Harel and R. Nathan, "The characteristic time-scale of perceived information for decision-making: Departure from thermal columns in soaring birds," Functional ecology **32**, 2065–2072 (2018).

[36] A. D. Laud, *Theory and application of reward shaping in reinforcement learning* (University of Illinois at Urbana-Champaign, 2004).

[37] A. Raffin, A. Hill, A. Gleave, A. Kanervisto, M. Ernestus, and N. Dormann, "Stable-baselines3: Reliable reinforcement learning implementations," The Journal of Machine Learning Research **22**, 12348–12355 (2021).

[38] S. Falkner, A. Klein, and F. Hutter, "Bohb: Robust and efficient hyperparameter optimization at scale," in *International Conference on Machine Learning* (PMLR, 2018) pp. 1437–1446.

[39] J. A. Hartigan and M. A. Wong, "Algorithm as 136: A k-means clustering algorithm," Journal of the royal statistical society. series c (applied statistics) **28**, 100–108 (1979).

[40] V. Satopaa, J. Albrecht, D. Irwin, and B. Raghavan, "Finding a" kneedle" in a haystack: Detecting knee points in system behavior," in *2011 31st international conference on distributed computing systems workshops* (IEEE, 2011) pp. 166–171.

[41] R. Nainggolan, R. Perangin-angin, E. Simarmata, and A. F. Tarigan, "Improved the performance of the k-means cluster using the sum of squared error (sse) optimized by using the elbow method," in *Journal of Physics: Conference Series*, Vol. 1361 (IOP Publishing, 2019) p. 012015.

[42] H. J. Williams, O. Duriez, M. D. Holton, G. Dell'Omo, R. P. Wilson, and E. L. Shepard, "Vultures respond to challenges of near-ground thermal soaring by varying bank angle," Journal of Experimental Biology **221**, jeb174995 (2018).

[43] A. Silva, M. Gombolay, T. Killian, I. Jimenez, and S.-H. Son, "Optimization methods for interpretable differentiable decision trees applied to reinforcement learning," in *International conference on artificial intelligence and statistics* (PMLR, 2020) pp. 1855–1865.

[44] Y. Coppens, K. Efthymiadis, T. Lenaerts, A. Nowé, T. Miller, R. Weber, and D. Magazzeni, "Distilling deep reinforcement learning policies in soft decision trees," in *Proceedings of the IJCAI 2019 workshop on explainable artificial intelligence* (2019) pp. 1–6.

[45] G. Liu, O. Schulte, W. Zhu, and Q. Li, "Toward interpretable deep reinforcement learning with linear model u-trees," in *Machine Learning and Knowledge Discovery in Databases: European Conference, ECML PKDD 2018, Dublin, Ireland, September 10–14, 2018, Proceedings, Part II 18* (Springer, 2019) pp. 414–429.

[46] M. Vasic, A. Petrovic, K. Wang, M. Nikolic, R. Singh, and S. Khurshid, "Moët: Interpretable and verifiable reinforcement learning via mixture of expert trees," arXiv preprint arXiv:1906.06717 (2019).

[47] M. A. Lewis, W. F. Fagan, M. Auger-Methe, J. Frair, J. M. Fryxell, C. Gros, E. Gurarie, S. D. Healy, and J. A. Merkle, "Learning and animal movement," Frontiers in Ecology and Evolution **9**, 681704 (2021).

[48] A. Goldshtein, M. Handel, O. Eitan, A. Bonstein, T. Shaler, S. Collet, S. Greif, R. A. Medellín, Y. Emek, A. Korman, *et al.*, "Reinforcement learning enables resource partitioning in foraging bats," Current Biology **30**, 4096–4102 (2020).

[49] W. Zhao, J. P. Queralta, and T. Westerlund, "Sim-to-real transfer in deep reinforcement learning for robotics: a survey," in *2020 IEEE symposium series on computational intelligence (SSCI)* (IEEE, 2020) pp. 737–744.

[50] W. Zhu, X. Guo, D. Owaki, K. Kutsuzawa, and M. Hayashibe, "A survey of sim-to-real transfer techniques applied to reinforcement learning for bioinspired robots," IEEE Transactions on Neural Networks and Learning Systems (2021).

[51] J. Ramírez, W. Yu, and A. Perrusquía, "Model-free reinforcement learning from expert demonstrations: a survey," Artificial Intelligence Review , 1–29 (2022).

[52] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel, "Domain randomization for transferring deep neural networks from simulation to the real world," in *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)* (IEEE, 2017) pp. 23–30.

Appendices and Supplementary Information

Revealing principles of autonomous thermal soaring in windy conditions using vulture-inspired deep reinforcement-learning

Yoav Flato, Roi Harel, Aviv Tamar and Tsevi Beatus

Appendix A: Aerodynamic force model and glider parameters

The environment is based on a 6 degrees-of-freedom (DOF) simulation of a point-mass glider governed by the equations of motion in Eq. 1. The aerodynamic forces: lift L, drag D and side force C, are:

$$L(V,\alpha) = \frac{1}{2}\rho S C_L(\alpha) V^2$$
$$D(V,\alpha,\beta) = \frac{1}{2}\rho S C_D(\alpha,\beta) V^2 \qquad \text{(A1)}$$
$$C(V,\beta) = \frac{1}{2}\rho S C_C(\beta) V^2,$$

where the forces are functions of the velocity V, the aerodynamic coefficients $C_L(\alpha), C_D(\alpha,\beta), C_C(\beta)$, the wing surface area S, the air density ρ. The force coefficients are functions of the angle-of-attack α and the sideslip angle β, and depend also on the glider's mass, wingspan and wing aspect ratio (Table A.1). Importantly, the aerodynamic forces are calculated in the wind frame of reference[29].

Appendix B: An upper bound for the thermal climb rate

One way to evaluate a policy of an agent in our system, would be to compare the policy climb rate performance (mean v_z) in a given environment to the maximum climb rate possible under the same conditions. Hence, we estimated an upper bound for the climb rate, as described below.

We assume that an optimal trajectory has constant rotation radius in the wind frame of reference and, therefore, constant control parameters (σ,α,β) in that frame. Note that to keep these control parameters constant in the wind frame of reference (under any wind, horizontal or vertical), an agent would need to modulate them in the body frame of reference. Further, we assume β=0 as used in our nominal agent.

First, for each pair of (σ,α) we analytically solve the equations of motion (section II B) in steady state and find the values of V_{ss}, γ_{ss} and R_{ss}, where the latter is the trajectory radius. Second, we define, d, the distance between the center of the trajectory and the thermal center, and use numerical optimization to find (σ,α,d) that result in maximum climb rate v_z in the world frame of reference. These two stages are detailed below.

In steady state of eq. (1) the velocity and glide angle are constant:

$$\dot{V} = 0 = -\frac{1}{m}D(V_{ss},\alpha,\beta) - g\sin\gamma_{ss}$$
$$\dot{\gamma} = 0 = \frac{1}{mV}\left(L(V_{ss},\alpha)\cos\sigma + C(V_{ss},\beta)\sin\sigma\right) - \frac{g}{V_{ss}}\cos\gamma_{ss}$$
$$\text{(B1)}$$

Assuming β=0, we get:

$$D(V_{ss},\alpha,0) = -mg\sin\gamma_{ss}$$
$$L(V_{ss},\alpha)\cos\sigma = mg\cos\gamma_{ss} \qquad \text{(B2)}$$

By dividing these two equations and rearranging, we obtain an expression for the steady state glide (pitch) angle:

$$\gamma_{ss}(\sigma,\alpha) = \arctan\left(-\frac{C_D(\alpha,0)}{C_L(\alpha)cos(\sigma)}\right). \qquad \text{(B3)}$$

We then substitute the definition of $D(V,\alpha,\beta)$ from eq. (A1) into eq. (B2) to get V_{ss}:

$$V_{ss}(\sigma,\alpha) = \sqrt{-\frac{2mg\sin(\gamma_{ss}(\alpha,\sigma))}{C_D(\alpha,0)S\rho}}. \qquad \text{(B4)}$$

In this steady state of circular motion in the wind frame of reference, the radial force due to the tilted lift vector is equal to the radial acceleration: $L(V_{ss},\alpha)\sin(\sigma) = mV_{ss}^2/R_{ss}$. To find R_{ss} from this equation, we substitute $L(V_{ss},\alpha)$ from eq. (A1):

$$R_{ss}(\sigma,\alpha) = \frac{2m}{C_L(\alpha)S\rho\sin(\sigma)}. \qquad \text{(B5)}$$

Note that because $L \sim V^2$, then R_{ss} is independent of V_{ss}. The steady state climb rate in the wind frame is:

$$v_z^{\text{wind}}(\sigma,\alpha) = V_{ss}(\sigma,\alpha)\sin(\gamma_{ss}(\sigma,\alpha)) \qquad \text{(B6)}$$

Next, for each combination of (σ,α,d), we calculate the average climb rate v_z in the world frame of reference. This climb rate consists of two terms:

$$v_z(\sigma,\alpha,d) = v_z^{\text{wind}}(\sigma,\alpha) + v_z^{\text{thermal}}(\sigma,\alpha,d). \qquad \text{(B7)}$$

The first term is given in eq. (B6) at steady state, and the second term is the vertical velocity of the wind frame itself due

Symbol	Name	Value	Units
AR	aspect ratio	16	-
l	wingspan	2.5	Meter
W	mass	5	kg

TABLE A.1. **Glider parameters.** The glider parameters used in the simulation are based on Beeler *et al.*[29].

to the thermal updraft averaged across the agent's trajectory. Each pair of control parameters (σ, α) defines a value of R_{ss} (eq. (B5)). Together with d, and relying on the radial symmetry of the thermal, we numerically calculate the mean thermal updraft along one rotation period $v_z^{\text{thermal}}(\sigma, \alpha, d)$:

$$v_z^{\text{thermal}}(\sigma, \alpha, d) = \frac{1}{T} \int_0^T w(r, z) dt, \qquad \text{(B8)}$$

where T is the rotation period, $w(r, z)$ is the thermal updraft velocity (eq. (2)), $r = r(d, R_{ss}, t)$ is the glider distance from the thermal center, and z is the glider altitude. We assume constant altitude of 500m because we characterize the optimal updraft at this altitude and because the thermal updraft profile does not change much with altitude (Fig. 3).

Finally, using numerical optimization on (σ, α, d), we find that under our simplifying assumptions the upper bound the the climb rate in the world frame of reference is obtained for $\alpha \approx 13.3°$, $\sigma \approx 31.5°$, $d = 0$ (*i.e.*, flying directly around the thermal center) and $R_{ss} = 28.2\,\text{m}$. The upper bound is:

$$v_z^{\text{optimal}} = 0.72\,\text{m/sec} \qquad \text{(B9)}$$

Appendix C: Hyper-parameters search

We used a Bayesian method for hyper-parameter search[38] to optimize the following hyper-parameters of our RL system: the learning algorithm (DDPG[20] or PPO[19]), learning rate, and the NN architecture (hidden layer size and number of hidden layers) for both actor and critic. Each combination of hyperparameters, was tested on a model problem of thermal soaring under $u=1\,\text{m/sec}$ given 10^6 time steps (~5,000 thermals) to converge.

The optimization results are summarized in Fig. C.1. The chosen algorithm was DDPG with learning rate of 10^{-3}. The actor NN architecture was: 2 hidden layers of 200 neurons each and ReLU activation, and tanh activation for the output layer. The critic NN architecture was the same, without an activation function on its (scalar) output. In this parameter scan, the PPO algorithm achieved similar results but with larger networks of 500 neurons in 2 hidden layers.

Appendix D: Comparing the agent performance to real data of soaring vultures

We compared the performance of our nominal agent to the trajectories of real vultures soaring in thermals, as measured by Harel *et al.* in 2013-2014[1]. The data consists of GPS

FIG. C.1. **Bayesian Hyper-Parameter Search Results.** This scheme includes of five columns: four for each hyperparameter and the rightmost one for the agent's performance in terms of its average thermal time. Each continuous line represents a single run of 10^6 timesteps, indicating the values of the four hyperparameters and gliding performance. The lines are color-coded by gliding performance.

samples taken at 1Hz, which provide the longitude, latitude, height, and timestamp for each sample. We first found the trajectory segments that correspond to thermal soaring. Each data point was labeled as 'thermal soaring' if the vulture's average climb rate during the preceding 20 seconds was positive. A sequence of ≥ 100 such points was defined as a thermal soaring trajectory. The data contains ~6,000 thermalling trajectories. Velocity and acceleration were calculated using the Savitzky-Golay filter.

To estimate the bank angle from the data, we consider the forces in the radial and vertical axes:

$$\begin{aligned} ma_r &= L\sin(\sigma)\cos(\gamma) - D\sin(\sigma)\sin(\gamma) \\ mg &= L\cos(\sigma)\cos(\gamma) - D\cos(\sigma)\sin(\gamma), \end{aligned} \qquad \text{(D1)}$$

were a_r is the radial acceleration. Since $\sin(\gamma) = v_z/V \approx 0.1$ and $D < L$, we neglect the drag components in eq. D1, and by dividing the remaining terms we estimate $\sigma \approx \arctan(a_r/g)$. We obtain σ in each timestep by calculating a_r from the data, and then averaging σ over each trajectory. To validate the estimation the average σ we tested this calculation on the simulation results, where σ is known. On average, our estimation was accurate within 7%.

To approximate the wind velocity in the data, we calculated the average velocity in the xy plane during an entire thermalling trajectory. This approximation neglects the effect of thermal leaning[33], yet it provides a wind velocity distribution similar to the distribution measured on the same dataset using the RAMS atmospheric model[1]. we use the estimated wind velocity to choose the data trajectories for comparison with

FIG. D.1. **Comparing thermalling of the nominal agent and of real vultures.** Both vulture- and agent-data used in these statistics include only the thermalling parts of the trajectories, under horizontal winds of 1–4 m/sec. The horizontal wind in the data was estimated from the tilt angle of the measured trajectories. The parameters shown are the mean climb rate v_z, the mean speed V, and the mean bank angle σ (known for the agent, estimated for the vultures, as detailed in Appendinx D).

FIG. E.1. **NN neural clusters during the learning process of reduced-state agent.** **(a)** Performances values during the learning process. The high performance values observed in the beginning of the run are attributed to the fact that this learning process started from pre-trained agents. **(b)** Distribution of the clusters of each agent as a function of θ.

the agent's trajectories.

Finally, we compared the data and agent trajectories in terms of their average climb rate v_z, average speed V, and average bank angle σ (Fig D.1). The comparison was performed for trajectories with horizontal wind of 1–4 m/sec. The average climb rate of the vultures was 1.39 m/sec, compared with 0.49 m/sec of the agent. However, this comparison should consider two differences between the data and simulation: first, the physical parameters of the vulture and agent are different, mainly in their wing area and body mass (see below); second, the thermal updraft velocity in the data is unknown, and may be greater than the value used in the simulations. We can address the latter difference by inverting our estimation of the optimal v_z performance given the thermal parameters. We estimate that if the vultures' soaring is optimal, then soaring at v_z=1.39 m/sec should correspond to a thermal with $w_{core}\approx2.6$ m/sec. This estimation considers the greater wing area and mass of the vulture compared with our simulated agent. When performing the same calculation with our agent parameters, we get that climbing at v_z=1.39 m/sec should correspond to $w_{core}\approx3.1$ m/sec. Both these updraft velocities are greater than the $w_{core}\approx2.3$ m/sec used in our simulations. Hence, even if vulture soaring is optimal, it still means that the thermals in the data were stronger than the thermals in the simulation. Finally, estimating the optimal v_z of a glider with vulture parameters in thermals with $w_{core}\approx2.3$ m/sec, gives $v_z^{optimal}$=1.13 m/sec, meaning that the vulture physical parameters yield better gliding performance than the agent's physics parameters. In summary, the difference in the vulture and agent soaring performance is at least partially attributed to stronger thermals in the data and the superior physical parameters of the vultures.

Next, we show that the difference in the bank angle be-

tween the vultures and our simulated agent are explained by their different physical parameters. Assuming the vultures and agent circle the thermal at the same radius $R_a = R_v$, we can use eq. (B5) to derive the following relationship:

$$\frac{2m_a}{C_{L_a}(\alpha_a)S_a\rho\sin(\sigma_a)} = R_a = R_v = \frac{2m_v}{C_{L_v}(\alpha_v)S_v\rho\sin(\sigma_v)}, \quad (D2)$$

Where the subscript "a" denotes an agent parameter and the subscript "v" denotes vulture parameters. Assuming the aerodynamic coefficients of the two are similar, the main differences between them are the mass (m_v=7.65kg, m_a=5kg) and wing area (S_v=0.87m^2, S_a=0.39m^2). Under these assumptions, we substitute the value σ_v = 22.09° based on the data into eq. (D2) and get that $\sigma_a = \arcsin(\frac{S_v m_a \sin(\sigma_v)}{S_a m_v})$=33.25°. This value is quite close to the value of σ_a=35.6° from the simulation (Fig. D.1).

Appendix E: Clustering analysis of agents with a reduced state representation

To verify that the activity distribution of the NN clusters in θ was not a trivial outcome of having θ as an implicit state variable, we trained an agent whose state did not include θ. Instead, the state included $\{V, v_z, \sigma\}$ and the agent was trained on one value of u=1 m/sec. The agent with this reduced state-representation achieved stable soaring and exhibited similar

clustering characteristics that evolved to be θ-dependent with the agent's 'age' (Fig. E.1).

Appendix F: Supplementary material

Supplementary videos. Representative trajectories of the nominal agent soaring in a thermal under horizontal winds of 2.4 m/sec (Video 1) and 3 m/sec (Video 2).