Unwanted coliforms can hide in mature drinking water biofilms, grown in full-scale distribution networks

Fien Waegenaar[1,2], Cristina García-Timermans[1,2], Bart De Gusseme[1,2,3], Nico Boon[1,2,*]

[1]Center for Microbial Ecology and Technology (CMET), Department of Biotechnology, Ghent University, Coupure Links 653, B-9000 Ghent, Belgium.

[2]Center for Advanced Process Technology for Urban Resource Recovery (CAPTURE), Frieda Saeysstraat 1, B-9000 Ghent, Belgium.

[3]Farys, Department R&D – Innovation Water, Stropstraat 1, B-9000 Ghent, Belgium.

Running title:

Coliform invasion in drinking water biofilms.

*Correspondence: nico.boon@ugent.be

Abstract

Biofilms within drinking water distribution systems are an important habitat for drinking water microorganisms. However, they can play a role in microbial regrowth, water discoloration and can be a reservoir for unwanted microorganisms. In this study, we investigated whether indicator organisms for drinking water quality, such as coliforms, can settle in mature drinking water biofilms. Therefore, a biofilm monitor consisting of glass rings was used to grow and sample drinking water biofilms. Two mature drinking water biofilms were characterized by flow cytometry, ATP measurements, confocal laser scanning microscopy and 16S rRNA sequencing. Overall, biofilms developed under treated chlorinated surface water supply exhibited lower cell densities in comparison with biofilms resulting from treated groundwater. We observed that water sources shaped the biofilm community composition while drinking water disinfection determined the biofilm density. In addition, the response of the biofilm microbiome and possible biofilm detachment after minor water quality changes were

investigated. Limited changes in pH and free chlorine addition, to simulate operational changes

that are relevant for practice, were evaluated. It was shown that both biofilms remained resilient.

Finally, mature biofilms were prone to invasion of the coliform, *Serratia fonticola*. After

spiking low concentrations (i.e. ± 100 cells/100 mL) of the coliform to the corresponding bulk

water samples, the coliforms were able to attach and get established within the mature biofilms.

These outcomes are emphasizing the need for continued research on biofilm detachment and

its implications for water contamination in distribution networks.

1 Introduction

Microbial communities are ubiquitously present in drinking water distribution systems (DWDS). More than 98% of these microorganisms form biofilms on pipe materials or are associated with loose deposits (1–3). Biofilms can play a role in drinking water discoloration, the transformation of organic compounds, the decay of free chlorine, microbial regrowth, the formation of disinfection by-products and unwanted odor compounds, etc. (4–7). Furthermore, it is known that they can be a potential source of opportunistic pathogens (3, 8–12). Previous researchers detected pathogens such as *Mycobacteria* spp. and *Legionella* spp. as well as fecal indicator bacteria such as *Escherichia coli* in biofilm samples from a full-scale distribution network (9, 11). Furthermore, *Pseudomonas aeruginosa*, *Mycobacterium avium* and *Legionella pneumophila* can survive in young biofilms after spiking 10^5-10^6 cells/mL (12, 13). As a result, biofilms are a potential risk to human health as biofilm cells can be released to the planktonic water phase in some conditions. Nowadays, the measurement of coliform bacteria is used as an indicator for fecal contamination and to control the effectiveness of disinfection processes and the cleanliness and integrity of distribution systems (14, 15). In Flanders, 3.30% norm exceedances of the coliform indicator parameter were measured in 2021, however, the source of microbial contaminations is often not retrievable (14, 16, 17). Though, Kilb et al. (17) detected coliforms on rubber-coated valves from distribution networks, which could be possible sources of contaminations. However, more insights about pathogen invasion and detachment are needed to estimate corresponding unwanted consequences on the final water quality and safety.

Characterizing biofilm microbial compositions and physical characteristics, and therefore investigating the drinking water biofilm, is challenging as sampling is difficult in practice. Previous researchers used lab set-ups to determine biofilm microbial development and community compositions (18–25). Biofilm formation rates in terms of ATP activity and

deposition of iron and manganese is previously studied using biofilm monitors consisting of

glass rings (26–28). Relatively new sampling techniques consist of a coupon holder to

implement in a part of the drinking water distribution systems (DWDS) or in pilot-scale

networks (29, 30). Ginige et al. (27) showed that the microbial ATP content on glass rings was

80% less than on plastic coupons for young biofilms (i.e. 6 months). However, inert glass allows

the bulk water characteristics to be the only variable determining biofilm formation and

composition (26).

A typical drinking water biofilm consists of a diverse microbial community attached to

distribution pipes and immersed in a self-produced matrix of extracellular polymeric substances

(EPS), which mainly contain polysaccharides and proteins (3, 31, 32). The bacterial biofilm

community is dominated by *Proteobacteria*, more specifically *Alpha-* and

Gammaproteobacteria. The most prominent biofilm genera on distribution pipes are

Pseudomonas, *Sphingomonas* and *Acinetobacter* (1, 6, 30, 33–40). The drinking water biofilm

environment offers protection against antibiotics, metals, disinfectants such as free chlorine and

changing operational conditions such as shear stress, because of the EPS matrix and the

interconnected processes among the biofilm bacteria (41–43). Additionally, EPS can serve as

precursor for the formation of disinfection by-products (7). However, more research is needed

to determine the role and influences of EPS on the final drinking water quality. Biofilm

formation, its corresponding physical structure and the present microbial community are mainly

influenced by the raw water source and treatment (e.g. microbial and nutrient composition) (3,

20, 44–47). For example, previous studies reported a shift in the microbial biofilm community

and concentrations on distribution pipes after switching from drinking water with more carbon

and a higher conductivity to less turbid water with a lower nutrient content (45, 46). In addition,

the drinking water biofilm composition, and therefore biofilm detachment, is affected by the

water residence time, pipe materials, free chlorine concentrations and temperature (5, 22, 24,

48–54). Previous researchers mainly investigated the bacterial removal efficacy of

hydrodynamic stressors such as flushing, increasing chlorination concentrations or interrupted

water flow (23, 49, 51, 54). For example, shock chlorination (10 mg Cl_2/L, 60 minutes contact

time) removes 75% of the biofilm bacteria (23). However, the influence of minor operational

changes, which often happens in practice, on biofilm dispersal to the water phase is lacking in

literature.

Here, two biofilm monitors consisting of glass rings were set up to investigate whether

unwanted coliforms can intrude into mature drinking water biofilms. First, the biofilms were

characterized regarding bacterial cell density and community compositions as well as physical

parameters such as biofilm biomass and thickness. Secondly, the response of the biofilm

microbiome and possible biofilm detachment after minor water quality changes were

investigated. These quality changes (pH, free chlorine concentration) were specifically chosen

to simulate operational changes that are relevant for the full-scale DWDS in operation. Finally,

survival of the coliforms in the bulk water phase was evaluated and attachment of these

coliforms on the biofilm was investigated using confocal laser scanning microscopy and qPCR.

Again, we explicitly chose to spike coliforms in low concentrations, in order to simulate real-

life contaminations and thus conditions relevant for practice.

2 Materials and Methods

Biofilm sampling device, conditions and experimental design. A KIWA biofilm monitor was used (KWR, The Netherlands) consisting of 40 glass rings to collect drinking water biofilm (Figure A1). This monitor was placed at two different locations (Table A1). Monitor 1 was placed at the outlet of a drinking water reservoir receiving treated groundwater, before the UV post-disinfection step. Monitor 2 was placed at the outlet of a drinking water tower receiving treated surface water with residual free chlorine. The monitors were operating for 17 months at the respective locations and there was a continuous flow of 270 L/h, according to the manufacturer's instructions. Water quality parameters were measured by the respective drinking water providers (55). The total organic carbon (TOC) concentration was measured at the end of the experiment (16).

After 11 months and 17 months, 3 rings were analyzed with confocal laser scanning microscopy (CLSM). 4 rings were put in 10 mL autoclaved tap water and sonicated in a water bath (37 kHz, Elma – Ultrasonic, Belgium) 3 times for 2 minutes with a vortex step in between according to the manufacturer's instructions, to detach the biofilm. The biomass was quantified in terms of heterotrophic plate counts (HPC), ATP and total cell concentration (TCC) and the microbial community was characterized with 16S rRNA amplicon sequencing as described further. In the second part of the study, the KIWA monitors were transported to laboratory conditions to be able to manipulate the water conditions and to perform invasion experiments. During these experiments, the corresponding water types were used (Table A1). The monitor was connected to a 10 L plastic vessel and the water was pumped (WM 323 peristaltic pump, Watson Marlow, Belgium) and recirculated over the biofilm monitor. The pump was operating on 150 rpm and the flow was 42 L/h. The experiments were performed at room temperature (i.e. 22 °C).

Changing operational conditions in terms of the Langulier Saturation Index and

HOCl addition. The LSI was calculated according to WAC/III/A/011 (56) (Table 1). The pH,

conductivity and calcium concentration were measured using a Multi-parameter analyser

C1010 (Consort, Belgium), a Hanna Edge Conductivity Meter (HANNA Instruments, Belgium)

and the Total Hardness Test (Merck, Belgium), respectively. The alkalinity of the water samples

was determined based on WAC/III/A/006 (57). Using 1M NaOH and 1M HCl (Chem-lab,

Belgium), the pH was adapted to the a higher and lower Langelier Saturation Index (LSI)

(Table 1). In addition, HOCl solution was added to have a free chlorine concentration of 0.20

mg/L and 0.28 mg/L, for the groundwater and surface water samples, respectively. The chlorine

concentrate solution was prepared by addition of a NaOCl tablet (B-Care Chemicals, Belgium)

to 1 L ultrapure water (Milli-Q, Merck Millipore, Germany). The amount of free chlorine was

quantified with the Pocket Colorimeter II (Hach,Belgium).

Invasion experiments with GFP-labelled *Serratia fonticola*. The strain was isolated

from the Flemish drinking water distribution network (Antwerp, Pidpa). The strain was made

ampicillin resistant by serial selections on Luria Broth (LB) agar (Carl Roth, Belgium) with

increasing concentrations ampicillin (5 µL/mL to 100 µL/mL) (Merck, Belgium). Each time,

the cultures were incubated for 24 hours at 28°C. GFP-labelling was performed using triparental

mating. Briefly, the donor strain *Escherichia coli* DH5α pME6012 containing the plasmid ptac-

gfp and the helper strain *Escherichia coli* HB101 containing the plasmid pRK2013 needed for

conjugation were grown in LB medium at 37°C for 24 hours with 8 µg/mL tetracycline and 50

µg/mL kanamycin, respectively. The acceptor, *Serratia fonticola*, was grown in LB medium

with 50 µg/mL ampicillin at 28°C for 24 hours. Next, the cultures were washed twice. They

were centrifuged for 5 minutes at 3000 g, the supernatant was removed and 0.22 µm filtered

sterile PBS (PBS tablet, Merck, Belgium) was added. Triparental mating was performed by

adding10 µL of each culture on LB agar. Plates were incubated at 28°C for 24 hours. GFP-

labelled coliforms were selected for resistance to tetracycline (8 µg/mL) and ampicillin (50

µg/mL) and screened for GFP fluorescence using a dark reader (Clare Chemical Research,

USA). The final identification of the pure culture was performed with 16S rRNA gene Sanger

sequencing as described in (58) and NCBI BLAST (59).

Two invasion experiments were performed by spiking GFP-labelled *Serratia fonticola*

to the corresponding water samples (V = 10 L) in plastic vessels which were connected to the

KIWA monitor. Therefore, a few colonies were picked from the agar plate and resuspended in

25 mL of 3 g/L sterile R2A broth medium (Oxoid, England) with tetracycline (8 µg/mL) and

ampicillin (50 µg/mL) and the tubes were incubated at 28°C and 100 rpm for 24 hours.

Subsequently, the culture was washed using sterile 8.5% NaCl as explained before. Afterwards,

the culture was transferred to a diluted liquid medium of 50 mg/L R2A broth medium (Oxoid,

England) with tetracycline (8 µg/mL) and ampicillin (50 µg/mL) and incubated at 28°C and

100 rpm for 24 hours. The culture was washed before measuring the TCC with flow cytometry.

The culture was diluted using sterile 8.5% NaCl and final spike concentrations were ranging

from 50 – 500 cells/100 mL. The concentration of *Serratia fonticola* in the bulk water was

determined by filtering (3x 100 mL) on S-Pack filters 0.45 µm (Merck, Belgium) using a

filtration unit consisting of six filtration funnels and a Microsart e.jet vacuum pump (Sartorius,

Germany) and incubation (18 – 23 h, 37°C) on coliforms chromogenic agar (Carl Roth,

Belgium), according to the ISO 9308-1:2014 method for drinking water (55). Water was

refreshed after 4 days of recirculation.

Confocal laser scanning microscopy. Visual characterization of the biofilms was done

with a Nikon A1R confocal microscope (Nikon Instruments Inc., USA), which consists of 4

lasers with in total 7 laser lines (405, 457, 476, 488, 514, 561, 639 nm). Prior to analysis,

samples were fixed in 4% paraformaldehyde (Merck, Belgium) for 24 hours. Fixated biofilm

rings were stored at -20°C in a PBS:EtOH 1:1 solution prior to analysis. All samples were

analyzed within 14 days. First, the EPS protein content was stained for 30 minutes with

FilmTracer Sypro Ruby Biofilm Matrix Stain (Thermofisher Scientific, Belgium) and the

carbohydrates with 25 µL/mL Concanavalin A CF640R (Biotium, USA) for 30 minutes.

Nucleic acids were labelled with 3 µM DAPI (Merck, Belgium) for 20 minutes. Staining was

performed at room temperature (i.e. $\pm$ 22°C) and in the dark, after each staining step a washing

step with cold (i.e. $\pm$ 6°C), filtered through 0.2 µm, PBS. Finally, the rings were air-dried and

Fluoroshield mounting medium (Merck, Belgium) was added to prevent bleaching. A

construction was made and Nunc™ Glass Bottom Dishes (Thermofisher Scientific, Belgium)

were used to fit the biofilm ring under the CLSM. For each location, 3 biofilm rings (n = 3)

were analyzed with confocal microscopy and technical replicates (n = 4) were taken. Image

stacks were processed in ImageJ and the plugin Comstat2 was used to determine biomass,

roughness and thickness of the biofilms (61). An automatic threshold (Otsu's method) was used

for all image processing.

Biomass analysis. HPC, ATP and TCC were determined as described in (16). In brief,

The ATP concentration was measured using the BacTiter-Glo™ Microbial Cell Viability Assay

(Promega, Belgium) and luminescence was measured with the Infinite M Plex, multimode

microplate reader (Tecan, Switzerland). TCC was measured using an Attune NxT BRXX flow

cytometer (ThermoFisher Scientific, USA) and staining was performed with 1 v% of SYBR

Green I solution. Biofilm samples were 10 times diluted in 0.2 µm filtered Evian and all samples

were measured in technical triplicate.

Molecular analysis of microbial communities. 16S rRNA gene amplicon sequencing

was performed on biofilm and bulk samples. Biofilm samples (volume = 15 mL) were filtered

using Millipore Express PLUS Membranes (Merck, Belgium) and Polycarbonate syringe filter

holder (Sartorius, Germany). MF-Millipore Membrane Filters (Merck, Belgium) and a filtration

unit consisting of six filtration funnels and a Microsart e.jet vacuum pump (Sartorius, Germany)

were used to filter bulk water samples. DNA extraction was performed using the DNeasy

PowerSoilPro kit (Qiagen, Germany), following the manufacturer's protocol. PCR

amplification was performed according to Van Landuyt et al. (62). 10µL genomic DNA extract

was send out to LGC genomics GmbH (Berlin, Germany) for library preparation and

sequencing on an Illumina Miseq platform with v3 chemistry (Illumina, USA).

Quantitative polymerase chain reaction (qPCR) to detect Serratia fonticola. QPCR

assays were performed using a StepOnePlus real-time PCR system (Bio-Rad, Belgium).

Specific primers were used to detect the gfp-gen: Forward (5'-

AGTGGAGAGGGTGAAGGTGA-3') and Reverse (5'-ACGGGAAAAGCATTGAACAC-

3'). Reactions were performed in a volume of 20 µL consisting of 10 µL of 2x iTAQ universial

SYBR Green supermix (Bio-Rad Laboratories, USA), 2.0 µL DNA template, 0.8 µL (10 µM)

of each primer, and 6.4 µL nuclease-free water. Amplification conditions were outlined

according to the manufacturer's instructions. Quantification was done a standard curve based

on known concentrations of DNA standard dilutions from 10^7 copies/µL to 10 copies/µL.

Reactions were performed in technical triplicates, a negative and positive control was included.

Data analysis and Statistics. Data analysis was done in R (63) in RStudio version 4.2.1

(64). The Flow Cytometry Standard (.fcs) files were imported using the flowCore package

(v2.12.2) (65). The background data was removed by manually drawing a gate on the FL1-H

(green) and FL3-H (red) fluorescence channels as described in Props et al. (2016). The xlsx

package (v4.2.5.2) was used to analyze the data from the confocal microscopy (67). Illumina

data was processed using the DADA2 pipeline (v1.28.0) as outlined by

https://benjjneb.github.io/dada2/tutorial_1_2.html (68). Taxonomy was assigned using the

Silva database v138 (69). Further data analysis was performed using statistical packages such

as the phyloseq package (v1.44.0) and the vegan package (v2.6-4) (70, 71). Data visualization

was done using the ggplot2 (v3.4.3) and ggpubr (v0.6.0) packages (72, 73). Statistical analysis

was done with the dplyr package (v1.1.2) and the vegan package (v2.6-4) (71, 74).

3   Results

Mature biofilm characterization. A KIWA biofilm monitor was used to grow and sample

a drinking water biofilm (Figure A1). The monitor was set up at two different places receiving

two different water types: treated groundwater without a disinfection step and treated surface

water with a chlorination step. Treated surface water contained more minerals such as

aluminum, calcium, nitrate, resulting in a higher hardness, whereas treated groundwater had a

higher TOC content and more total colony counts (Table A1).

After 11 and 17 months of biofilm development, the biofilms were characterized by flow

cytometry, ATP analysis, confocal laser scanning microscopy (CLSM) and 16S rRNA

sequencing (Table 2, Figure 1). The cell densities and ATP concentrations of the groundwater

biofilms were 10 times higher than the surface water biofilms. Similar observations were seen

using CLSM, where DAPI staining was used to determine the biofilm biomass, roughness and

average thickness. Significant statistical differences were observed between the two biofilms

(Table 2). In addition, using 16S rRNA sequencing, a significant difference between the two

biofilm community compositions was observed (ANOSIM, $p < 0.05$, Figure 1). *Chloroflexi* and

Proteobacteria were identified as the most dominant phyla in the groundwater biofilm samples,

with an abundance of 37% and 35% respectively. *Chloroflexi* were mainly represented by

uncultured and unclassified JG30-KF-CM66 (~30%) and S085 (~7%) bacteria, however, only

1.5% of the groundwater bulk bacteria belonged to this phyla. The bulk community was

dominated by *Cyanobacteria* (~26%) and *Alphaproteobacteria* (~22%), for example,

Hyphomicrobiaceae (~3%) and *Hyphomonodaceae* (~3%) (Figure A2). These families were

also detected in the surface water biofilm samples (i.e. ~3% and ~11%, respectively) and to a

lower extent in the corresponding bulk samples (i.e. ~2% and ~7%, respectively). More than

65% of the bacteria in the biofilms developed under surface water supply were

Alphaproteobacteria, more specifically *Acetobacteraceae* (~12%), *Beijerinckiaceae* (~8.5%)

and *Sphingomonadaceae* (~ 7%). Furthermore, these bacteria were predominant in the surface

water bulk samples (~70%, Figure A2). These results indicate that the raw water sources are

mainly influencing the bacterial community traits whereas treatment (e.g. disinfection) is

determining the biofilm cell densities.

As extracellular polymeric substances (EPS) are an important part of a biofilm structure,

the protein and sugar content were determined as well (Table 2, Figure 2). In accordance with

the other measurements, 10 times more EPS biovolume was noticed for the groundwater biofilm

over the surface water biofilm. However, the ratio sugars:biomass and proteins:biomass were

similar for both mature biofilms (Figure A3). Higher bacterial and EPS content in the

groundwater biofilm could be related to the higher carbon content in the raw water and the fact

that no disinfectant was used (Table A1). To illustrate that the biofilms used in further

experiments were mature, statistical analyses were performed between the two time points,

more precisely after 11 and 17 months. Biomass and community composition were not

significantly different over time for both biofilms (Table A2).

Effect of operational water quality changes on biofilm detachment. After 17 months

of growing a drinking water biofilm, the KIWA monitors were transferred from the water

reservoirs to laboratory conditions and the original water quality was adapted to examine the

response of the biofilm microbiome towards limited changes that are also observed in practice.

More concretely, the effects of minor pH variations and the addition of small concentrations of

HOCl on biofilm detachment were investigated. These small pH changes were leading to an

increase or decrease in the Langelier Saturation Index (LSI) (Table 1). This qualitative index is

used to predict the scale forming potential of water and is based on the measurement of pH,

conductivity, alkalinity, calcium ions and temperature (75, 76). Cell counts in the bulk were

measured with flow cytometry for 8 hours. In general, little or no detachment of the biofilm

was observed compared to the blank (Figure 3). Linear regression with a confidence interval of

95% was performed to quantify cell release rates to the bulk. If the cell release rate is higher

than zero, there is an indication that biofilm cells are dispersed into the bulk water phase.

Briefly, a detachment was always observed except for two blank conditions. Furthermore, the

dispersal of biofilm cells to the bulk water was faster (i.e. higher release rates) when the LSI

was changed or when HOCl was added. Therefore, statistics on the residuals and the slopes of

the linear regression models were done and no significant difference was observed between the

blanks and the applied operational changes (Table A3).

Invasion of coliforms onto drinking water biofilms. *Serratia fonticola*, isolated from

the Flemish distribution network, was labelled with a green fluorescent protein (GFP) to

distinguish this specific strain from other drinking water biofilm bacteria and spiked (15 – 500

cells/100 mL) to the water fed to the biofilm monitors. Two spike experiments were performed

for each water type, and the start concentration and survival of the coliform in the bulk water

were followed using selective media. Additionally, qPCR and CLSM were used to determine

whether *Serratia fonticola* was attached to the biofilm (Table 3, Figure 4). For treated surface

water, the coliforms were still present in the bulk water phase after three hours. After 24 hours,

the coliforms were below detection limit (< 0 cells/100 mL) for both water types. Biofilms on

the glass rings were analyzed after 4 or 7 days using CLSM and qPCR. For the first spike

experiment, the gene copies were below the limit of quantification (LOQ = 28.57 gene

copies/cm²), whereas for the second spike experiment, 578.59 ± 38.45 and 358.36 ± 24.03 gene

copies/cm² of the invader were measured in the groundwater and surface water biofilms,

respectively. Detection of the GFP-labelled *Serratia fonticola* in the biofilm was also done with

CLSM and coliforms were detected 7 or 8 days after the spike for each water type. Even though

mature biofilms seem strong microbial ecosystems and minor water quality changes do not lead

to major detachment into the bulk phase, they are susceptible towards unwanted invasion of

coliforms.

4. Discussion

Water sources shape the biofilm community composition while drinking water

disinfection determines the biofilm density. Two biofilm monitors consisting of glass rings

were used to investigate drinking water biofilms. They were placed at two different drinking

water reservoirs, one received treated groundwater without disinfection step whereas the other

received treated surface water, with residual free chlorine. Using glass as a carrier material is a

reproducible way of sampling biofilms and it only considers the biofilm formation potential.

However, as glass does not leach nutrients, the biofilm density is lower compared to for

example on plastic coupons (27). In general, bacterial cell densities of biofilms vary from 10^4

$- 10^8$ cells/cm² (2, 3, 21). We observed similar concentrations, although a lower cell density

was observed for biofilms developed under surface water supply probably due to the use of a

free chlorine disinfectant (Table 2). Furthermore, our results were in line with previous studies

where ATP concentrations of 100 – 1100 pg/cm² and 10 – 100 pg ATP/cm² were measured for

unchlorinated and chlorinated water respectively (37, 77). Regarding the results of the CLSM

analysis, lower biomass content was observed for treated surface water biofilms but still around

1 µm³/µm² which was early reported in literature (5). In a study from Shen et al. (78) it was

shown that biofilm roughness is positively correlated with adhesion and negatively with

detachment. Here, a significantly higher biofilm roughness was measured for the surface water

biofilm, but this did not result in a higher biomass content probably due to the chlorine

treatment. Overall, the biofilm resulting from treated groundwater without chlorination had a

10 times higher FCM cell concentration, biofilm thickness, ATP and biomass content. Higher

cell and TOC concentrations in the bulk water and the fact that no disinfection was applied are

plausible explanations. Moreover, chlorination does not only lower biofilm density, but also

EPS contact points resulting in less EPS production, which was also observed in our study

(Figure 2, Table 2) (22).

16S rRNA sequencing showed a significant difference between treated groundwater and

surface water biofilms (Figure 1). The groundwater biofilm community was dominated by

Alphaproteobacteria, *Chloroflexi* and *Actinobacteriota*, whereas the surface water biofilm

mainly consists of *Alphaproteobacteria* and *Gemmatimonadota*. Within the *Chloroflexi*

phylum, the class JG30-KF-CM66 was most abundant, even though only small concentrations

were found in the bulk. The latter is similar to raw groundwater measurements reported in

literature (Figure 1, Figure A2) (79). Additionally, the members of the *Chloroflexi* and

Actinobacteriota clusters are known to degrade complex organic matter structures that could be

present in biofilms (80, 81). On the other hand, previous studies confirmed that the biofilm and

bulk   core   microbiome   of   treated   chlorinated   surface   water   mainly   consists   of

Alphaproteobacteria such as *Hyphomicrobiaceae* and *Sphingomonadaceae* (18, 25, 52, 82–84).

These taxa are both known to easily colonize surfaces, produce EPS and can degrade a wide

range of organic carbon compounds (18, 83, 85).

To conclude, treated groundwater and chlorinated treated surface water resulted in a

significantly different biofilm regarding cell density as well as community composition.

Previous studies already showed that source water is shaping the biofilm community

composition, which was also observed in this study (35, 40). Although, other researchers

showed that there is no difference in biofilm community regarding the drinking water source,

and that treatment (e.g. disinfection) is more important for the biofilm core community in

distribution pipes (86).

Mature biofilms react minimally towards operational water quality changes. During

drinking water distribution water quality remains mainly constant, however, minor operational

changes can happen which can in turn influence water microbiology (87). For example,

additional chlorination because of water works, changing quality of raw water sources, mixing

different water types in the DWDS, etc. (88, 89). Where previous studies are focused on the

influence of harsh operational changes such as flushing and shock chlorination, the goal of this work was to investigate the influences of these minor variations, that often happen in practice, on biofilm detachment.

Drinking water providers maintain fixed pH values and free chlorine dosage during treatment to control biofilm formation and corrosion of pipe materials, valves, pumps, etc. (15). To evaluate water corrosivity, the LSI, a qualitative index that predict the scale forming potential of water, is determined. The European as well as Belgian drinking water directives report to measure an LSI above -0.5 (14, 90). A slightly negative LSI means more aggressive water and a positive LSI indicates $CaCO_3$ supersaturated water that has the potential to form scale (75). In this study, the LSI of the tested waters was adapted by changing the pH (Table 1). Also, HOCl solution was added to have a free chlorine concentration of 0.20 mg/L and 0.28 mg/L, for the groundwater and surface water samples, respectively. In general, there was detachment towards the bulk water phase as the slopes of the regression models were higher than zero, but no significant biofilm detachment was observed between the blank waters and the adapted waters (Figure 3, Table A3). Besides, our drinking water setup, and distribution systems in general, were quite resilient (35). The pH was recovered after 4 hours and the free chlorine concentration was under the detection limit (< 0.05 mg Cl_2/L) after 2 hours of recirculation (data not shown). Similarly, the research of Trihn et al. (5) observed the role of biofilms in free chlorine decay.

However, the implementation of the results should be handled with care as only the short effect (i.e. 8 hours) of the operational changes was investigated. Continuous pH changes could alter the electrostatic interactions between materials and microorganisms as well as between microorganisms (8, 78). Former studies examined the long-term effect of chlorine on biofilms, and mentioned that small increases in chlorine concentrations could lead to a decrease in culturable biofilm bacteria and EPS production (42, 51). Furthermore, in our study, biofilms

were grown on glass rings, whereas in a full-scale distribution network aged biofilms on iron

or plastic piping materials are used, which are more susceptible towards corrosive water. For

example, biofilms attached to stainless steel compound pipes are more sensitive towards

flushing than those attached to ductile cast iron pipes (54).

Mature biofilms are susceptible towards the invasion of *Serratia fonticola*. Even

though mature biofilms seemed resilient ecosystems and were not susceptible to minor

operational quality changes, such as pH and chlorine, they were prone to invasion. In this study,

we spiked a GFP-labelled coliform, *Serratia fonticola* (i.e. ± 100 cells/100 mL) to the treated

groundwater and surface water samples. Water was recirculated over the biofilm monitor for 4

days and *Serratia fonticola* was followed using selective media. Our results showed that the

coliform was not able to survive in the bulk waters possibly because of the oligotrophic drinking

water environment or competition with the resident drinking water community (87, 91–93).

However, after 7 days, the coliform was detected in the biofilm samples (Figure 4, Table 3).

Since confocal microscopy is limited (e.g. operator dependent) and bleaching of the fluorescent

protein was observed, the results were confirmed using qPCR based on the detection of the

fluorescent gene, which was incorporated into the genome of the coliform. During the first spike

experiment, the gene copies were below the limit of quantification, but the second spike

experiment resulted in detection with qPCR (Table 3). This could be related to the sampling

day (after 7 days instead of 4 days), more favorable invasion circumstances or variability over

the glass rings in the biofilm monitor. Overall, adhesion and invasion onto a drinking water

biofilm depend on nutrient availability, surrounding microorganisms, local hydrodynamics and

biofilm roughness (78, 91).

Previous researchers already showed that biofilms could be a reservoir for pathogens (8,

10). Pathogens such as *Pseudomonas aeruginosa* were able to persist in drinking water biofilms

after spiking to bulk water samples (12). However, in comparison with the microbial drinking

water legislation, too high spike concentrations were used (i.e. 10^5-10^7 cells/mL) in former

studies, as the drinking water guidelines report a limit for *E. coli* and total coliform bacteria of

0/100 mL (12, 13, 15, 91). Here, in this study, we demonstrated that even low concentrations

of coliforms (± 100 cells/100 mL) can attach and get established in mature drinking water

biofilms. We explicitly chose to use low concentrations as they are relevant for the full-scale

practice, where the bigger volumes and flow rates in the DWDS might get contaminated by for

example groundwater intrusion after pipe burst, or rain-, river- or wastewater contamination

due to wrong connections (94, 95). Furthermore, it is important to notice that *Serratia fonticola*

was able to settle in two different biofilms regarding cell density and community composition

(Figure 1, Table 2). As biofilms can be disrupted by water stagnation, changes in water flow

rates and flushing after water works, coliforms could be released to the water phase, and this

could result in water contamination (49, 54, 89). Moreover, detached coliforms could settle

elsewhere in the DWDS. Despite, further research about biofilm detachment is needed to

understand the occurrence of contaminations in distribution networks.

4 Conclusion

In conclusion, we have used a biofilm monitor consisting of glass rings to study drinking

water biofilms. More specifically, we investigated the response of the biofilm microbiome

towards limited operational variations in pH and free chlorine concentration, and the ability of

the coliform, *Serratia fonticola*, to settle onto these biofilms. Two mature drinking water

biofilms were characterized using several techniques and it was shown that they were

significantly different from each other regarding cell density and community composition. To

summarize, the biofilm resulting from treated groundwater had a 10 times higher cell density,

biofilm thickness, ATP and biomass content than biofilm resulting from treated chlorinated

surface water. Next, it was observed that the biofilms remained resilient when applying limited

changes that are seen in the full-scale drinking water network. Finally, *Serratia fonticola*, spiked

at low concentrations to the bulk water samples, demonstrated the ability to attach and get

established within the mature biofilms, highlighting the potential for biofilms to act as

reservoirs for unwanted microorganisms in drinking water distribution systems.

Acknowledgements

We would like to thank all colleagues of Pidpa, De Watergroep and Farys who were involved in this project. Special acknowledgements go to thank Martine Cuypers (Pidpa), Katrien De Maeyer (Pidpa), Bart Van Calenberge (De Watergroep), Tom Vandermarliere (Farys), Benjamin Buysschaert (EKOPAK), Geert Van Nimmen (Farys) for installing and maintaining the biofilm monitors. Paul Bielen (Pidpa) and Tom Vandermarliere (Farys) for collecting the raw water quality measurements. We thank Katrien De Maeyer (Pidpa) for providing the coliform strain, Jan Roelof van der Meer (Until, Switzerland) for providing the donor and helper strains to label the coliform with a GFP and Jorien Favere (ORB, United Kingdom) for her help in performing the triparental mating experiments. We would like to thank Geert Meesen for his help on the confocal microscope and Tim Lacoere and Inez Roegiers for helping to perform and interpret the qPCR analysis and results. Finally, we would like to thank Jorien Favere and Josefien Van Landuyt to discuss the results of the experiments.

F.W. is supported by the Research Foundation—Flanders (FWO) (grant number 1S02022N) and contributes to the FWO-SBO Biostable project (grant number S006221N). C.G. is funded by the Research Foundation – Flanders (FWO) in the FWO-SBO Biostable project [grant number S006221N]. The work is part of the Ghent University-Aquaflanders Chair for Sustainable Drinking Water, which is supported by Aquaflanders, the federation of Flemish companies that are responsible for drinking water and sewer management (www.aquaflanders.be). F.W., C.G., B.D.G. and N.B. conceived the study. F.W. carried out the laboratory work, analyzed the data, interpreted the results and wrote the paper. C.G., B.D.G. and N.B. interpreted the results and supervised the findings of this work. All authors reviewed and approved the manuscript. The authors declare that there are no conflicts of interest.

Data availability statement

The datasets presented in this study can be found in online repositories. The names of the repository/repositories and accession number(s) can be found below: https://github.com/waegenaarfien/2023_Unwanted-coliforms-can-hide-in-mature-drinking-water-biofilms.git, https://www.ncbi.nlm.nih.gov/bioproject/PRJNA1015597.

463 **Supplemental material**

464 Supplemental material for this article may be found at ...

References

1. Liu G, Bakker GL, Li S, Vreeburg JHG, Verberk JQJC, Medema GJ, Liu WT, Van Dijk

JC. 2014. Pyrosequencing Reveals Bacterial Communities in Unchlorinated Drinking

Water Distribution System: An Integral Study of Bulk Water, Suspended Solids, Loose

Deposits, and Pipe Wall Biofilm. Environ Sci Technol 48:5467–5476.

2. Proctor CR, Hammes F. 2015. Drinking water microbiology — from measurement to

management. Current Opinion in Biotechnology 33:87–94.

3. Liu G, Zhang Y, Knibbe W-J, Feng C, Liu W, Medema G, van der Meer W. 2017.

Potential impacts of changing supply-water quality on drinking water distribution: A

review. Water Research 116:135–148.

4. Zhou X, Zhang K, Zhang T, Li C, Mao X. 2017. An ignored and potential source of taste

and odor (T&O) issues—biofilms in drinking water distribution system (DWDS). Appl

Microbiol Biotechnol 101:3537–3550.

5. Trinh QT, Bal Krishna KC, Salih A, Listowski A, Sathasivan A. 2020. Biofilm growth

on PVC and HDPE pipes impacts chlorine stability in the recycled water. Journal of

Environmental Chemical Engineering 8:104476.

6. Douterelo I, Sharpe R, Boxall J. 2014. Bacterial community dynamics during the early

stages of biofilm formation in a chlorinated experimental drinking water distribution

system: implications for drinking water discolouration. J Appl Microbiol 117:286–301.

7. Lemus Pérez MF, Rodríguez Susa M. 2017. Exopolymeric substances from drinking

water biofilms: Dynamics of production and relation with disinfection by products.

Water Research 116:304–315.

8.   Hemdan BA, El-Taweel GE, Goswami P, Pant D, Sevda S. 2021. The role of biofilm in

the development and dissemination of ubiquitous pathogens in drinking water

distribution systems: an overview of surveillance, outbreaks, and prevention. World J

Microbiol Biotechnol 37:36.

9.   Juhna T, Birzniece D, Larsson S, Zulenkovs D, Sharipo A, Azevedo NF, Ménard-

Szczebara F, Castagnet S, Féliers C, Keevil CW. 2007. Detection of Escherichia coli in

Biofilms from Pipe Samples and Coupons in Drinking Water Distribution Networks.

Applied and Environmental Microbiology 73:7456–7464.

10.   Wingender J, Flemming H-C. 2011. Biofilms in drinking water and their role as

reservoir for pathogens. International Journal of Hygiene and Environmental Health

214:417–423.

11.   Chen J, Li W, Zhang J, Qi W, Li Y, Chen S, Zhou W. 2020. Prevalence of antibiotic

resistance genes in drinking water and biofilms: The correlation with the microbial

community and opportunistic pathogens. Chemosphere 259:127483.

12.   Moritz MM, Flemming H-C, Wingender J. 2010. Integration of Pseudomonas

aeruginosa and Legionella pneumophila in drinking water biofilms grown on domestic

plumbing materials. Int J Hyg Environ Health 213:190–197.

13.   Lehtola MJ, Torvinen E, Kusnetsov J, Pitkänen T, Maunula L, von Bonsdorff C-H,

Martikainen PJ, Wilks SA, Keevil CW, Miettinen IT. 2007. Survival of Mycobacterium

avium, Legionella pneumophila, Escherichia coli, and Caliciviruses in Drinking Water-

Associated Biofilms Grown under High-Shear Turbulent Flow. Applied and

Environmental Microbiology 73:2854–2859.

14.   VMM. 2021. Kwaliteit van het drinkwater, 2021.

15. World Health Organization. 2022. Guidelines for drinking-water quality: fourth edition

incorporating the first and second addenda4th ed + 1st add + 2nd add. World Health

Organization, Geneva. https://apps.who.int/iris/handle/10665/352532. Retrieved 17 May

2022.

16. Waegenaar F, Baele A, De Maeyer K, De Gusseme B, Vervaeren H, Spanoghe P, Boon

N. 2023. Insects in water towers: Hibernating flies could compromise microbial drinking

water quality. Frontiers in Water 5.

17. Kilb B, Lange B, Schaule G, Flemming H-C, Wingender J. 2003. Contamination of

drinking water by coliforms from biofilms grown on rubber-coated valves. International

Journal of Hygiene and Environmental Health 206:563–573.

18. Zhang J, Li W, Chen J, Qi W, Wang F, Zhou Y. 2018. Impact of biofilm formation and

detachment on the transmission of bacterial antibiotic resistance in drinking water

distribution systems. Chemosphere 203:368–380.

19. Clayton GE, Thorn RMS, Reynolds DM. 2021. The efficacy of chlorine-based

disinfectants against planktonic and biofilm bacteria for decentralised point-of-use

drinking water. npj Clean Water 4:48.

20. Camper A, Burr M, Ellis B, Butterfield P, Abernathy C. 1998. Development and

structure of drinking water biofilms and techniques for their study. Journal of Applied

Microbiology 85:1S-12S.

21. Manuel CM, Nunes OC, Melo LF. 2007. Dynamics of drinking water biofilm in

flow/non-flow conditions. Water Research 41:551–562.

22.   Shen Y, Huang C, Monroy GL, Janjaroen D, Derlon N, Lin J, Espinosa-Marzal R,

Morgenroth E, Boppart SA, Ashbolt NJ, Liu W-T, Nguyen TH. 2016. Response of

Simulated Drinking Water Biofilm Mechanical and Structural Properties to Long-Term

Disinfectant Exposure. Environ Sci Technol 50:1779–1787.

23.   Mathieu L, Bertrand I, Abe Y, Angel E, Block JC, Skali-Lami S, Francius G. 2014.

Drinking water biofilm cohesiveness changes under chlorination or hydrodynamic stress.

Water Research 55:175–184.

24.   Pan R, Zhang K, Cen C, Zhou X, Xu J, Wu J, Wu X. 2021. Characteristics of biostability

of drinking water in aged pipes after water source switching: ATP evaluation, biofilms

niches and microbial community transition. Environmental Pollution 271:116293.

25.   Lee D, Calendo G, Kopec K, Henry R, Coutts S, McCarthy D, Murphy HM. 2021. The

Impact of Pipe Material on the Diversity of Microbial Communities in Drinking Water

Distribution Systems. Front Microbiol 12:779016.

26.   van der Kooij D, Veenendaal HR, Baars-Lorist C, van der Klift DW, Drost YC. 1995.

Biofilm formation on surfaces of glass and Teflon exposed to treated water. Water

Research 29:1655–1662.

27.   Ginige MP, Garbin S, Wylie J, Krishna KCB. 2017. Effectiveness of Devices to Monitor

Biofouling and Metals Deposition on Plumbing Materials Exposed to a Full-Scale

Drinking Water Distribution System. PLOS ONE 12:e0169140.

28.   Ginige MP, Wylie J, Plumb J. 2011. Influence of biofilms on iron and manganese

deposition in drinking water distribution systems. Biofouling 27:151–163.

29. Deines P, Sekar R, Husband PS, Boxall JB, Osborn AM, Biggs CA. 2010. A new

coupon design for simultaneous analysis of in situ microbial biofilm formation and

community structure in drinking water distribution systems. Appl Microbiol Biotechnol

87:749–756.

30. Douterelo I, Jackson M, Solomon C, Boxall J. 2016. Microbial analysis of in situ biofilm

formation in drinking water distribution systems: implications for monitoring and

control of drinking water quality. Appl Microbiol Biotechnol 100:3301–3311.

31. E. Fish K, Mark Osborn A, Boxall J. 2016. Characterising and understanding the impact

of microbial biofilms and the extracellular polymeric substance (EPS) matrix in drinking

water distribution systems. Environmental Science: Water Research & Technology

2:614–630.

32. Flemming H-C. 2016. EPS—Then and Now. 4. Microorganisms 4:41.

33. Shaw JLA, Monis P, Weyrich LS, Sawade E, Drikas M, Cooper AJ. 2015. Using

Amplicon Sequencing To Characterize and Monitor Bacterial Diversity in Drinking

Water Distribution Systems. Applied and Environmental Microbiology 81:6463–6473.

34. Ren H, Wang W, Liu Y, Liu S, Lou L, Cheng D, He X, Zhou X, Qiu S, Fu L, Liu J, Hu

B. 2015. Pyrosequencing analysis of bacterial communities in biofilms from different

pipe materials in a city drinking water distribution system of East China. Appl Microbiol

Biotechnol 99:10713–10724.

35. Henne K, Kahlisch L, Brettar I, Höfle MG. 2012. Analysis of Structure and Composition

of Bacterial Core Communities in Mature Drinking Water Biofilms and Bulk Water of a

Citywide Network in Germany. Applied and Environmental Microbiology 78:3530–

3538.

36. Rosales E, Del Olmo G, Calero Preciado C, Douterelo I. 2020. Phosphate Dosing in

Drinking Water Distribution Systems Promotes Changes in Biofilm Structure and

Functional Genetic Diversity. Front Microbiol 11:599091.

37. Ahmad JI, Dignum M, Liu G, Medema G, van der Hoek JP. 2021. Changes in biofilm

composition and microbial water quality in drinking water distribution systems by

temperature increase induced through thermal energy recovery. Environmental Research

194:110648.

38. Kitajima M, Cruz MC, Williams RBH, Wuertz S, Whittle AJ. 2021. Microbial

abundance and community composition in biofilms on in-pipe sensors in a drinking

water distribution system. Science of The Total Environment 766:142314.

39. Martiny AC, Jørgensen TM, Albrechtsen H-J, Arvin E, Molin S. 2003. Long-Term

Succession of Structure and Diversity of a Biofilm Formed in a Model Drinking Water

Distribution System. Applied and Environmental Microbiology 69:6899–6907.

40. Douterelo I, Jackson M, Solomon C, Boxall J. 2017. Spatial and temporal analogies in

microbial communities in natural drinking water biofilms. Science of The Total

Environment 581–582:277–288.

41. Flemming H-C, Wingender J. 2010. The biofilm matrix. Nat Rev Microbiol 8:623–633.

42. Lin H, Zhu X, Wang Y, Yu X. 2017. Effect of sodium hypochlorite on typical biofilms

formed in drinking water distribution systems. Journal of Water and Health 15:218–227.

43. Schwering M, Song J, Louie M, Turner RJ, Ceri H. 2013. Multi-species biofilms defined

from drinking water microorganisms provide increased protection against chlorine

disinfection. Biofouling 29:917–928.

44.   Hu Y, Dong D, Wan K, Chen C, Yu X, Lin H. 2020. Potential shift of bacterial

community structure and corrosion-related bacteria in drinking water distribution

pipeline driven by water source switching. Front Environ Sci Eng 15:28.

45.   Li W, Wang F, Zhang J, Qiao Y, Xu C, Liu Y, Qian L, Li W, Dong B. 2016. Community

shift of biofilms developed in a full-scale drinking water distribution system switching

from different water sources. Science of The Total Environment 544:499–506.

46.   Zhang K, Wu X, Zhang T, Cen C, Mao R, Pan R. 2022. Pilot investigation on

biostability of drinking water distribution systems under water source switching. Appl

Microbiol Biotechnol 106:5273–5286.

47.   Pick FC, Fish KE, Boxall JB. 2021. Assimilable organic carbon cycling within drinking

water distribution systems. Water Research 198:117147.

48.   Zlatanović Lj, van der Hoek JP, Vreeburg JHG. 2017. An experimental study on the

influence of water stagnation and temperature change on water quality in a full-scale

domestic drinking water system. Water Research 123:761–772.

49.   Manuel CM, Nunes OC, Melo LF. 2009. Unsteady state flow and stagnation in

distribution systems affect the biological stability of drinking water. Biofouling 26:129–

139.

50.   Calero Preciado C, Boxall J, Soria-Carrasco V, Martínez S, Douterelo I. 2021.

Implications of Climate Change: How Does Increased Water Temperature Influence

Biofilm and Water Quality of Chlorinated Drinking Water Distribution Systems?

Frontiers in Microbiology 12.

51.   Tsvetanova Z. 2019. Quantification of the bacterial community of drinking water-

620   associated biofilms under different flow velocities and changing chlorination regimes.

621   Appl Water Sci 10:3.

622   52.   Zhu Z, Wu C, Zhong D, Yuan Y, Shan L, Zhang J. 2014. Effects of Pipe Materials on

623   Chlorine-resistant Biofilm Formation Under Long-term High Chlorine Level. Appl

624   Biochem Biotechnol 173:1564–1578.

625   53.   Fish KE, Sharpe RL, Biggs CA, Boxall JB. 2022. Impacts of temperature and hydraulic

626   regime on discolouration and biofilm fouling in drinking water distribution systems.

627   PLOS Water 1:e0000033.

628   54.   Liu J, Luo Z, Liu K, Zhang Y, Peng H, Hu B, Ren H, Zhou X, Qiu S, He X, Ye P,

629   Bastani H, Lou L. 2017. Effect of flushing on the detachment of biofilms attached to the

630   walls of metal pipes in water distribution systems. J Zhejiang Univ Sci A 18:313–328.

631   55.   emis V. 2020. Compendium voor de monsterneming, meting en analyse van water.

632   56.   emis V. 2023. Berekening van de saturatie-index.

633   57.   emis V. 2023. Bepaling van de alkaliniteit en de buffercapaciteit.

634   58.   Kerckhof F-M, Sakarika M, Van Giel M, Muys M, Vermeir P, De Vrieze J, Vlaeminck

635   SE, Rabaey K, Boon N. 2021. From Biogas and Hydrogen to Microbial Protein Through

636   Co-Cultivation of Methane and Hydrogen Oxidizing Bacteria. Frontiers in

637   Bioengineering and Biotechnology 9.

59.   2008. NCBI BLAST: a better web interface. Nucleic Acids Research 36:5–9.

60.   Montelongo-Jauregui D, Srinivasan A, Ramasubramanian A, Lopez-Ribot J. 2018. An In
Vitro Model for Candida albicans–Streptococcus gordonii Biofilms on Titanium
Surfaces. JoF 4:66.

61.   Heydorn A, Nielsen AT, Hentzer M, Sternberg C, Givskov M, Ersbøll BK, Molin S.
2000. Quantification of biofilm structures by the novel computer program comstat.
Microbiology 146:2395–2407.

62.   Van Landuyt J, Kundu K, Van Haelst S, Neyts M, Parmentier K, De Rijcke M, Boon N.
2022. 80 years later: Marine sediments still influenced by an old war ship. Frontiers in
Marine Science 9.

63.   R Core Team. 2022. R: A Language and Environment for Statistical Computing. R
Foundation for Statistical Computing, Vienna, Austria. https://www.R-project.org/.

64.   RStudio Team. 2020. RStudio: Integrated Development Environment for R. RStudio,
PBC., Boston, MA. http://www.rstudio.com/.

65.   Ellis B, Haaland P, Hahne F, Meur NL, Gopalakrishnan N, Spidlen J, Jiang M, Finak G.
2022. flowCore: flowCore: Basic structures for flow cytometry data.

66.   Props R, Monsieurs P, Mysara M, Clement L, Boon N. 2016. Measuring the biodiversity
of microbial communities by flow cytometry. Methods in Ecology and Evolution
7:1376–1385.

67.   Dragulescu A, Arendt C. 2020. xlsx: Read, Write, Format Excel 2007 and Excel
97/2000/XP/2003 Files. https://CRAN.R-project.org/package=xlsx.

68.   Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJA, Holmes SP. 2016.

DADA2: High-resolution sample inference from Illumina amplicon data. 7. Nat

Methods 13:581–583.

69.   Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glöckner FO.

2013. The SILVA ribosomal RNA gene database project: improved data processing and

web-based tools. Nucleic Acids Res 41:D590-596.

70.   McMurdie PJ, Holmes S. 2013. phyloseq: An R package for reproducible interactive

analysis and graphics of microbiome census data. PLoS ONE 8:e61217.

71.   Oksanen J, Simpson GL, Blanchet FG, Kindt R, Legendre P, Minchin PR, O'Hara RB,

Solymos P, Stevens MHH, Szoecs E, Wagner H, Barbour M, Bedward M, Bolker B,

Borcard D, Carvalho G, Chirico M, Caceres MD, Durand S, Evangelista HBA, FitzJohn

R, Friendly M, Furneaux B, Hannigan G, Hill MO, Lahti L, McGlinn D, Ouellette M-H,

Cunha ER, Smith T, Stier A, Braak CJFT, Weedon J. 2022. vegan: Community Ecology

Package. https://CRAN.R-project.org/package=vegan.

72.   Kassambara A. 2020. ggpubr: "ggplot2" Based Publication Ready Plots.

https://CRAN.R-project.org/package=ggpubr.

73.   Wickham H. 2016. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New

York. https://ggplot2.tidyverse.org.

74.   Wickham H, François R, Henry L, Müller K. 2022. dplyr: A Grammar of Data

Manipulation. https://CRAN.R-project.org/package=dplyr.

75. Chien CC, Kao CM, Chen CW, Dong CD, Chien HY. 2009. Evaluation of biological

stability and corrosion potential in drinking water distribution systems: a case study.

Environ Monit Assess 153:127–138.

76. Langelier WF. 1936. The Analytical Control of Anti-Corrosion Water Treatment.

Journal AWWA 28:1500–1521.

77. Inkinen J, Kaunisto T, Pursiainen A, Miettinen IT, Kusnetsov J, Riihinen K, Keinänen-

Toivola MM. 2014. Drinking water quality and formation of biofilms in an office

building during its first year of operation, a full scale study. Water Research 49:83–91.

78. Shen Y, Monroy GL, Derlon N, Janjaroen D, Huang C, Morgenroth E, Boppart SA,

Ashbolt NJ, Liu W-T, Nguyen TH. 2015. Role of Biofilm Roughness and

Hydrodynamic Conditions in Legionella pneumophila Adhesion to and Detachment

from Simulated Drinking Water Biofilms. Environ Sci Technol 49:4274–4282.

79. Yan L, Herrmann M, Kampe B, Lehmann R, Totsche KU, Küsel K. 2020.

Environmental selection shapes the formation of near-surface groundwater microbiomes.

Water Research 170:115341.

80. Wu J, Wang L, Du J, Liu Y, Hu L, Wei H, Fang J, Liu R. 2023. Biogeographic

distribution, ecotype partitioning and controlling factors of Chloroflexi in the sediments

of six hadal trenches of the Pacific Ocean. Science of The Total Environment

880:163323.

81. Suominen S, van Vliet DM, Sánchez-Andrea I, van der Meer MTJ, Sinninghe Damsté

JS, Villanueva L. 2021. Organic Matter Type Defines the Composition of Active

Microbial Communities Originating From Anoxic Baltic Sea Sediments. Frontiers in

Microbiology 12.

82.   Chan S, Pullerits K, Keucken A, Persson KM, Paul CJ, Rådström P. 2019. Bacterial

release from pipe biofilm in a full-scale drinking water distribution system. 1. npj

Biofilms Microbiomes 5:1–8.

83.   Williams M m., Domingo J w. s., Meckes M c., Kelty C a., Rochon H s. 2004.

Phylogenetic diversity of drinking water bacteria in a distribution system simulator.

Journal of Applied Microbiology 96:954–964.

84.   Douterelo I, Husband S, Loza V, Boxall J. 2016. Dynamics of Biofilm Regrowth in

Drinking Water Distribution Systems. Applied and Environmental Microbiology

82:4155–4168.

85.   Vaz-Moreira I, Nunes OC, Manaia CM. 2011. Diversity and antibiotic resistance

patterns of Sphingomonadaceae isolates from drinking water. Appl Environ Microbiol

77:5697–5706.

86.   Learbuch KLG, Smidt H, van der Wielen PWJJ. 2022. Water and biofilm in drinking

water distribution systems in the Netherlands. Sci Total Environ 831:154940.

87.   Favere J, Barbosa RG, Sleutels T, Verstraete W, De Gusseme B, Boon N. 2021.

Safeguarding the microbial water quality from source to tap. 1. npj Clean Water 4:1–6.

88.   Favere J, Buysschaert B, Boon N, De Gusseme B. 2020. Online microbial fingerprinting

for quality management of drinking water: Full-scale event detection. Water Research

170:115353.

89.   Van Nevel S, Buysschaert B, De Roy K, De Gusseme B, Clement L, Boon N. 2017.

Flow cytometry for immediate follow-up of drinking water networks after maintenance.

Water Research 111:66–73.

90. European Union. 2020. RICHTLIJN (EU) 2020/2184 VAN HET EUROPEES

PARLEMENT EN DE RAAD. 2184.

91. Van Nevel S, De Roy K, Boon N. 2013. Bacterial invasion potential in water is

determined by nutrient availability and the indigenous community. FEMS Microbiol

Ecol 85:593–603.

92. van Bel N, van der Wielen P, Wullings B, van Rijn J, van der Mark E, Ketelaars H,

Hijnen W. 2021. Aeromonas Species from Nonchlorinated Distribution Systems and

Their Competitive Planktonic Growth in Drinking Water. Applied and Environmental

Microbiology 87:e02867-20.

93. Vital M, Hammes F, Egli T. 2012. Competition of Escherichia coli O157 with a drinking

water bacterial community at low nutrient concentrations. Water Research 46:6279–

6290.

94. Waegenaar F, Favere J, Boon N, De Gusseme B. 2021. Online microbial monitoring of

drinking water: How do different techniques respond to contaminations in practice?

Water Research 202:117387.

95. Braeye T, Schrijver KD, Wollants E, Ranst M van, Verhaegen J. 2015. A large

community outbreak of gastroenteritis associated with consumption of drinking water

contaminated by river water, Belgium, 2010. Epidemiology & Infection 143:711–719.

Figure 1: Relative abundances of the 20 most abundant families from the treated groundwater (not disinfected) **(A)** and treated surface water (chlorinated) **(B)** biofilm. Biofilm samples (n = 2) were taken after 11 and 17 months. Significant differences were observed between both biofilms at each timepoint (ANOSIM, p < 0.05).

Figure 2: Confocal microscopy images of the treated groundwater (top images) and treated surface water (bottom images) biofilms. Biofilm cells were stained using DAPI and the EPS content, more specifically

the protein and sugar content were stained with Sypro Ruby and Concanavalin A, respectively. Samples were analyzed after 17 months and the images were processed using ImageJ.

Figure 3: Average cell density of the bulk water phase (n = 3) in function of time (hours) for each water type. The reference detachment profile is indicated with blue, the water cell density after applying different water quality changes (free chlorine, pH) is indicated with green. A linear regression model was calculated (95% confidence interval) and the corresponding slopes and R^2 is shown in a black box.

Figure 4: Confocal microscopy images of the invasion experiment with *Serratia fonticola* for the treated surface water biofilm. From left to right: biofilms stained with DAPI, the GFP-labelled coliforms, an overlay image.

Table 1: Original pH and corresponding Langelier Saturation Index (LSI) for each water type. To evaluate biofilm detachment, the LSI was changed by decreasing or increasing the pH using HCl and NaOH, respectively.

Water type	Original pH	Original LSI	pH adapted	LSI	pH adapted	LSI
Treated groundwater (no disinfection)	7.10	-0.04	6.84	-0.52	7.58	0.25
Treated surface water (chlorination)	7.75	0.10	7.30	-0.55	7.90	0.31

Table 2: Characterization of the biofilms using different techniques after 11 and 17 months. Statistics are done using the Wilcoxon rank sum test or the t test indicated with a '*'. Biofilms resulting from treated groundwater were more dens and active than biofilms resulting treated chlorinated surface water.

Technique	Parameter	After 11 months		P value	After 17 months		P value
	Water type	**Treated groundwater (no disinfection)**	**Treated surface water (chlorinated)**		**Treated groundwater (no disinfection)**	**Treated surface water (chlorinated)**	
Flow cytometry	**Total cell density (cells/cm²)**	$(1,01 \pm 0,04) \times 10^7$	$(5,96 \pm 1,01) \times 10^5$	4.11×10^{-5}	$(7,46 \pm 0,58) \times 10^6$	$(5,23 \pm 3,68) \times 10^5$	4.11×10^{-5}
ATP analysis	**ATP content (pg/cm²)**	$411,34 \pm 52,58$	$51,86 \pm 3,22$	8.23×10^{-5}	$896,54 \pm 72,11$	$77,26 \pm 41,48$	4.04×10^{-4}
CLSM	**Roughness (Ra)**	$1,25 \pm 0,39$	$1,97 \pm 0,03$	0.06	$0,78 \pm 0,14$	$1,68 \pm 0,04$	3.97×10^{-5}
CLSM	**Average thickness (µm)**	$15,78 \pm 5,89$	$0,94 \pm 0,57$	0.06	$4,95 \pm 2,62$	$1,31 \pm 0,33$	7.18×10^{-3}
CLSM	**Biomass (µm³/µm²)**	$5,65 \pm 2,23$	$0,57 \pm 0,45$	$0.08*$	$4,10 \pm 3,07$	$0,25 \pm 0,10$	1.59×10^{-4}
CLSM EPS	**Protein biovolume (µm³/µm²)**	Not determined	Not determined	/	1.23 ± 1.09	0.13 ± 0.07	3.97×10^{-5}
CLSM EPS	**Sugar biovolume (µm³/µm²)**	Not determined	Not determined	/	2.73 ± 2.54	0.29 ± 0.25	7.94×10^{-5}

Table 3: Serratia fonticola was spiked in the bulk water phase and followed with selective plating (CCA). Invasion of the coliform in the biofilm was determined using CLSM and qPCR. Positive detection on the respective day after the spike (Dx) with CLSM is indicated with "check". It was not possible to perform CLSM for the groundwater biofilms of the second spike experiment because of calcium precipitation on the rings. Using qPCR, the GFP-labelled coliform was found in the biofilm after 7 days (D7).

	Bulk			Biofilm	
Technique	**Coliform Chromogenic Agar (CCA)**			**CLSM**	**qPCR**
Water type	Start concentration (cells/100 mL)	After 3 hours (cells/100 mL)	After 24 hours (cells/100 mL)	/	(Gene copies/cm²)
Treated groundwater (no disinfection)	104.0 ± 10.6	0	0	D8: check	D4: under LOQ
Treated groundwater (no disinfection)	15.3 ± 3.0	0	0	D7: not possible	D7: 578.59 ± 38.45
Treated surface water (chlorinated)	650.0 ± 14.1	420.0 ± 17.0	0	D8: check*	D4: under LOQ
Treated surface water (chlorinated)	39.5 ± 5.0	1.0 ± 1.4	0	D7: check	D7: 358.36 ± 24.03