Sequence analysis

BAllC and BAllCools: Efficient Formatting and Operating for Single-Cell DNA Methylation Data

Wei Tian[1], Wubin Ding[1], Jiawei Shen[2], Daofeng Li[2], Ting Wang[2,3] and Joseph R. Ecker[1,4,*]

[1]Genomic Analysis Laboratory, The Salk Institute for Biological Studies, La Jolla, CA 92037, USA,

[2]Department of Genetics, The Edison Family Center for Genome Sciences & Systems Biology, Washington University School of Medicine, St. Louis, MO 63110, USA,

[3]McDonnell Genome Institute, Washington University School of Medicine, St. Louis, MO 63108, USA

[4]Howard Hughes Medical Institute, The Salk Institute for Biological Studies, La Jolla, CA 92037, USA.

*To whom correspondence should be addressed.

Abstract

Motivation: With single-cell DNA methylation studies yielding vast datasets, existing data formats struggle with the unique challenges of storage and efficient operations, highlighting a need for improved solutions.
Results: BAllC (Binary All Cytosines) emerges as a tailored binary format for methylation data, addressing these challenges. BAllCools, its complementary software toolkit, enhances parsing, indexing, and querying capabilities, promising superior operational speeds and reduced storage needs.
Availability: https://github.com/jksr/ballcools
Contact: ecker@salk.edu
Supplementary information: Supplementary data are available at Bioinformatics online.

1 Introduction

The advent of single-cell DNA methylation (scDNAm) research has significantly enhanced our grasp of epigenetic intricacies, bringing to light the heterogeneities existing across individual cells – heterogeneities that are often masked in bulk assays (Luo *et al.*, 2017; Liu *et al.*, 2021; Tian *et al.*, 2023). However, the granularity and scope of such investigations yield immense datasets, often spanning tens to hundreds of terabytes, presenting storage and processing challenges. For instance, Neuroscience Multi-Omic Data Archive (NeMO Archive), a prominent omic database for brain science, harbors over four hundred terabytes of scDNAm data, occupying more than half of its total storage capacity (as of Mar 22, 2024). Moreover, it has been revealed that >40% of the storage space in the NCBI Gene Expression Omnibus (GEO) is allocated to scDNAm data (private conversations). Such substantial storage demands for scDNAm data have become significant technical obstacles and financial burdens for both researchers and databanks. While various specialized formats have been developed for DNA methylation profiling (Argelaguet *et al.*, 2019; Li *et al.*, 2021; Ding *et al.*, 2022; Loyfer *et al.*, 2023), many fail to adequately address the distinct sparsity of scDNAm, encompass both CpG and non-CpG methylation contexts, or achieve the optimal operational speed and storage efficiency. Recognizing the pressing need for a more efficient alternative, we embarked on the development of BAllC (Binary All Cytosines), a tailored binary format

for single-cell DNA methylation data. Accompanied by its software toolkit, BAllCools, this system aims to counter the limitations of existing formats, offering researchers a streamlined approach for the next era of epigenetic exploration.

2 Methods

2.1 The BAllC format

The BAllC format comprises a header and a methylation record section (Figure 1). The header identifies the BAllC version, provides genome reference information, and accommodates user notes. The methylation record section contains genome coordinates and both methylated and total counts for each cytosine. To leverage the inherent bound for non-duplicated counts of individual cytosines in single-cell as well as accommodating the frequent need to merge single-cell data to pseudo-bulk levels, the BAllC format employs different data types for single-cell and bulk files (uint8 and uint16, respectively; Figure 1). This strategy optimizes storage efficiency while maintaining data integrity. A supplementary TAB-delimited CMeta file is used to store the positions and contexts of each cytosine in the genome (Table S1). Only one CMeta file is required for multiple BAllC files sharing the same genome reference, minimizing data redundancy. Both BAllC and CMeta files

employ the blocked compressed format (BGZF (Bonfield *et al.*, 2021)) and can be indexed for rapid data retrieval.

2.2 BAllCools software package

BAllCools is a C/C++ software package designed for operations on BAllC files. It supports format conversion between BAllC and the AllC text-based format (Schultz *et al.*, 2015), provides indexing and querying capabilities for BAllC files, and offers efficient methylation information retrieval based on user-defined genome range(s), strandness, or cytosine context. Notably, BAllCools can merge multiple BAllC files rapidly, facilitating analysis of methylomes at cluster or cell-type levels. Additionally, Python and Javascript wrappers are also available to enhance flexibility in utilizing the BAllC format.

Field			Description	Type	Value
header					
	magic		magic string	char[6]	"BALLC\1"
	version		format major version	uint8_t	e.g. "0"
	version_minor		format minor version	uint8_t	e.g. "1"
	sc		flag of single cell	uint8_t	"0" or "1"
	l_assembly		length of assembly text	uint32_t	
	assembly_text		user specified assembly info	char[l_assembly]	e.g. "mm10", "hg38", "donor1"
	l_text		length of header text	uint32_t	
	header_text		note for this BAllC file	char[l_text]	
	n_refs		number of references (chroms)	uint16_t	
	refs		list of refs (n=n_refs)		
		ref			
		l_name	length of reference name	uint32_t	
		ref_name	reference name	char[l_name]	e.g. "chr1"
		ref_len	length of reference	uint32_t	e.g. "248956422"
mc_records			list of mc_records		
	mc_record				
	pos		position of cytosine	uint32_t	
	ref_id		reference id, 0 ≤ref_id < n_refs	uint16_t	
	mc		number of counts supporting methylation call	uint16_t when sc=0, uint8_t when sc=1	
	cov		number of counts covering the position	uint16_t when sc=0, uint8_t when sc=1	

Figure 1. Specification of the BAllC format.

3 Results

We evaluated the efficiency of BAllC/BAllCools using large public single-cell DNA methylation datasets (Liu *et al.*, 2021; Tian *et al.*, 2023) and benchmarked them against the text-based AllC format (Schultz *et al.*, 2015) and the associated toolkit AllCools (Liu *et al.*, 2021), both of which are extensively used in studies of single cell DNA methylation.

3.1 Storage efficiency

Due to its binary nature and minimized redundancy, the BAllC format significantly optimizes storage in comparison to text-based formats. Specifically, the BAllC format achieved a >94% reduction in storage compared to the uncompressed text-based format. When compared to the compressed text-based format (BGZF format), the bulk mode BAllC format achieved approximately 50.4% reduction in storage, while the single-cell BAllC mode format achieved about 55.2% reduction.

3.2 Operational speed

Merging multiple single-cell methylomes into pseudo-bulk level is one of the most frequent operations in processing scDNAm datasets, permitting further analyses like differential methylation calling and visualization on genome browsers. Merging with BAllCools drastically cuts down the time required in comparison to text-based alternatives (Figure S1). For instance, merging a typical set of 500 scDNAm data takes only about 1.8 hours using one CPU core (2.80GHz), resulting in over 47x time savings compared to the text-based alternative.

3.3 Flexible data query and visualization

BAllCools extends its functionality beyond mere retrieval of DNA methylation records for specific genome coordinates. It offers users the capability to refine their queries by considering strandness and cytosine context. Users can retrieve methylation statuses of only CpG sites or cytosines within contexts of particular interest (Figure S2). These flexibilities are often unattainable with the text-based format and its associated tools. BAllCools also facilitates various operations on the queried regions, including aggregation of methylated and unmethylated

counts, cytosine count tallying, and average methylation level calculations. These operations furnish essential metrics at the genome region level. The BAllC format file can also be visualized in the WashU Epigenome Browser (Li *et al.*, 2019) for checking methylation status (Supplementary Data).

4 Conclusions

The increasing volume of single-cell DNA methylation data provides valuable resources for understanding gene regulation and heterogeneity. Despite the availability of various well-established and effective analysis tools such as DSS, methylKit, MethPipe, AllCools, Methylpy, etc. (Feng *et al.*, 2014; Akalin *et al.*, 2012; Song *et al.*, 2013; Liu *et al.*, 2021; Schultz *et al.*, 2015), the challenge of storage remains unaddressed. In response to this challenge, we introduce the BAllC format as an efficient storage solution for scDNAm data. This binary format, in conjunction with the efficient toolkit BAllCools, represents a significant advancement in handling scDNAm datasets, ensuring optimal performance in terms of storage, speed, and data retrieval.

Acknowledgements

We thank Jingtian Zhou for assistance in testing and for suggestive comments. We are very grateful to members of the Ecker group for their feedback and discussion.

Funding

This work was supported by grants from NIMH U19MH11483, U01MH121282 and UM1MH130994 to J.R.E.

Conflict of Interest: J.R.E is a member of the scientific advisor for Zymo Research In. and Ionis Pharmaceuticals.

References

Akalin,A. *et al.* (2012) methylKit: a comprehensive R package for the analysis of genome-wide DNA methylation profiles. *Genome Biol.*, **13**, R87.

Argelaguet,R. *et al.* (2019) Multi-omics profiling of mouse gastrulation at single-cell resolution. *Nature*, **576**, 487–491.

Bonfield,J.K. *et al.* (2021) HTSlib: C library for reading/writing high-throughput sequencing data. *Gigascience*, **10**.

Ding,Y. *et al.* (2022) mHapTk: a comprehensive toolkit for the analysis of DNA methylation haplotypes. *Bioinformatics*, **38**, 5141–5143.

Feng,H. *et al.* (2014) A Bayesian hierarchical model to detect differentially methylated loci from single nucleotide resolution sequencing data. *Nucleic Acids Res.*, **42**, e69.

Li,D. *et al.* (2019) WashU Epigenome Browser update 2019. *Nucleic Acids Res.*, **47**, W158–W165.

Li,L. *et al.* (2021) Dissecting the epigenomic dynamics of human fetal germ cell development at single-cell resolution. *Cell Res.*, **31**, 463–477.

Liu,H. *et al.* (2021) DNA methylation atlas of the mouse brain at single-cell resolution. *Nature*, **598**, 120–128.

Loyfer,N. *et al.* (2023) A DNA methylation atlas of normal human cell types. *Nature*, **613**, 355–364.

Luo,C. *et al.* (2017) Single-cell methylomes identify neuronal subtypes and regulatory elements in mammalian cortex. *Science*, **357**, 600–604.

Schultz,M.D. *et al.* (2015) Human body epigenome maps reveal noncanonical DNA methylation variation. *Nature*, **523**, 212–216.

Song,Q. *et al.* (2013) A reference methylome database and analysis pipeline to facilitate integrative and comparative epigenomics. *PLoS One*, **8**, e81148.

Tian,W. *et al.* (2023) Single-cell DNA methylation and 3D genome architecture in the human brain. *Science*, **382**, eadf5357.