Ensembled best subset selection using summary statistics for polygenic risk prediction

Tony Chen[1], Haoyu Zhang[1,2*], Rahul Mazumder[3*], Xihong Lin[1,4*]

[1] Department of Biostatistics, Harvard T.H. Chan School of Public Health, Boston, MA, USA

[2] Division of Cancer Epidemiology and Genetics, National Cancer Institute, Bethesda, MD, USA

[3] Operations Research and Statistics Group, MIT Sloan School of Management, Cambridge, MA, USA

[4] Department of Statistics, Harvard University, Cambridge, MA, USA

[*] These authors jointly supervised this work

Abstract

Polygenic risk scores (PRS) enhance population risk stratification and advance

personalized medicine, yet existing methods face a tradeoff between predictive power

and computational efficiency. We introduce ALL-Sum, an easy-to-implement PRS

method that combines an efficient summary statistic-based L_0L_2 penalized regression

algorithm with an ensembling step that aggregates estimates from different tuning

parameters for improved prediction performance. In extensive large-scale simulations

across a wide range of polygenicity and genome-wide association studies (GWAS)

sample sizes, ALL-Sum consistently outperforms popular alternative methods in terms

of prediction accuracy, runtime, and memory usage. We analyze 27 published GWAS

summary statistics for 11 complex traits from 9 reputable data sources, including the

Global Lipids Genetics Consortium, Breast Cancer Association Consortium, and

FinnGen, evaluated using individual-level UKBB data. ALL-Sum achieves the highest

accuracy for most traits, particularly for GWAS with large sample sizes. We provide

ALL-Sum as a user-friendly command-line software with pre-computed reference data

for streamlined user-end analysis.

Keywords: polygenic risk scores, penalized regression, L0Learn, ensemble learning

Main

Polygenic risk scores (PRS) have emerged as an attractive method for improving risk stratification across a diverse range of traits from cancers to psychiatric disorders[1–6]. PRS can enhance patient risk profiling, refine diagnoses, inform treatment plans, and ultimately improve health outcomes[7–9]. Consequently, PRS has garnered significant interest in both research and clinical practice.

Several methods have been developed to construct PRS based on summary statistics from genome-wide association studies (GWAS). Clumping and thresholding (C+T)-based methods[10,11], which are fast and widely used, identify a subset of single nucleotide polymorphisms (SNPs) passing thresholds for linkage disequilibrium (LD) and GWAS p-values. However, this filtering process may remove potentially predictive SNPs and ultimately hurt prediction accuracy[12]. Bayesian methods[13–18] offer intuitive priors to model joints SNP effects and generally strong prediction performance, but their computation is often expensive and sometimes may not even converge, particularly when dealing with large and complex data[18]. Penalized regression-based methods[19,20] have more efficient optimization algorithms to model joint SNP effects. However, popular penalties such as Lasso can select many false positives under strong correlation[15], which may lead to reduced prediction accuracy due to complex LD patterns across the genome[21,22].

In general, these methods require a grid of tuning parameters and identify the best combination for a particular application. While this is a simple way to build a prediction model, it is best suited when one only needs to search through a relatively small tuning parameter space. In high-dimensional problems such as PRS which

involve a large number of SNPs, the best tuning parameters may be in the gaps or

outside the bounds of the fixed grid being considered[23]. Recent works, in both theory

and PRS applications, have demonstrated that ensembling multiple predictors can yield

better prediction accuracy than choosing a single best predictor from grid search[24–30].

In this paper, we propose ALL-Sum (Aggregated L0Learn using Summary-level

data), a fast and scalable method of constructing PRS from publicly-accessible GWAS

summary statistics and LD reference. ALL-Sum has two key components. First, we use

a L_0L_2-penalized regression framework, based on the recently developed L0Learn

method[31–33], that only requires GWAS and LD summary-level data. L0Learn has been

shown to better handle complex correlation structures and improve prediction accuracy

over methods like Lasso and Bayesian spike-and-slab[32,33]. This offers an attractive

penalized approach to model sparse joint effects of SNPs in LD and improve PRS

accuracy over methods such as Lassosum2 and LDPred2.

However, a key limitation is that L0Learn requires access to individual-level data,

which cannot be easily analyzed in large scale and is often not publicly available. Thus,

we modify the optimization problem to only require summary-level data and implement a

fast coordinate descent optimization to efficiently provide candidate PRS estimates from

a large grid of tuning parameters. Then, in an ensembling step, we use Lasso to

estimate weights for each of PRS estimate from different combinations of L_0 and L_2

tuning parameters in order to construct a final aggregated PRS. While ensembling

typically comes at the practical cost of a dense solution with more SNPs in the final

prediction model, it ensures higher prediction accuracy compared to the grid search

solution.

We compare ALL-Sum's performance with four alternative methods – Clumping

and Thresholding (C+T)[10,11], LDPred2[14], Lassosum2[20], and Stacked C+T[29]. Variants of

these methods have been commonly used in practice[3,34–38], and we take them to be

representative of the broad classes of methods previously discussed. We first evaluate

the five methods in large-scale analyses of simulated GWAS data based on European

ancestry. Additionally, we construct PRS using 27 published GWAS summary statistics

for 11 complex traits from 9 reputable data sources, such as the Breast Cancer

Association Consortium[4], Global Lipids Genetics Consortium[3], FinnGen[39,40], and UK

Biobank (UKBB)[40,41]. All methods are then validated using independent individual-level

data from UKBB. Our simulations and real data analyses show that ALL-Sum can

achieve up to 60% improvement in R^2 for continuous traits and 8% improvement in AUC

for binary disease traits, with upwards of 25-times faster runtime and 5-times less

memory usage, compared to popular methods.

Results

Overview of ALL-Sum framework

ALL-Sum is a computationally efficient PRS method based on summary-level

data designed to model joint effects across the genome and improve PRS prediction

performance within a specific ancestry (**Methods**). The method consists two main

components: (1) $L_0 L_2$ penalized regression using GWAS summary statistics and LD,

and (2) aggregation of PRS candidates estimated using different tuning parameter

combinations (**Figure 1**). $L_0 L_2$ penalized regression allows for control over the number

of selected SNPs (L_0) and shrinkage of effect sizes to avoid overfitting (L_2). These two

penalties together can improve prediction performance by better leveraging SNPs in

high LD compared to the L_1 penalty used in Lassosum, and also have a conceptual

connection to the Gaussian spike-and-slab prior commonly used in statistical

genetics[13,15,33,42–46]. Using a fast coordinate optimization algorithm, we can efficiently

generate effect estimates, with a closed-form at each iteration, given a grid of L_0 and L_2

tuning parameter combinations.

These effect estimates are applied to individual-level genotypes in a tuning

dataset to construct a set of candidate PRSs corresponding to the tuning parameter

grid. Then, in an ensembling step within this tuning dataset, we use the PRSs as

predictors in cross-validated Lasso regression to obtain weights for each candidate

PRS. The weights are used to aggregate the effect estimates across the tuning

parameter grid and to yield a final effect estimate for prediction (**Methods**, **Figure 1**). In

both simulations and real data, we find that an ensemble of multiple candidate PRSs

across different tuning parameters leads to more accurate prediction than choosing the

single best model from grid search. Furthermore, we show analytically in **Methods** that

the classical grid search approach is a special case of the ensembling approach and

expected to perform worse than the ensembled estimate.

The default tuning parameters for implementing ALL-Sum include 5 values of λ_2

between 0.1 and 100 on the log-scale and 50 values of λ_0 with an adaptive

regularization path described in the **Supplementary Method Notes**. Ensembling is

done via 3-fold cross-validation lasso to choose $\tilde{\lambda}_1$ using the defaults of the glmnet

package (version 3.0) in R[47]. The implementation of the four alternative PRS methods is

provided in the **Methods** section.

Prediction performance in simulation studies

We first compare prediction performance of ALL-Sum against four alternative

PRS methods in a wide range of GWAS sample sizes and causal SNP proportions. Our

simulations include 120,000 simulated individuals based on European ancestry

generated from HapGen2[48] and about 1.2 million SNPs from HapMap3[49]. Out of the

120,000 total samples, 100,000 training samples are used to compute GWAS summary

statistics, 10,000 tuning samples to compute LD and choose a best PRS model

according to each method, and 10,000 validation samples to evaluate out-of-sample

prediction accuracy. We vary the causal SNPs from 0.01% to 10% and GWAS sample

size from 15,000 to 100,000. For simulation setting, we generate 10 simulation

replicates of a continuous phenotype using GCTA[50] based on a linear additive model

with total heritability around 0.4.

Across all sample size and causal SNP proportion settings, we find that ALL-Sum

consistently shows top prediction accuracy (**Figure 2, Supplementary Figure 1,**

Supplementary Table 5). In the case of extremely low polygenicity (0.01% causal), the

signals are strong enough that most methods can get close to the true heritability of 0.4,

aligning with previously established bounds on prediction accuracy as a function of

causal SNP proportion and sample size[51,52]. Even so, ALL-Sum is able to outperform all

methods by about 10% in terms of validation R^2 on average across all settings

(**Supplementary Figure 2**). Under moderately low polygenicity (0.05% and 0.1%) ALL-

Sum shows up to 34% in validation R^2 over LDPred2 and 19% over Lassosum2. As

polygenicity increases up to 10% causal, we observe at least around 10% increase in

R^2 by ALL-Sum over Stacked C+T and Lassosum2. Across all settings, ALL-Sum vastly

outperforms simple C+T, achieving up to twice the R^2 in some settings. Alternative

methods seem to show preference to either very strong (Stacked C+T and Lasossum2)

or weak (LDPred2) signals with respect to both polygenicity and GWAS sample size.

However, leveraging both the L_0L_2 regression and ensembling steps allows ALL-Sum to

perform well in all scenarios.

Runtime and memory usage in simulation studies

Beyond prediction performance, we also evaluate the runtime and memory

usage of ALL-Sum on three chromosomes (**Figure 3, Supplementary Table 6**). We use

LDPred2 as a benchmark for comparison, given its widespread usage in the field[34,53].

Across all settings, ALL-Sum runs about 20 times faster than LDPred2 on average for

larger chromosomes while using up to four times less memory (**Supplementary Figure**

3). This efficiency can be attributed to the rapid coordinate descent algorithm, and the

integration with plink 2.0 for efficiently computing multiple risk scores at once[54]. Within

the ALL-Sum pipeline, most of the runtime for ALL-Sum is dedicated to coordinate

descent, while a consistent proportion of time is taken up by computing PRS at various

steps (**Supplementary Figure 4**). It is important to note that LDPred2 and other

methods implemented in the bigsnpr R package (Stacked C+T and Lassosum2), not

only require memory during analysis but also when generating new backing files that

require substantial additional memory on top of the existing plink-format genotype

data[55].

Continuous trait prediction in UK Biobank

To evaluate the practical usage of ALL-Sum, we apply ALL-Sum and the four

alternative methods using large-scale consortium- and biobank-based GWAS summary

statistics (**Supplementary Tables 1-4**). We perform tuning and validation of the PRS

methods using genotype and phenotype data of 40,000 randomly selected European

samples from the UK Biobank (UKBB), with 20,000 samples used for each step. We

used publicly available GWAS for 6 continuous traits: high-density lipoprotein (HDL)

cholesterol, low-density lipoprotein (LDL) cholesterol, log-triglycerides (logTG), and total

cholesterol (TC) from the Global Lipids Genetics Consortium (GLGC), as well as height

and body mass index (BMI) from the Genetic Investigation of ANthropometric Traits

(GIANT) Consortium. We specifically chose summary statistics that exclude UKBB

samples to ensure valid prediction evaluation. To provide a broader comparison, we use

the remaining 278,052 European UKBB samples not used in tuning or validation as

additional training data to compute GWAS summary statistics for each trait.

Across nearly all traits and data sources, ALL-Sum shows the best prediction

performance, measured by R^2 of the PRS in the 20,000 validation samples adjusted for

age, sex, and the first 10 principal components (PCs) (**Figure 4, Supplementary Table**

7). ALL-Sum achieves up to 60% higher R^2 compared to alternative methods

(**Supplementary Figure 5**). We see particularly strong performance of ALL-Sum using

the GLGC-based summary statistics, which have about four times larger sample size

than UKBB, suggesting that our method can make better use of well-powered GWAS

than other methods. The GIANT- and UKBB-based summary statistics have similar

sample sizes, but the GIANT summary statistics contain fewer SNPs after filtering to

overlap with the UKBB genotype data. In this case, we notice that ALL-Sum performs

better using the UKBB summary statistics, showing the increased predictive potential

with a larger set of SNPs to analyze.

Within LDPred2 results, we find that prediction accuracy tends to be better using

UKBB-based GWAS summary statistics regardless of differences in sample size or

number of SNPs, suggesting a sensitivity to the similarity in underlying genetic

architecture between the data used to compute GWAS summary statistics and LD,

which has also been observed in previous analysis[20]. Furthermore, LDPred2 failed to

converge after trying 20 different random seeds for HDL using GLGC summary

statistics, demonstrating practical implementation issues with the MCMC algorithm.

Disease risk prediction in UK Biobank

We further apply the PRS methods to five binary disease traits: asthma, coronary

artery disease (CAD), type 2 diabetes (T2D), breast cancer, and prostate cancer. We

obtain summary statistics from case-control GWAS published by reputable consortia:

Transnational-National Asthma Genetic Consortium (TNAGC)[56], Coronary Artery

Disease Genome-wide Replication and Meta-analysis plus The Coronary Artery Disease

Genetics (CARDIoGRAMplusC4D)[57], Diabetes Genetics Replication And Meta-analysis

(DIAGRAM) consortium[58], Breast Cancer Association Consortium (BCAC)[4], and

Prostate Cancer Association Group to Investigate Cancer Associated Alterations in the

Genome (PRACTICAL)[59]. Additionally, we obtained GWAS summary statistics from

FinnGen[39], which published several well-powered binary disease GWAS, and the

278,052 European UKBB samples. Using the same analysis pipeline as with continuous

traits, we evaluate each PRS method's performance using Area under the ROC Curve

(AUC) adjusted for baseline covariates[60].

Across various disease traits and data sources, ALL-Sum again shows generally

better and robust performance. Compared to alternative methods, ALL-Sum shows up

to 8% increase in AUC over alternative PRS methods (**Supplementary Figure 5**) and

typically achieves either the highest or second-highest AUC across all methods (**Figure**

5, **Supplementary Table 8**) and. ALL-Sum particularly excels in predicting T2D and

prostate cancer, whereas LDPred2 performs well for CAD and Breast Cancer. As

expected from continuous trait analyses, ALL-Sum generally shows significant

prediction gains when using consortium-based GWAS that have a large number of both

cases and controls. Meanwhile, UKBB generally has few cases, resulting in potentially

underpowered summary statistics. While FinnGen has fairly well-powered summary

statistics relative to UKBB, but genetic differences between the Finnish and British

populations may explain why there is not a substantial improvement in prediction

accuracy[39,61].

Runtime and memory usage for prediction in UK Biobank

To further verify the practical usability of our method, we also compare the

runtime and memory usage of ALL-Sum and LDPred2 using the 11 full UKBB-based

summary statistics (**Supplementary Figure 6, Supplementary Table 9**). We find that

ALL-Sum completes full analysis, from processing input data to final validation, in less

than 30 minutes and using about 20 GB for both continuous and binary traits. On the

other hand, LDPred2 takes at least a few hours to run without parallelization, with up to

25 times longer runtime and 3 times more memory compared to ALL-Sum. In these real

data settings, ALL-Sum consistently requires far fewer computational resources to

deliver similar to better risk stratification than popular Bayesian computing.

Prediction gains from ensembling over grid search of tuning parameters

245   As a key component of our method is the ensembling step that aggregates PRS

models estimated using different tuning parameters to improve prediction accuracy and

stability over a simple grid search for the optimal tuning parameters. Our simulation

studies reveal that in the extreme high and low polygenicity settings, grid search and

ensembling yield similar predication accuracy (**Supplementary Figure 7,**

Supplementary Table 10). With low polygenicity, both estimates can identify a highly

predictive PRS, given the strength of the signals[51,52]. At high polygenicity, weak and

dense signals are adequately captured by the grid search estimate since the L_2 penalty

component yields a dense ridge-like estimate. However, at the intermediate polygenicity

levels, ensembling offers a more noticeable gain in R^2, suggesting that the tuning

parameter grid may not always contain the best parameter for the grid search PRS

estimate to perform well. Ensembling ensures high prediction accuracy by borrowing

information from multiple PRS candidates, but it also includes a larger number of SNPs

as a trade-off. For practical applications that require a PRS with few SNPs, grid search

may be more suitable, despite the additional fine-tuning required.

260   To further evaluate our ensembling approach, we compare the prediction

performance of ensembling with Lasso (L_1-penalty) against standard grids search, as

well as ensembling with Ridge (L_2-penalty). Our experiments on real continuous traits

favor Lasso for ensembling different PRS estimates (**Supplementary Figure 8,**

Supplementary Table 11). Ensembling with Ridge can achieve similar prediction

accuracy as Lasso across all traits. However, since no variable selection is performed,

Ridge keeps all candidate PRS and leads to a much larger number of selected SNPs in

the final prediction model. Thus, while ensembling will yield a much denser solution than

grid search, we choose to use Lasso since it still performs some selection to prioritize

the most predictive candidate PRS.

Stability across different LD references

We further evaluate ALL-Sum's performance using different LD references, given

that GWAS summary statistics and LD are typically computed on different genotype

data. We assess the validation R^2 in both simulations and UKBB continuous traits with

three LD reference panels: the training data used for GWAS, the tuning data used in our

primary analyses, and the 503 European samples from the 1000 Genomes Project

(1000G)[62].

Our analyses using both simulated and UKBB-based lipid summary statistics

show virtually identical results across when using either the training or tuning data as

the LD reference (**Supplementary Figure 9-10, Supplementary Table 12-13**). There is

a slight drop in prediction accuracy when using UKBB-based summary statistics and

1000G-based LD, about 4% lower R^2 on average compared to using LD based on the

UKBB tuning data. Although both UKBB and 1000G LD only consist of European

ancestry, the UKBB is primarily British Europeans, while 1000G includes a wider range

of European populations.

Our analyses suggest that ALL-Sum is fairly robust to the use of different LD

references. Specifically, prediction accuracy shows negligible differences when using in-

sample LD from training data or external LD from tuning or 1000 Genomes data. While

prediction accuracy is better when using UKBB-based LD for UKBB-based GWAS,

using 1000G-based LD only diminishes prediction accuracy by a small percentage and

is still about the same if not better than other methods using UKBB-based LD in the

main analysis. Furthermore, we show that using LD based on tuning data yields the

same prediction as using LD based on the training data used for generating GWAS

summary statistics. Thus, we can just use LD computed from a small and accessible

dataset, such as the tuning data or 1000G, so long as the population is similar to that of

the GWAS. As part of our software package, we provide two pre-computed LD based on

1000 Genomes Project and UKBB for convenient direct input for analysis.

Discussion

In this paper, we propose ALL-Sum as a fast and scalable PRS method that

combines efficient L_0L_2 optimization using publicly accessible GWAS summary statistics

and LD with ensembling of PRS estimates from different tuning parameters to improve

prediction accuracy. Extensive simulation studies and real data analyses show that our

method consistently provides strong prediction performance across a broad spectrum of

traits and data sources, is robust to different LD reference, and uses much less time

and memory compared to the state-of-the-art Bayesian approach. ALL-Sum's

performance in improving PRS prediction is most evident in continuous traits and

GWAS with large sample sizes. The prediction performance for binary traits is more

variable due to the predominance of healthy individuals in UKBB and hence few disease

cases[63]. However, with the ongoing expansion of biobank data, we anticipate the

potential for richer clinical data and more accurate disease risk prediction in the future.

Although ALL-Sum introduces improvements in prediction and computational and

resource efficiency, there are several limitations and opportunities for continued work.

The current model is designed for single ancestry analysis. While a large portion of

GWAS data currently comes from individuals of European ancestry, it is well-known that

polygenic risk scores do not transfer well between individuals of different ancestries,

which can impact their utility for patients of non-European ancestry[64–69]. Many methods

that utilize summary data from multiple populations have already been proposed and

demonstrate improved prediction in under-represented populations[25,26,30,70–74]. As

genetics research moves towards greater diversity, ALL-Sum serves as a valuable

foundation for extension to incorporating data from multiple ancestries, as well as

admixed individuals[75–77].

Our coordinate descent algorithm significantly reduces runtime compared to

Bayesian computation, but there are several directions primed for further software

refinement. One way is to devise a smaller data-driven tuning parameter grid similar to

the "auto" functions in some Bayesian softwares[14,16], which would reduce calls to

coordinate descent algorithm and reduce both runtime and memory usage. Future work

can also incorporate active set updates and combinatorial swaps from the original

L0Learn algorithm, as well as parallelization and sparse matrices, to speed up

optimization and potentially give better prediction accuracy[31,78,79]. In terms of

ensembling, we focus on Lasso given its well-established software and defaults in the

glmnet R package, simple linear interpretations, and implementation in other

ensembling contexts[29]. Future work can incorporate more intricate strategies, such as

those provided in the SuperLearner package[80], to provide even more flexible models to

further improve prediction accuracy.

Finally, while the first step of L_0L_2 penalized regression is applied to summary-

level data alone to construct PRS models, we still need access to individual-level data

for ensembling within the tuning dataset. This is also the case for tuning and validation

of the other methods compared in this paper. Having sufficient data for both tuning and

validation may be difficult to come by, especially for rare binary outcomes that are not

well-recorded in well-established sources like UKBB[63]. Furthermore, the cross-validation

step for ensembling may be sensitive if there are few samples or cases in the tuning

dataset, although this will similarly affect other methods. Methods have proposed for

tuning PRS methods without individual-level data[81–85]. However, final prediction

accuracy in final validation may not be as good due to approximations either from

generating proxy new data or using unsupervised approaches to the best PRS.

To conclude, we introduce ALL-Sum as a fast and scalable method for PRS using

summary-level data and demonstrate its strong prediction performance through

comprehensive evaluations in simulations and real data analysis. ALL-Sum is available

as a streamlined R software from automated data processing to final validation, using

simple command-line inputs.

Acknowledgements

We would like to thank Jin Jin, Jingwen Zhang, Hussein Hazimeh, Hui Li, Peter Kraft, and Rui Duan for their assistance, insights, and feedback on this project. We are grateful to participants in the UK Biobank (obtained under UK Biobank resource application 52008), FinnGen, and all consortiums referenced in this paper for providing data necessary for our analysis. All analyses were conducted on Harvard FAS Research Computing. This research was supported by NIH Training Grant T32GM135117 and NSF Graduate Research Fellowship DGE-2140743 (T.C.), NIH grants K99 CA256513 and NIH Intramural Research Program (H.Z.), Office of Naval Research grants N000142112841 and N000142212665 (R.M.), and NIH grants R35-3 CA197449, U19-CA203654, R01-HL163560, U01-HG009088 U01-HG012064 (X.L.).

Author Contributions

All four authors conceived the project. T.C. carried out the data analyses and developed the software and online resources for sharing, under the supervision of H.Z., R.M., and X.L. All authors drafted, reviewed, and approved the final version of this manuscript.

Data and Code Availability

Simulated genotype data can be found on the Harvard Dataverse (https://doi.org/10.7910/DVN/COXHAP). Access to FinnGen- and consortium-based GWAS summary statistics are detailed in **Supplementary Table 1**. The ALL-Sum software is available at https://github.com/chen-tony/ALL-Sum/. The repository includes the main R and C++ code for analysis, as well as a tutorial with example data. Pre-computed European-based LD from the 1000 Genomes Project and UKBB will be available on the Harvard Dataverse.

References

1. Chatterjee, N., Shi, J. & García-Closas, M. Developing and evaluating polygenic risk prediction models for stratified disease prevention. *Nat Rev Genet* **17**, 392–406 (2016).

2. Hung, R. J. *et al.* Assessing Lung Cancer Absolute Risk Trajectory Based on a Polygenic Risk Model. *Cancer Res* **81**, 1607–1615 (2021).

3. Graham, S. E. *et al.* The power of genetic diversity in genome-wide association studies of lipids. *Nature* **600**, 675–679 (2021).

4. Zhang, H. *et al.* Genome-wide association study identifies 32 novel breast cancer susceptibility loci from overall and subtype-specific analyses. *Nat Genet* **52**, 572–581 (2020).

5. Wray, N. R. *et al.* Genome-wide association analyses identify 44 risk variants and refine the genetic architecture of major depression. *Nat Genet* **50**, 668–681 (2018).

6. Schaid, D. J., Sinnwell, J. P., Batzler, A. & McDonnell, S. K. Polygenic risk for prostate cancer: Decreasing relative risk with age but little impact on absolute risk. *The American Journal of Human Genetics* **109**, 900–908 (2022).

7. Torkamani, A., Wineinger, N. E. & Topol, E. J. The personal and clinical utility of polygenic risk scores. *Nature Reviews Genetics* vol. 19 581–590 Preprint at https://doi.org/10.1038/s41576-018-0018-x (2018).

8. Lewis, C. M. & Vassos, E. Polygenic risk scores: From research tools to clinical instruments. *Genome Medicine* vol. 12 Preprint at https://doi.org/10.1186/s13073-020-00742-5 (2020).

9. Adeyemo, A. *et al.* Responsible use of polygenic risk scores in the clinic: potential benefits, risks and gaps. *Nature Medicine* vol. 27 1876–1884 Preprint at https://doi.org/10.1038/s41591-021-01549-6 (2021).

10. Wray, N. R., Goddard, M. E. & Visscher, P. M. Prediction of individual genetic risk to disease from genome-wide association studies. *Genome Res* **17**, 1520–1528 (2007).

11. Purcell, S. M. *et al.* Common polygenic variation contributes to risk of schizophrenia and bipolar disorder. *Nature* **460**, 748–752 (2009).

12. Lo, A., Chernoff, H., Zheng, T. & Lo, S.-H. Why significant variables aren't automatically good predictors. *Proceedings of the National Academy of Sciences* **112**, 13892–13897 (2015).

13. Vilhjálmsson, B. J. *et al.* Modeling Linkage Disequilibrium Increases Accuracy of Polygenic Risk Scores. *Am J Hum Genet* **97**, 576–592 (2015).

14. Privé, F., Arbel, J. & Vilhjálmsson, B. J. LDpred2: Better, faster, stronger. *Bioinformatics* **36**, 5424–5431 (2020).

15. Lloyd-Jones, L. R. *et al.* Improved polygenic prediction by Bayesian multiple regression on summary statistics. *Nat Commun* **10**, (2019).

16. Ge, T., Chen, C. Y., Ni, Y., Feng, Y. C. A. & Smoller, J. W. Polygenic prediction via Bayesian regression and continuous shrinkage priors. *Nat Commun* **10**, (2019).

17. Ni, G. *et al.* A Comparison of Ten Polygenic Score Methods for Psychiatric Disorders Applied Across Multiple Cohorts. *Biol Psychiatry* **90**, 611–620 (2021).

18. Zhou, G. & Zhao, H. A fast and robust Bayesian nonparametric method for prediction of complex traits using summary statistics. *PLoS Genet* **17**, e1009697 (2021).

418   19.   Mak, T. S. H., Porsch, R. M., Choi, S. W., Zhou, X. & Sham, P. C. Polygenic scores via
419   penalized regression on summary statistics. *Genet Epidemiol* **41**, 469–480 (2017).

420   20.   Privé, F., Arbel, J., Aschard, H. & Vilhjálmsson, B. J. Identifying and correcting for
421   misspecifications in GWAS summary statistics and polygenic scores. *Human Genetics and*
422   *Genomics Advances* **3**, 100136 (2022).

423   21.   Su, W., Bogdan, M. & Candès, E. False discoveries occur early on the Lasso path. *The*
424   *Annals of Statistics* **45**, (2017).

425   22.   Slatkin, M. Linkage disequilibrium — understanding the evolutionary past and mapping
426   the medical future. *Nat Rev Genet* **9**, 477–485 (2008).

427   23.   Liashchynskyi, P. & Liashchynskyi, P. Grid Search, Random Search, Genetic Algorithm: A
428   Big Comparison for NAS. (2019).

429   24.   Le, T. M. & Clarke, B. *Model Averaging Is Asymptotically Better Than Model Selection For*
430   *Prediction*. *Journal of Machine Learning Research* vol. 23 (2022).

431   25.   Zhang, J. *et al.* An Ensemble Penalized Regression Method for Multi-ancestry Polygenic
432   Risk Prediction. *bioRxiv* (2023) doi:10.1101/2023.03.15.532652.

433   26.   Jin, J. *et al.* ME-Bayes SL: Enhanced Bayesian Polygenic Risk Prediction Leveraging
434   Information across Multiple Ancestry Groups. *bioRxiv* (2023)
435   doi:10.1101/2023.04.12.536510.

436   27.   Rauschenberger, A., Glaab, E. & Van De Wiel, M. A. Predictive and interpretable models
437   via the stacked elastic net. *Bioinformatics* **37**, 2012–2016 (2021).

438   28.   van der Laan, M. J., Polley, E. C. & Hubbard, A. E. Super Learner. *Stat Appl Genet Mol Biol*
439   **6**, (2007).

440   29.   Privé, F., Vilhjálmsson, B. J., Aschard, H. & Blum, M. G. B. Making the Most of Clumping
441   and Thresholding for Polygenic Scores. *Am J Hum Genet* **105**, 1213–1221 (2019).

442   30.   Zhang, H. *et al.* A new method for multi-ancestry polygenic prediction improves
443   performance across diverse populations. *bioRxiv* (2023) doi:10.1101/2022.03.24.485519.

444   31.   Hazimeh, H. & Mazumder, R. Fast best subset selection: Coordinate descent and local
445   combinatorial optimization algorithms. *Oper Res* **68**, 1517–1537 (2020).

446   32.   Dedieu, A., Hazimeh, H. & Mazumder, R. *Learning Sparse Classifiers: Continuous and*
447   *Mixed Integer Optimization Perspectives Dedieu, Hazimeh, and Mazumder*. *Journal of*
448   *Machine Learning Research* vol. 22 (2021).

449   33.   Mazumder, R., Radchenko, P. & Dedieu, A. Subset Selection with Shrinkage: Sparse Linear
450   Modeling When the SNR Is Low. *Oper Res* (2022) doi:10.1287/opre.2022.2276.

451   34.   Khera, A. V. *et al.* Genome-wide polygenic scores for common diseases identify
452   individuals with risk equivalent to monogenic mutations. *Nat Genet* **50**, 1219–1224
453   (2018).

454   35.   Wang, Z. *et al.* The Value of Rare Genetic Variation in the Prediction of Common Obesity
455   in European Ancestry Populations. *Front Endocrinol (Lausanne)* **13**, (2022).

456   36.   Elliott, J. *et al.* Predictive Accuracy of a Polygenic Risk Score–Enhanced Prediction Model
457   vs a Clinical Risk Score for Coronary Artery Disease. *JAMA* **323**, 636 (2020).

458   37.   Wong, C. K. *et al.* Polygenic risk scores for cardiovascular diseases and type 2 diabetes.
459   *PLoS One* **17**, e0278764 (2022).

460   38.   Patel, A. P. *et al.* A multi-ancestry polygenic risk score improves risk prediction for
461   coronary artery disease. *Nat Med* (2023) doi:10.1038/s41591-023-02429-x.

39. Kurki, M. I. *et al.* FinnGen provides genetic insights from a well-phenotyped isolated
population. *Nature* **613**, 508–518 (2023).

40. Sudlow, C. *et al.* UK Biobank: An Open Access Resource for Identifying the Causes of a
Wide Range of Complex Diseases of Middle and Old Age. *PLoS Med* **12**, e1001779 (2015).

41. Berisa, T. & Pickrell, J. K. Approximately independent linkage disequilibrium blocks in
human populations. *Bioinformatics* **32**, 283–285 (2016).

42. Polson, N. G. & Sun, L. Bayesian L0-regularized least squares. *Appl Stoch Models Bus Ind*
35, 717–731 (2019).

43. Park, J.-H. *et al.* Distribution of allele frequencies and effect sizes and their
interrelationships for common genetic susceptibility variants. *Proceedings of the National*
Academy of Sciences **108**, 18026–18031 (2011).

44. Loh, P.-R. *et al.* Efficient Bayesian mixed-model analysis increases association power in
large cohorts. *Nat Genet* **47**, 284–290 (2015).

45. Henderson, C. R. Best Linear Unbiased Estimation and Prediction under a Selection
Model. *Biometrics* **31**, 423 (1975).

46. Meuwissen, T. H. E., Hayes, B. J. & Goddard, M. E. Prediction of Total Genetic Value Using
Genome-Wide Dense Marker Maps. *Genetics* **157**, 1819–1829 (2001).

47. Friedman, J., Hastie, T. & Tibshirani, R. *Regularization Paths for Generalized Linear Models*
via Coordinate Descent. *JSS Journal of Statistical Software* vol. 33
http://www.jstatsoft.org/ (2010).

48. Su, Z., Marchini, J. & Donnelly, P. HAPGEN2: Simulation of multiple disease SNPs.
Bioinformatics **27**, 2304–2305 (2011).

49. International HapMap 3 Consortium. Integrating common and rare genetic variation in
diverse human populations. *Nature* **467**, 52–58 (2010).

50. Yang, J., Lee, S. H., Goddard, M. E. & Visscher, P. M. GCTA: A Tool for Genome-wide
Complex Trait Analysis. *The American Journal of Human Genetics* **88**, 76–82 (2011).

51. Daetwyler, H. D., Villanueva, B. & Woolliams, J. A. Accuracy of predicting the genetic risk
of disease using a genome-wide approach. *PLoS One* **3**, (2008).

52. Wray, N. R. *et al.* Pitfalls of predicting complex traits from SNPs. *Nature Reviews Genetics*
vol. 14 507–515 Preprint at https://doi.org/10.1038/nrg3457 (2013).

53. Ding, Y. *et al.* Large uncertainty in individual polygenic risk score estimation impacts PRS-
based risk stratification. *Nat Genet* **54**, 30–39 (2022).

54. Chang, C. C. *et al.* Second-generation PLINK: rising to the challenge of larger and richer
datasets. *Gigascience* **4**, 7 (2015).

55. Privé, F., Aschard, H., Ziyatdinov, A. & Blum, M. G. B. Efficient analysis of large-scale
genome-wide data with two R packages: bigstatsr and bigsnpr. *Bioinformatics* **34**, 2781–
2787 (2018).

56. Demenais, F. *et al.* Multiancestry association study identifies new asthma risk loci that
colocalize with immune-cell enhancer marks. *Nat Genet* **50**, 42–53 (2018).

57. Nikpay, M. *et al.* A comprehensive 1000 Genomes-based genome-wide association meta-
analysis of coronary artery disease. *Nat Genet* **47**, 1121–1130 (2015).

58. Mahajan, A. *et al.* Fine-mapping type 2 diabetes loci to single-variant resolution using
high-density imputation and islet-specific epigenome maps. *Nat Genet* **50**, 1505–1513
(2018).

59.   Schumacher, F. R. *et al.* Association analyses of more than 140,000 men identify 63 new
prostate cancer susceptibility loci. *Nat Genet* **50**, 928–936 (2018).
60.   Foucher, Y., Le Borgne, F., Chatton, A. & Sabathe, C. RISCA: Causal Inference and
Prediction in Cohort-Based Analyses. Preprint at https://CRAN.R-
project.org/package=RISCA (2022).
61.   Sun, B. B. *et al.* Genetic associations of protein-coding variants in human disease. *Nature*
603, 95–102 (2022).
62.   Auton, A. *et al.* A global reference for human genetic variation. *Nature* **526**, 68–74 (2015).
63.   Schoeler, T. *et al.* Participation bias in the UK Biobank distorts genetic associations and
downstream analyses. *Nat Hum Behav* (2023) doi:10.1038/s41562-023-01579-9.
64.   Lewis, A. C. F. & Green, R. C. Polygenic risk scores in the clinic: new perspectives needed
on familiar ethical issues. *Genome Med* **13**, (2021).
65.   Hao, L. *et al.* Development of a clinical polygenic risk score assay and reporting workflow.
Nat Med **28**, 1006–1013 (2022).
66.   Krainc, T. & Fuentes, A. Genetic ancestry in precision medicine is reshaping the race
debate. *Proceedings of the National Academy of Sciences* **119**, (2022).
67.   Ding, Y. *et al.* Polygenic scoring accuracy varies across the genetic ancestry continuum.
Nature (2023) doi:10.1038/s41586-023-06079-4.
68.   Pärna, K. *et al.* A Principal Component Informed Approach to Address Polygenic Risk
Score Transferability Across European Cohorts. *Front Genet* **13**, (2022).
69.   Lennon, N. J. *et al.* Selection, optimization, and validation of ten chronic disease polygenic
risk scores for clinical implementation in diverse populations. *medRxiv* (2023)
doi:10.1101/2023.05.25.23290535.
70.   Cai, M. *et al.* A unified framework for cross-population trait prediction by leveraging the
genetic correlation of polygenic traits. *Am J Hum Genet* **108**, 632–655 (2021).
71.   Albiñana, C. *et al.* Leveraging both individual-level genetic data and GWAS summary
statistics increases polygenic prediction. *Am J Hum Genet* **108**, 1001–1011 (2021).
72.   Weissbrod, O. *et al.* Leveraging fine-mapping and multipopulation training data to
improve cross-population polygenic risk scores. *Nat Genet* **54**, 450–458 (2022).
73.   Ruan, Y. *et al.* Improving polygenic prediction in ancestrally diverse populations. *Nat
Genet* **54**, 573–580 (2022).
74.   Zhao, Z., Fritsche, L. G., Smith, J. A., Mukherjee, B. & Lee, S. The Construction of Multi-
ethnic Polygenic Risk Score using Transfer Learning. doi:10.1101/2022.03.08.22272114.
75.   Sun, Q. *et al.* Improving polygenic risk prediction in admixed populations by explicitly
modeling ancestral-specific effects via GAUDI. doi:10.1101/2022.10.06.511219.
76.   Machado Reyes, D., Bose, A., Karavani, E. & Parida, L. *FairPRS: adjusting for admixed
populations in polygenic risk scores using invariant risk minimization*.
www.worldscientific.com (2022).
77.   Kachuri, L. *et al.* Principles and methods for transferring polygenic risk scores across
global populations. *Nat Rev Genet* (2023) doi:10.1038/s41576-023-00637-2.
78.   Kim, J. & Park, H. Fast Active-set-type Algorithms for L1-regularized Linear Regression.
International Conference on Artificial Intelligence and Statistics (2010).

79. Nutini, J., Laradji, I. & Schmidt, M. Let's Make Block Coordinate Descent Converge Faster:
Faster Greedy Rules, Message-Passing, Active-Set Complexity, and Superlinear
Convergence. *Journal of Machine Learning Research* **23**, 1–74 (2022).
80. Polley, E., LeDell, E., Kennedy, C. & van der Laan, M. SuperLearner: Super Learner
Prediction. Preprint at https://CRAN.R-project.org/package=SuperLearner (2021).
81. Zhao, Z. *et al.* PUMAS: fine-tuning polygenic risk scores with GWAS summary statistics.
Genome Biol **22**, (2021).
82. Zhao, Z. *et al.* Optimizing and benchmarking polygenic risk scores with GWAS summary
statistics. *bioRxiv* (2022) doi:10.1101/2022.10.26.513833.
83. Miao, J. *et al.* Quantifying portable genetic effects and improving cross-ancestry genetic
prediction with GWAS summary statistics. *Nat Commun* **14**, 832 (2023).
84. Coombes, B. J., Ploner, A., Bergen, S. E. & Biernacka, J. M. A principal component
approach to improve association testing with polygenic risk scores. *Genet Epidemiol* **44**,
676–686 (2020).
85. Jiang, W., Chen, L., Girgenti, M., Zhao, H. & Girgenti, M. J. Tuning Parameters for Polygenic
Risk Score Methods Using GWAS Summary Statistics from Training Data Tuning
Parameters for Polygenic Risk Score. (2023) doi:10.21203/rs.3.rs-2939390/v1.
86. Zou, H. & Hastie, T. *Regularization and variable selection via the elastic net*. *J. R. Statist.*
Soc. B vol. 67 (2005).
87. Tibshirani, R. *Regression Shrinkage and Selection via the Lasso*. *Source: Journal of the*
Royal Statistical Society. Series B (Methodological) vol. 58 (1996).
88. Bertsimas, D., King, A. & Mazumder, R. Best subset selection via a modern optimization
lens. *Ann Stat* **44**, 813–852 (2016).
89. Fan, J., Liao, Y. & Mincheva, M. High-dimensional covariance matrix estimation in
approximate factor models. *The Annals of Statistics* **39**, (2011).
90. Gao, J., Han, X., Pan, G. & Yang, Y. High dimensional correlation matrices: the central limit
theorem and its applications. *J R Stat Soc Series B Stat Methodol* **79**, 677–693 (2017).
91. Pritchard, J. K. & Przeworski, M. Linkage Disequilibrium in Humans: Models and Data. *The*
American Journal of Human Genetics **69**, 1–14 (2001).
92. Bulik-Sullivan, B. *et al.* LD score regression distinguishes confounding from polygenicity in
genome-wide association studies. *Nat Genet* **47**, 291–295 (2015).
93. Dey, R. *et al.* Efficient and accurate frailty model approach for genome-wide survival
association analysis in large-scale biobanks. *Nat Commun* **13**, 5437 (2022).
94. Bien, S. A. *et al.* Strategies for Enriching Variant Coverage in Candidate Disease Loci on a
Multiethnic Genotyping Array. *PLoS One* **11**, e0167758 (2016).
583
584

  Methods

  ALL-Sum

587   *L0Learn-based prediction using individual-level data*

588   Suppose we have a linear model

$$Y_i = \sum_{j=1}^{p} G_{ij}\beta_j + \epsilon_i, \tag{1}$$

where Y_i is the observed phenotype for an individual $i \in \{1, \dots n\}$, β_j is the effect size for

SNP $j \in \{1, \dots, p\}$, G_{ij} is the dosage of SNP j for individual i that takes values between 0

and 2, and ϵ_i is a normally distributed error term.

In a high-dimensional setting where p can be several orders of magnitude larger

than n, we assume that a subset of SNPs are causal, or with nonzero effects β_j. This

motivates the use of penalties to encourage sparsity in our effect estimate[86–88]. L0Learn

was recently proposed as a general penalized regression framework that directly

penalizes the number of nonzero effects to give very sparse estimates[31]. Specifically,

the method aims to estimate the regression coefficients $\boldsymbol{\beta} = (\beta_1, \dots, \beta_p)$ by minimizing

the penalized least squares loss function:

$$\frac{1}{2}\sum_{i=1}^{n}\left(Y_i - \sum_{j=1}^{p} G_{ij}\beta_j\right)^2 + \lambda_0 \sum_{j=1}^{p} I(\beta_j \neq 0) + \lambda_1 \sum_{j=1}^{p}|\beta_j| + \lambda_2 \sum_{j=1}^{p}\beta_j^2 \tag{2}$$

The first term is the squared error from using $\boldsymbol{\beta}$ as coefficients for each SNP. In the

second term, $I(\beta_j \neq 0)$ is an indicator that equals 1 if the j-th entry of $\boldsymbol{\beta}$ is nonzero and

0 otherwise. The sum of these indicators forms the L_0 pseudonorm, which describes the

sparsity of $\boldsymbol{\beta}$ by the total number of nonzero entries. The parameter λ_0 controls the

strength of the penalty on nonzero entries, where higher values impose stronger

penalties and thus fewer nonzero entries. The third and fourth terms refer to additional

regularization on either the absolute or squared value of β_j. The corresponding penalty

parameters λ_1 and λ_2 enforce shrinkage on the estimated effect sizes, reducing

overfitting to the training data and improve out-of-sample prediction.

L0Learn-based prediction using GWAS summary statistics

The loss function in (2), which was used in the original L0Learn method[31], requires

individual-level data that often cannot be easily shared publicly. Furthermore, the

algorithm may not scale easily to the order of genome-scale analysis, involving millions

of SNPs and hundreds of thousands of individuals. To address these issues, we first

propose L0Learn using publicly accessible LD and GWAS summary-level statistics.

Specifically, equation (2) can be rewritten more concisely into matrix notation as:

618
$$\frac{1}{2}Y^TY + \frac{1}{2}\beta^T(G^TG)\beta - \beta^T(G^TY) + \lambda_0\left|\left|\beta\right|\right|_0 + \lambda_1\left|\left|\beta\right|\right|_1 + \lambda_2\left|\left|\beta\right|\right|_2^2. \qquad (3)$$

619   Assuming Y and each column of G are standardized to have mean 0 and variance $\frac{1}{n}$, we

620   can transform equation (3) to the following equation, which only depends on GWAS

621   association summary statistics and the LD matrix:

622
$$\frac{1}{2}\beta^TR\beta - \beta^Tr + \lambda_0\left|\left|\beta\right|\right|_0 + \lambda_1\left|\left|\beta\right|\right|_1 + \lambda_2\left|\left|\beta\right|\right|_2^2 \qquad (4)$$

R is a $p \times p$ matrix representing the LD matrix approximating G^TG when the genotypes

are standardized. r is a p-length vector corresponding to G^TY , which is equal to the

correlation of each SNP with the phenotype under the standardization. Each entry r_j can

be computed as $\dfrac{t_j}{\sqrt{n_j-2+t_j^2}}$, where $t_j = \dfrac{\beta_j^{GWAS}}{se\left(\beta_j^{GWAS}\right)}$ is the GWAS test statistic for the

marginal SNP effect and n_j is the sample size observed for that SNP. This formula for r_j

is based on the test statistic for Pearson's correlation and is nearly identical to $\boldsymbol{G}_j^T \boldsymbol{Y}$ for

large n_j.

Scalable coordinate descent optimization

632   The optimization problem can be solved using cyclical coordinate descent, an

633   efficient algorithm for high-dimensional problems[31,47]. Given an initialization $\boldsymbol{\beta}^{(0)}$, each

634   coordinate or variable j at timestep t is iteratively updated by the following rule, which

635   has a closed form:

$$\beta_j^{(t)} = \begin{cases} \dfrac{\left|\tilde{\beta}_j^{(t)} - \lambda_1\right|}{1 + 2\lambda_2} \text{sign}\left(\tilde{\beta}_j^{(t)}\right) & \text{if} \quad \left|\tilde{\beta}_j^{(t)} - \lambda_1\right| > \sqrt{2\lambda_0(1 + 2\lambda_2)} \\ 0 & \text{otherwise} \end{cases} \tag{5}$$

where $\tilde{\beta}_j^{(t)} = r_j - \boldsymbol{R}_{j,-j}\boldsymbol{\beta}_{-j}^{(t-1)}$ represents the residualized marginal effect of SNP j,

adjusting for effects of LD by neighboring SNPs. $\boldsymbol{R}_{j,-j}$ refers to the j-th row of R after

removing the j-th column entry. Similarly, $\boldsymbol{\beta}_{-j}^{(t-1)}$ removes the j-th entry of $\boldsymbol{\beta}^{(t-1)}$. In the

context of sharing and accessing large-scale genetic data, $\boldsymbol{r}$ and $\boldsymbol{R}$ are typically

computed from different sets of genotypes. For instance, $\boldsymbol{r}$ may come from large

publicly-available GWAS, and $\boldsymbol{R}$ from well-established reference data such as the 1000

Genomes Project[62]. For the L_0L_2-penalized estimator, equation (5) simplifies to

$$\beta_j^{(t)} = \frac{\tilde{\beta}_j^t}{1 + 2\lambda_2} I\left(\left|\tilde{\beta}_j^t\right| > \sqrt{2\lambda_0(1 + 2\lambda_2)}\right) \tag{6}$$

where $I(\cdot)$ is an indicator function that equals 1 if the inequality in parentheses is

satisfied and 0 otherwise.

In practice, using the entire LD matrix is far too large to store and share.

Furthermore, since the number of SNPs often far exceeds the number of samples,

estimating all pairwise correlations can be noisy and potentially hinder downstream

analysis[89,90]. A simple workaround is to approximate LD by a sparse matrix with only a

subset of pairwise correlations. Our current implementation focuses on a block-diagonal

approximation using LD blocks based on published base-pair positions corresponding to

roughly independent regions along the genome[41]. This simplification greatly improves

the efficiency of the algorithm by effectively dividing the overall optimization problem into

smaller independent problems.

Since the penalized regression problem assumes that both the outcome and

genotypes have all been standardized, we can re-scale the effect estimates so that they

correspond to genotypes on the original scale, where SNP dosage ranges from 0 to 2.

This adjustment requires access to minor allele frequencies (MAF), which may either be

included with the GWAS summary statistics or estimated using available genotype data.

For a given effect estimate $\hat{\beta}_j$ and corresponding SNP minor allele frequency π_j, the

rescaled effect estimate is given as $\dfrac{\hat{\beta}_j}{\sqrt{2\pi_j(1-\pi_j)}}$.

Ensembled PRS from tuning parameter grid

After producing multiple estimates for $\boldsymbol{\beta}$ according to a grid of tuning parameter

combinations, the immediate next step is to choose the $\boldsymbol{\beta}$ that gives the best fit on a

tuning dataset. Traditional grid search for fine-tuning is simple and may work well if the

best tuning parameters can be easily identified within the grid. However, this may miss

out on the parameterization that yields the best predictor. First, the optimal tuning

parameters may lie outside the fixed grid. Second, more importantly, as shown in

equations (4) and (5), the same tuning parameters are used for all SNPs. For example,

in equation (6), at each iteration the same hard threshold $\sqrt{2\lambda_0(1 + 2\lambda_2)}$ and shrinkage

$\frac{1}{1+2\lambda_2}$ are used for estimating all coefficients β_j.

To identify a high-accuracy and more flexible prediction model, we propose an

ensemble method that combines different $\widehat{\boldsymbol{\beta}}$ across the whole tuning parameter grid.

This is done by estimating an optimal weighting using cross-validated Lasso regression.

Ensembling across the tuning parameter grid allows different β_j to follow different

thresholding and shrinkage.

Specifically, suppose we have a grid of N different combinations of tuning

parameters λ_0 and λ_2. For each grid point $k \in \{1, \dots . K\}$, we generate effect estimates

$\widehat{\boldsymbol{\beta}}^{(k)}$ to tuning parameters $\lambda_0^{(k)}$ and $\lambda_2^{(k)}$. We first multiply each effect estimate by the

genotypes in a tuning dataset to compute PRS $\widehat{\boldsymbol{Y}}_{tun}^{(k)} = \boldsymbol{G}_{tun}\widehat{\boldsymbol{\beta}}^{(k)}$. These PRS are then

used as covariates in a Lasso regression of the outcome in the tuning dataset $\boldsymbol{Y}_{tun}$ on

the PRSs $\widehat{\boldsymbol{Y}}_{tun}^{(k)}$ to estimate the weights w_k by minimizing the penalized regression

$$\widehat{\boldsymbol{w}} = \underset{w_1 \cdots w_N}{\operatorname{argmin}} L\left(\boldsymbol{Y}_{tun}, \sum_{k=1}^{K} w_k \widehat{\boldsymbol{Y}}_{tun}^{(k)}\right) + \tilde{\lambda}_1 \left\lVert \boldsymbol{w} \right\rVert_1, \tag{7}$$

where $L(\boldsymbol{y}, \widehat{\boldsymbol{y}})$ is either the least squares loss $\sum_{i=1}^{n}(y_i - \hat{y}_i)^2$ for continuous outcomes or

logistic loss $\sum_{i=1}^{n}[y_i\hat{y}_i - \log(1 + e^{\hat{y}_i})]$ for binary outcomes, and $\tilde{\lambda}_1$ is the Lasso tuning

parameter chosen by 3-fold cross-validation. Using the PRS as proxies for the effect

estimates, we use the estimated ensembling weights $\widehat{w}_1 \cdots \widehat{w}_K$ to obtain a final

aggregated regression coefficient estimate:

$$691 \qquad \widehat{\boldsymbol{\beta}} = \sum_{k=1}^{K} \widehat{w}_k \widehat{\boldsymbol{\beta}}^{(k)} \qquad (8)$$

692   To get an insight into how this estimator improves over the traditional grid search-

693   based estimator, using equation (6), the ensembled estimator $\widehat{\boldsymbol{\beta}}$ in equation (8) can be

694   written as an iterative estimator

$$695 \qquad \beta_j^{(t)} = \sum_{k=1}^{K} \widehat{w}_k \frac{\tilde{\beta}_j^t}{1 + 2\lambda_2^{(k)}} I\left(|\tilde{\beta}_j^t| > \sqrt{2\lambda_0^{(k)}\left(1 + 2\lambda_2^{(k)}\right)} \right) \qquad (9)$$

which combines the $\tilde{\beta}_j^{(t)}$ estimators obtained using different hard thresholds

$\sqrt{2\lambda_0^{(k)}\left(1 + 2\lambda_2^{(k)}\right)}$ and shrinkages $\frac{1}{1+2\lambda_2^{(k)}}$. In fact, the traditional grid search corresponds

to regressing $\boldsymbol{Y}_{tun}$ on each $\widehat{\boldsymbol{Y}}_{tun}^{(k)}$ individually and identifying the single best $\widehat{\boldsymbol{Y}}_{tun}^{(k)}$ to

predict $\boldsymbol{Y}_{tun}$. This is equivalent to estimating the w_k's in the regression model of $\boldsymbol{Y}_{tun}$ on

$\left\{w_k \widehat{\boldsymbol{Y}}_{tun}^{(k)}\right\}_{k=1}^{N}$ using a one-step forward selection procedure to identify the single best

$\widehat{\boldsymbol{Y}}_{tun}^{(k)}$, which will identify a model with inferior prediction performance compared to

estimating w_k's by minimizing the problem in equation (7).

With the ensembled effect estimates, we construct a PRS in an out-of-sample

validation dataset $\widehat{\boldsymbol{Y}}_{val} = \boldsymbol{G}_{val}\widehat{\boldsymbol{\beta}}$, which remains separate from the cross-validation Lasso

regression in the tuning dataset. Lastly, we assess the PRS's prediction performance on

the validation outcome $\boldsymbol{Y}_{val}$, using R^2 for continuous outcomes and AUC for binary

outcomes.

Implementation of PRS Methods

C+T[10,11] is a method that first removes SNPs in high LD with an index SNP with the

most significant GWAS p-value in a particular base-pair window. Then, several p-value

thresholds are applied to the remaining SNPs to decide which parameter combination

gives the best PRS. This was implemented in plink 1.9[54] using LD thresholds r^2 of 0.05

and 0.1, windows of size $\frac{w_b}{r^2}$ kb, where the window base w_b is either 25 or 50, and 23 p-

value thresholds p_T ranging from 1×10^{-11} to 1. The use of $\frac{w_b}{r^2}$ is motivated by an inverse

relationship between LD and genetic distance between SNPs[91]. We choose the best

clumping parameters and p-value threshold within the tuning dataset to construct the

PRS.

Stacked C+T[29] is an ensembling-based method that uses elastic net to aggregate PRS

estimates from different clumping and thresholding parameterizations. Based on the

online tutorial, we use 7 LD thresholds r^2 between 0.01 and 0.95, 4 window bases w_b

(50, 100, 200, and 500 kb), 50 p-value thresholds p_T, and 3 weights α (1, 0.01, and

0.0001) for Lasso versus ridge.

Lassosum2[20] is an extension of the previously developed Lassosum method[19]. The

original Lassosum solves a Lasso regression using summary-level data from GWAS

and LD, with an additional penalty applied to the LD matrix:

$$\boldsymbol{\beta}^T\big((1-s)\boldsymbol{R}+s\boldsymbol{I}\big)\boldsymbol{\beta}-\boldsymbol{\beta}^T\boldsymbol{r}+\lambda_1\big|\big|\boldsymbol{\beta}\big|\big|_1 \tag{8}$$

The tuning parameter $s \in (0,1]$ is used to ensure convexity of the optimization, since the

GWAS and LD are typically from different genotype data. The original Lassosum uses a

block-diagonal LD approximation[41] for $\boldsymbol{R}$, while Lassosum2 uses a banded LD

approximation for each chromosome – the original results do not show much difference

in prediction between the two LD approximations. For the grid search, we use 4 values

of s (0.001, 0.01, 0.1, and 1) and 30 values of λ_1.

LDPred2[14] is a computational extension of the previously developed LDPred method[13].

This method is based on the Gaussian spike-and-slab prior for each SNP effect size β_j:

$$
739 \qquad \beta_j \sim \begin{cases} N\left(0, \dfrac{h^2}{M\pi}\right) & \text{with probability } \pi \\ 0 & \text{with probability } 1 - \pi \end{cases}, \tag{9}
$$

where h^2 is the total heritability of a trait, M is the total number of SNPs, and π is the

proportion of nonzero SNPs. Then, a Gibbs sampling MCMC algorithm is used to

compute the posterior mean $E[\boldsymbol{\beta}|\bar{\boldsymbol{\beta}}, \boldsymbol{R}]$, conditional on marginal effect sizes $\bar{\boldsymbol{\beta}}$ from

GWAS and banded LD $\boldsymbol{R}$. LDPred2 introduces improvements in efficiency that allow for

a larger grid search compared to LDPred. For this grid search, we use 0.7, 1, and 1.3

times the heritability h^2 estimated from LD score regression[92] – 21 values of π between

10^{-5} and 1, as well as "True" and "False" for the "sparse" setting that forces more

posterior SNP effects to be 0.

Stacked C+T, Lassosum2, and LDPred2 were implemented using bigsnpr (version

1.8.1) in R, following online tutorials, with 10 cores for parallel computing[14,20,29,55]. For

Lassosum2 and LDPred2, we used a 500 kb-width banded LD for each chromosome.

Published GWAS Summary Statistics and Evaluation in UK Biobank

We further compare the PRS methods on 27 published summary statistics across

11 traits and 9 data sources. Tuning and validation were done using individual-level

genotype and phenotype data from the UKBB[40]. We focus our analysis on individuals of

European ancestry, based on self-reported race as "British", "Irish", "White", or 'Any

other white background." After excluding individuals who withdrew consent as of April

26, 2023, and have missing baseline measurements for age, sex, and the first ten PCs,

and further restricting to unrelated samples so that no pair has relationship closer than

fourth degree[93], we have a total of 318,052 samples for analysis. 40,000 samples were

randomly chosen for tuning and validation - with 20,000 samples in each split. We use

the tuning sample as the LD reference for each of the PRS methods. Our analysis is

restricted to about 1.5 million SNPs in HapMap3[49] and Multi-Ethnic Genotyping Arrays

(MEGA)[94] chips that are shared between the GWAS and UKBB imputed genotype. Any

remaining missing SNP values were assigned a dosage of 0 for consistency across

methods. The 1.5 million SNPs were selected according to analysis of GLGC traits in

the recently published CT-SLEB paper[30]. Note that quality control might result in varying

number of SNPs across different datasets, but all PRS methods use the same GWAS

summary statistics to ensure fair comparison.

The summary statistics for these traits were collected from a variety of publicly

available sources (**Supplementary Tables 1-3**). Baseline covariates (age, sex, and the

first ten PCs) and continuous trait measurements were obtained from the "initial

assessment visit" period. Binary traits were defined using ICD10 codes, where the

outcome is set as 1 if at least one code was observed and 0 otherwise (**Supplementary**

Table 4). For tuning and validation of continuous traits, we compute R^2 with respect to

the residuals of the trait after regressing out the baseline covariates. For binary traits,

we use the RISCA package (version 1.0.3) in R[60] to compute adjusted AUC to account

for baseline covariates in logistic regression.

Main Figures

Figure 1 Overview of ALL-Sum framework. (1) Obtain GWAS summary statistics and LD, typically from unobserved training and reference data, respectively. (2) Use the L0Learn-Sum algorithm using GWAS and LD to estimate coefficients $\widehat{\boldsymbol{\beta}}^{(k)}$ corresponding to L_0L_2 tuning parameters $\{\lambda_0, \lambda_2\}^{(k)}$ with $k = 1, \dots, K$. (3) Apply each set of tuning parameter-specific coefficients to tuning genotype data to construct K candidate PRSs. Run cross-validated Lasso regression of the outcome on the K PRSs to obtain ensembling weights $\widehat{w}_1, \cdots, \widehat{w}_K$ and combine effect estimates from different tuning parameters. (4) Apply ensembled effect estimate to validation data and evaluate final the PRS, using common metrics such as R^2 or AUC.

Figure 2 Method comparison in simulation studies with 1.2 million SNPs with varying proportions of causal SNPs. The predictive accuracy of ALL-Sum and four alternative PRS methods are evaluated on simulated data across six causal SNP proportions (panels) and four GWAS sample sizes (X-axis). The Y-axis corresponds to R^2 on 10,000 validation samples set after choosing a best PRS for each method on 10,000 tuning samples. Bar plots indicate the average R^2 across 10 simulation replicates for each setting, and error bars represent the range in R^2.

Figure 3 Runtime and memory usage comparison between ALL-Sum and LDPred2. Runtime (Y-axis A) and memory usage (Y-axis B) were compared using simulated data on chromosomes 1, 10, and 21 (X-axis), with causal SNP proportions 0.1%, 1%, and 10% (panels) and GWAS sample size of 100,000.

Figure 4 Prediction accuracy comparison of PRS for continuous traits using

consortium- and UKBB-based GWAS, validated in UKBB. We compare the

prediction accuracy (Y-axis) of ALL-Sum and 4 alternative PRS methods on 6

continuous traits (X-axis), train using summary statistics from either consortium-based

(top panel) or UKBB-based GWAS (bottom panel) with sample sizes up to 930,000 and

276,000, respectively. Prediction accuracy is measured as the R^2 of the PRS from each

method with respect to the residuals of a trait after regression out age, sex, and the first

10 PCs. Bar plots indicate the bootstrap mean R^2 over 10,000 resamples within a

validation sample of 20,000 European individuals in the UKBB, independent from those

used for UKBB-based GWAS. Error bars indicate the bootstrap 95% confidence interval.

(Note: LDPred2 failed to converge for HDL using consortium GWAS summary statistics)

Figure 5 Prediction accuracy comparison of PRS for binary traits using consortium-, FinnGen-, and UKBB-based GWAS, validated in UKBB. We compare the prediction accuracy (Y-axis) of ALL-Sum and 4 alternative PRS methods on 6 continuous traits (X-axis), using summary statistics from either consortium-based (top panel), FinnGen-based (middle panel), or UKBB-based GWAS (bottom panel) with up to 180,000, 49,000, and 20,000 cases, respectively. Prediction accuracy is measured as the adjusted AUC of the PRS from each method conditional on age, sex, and the first 10 PCs. Sex is not used as a covariate for breast and prostate cancers. Bar plots indicate the bootstrap mean R^2 over 10,000 resamples within a validation sample of 20,000 European individuals in the UKBB, independent from those used for UKBB-based GWAS. Error bars indicate the bootstrap 95% confidence interval.