Background-matching patterns are attractive: support for a processing bias

Yseult Héjja-Brichard[1,2,3,4] *, Michel Raymond[5], Innes C. Cuthill[6], Tamra C. Mendelson[1]¶, Julien P. Renoult[2] * ¶

[1] University of Maryland, Baltimore County, Baltimore, MD; [2] CEFE, University of Montpellier, CNRS, EPHE, IRD, Montpellier, France; [3] Department of Interdisciplinary Life Sciences, KLIVV, University of Veterinary Medicine, Vienna, Austria; [4] Department of Behavioural and Cognitive Biology, University of Vienna, Vienna, Austria; [5] Institut des Sciences de l'Evolution (CNRS-UMR 5554), Montpellier, France; [6] School of Biological Sciences, University of Bristol, Bristol, United Kingdom

* Corresponding authors. E-mails: yseulthb@gmail.com ; julien.renoult@cefe.cnrs.fr
¶ These authors contributed equally to this work

Abstract

Background-matching visual patterns are selected to minimize detection by predators. However, once detected, what effects do these patterns have on conspecific perception? In humans, considerable evidence supports a "processing bias" by which people prefer images that match the spatial statistics of natural scenes, likely because the brain has evolved, or develops, to process such scenes efficiently. A direct but untested prediction of this bias is that people should prefer background-matching patterns compared to similar patterns that mismatch the spatial statistics of their surroundings. We conducted an online experiment to test this prediction on over 1,700 participants. Our results show that a preference for the most frequent value of Fourier slope (a measure of spatial structure) observed in natural scenes can be modulated by an additional preference for background-matching. Because the initial stages of perception that underlie the efficient processing of visual scenes are widely conserved among animals, especially vertebrates, we expect this preference for background-matching patterns to be shared by other organisms. Two overlooked potential implications are that some animals may choose display sites with spatial statistics matching their own phenotype, and that the evolution of visual signals will, variously, be constrained or facilitated by such preferences for background-matching patterns.

Keywords

34   Background-matching patterns ; processing bias ; online experiment ; sexual signals
35

Highlights

-    "Processing bias" has been proposed to explain the origins of preferences for sexual
signals and aversion to aposematic signals
-    It predicts that the visual properties of background-matching patterns make them
attractive
-    An online experiment with over 1,700 human participants confirms that prediction
-    Results have important implications for the preference and design of animal signals

Introduction

Understanding the origin of preferences for sexual signals is an ongoing focus of evolutionary
biology. One hypothesis is that preferences originate as perceptual biases that arose in
contexts other than mating (e.g., Endler & Basolo, 1998; Ryan & Cummings, 2013).
"Processing bias" has been proposed as a pre-existing perceptual bias that could explain the
origin of preferences and the subsequent evolution of sexual signals (Renoult & Mendelson,
2019). The processing bias hypothesis suggests that preferences originate as a bias for
efficiently processed information (Renoult & Mendelson, 2019). Efficiency refers to the
processing of information with both few errors and low metabolic cost, and it translates as the
ease with which a signal is processed by the brain. Importantly, efficiency is known to increase
the attractiveness of a stimulus (Fantz, 1957; Reber et al., 2004; Munar et al., 2015; Spehar
et al., 2015; Renoult et al., 2016), likely because efficient information processing generates a
feeling of fluency that is experienced as pleasant and therefore rewarding (Geller et al., 2022).

For visual signals, efficiency can be achieved by matching signal design with the sensitivity
(i.e., tuning) of visual neurons (Barlow, 1961). A well-supported finding in neuroscience is that
the visual system is adapted to efficiently process spatial statistics (e.g. luminance contrast
distribution, feature orientations) of the environment (Field, 1987; Olshausen & Field, 1997;
Simoncelli & Olshausen, 2001). As a result, stimuli that resemble the underlying spatial
patterns of natural scenes will be processed more efficiently and experienced as pleasant or
attractive. Indeed, a preference in humans for the statistical features of natural scenes is a
robust finding in experimental psychology (e.g., Hagerhall et al., 2004; Spehar et al., 2003,
2015). In nature, background-matching is a type of camouflage whereby the color and pattern
of an animal's phenotype mimic those of its surroundings (see e.g. Cuthill, 2019; Merilaita &
Stevens, 2011). Given that background-matching relies on matching visual statistics of a

stimulus with those of the habitat, the processing bias hypothesis predicts that background-
matching patterns are visually attractive. This study aims to test this hypothesis and to discuss
potential consequences of this prediction for the evolution of attractive and aversive signals in
humans and other animals.

The attractiveness of patterns that mimic natural spatial statistics may seem to contradict
predictions and empirical findings in visual ecology, which show that the function of this type
of design is to go unnoticed. However, these two phenomena are not contradictory if we
consider the detection of a stimulus and the processing of the information it contains as two
distinct and sequential perceptual stages (Chun & Potter, 1995). Indeed, the same feature can
function to minimize perceptual efficiency for detection, for example by reducing
conspicuousness, but also to maximize processing efficiency once that pattern is detected.
For instance, although the leopard's rosettes were likely selected to increase their camouflage
(Allen et al., 2010), those same rosettes are salient cues used by macaques to recognize the
leopard as a predator (Coss et al., 2005). From an ecological perspective, this dichotomy
explains why and how animals can bypass the trade-off between sexual and natural selection
that is typically inferred in the context of detection, where sexual selection favors
conspicuousness and natural selection favors crypsis. Animals can be both cryptic and
conspicuous, for example if detection is only possible via private communication channels
among conspecifics (Cummings et al., 2003), the appearance of the pattern is distance-
dependent (Barnett et al., 2017), or if the signaler's behavior involves ostentatious displays,
as in the Indian peafowl (*Pavo cristatus*), the timing of which can be controlled to avoid
detection by predators (Kane et al., 2019). The question is then: what is the effect of a
background-matching pattern on the attractiveness of an object or stimulus, once that stimulus
has been detected?

There are two potential mechanisms by which the attractiveness of a stimulus can be
influenced by its match with natural spatial statistics. A first hypothesis predicts a global
preference for spatial statistics that are characteristic of natural visual scenes. That prediction
was supported by Spehar and colleagues (2015), who found a strong relationship between
human visual sensitivity and preference for simple visual patterns that mimic the spatial
properties of natural scenes. Moreover, a large body of results in empirical aesthetics show
that visual artwork often imitates natural spatial statistics (Graham & Field, 2008; Graham &
Redies, 2010), increasing their perceived attractiveness. A second hypothesis suggests
preferences will be stronger for background-matching patterns. For instance, Menzel and
collaborators (2015) varied the slope of the background against which faces were presented
and asked participants to rate their attractiveness. Faces were rated as more attractive when

they were presented against a background that was closer to the statistics of both natural
scenes and faces, i.e. when faces had statistical properties in common with backgrounds.

Here, using psychophysical experiments with humans as a model, we provide empirical
evidence that the level of background-matching is correlated with the level of visual
attractiveness, once a stimulus is detected. We used abstract stimuli made from white noise
images to ensure that measured responses were due to the processing of low-level visual
statistics as performed by the perceptual system, and not to cognitive mechanisms involving
object recognition. This approach reduces the effect on preference of any benefit or danger
associated with the stimulus, thereby facilitating the interpretation of results within the
framework of processing bias. In the first task, we used a detection task to assess the
effectiveness in minimizing detectability of different circular patterned stimuli ('targets') that
varied in their level of background-matching. The backgrounds were artificial but with spatial
statistics either similar to those of many natural scenes or manipulated away from typical
values. Participants were required to click on the target as quickly as possible. This first task
was necessary to demonstrate that our method for manipulating stimuli results in perceived
variation in background-matching. In the second and third tasks, we evaluated the
attractiveness of these targets, using the same patterned stimuli as for the detection task but
removing the detectability constraint. Participants were asked in a forced-choice task to
indicate which of the two patterns they preferred. In the second task, stimuli were presented in
pairs against a uniform grey background to assess the baseline attractiveness of the target
stimuli, independent of the background. This task measures the absolute preference for our
stimuli, that is, without any background-matching effect. In the third task, stimuli were
presented in pairs against the same patterned backgrounds as for the detection task, so that
the degree of background-matching varied across stimuli, but stimuli were outlined to make
them easily detectable. The third task, therefore, tested our main prediction that background-
matching patterns are attractive when rendered detectable.

128
129

Methods

Ethical note

132 Participants were recruited through advertisements on dedicated mailing lists and on social
133 networks. Participants were not paid, and they were required to be at least 16 years old.
134 Approvals from the French (deemed exempt, CNIL number 2-21044) and American (deemed

exempt, UMBC IRB #522) ethics committees were obtained before the start of the experiment. Before launching the online experiment, the study's objectives and planned analyses were pre-registered following open science practices (available on [link to the repository]).

Online experiment and participant recruitment

The experiment took place online on a website hosted by the Montpellier Bioinformatics Biodiversity platform (University of Montpellier, France) and is available for demonstration purposes at [link to experiment]. The experiment was programmed using a custom HTML script (including JavaScript, CSS, and PHP) and jsPsych, a JavaScript library for creating online experiments (de Leeuw, 2015), and is available to play on all standard internet browsers. The experiment had to be conducted with a desktop or laptop computer, excluding smartphones and tablets.

Stimulus design

Sets of stimuli for the three tasks were generated with the Python programming language (Python Software Foundation, https://www.python.org/). The procedure to create each image for the different experimental conditions for the first task was the following: two randomly generated white noise images (650 x 650 pixels), a target image and a background image, were first created and then Fourier transformed to change the slope of the relationship between the log-power spectrum and the log-frequency (i.e., the "Fourier slope") corresponding to our different conditions (background image: slope = -1, -2, -3; target image: slope = background slope ± 0.25; ± 0.5; ±0.75). Concretely, an image contains features that span different scales, from broad (e.g. the homogeneous blue coloration of the sky) to fine details (e.g. sharp contrasts caused by grass). Those features have different spatial frequencies, low frequencies for broad-scale features and high frequencies for fine details, which are processed separately by the visual system (Musel et al., 2013). Measuring the Fourier slope of an image allows us to quantify the relative distribution of those spatial frequencies, which is known to influence visual preferences (see e.g., Nguyen & Spehar, 2021). Details of Fourier slope manipulation are available in the supplementary material.

A negative linear relationship on a log-log plot indicates that the structure of a pattern tends to be scale-invariant and most natural scenes are characterized by a Fourier slope close to a value of -2 (Pouli et al., 2013). However, methods of Fourier slope calculation vary across the literature, and thus any comparison of slope values across datasets must be based on the same calculation. We therefore used our method of Fourier slope calculation to estimate the slope of 4,319 images of the Landscape Pictures dataset (Rougetet, 2020), which contains images of different types of landscapes (e.g. mountain, beach, desert), to confirm the value of

the dominant slope in natural scenes. We found an average slope of -2.39 (SD: 0.31) for those

images.

To generate stimuli, a circular selection with a radius of 80 pixels was selected from a random

location of a target image and superimposed onto a background image at the same random

coordinates. Targets could appear anywhere on the background, as long as they did not get

cropped out of the frame (see Figures 1 and 2A for several examples). To eliminate pixelated

edges, a very slight amount of blur was applied to the target edges. More specifically, a

Gaussian filter (with a standard deviation of 0.5) was applied around the edge of each target

before superimposing it onto the background image. Similarly, Gaussian filtering was applied

to the background image at the target's location to smooth the contours around the target.

This procedure had only a marginal effect on the slope of the power spectrum of the entire

targets/backgrounds. The final shape and dimensions of those stimuli were a square of 650 x

650 pixels. Those dimensions are fixed and do not vary with the monitor size of participants.

Using the same procedure, for the second and third tasks (forced-choice tasks), we created a

second set of stimuli of larger dimensions (650 x 1300 pixels) to contain two targets, one

centered in each half of the stimulus (Figure 3A and 4A). To make the targets conspicuous

(i.e. easily detectable), we outlined them with a dark grey contour (linewidth: 1.5 and pixel

intensity of the grey color: 64). The set of stimuli for the second task was created with a

uniform, grey background (pixel intensity of the grey color: 128) in contrast to the patterned

background of the third task. Here, the colour properties of the grey contour are given on a

uint8 scale where a pixel intensity value of 255 corresponds to white and 0 to black.

For each of the three tasks, we created 5 versions of stimulus images per condition to

introduce variability in the pattern design. The slope value of all five versions was identical,

but the resulting patterns varied in their local pixel arrangement. Thus, in total, task 1 had 18

different conditions (3 levels for the background variable: -1; -2; -3 and 6 levels for the

difference between the background and the target slope: ± 0.25; ± 0.5; ± 0.75), each with 5

versions of the stimulus images, representing a total of 90 unique images. Task 2 had a total

of 78 conditions (1 background slope value: "grey", 2 targets with 6 slope differences each:

±0.25; ±0.5; ±0.75, and 2 sides: left or right), each with 5 stimulus versions, resulting in 390

unique images. Task 3 with a patterned background had a total of 90 conditions (3 background

slope values: -1; -2; -3, 2 targets with 6 slope differences each: ±0.25; ±0.5; ±0.75, and 2

sides: left or right), each with 5 stimulus versions, resulting in 450 unique images. Note that

paired targets were never identical.

Experimental design

Each participant engaged in two tasks: the detection task ("Task 1") and one of the two forced-choice tasks (grey or patterned background; "Task 2" or "Task 3"), which was randomly assigned. The presentation order of the two tasks was counterbalanced between participants.

Task 1: Detection task

$N_{participants}$ = 1,757 (all participants)
N_{trials} = 35,493
Background: patterned, 3 slope values (-1, -2, -3)
Target: 6 values per background
Target display: single, random location

Background: -2
Target: -2.5

Random assignment to one of the preference tasks

Task 2: Preference task

$N_{participants}$ = 981
N_{trials} = 20,440
Background: Uniform gray
Target: 12 values
Target display: paired, centered

Background: Uniform gray
Left target: -1.25 / Right target: -0.25

Task 3: Preference task

$N_{participants}$ = 775
N_{trials} = 16,006
Background: patterned, 3 slope values (-1, -2, -3)
Target : 6 values per background
Target display: paired, centered

Background: -3
Left target: -2.75 / Right target: -2.5

***Figure 1: Overview of the experiment.** For each of the three tasks, the number of participants that completed them and the total number of trials this represents are reported along with the main characteristics of the stimuli. An example of those stimuli is also included.*

Detection task (Task 1)

Each stimulus was displayed at the center of the webpage, one at a time, in a randomized order for a maximum duration of 8,000 ms. The intertrial interval was picked from a uniform distribution between 500 and 2,000 ms (in steps of 1 ms) to avoid habituation (see e.g. Geer, 1966). The task contained 21 trials, which correspond to the number of images seen by each participant. This number was kept low to ensure that participants would complete the

experiment. Each stimulus was randomly picked from the pool of 90 created images and presented only once, except for three of the first ten trials that were repeated at the very end to check for within-participant consistency. At the end of each trial (i.e. after the participant clicked on the stimulus with a mouse or a laptop's touchpad, or when the response time limit had been reached), participants received feedback in the shape of a yellow circle, highlighting the location of the target. Before the test trials, three practice trials were presented to make sure the participant understood the task. Participants were instructed to "Click on the target as fast as possible". The location and time of mouse clicks were recorded and used to define detection rate and response times. Detection rate was computed as the number of trials for which a target was correctly detected (i.e., clicked on) divided by the total number of trials. Response times correspond to the recorded time of a mouse click and could take any value between 0 and 8,000 ms (maximum presentation time). In the absence of a mouse click, the response time of a trial was set to NA.

Forced-choice task (Task 2 or 3)

Stimuli were presented in a randomized order for a maximum duration of 12,000 ms. The intertrial interval was picked from a uniform distribution between 500 and 2,000 ms (in steps of 1 ms). The task contained 21 trials, which correspond to the number of images seen by each participant. Each pair of stimuli randomly picked from the pool of 390 (grey background, Task 2) or 450 (patterned background, Task 3) created images was presented only once, except for three of the first ten trials that were repeated at the very end to check for within-participant consistency. Pairs of stimuli differed in two ways: the background slope values (-1; -2; -3 or a grey background) and the position (left-side or right-side of the image) of the target could take four and two different values, respectively. Importantly, both targets always differed in their slope value. Participants were asked the following question, displayed above the stimuli: "Compare the patterns in the two circles, which one do you prefer?". The location of participants' mouse clicks was recorded and used to determine the preferred pattern.

Preference scores for a target with a specific slope value were expressed as a ranking, computed via the Élő score (using the EloChoice package in R, v0.29.4; Neumann, 2019), an iterative algorithm traditionally used in chess games and that performs pairwise comparisons. Élő scores are now frequently used as a measure of aesthetic value and are well suited for unbalanced designs as is the case in our study (see Tribot et al., 2018; Clark et al., 2018 for similar use; Goodspeed, 2017 for a comparison of different pairwise ranking systems). Briefly, each pair of stimuli is similar to a contest where the preferred stimulus wins points and the non-preferred stimulus loses the same number of points. Importantly, Élő rankings are a relative ranking system, meaning that stimuli with higher Élő scores have a higher probability

of being preferred than stimuli with lower Élő scores. Moreover, Élő scores cannot be
compared across contests that share no common stimuli. Thus, for task 3, Élő scores were
computed separately for each background (i.e., -1, -2, and -3), because pairs of targets were
presented against the same background, and thus inter-background comparisons are not
possible. As in Clark and collaborators (2018), we used the elochoice function with initial Élő
scores set to 0, and *k* set to 100. We ran 1,000 simulations to make sure ratings were stable.
We ran the analysis image-wise, that is, by considering each of the five versions of a stimulus
as an independent condition to account for potential variability between stimulus versions.
Running the same code but by considering all five versions of a stimulus as the same condition
did not yield different results. To ensure we had sufficient trials to have stable Élő scores, we
estimated the minimum number of participants required to achieve stability in ratings using the
raterprog function of the EloChoice package with the ratershuffle argument set to 10 to avoid
a participant order effect. We found that using the data from 378 participants for images with
a grey background (reliability index = 0.57, Figure S2a) and from 263 participants for images
with a patterned background (reliability index = 0.59, Figure S2b) was sufficient to reach stable
ratings (reliability index of 0.6 is interpreted as indicating "good reliability", see Neumann &
Clark, 2019).

Questionnaires
Participants were asked 5 questions before and 2 questions after they performed both tasks.
Questions were demographic in nature and related to education level and frequency of
exposure to visual art (Table S5).

Statistical analyses

All statistical analyses were performed using the software R (R Core Team, 2021, version
4.4.1). We removed participants who did not finish the experiment and participants who took
part in the experiment more than once (IP address verification procedure). In total, we kept
the data of 1,757 participants out of the 2,567 participation events that were recorded (68.6%
of participants). For details on sociodemographic data, see the supplementary material.

For the detection task, we removed 49 trials (0.14% of trials) where responses were faster
than neurophysiological limits (i.e. below 150 ms, see e.g. Thorpe et al., 1996) and therefore
likely correspond to accidental clicking. For the two-alternative forced-choice tasks, we found
no lateral bias in participants' responses: the left target was chosen in 50.5 to 51% of the trials.

In each task, three of the 18 trials (i.e. corresponding to different stimuli) were presented twice,
resulting in a total of 21 trials. Responses to the second presentation of those three repeated

trials were compared to those from the first presentation by performing paired comparisons
with t-tests. This procedure allows for checking internal consistency without dramatically
lengthening the experiment. For the detection task, we found no difference for the detection
rate, as defined by the number of times the stimulus target was correctly located divided by
the total number of presentations of the stimulus (t = -0.8238, df = 177.16, p = 0.4112). We
found the response time for the second repetition (mean: 1,577) to be faster than for the first
repetition (mean: 1,733) (t = -6.7704, df = 13147, p < 0.0001), suggesting participants were
improving in this aspect of the task. For the preference tasks, we found no difference between
the first and second presentation of the three repeated trials in terms of preferred stimulus,
neither for the grey background (t = 0.5223, df = 7754, p = 0.6015), nor for the patterned
background (t = 0.2833, df = 6034, p = 0.7770). Further analyses for all tasks were conducted
on the non-repeated trials only.

For the detection task, we first assessed detection success by fitting participants' responses
with a linear mixed-effects binomial model. The response variable is binary, with 1
corresponding to a detected target and 0 to a missed target. To investigate variation in
response times across conditions, we fitted a second generalised linear model with a gamma
distribution for the target-detected trials only. For both models, independent variables included
the slope of the background, the absolute difference between the target slope and the
background slope, and the interaction of both variables. Three random effects were also
added: the stimulus displayed (*1|Stimulus*), the condition tested (*1|Condition*), and the
participants' anonymised identifier (*1|Participant*).

For the preference tasks, we fitted the data with linear mixed-effects models (*lme4* package,
Bates et al., 2015) using maximum likelihood estimation. We first estimated the Élő score for
each image and used those scores as the dependent variable. For Task 2 (with a grey
background), independent explanatory variables (fixed effects) included the slope value of the
target and the quadratic of this variable, shown to be needed when comparing models outputs.
We added the stimulus version (5 versions per stimulus type) as a random effect. There were
in total 60 different images (that is, across conditions and for each stimulus version
separately). For Task 3 (with patterned backgrounds), we ran three similar models for each
background separately. Independent explanatory variables (fixed effects) included the
absolute difference between the background slope and the target slope, the sign of the
difference (positive or negative, coded as 1 and -1, respectively), and their interaction.
Similarly to Task 2, we ran additional models with the slope value of the target and the
quadratic of this variable to estimate the peak of the preference. Again, we added the stimulus

version (5 versions per stimulus type) as a random effect. There were in total 30 different
images per background (that is, across conditions and for each stimulus version separately).

In addition to the Élő score approach described for Tasks 2 and 3, we replicated the analyses
using alternative methods based on linear mixed-effects binomial models. Data for those
binomial models correspond to the individual participants' responses. For both tasks, these
models yielded qualitatively similar results (see Supplementary Methods).

Data and code availability

334 A GitLab repository contains the code to reproduce the stimuli and the images used for the
335 online experiment in high resolution, the preprocessed data and the code to reproduce the
336 main analyses and figures: [link to the repository].

Results

Task 1: Detection task
The goal of the first task was to validate that our method effectively generated perceptually
meaningful variation in background-matching. We predicted that targets with a Fourier slope
closer to the slope of the background would be less frequently detected and require more time
to detect. Results confirmed this prediction: targets with slopes more similar to the background
(smaller slope difference value) were the hardest to find (lower detection rates and higher
response times, Figure 2B and C, Tables S1a and S1b). Targets presented against the
steepest background slope (BKG -3) were easier to detect compared to other background
conditions (BKG -1 and BKG -2) (Figure 2B). This is likely because on backgrounds with a
Fourier slope of -3, more of the spectral power (contrast) is concentrated in lower spatial
frequencies: the pattern of dark and light is more coarse-grained. As a result, phase-
mismatches at the target's edge are clearer than on finer-grained backgrounds (e.g. slopes of
-2 or -1). In simple terms, on coarse-grained backgrounds there are larger areas of dark and
light so, even if the target has the same coarse-grained pattern, there is a greater chance of
light areas on the target lying on, or next to, dark areas of the background, and likewise for
dark on light. Nevertheless our results confirm that, at least with BKG -1 and BKG -2, we
successfully generated perceptually meaningful variation in background-matching across
stimuli.

Figure 2: Detection task. *(A) Examples of the presented stimuli with target values indicated below*

each image. The Fourier slope, always negative, is steeper for images with more low spatial

 frequency features, such as luminance variation extending over several pixels. (B) Detection

probabilities for the different conditions, computed as the number of trials for which the target was

detected divided by the total number of presented trials. Error bars correspond to 95% confidence

intervals around the mean (represented by a full dot). Background slope values are color-coded: blue

for -1, orange for -2, and grey for -3. Dashed lines represent a quadratic fit to the data for each

background separately (-1, -2, and -3). Arrows indicate the corresponding background value. (C)

Reaction times (ms) for detected trials of the different conditions. Box plots indicate the amount of

within-condition variation in reaction times. Background slope values are color-coded: blue for -1,

orange for -2, and grey for -3.

Task 2: Forced-choice task to assess preference for natural statistics in abstract visual patterns

Our second task tested whether the patterns we generated for the targets in the first task also varied in their attractiveness against a grey background. Targets with differing Fourier slopes elicited markedly different preferences (Figure 3C). The resulting Élő score rankings can be fitted with a simple quadratic model (ranking ~ slope + slope²), which predicts a preference peak for a target slope of -2.36, with 95% CIs [-2.33, -2.39] (fit adjusted R^2: 0.9136, Table S2). This preference peak is similar to the preferred peak value reported in previous studies (see e.g. Spehar et al., 2015) and also to the dominant Fourier slope of the natural visual environment, which is typically between -1.81 and -2.4, depending on the study (Pouli et al., 2013). As noted above, when computing the Fourier slope of a large dataset of landscape pictures, we found an average Fourier slope of -2.39 (SD: 0.31), a value very similar to the preference peak inferred from Task 2 (-2.36). Thus, our results further corroborate the general finding that people prefer images with the Fourier slope of natural scenes. Combined with those from the detection task, our results validate the use of the Fourier slope to manipulate both the effective level of background-matching and the attractiveness of stimuli. They also indicate a baseline pattern preference that must be accounted for when considering a preference for background-matching stimuli in Task 3.

Figure 3: Preference task on grey background. *(A) Example of a presented stimulus. Target slopes are -1.25 for the left target and -0.25 for the right target. In this example, we expected participants to prefer the left target. For display reasons, the background color here is lighter than that of the stimuli used in the experiment (see Methods). (B) Measurement of the typical Fourier slope of natural images. Log-log plot of the averaged power spectrum from which the Fourier slope of an image is derived (red regression line), here representing the averaged Fourier slope of images from the Landscape Pictures dataset. (C) Élő rankings for the two-alternative forced choice (AFC) task with a grey background. Each condition (i.e. target slope value) is represented by five closed circles (made more visible using jittering) corresponding to five different stimuli versions. Dots indicate the mean ranking values for each of the five stimuli versions of each condition (indicated on the x-axis). Box plots give the variability of preference scores across those versions. The boxplot central line indicates the median, the hinges the 25th and 75th percentiles, and the upper (lower) whiskers extend from the hinge to the largest (smallest) value no further than 1.5 * IQR (inter-quartile range, or distance between the first and third quartiles) from the hinge. The dotted line indicates a quadratic fit of the data.*

Task 3: Forced-choice task to assess the attractiveness of background-matching patterns.

In our third task, we assessed the attractiveness of patterns that varied in their degree of background-matching. Because they were clearly outlined, all targets were assumed to be equally conspicuous, and we assessed participants' preferences for different levels of background-matching with a two-alternative forced choice (2-AFC) task.

Running separate linear mixed-models for each background to investigate a background-
matching effect, we found similar trends for backgrounds -1 and -3. We found a significant
interaction between the absolute slope difference value (background - target) and the sign of
that difference (see Tables S3a-c for statistical details), meaning that preference increases
with greater background-matching (smaller difference between the background slope and the
target slope) when the sign of the difference is negative, but decreases when the difference is
positive (Figure 4B).
For background -2, the absolute slope difference value and the sign of that difference are both
independently significant (no interaction). Here, preference increased with greater
background-matching, and preferences were higher when the difference between the slope of
the target and the background was positive.
Those results, especially for backgrounds -1 and -3, suggest the presence of an additional
effect to background-matching.
424
We thus tested for a preference for natural statistics in Task 3, which would translate as a
preference for targets with a slope closer to -2.39. We ran separate quadratic models for each
background (ranking ~ slope + slope²) to estimate the target slope value with the highest
ranking against each background. (Tables S4a-c). For background -1, preference peaked at
a target slope of -2, with 95% CIs [-1.71, -2.7]. For background -2, the preferred target slope
was -2.14, with 95% CIs [-2.11, -2.18]. For background -3, it was -2.48, with 95% CIs [-2.61, -
2.24]. Thus, confidence intervals for backgrounds -1 and -3 included the average Fourier slope
value of natural scenes (-2.39), indicating that this well-established preference only appears
when presented against certain backgrounds. Confidence intervals for background -2 did not
include the average Fourier slope of natural scenes. Indeed, there was no overlap between
the confidence intervals for backgrounds -2 and -3, indicating different preference peaks for
these two backgrounds., The fact that preferences peaked at different maxima depending on
the background, and that these peaks were shifted away from -2.39 toward the value of the
background, confirms that background-matching is an important factor in shaping pattern
preferences.
440
441
442
443

Figure 4. Preference task on a patterned background. *(A) Examples of the presented stimuli with target values indicated below each image. (B) Élő rankings for the 2-AFC task with a patterned background. Each condition (i.e. one combination of background slope and target slope) is represented by five closed circles (made more visible using jittering) corresponding to five different stimulus versions. Box plots give the variability of preference scores across the 5 stimulus versions. The boxplot central line indicates the median, the hinges the 25th and 75th percentiles and the upper (lower) whiskers extend from the hinge to the largest (smallest) value no further than 1.5 * IQR (inter-quartile range, or distance between the first and third quartiles) from the hinge. Background slope values are colour-coded: blue for -1, orange for -2, and grey for -3. Dashed lines represent a quadratic fit to the data for each background separately (-1, -2, and -3), and arrows indicate the corresponding background value.*

Discussion

Our study aimed to test a prediction of the processing bias hypothesis, which proposes that animals prefer efficiently processed stimuli. Because brains are tuned to the statistical patterns of natural scenes (whether through evolution or life experience), stimuli that mimic those patterns should be efficiently processed and therefore, in some sense, "attractive" (Redies et al., 2007; Spehar et al., 2015). Background-matching is one way in which organisms mimic

the spatial statistics of natural scenes; therefore, a processing bias hypothesis predicts that

background-matching patterns should be attractive when detected. We developed an online

experiment to test that prediction, by estimating preferences for stimuli that varied in the

degree of background-matching while holding conspicuousness constant. Our results

constitute two main findings. First, they corroborate previous studies showing a clear

preference for the average Fourier slope of natural scenes (Task 2). Second, they

demonstrate that this preference can be modified, shifting toward the pattern of the

background (Task 3). Whether and how a preference for natural scene statistics drives the

evolution of animal signaling is discussed.

Evidence for a processing bias

Results of the first task demonstrated our ability to generate variation in background-matching

across stimuli, by manipulating the Fourier slope of abstract patterns. Stimuli in which the

Fourier slope of the circular target more closely matched the slope of the background were

located less frequently by participants and took longer to detect. Our results thus align with

previous studies showing a link between Fourier slope and background-matching

effectiveness. For instance, performing a spectral analysis of octopus patterns, Josef and

colleagues (2012) found that octopuses adapt their background-matching pattern to specific

features of their environment by imitating the Fourier slope of nearby structures. In cuttlefish,

the Fourier slope of an animal's pattern better matches its background when hiding from

predators or prey compared to when signalling (Zylinski et al., 2011). Our results complement

these correlational studies, showing that the Fourier slope can be manipulated to generate

variation in the detectability of background-matching stimuli. We note that, in addition to the

neural coding of the observer, absolute properties of the background also affect how easy it

is to avoid detection through background matching. For example, a phase mismatch between

target and background (manifested as a clear edge to the target) is harder to detect on

backgrounds where more of the spectral power is at high spatial frequencies. In Figure 2, the

lowest detection probabilities and longest response times are for background-matching targets

on backgrounds of slope -1 (fine-grained) as compared to a background of -2 and particularly

compared to the coarse-grained background of -3. In other words, a background-matching

target on a fine-grained background is hard to detect wherever it lies, but a background-

matching target on a coarse-grained background may, by chance, lie on or next to a region it

mismatches.

Results of the second task corroborated a preference for the Fourier slope that is typical of

natural scenes, based on a forced-choice task for stimuli of different slopes against a grey

background (see also results with binomial models in Supplementary Material). A preference

for a Fourier slope typical of natural scenes has been reported in numerous studies in
experimental psychology (e.g., Hagerhall et al., 2004; Spehar et al., 2003); here we
corroborate that finding with an unusually large sample size (Figures 1 and 3). In a particularly
compelling study, Spehar and collaborators (2015) showed that the Fourier slope typical of
most natural scenes is not only the most attractive, but also the slope to which people have
the highest visual sensitivity (i.e. absolute detection, discrimination, and contrast sensitivities).
Their result emphasizes the influence of efficient processing on visual preferences: patterns
whose properties coincide with visual sensitivity are processed more efficiently by the visual
system and are generally preferred over patterns that are more dissimilar to visual sensitivity
peaks. A preference for natural scene statistics is also consistent with the processing bias
hypothesis (Renoult & Mendelson, 2019), and it can explain a large body of results in empirical
aesthetics, which show that visual artwork imitates natural spatial statistics (Graham & Field,
2008; Graham & Redies, 2010). For example, faces painted by portrait artists across time and
cultures tend to have a Fourier slope value approximating that of natural landscapes even
though real faces typically do not, suggesting that artists increase the attractiveness of their
work by unconsciously mimicking the spatial statistics of natural scenes (Redies et al., 2007).
514
Results of the third task also confirm a preference for target slopes near -2, that is, for the
Fourier slope typical of natural scenes. However, estimated preference maxima also revealed
that this preference is additionally modulated by the background slope, indicating a preference
for patterns that more closely match the pattern of the background. Our results therefore
support the processing bias hypothesis and also highlight a potential interaction between
absolute and relative preferences for stimuli that match the spatial statistics of visual scenes.
An absolute preference for natural statistics would be determined by the general, "hard-coded"
adaptation of neuronal sensitivities to the average spatial statistics of natural scenes, or by
the long-term tuning of neuronal sensitivities to these statistics during early development
(Sengpiel et al., 1999); whereas, a relative preference, corresponding to a preference for
patterns that match the local background, would be determined by the short-term, plastic
tuning of neuronal sensitivity. Both preferences have been demonstrated in the literature (e.g.
Menzel et al., 2015; Spehar et al., 2015); here, we find evidence for both in a single
experiment. We found an absolute preference for patterns with the average Fourier slope of
natural scenes and furthermore that this preference can be modified by the visual statistics of
the background against which a stimulus is displayed.
531
532   **Implications for animal preferences**
533

The extent to which these results observed in humans have implications for the ecology of signaling and preferences in other animal species primarily depends on whether a preference for natural statistics exists in non-human animals. The adaptation of the brain to efficiently process natural statistics was first shown in primates and later found in rodents (mice, ferrets: Akerman et al., 2004; Qiu et al., 2021), probably reflecting a general strategy shared across most animals (Baden, 2021; Laughlin, 1981; Troscianko & Osorio, 2023). Indeed, there are known similarities between the early visual systems of humans and those of macaques (Fize et al., 2011), cats (Kang et al., 2009), mice (B. Williams et al., 2021) and birds (W. Clark et al., 2022), and there is strong evidence that tuning of the visual system to the statistics of natural habitats allows efficient information processing in vertebrates (Olshausen & Field, 1997; Simoncelli & Olshausen, 2001) and insects (Laughlin, 1981). Moreover, a substantial body of research on non-human animals suggests a bias for efficiently processed stimuli (reviewed in Renoult & Mendelson, 2019). For example, stimuli with continuous or symmetric surfaces/lines, fractal structures, temporal repetition, or those that are representative of a perceptual category (i.e., prototypical) are both processed more efficiently and preferred by animals compared to stimuli lacking these characteristics.

Recently, Hardenbicker and Tedore (2023) discovered that peacock jumping spiders prefer images with the Fourier slope of natural scenes over two other options. In their study, preference was defined as time spent oriented towards presented stimuli, with greater time indicating greater preference. Inspection time is routinely used to assess preferences in several taxa, including humans, with studies in infants relying on a similar protocol (e.g., Langlois et al., 1991). Taken together, these findings strongly suggest that a preference for natural statistics likely occurs in non-human animals as well as in the participants in our study.

Implications for animal signaling

If preferences can originate as pre-existing perceptual biases for background-matching patterns, this implies that signal patterns will be shaped by the spatial statistics of the environment, i.e., patterns that mimic those statistics will be efficiently processed and therefore attractive (Renoult & Mendelson, 2019). We are not claiming that the attractiveness of a visual scene, camouflage pattern or artwork is necessarily underpinned by the same emotional or physiological state as sexual arousal. A scene or stimulus may be attractive without evoking sexual arousal. The key point is that the valence in each case is positive, eliciting attention and a desire for physical proximity. In the case of sexually arousing stimuli, the animal seeks to mate; in the case of efficiently processed information, the animal seeks to continue processing the stimulus. Efficiently processed signals might also increase attractiveness

through "misattribution", whereby the observer misattributes the pleasure emerging from
efficient processing to the observed object instead (Renoult & Mendelson, 2019). If these
motivations are additive and increase the probability of mate choice, a preference for
background-matching patterns could influence the direction of sexual signal evolution towards
including a background-matching component (Mendelson et al., 2025).

This prediction of the processing bias hypothesis is an extension of "sensory exploitation"
(Ryan et al., 1990) and "sensory drive" (Endler, 1992), which propose that the environment
shapes both sexual signals and preferences. Most examples of sensory drive focus on a bias
for detectability, with animal signals evolving to be more easily detected (Endler & Basolo,
1998), and for particular colours. The African cichlid fish *Pundamilia nyererei,* for example,
lives in an environment with red-shifted light. Females exhibit an increased expression of red-
sensitive photoreceptors that render red stimuli more detectable, and males exhibit more
reddish coloration (Seehausen et al., 2008). Our results suggest that expanding sensory drive
beyond the framework of signal detection, to account for the effect of processing bias once a
signal is detected, can help us understand the evolution of signal patterns in addition to
coloration.

A preference for natural and background statistics in animals also has implications for
signalling strategy. Results of our study suggest that courters should respond behaviourally
or physiologically so that the statistical features of their patterns mimic not only those of the
average natural statistics encountered by the population, but also potentially of the local
background against which they are displaying. And if their sexual signal changes, as in some
fish that change sex during development, individuals might choose an alternative displaying
site that better matches their pattern. Previous studies have shown that animals choose their
display site in relation to their own sexual signals (Endler & Thery, 1996; Fleishman et al.,
2022); however, those studies focus on coloration, showing that animals gain attractiveness
by maximizing contrast with the background and the ambient light. Our results shift the focus
to signal patterns, but predict that for this signal component, animals would benefit from
mimicking spatial statistics of the visual environment. At the very least, if signalling favours
departure of patterns from that of the background (e.g., for detectability), a constraint of
reduced positive valence will need to be overcome. Importantly, matching its pattern with the
background scene does not prevent an animal from being conspicuous: multimodal signaling
and distance-dependence readily allow for the combination of ostentatious features (e.g.,
colors or sounds) with cryptic features (Marshall, 2000; Tullberg et al., 2005; Barnett et al.,
2017). In general, our study aligns with earlier suggestions (Endler, 1992), recently brought

back into focus (Caves et al., 2023), to consider the importance of the visual background in
animal signalling strategies.

Another strategy to leverage the attractiveness of background-matching patterns might be
seasonal variation in detectability. Individuals that are camouflaged most of the year could be
temporarily rendered more attractive by the addition of a detectable feature during the mating
season. Male darter fish (genus *Etheostoma)*, for example, exhibit vivid and species-specific
colours during the breeding season that appear to complement rather than conceal their
underlying background-matching pattern (Kuehne & Barbour, 1983; Page, 1983, Figure 5B).
Indeed, females in at least two species of darters are attracted similarly to conspecific colour
and pattern when these signal components are decoupled (Williams & Mendelson, 2011). An
attractive and conspicuous seasonal addition could thus enhance, and be enhanced by, the
underlying attractiveness of the background-matching pattern.

Processing bias may also play a role in the evolution of defensive signaling. For example,
aposematic signals are typically conspicuous and easily learned by predators, consistent with
efficient processing (e.g., Green et al., 2018). Notably, many of these warning signals are also
attractive to conspecifics of the opposite sex (Rojas et al., 2018), as in the strawberry poison
dart frog *Oophaga pumilio* (Maan & Cummings, 2008) and the red postman butterfly
Heliconius erato (Finkbeiner et al., 2014). Many aposematic patterns in frogs appear as
irregular, rounded blotches, which could be due to developmental constraints, but which could
also be perceived as colourful embellishments of attractive background-matching patterns
(Figure 5C; Galindo Uribe et al., 2014). The attractiveness of aposematic patterns, therefore,
may be due to the ease with which they are processed, with sexual selection and natural
selection similarly aligned in the evolution of warning signals. However, an alternative way to
dissuade receivers (e.g., predators), aside from the vivid coloration typical of aposematic
signals, is to exhibit patterns that generate discomfort, such as patterns that depart from
natural scene statistics. This is indeed what is found in the colour patterns of some Lepidoptera
(Penacchio et al., 2024). Additionally, an aversion or 'visual discomfort' in response to patterns
that depart from natural scene statistics has been found in humans for whom a simple
deviation from the average Fourier slope predicts judgements of discomfort from images
(Penacchio & Wilkins, 2015).

The roles of natural and sexual selection in the evolution of courtship communication

The idea that background matching can be attractive may appear counterintuitive given the
extensive literature documenting conflicts between natural and sexual selection in courtship

communication. Because traditional approaches to understanding the evolution of signal design are based on signal detection, natural and sexual selection are usually pitted in conflict along an axis of detectability, with natural selection favoring crypsis and sexual selection favoring conspicuousness. Guppy fish highlight this tradeoff: females prefer males with brighter and larger orange spots, but the size and color of those spots depend on predator abundance (e.g., Breden & Stoner, 1987; Endler, 1978, 1980; Houde & Endler, 1990). However, while antagonism between these two types of selection is likely common when it comes to detection, this is not necessarily the case for all signal components, especially those processed once detection has occurred, such as the patterns in the current study. Our results suggest that natural and sexual selection can act synergistically for patterns: background-matching patterns may be favored by natural selection because they reduce detectability to predators, and once detected by conspecifics, they also may contribute to enhance a signaller's attractiveness and mating success. In this way, background-matching patterns could be evolutionarily co-opted by sexual selection. For example, if a change of ecological factors reduces predation pressure, a mutation that makes a signaller and its background-matching patterns more easily detectable, for example a conspicuous color, could increase their attractiveness because of the efficiency with which the patterns are processed. Hidden preferences for those efficiently processed patterns thus are predicted to lead to an increase in the frequency of attractive phenotypes if ecological conditions permit (Figure 5).

An important limitation of these implications for natural and sexual selection is that predators and conspecifics often have different visual perception and viewing conditions. Fully characterizing the role of processing bias in the evolution of communication signals under different types of selection requires knowledge of the visual systems of interacting prey and predators. If they are sufficiently different, this reduces the conflict imposed by the two types of receivers, by facilitating the possibility of simultaneously cryptic (to predators) and conspicuous (to conspecifics) signals. On the other hand, these differences also mean that what is perceived as background matching by a predator may not be perceived as such by a potential mate. The distance at which predators and conspecifics view the signal should also be considered, given the known relationship between distance and conspicuousness or camouflage (e.g. Barnett et al., 2017; Marshall, 2000; Tullberg et al., 2005). The patterns examined in this study vary in their Fourier slope, and therefore in their degree of scale invariance, which makes the results relatively robust to small differences in viewing distance and visual acuity. Nevertheless, accounting for the specific psychophysical characteristics of the different receivers will be a crucial (and likely limiting) component for testing these predictions in realistic ecological contexts in animals. Although this might limit the generalization of our results, our study represents a proof of concept where we test the logic

679   by which a bias for efficiently processed stimuli may influence the evolution of signaling
680   strategies.
681
In sum, we provide robust evidence for a preference for patterns matching the average image
statistics of natural scenes, and that this preference can be influenced by the pattern of the
background against which a stimulus is viewed. Although demonstrated here only in humans,
this result is expected to generalize to other species. By providing evidence of a processing
bias, the key mechanism by which background-matching patterns can be co-opted to function
as sexual signals, this study highlights the importance of considering the psychological
landscape (Guilford & Dawkins, 1991) of signal receivers, and of interfacing research in
evolutionary biology with the vast literature in human cognitive psychology.
690

Figure 5. Evolution from background-matching to sexual signalling through the exploitation of processing bias. Panel A: 1. Natural selection due to predation generally results in inconspicuous phenotypes. Phenotypes with a pattern that matches that of the environment ('inconspicuous pattern') are well-camouflaged and thus gradually increase in frequency in the population. Such phenotypes typically do not elicit strong preferences among conspecifics because of their low detectability. *2.* Any new mutation increasing conspicuousness should be negatively selected by predation (low survival). However, because they are highly detectable by potential mates and thus reduce their cost of mating, or if they enhance sexual arousal, these phenotypes are potentially attractive. Among conspicuous phenotypes, background-matching patterns that match the visual structure of the habitat ('conspicuous patterned') should be preferred (ΔP) over those that do not ('conspicuous plain') because they are even more efficiently processed. In this study, we have provided the first empirical evidence supporting this prediction. *3.* These 'sleeping beauties' would remain negatively selected by natural selection until a

change in ecological factors (e.g., colonization of habitats or regions with fewer predators, the appearance of new, alternative prey, predators' focus on new sensory cues) makes sexual selection strong enough to counteract the effects of predation on phenotype evolution **4**. *Thus, conspicuous phenotypes that have evolved from background-matching patterns can be evolutionarily co-opted by sexual selection.* **Lower panels***: Examples of background-matching patterns underlying conspicuous color and patterns. B:* Etheostoma caeruleum *(Julien Renoult). C:* Ranitomeya reticulata *(DH Fischer). D: Painting of a peacock* (Pavo cristatus) *hidden in a tree by Abbott H. Thayer. Thayer, a naturalist painter of the 18th century, explored the idea that the primary function of animal patterns is camouflage. Although widely criticized at the time, Thayer's idea is consistent with the proposed framework, that even the most canonical nuptial patterns can evolve from, and continue to function at least in part as, camouflage. (Abbott Handerson Thayer, Richard S. Meryman, Peacock in the Woods, study for book Concealing Coloration in the Animal Kingdom, 1907, oil on canvas, Smithsonian American Art Museum).*

Acknowledgement

This work was supported by the National Science Foundation grant NSF IOS 2026334.

References

Barlow, H. B., 'Possible Principles Underlying the Transformations of Sensory Messages', in Walter A. Rosenblith (ed.), *Sensory Communicatio*n (Cambridge, MA, 2012; online edn, MIT Press Scholarship Online, 22 Aug. 2013), https://doi.org/10.7551/mitpress/9780262518420.003.0013

Akerman, C. J., Grubb, M. S., & Thompson, I. D. (2004). Spatial and Temporal Properties of Visual Responses in the Thalamus of the Developing Ferret. *Journal of Neuroscience*, *24*(1), 170–182. https://doi.org/10.1523/JNEUROSCI.1002-03.2004

Allen, W. L., Cuthill, I. C., Scott-Samuel, N. E., & Baddeley, R. (2010). Why the leopard got its spots: Relating pattern development to ecology in felids. *Proceedings of the Royal Society B: Biological Sciences*, *278*(1710), 1373–1380. https://doi.org/10.1098/rspb.2010.1734

Baden, T. (2021). Circuit mechanisms for colour vision in zebrafish. *Current Biology*, *31*(12), R807–R820. https://doi.org/10.1016/j.cub.2021.04.053

Barlow, H. B. (1961). Possible Principles Underlying the Transformations of Sensory Messages. In W. A. Rosenblith (Ed.), *Sensory Communication* (pp. 216–234). The MIT Press. https://doi.org/10.7551/mitpress/9780262518420.003.0013

Barnett, J. B., Cuthill, I. C., & Scott-Samuel, N. E. (2017). Distance-dependent pattern blending can camouflage salient aposematic signals. *Proceedings of the Royal Society B: Biological Sciences*, *284*(1858), 20170128. https://doi.org/10.1098/rspb.2017.0128

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software*, *67*, 1–48. https://doi.org/10.18637/jss.v067.i01

Breden, F., & Stoner, G. (1987). Male predation risk determines female preference in the Trinidad guppy. *Nature*, *329*, 831–833. https://doi.org/10.1038/329831a0

Caves, E. M., Davis, A. L., Nowicki, S., & Johnsen, S. (2023). Backgrounds and the evolution of visual signals. *Trends in Ecology & Evolution*, *0*(0).

https://doi.org/10.1016/j.tree.2023.09.006

Chun, M. M., & Potter, M. C. (1995). A two-stage model for multiple target detection in rapid

serial visual presentation. *Journal of Experimental Psychology: Human Perception*

and Performance, *21*(1), 109–127. https://doi.org/10.1037/0096-1523.21.1.109

Clark, A. P., Howard, K. L., Woods, A. T., Penton-Voak, I. S., & Neumann, C. (2018). Why

rate when you could compare? Using the "EloChoice" package to assess pairwise

comparisons of perceived physical strength. *PLOS ONE*, *13*(1), e0190393.

https://doi.org/10.1371/journal.pone.0190393

Clark, W., Chilcott, M., Azizi, A., Pusch, R., Perry, K., & Colombo, M. (2022). Neurons in the

pigeon visual network discriminate between faces, scrambled faces, and sine grating

images. *Scientific Reports*, *12*(1), Article 1. https://doi.org/10.1038/s41598-021-

04559-z

Coss, R. G., Ramakrishnan, U., & Schank, J. (2005). Recognition of partially concealed

leopards by wild bonnet macaques (*Macaca radiata*). *Behavioural Processes*, *68*(2),

145–163. https://doi.org/10.1016/j.beproc.2004.12.004

Cummings, M. E., Rosenthal, G. G., & Ryan, M. J. (2003). A private ultraviolet channel in

visual communication. *Proceedings of the Royal Society of London. Series B:*

Biological Sciences, *270*(1518), 897–904. https://doi.org/10.1098/rspb.2003.2334

Cuthill, I. C. (2019). Camouflage. *Journal of Zoology*, *308*(2), 75–92.

https://doi.org/10.1111/jzo.12682

de Leeuw, J. R. (2015). jsPsych: A JavaScript library for creating behavioral experiments in

a Web browser. *Behavior Research Methods*, *47*(1), 1–12.

https://doi.org/10.3758/s13428-014-0458-y

Endler, J. A. (1978). A Predator's View of Animal Color Patterns. In M. K. Hecht, W. C.

Steere, & B. Wallace (Eds.), *Evolutionary Biology* (pp. 319–364). Springer US.

https://doi.org/10.1007/978-1-4615-6956-5_5

Endler, J. A. (1980). Natural Selection on Color Patterns in Poecilia Reticulata. *Evolution*,

34(1), 76–91. https://doi.org/10.1111/j.1558-5646.1980.tb04790.x

Endler, J. A. (1992). Signals, Signal Conditions, and the Direction of Evolution. *The*

American Naturalist, *139*, S125–S153. https://doi.org/10.1086/285308

Endler, J. A., & Basolo, A. L. (1998). Sensory ecology, receiver biases and sexual selection.

Trends in Ecology & Evolution, *13*(10), 415–420. https://doi.org/10.1016/s0169-

5347(98)01471-2

Endler, J. A., & Thery, M. (1996). Interacting Effects of Lek Placement, Display Behavior,

Ambient Light, and Color Patterns in Three Neotropical Forest-Dwelling Birds. *The*

American Naturalist, *148*(3), 421–452. https://doi.org/10.1086/285934

Fantz, R. L. (1957). Form preferences in newly hatched chicks. *Journal of Comparative and*

Physiological Psychology, *50*(5), 422–430. https://doi.org/10.1037/h0044973

Field, D. J. (1987). Relations between the statistics of natural images and the response

properties of cortical cells. *Journal of the Optical Society of America. A, Optics and*

Image Science, *4*(12), 2379–2394. https://doi.org/10.1364/josaa.4.002379

Finkbeiner, S. D., Briscoe, A. D., & Reed, R. D. (2014). Warning signals are seductive:

Relative contributions of color and pattern to predator avoidance and mate attraction

in Heliconius butterflies. *Evolution*, *68*(12), 3410–3420.

https://doi.org/10.1111/evo.12524

Fize, D., Cauchoix, M., & Fabre-Thorpe, M. (2011). Humans and monkeys share visual

representations. *Proceedings of the National Academy of Sciences*, *108*(18), 7635–

7640. https://doi.org/10.1073/pnas.1016213108

Fleishman, L. J., Perez-Martinez, C. A., & Leal, M. (2022). Can Sensory Drive Explain the

Evolution of Visual Signal Diversity in Terrestrial Species? A Test with Anolis Lizards.

The American Naturalist, 000–000. https://doi.org/10.1086/720267

Galindo Uribe, D., Sunyer, J., Hauswaldt, S., Amézquita, A., Proehl, H., & Vences, M.

(2014). Colour and pattern variation and Pleistocene phylogeographic origin of the

strawberry poison frog, Oophaga pumilio, in Nicaragua. *Salamandra*, *50*, 225–235.

Geer, J. H. (1966). Effect of interstimulus intervals and rest-period length upon habituation of

the orienting response. *Journal of Experimental Psychology*, *72*(4), 617–619.

https://doi.org/10.1037/h0023760

Geller, H. A., Bartho, R., Thömmes, K., & Redies, C. (2022). Statistical image properties

predict aesthetic ratings in abstract paintings created by neural style transfer.

Frontiers in Neuroscience, *16*, 999720. https://doi.org/10.3389/fnins.2022.999720

Goodspeed, R. (2017). Research note: An evaluation of the Elo algorithm for pairwise visual

assessment surveys. *Landscape and Urban Planning*, *157*, 131–137.

https://doi.org/10.1016/j.landurbplan.2016.06.009

Graham, D., & Field, D. (2008). Statistical regularities of art images and natural scenes:

Spectra, sparseness and nonlinearities. *Spatial Vision*, *21*(1–2), 149–164.

https://doi.org/10.1163/156856807782753877

Graham, D., & Redies, C. (2010). Statistical regularities in art: Relations with visual coding

and perception. *Vision Research*, *50*(16), 1503–1509.

https://doi.org/10.1016/j.visres.2010.05.002

Green, N. F., Urquhart, H. H., van den Berg, C. P., Marshall, N. J., & Cheney, K. L. (2018).

Pattern edges improve predator learning of aposematic signals. *Behavioral Ecology*,

29(6), 1481–1486. https://doi.org/10.1093/beheco/ary089

Guilford, T., & Dawkins, M. S. (1991). Receiver psychology and the evolution of animal

signals. *Animal Behaviour*, *42*(1), 1–14. https://doi.org/10.1016/S0003-

3472(05)80600-1

Hagerhall, C. M., Purcell, T., & Taylor, R. (2004). Fractal dimension of landscape silhouette

outlines as a predictor of landscape preference. *Journal of Environmental*

Psychology, *24*(2), 247–255. https://doi.org/10.1016/j.jenvp.2003.12.004

Hardenbicker, M.-C., & Tedore, C. (2023). Peacock spiders prefer image statistics of

average natural scenes over those of male ornamentation. *Behavioral Ecology*,

arad042. https://doi.org/10.1093/beheco/arad042

Henrich, J., Heine, S. J., & Norenzayan, A. (2010). The weirdest people in the world? *The*

Behavioral and Brain Sciences, *33*(2–3), 61–83; discussion 83-135.

https://doi.org/10.1017/S0140525X0999152X

Houde, A. E., & Endler, J. A. (1990). Correlated Evolution of Female Mating Preferences and

Male Color Patterns in the Guppy Poecilia reticulata. *Science (New York, N.Y.)*,

248(4961), 1405–1408. https://doi.org/10.1126/science.248.4961.1405

Josef, N., Amodio, P., Fiorito, G., & Shashar, N. (2012). Camouflaging in a Complex

Environment—Octopuses Use Specific Features of Their Surroundings for

Background Matching. *PLOS ONE*, *7*(5), e37579.

https://doi.org/10.1371/journal.pone.0037579

Kane, S. A., Wang, Y., Fang, R., Lu, Y., & Dakin, R. (2019). How conspicuous are peacock

eyespots and other colorful feathers in the eyes of mammalian predators? *PLOS*

ONE, *14*(4), e0210924. https://doi.org/10.1371/journal.pone.0210924

Kang, I., Reem, R. E., Kaczmarowski, A. L., & Malpeli, J. G. (2009). Contrast Sensitivity of

Cats and Humans in Scotopic and Mesopic Conditions. *Journal of Neurophysiology*,

102(2), 831–840. https://doi.org/10.1152/jn.90641.2008

Kuehne, R. A., & Barbour, R. W. (1983). *The American Darters*. University Press of

Kentucky. https://www.jstor.org/stable/j.ctt130hpj2

Langlois, J. H., Ritter, J. M., Roggman, L. A., & Vaughn, L. S. (1991). Facial diversity and

infant preferences for attractive faces. *Developmental Psychology*, *27*(1), 79–84.

https://doi.org/10.1037/0012-1649.27.1.79

Laughlin, S. (1981). A simple coding procedure enhances a neuron's information capacity.

Zeitschrift Fur Naturforschung. Section C, Biosciences, *36*(9–10), 910–912.

Maan, M. E., & Cummings, M. E. (2008). Female Preferences for Aposematic Signal

Components in a Polymorphic Poison Frog. *Evolution*, *62*(9), 2334–2345.

https://doi.org/10.1111/j.1558-5646.2008.00454.x

Marshall, N. J. (2000). Communication and camouflage with the same 'bright' colours in reef

fishes. *Philosophical Transactions of the Royal Society B: Biological Sciences*,

355(1401), 1243–1248.

Mendelson, T. C., Renoult, J. P., Rosenthal, G. G., & Shuker, D. M. (2025). On the biological

basis of beauty. *Biological Reviews*, *100*(4), 1578–1593.

https://doi.org/10.1111/brv.70014

Menzel, C., Hayn-Leichsenring, G. U., Langner, O., Wiese, H., & Redies, C. (2015). Fourier

Power Spectrum Characteristics of Face Photographs: Attractiveness Perception

Depends on Low-Level Image Properties. *PLOS ONE*, *10*(4), e0122801.

https://doi.org/10.1371/journal.pone.0122801

Merilaita, S., & Stevens, M. (2011). Crypsis through background matching. In M. Stevens &

S. Merilaita (Eds.), *Animal Camouflage: Mechanisms and Function* (pp. 17–33).

Cambridge University Press. https://doi.org/10.1017/CBO9780511852053.002

Munar, E., Gómez-Puerto, G., Call, J., & Nadal, M. (2015). Common Visual Preference for

Curved Contours in Humans and Great Apes. *PLOS ONE*, *10*(11), e0141106.

https://doi.org/10.1371/journal.pone.0141106

Musel, B., Bordier, C., Dojat, M., Pichat, C., Chokron, S., Le Bas, J.-F., & Peyrin, C. (2013).

Retinotopic and Lateralized Processing of Spatial Frequencies in Human Visual

Cortex during Scene Categorization. *Journal of Cognitive Neuroscience*, *25*(8),

1315–1331. https://doi.org/10.1162/jocn_a_00397

Neumann, C. (2019). *EloChoice: Preference Rating for Visual Stimuli Based on Elo Ratings*

(Version 0.29.4) [Computer software]. https://rdrr.io/cran/EloChoice/

Nguyen, L. Y., & Spehar, B. (2021). Visual adaptation to natural scene statistics and visual

preference. *Vision Research*, *180*, 87–95.

https://doi.org/10.1016/j.visres.2020.11.011

Olshausen, B. A., & Field, D. J. (1997). Sparse coding with an overcomplete basis set: A

strategy employed by V1? *Vision Research*, *37*(23), 3311–3325.

https://doi.org/10.1016/S0042-6989(97)00169-7

Page, L. M. (1983). *Handbook of Darters* (First Edition). Tfh Pubns Inc.

Penacchio, O., Halpin, C. G., Cuthill, I. C., Lovell, P. G., Wheelwright, M., Skelhorn, J.,

Rowe, C., & Harris, J. M. (2024). A computational neuroscience framework for

quantifying warning signals. *Methods in Ecology and Evolution*, *15*(1), 103–116.

https://doi.org/10.1111/2041-210X.14268

Penacchio, O., & Wilkins, A. J. (2015). Visual discomfort and the spatial distribution of

Fourier energy. *Vision Research*, *108*, 1–7.

https://doi.org/10.1016/j.visres.2014.12.013

Pouli, T., Reinhard, E., & Cunningham, D. W. (2013). *Image Statistics in Visual Computing*.

A K Peters/CRC Press. https://doi.org/10.1201/b15981

Qiu, Y., Zhao, Z., Klindt, D., Kautzky, M., Szatko, K. P., Schaeffel, F., Rifai, K., Franke, K.,

Busse, L., & Euler, T. (2021). Natural environment statistics in the upper and lower

visual field are reflected in mouse retinal specializations. *Current Biology*, *31*(15),

3233-3247.e6. https://doi.org/10.1016/j.cub.2021.05.017

Reber, R., Schwarz, N., & Winkielman, P. (2004). Processing Fluency and Aesthetic

Pleasure: Is Beauty in the Perceiver's Processing Experience?: *Personality and*

Social Psychology Review. https://doi.org/10.1207/s15327957pspr0804_3

Redies, C., Hasenstein, J., & Denzler, J. (2007). Fractal-like image statistics in visual art:

Similarity to natural scenes. *Spatial Vision*, *21*(1–2), 137–148.

https://doi.org/10.1163/156856807782753921

Renoult, J. P., Bovet, J., & Raymond, M. (2016). Beauty is in the efficient coding of the

beholder. *Royal Society Open Science*, *3*(3), 160027.

https://doi.org/10.1098/rsos.160027

Renoult, J. P., & Mendelson, T. C. (2019). Processing bias: Extending sensory drive to

include efficacy and efficiency in information processing. *Proceedings of the Royal*

Society B: Biological Sciences, *286*(1900), 20190165.

https://doi.org/10.1098/rspb.2019.0165

Rojas, B., Burdfield-Steel, E., De Pasqual, C., Gordon, S., Hernández, L., Mappes, J.,

Nokelainen, O., Rönkä, K., & Lindstedt, C. (2018). Multimodal Aposematic Signals

and Their Emerging Role in Mate Attraction. *Frontiers in Ecology and Evolution*, *6*.

https://doi.org/10.3389/fevo.2018.00093

Rougetet, A. (2020). *Landscape Pictures* (Version 1) [Dataset].

https://www.kaggle.com/datasets/arnaud58/landscape-pictures

Ryan, M. J., & Cummings, M. E. (2013). Perceptual Biases and Mate Choice. *Annual*
Review of Ecology, Evolution, and Systematics, *44*(1), 437–459.
https://doi.org/10.1146/annurev-ecolsys-110512-135901
Ryan, M. J., Fox, J. H., Wilczynski, W., & Rand, A. S. (1990). Sexual selection for sensory
exploitation in the frog Physalaemus pustulosus. *Nature*, *343*(6253), Article 6253.
https://doi.org/10.1038/343066a0
Seehausen, O., Terai, Y., Magalhaes, I. S., Carleton, K. L., Mrosso, H. D. J., Miyagi, R., van
der Sluijs, I., Schneider, M. V., Maan, M. E., Tachida, H., Imai, H., & Okada, N.
(2008). Speciation through sensory drive in cichlid fish. *Nature*, *455*(7213), 620–626.
https://doi.org/10.1038/nature07285
Sengpiel, F., Stawinski, P., & Bonhoeffer, T. (1999). Influence of experience on orientation
maps in cat visual cortex. *Nature Neuroscience*, *2*(8), 727–732.
https://doi.org/10.1038/11192
Simoncelli, E. P., & Olshausen, B. A. (2001). Natural Image Statistics and Neural
Representation. *Annual Review of Neuroscience*, *24*(1), 1193–1216.
https://doi.org/10.1146/annurev.neuro.24.1.1193
Spehar, B., Clifford, C. W. G., Newell, B. R., & Taylor, R. P. (2003). Universal aesthetic of
fractals. *Computers & Graphics*, *27*(5), 813–820. https://doi.org/10.1016/S0097-
8493(03)00154-7
Spehar, B., Wong, S., van de Klundert, S., Lui, J., Clifford, C., & Taylor, R. (2015). Beauty
and the beholder: The role of visual sensitivity in visual preference. *Frontiers in*
Human Neuroscience, *9*.
https://www.frontiersin.org/articles/10.3389/fnhum.2015.00514
Thorpe, S., Fize, D., & Marlot, C. (1996). Speed of processing in the human visual system.
Nature, *381*(6582), 520–522. https://doi.org/10.1038/381520a0
Tribot, A.-S., Carabeux, Q., Deter, J., Claverie, T., Villéger, S., & Mouquet, N. (2018).
Confronting species aesthetics with ecological functions in coral reef fish. *Scientific*
Reports, *8*(1), 11733. https://doi.org/10.1038/s41598-018-29637-7

Troscianko, J., & Osorio, D. (2023). A model of colour appearance based on efficient coding

of natural images. *PLOS Computational Biology*, *19*(6), e1011117.

https://doi.org/10.1371/journal.pcbi.1011117

Tullberg, B. S., Merilaita, S., & Wiklund, C. (2005). Aposematism and crypsis combined as a

result of distance dependence: Functional versatility of the colour pattern in the

swallowtail butterfly larva. *Proceedings of the Royal Society B: Biological Sciences*,

272(1570), 1315–1321. https://doi.org/10.1098/rspb.2005.3079

Williams, B., Rosario, J. D., Muzzu, T., Peelman, K., Coletta, S., Bichler, E. K., Speed, A.,

Meyer-Baese, L., Saleem, A. B., & Haider, B. (2021). Spatial modulation of dark

versus bright stimulus responses in the mouse visual system. *Current Biology*,

31(18), 4172-4179.e6. https://doi.org/10.1016/j.cub.2021.06.094

Williams, T. H., & Mendelson, T. C. (2011). Female preference for male coloration may

explain behavioural isolation in sympatric darters. *Animal Behaviour*, *82*(4), 683–689.

https://doi.org/10.1016/j.anbehav.2011.06.023

Supplementary material

List of Supplementary Materials:

Supplementary Text 1: Fourier slope manipulation and estimation

Tables S1a and S1b, Figures S1a and S1b: Outputs of statistical models for Task 1 and graphical representations of their predicted fixed effects

Tables S2a: Output of statistical model for Task 2

Tables S3a, S3b, S3b: Outputs of statistical models for Task 3

Tables S4a, S4b, S4b: Outputs of statistical models for Task 3 (peak estimate)

Supplementary Text 2: Participants' recruitment and experiment questionnaire

Table S5: Experiment questionnaire and response options

Fig. S2a: Ratings stability for the 2-AFC task with a grey background

Fig. S2b: Ratings stability for the 2-AFC task with a patterned background

Supplementary Text 3: Statistical analyses with binomial models and Results of binomial models

Fourier slope manipulation and estimation

To manipulate the Fourier slope of our white noise images, we first converted our image to the Fourier domain using the Fast Fourier Transform function implemented in Python. After normalizing its Fourier transform by its greatest absolute value, we separated the image into a phase matrix and an amplitude matrix. We then estimated the rotational average of the power spectrum for each frequency before estimating the slope of the power spectrum with a linear regression. To create an image with the desired slope, we first generated a residual matrix from the difference between the image and an even amplitude spectrum with the desired slope. We then applied the residuals to an amplitude matrix with the desired slope and applied it to the phase matrix before reconstructing the image with an inverse Fourier transform. The obtained output image now has the desired slope value. To estimate the Fourier slope of an image, we fast Fourier transformed it and computed the rotational average of the power spectrum for all spatial frequencies between 10 and 110 cycles per image. This frequency selection limits edge effects and high-frequency noise. To give equal weight to all frequencies, we also binned (n=20) each power spectrum before estimating the slope value of the averaged power spectrum using a linear regression.

Outputs of statistical models for Task 1

Table S1a: Output of a linear mixed-effects binomial model predicting detection success. Background corresponds to the slope of the background and is defined as a qualitative variable (factor with 3 levels), Slope difference to the absolute difference between the target slope and the background slope, and Background:Slope difference to the interaction of both variables. Significance was estimated with Type II Wald chi-square tests.

Detected_binary ~ Background * Slope difference + (1|Stimulus) + (1|Condition) + (1|Participant)

Random effects:

Groups	Name	Variance	Std. Dev.
Participant	(Intercept)	1.6712	1.2927
Stimulus	(Intercept)	0.8443	0.9188
Condition	(Intercept)	0.4951	0.7036

Number of observations: 35493, groups: Participant, 1748; Stimulus, 90; Condition, 18

Fixed effects:

Parameters	Estimate	Std. Error	z value	p-value
Intercept	-1.64284	0.01308	-125.6	<0.001
Background -3 (reference is -2)	4.98291	0.01038	479.9	<0.001
Background -1 (reference is -2)	-1.57621	0.01372	-114.9	<0.001
Slope difference	5.89397	0.01454	405.3	<0.001
Background -3 (ref -2):Slope difference	-4.63358	0.01037	-446.9	<0.001
Background -1 (ref -2):Slope difference	2.87080	0.01249	229.8	<0.001

1019

1020 **Figure S-1a. Predicted values (marginal effects) for slope difference and background**
1021 **values**, derived from the above-mentioned binomial model (Table S1a) and estimated with
1022 95% CIs.

1023

Table S1b: Reaction times for detected trials only. Output of the linear mixed-effects model
with gamma-distributed reaction times. Background corresponds to the slope of the
background and is defined as a qualitative variable (factor with 3 levels), Slope difference to
the absolute difference between the target slope and the background slope, and
Background:Slope difference to the interaction of both variables. Significance was estimated
with Type II Wald chi-square tests.

1030

1031   Reaction times ~ Background * Slope difference + (1|Stimulus) + (1|Condition) +
1032   (1|Participant)

1033

1034 <u>Random effects:</u>

1035 | Groups | Name | Variance | Std. Dev. |
|---|---|---|---|
1036 | Participant | (Intercept) | 0.02830 | 0.16822 |
1037 | Stimulus | (Intercept) | 0.01001 | 0.10007 |
1038 | Condition | (Intercept) | 0.00330 | 0.05744 |
1039 | Residual | | 0.14068 | 0.37508 |

1040 Number of observations: 27295, groups: Participant, 1725; Stimulus, 90; Condition, 18

1041

1043	Parameters	Estimate	Std. Error	z value	p-value
1044	Intercept	8.14558	0.08027	101.482	<0.001
1045	Background -3 (reference is -2)	-1.17252	0.11272	-10.402	<0.001
1046	Background -1 (reference is -2)	0.39504	0.11388	3.469	<0.001
1047	Slope difference	-1.34011	0.14785	-9.064	<0.001
1048	Background -3 (ref -2):Slope difference	1.16256	0.20828	5.582	<0.001
1049	Background -1 (ref -2):Slope difference	-0.55745	0.20972	-2.658	<0.001

1050

1051

1052   **Figure S-1b. Predicted values (marginal effects) for slope difference and background**

1053   **values**, derived from the above-mentioned model (Table S1b) and estimated with 95% CIs.

1054

Outputs of statistical models for Task 2

Table S2: Linear mixed-effect model for predicting preferences (Élő scores) for stimuli presented against a grey background. Target slope corresponds to the slope value of the target, and (Target slope) ^2 to its quadratic value.

Random effects:

Groups	Name	Variance
Stimulus version	Intercept	1.386e-30
Residual		4.656e+02

Number of observations: 60, groups: Stimulus version, 5

Fixed effects:

	Estimate	Std. Error	df	t value	p-value
Intercept	-216.335	8.880	60	-24.36	<0.001
Target slope	-246.169	10.425	60	-23.61	<0.001
(Target slope) ^2	-52.158	2.533	60	-20.59	<0.001

Outputs of statistical models for Task 3

Table S3a: Linear mixed-effect model for predicting preferences (Élő scores) for stimuli presented against a patterned background with a Fourier slope of -1. Slope difference corresponds to the difference between the slope of the target and the slope of its background. A significant effect indicates a preference for more camouflaged patterns. The absolute value the sign of the value (two levels: + or -) and their interaction are reported.

ranking ~ Value of the slope difference * Sign of the slope difference + (1 | stim_ver)

Random effects:

Groups	Name	Variance	Std. Dev.
Stimulus version	(Intercept)	1.397e-31	3.737e-16
Residual		1.778e+02	1.333e+01

Number of observations: 30, groups: stimulus version, 5

Fixed effects:

	Estimate	Std. Error	df	t-value	p-value
Intercept	31.512	9.109	30	3.460	0.002
Value of the slope difference	-183.233	16.866	30	-10.864	<.001
Sign of the slope difference (1)	-2.539	12.882	30	-0.197	0.845
Value of the slope difference **:** Sign of the slope difference (1)	245.495	23.853	30	10.292	<.001

Table S3b: Linear mixed-effect model for predicting preferences (Élő scores) for stimuli presented against a patterned background with a Fourier slope of -2. Slope difference corresponds to the difference between the slope of the target and the slope of its background. A significant effect indicates a preference for more camouflaged patterns. The absolute value and the sign of the value (two levels: + or -) are reported in separatevariables. For this backgroud, the interaction was not significant and comparison between models with and without the interaction favoured the latter.

ranking ~ Value of the slope difference + Sign of the slope difference + (1 | stim_ver)

Random effects:

1108				
1109	Groups	Name	Variance	Std. Dev.
1110	Stimulus version	(Intercept)	1.447e-31	3.804e-16
1111	Residual		300.3	17.33

1112 Number of observations: 30, groups: stimulus version, 5

1114 Fixed effects:

1115		Estimate	Std. Error	df	t-value	p-value
1116	Intercept	50.263	8.949	30	5.616	<.001
1117	Value of the slope difference	-143.801	15.501	30	-9.277	<.001
1118	Sign of the slope difference (1)	43.276	6.328	30	6.839	<.001

Table S3c: Linear mixed-effect model for predicting preferences (Élő scores) for stimuli
presented against a patterned background with a Fourier slope of -3. Slope difference
corresponds to the difference between the slope of the target and the slope of its background.
A significant effect indicates a preference for more camouflaged patterns. The absolute value
and the sign of the value (two levels: + or -) and their interaction are reported.

ranking ~ Value of the slope difference * Sign of the slope difference + (1 | stim_ver)

Random effects:

1131	Groups	Name	Variance	Std. Dev.
1132	Stimulus version	(Intercept)	1.016e-30	1.008e-15
1133	Residual		557.00	23.60

1134 Number of observations: 30, groups: stimulus version, 5

1136 Fixed effects:

1137		Estimate	Std. Error	df	t-value	p-value
1138	Intercept	84.40	16.12	30	5.235	<.001
1139	Value of the slope difference	-16.53	29.85	30	-0.554	0.584
1140	Sign of the slope difference (1)	-25.81	22.32	30	-1.156	0.2567
1141	Value of the slope difference **:**	-252.95	42.22	30	-5.991	<.001
1142	Sign of the slope difference (1)					

1145 **Table S4a: Linear model for predicting preferences (Élő scores) for stimuli presented**
1146 **against a patterned background with a Fourier slope of -1.** The function poly(variable,
1147 degree=2, raw = TRUE) was used to compute the quadratic value of the slope of the target.
1148
1149   ranking ~ Slope of the target + (Slope of the target) ^2
1150

	Estimate	Std. Error	t-value	p-value
Intercept	-163.47	10.24	-15.967	<.001
Slope of the target	-241.71	25.09	-9.632	<.001
(Slope of the target) ^2	-60.57	12.32	-4.914	<.001

1155
1156
1157 **Table S4a: Linear model for predicting preferences (Élő scores) for stimuli presented**
1158 **against a patterned background with a Fourier slope of -2.** The function poly(variable,
1159 degree=2, raw = TRUE) was used to compute the quadratic value of the slope of the target.
1160
1161   ranking ~ Slope of the target + (Slope of the target) ^2
1162

	Estimate	Std. Error	t-value	p-value
Intercept	-603.94	64.56	-9.354	<.001
Slope of the target	-606.45	68.42	-8.864	<.001
(Slope of the target) ^2	-141.89	17.03	-8.333	<.001

1167
1168 **Table S4a: Linear model for predicting preferences (Élő scores) for stimuli presented**
1169 **against a patterned background with a Fourier slope of -3.** The function poly(variable,
1170 degree=2, raw = TRUE) was used to compute the quadratic value of the slope of the target.
1171
1172   ranking ~ Slope of the target + (Slope of the target) ^2
1173

	Estimate	Std. Error	t-value	p-value
Intercept	-803.13	193.65	-4.147	0.0003
Slope of the target	-711.91	132.52	-5.372	<.001
(Slope of the target) ^2	-143.42	22.04	-6.507	<.001

1178

Participants' recruitment and experiment questionnaire

Recruitment: Participants were recruited through advertisements on dedicated mailing lists and social networks. Participants were not paid, and they had to be at least 16 years old, corresponding to the legal digital majority in the EU. Before the experiment, participants were asked to report their month and year of birth to enforce that rule. For American citizens aged between 16 and 18 years, participants were asked to obtain their parents' verbal approval before they participated in the experiment. Participants were asked to take part in the study only once. On top of informing them of that condition before the experiment. The IP address of the participant was only used to enforce that rule and was not associated with personal information, following a protocol approved by the CNIL. Collected data were stored on-site.

All research was performed following relevant guidelines/regulations. By French legislation, the protocols for this study have been submitted and approved by the French National Commission on Informatics and Liberty (CNIL number 2-21044). The CNIL, an independent public authority affiliated to the European Data Protection Board, is responsible for ensuring that information technology ethically serves the citizen and that it does not infringe on human identity, human rights, privacy or individual or public liberties. The present research is an online experiment with volunteers interacting remotely and anonymously, thus no ethical approval was required—nor possible—from an academic or scientific comity under French legislation, as their recourse is only possible if it is compulsory. The European GDPR (General Data Protection Regulation) was fully applied, and all participants were informed of the subject of the study.

Procedure: At the beginning of an experiment, participants were offered to choose the instruction language between French, English, and Spanish. After agreeing to the study details (consent form) and answering some questions about participants' demographic details (Table S5), the experiment started.

1207 **Table S5: Experiment questionnaire and response options**

1208

Questions	Options
Please indicate what best describes your gender	Female (cis/trans), Male (cis/trans), Non binary, I prefer not to say, Other / I prefer to self-describe
Please indicate your birth date	Year and Month
Do you have uncorrected colour-blindness?	Yes, No
Education: select the option that corresponds to your highest qualification	Graduate Degree, Associate Degree or Bachelor's Degree, High School, Vocational training school certificate, CGE SSCE, PSC no diploma
What is your country of current residency?	List of countries
Does your job or any of your hobbies involve visual artistic activity or visual creation?	Not at all, Sometimes, Often, Daily
How often do you go to art exhibitions (museums, galleries)?	Once a week, Once a month, Once a year, Never

1209

Sociodemographic data

Participants whose data were included in the analysis were 61% women (n=1069), 36% men (n=629), and 3% in other categories (non-binary: 38, prefer to self-describe: 5, prefer not to say: 16). A majority of participants had graduate degrees (66%, n=1162). 35 participants self-reported as color-blind, representing less than 2% of the participants. Most participants were born after 1980, with a peak in the early 2000s, corresponding to undergraduate students who took part in the study as a way to get extra credit. When asked about their hobbies, most participants (82%) reported having hobbies that don't involve visual creativity or only rarely. Most participants go to art exhibitions once a year or less (82%). Participants were mostly located in France (46%) and in the US (29%), with an additional good representation of Western Europe and Canada. Our participants are therefore WEIRD (from Western, Educated, Industrialized, Rich and Democratic countries as described in Henrich et al., 2010), which was expected given our advertising methods (mostly academic or professional mailing lists in Western countries).

It is possible that certain demographic traits, as well as higher exposure to visual art or creativity, might influence stimulus preferences. Therefore, we looked for potential relationships between demographic variables (age, gender, education level) and the ranking scores, and between visual exposure to art (presence of visual arts activity in jobs or hobbies, and frequency of art exhibition visits) and the ranking scores. For each demographic variable of interest, we computed the ranking score for patterned and grey images for a subset of the data, corresponding to the targeted participants. We then randomly sampled from the whole participant dataset a subset of the same size and computed the ranking for those participants as well (for both patterned and grey images). After making sure the rankings of both subsets (or groups of participants) were normally distributed, we compared them using a t-test. Overall, no difference was found for any of the tested sociodemographic variables.

Ratings stability and reliability index

1236

1237

Figure S2a: Ratings stability for the 2-AFC task with a grey background. *The intersection of the two red*
lines indicates the number of raters needed to achieve the averaged reliability index (avgRI). AvgRI is
measured as the average RI between 400 and 981 participants, for which we can see that ratings have
achieved stability. The obtained avgRI is 0.567, corresponding to 378 raters and to a good reliability
(Neumann and Clark, 2019). This was averaged across all 10 simulations, which correspond to a
randomised order of raters.

1244

1245

1246 ***Figure S2b: Ratings stability for the 2-AFC task with a patterned background***. *The intersection of the*
1247 *two red lines indicates the number of raters needed to achieve the averaged reliability index (avgRI).*
1248 *AvgRI is measured as the average RI between 250 and 775 participants, for which we can see ratings*
1249 *have achieved stability. The obtained avgRI is 0.585, corresponding to 263 raters and to a good reliability*
1250 *(Neumann and Clark, 2019). This was averaged across all 10 simulations, which correspond to a*

1251 *randomised order of raters.*

1252

Statistical analyses with binomial models

In addition to the Élő score approach described in the manuscript for tasks 2 and 3, we replicated the analyses using alternative methods based on linear mixed-effects binomial models. Data for those binomial models correspond to the individual participants' responses. A description of each of the included variables and of the model predictions is included for each task, followed by the tables of results.

In task 2, the goal was to test for a general preference for natural statistics. The measure of the average Fourier slope value of the Landscape dataset, which comprises 4,319 pictures of various landscapes from different categories (e.g. beaches, forests), revealed that this average is at -2.39, consistent with the range of values usually reported for similar pictures (Pouli et al., 2013). This value was used as a reference when assessing a preference for natural statistics.
A linear mixed-effects binomial model was run on the data. The response variable *bino_click* was defined as a binary variable where 1 indicates that the left target was chosen (i.e. clicked on) and 0 that the right target was chosen. For each side (left and right), we calculated the Manhattan distance between the slope target and -2.39, to quantify "how similar to natural statistics the target is". The explanatory variable was then calculated as the difference between Manhattan distances of the two sides: *[abs(slope_targetL-2.39) - abs(slope_targetR-2.39)]*. We predicted a preference for targets that have a Fourier slope closer to the one found in natural scenes (-2.39). This translates as a negative estimate for that explanatory variable: if the left target slope value is closer to -2.39 than the right target, the difference will be negative, while bino_click should tend towards 1 (click on target left). Three random effects were also included: the stimulus displayed (*1|Stimulus*), the condition tested (*1|Condition*), and the participants' anonymised identifier (*1|Participant*).

In addition, we conducted simulations to compare the ability of the above model to predict preferences when the average slope for natural images varies between 0 and -4 (step: 0.05), rather than being fixed at -2.39. If there is a peak in preference at this natural slope value, we predict the best fit (lowest AIC) for models with slope values around -2.39.

In task 3, we tested the hypothesis of a preference for background-matching stimuli. A linear mixed-effect binomial model was run on the data. The response variable *bino_click* was defined as a binary variable where 1 indicates that the left target was chosen (i.e. clicked on) and 0 that the right target was chosen. Several explanatory variables were included, all of them exploring condition differences between the targets.

The first explanatory variable describes the level of background-matching between a target

and the background. It is calculated as the difference between the two sides of the Manhattan

distance between the target slope and the background slope (the background is the same for

the two sides): *[abs(slope_targetL-slope_background) - abs(slope_targetR-*

slope_background)]. This variable is predicted to yield a negative estimate, translating as a

preference for smaller differences between a target and the background (i.e; higher level of

background-matching): if the left target slope value is closer to the background slope value

than the right target, the difference will be negative while bino_click should tend towards 1

(click on left target).

To control for a general preference for natural statistics, we added the same explanatory

variable as in Task 2 (*[abs(slope_targetL-2.39) - abs(slope_targetR-2.39)]*). We also included

the background's Fourier slope (*factor(background_slope);* categorical variable with three

levels: -1, -2, -3), and the interaction between these two variables in case this preference is

modulated by the background. As for task 2, we expect a negative estimate for the variable

[abs(slope_targetL-2.39) - abs(slope_targetR-2.39)], demonstrating a preference for natural

scene statistics.

Finally, a last explanatory variable was the sign of the difference between the target and the

background (*sign_of_target_background_difference*). It is a three-level categorical variable:

'oo' where the difference sign is the same for both targets, '+-' where the difference between

the left target and the background is positive while it is negative for the right background, and

'-+' where the reverse is true. A difference in the sign of the difference between the target and

its background should not lead to a difference in preferences.

Three random effects were included: the stimulus displayed (*1|Stimulus*), the condition tested

(*1|Condition*), and the participants' anonymised identifier (*1|Participant*).

All continuous variables for both tasks were centered and scaled to improve the fit of the linear

mixed-effect models.

All statistical analyses were performed using the software R (R Core Team, 2021, version

4.4.1). We fitted the data with linear mixed-effects models (*lme4* package, Bates et al., 2015)

with REML set to false.

1315

Model results

Task 2:

bino_click ~ [abs(slope_targetL-2.39) - abs(slope_targetR-2.39)] + (1|Stimulus) + (1|Condition) + (1|Participant)

Random effects:

Groups	Name	Variance	Std. Dev.
Participant	(Intercept)	0.17612	0.4197
Stimulus	(Intercept)	0.07197	0.2683
Condition	(Intercept)	0.00000	0.0000

Number of observations: 20440, groups: Participant, 981; Stimulus, 390; Condition, 39

Fixed effects:

	Estimate	Std. Error	z value	p-value
Intercept	0.01823	0.02402	0.759	0.448
abs(slope of the left target-2.39) - abs(slope of the right target -2.39)	-0.56393	0.02604	-21.656	<0.001 ***

Signif. codes: 0 '***'

As expected, and as found with the Élő score analysis, a significant negative estimate was found for the explanatory variable, indicating that participants preferred targets with a Fourier slope closer to the one found in natural scenes (-2.39).

Simulation: As predicted, the lowest AIC score was found for a reference value of -2.4.

1340

1341 **Task 3:**

1342　　　bino_click ~ [abs(slope_targetL-slope_background) - abs(slope_targetR-

1343　　　slope_background)] + [abs(slope_targetL-2.39) - abs(slope_targetR-2.39)] *

1344　　　factor(background_slope) + sign_of_target_background_difference+ (1|Stimulus) +

1345　　　(1|Condition) + (1|Participant)

1346

1347　Random effects:

Line	Groups	Name	Variance	Std. Dev.
1348	Groups	Name	Variance	Std. Dev.
1349	Participant	(Intercept)	0.1818	0.4264
1350	Stimulus	(Intercept)	0.0592	0.2433
1351	Condition	(Intercept)	0.0000	0.0000

1352 Number of observations: 16006, groups: Participants, 775; Stimulus, 450; Condition, 45

1353

1354　Fixed effects:

Line		Estimate	Std. Error	z value	p-value
1355		Estimate	Std. Error	z value	p-value
1356	Intercept	-0.01187	0.07580	-0.157	0.875582
1357	abs(slope_targetL-slope_background)	-0.13362	0.02146	-6.226	4.77e-10 ***
1358	- abs(slope_targetR-slope_background)				
1359	abs(slope_targetL-2.39)	-0.37656	0.10489	-3.590	0.000330 ***
1360	- abs(slope_targetR-2.39)				
1361	Sign_of_target_background_difference +-	0.07942	0.13884	0.572	0.567316
1362	Sign_of_target_background_difference oo	0.08065	0.08104	0.995	0.319701
1363	abs(slope_targetL-2.39)	-0.45958	0.17175	-2.676	0.007453 **
1364	- abs(slope_targetR-2.39): Background -3				

```
1365    abs(slope_targetL-2.39)                    -0.26846    0.07894    -3.401    0.000672 ***
1366            - abs(slope_targetR-2.39): Background -1
1367    ---
1368    Signif. codes:  0 '***' 0.001 '**'
```

As predicted, a significant negative effect was found for the [abs(slope_targetL-slope_background) - abs(slope_targetR-slope_background)] variable, suggesting the existence of a preference for smaller differences between a target and the background, that is, for higher levels of camouflage matching. Importantly, this effect occurs while controlling for a general preference for a Fourier slope closer to the one found in natural scenes. Similar to task 2, a significant negative effect was also found for the [abs(slope_targetL-2.39) - abs(slope_targetR-2.39)] variable: Participants preferred targets with a Fourier slope closer to the one found in natural scenes (-2.39). Furthermore, this preference significantly interacted with the Fourier slope of the background: the estimate for background -3 is almost twice the estimate for background -1, suggesting that preferences for targets presented against background -3 were higher than for the ones presented against a background of -1. However, such an effect was not true for background -2, here used as the reference value, suggesting that when presented against background -2, targets closer to -2.39 are preferred to targets distant from -2.39, but less so compared to when presented against background -1 or -3. Finally, there was no effect of the sign of the difference between the target slope and the background slope, as expected.