Asynchronous Detection of Erroneous Behaviors in Human-Robot Interaction with EEG:

A Comparative Analysis of Machine Learning Models.

Zhezheng Ren[1,6,7], Xuzhe Xia[2,6,7], Yuzhi Tang[3,6,7], Bo Zhao[4,6], Chun Pang Wong[2,6], Dongsheng Xiao[5,6]*

[1]University of British Columbia, Department of Electrical and Computer Engineering, BC V6T 1Z3, Canada
[2]University of British Columbia, Department of Computer Science, BC V6T 1Z3, Canada
[3]University of Toronto, Department of Computer Science, 40 St George St, Toronto, ON M5S 2E4, Canada
[4]Bank of Montreal, Data & Analytics, Toronto, Canada
[5]University of British Columbia, Department of Psychiatry, Kinsmen Laboratory of Neurological Research, Detwiller Pavilion, 2255 Wesbrook Mall, Vancouver, BC V6T 1Z3, Canada
[6]NeuroPrior AI, Neurointelligence Labs, Vancouver, Canada

[7]These authors contributed equally to this work.

*Correspondence to: Dongsheng Xiao

Address: 2255 Wesbrook Mall, Detwiller Pavilion, Vancouver, B.C. V6T 1Z3, Canada

E-mail: michaelxiao8@gmail.com

Abstract

We present a comparative analysis of two distinct machine-learning models designed to detect asynchronous errors during Human-Robot Interaction (HRI). The models under scrutiny are a customized ResNet model and an ensemble model, both trained and validated using EEG data. The ResNet model is a unique adaptation of the Residual Network, comprising a one-dimensional convolutional layer followed by batch normalization and ReLU activation. It also features a custom Residual Block structure and an adaptive average pooling layer, concluding with a fully connected linear layer for binary classification. The ensemble model, on the other hand, incorporates various machine learning models such as MLP, logistic regression, SVM, random forest, and XGBoost, unified in a pipeline with feature extraction and transformation steps. A critical component of our research is the innovative probability map, which maintains a granularity of 0.1 seconds. This map forecasts the likelihood of forthcoming one-second intervals being classified as either Error or Non-error. Our comparative analysis reveals significant variations in the performance of the two models, both of which exhibit promising results in detecting erroneous behaviors during HRI. We provide detailed validation results, including the accuracy, F1 score, and confusion matrix for each model. This study offers valuable insights into the potential of machine learning in enhancing HRI efficiency and accuracy, indicating promising directions for future research.

Keywords: Human-Robot Interaction, EEG, Machine Learning, ResNet, Ensemble Model

INTRODUCTION

The integration of robotics into everyday life is no longer a fantastical dream but an evolving reality. With robots and artificial intelligence becoming increasingly ubiquitous, the interaction between humans and machines is a field that has garnered significant attention. Human-Robot Interaction (HRI) stands at the intersection of technology, neuroscience, and human psychology, aiming to foster seamless communication between humans and robots(Ayanoğlu & Duarte, 2019; Dautenhahn & Saunders, 2011; Filippini & Merla, 2023; Henschel, 2020; Jost et al., 2020; Okamura et al., 2010; Oliveira et al., 2021).

Historically, the concept of HRI has been romanticized in science fiction literature, such as Isaac Asimov's "Three Laws of Robotics" and even in modern representations like Marvel Comics' robot healthcare companion – Baymax(Bartneck, 2004). Today, the rapid advancements in artificial intelligence and robotics have turned this fiction into tangible applications. Robots are now sharing spaces with humans, collaborating to achieve common goals, and the essence of this interaction lies in understanding and decoding human emotions and intentions(Urakami & Seaborn, 2023; Y. Wang, 2021; Xue et al., 2020).

The challenge of facilitating more natural and intuitive interaction between humans and robots has led to the exploration of human brain activity as a potential source of intrinsic feedback(Kim et al., 2017). By retrieving information from electroencephalogram (EEG) data, insights into the human mindset and subjective satisfaction with the robot's performance can be obtained(Chiang, 2023; Tonin et al., 2021). This, however, poses tremendous challenges such as the feasibility of recording

and using EEG data under real-world conditions(Protzak & Gramann, 2018), and decoding the

brain asynchronously(Lotte et al., 2018). Addressing these challenges is central to the ongoing

research efforts in the field. The main goal of the present challenge is to develop innovative signal

processing and machine learning approaches for the asynchronous detection of erroneous

behaviors based on single-trial EEG analysis. This involves the training of a machine learning

model to detect the onset of deliberately introduced errors and perform validation using cross-

validation techniques and unlabeled test data.

This study is at the forefront of these efforts, providing a comparative analysis of two distinct

machine-learning models designed to detect asynchronous errors during HRI using EEG data. We

present a customized ResNet model and an ensemble model, both rigorously evaluated and

validated. We further introduce an innovative probability map, offering granularity in forecasting

the likelihood of erroneous behaviors. Our analysis uncovers significant variations in the

performance of the two models, highlighting the potential of machine learning to enhance HRI

efficiency and accuracy.

Our study is further validated by our first-place win in the offline competition. The contributions

of this research can be summarized as: (1) Customized and comparative analysis of ResNet and

ensemble models for error detection in HRI. (2) Introduction of an innovative probability map for

granular forecasting. (3) Significant insights into the potential of machine learning in enhancing

HRI, signaling promising directions for future research.

By successfully intertwining the fields of neuroscience, robotics, and machine learning, this study

sets a precedent for future work in HRI, demonstrating the potential to translate theoretical

concepts into practical applications that can enhance human life and collaboration with robots.

METHODOLOGY

Experiments

The experiment was conducted as part of the IntEr-HRI competition at IJCAI 2023 (https://ijcai-

23.dfki-bremen.de/competitions/inter-hri/), aiming to record a dataset for the detection of event-

related potentials (ERPs) in EEG data(Kueper et al., 2023). The study took place inside the lab of

the SMT department (BB311) at the University of Duisburg-Essen and involved a total of eight

young, healthy subjects.

The subjects performed a flexion-extension task while standing and wearing an active orthosis on

their right arm. This orthosis, designed to move automatically upon the application of small forces,

executed flexion or extension movements with the right arm. Errors were deliberately introduced

during normal operations to study the corresponding ERPs. Variations were introduced for specific

subjects to explore different error positions and feedback mechanisms. The experiment was based

on two primary conditions: (1) Baseline Condition: Subjects executed 15 flexions and 15

extensions under standard conditions, with the orthosis moving between fully extended (-10

degrees) and fully flexed (-90 degrees) positions. (2) Multimodal Condition: The same movements

were executed, but errors were randomly introduced 6 times around specific mean error positions.

Subjects were instructed to squeeze an air-filled ball if they recognized the error. The experiment

included the collection of EEG and EMG data. Errors were manifested through a change of movement direction for 250 ms, and subjects' responses were captured through their interactions with the air-filled ball.

The Brain products LiveAmp64 system was employed for EEG measurements. This system is wireless and utilizes active electrodes. Recordings were performed both wirelessly on the computer and on hardware using an SD-card. The BrainVision Recorder software (V. 1.25.0001) was used for the recording process. A total of 67 channels were used for measurements, including 64 EEG channels and 3 accelerometer channels. The sampling rate was set at 500 Hz, and an Acticap slim cap was used with a 10-20 layout (Ref = FCz, GND = AFz). The maximum impedance level of the electrodes was 5 kOhm, with impedance checks conducted both before and after measurements.

Several event markers were defined for the EEG recordings. The synchronization marker was labeled as "Sync," and the start/stop trigger for EMG was represented by "S1." Movement-related markers included the start of flexion ("S 64"), the start of extension ("S 32"), standard events (mid of movement, no error introduced, "S 48"), error introduction ("S 96"), and button press response ("S 80"). The experimental setup provided a controlled environment to study ERPs related to error detection. By using an active orthosis device and introducing deliberate errors, the dataset captured valuable insights into the underlying cognitive processes. The defined instructions for EEG measurements ensured precise recording and consistent representation of events, contributing to the reliability of the data and the robust foundation for the study's objectives.

EEG signal processing

EEG signal processing is essential in brain-computer interfaces (BCIs) and error-related potential

studies (Gramann et al., 2014). Preprocessing employs a bandpass filter on the raw EEG signals,

with a frequency range of 0.1Hz to 30Hz. The lower limit of 0.1Hz helps to attenuate slow drifts

and artifacts, while the upper limit of 30Hz captures the essential frequency components related to

cognitive activities. Bandpass filtering is vital in EEG signal processing as it reduces noise effects,

focusing on the frequencies where the relevant information resides. This enhancement in the

signal-to-noise ratio (SNR) preserves the information connected to the ERPs, facilitating a more

accurate analysis.

Feature extraction transforms the preprocessed signals into a format that encapsulates the essential

information. The following techniques were utilized: (1) Xdawn(Rivet et al., 2009) is a spatial

filtering method that optimizes the SNR for ERPs, particularly in error detection. It enhances the

discriminability between error and non-error states, offering robust feature representation. (2)

ERPs are neurophysiological responses that reflect cognitive processes like error recognition(Kim

et al., 2023). **Figure 1** presents the visualization for the ERPs in the 10-20 systems in our project.

The P300 component, a positive deflection occurring approximately 300 milliseconds post-event,

is a key feature in error detection. By extracting these specific ERP features, the analysis delves

into underlying cognitive processes, contributing to the precise identification of error-related

activities.

Figure 1. The example of ERPs and data visualization correspond to the average S 96 period of the 10-20 64 channels EEG system.

Machine learning models

Our analysis employs two machine learning models: a customized ResNet and an ensemble model.

We first create the training dataset by slicing out 1s trials of events (64 x 501) from the raw EEG

sets. Both models take a 1s EEG trial (64 x 501) as input and predict it as either Error (S96) or

Non-error (non-S96). A 0.1-30 Hz bandpass filter is applied to EEG raw data using the MNE

package(*Tutorials — MNE 1.4.2 Documentation*, n.d.).

Customized ResNet model: The ResNet model starts with a 1-D convolutional layer, followed

by batch normalization and a ReLU activation. A Residual Block structure is defined, which

consists of two convolutional layers with batch normalization and ReLU activation, as well as a

skip connection path from the input to the output. The residual block is applied once. After passing

through the residual blocks, the output is passed to an adaptive average pooling layer, flattened,

and finally fed to a fully connected linear layer for binary classification. **Figure 2** shows the

architecture for the ResNet model. For training, the data is split into training, validation, and testing

181   sets in a 7:1:2 ratio. The data is first preprocessed with a bandpass filter and subsequently

182   standardized per channel across the entire training data. The model with the best validation loss

183   during training is saved. Its performance is measured on the test set and its confusion matrix is

184   plotted. The model is additionally evaluated using 10-fold cross-validation for each subject.

187
188   **Figure 2.** The architecture for the ResNet model. Conv block presents the 1D Convolution Layer and
189   Gemm shows the Fully Connected Layer. The model has 8610 trainable parameters.
190

Ensemble model: An ensemble of machine learning models comprising MLP, logistic regression,

SVM, random forest, and XGBoost are bundled in a pipeline with feature extraction and

transformation steps. First, Xdawn Covariances(Barachant, n.d.) is applied to estimate the

covariance matrices from the EEG data for each trial. This step applies the xDAWN spatial

filtering method which enhances the signal-to-noise ratio, making it particularly suitable for ERP

analysis. These covariance matrices are then transformed using Tangent Space. **Figure 3** shows

the architecture for the Ensemble model. Because the covariance matrices lie in the space of

Symmetric Positive Definite (SPD) matrices, which are not Euclidean, they are mapped to a

tangent space where classical vector space operations can be performed. This allows the

application of traditional machine learning techniques on the transformed data. The classifiers are

combined into a soft-voting classifier, leveraging the averaged predicted probabilities for final

decision-making. This ensemble model is evaluated using 10-fold cross-validation with the

SMOTE (Synthetic Minority Over-sampling Technique) technique(Chawla et al., 2002) employed

for each fold to oversample the minority class and address the class imbalance. Metrics, including

accuracy, F1 score, and a confusion matrix, are calculated for each fold, visualized, and stored as

text files, with the trained models saved as joblib files.

Figure 3. The architecture for the ensemble model. MLP is the Multilayer perceptron model. SVM is the
Support Vector Machine model and XGBoost is the robust machine-learning algorithm.

Probability Map: The granularity of the probability map maintains a resolution of 0.1 seconds,

and it is designed to forecast the likelihood of one-second intervals being classified either as S96

or non-S96 at the onset of every 0.1-second period. The algorithm achieves this by predicting the

probabilities of the forthcoming one-second interval receiving either the S96 or non-S96 label

and subsequently summing them. Within each 0.1-second interval, the pre-trained model

computes the likelihood of the ensuing one-second period being assigned the S96 or non-S96

label.

RESULTS

Ensemble and ResNet model were employed to detect erroneous behaviors during HRI. The results

of both models are presented in terms of mean and standard deviation, total score, set score, and

the number of true positives.

Performance of Ensemble Model: Table 1 shows the mean and standard deviation of the

Ensemble model for different subjects. The standard deviation values are relatively small,

indicating a consistent performance across the subjects. This consistency can be attributed to the

soft-voting classifier, which neutralizes the individual results of the classifiers within the ensemble.

The sum results in **Table 2** further highlight the efficiency of the Ensemble model, with a total

score of 53804 and an online speed of 1.98 ms/data.

Table 1. The results of 10-fold validation for the Ensemble model and ResNet model (Accuracy)

Subject	AA56D	AC17D	AJ05D	AQ59D	AW59D	AY63D	BS34D	BY74D
								234
Ensemble model (Mean±Std)	0.9622 ± 0.0155	0.9852 ± 0.0181	0.9683 ± 0.0170	0.9832 ± 0.0125	0.9788 ± 0.0135	0.9582 ± 0.0228	0.9760 ± 0.0235	235 0.9878 ± 0.0132 236
ResNet model (Mean±Std)	0.9152 ± 0.0544	0.9501 ± 0.0261	0.9238 ± 0.0292	0.8236 ± 0.0661	0.9633 ± 0.0336	0.8803 ± 0.049	0.9100 ± 0.0534	237 0.9614 ± 0.0268 238

Performance of ResNet Model: The ResNet model's mean and standard deviation values in **Table**

1 reveal a performance that varies across subjects. Although the model achieved commendable

results, there is a noticeable disparity in some cases, signifying room for potential improvement.

The sum results for the ResNet model, presented in **Table 2**, yield a total score of 51001, with a

significantly faster online speed of 0.29 ms/data compared to the Ensemble model.

Table 2. Test dataset results of Ensemble model and ResNet model

	AA56D (sum)	AC17D (sum)	AJ05D (sum)	AQ59D (sum)	AW59D (sum)	AY63D (sum)	BS34D (sum)	BY74D (sum)	Online Speed (ms/data)	Total Score
Ensemble model	8302	7505	11122	8380	6601	4999	2957	3938	1.98	53804
ResNet model	8704	2084	5131	9341	5704	4420	11119	4498	0.29	51001

Comparison of Ensemble and ResNet Models: Figure 4 presents the confusion matrix by using

all of the data. Comparing the results of the Ensemble and ResNet models, the Ensemble model

generally outperforms the ResNet model in terms of mean values and consistency. However, the

ResNet model excels in online processing speed. **Figure 5** presents the example error time point

prediction using the probability map. This calculated probability is then allocated to the imminent

ten data points, each symbolizing a fraction of one-tenth of a second. The algorithm perpetually

revises the maximum probability for each point throughout this process. In the concluding phase,

the algorithm pinpoints the six time points that generate the highest probabilities.

Figure 4. The result of the confusion matrix using all data, A is the result of the confusion matrix by
using the Ensemble model, and B is the result of the confusion matrix by using the ResNet model.

Figure 5. The example error time point prediction using the probability map, the red dotted line indicates
ground truth error time, the blue line indicates the prediction for the Ensemble model, and the black line
indicates the prediction for the ResNet model.

Offline Stage Evaluation: The evaluation of the offline stage competition was conducted based on the comparison of the submitted sample indices against the ground truth. Each of the submitted sample indices (six per set) was converted into corresponding time points in milliseconds and then compared against the reference. The temporal error, defined as the difference in milliseconds, was calculated up to a maximum time point limit (e.g., 3000 ms). If a detection occurred outside this maximum time point, a penalty equivalent to the maximum time point limit was added to the team's total. The error term was summed across all sets and subjects, resulting in a grand total that determined the winners of the competition. This rigorous evaluation process ensured an accurate and fair assessment of the models' capabilities in the offline stage, reflecting their efficiency and effectiveness in detecting error-related potentials.

Offline Stage Results: Tables 3 and **4** provide detailed results of the offline stage, including predicted labels, ground truth labels, set scores, and the number of true positives. **Figure 6** presents the result of the offline stage competition where our method secured first place. The Ensemble model achieved a sum score of 53804 with 48 true positives, while the ResNet model achieved a sum score of 51001 with 52 true positives. It is important to note that the score mentioned here is different from the one presented in **Table 3**. The discrepancy arises from improvements made to the Ensemble model. Specifically, we refined the model by deleting some of the worse-performing individual classifiers within the ensemble, leading to enhanced accuracy and a lower score, indicating better performance.

Table 3. The results of the offline stage include the predicted label and ground truth label for the Ensemble model.

DataSet	Predicted	Ground Truth	Set Score	No. of True Positives
AQ59D_set6	45470, 75920, 83870, 95020, 105870, 116620	30989, 45383, 80984, 94935, 105786, 116483	3306	3
AQ59D_set7	32444, 51294, 62494, 73394, 114194, 119544	20550, 32360, 51188, 62390, 73316, 119470	5074	1
AJ05D_set5	21290, 25740, 51190, 59490, 73540, 94490	29859, 44867, 59376, 73436, 94344, 111985	6000	0
AJ05D_set6	34594, 58044, 98844, 111294, 116794, 130544	34472, 46150, 57921, 98744, 111208, 130666	5122	1
BS34D_set6	39644, 56694, 66894, 72494, 93594, 113694	39528, 56616, 66819, 83440, 93522, 113575	1460	5
BS34D_set5	29868, 40068, 50368, 84018, 89218, 110918	29753, 39928, 50250, 83927, 94285, 110885	1497	5
AW59D_set5	28425, 53625, 72825, 82425, 95075, 104875	28346, 53529, 72696, 82370, 94985, 104723	601	6
AW59D_set6	89920, 115820, 124870, 151470, 156720, 169170	80025, 89766, 99353, 115699, 126243, 151322	6000	0
AA56D_set5	52545, 80595, 94095, 106845, 110545, 123245	38339, 52386, 80472, 93949, 110389, 127213	5156	1

DataSet	Predicted	Ground Truth	Set Score	No. of True Positives
AA56D_set6	41745, 46345, 56245, 76595, 108395, 112445	35438, 45679, 56132, 76437, 92538, 112236	3146	4
BY74D_set5	35958, 45858, 62708, 71708, 98358, 107908	35875, 45760, 55458, 71575, 84799, 107807	2415	4
BY74D_set6	63259, 79809, 99809, 116559, 126709, 147159	63161, 79681, 99674, 116457, 126649, 143375	1523	5
AY63D_set5	58813, 76263, 92213, 100713, 104713, 116163	30827, 44573, 58691, 76108, 104608, 116030	4238	2
AY63D_set6	33947, 48347, 68697, 88947, 106247, 123597	33830, 48181, 68574, 88862, 106121, 123453	761	6
AC17D_set6	42913, 59413, 86063, 99213, 106263, 116063	32985, 42838, 59319, 85930, 99094, 115967	5096	1
AC17D_set5	44941, 49341, 65591, 75941, 85941, 106041	24574, 44832, 65498, 75827, 85830, 105950	2409	4
Sum			53804	48

289 **Table 4. The result of the offline stage includes the predicted label and ground truth label for the**
290 **ResNet model.**

DataSet	Predicted	Ground Truth	Set Score	No. of True Positives

AQ59D_set6	31120, 36170, 81120, 94270, 110720, 115220	30989, 45383, 80984, 94935, 105786, 116483	4267	2
AQ59D_set7	32594, 53794, 73344, 89494, 100894, 119544	20550, 32360, 51188, 62390, 73316, 119470	5074	1
AJ05D_set5	29990, 53490, 59590, 73540, 94540, 118540	29859, 44867, 59376, 73436, 94344, 111985	2645	4
AJ05D_set6	34544, 58044, 91044, 98894, 111294, 130844	34472, 46150, 57921, 98744, 111208, 130666	2486	4
BS34D_set6	54294, 67044, 83494, 93594, 108394, 113694	39528, 56616, 66819, 83440, 93522, 113575	5119	1
BS34D_set5	16668, 29868, 85318, 94518, 106668, 110818	29753, 39928, 50250, 83927, 94285, 110885	6000	0
AW59D_set5	28375, 53625, 72875, 82375, 92725, 104875	28346, 53529, 72696, 82370, 94985, 104723	1461	5
AW59D_set6	80170, 87570, 115770, 126420, 142070, 151420	80025, 89766, 99353, 115699, 126243, 151322	4243	2
AA56D_set5	38495, 52545, 94095, 110595, 123245, 127345	38339, 52386, 80472, 93949, 110389, 127213	3447	3
AA56D_set6	35695, 56295, 62845, 72045, 76595, 110995	35438, 45679, 56132, 76437, 92538, 112236	5257	1

BY74D_set5	35958, 43658, 53808, 72158, 84958, 107908	35875, 45760, 55458, 71575, 84799, 107807	2926	4
BY74D_set6	63309, 79809, 109159, 116609, 126659, 143509	63161, 79681, 99674, 116457, 126649, 143375	1572	5
AY63D_set5	30963, 44813, 59913, 104663, 110913, 116163	30827, 44573, 58691, 76108, 104608, 116030	3509	3
AY63D_set6	33947, 48347, 68697, 89097, 106247, 123597	33830, 48181, 68574, 88862, 106121, 123453	911	6
AC17D_set6	33113, 42913, 59413, 86063, 99313, 112413	32985, 42838, 59319, 85930, 99094, 115967	1649	5
AC17D_set5	24641, 44891, 65591, 75891, 85891, 106041	24574, 44832, 65498, 75827, 85830, 105950	435	6
Sum			51001	52

Figure 6. The result of the offline stage competition showcased our data's achievement in the first place. The figure illustrates the performance rankings and highlights our superior performance in this challenging domain.

The final standings in the offline stage competition are summarized in **Table 5**, which shows the

accumulated scores in milliseconds for the top three teams. Analysis of the competition results

reveals that our team secured first place with an accumulated score of 56132 ms, outperforming

the second and third-place teams by significant margins. The difference in scores between the

top three teams highlights the efficiency and accuracy of our detection models, particularly in the

context of time-constrained error detection. The success in the competition underscores the

effectiveness of our approach, validates the methodologies employed, and represents a

significant milestone in our research into Human-Robot Interaction (HRI).

305 **Table 5. The result of the offline stage competition for the top three teams**

	1st place team	2nd place team	3rd place team
Accumulated Score (ms)	56132	73270	78820

DISCUSSION

In this research, we have studied and compared the Ensemble and ResNet models for detecting

erroneous behaviors during Human-Robot Interaction (HRI). Our findings corroborate with

previous research(Barachant, n.d.; Craik et al., 2019) that Ensemble models, through the use of

soft-voting classifiers, can provide consistent performance across different subjects, making them

suitable for error detection in HRI. However, the ResNet model's superior online processing speed

poses an interesting trade-off between accuracy and real-time responsiveness. This insight aligns

with the growing need for efficient, real-time error detection in adaptive and intuitive robotic

systems. The offline stage competition further validates our approach and demonstrates the

practical applicability of our models. The competition's evaluation methodology, involving the

conversion of sample indices to corresponding time points and calculation of temporal error, has

provided a rigorous assessment of our models' performance. We've managed to improve the

Ensemble model's performance by deleting some of the worst-performing models, leading to a

lower score and better performance. Future work may include further optimization of these models

and exploration of additional ensemble techniques to enhance the detection of error-related

potentials.

Deep learning has significantly revolutionized the way machine learning is perceived in the HRI

domain(Fitz & Romero, 2021; Karoly et al., 2021). Many previous works utilize neural networks

for EEG signal classification, with the majority of the networks CNN-based(Craik et al., 2019).

The primary design features for CNNs are the number of convolutional layers and the type of end

classifier, which is typically a fully connected layer. For example, Lun et al. (Lun et al., 2020)

designed a 5-layer CNN with max-pooling and a fully connected layer for a motor imagination

classification task. Their network is able to obtain State-of-the-art performance on the Physionet

database with 97.28 accuracy. ResNet(He et al., 2016) is a variant of CNN that has been the state-

of-the-art model for image classification in computer vision. By introducing skip connections,

ResNet makes error propagation during training easier. In our work, following the path of existing

works, we designed a lightweight ResNet model for EEG classification. Another line of work

involves expert feature extraction methods for CNN classification. Continuous wavelet

transforms(Mao et al., 2020), Power spectral density(R. Wang et al., 2015), etc. have been used to

extract features for EEG classification. xDawn(Rivet et al., 2009) is a state-of-the-art feature

extractor that is specifically designed for processing ERPs in EEG data. It aims to maximize the

signal-to-noise ratio of the ERP components thus enhancing their detectability. We used the

xDawn algorithm to enhance ERP detectability and used an ensemble of simple classifiers to do

the classification.

CONCLUSION

This study provides valuable insights into the detection of error-related potentials in Human-Robot

Interaction, with a focus on Ensemble and ResNet models. Our models' performance in various

sets and subjects has been rigorously evaluated, and the offline stage competition attests to the

robustness and reliability of our approach. Our research contributes to ongoing efforts in the development of adaptive and intuitive robotic systems, laying the groundwork for more sophisticated, real-time interactions between humans and robots.

DATA AND CODE AVAILABILITY STATEMENT

All the datasets used in this study are available at https://zenodo.org/record/7951044 for training data, and at https://zenodo.org/record/7966275 for testing data. All the source codes of models are available at https://github.com/NeuroPrior-AI/IntEr-HRI-Competition.

AUTHOR CONTRIBUTIONS

ZR: methodology, software, formal analysis, writing—original draft, and visualization. XX: methodology, software, formal analysis, writing—original draft, and visualization. YT: methodology, software, formal analysis, writing—original draft, and visualization. BZ: conceptualization, methodology, software. CPW: investigation, visualization. DX: conceptualization, methodology, resources, investigation, supervision, writing—original draft, and visualization. All authors contributed to the article and approved the submitted version.

ACKNOWLEDGMENTS

We would like to thank all the members of the NeuroPrior AI, Neurointelligence Labs, whose collaboration and dedication have contributed immensely to the success of this work. We are grateful to the organizers of the International Joint Conference on Artificial Intelligence (IJCAI)

Human-Robot Interaction (HRI) Competition for providing the platform to showcase our research.

The authors would also like to acknowledge the support from various funding agencies, colleagues,

and anyone else who contributed to the project.

REFERENCES

Ayanoğlu, H., & Duarte, E. (2019). *Emotional Design in Human-Robot Interaction: Theory,*

Methods and Applications. Springer Nature.

Barachant, A. (n.d.). *MEG decoding using Riemannian Geometry and Unsupervised*

classification. Retrieved July 31, 2023, from

https://citeseerx.ist.psu.edu/document?repid=rep1&type=pdf&doi=753be0d9cf14014b2e6ac

0f9e2a861d9b1468461

Bartneck, C. (2004). *From Fiction to Science-A cultural reflection on social robots*.

http://ir.canterbury.ac.nz/handle/10092/16930

Chawla, N. V., Bowyer, K. W., Hall, L. O., & Kegelmeyer, W. P. (2002). SMOTE: Synthetic

Minority Over-sampling Technique. *Journal of Artificial Intelligence Research*, *16*, 321–

357.

Chiang, K.-J. (2023). *EEG-Based Assessment of Human Cognitive and Affective States in Real-*

World Scenarios. University of California, San Diego.

Craik, A., He, Y., & Contreras-Vidal, J. L. (2019). Deep learning for electroencephalogram

(EEG) classification tasks: a review. *Journal of Neural Engineering*, *16*(3), 031001.

Dautenhahn, K., & Saunders, J. (2011). *New Frontiers in HumanRobot Interaction*. John

Benjamins Publishing.

Filippini, C., & Merla, A. (2023). Systematic Review of Affective Computing Techniques for

Infant Robot Interaction. *International Journal of Social Robotics*, *15*(3), 393–409.

Fitz, S., & Romero, P. (2021). Neural Networks and Deep Learning: A Paradigm Shift in

Information Processing, Machine Learning, and Artificial Intelligence. In R. Rau, R.

Wardrop, & L. Zingales (Eds.), *The Palgrave Handbook of Technological Finance* (pp.

589–654). Springer International Publishing.

Gramann, K., Ferris, D. P., Gwin, J., & Makeig, S. (2014). Imaging natural cognition in action.

International Journal of Psychophysiology: Official Journal of the International

Organization of Psychophysiology, *91*(1), 22–29.

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep residual learning for image recognition.

Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 770–

778.

Henschel, A. (2020). *New approaches to the emerging social neuroscience of human-robot*

interaction [PhD, University of Glasgow]. https://doi.org/10.5525/gla.thesis.81883

Jost, C., Le Pévédic, B., Belpaeme, T., Bethel, C., Chrysostomou, D., Crook, N., Grandgeorge,

M., & Mirnig, N. (2020). *Human-Robot Interaction: Evaluation Methods and Their*

Standardization. Springer Nature.

Karoly, A. I., Galambos, P., Kuti, J., & Rudas, I. J. (2021). Deep learning in robotics: Survey on

model structures and training strategies. *IEEE Transactions on Systems, Man, and*

Cybernetics, *51*(1), 266–279.

Kim, S. K., Kirchner, E. A., Stefes, A., & Kirchner, F. (2017). Intrinsic interactive reinforcement

learning - Using error-related potentials for real world human-robot interaction. *Scientific*

Reports, *7*(1), 17562.

Kim, S. K., Maurus, M., Trampler, M., Tabie, M., & Kirchner, E. A. (2023). Asynchronous

Classification of Error-Related Potentials in Human-Robot Interaction. *Human-Computer*

Interaction, 92–101.

Kueper, N., Chari, K., Bütefür, J., Habenicht, J., Kim, S. K., Rossol, T., Tabie, M., Kirchner, F., & Kirchner, E. A. (2023). EEG and EMG dataset for the detection of errors introduced by an active orthosis device. In *arXiv [cs.HC]*. arXiv. http://arxiv.org/abs/2305.11996

Lotte, F., Bougrain, L., Cichocki, A., Clerc, M., Congedo, M., Rakotomamonjy, A., & Yger, F. (2018). A review of classification algorithms for EEG-based brain-computer interfaces: a 10 year update. *Journal of Neural Engineering*, *15*(3), 031005.

Lun, X., Yu, Z., Chen, T., Wang, F., & Hou, Y. (2020). A Simplified CNN Classification Method for MI-EEG via the Electrode Pairs Signals. *Frontiers in Human Neuroscience*, *14*, 338.

Mao, W.-L., Fathurrahman, H. I. K., Lee, Y., & Chang, T. W. (2020). EEG dataset classification using CNN method. *Journal of Physics. Conference Series*, *1456*(1), 012017.

Okamura, A., Mataric, M., & Christensen, H. (2010). Medical and health-care robotics. *IEEE Robotics & Automation Magazine / IEEE Robotics & Automation Society*, *17*(3), 26–37.

Oliveira, R., Arriaga, P., Axelsson, M., & Paiva, A. (2021). Humor–Robot Interaction: A Scoping Review of the Literature and Future Directions. *International Journal of Social Robotics*, *13*(6), 1369–1383.

Protzak, J., & Gramann, K. (2018). Investigating Established EEG Parameter During Real-World Driving. *Frontiers in Psychology*, *9*, 2289.

Rivet, B., Souloumiac, A., Attina, V., & Gibert, G. (2009). xDAWN algorithm to enhance evoked potentials: application to brain-computer interface. *IEEE Transactions on Bio-Medical Engineering*, *56*(8), 2035–2043.

Tonin, L., Menegatti, E., & Coyle, D. (2021). *Advances in the Integration of Brain-Machine*

Interfaces and Robotic Devices. Frontiers Media SA.

Tutorials — MNE 1.4.2 documentation. (n.d.). Retrieved July 31, 2023, from

https://mne.tools/stable/auto_tutorials/index.html

Urakami, J., & Seaborn, K. (2023). Nonverbal Cues in Human–Robot Interaction: A

Communication Studies Perspective. *J. Hum.-Robot Interact.*, *12*(2), 1–21.

Wang, R., Wang, J., Yu, H., Wei, X., Yang, C., & Deng, B. (2015). Power spectral density and

coherence analysis of Alzheimer's EEG. *Cognitive Neurodynamics*, *9*(3), 291–304.

Wang, Y. (2021). *Modeling human adaptation with game-theoretic intention decoding in human-*

robot interactions.

https://search.proquest.com/openview/bda4fea29dfc26cad52707d0e2b3df06/1?pq-

origsite=gscholar&cbl=18750&diss=y

Xue, T., Wang, W., Ma, J., Liu, W., Pan, Z., & Han, M. (2020). Progress and prospects of

multimodal fusion methods in physical human–robot interaction: A review. *IEEE Sensors*

Journal, *20*(18), 10355–10370.

453