Title: From sensory to perceptual manifold: the twist of neural geometry

Running title: Geometric twist of neural manifolds

Authors: Heng Ma[1#], Longsheng Jiang[2#], Tao Liu[1#], Jia Liu[1*]

Affiliation: [1]Department of Psychology & Tsinghua Laboratory of Brain and Intelligence,

Tsinghua University, Beijing 100084, China; [2]Beijing Academy of Artificial Intelligence (BAAI),

Beijing 100085, China

[#]**Equal contribution**

[*]**Correspondence**: liujiathu@tsinghua.edu.cn

Abstract

To humans, everything is classifiable-big versus small, edible or poisonous, righteous or unjust.

Similarly, at the heart of most machine learning tasks lies the fundamental goal of classification,

yet the enduring challenge of linear inseparability has plagued artificial neural networks since

their inception. Here we asked how biological neural networks tackle this issue by investigating

the geometric embedding of neural manifolds in macaques` V2 during orientation discrimination

of motion-induced illusory contour. Specifically, we constructed a three-dimensional stimulus

space that inherently rendered the orientation classification of these contours as a linear-

inseparable problem. As expected, we identified a sensory manifold, formed by the V2 neuron

population, that faithfully corresponded to this stimulus space. Crucially, this sensory manifold

underwent a series of twist operations, resulting in new axes orthogonal to the original ones.

Within this expanded, high-dimensional perceptual manifold, the problem of linear inseparability

became linearly separable. Computational modeling further revealed that the geometric

transformation from the sensory to perceptual manifold was achieved by neurons exhibiting

nonlinear mixed selectivity and heterogeneous connectivity patterns among them. Taken

together, our findings elucidate how perception arises from sensation from a neural geometry

perspective, enriching our understanding of how cognitive functions derive from underlying

anatomical structure.

Keywords: motion-induced illusory contour; nonlinearly inseparable problem; neural geometry;

nonlinear mixed selectivity; connectivity structure

Introduction

Classification constitutes a core cognitive challenge for both biological and artificial intelligence systems, with the majority of tasks potentially reducible to classification problems (Cover, 1965; Chung et al., 2018; DiCarlo et al., 2012; Bernardi et al., 2020). The primary challenge in classification lies in the prevalence of linearly inseparable problems, where perfectly segregating data points into their respective classes using a linear boundary is infeasible (Minsky & Papert, 1969; Fusi et al., 2016). Therefore, machine learning often resorts to complex, nonlinear decision boundaries to address this issue (Schölkopf & Smola, 2002; Williams & Rasmussen, 2006). Here we asked how biological systems address linearly inseparable problems, which may provide insights for developing new machine learning algorithms.

Here we employed an orientation discrimination task involving motion-induced contours (MIC), wherein moving dots generated an illusory contour at the center of a circular viewing area (Fig. 1A). Specifically, dots in one hemisphere of the viewing area moved coherently in a single direction, whereas those in the opposing hemisphere moved contrarily (Chen et al., 2014; Marcar et al., 2000; Mysore et al., 2006). This symmetrical motion led the dots to either converge or diverge at the center of the viewing area, thus instantaneously forming a left- or right-tilted illusory contour (Fig. 1B). Further, we constructed a three-dimensional stimulus space based on three orthogonal stimulus axes (Lu et al., 2010; Chen et al., 2014; Ma et al., 2021): (1) horizontal versus vertical, (2) outward versus inward, and (3) clockwise or anti-clockwise (Fig. 1C). This resulted in a three-dimensional Euclidean space that embedded the stimulus space within a cylindrical surface (Fig. 1D). Crucially, stimuli sharing the same MIC orientation (e.g., right-titled, red) were interspersed among those with the opposing orientation (i.e., left-tilted, blue), indicating that the classification of MIC orientations presents a linearly inseparable problem within this stimulus space.

Previous neurophysiological studies have revealed that neurons in macaques' V2 show selectivity for cue-invariant MIC orientations (Marcar et al., 2000; Ma et al., 2021), suggesting that what is the linearly inseparable problem in the stimulus space becomes linearly separable when processed by V2 neurons. Here in this study, we recorded neuronal activity in the V2 to elucidate how the

sensory manifold, where MIC orientations remains linearly inseparable akin to the stimulus space,

transforms into the perceptual manifold that affords linear separability. To do this, we utilized the

population coding doctrine to characterize neural manifolds constituted by neuron population

(SueYeon Chung & Abbott, 2021; Seung HS & Lee DD, 2000; DiCarlo & Cox, 2007), an approach

recently applied to various domains such as vision (Froudarakis et al., 2020; Dyballa et al., 2023),

memory (Xie et al., 2022; She et al., 2021), decision (Okazawa et al., 2021; Flesch et al., 2022;

Genkin et al., 2023), navigation (Gardner et al., 2022; Low et al., 2023) and motor execution

(Churchland et al., 2012; Russo et al., 2020; Gallego et al., 2017; Gallego et al., 2018). Specifically,

we first established the correspondence between the sensory manifold and the stimulus space. Then,

we illustrated how twist operations transformed the low-dimensional sensory manifold into the

high-dimensional perceptual manifold by generating new dimensions, where the originally linearly

inseparable problem became linearly separable. Furthermore, the expansion of the neural

manifold's embedding dimensions required neurons exhibiting nonlinear mixed selectivity and

interconnected by heterogeneous connectivity patterns, thereby echoing the longstanding dictum

that structure determines function.

Results

Stimulus space and linearly inseparable problems

Two macaque monkeys were trained to perform an MIC orientation classification task by

executing a saccade towards the corresponding side based on the MIC orientation (Fig. 1A). To

render the classification a linearly inseparable problem, we designed a three-dimensional

stimulus space. For dots in opposing halves, they moved in the opposite directions within a range

of $[0, \pi]$ (e.g., dot I and dot II in Fig. 1B, left), and here we used the horizontal direction (i.e., 0)

and the vertical direction (i.e., $\pi/2$) as the motion axis of HV (i.e., horizontal versus vertical,

Fig. 1C, left). For dots within the same half, one dot (e.g., dot III) either led or trailed another

dot (e.g., dot IV) (Fig. 1B, right), quantifiable as the angular location of dot IV with respect to

dot III, known as motion shearing. The motion shearing operates within a range of $[0, 2\pi]$ and

possesses two independent axes: outward versus inward (OI) and clockwise versus anti-

clockwise (CA). Here we chose the shearing directions of $\pi/4$ (inward and clockwise), $3\pi/4$

(inward and anti-clockwise), $5\pi/4$ (outward and anti-clockwise) and $7\pi/4$ (outward and

clockwise), which are orthogonally constructed by these two axes (Fig. 1C, right). Consequently,

using these three axes of HV, OI, and CA, we constructed a three-dimensional Euclidean space

within which the stimulus space of a cylindrical surface was embedded, with the stimuli utilized

in this study positioned at the vertices of the inner tangent cube of the cylinder (Fig. 1D). Thus,

there were eight global patterns formed by local dot motion, with four patterns exhibiting a right-

tilted contour (No. 1 – No.4, red) and the remaining four left-tilted (No. 5 – No.8, blue).

Crucially, in the stimulus space, stimuli sharing the same MIC orientation (e.g., right-titled, red)

were always interspersed with stimuli exhibiting the opposite orientation (i.e., left-tilted, blue)

(Fig. 1D, for the whole set of stimulus parameters, see Fig. S1A, also see Movie S1 for the 8

stimuli). In essence, this setup created a classification task that was linearly inseparable. Despite

this challenge, both monkeys adeptly performed the task with an accuracy exceeding 90% at

100% dots coherence (Ma et al., 2021).

Figure 1. Overview of Stimulus Space.

(A) Left: the MIC orientation discrimination task; right: A right-titled MIC defined by surrounding moving

dots. Monkeys were trained to make saccades according to MIC orientations. This figure is modified from (Ma

et al., 2021). RF: array population receptive field.

(B) Sample stimulus. The intrinsic dimensions of the stimulus consist of a motion axis (left) and motion

shearing (right). The motion axis represents the direction of dots' symmetric movement, for example, dot I and

II move horizontally. Right: the motion shearing reveals the relative positioning of adjacent dots moving in the

same direction, for example, dot III and IV is $5\pi/4$ in shearing ring, and we define this as outward and anti-

clockwise (see panel C).

(C) Axes of stimulus space. Left: the parameters for the motion axis ranging from $[0, \pi]$; Right: the

parameters for the motion shearing ranging from $[0, 2\pi]$. From these parameters, three orthogonal axes were

extracted: HV (Horizontal vs. Vertical), OI (Outward vs. Inward), and CA (Clockwise vs. Anti-clockwise).

Binary values along each axis were used to generate eight stimuli. Within these three axes, the sample stimulus

(red) is termed as HOA (Horizontal, Outward, and Anti-clockwise).

(D) Stimulus space. The eight stimuli used in the study, each labeled numerically and color-coded based on

their axis locations and MIC orientations (red: right-tilted; blue: left-tilted). It is important to note that the

classification of MIC orientations poses a linearly inseparable problem in this stimulus space.

Sensory and Perceptual manifolds

To investigate how the brain addressed this linearly inseparable problem, we recorded 93

neurons in the V2 of the two monkeys to construct a high-dimension neural space (see Methods).

First, we investigate how the stimulus space was encoded at the level of neuron population. To

do this, we utilized linear support vector machines (SVM) to analyze the time course of the 93

neurons in response to all the 8 stimuli to determine whether the three axes of the stimulus space

(Fig. 1D), HV ({1,2,5,6} versus {3,4,7,8}), OI ({1,3,5,7} versus {2,4,6,8}), and CA ({2,3,5,8}

versus {1,4,6,7}), could be decoded. We found that classifications along all three axes were

linearly separable, with accuracies above 75% and significantly higher than the shuffled baseline

(bootstrap t-tests, all ps < 0.001) (Fig. 2A). This finding was replicated with other methods such

as the analysis on population average responses and the principal component analysis (Fig. S1

B&C). Crucially, the optimal separation direction vectors (determined by SVM, see methods) for

HV, OI, and CA, were mutually orthogonal, as the distribution of the subtended angles between

these vectors was significantly more concentrated around 90° than the distribution of angles

between two random direction vectors, and also significantly larger than angle distributions

between the same classification vectors (Fig. S1E&F).

To visualize the dynamic encoding of the stimuli by the neuronal population, we projected the

neural states into a three-dimensional neural subspace formed by the direction vectors for HV,

OI, and CA (see Methods). Figure 2B shows that, prior to stimulus onset, the neural states for the

stimuli were closely clustered and inseparable. Following the onset, these states gradually spread

and became completely separable along the HV axis; then, they remained in a steady phase for

the duration of stimulus presentation before reverting to their original locations after stimulus

offset (see Movie S2 and Fig. S3). Similar dynamic patterns were observed for the OI (Fig. 2C)

and CA (Fig. 2D) axes as well. To further illustrate the neural geometry, we utilized the neural

states during the steady phase, ranging from 200ms to 500ms post-stimulus onset. Fig. 2E shows

that each stimulus-associated neural state was located at a vertex of a slightly distorted cube.

Crucially, the geometric relation among these neural states corresponded to the geometric

relation among stimuli in the original stimulus space (Fig. 1D); accordingly, we refer to the

neural states embedded in this three-dimensional subspace as the "sensory manifold". Since the

function of sensation is to convert environmental energy into neural signals, the sensory

manifold was sensitive to variations in the coherence of moving dots in the stimuli, which gave

rise to a series of concentric cubic sensory manifolds with higher coherence level eliciting larger

cubic manifolds (Fig S2& Fig. S3). Taken together, the sensory manifold faithfully represented

the stimulus space, with HV, OI, and CA serving as the axes of the neural subspace that

embedded this manifold. Consequently, the linearly inseparable problem cannot be solved within

the sensory manifold.

Consistent with previous studies on individual neurons (Marcar et al., 2000; Ma et al., 2021), our

SVM analysis at the population level was able to linearly decode MIC orientations (i.e., left-

versus right-titled, LR) (Fig. 2A, orange line), and the accuracy was comparable to that of

decoding the stimuli's features (i.e., HV, OI, and CA). Fig. 2F illustrates the neural states along

the optimal separation vector for LR, where the linearly inseparable problem became linearly

separable along this axis (for dynamic trajectories see Fig. S4 & Movie S2). Critically, this LR

axis was orthogonal to the three existing axes for the sensory manifold (Fig. S1D), suggesting

that the LR axis emerged not directly from the stimuli but from the processing of sensory

information. Evidence supporting this conjecture comes from the analysis on the latency of the

emergence of the LR axis, which occurred about 30ms after the emergence of the axes encoding

the stimuli's features (i.e., HV, OI, and CA) (Fig. 3F). This observation is line with previous

findings on visual motion segregation (Braddick, 1993; Lamme, 1995; Chen et al., 2014; Hu et

al., 2018), echoing the idea that perception is a result of operations on sensory information

(Goldstein, E. B., & Cacciamani, L, 2021). Accordingly, we refer to the manifold embedded in

this dimension-expanded neural subspace, which now incorporated the new LR axis in addition

to the existing axes for the sensory manifold, as the "perceptual manifold". Next, we explored

the potential operation that transforms the sensory manifold into the perceptual manifold.

Figure 2. Neural geometry of sensory and perceptual manifolds.

(A) Time-course accuracies by linear SVM classifiers. The SVMs were trained on neural data from 93 neurons

within the time interval [-200ms, 1000ms] relative to stimulus onset. Shaded regions denote the mean SVM

accuracy (±3 standard deviations) of the baselines by shuffling stimulus labels 1000 times. Individual

monkey's results are shown in Fig. S3 E&F.

(B-D) Dynamic trajectories of neural states. Neural states change from -50ms to 1000ms were projected onto

the neural subspace defined by the HV, OI, and CA axes. Black arrows indicate the direction of neural state

movement. Blue and red colors indicate categorization along the HV, OI, and CA axes for (B), (C), and (D),

respectively. Dynamic trajectories for other motion coherence levels are in Fig. S5, and individual monkey's

results are in Fig. S6.

(E) Sensory manifold. Eight clusters of neural states in the steady phase (200ms-500ms after stimuli onset)

corresponded to the 8 stimuli. The centers of these clusters are connected with dashed lines. Cool and warm

colors indicate the two MIC orientations, respectively. Individual monkey's results are in Fig. S3 A&B.

(F) Dynamic trajectories of neural states along the LR axis. The clusters follow the same color code as in E,

with the centers of the clusters marked. Note that cool and warm colors are separated along the LR axis.

Motion strength (r), which is the Euclidean distance between the neural states and the origin in the sensory

manifold in E, is included for display purposes only.

Twist operations on neural geometry

For simplicity, here we use x, y, and z to denote the axes of HV, OI, and CA, respectively. In the

z-x plane, the four vertices {1,3,5,7} exemplify the standard planar XOR problem (Fig. 3A, left).

Traditional solutions to the XOR problem often involve expanding dimensionality (Minsky &

Papert, 1969; Fusi et al., 2016). For example, twisting two parallel edges along the z-axis in

opposite directions around the x-axis can resolve the issue (Fig. 3A, middle), thus termed as twist

operation (for a similar idea, see Nogueira et al., 2023). Accordingly, this twist operation

transforms the 2-D plane into a curved 3-D surface (Fig. 3A, right). In this new 3-D space, a new

axis, denoted as v, is constructed through a cross-product-like operation between z and x,

expressed as $v = z \oplus x$. Along this new v axis, the four vertices become linearly separable.

To examine whether this theoretically derived v axis was present in the actual neural space, we

trained linear SVMs to classify three sets of vertex pairs among four vertices. As expected, the

vertex pair of {1,5} versus {3,7} and that of {1,7} versus {3,5} were linearly separable along the x

axis and z axis, respectively, with accuracies greater than 75%. Critically, the vertex pair of {1,3}

versus {5,7} was also linearly separable along the v axis, suggesting that the v axis was indeed

present in the neural space (Fig. 3B). Next, we generalize this twist operation from the planar XOR

problem to the cubic XOR problem (i.e., {1, 2, 3, 4} versus {5, 6, 7, 8}, Fig. 3C, left).

Apparently, a single twist operation with $v = z \oplus x$ proves insufficient to resolve the cubic

XOR problem (Fig 3C, middle). However, incorporating a second twist in a plane parallel to the

v axis around the y axis makes the vertex pair of {1, 2, 3, 4} versus {5, 6, 7, 8} linearly

separable (Fig 3C, right). In this second twist, a new axis, denoted as p, is constructed through a

cross-product-like operation between v and y: $p = v \oplus y = z \oplus x \oplus y$. Interestingly, this

newly constructed p axis is the axis that differentiates between the left- and right-tilted MIC

orientations. Indeed, the p axis is the LR axis illustrated in Fig. 2F.

Figure 3: The double-twist model.

(A) One twist operation on a planar XOR problem. Left: the coplanar vertices {1,3,5,7} are colored based on MIC orientations, forming a standard XOR problem on the z-x plane. Middle: a twist operation along the z-axis resolves the XOR problem by rotating two parallel edges in opposite directions around the x-axis. Right: this twist operation generates the v axis orthogonal to the z-x plane.

(B) Time courses of SVM classification accuracies. Shaded regions denote the mean SVM accuracy (±3 standard deviations) of the baselines by shuffling stimulus labels 1000 times.

(C) Double twist operations on a cubic XOR problem. Two consecutive twists are required to correctly classify the 8 vertices according to their MIC orientations. Left: the theoretical sensory manifold in the y-z-x space; Middle: the intermediate manifold achieved after one twist operation on the z-x plane, with the emergence of the new v axis. Right: the task-relevant p axis emerges after the second twist operation on the y-v plane.

(D) Neural manifolds corresponding to the theoretical manifolds achieved through twist operations. The axes of x, y, z, v and p in the neural space were achieved through corresponding SVM classifiers. Eight clusters of neural states corresponded to the 8 stimuli, and the centers of these clusters were used to depict the geometry of neural manifolds through linear fitting.

(E) Angle distribution between x, y, z, v and p axes. The distribution of the subtended angles between the optimal separation direction vectors as determined by SVM was concentrated around 90°.

(F) Latency of axis emergence. Left: time courses of classification accuracies of the axes. The enlarged insert shows the latencies of the emergence of the z, x, v, and p axes (against their corresponding baselines) at 43ms, 57ms, 65ms, and 87ms, respectively. Shaded regions denote the mean SVM accuracy (±3 standard deviations) of the baselines by shuffling stimulus labels 1000 times. Right: The latencies of the sensory axes (0-twist, blue), the intermediate axes (1-twist, green), and the task-relevant axis (2-twist, red). **: $p < 0.001$.

To visualize the perceptual manifold embedded in the neural subspace constructed by the z, x, y, v, and p axes, we projected the neural states during the steady phase (i.e., 300ms–500ms) onto a 3-D subspace constructed by three axes selected. Figure 3D shows the geometric transformation of the sensory manifold (left) into the perceptual manifold (right), which are equivalent to two successive twist operations (see also S7A). After the first twist operation, two planar XOR problems were resolved: the vertex pair of {1, 3} versus {5, 7} and that of {2, 4} versus {6, 8} became linearly separable along the intermediate v axis (Fig. 3D, middle). After the second twist, the cubic XOR problem was resolved along the task-relevant p axis, and the perceptual manifold emerged accordingly (Fig. 3D, right). In addition, the v and p axis, as well as the z, x, and y axes, were mutually orthogonal (Fig. 3E). Note that the neural manifolds derived from actual neural states (Fig 3D) closely matched the theoretical manifolds generated through twist operations (Fig 3C) (all $R^2 \geq 0.8$, for details see Methods), suggesting that the neural manifolds observed in the macaques' V2 may indeed undergo geometric transformations equivalent to those theorized in the twist operations.

More direct evidence supporting this conjecture comes from the analysis on the latency of the emergence of the intermediate v axis. Our double-twist model predicts that the v axis should emerge after the sensory axes of z and x, upon which the first twist operation acts, and before the MIC-related p axis, which relies on the v axis for the second twist. Consistent with this prediction, the v axis emerged (against the baseline) at 65ms post-stimulus onset, significantly earlier than the

emergence of the z and x axes (at 43ms and 57ms respectively; bootstrap t-test, p < 0.001), yet

later than that of the p axis (at 87ms; bootstrap t-test, p < 0.001) (Fig. 3F, left; for the time courses

of all axes, see Fig S7 B & C).

Taken together, the presence of the MIC-unrelated v axis, along with the observed temporal

sequence among the different axes, suggests that the perceptual manifold did not directly or

instantaneously derive from the sensory manifold; instead, it appears to transition through a

sequence of intermediate transformations, each adhering to essential geometric procedures

required for evolving from one manifold to another. Next, we explored the possible existence of

other intermediate axes similar to the v axis.

Dimensionality of perceptual manifold

Given the commutative nature of the twist operation, $p = z \oplus x \oplus y$ can alternatively be

expressed as $p = x \oplus y \oplus z$ or $p = y \oplus z \oplus x$. This opens up the possibility for two additional

intermediate axes: $u = x \oplus y$, which classifies vertices {1,4,5,8} from vertices {2,3,6,7}, and

$w = y \oplus z$, which classifies vertices {1,2,7,8} from vertices {3,4,5,6}. Indeed, the SVM analysis

showed significantly higher classification accuracies for these vertex pairs compared to the

baseline, confirming the existence of these two intermediate u and w axes in the neural space (Fig.

S7A). The characteristics of the u and w axes were the same as those of the previously identified

v axis: first, the u and w axes were orthogonal to each other and to the other axes (Fig. S7D);

second, they emerged subsequent to the sensory axes (i.e., z, x, and y axes) yet prior to the p axis

($F(2, 697) = 1015.6$, $p < 0.001$; for all pair-wise comparisons, $ps < 0.001$, Bonferroni

corrected) (Fig. 3F, right; see also Fig. S7 B&C); third, the cubic XOR problem can be addressed

using either the u axis or the w axis as the intermediate axis (Fig. S8). In sum, seven axes, the x,

y, z, u, v, w and p axes, were identified in the neural space of the neuron population in the V2,

suggesting that the perceptual manifold was embedded in a 7-D neural subspace, a dimensionality

much higher than that of the sensory manifold (i.e., 3-D).

An intriguing question arises: why was the perceptual manifold embedded in a 7-D space when a

4-D space, constructed by x, y, z, and p axes, would suffice for the LR classification in the MIC

task? One possibility is that the availability of multiple alternative pathways to construct the task-

relevant p axis enhances the robustness for the LR classification. Alternatively, the perceptual
manifold may not be task-specific; rather, the LR classification could be just one of its many
possible applications. That is, for the stimulus space with 8 vertices, there are $2^8=256$ possible
classifications. Some of these are linearly separable, like vertex {1} versus {2,3,4,5,6,7,8} or
vertices {1,5} versus {2,3,4,6,7,8} (Fig. 4A), while others are not, such as {1,3} versus
{2,4,5,6,7,8} (Fig. 4B). Let a linear classification be X versus X^c with $\|X\| = 0, \dots, 8$, there exist
104 different types of linear classifications, leaving the rest 152 classifications are linearly
inseparable (for a full list, see Fig. S11 and Table S2). Critically, these linearly inseparable
classifications in the stimulus space become linearly separable in the 7-D space. For example, the
vertex pair of {1,3} versus {2,4,5,6,7,8} becomes linearly separable in the y-z-p subspace (Fig.
4C). In total, there are $C_3^7 = 35$ 3-D subspaces (Fig. S9), and each of the 152 linearly inseparable
classifications becomes linearly separable in at least one of these 35 subspaces (Table S1). That is,
within the 7-D space, every conceivable classification in the stimulus space becomes linearly
separable.
315
In line with this observation, we also analyzed the population activity of the same set of the V2
neuron population when the monkeys passively fixated on the screen where the same type of the
stimuli were present (24 conditions in total, for details see Fig. S13A-D). Even in the absence of
the MIC task, we also identified the same seven axes that share characteristics with those observed
during the MIC task (Fig. S13E&F). First, SVM classification accuracies for all seven axes were
above 75%; second, the axes were mutually orthogonal; and third, theycollectively constructed the
same 7-D perceptual space. Therefore, the perceptual manifold is not the manifold for decision-
making or action; rather, it provides a reservoir of all possible candidates (in our case, solutions
for all conceivable classifications), awaiting selection by higher-order cognitive processes.
325
In support of this idea, we found that, upon the removal of neurons highly sensitive to MIC
orientations (i.e., task-relevant neurons) from the V2 neuron population, the remaining neurons
with mixed selectivity were still capable of decoding MIC orientation at the population level, just
as effectively as the original neuron population (Fig. S1 G&H). This finding suggests that neurons
with mixed selectivity to various features (Rigotti et al., 2013; Kaufman et al., 2022) may play a
critical role in transforming the sensory manifold into the perceptual manifold.

Figure 4: Linearly separable and inseparable classifications in the stimulus space.

(A) Examples of linearly separable but non-axial classifications in the stimulus space. The classification

separates a subset X of vertices from the rest with $\|X\| = 0, 1, 2, 3,$ and 4 (left to right, red vertices). The

classifications with $\|X\| = 5, 6, 7,$ and 8 are complementary (blue vertices). In total, there are 104 linearly

separable classifications in the stimulus space when the axial classifications are included.

(B) Examples of linearly inseparable classifications in the stimulus space, including the LR classification

(right). In total, there are 152 linearly inseparable classifications in the stimulus space.

(C) The classifications in (B) become linearly separable in new subspaces obtained through twist operations

(see Table S1).

Nonlinear mixed selectivity neurons and their heterogeneous connectivity patterns

To exemplify the role of neurons with different response profiles in expanding dimensionality of

neural manifolds, we examined a one-layer network consisting of three neurons, s_1, s_2 and s_3.

These neurons receive inputs consisting of two continuous features, a and b, that form a 2-D

feature sheet (Fig. 5A, top). The XOR problem, in this context, is defined as categorizing points

located at diagonally opposite corners (i.e., red versus blue points). The neurons receive either pure

(either a or b) or mixed (the combination of a and b) inputs, and possess either linear or nonlinear

(e.g., ReLU) activation functions, leading to four distinct output patterns (Fig. 5A, bottom).

Neurons with pure selectivity and the linear activation function (i.e., linear pure selectivity) afford

only a simple affine transformation of the original feature sheet (Fig. 5B). Because the rotation

axis is aligned with the orange and black edges, the edges remain parallel after transformation. For

neurons with nonlinear pure selectivity, the feature sheet undergoes bending because of the

nonlinear activation function (Fig. 5C). Because the bending occurs along an axis parallel to the

orange and black edges, the edges remain parallel after bending. For neurons with linear mixed

selectivity (Fig. 5D), the feature sheet endures a complex affine rotation, with the rotation axis not

aligning with the three main axes. However, even after this rotation, the edges remain parallel. In

these three scenarios, neither bending nor rotation alone suffices to expand the dimensionality of

the feature sheet, and thus the red and blue points remain linearly inseparable.

In contrast, neurons with nonlinear mixed selectivity (NMS) perform a twist operation on the

feature sheet, which derives from the combination of affine rotation and the bending. After the

twist operation, the orange and black edges are no longer parallel (Fig. 5E), making the XOR

problem linearly separable. In sum, this theoretical analysis suggests that NMS neurons likely play

a critical role in addressing the XOR problem.

Figure 5: Neurons with different response profiles in realizing twist operations.

(A) Top: The 2-D feature sheet represents all possible combinations of stimulus features a and b. Two edges of

this sheet are highlighted as orange and black, and four corners are colored red and blue to indicate different

categories. Bottom: Four types of neurons' response profiles derive from the combination of input (pure versus

mixed) with activation function (linear versus nonlinear) activation functions. ReLU is used for the illustration

of nonlinear activation functions. The neuron marked in light purple denotes the NMS neuron.

(B-E) The representations in the neural space constructed by (B) three linear pure selectivity neurons, (C) three

nonlinear pure selectivity neurons, (D) two linear pure selectivity neurons and one linear mixed selectivity

neuron, or (E) two nonlinear pure selectivity neurons and one NMS neuron.

The formal proof shows that the unique characteristic of NMS neurons lies in their interactive

responsiveness to stimulus features (see Methods for details). For example, the time course and

average activity of a typical V2 neuron shows that this neuron responded differently to HV and

CA while showing no sensitivity to OI (Fig. 6A&B, top). Thus, we used the significance of three-

way interactions among the stimulus features (HV, OI and CA) as an index to evaluate whether a

neuron exhibits nonlinear mixed selectivity (see Methods). We found that all V2 neurons recorded

showed significant interactions (with a minimum $F(1, 2200) = 18.25, p < 0.001$), suggesting

that they were all NMS neurons. To simulate neurons with pure selectivity (Rigotti et al., 2013),

we generated synthetic neurons exclusively tuned to one of the three features (Fig. S12). For

example, Fig. 6A&B (bottom) shows a typical synthetic neuron with pure selectivity to OI. Next,

we examined the performance of both NMS and pure selectivity neurons in addressing problems

that are either linearly separable or inseparable.

Figure 6: Classification performance of NMS and pure selectivity neurons.

(A) Time courses of an NMS neuron (top) and a synthetic neuron with pure selectivity (bottom). Colors and

numbers denote different stimuli and their associated neural responses. The time course of the synthetic neuron

was generated by modifying the time course of the NMS neuron shown above.

(B) Average activity of the NMS neuron (top) and the synthetic neuron (bottom). Activity magnitude

represents the average activity from 200ms to 750ms after stimulus onset. Colors denote different conditions of

a feature, and error bars denote the standard error of mean.

(C) The number of successful linear classifications increases as a function of neuron population size for both

pure selectivity neurons (gray) and NMS neurons (dark). The gray curve plateaus at 104, the total number of

linearly separable problems in the stimulus space, whereas the dark curve converges to 256, which includes

152 linearly inseparable problems in addition to 104 linear separable ones. Real neuron: neurons recorded in

the V2; Pure neuron: synthetic neuron with pure selectivity; error bar: standard deviation.

To evaluate the classification efficacy for 152 linearly inseparable problems (Table S1) and 104

linear separable problems (Table S2) in the stimulus space, we used a population-increment

procedure, where the population size was progressively increased from a single neuron to the entire

set of 93 neurons, adding one randomly selected neuron each time. During each iteration, we

trained SVMs with neural activities for all possible classifications, and a classification accuracy

threshold of 75% was set as the criterion for successful classification (for details, see Methods).

Fig. 6C shows the number of successful linear classifications (i.e., binary classification) as a

function of neuron population size. With NMS neurons, we achieved the full range of possible

classifications (256 in total) for both linearly separable and inseparable problems (Fig. 4C, black

curve) once the number of NMS neurons exceeded 81. In contrast, using the synthetic neurons

with pure selectivity, the total number of successful classifications plateaued at 104 (Fig. 4C, gray

curve) once the population size exceeded 49. That is, additional increases in population size did

not improve classification performance. Critically, close examination of the problems successfully

classified by pure selectivity neurons revealed that they were all linearly separable in the stimulus

space (Table S1), and none came from the set of linear inseparable problems (Table S2). That is,

regardless of population size, neurons with pure selectivity can only address linearly separable

problems. This observation was further replicated when the monkeys passively viewed the stimuli

(Fig. S13G). Taken together, our finding suggests that pure selectivity neurons alone cannot expand

the sensory manifold to a higher dimensionality; instead, NMS neurons are necessary in expanding

the dimensionality of neural manifolds, hereby transforming the sensory manifold into the

perceptual manifold.

While necessary, NMS neurons alone seem insufficient for dimension expansion, as it has been

suggested that the dimensionality of neural manifolds is also dictated by the connectivity structure

of neural networks (Langdon et al., 2023). Here we further investigated the connectivity structure

among NMS neurons that may underpin dimension expansion. To easily quantify the connectivity

structure, we built a one-layer feedforward neural network tasked with processing the stimuli used

in the macaques' experiment (for details on the network, see Methods). In this network, each

neuron receives inputs of all three stimulus features (i.e., HV, OI and CA) and employs a nonlinear

activation function, with connectivity weights independently sampled from a Gaussian distribution.

As a result, all neurons in the neural network demonstrate a response profile of NMS.

In this network, the connectivity structure is controlled by parameter d, which signifies the degree

of diversity in connection patterns among different neurons (Fig. 7A). This diversity ranges from

identical patterns ($d = 0$) to completely uncorrelated patterns ($d = 1$) (see Methods). That is,

when d = 1, each neuron generates a distinct response because the connection pattern from the

inputs is unique (Fig. 7A, right). Therefore, the matrix of connectivity weights is full rank, and

after passing through the nonlinear activation function this connectivity structure allows the neural

manifold to carry out all possible linear and nonlinear classifications composed by the stimulus

features. Indeed, the SVM analysis, similar to that on the macaques' data, was performed, and a 7-

D perceptual manifold was identified. For visualization, neurons' activations are projected into 3-

D subspaces (Fig. 7B), where each dot denotes the neural state of a stimulus, with red and blue

colors representing the two MIC orientations. Within this 7-D perceptual manifold, we can identify

the sensory manifold embedded in a 3-D subspace constructed by axes corresponding to the three

stimulus features (Fig. 7B, left), the intermediate manifold in a 3-D subspace with a new axis of

$v = z \oplus x$ after one twist operation (Fig. 7B, middle), and the subspace achieved after the second

twist operation where linearly separating MIC orientations becomes possible (Fig. 7B, right). In

addition, we also used continuous stimuli that spanned the entire motion-shearing rings (Fig. 1C,

right) and found similar results (Fig. S14). In sum, this 7-D perceptual manifold constructed by

the network of NMS neurons with a random connectivity (i.e., $d = 1$) is similar to the 7-D

perceptual space identified in the macaque's V2 (Fig. 3D).

In contrast, when $d = 0$, all neurons have the same inputs and thus generate identical responses,

similar to neurons in a theoretical functional module that have the same response profile.
Accordingly, the matrix of connectivity weights of the network is rank 1 (or 0 if all weights are 0),
and thus the dimensionality of the neural manifold generated by this network is low
(dimensionality = 1.3, std = 0.70). This can be clearly demonstrated with PCA analysis on the
variance of neurons' activation of the network (Fig. 7D). When $d = 0$, the first PC explained 99.84%
of total variance, leaving nearly no variance for the rest of PCs. Thus, the neural states of the
stimuli were confined into an approximately 1-D space (Fig. 7C). In contrast, when $d = 1$, to
explain the same amount of variance of first PC when $d = 0$, the first 6 PCs (99.78%) were
required. In other words, the neural states of the stimuli were dispersed into a higher dimensional
space. Therefore, unlike the network with high diversity in connectivity (i.e., d = 1), the neural
manifold constructed by the network with no diversity (i.e., d = 0) suffers a severe deficit in
performing either linear or nonlinear classification (number of linearly separable problems
successful addressed = 9.16 or 8.8% of the whole set, std = 2.89; number of linearly inseparable
problems successful addressed = 2.74 or 1.8%, std = 2.23). That is, networks with identical
connection patterns hardly encode much information, even with all neurons showed a response
profile of NMS.

To systematically investigate how connectivity structure influences neural manifolds, we
constructed a series of neural networks with different parameter d, and then measured the
dimensionality of the neural manifolds and the classification performances on both linearly
separable and inseparable problems (see Methods). We found that as the diversity of connectivity
patterns increased, the dimensionality of the neural manifolds also increased monotonically (Fig.
7E, red curve). Interestingly, the network did not need to possess a completely diverse structure to
support a high-dimensional neural manifold. With $d > 0.5$, the dimensionality was reliably
expanded to 7. Accordingly, the number of successful classifications increased monotonically,
finally capable of successfully classifying all possible problems (i.e., 256) after the dimensionality
reliably reached 7 (Fig. 7E, blue curve). Interestingly, the linearly inseparable problems were
resolved in parallel with the linearly separable classifications (Fig. S15).

In sum, NMS neurons alone are not sufficient; the connectivity structure is also critical, and its
diversity optimally leverages the NMS neurons to construct a higher-dimensional neural space.

Figure 7. Connectivity structure on dimensionality.

(A) Schematic illustration of a one-layer feedforward neural network. Each neuron of the network receives the

inputs encoding three stimulus features (HV, OI and CA), indexed by x, y, and z, respectively. The

connectivity weights are randomly sampled from a multivariate Gaussian distribution, with the thickness of

lines indicting the magnitudes of weights. The connectivity from feature x to units is highlighted by color for

display purpose. Neurons' output is achieved through linear summation and ReLU activation. Networks with

three diversities are shown here.

(B) Visualization of neural manifolds in 3-D subspaces when $d = 1$. Left: the sensory manifold that

corresponding to the stimulus space; Middle: the intermediate manifold after one twist operation ($v = z \oplus x$);

Right: the subspace where linearly separating MIC orientations is achieved. Each point denotes the neural state

of a stimulus, with red and blue colors representing the two MIC orientations (LR), respectively.

(C) Visualization of neural manifold in a 3-D subspace when $d = 0$. The subspace is constructed by the first

three PCs of neurons' activation.

(D) Variance explained by PCs of neurons' activation with different connectivity structures. When $d = 0$,

indexed by the dashed line with the lightest blue, the variance is nearly explained by the first PC alone. When

$d = 1$, indexed by the dashed line with the darkest blue, the curve of variance explained by each PC is

flattened.

(E) The dimensionality and the number of successful classifications as the function of connectivity structure of

networks. Left axis (blue): the number of successful binary classifications. Right axis (red): the effective

dimensionality of the neural manifolds constructed by the network. Error bars represent stand deviation.

Discussion

Sensation is typically defined as the conversion of environmental energy into neural signals, which are subsequently interpreted and give rise to perception. However, the lack of conceptual clarity often leads to debates on whether the dichotomy between sensation and perception is real and necessary (e.g., Gibson, 1979), and if real, where and why the line of demarcation shall be drawn. Here we investigate how physical moving dots acting upon sense organs are interpreted as an illusory contour through the lens of the population doctrine. By analyzing neural geometry constructed by the neuronal ensemble in macaques' V2, we found that the stimuli were faithfully represented in a 3-D sensory manifold. Critically, to linearly decode the orientation of the illusory contours, an inherently linearly inseparable problem, we identified four additional axes, along with three axes for the sensory manifold, constructing a 7-D perceptual manifold through geometric transformations equivalent to twist operations. Critically, the geometric transformation from the sensory manifold to the perceptual manifold was realized through collaborative work combining specialized neuronal properties of nonlinear mixed selectivity with heterogeneous connectivity pattern among these neurons. In summary, our study demonstrated an unambiguous line drawn between sensation and perception from a neural geometry perspective, enriching our understanding to the dictum that "structure determines function" in neural networks (Langdon et al., 2023; Sporns, 2014).

Previous studies on neural geometry have shown that neural manifolds can faithfully represent both stimulus space (Bao et al., 2020; Xie et al., 2022; Gardner et al., 2022) and action space (Churchland et al., 2012; Perich et al., 2020; Gallego et al., 2017). In line with these findings, our study revealed a cubic-shaped neural manifold encoding three mutually orthogonal axes, each of which corresponded to HV, OI, and CA feature of stimuli, respectively. In addition, the manifold's size was monotonically increased as a function of the motion coherence of local dots. That is, this manifold, generated by neural signals elicited when stimuli acted upon the eyes, is therefore termed the sensory manifold. Further, we identified four additional axes encoding features absent from the physical stimuli. Specifically, one such axis, geometrically equivalent to the two twist operations, encoded perceived orientations of the illusory contours. Consequently, the neural geometry transformed from the 3-D sensory manifold into a 7-D perceptual manifold within a delay of about 30ms. Interestingly, this perceptual manifold was task irrelevant, because in addition

to differentiating the MIC orientations, it is equipped to accomplish the remaining 255 possible

classifications, irrespective of linear separability. Indeed, even in the absence of task demands, the

same perceptual manifold was observed when passively viewing the same stimuli. Therefore, the

task irrelevance characteristics of the perceptual manifold also draws a line of demarcation

between the perceptual manifold and manifolds associated with decision-making or action.

The creation of these perception-related axes was solely attributed to NMS neurons through twist

operations, known for expanding dimensionality of neural manifolds (Rigotti et al., 2013; Fusi et

al., 2016). In addition, neurons either purely selective for a single feature or exhibiting a linear mix

of multiple features selectivity, showed their capability to address only linearly separable problems,

suggesting the necessity of NMS neurons in producing subjective experiences. Unfortunately, the

functionality of these neurons was largely ignored under the neuron doctrine, where attention was

predominantly directed to neurons with clear semantic meanings (i.e., neurons with pure

selectivity). In contrast, our study advocates the indispensable role of NMS neurons in geometric

transformations from the sensory manifold to the perceptual manifold and generating latent

variables from intermediate axes which do not have semantic description (Jazayeri & Ostojic,

2021). Therefore, NMS neurons shall lie at the core of the population doctrine.

However, the mere presence of NMS neurons is not sufficient, and their functional efficacy is

intrinsically tied to the heterogeneity in their connectivity patterns (Kriegeskorte & Wei, 2021;

Langdon et al., 2023). With the simulation of networks with NMS neurons, we found that when

NMS neurons were interconnected in a homogenous fashion, the expansion of neural

dimensionality was limited, thus constraining the network's computational power in classifying

either linearly separable or inseparable problems. Conversely, when the heterogeneity in the

connectivity patterns among NMS neurons was increased, a significant expansion in the

dimensionality of neural manifolds was observed, effectively transforming linearly inseparable

problems into linearly separable ones e. Taken together, our study revealed the symbiotic

relationship between NMS neurons and the diversity of their connectivity patterns. In this

framework, NMS neurons serves the "building blocks" that enable the construction of high-

dimensional neural manifolds, whereas the specific architectural configuration defined by their

connectivity provides the "blueprint" to actualizes this potential. That is, both specialized neuronal

properties and the intricate structure of neural connections are critical in sculpting the landscape
of neural computation.

The high dimensionality of the perceptual manifold provides a reservoir of all computational
solutions, enabling flexible classifications according to downstream task rules. However, this
flexibility comes with a cost as the potential solutions rise exponentially with the number of
dimensions. For example, in our study, downstream cortical regions must identify one proper
classification required by the task from 256 possibilities. While the mechanism for effectively
searching solutions based on task demands remains largely unknown, the strengthening or
weakening of the homogeneity of connectivity patterns through Hebbian ("fire together wire
together") and anti-Hebbian ("out of sync, lose the link") rules might hint at a possible mechanism
(Caporale & Dan, 2008). In networks with Hebbian plasticity, neurons that are frequently co-
activated by similar tasks or stimuli often develop stronger and more homogeneous connectivity
patterns, increase the information related to specific features and leading to the formation of
specialized modules. Within these modules, neurons tend to exhibit heightened selectivity,
minimizing their mixed selectivity (Weigand et al., 2017; Lindsay et al., 2017; Bullinaria, 2007).
On the other hand, with the anti-Hebbian rule, task-relevant features are disentangled from task-
irrelevant ones. Accordingly, axes associated with less pertinent features can be compressed,
thereby reducing effective dimensionality, and reshaping the manifold to focus on task-relevant
features (Ganguli & Sompolinsky, 2012; Rajan et al., 2010; Farrell et al., 2022; Bernardi et al.,
2020). Taken together, along the hierarchy of the ventral visual stream, while the representation
dimensionality is high, the amount of information in each dimension varies (Stringer et al., 2019).
Thus, specialized neuronal modules gradually emerge, within which neurons become increasingly
selective and attuned to task demands. This dynamic transformation orchestrates the progression
from perceptual to decision-making manifolds, and ultimately to action-oriented manifolds,
enabling us to act upon the physical world, in response to stimuli that have acted upon us.

Supplemental Information
Supplemental Information includes 15 figures, 2 tables and 2 videos.

Acknowledgments: This study was funded by Beijing Municipal Science & Technology

Commission, Administrative Commission of Zhongguancun Science Park (Z221100002722012),
Tsinghua University Guoqiang Institute (2020GQG1016), and Beijing Academy of Artificial
Intelligence (BAAI). We thank Dr. Xingyu Liu for her valuable discussion and comments, and Dr.
Haidong Lu for his supervision on conducting the experiments.

Author contributions: H.M., L.J., T.L. and J.L. developed the theoretical framework. H.M.
performed the experiments, collected the data, and compiled the data. H.M., L.J., T.L., and J.L.
conceived the data analyses. H.M. and L.J. performed the data analyses. L.J. developed the double-
twist model. T.L. performed the network simulation. H.M., L.J., and J.L. wrote the paper.

Competing interests: Authors declare no competing interests.

Data and materials availability: The neurophysiological data and analysis code are available at
Mendeley Data, https://doi.org/10.17632/vrj3645vgz.1.

	Reference
638	
639	Bao, P., She, L., McGill, M., & Tsao, D. Y. (2020). A map of object space in primate
640	inferotemporal cortex. *Nature*, *583*(7814), 103–108. https://doi.org/10.1038/s41586-020-
641	2350-5
642	Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The
643	Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. *Cell*, *183*(4), 954-
644	967.e21. https://doi.org/10.1016/j.cell.2020.09.031
645	Braddick, O. (1993). Segmentation versus integration in visual motion processing. *Trends in*
646	*Neurosciences*, *16*(7), 263–268. https://doi.org/10.1016/0166-2236(93)90179-P
647	B. Schölkopf and A. J. Smola, Learning with Kernels: Support Vector Machines Regularization
648	Optimization and Beyond, Cambridge, MA, USA: *MIT Press*, 2002.
649	Bullinaria, J. A. (2007). Understanding the emergence of modularity in neural systems.
650	*Cognitive Science*, *31*(4), 673–695. https://doi.org/10.1080/15326900701399939
651	Caporale, N., & Dan, Y. (2008). *Spike Timing – Dependent Plasticity: A Hebbian Learning Rule*.
652	https://doi.org/10.1146/annurev.neuro.31.060407.125639
653	Chen, M., Li, P., Zhu, S., Han, C., Xu, H., Fang, Y., Hu, J., Roe, A. W., & Lu, H. D. (2014). An
654	Orientation Map for Motion Boundaries in Macaque V2. *Cerebral Cortex*.
655	https://doi.org/10.1093/cercor/bhu235
656	Chung, S., Lee, D. D., & Sompolinsky, H. (2018). Classification and Geometry of General
657	Perceptual Manifolds. *Physical Review X*, *8*(3), 31003.
658	https://doi.org/10.1103/PhysRevX.8.031003
659	Chung, S., & Abbott, L. F. (2021). Neural population geometry: An approach for understanding
660	biological and artificial neural networks. *Current Opinion in Neurobiology*, *70*, 137–144.
661	https://doi.org/10.1016/j.conb.2021.10.010
662	Churchland, M. M., Cunningham, J. P., Kaufman, M. T., Foster, J. D., Nuyujukian, P., Ryu, S. I.,
663	Shenoy, K. V. (2012). Neural population dynamics during reaching. *Nature*, *487*(7405), 51–
664	56. https://doi.org/10.1038/nature11129
665	C. K. Williams and C. E. Rasmussen, Gaussian Processes for Machine Learning, Cambridge,
666	MA, USA: *MIT Press*, 2006.
667	Cover, T. M. (1965). Geometrical and Statistical Properties of Systems of Linear Inequalities
668	with Applications in Pattern Recognition. *IEEE Transactions on Electronic Computers*, *EC-*
669	*14*(3), 326–334. https://doi.org/10.1109/PGEC.1965.264137

Cristianini, Nello, and John Shawe-Taylor. An Introduction to Support Vector Machines and Other Kernel-Based Learning Methods. *Cambridge university press*, 2000.

DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How does the brain solve visual object recognition? *Neuron*, *73*(3), 415–434. https://doi.org/10.1016/j.neuron.2012.01.010

DiCarlo, J. J., & Cox, D. D. (2007). Untangling invariant object recognition. *Trends in Cognitive Sciences*, *11*(8), 333–341. https://doi.org/10.1016/j.tics.2007.06.010

Dyballa, L., Rudzite, A. M., Hoseini, M. S., Thapa, M., Stryker, M. P., Field, G. D., & Zucker, S. W. (2023). *Population encoding of stimulus features along the visual hierarchy*.

Ebitz, R. B., & Hayden, B. Y. (2021). The population doctrine in cognitive neuroscience. *Neuron*, *109*(19), 3055–3068. https://doi.org/10.1016/j.neuron.2021.07.011

Farrell, M., Recanatesi, S., Moore, T., Lajoie, G., & Shea-Brown, E. (2022). Gradient-based learning drives robust representations in recurrent neural networks by balancing compression and expansion. *Nature Machine Intelligence*, *4*(6), 564–573. https://doi.org/10.1038/s42256-022-00498-0

Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., & Summerfield, C. (2022). Orthogonal representations for robust context-dependent task performance in brains and neural networks. *Neuron*, *110*(7), 1258-1270.e11. https://doi.org/10.1016/j.neuron.2022.01.005

Froudarakis, E., Cohen, U., Diamantaki, M., Walker, E. Y., Reimer, J., Berens, P., Sompolinsky, H., & Tolias, A. S. (2020). Object manifold geometry across the mouse cortical visual hierarchy. *BioRxiv*, 2020.08.20.258798. https://doi.org/10.1101/2020.08.20.258798

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: High dimensionality for higher cognition. *Current Opinion in Neurobiology*, *37*, 66–74. https://doi.org/10.1016/j.conb.2016.01.010

Gallego, J. A., Perich, M. G., Miller, L. E., & Solla, S. A. (2017). Neural Manifolds for the Control of Movement. *Neuron*, *94*(5), 978–984. https://doi.org/10.1016/j.neuron.2017.05.025

Gallego, J. A., Perich, M. G., Naufel, S. N., Ethier, C., Solla, S. A., & Miller, L. E. (2018). Cortical population activity within a preserved neural manifold underlies multiple motor behaviors. *Nature Communications*, *9*(1), 1–13. https://doi.org/10.1038/s41467-018-06560-z

Ganguli, S., & Sompolinsky, H. (2012). Compressed sensing, sparsity, and dimensionality in
neuronal information processing and data analysis. *Annual Review of Neuroscience*, *35*,
485–508. https://doi.org/10.1146/annurev-neuro-062111-150410

Gardner, R. J., Hermansen, E., Pachitariu, M., Burak, Y., Baas, N. A., Dunn, B. A., Moser, M.
B., & Moser, E. I. (2022). Toroidal topology of population activity in grid cells. *Nature*,
602(7895), 123–128. https://doi.org/10.1038/s41586-021-04268-7

Genkin, M., Shenoy, K. V, Chandrasekaran, C., & Engel, T. A. (2023). The dynamics and
geometry of choice in premotor cortex. BioRxiv, 2023.07.22.550183
https://www.biorxiv.org/content/10.1101/2023.07.22.550183v1

Gibson, J. J. (1979). The ecological approach to visual perception. *Houghton, Mifflin, and*
Company.

Goldstein, E. B., & Cacciamani, L. (2021). *Sensation and perception*. Cengage Learning.

Hu, J., Ma, H., Zhu, S., Hu, J., Ma, H., Zhu, S., Li, P., Xu, H., Fang, Y., Chen, M., & Han, C.
(2018). Visual Motion Processing in Macaque V2 Article Visual Motion Processing in
Macaque V2. *CellReports*, *25*(1), 157-167.e5. https://doi.org/10.1016/j.celrep.2018.09.014

Jazayeri, M., & Ostojic, S. (2021). Interpreting neural computations by examining intrinsic and
embedding dimensionality of neural activity. *Current Opinion in Neurobiology*, *70*, 113–
120. https://doi.org/10.1016/j.conb.2021.08.002

Kaufman, M. T., Benna, M. K., Rigotti, M., Stefanini, F., Fusi, S., & Churchland, A. K. (2022).
The implications of categorical and category-free mixed selectivity on representational
geometries. *Current Opinion in Neurobiology*, *77*(October), 102644.
https://doi.org/10.1016/j.conb.2022.102644

Kriegeskorte, N., & Wei, X. X. (2021). Neural tuning and representational geometry. *Nature*
Reviews Neuroscience, *22*(11), 703–718. https://doi.org/10.1038/s41583-021-00502-3

Knuth, Donald E. The Art of Computer Programming, Vol. 2: Seminumerical Algorithms, Vol.
2. *Addison-Wesley*, Massachusetts, USA, 1973.

Lamme, V. A. F. (1995). The neurophysiology of figure-ground segregation in primary visual
cortex. *Journal of Neuroscience*, *15*(2), 1605–1615. https://doi.org/10.1523/jneurosci.15-
02-01605.1995

Langdon, C., Genkin, M., & Engel, T. A. (2023). A unifying perspective on neural manifolds

and circuits for cognition. *Nature Reviews Neuroscience*, *24*(6), 363–377.

https://doi.org/10.1038/s41583-023-00693-x

Lindsay, G. W., Rigotti, M., Warden, M. R., Miller, E. K., & Fusi, S. (2017). Hebbian learning

in a random network captures selectivity properties of the prefrontal cortex. *Journal of*

Neuroscience, *37*(45), 11021–11036. https://doi.org/10.1523/JNEUROSCI.1222-17.2017

Low, I. I. C., Giocomo, L. M., & Williams, A. H. (2023). *Remapping in a recurrent neural*

network model of navigation and context inference. *BioRxiv*, 2023.01.25.525596

https://doi.org/10.1101/2023.01.25.525596

Lu, H. D., Chen, G., Tanigawa, H., & Roe, A. W. (2010). A Motion Direction Map in Macaque

V2. *Neuron*, *68*(5), 1002–1013. https://doi.org/10.1016/j.neuron.2010.11.020

Ma, H., Li, P., Hu, J., Cai, X., Song, Q., & Lu, H. D. (2021). Processing of motion-boundary

orientation in Macaque V2. *ELife*, *10*, 1–24. https://doi.org/10.7554/eLife.61317

Mante, V., Sussillo, D., Shenoy, K. V., & Newsome, W. T. (2013). Context-dependent

computation by recurrent dynamics in prefrontal cortex. *Nature*, *503*(7474), 78–84.

https://doi.org/10.1038/nature12742

Marcar, V. L., Raiguel, S. E., Xiao, D., & Orban, G. a. (2000). Processing of kinetically defined

boundaries in areas V1 and V2 of the macaque monkey. *Journal of Neurophysiology*, *84*(6),

2786–2798.

Minsky, M. L., & Papert, S. (1969). Perceptrons, Expanded Edition, An Introduction to

Computational Geometry. In *MIT Press*.

Muller, M. E. (1959). A note on a method for generating points uniformly on n-dimensional
spheres. *Communications of the ACM*, *2*(4), 19–20. https://doi.org/10.1145/377939.377946
Mysore, S. G., Vogels, R., Raiguel, S. E., & Orban, G. a. (2006). Processing of kinetic

boundaries in macaque V4. *Journal of Neurophysiology*, *95*(3), 1864–1880.

https://doi.org/10.1152/jn.00627.2005

Nogueira, R., Rodgers, C. C., Bruno, R. M., & Fusi, S. (2023). The geometry of cortical
representations of touch in rodents. *Nature Neuroscience*, *26*(2), 239–250.
https://doi.org/10.1038/s41593-022-01237-9
Okazawa, G., Hatch, C. E., Mancoo, A., Machens, C. K., & Kiani, R. (2021). Representational

geometry of perceptual decisions in the monkey parietal cortex. *Cell*, *184*(14), 3748-

3761.e18. https://doi.org/10.1016/j.cell.2021.05.022

Perich, M. G., Conti, S., Badi, M., Bogaard, A., Barra, B., Wurth, S., Bloch, J., Courtine, G.,

Micera, S., Capogrosso, M., & Milekovic, T. (2020). Motor cortical dynamics are shaped by

multiple distinct subspaces during naturalistic behavior. *BioRxiv*, 2020.07.30.228767.

https://www.biorxiv.org/content/10.1101/2020.07.30.228767v2

Poland, J. (2000). Three different algorithms for generating uniformly distributed random points
on the N-sphere. *Computer Science, Physics.*
http://www-alg.ist.hokudai.ac.jp/~jan/randsphere.pdf.

Rajan, K., Abbott, L. F., & Sompolinsky, H. (2010). Stimulus-dependent suppression of chaos in

recurrent neural networks. *Physical Review E - Statistical, Nonlinear, and Soft Matter*

Physics, *82*(1). https://doi.org/10.1103/PhysRevE.82.011903

Rigotti, M., Barak, O., Warden, M. R., Wang, X. J., Daw, N. D., Miller, E. K., & Fusi, S. (2013).

The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585–

590. https://doi.org/10.1038/nature12160

Russo, A. A., Khajeh, R., Bittner, S. R., Perkins, S. M., Cunningham, J. P., Abbott, L. F., &

Churchland, M. M. (2020). Neural Trajectories in the Supplementary Motor Area and

Motor Cortex Exhibit Distinct Geometries, Compatible with Different Classes of

Computation. *Neuron*, *107*(4), 745-758.e6. https://doi.org/10.1016/j.neuron.2020.05.020

Seung HS & Lee DD. (2000). The manifold ways of perception. *Science 290: 2268–2269.*

She, A. L., Benna, M. K., Shi, Y., Fusi, S., & Tsao, D. Y. (2021). The geometry of face memory.

bioRxiv, 2021.03.12.435023. https://doi.org/10.1101/2021.03.12.435023

Sporns, O. (2014). Contributions and challenges for network models in cognitive neuroscience.

Nature Neuroscience, *17*(5), 652–660. https://doi.org/10.1038/nn.3690

Stringer, C., Pachitariu, M., Steinmetz, N., Carandini, M., & Harris, K. D. (2019). High-

dimensional geometry of population responses in visual cortex. *Nature*, *571*(7765), 361–

365. https://doi.org/10.1038/s41586-019-1346-5

Weigand, M., Sartori, F., & Cuntz, H. (2017). Universal transition from unstructured to

structured neural maps. *Proceedings of the National Academy of Sciences of the United*

States of America, *114*(20), E4057–E4064. https://doi.org/10.1073/pnas.1616163114

Xie, Y., Hu, P., Li, J., Chen, J., Song, W., Wang, X. J., Yang, T., Dehaene, S., Tang, S., Min, B.,
& Wang, L. (2022). Geometry of sequence working memory in macaque prefrontal cortex.
Science, *375*(6581), 632–639. https://doi.org/10.1126/science.abm0204
792