Title: From Sensory to Perceptual Manifolds: The Twist of Neural Geometry

Running title: Geometric Twist of Neural Geometry

Authors: Heng Ma[1#], Longsheng Jiang[2#], Tao Liu[1#], Jia Liu[1*]

Affiliation: [1]Department of Psychological and Cognitive Sciences & Tsinghua Laboratory of

Brain and Intelligence, Tsinghua University, Beijing 100084, China; [2]Beijing Academy of

Artificial Intelligence (BAAI), Beijing 100085, China

[#]These authors contributed equally: Heng Ma, Longsheng Jiang, Tao Liu

[*]**Correspondence**: liujiathu@tsinghua.edu.cn

Abstract

Classification constitutes a core cognitive challenge for both biological and artificial intelligence

systems, with many tasks potentially reducible to classification problems. Here we investigated

how the brain categorizes stimuli that are not linearly separable in the physical world by

analyzing the geometry of neural manifolds in high-dimensional neural space, formed by

macaques' V2 neurons during a classification task on the orientations of motion-induced illusory

contours. We identified two related but distinct neural manifolds in this high-dimensional neural

space: the sensory and perceptual manifolds. The sensory manifold was embedded in a 3-D

subspace defined by three stimulus features, where contour orientations remained linearly

inseparable. However, through a series of geometric transformations equivalent to twist

operations, this 3-D sensory manifold evolved into a 7-D perceptual manifold with four

additional axes, enabling the linear separability of contour orientations. Both formal proof and

computational modeling revealed that this dimension expansion was facilitated by nonlinear

mixed selectivity neurons exhibiting heterogeneous response profiles. These findings provide

insights into the mechanisms by which biological neural networks increase the dimensionality of representational spaces, illustrating how perception arises from sensation through the lens of neural geometry.

Keywords: motion-induced illusory contour; linearly inseparable problem; neural geometry; sensory manifold; perceptual manifold; nonlinear mixed selectivity.

Introduction

Imagine a person trying to identify various objects such as a cup, a book, and a pen on a clustered desk. The brain must process complex and overlapping sensory inputs with variations in light, angles, and occlusions by neurons encoding different features of the objects and their combinations to ultimately classify each object accurately (Biederman, 1987; DiCarlo et al., 2012; Chung & Sompolinsky, 2018). One primary challenge in this classification task lies in the prevalence of linearly inseparable problems, where perfectly segregating data points into their respective classes using a linear boundary is infeasible (Minsky & Papert, 1969; Fusi et al., 2016). Machine learning algorithms often resorts to complex, nonlinear decision boundaries to address this issue, employing techniques like kernel methods and deep learning (Schölkopf & Smola, 2002; Williams & Rasmussen, 2006). Here we asked how the brain addresses linearly inseparable problems present in the physical world from the perspective of neural geometry (Seung & Lee, 2000; DiCarlo & Cox, 2007; Chung & Abbott, 2021) constituted by the collective activity of large groups of neurons, an approach recently applied to various domains such as vision (Froudarakis et al., 2020; Dyballa et al., 2023), memory (Xie et al., 2022; She et al., 2024), decision (Okazawa et al., 2021; Flesch et al., 2022; Genkin et al., 2023), navigation

(Gardner et al., 2022; Low et al., 2023) and motor execution (Churchland et al., 2012; Gallego et

al., 2017; Gallego et al., 2018; Russo et al., 2020) to explore their characteristics in a high-

dimensional neural space.

To do this, we first designed a set of stimuli that cannot be linearly classified along one

stimulus feature. Specifically, we employed a visual illusion of motion-induced contours (MIC,

Marcar et al., 2000; Mysore et al., 2006; Chen et al., 2014), where moving dots generate an

illusory contour, either left- or right-tilted, at the center of a circular viewing area (Fig. 1B).

There are three independent stimulus features of moving dots that determine a particular instance

of MIC stimuli (Chen et al., 2014; Lu et al., 2010; Ma et al., 2021): dots move (1) either

horizontally or vertically, (2) outwardly or inwardly, and (3) clockwise-like or anti-clockwise-

like (Fig. 1C). Accordingly, a 3-D stimulus space is thus constructed (Fig. 1D), with each axis

corresponding to a stimulus feature of moving dots. Interesting, although each stimulus feature

of moving dots is linearly separable, the orientations of illusory boundary, constructed by

combining these three features, become linearly inseparable in this stimulus space. That is, MIC

stimuli sharing the same contour orientation (e.g., right-titled, red) are interspersed among those

with the opposing orientation (i.e., left-tilted, blue). Therefore, the classification of contour

orientations presents a linearly inseparable problem in the physical world.

In the mental world, however, the linear classification of contour orientations becomes

feasible, as previous neurophysiological studies have revealed that single neurons in macaques'

V2 exhibit selectivity for cue-invariant contour orientations (Marcar et al., 2000; Ma et al.,

2021). Accordingly, we analyzed neuronal activity data recorded in the V2 area (Ma et al., 2021),

aiming to elucidate how the linearly inseparable problem in the stimulus space becomes linearly

separable in the high-dimensional neural space constructed by the collective activity of V2

neurons. Importantly, because the contours do not exist in the physical world, being solely

created by the brain when integrating individual motions and interpreting symmetrical movement

patterns, we specifically examined two types of neural manifolds embedded in this high-

dimensional space: the sensory and perceptual manifolds. The sensory manifold, which arises

from the sensation process, directly responds to physical stimuli without involving interpretation

and thus provides the raw sensory data that the brain uses to build perceptual experiences. Given

its correspondence to external stimuli, contour orientations likely remain linearly inseparable in

the sensory manifold. In contrast, the perceptual manifold reflects the brain's effort to interpret

and make sense of the sensory data, where neural states for MIC stimuli may be separately

clustered based on contour orientations. Therefore, understanding the geometric difference

between the sensory and perceptual manifolds and further deriving potential mechanisms that

create such a difference provides a new perspective on how perception arises from sensation.

Results

Stimulus space and linearly inseparable problems

Two macaque monkeys were trained to perform a classification task by executing a saccade

towards the side corresponding to the orientation of an MIC (Fig. 1A). The MIC stimuli used in

this study were generated by moving dots, with their movement determined by two parameters.

As illustrated in in Fig. 1B, dots in opposing halves moved in opposite directions along a motion

axis (e.g., dot I and dot II in Fig. 1B, left). The motion axis could rotate within a range of $[0, \pi]$,

creating a circular structure (Supplementary Fig. 1A). For dots within the same half, one dot

(e.g., dot III) either led or trailed another (e.g., dot IV) (Fig. 1B, right), quantified by the angular

location of one dot relative to another, namely sheared configuration (Supplementary Fig. 2A &

2B). The sheared configuration varies periodically over $[0, 2\pi]$ (Supplementary Fig. 1B).

Accordingly, these two periodic parameters together define a stimulus manifold with a torus

topology (Supplementary Fig. 3, left), where each point represents a stimulus generated by a

unique combination of the motion axis and sheared configuration. In this study, we only used a

subset of this stimulus manifold. Specifically, we first projected the 2-D circular structure of the

motion axis onto the 1-D axis, selecting values of 0 and $\pi/2$ (Fig. 1C, left), while retaining the

2-D circular structure of the sheared configuration (Fig. 1C, right). Consequently, the subset

manifold has a cylindrical topology (Supplementary Fig. 3, right). Within this cylindrical

manifold, we sampled two values, 0 and $\pi/2$, referred to as the HV (horizontal versus vertical)

and four values from the sheared configuration ($\pi/4$, $3\pi/4$, $5\pi/4$ and $7\pi/4$, Fig. 1C, right),

defining two orthogonal axes: OI (outward versus inward) and CA (clockwise-like versus anti-

clockwise-like). These three axes of HV, OI, and CA were used to construct a 3-D Euclidean

space embedded in the stimulus manifold (Fig. 1D), referred to as the stimulus space. Eight

stimuli used in this study were positioned at the vertices of an inner cube tangent to the

cylindrical manifold.

In this stimulus space, MIC stimuli with one contour orientation formed by the

combination of different values in these three axes (e.g., right-titled, No.1 – No.4, red) were

interspersed with stimuli of the opposite orientation (i.e., left-tilted, No. 5 – No.8, blue) (Fig. 1D;

see Supplementary Movie. 1 for the 8 stimuli). This interspersion resulted in contour orientations

being linearly inseparable within this stimulus space, presenting a significant challenge for

classification. However, both macaques adeptly performed the task with an accuracy exceeding

90% at 100% motion coherence (Ma et al., 2021). Next, we investigated how neurons in

macaques' V2 tackle this linearly inseparable problem particularly from the perspective of neural

geometry.

Figure 1. Stimulus Space. (A) Left: Discrimination task on contour orientations. Monkeys were trained to

make saccades according to contour orientations. Right: A right-titled contour orientation formed by

surrounding moving dots. This figure is modified from Ma et al, 2021. RF: Array population receptive field.

(B) Stimulus features. An MIC stimulus is defined by the motion axis of moving dots (left: dot I and II move

horizontally) and the sheared configuration of the relative positioning of adjacent dots within the same half

(right: dot III and IV is $5\pi/4$ in sheared configuration, which is outward and anti-clockwise-like). (C) Feature

axes of stimulus space. Left: HV axis. Two values sampled from the motion directions of $[0, \pi]$, representing

horizontal (0) versus vertical ($\pi/2$) directions, thus forming the HV (Horizontal vs. Vertical) axis. Right: OI and

CA axes. Four values sampled from the sheared configuration of $[0, 2\pi]$: $\pi/4$, $3\pi/4$, $5\pi/4$ and $7\pi/4$, creating two

independent axes of OI (outward versus inward) and CA (clockwise-like versus anti-clockwise-like). Note that

the feature "clockwise" (and anti-clockwise) reflects the relation positions of moving dots, not the actual

rotation of moving dots. Within these three feature axes, the stimulus (red) is horizontal, outward, and anti-

clockwise-like. (D) Stimulus space. The eight stimuli used in the study, each labeled numerically and color-

coded based on their contour orientations (red: right-tilted; blue: left-tilted). In this stimulus space, the

classification of contour orientations poses a linearly inseparable problem.

Sensory and perceptual manifolds

To investigate how the brain addressed this linearly inseparable problem, we utilized neural

activity data from V2 neurons of two monkeys (93 neurons in total) to construct a high-

dimension neural space (see Methods; for neurons' receptive fields and selectivity, see

Supplementary Fig. 4). First we utilized linear support vector machines (SVM) to analyze the

collective activity to all the 8 stimuli to determine whether the three feature axes of the stimulus

space (Fig. 1D), HV ({1,2,5,6} versus {3,4,7,8}), OI ({1,3,5,7} versus {2,4,6,8}), and CA

({2,3,5,8} versus {1,4,6,7}), could be decoded. We found that classifications along all three axes

were linearly separable, with accuracies above 75% and significantly higher than the shuffled

baseline (bootstrap t-tests, all ps < 0.001) (Fig. 2A). This finding was replicated with other

methods such as the analysis on population average responses and the principal component

analysis (Supplementary Fig. 5). Critically, the optimal separation direction vectors (determined

by SVM, see Methods) for HV, OI, and CA, were mutually orthogonal. That is, the distribution

of the subtended angles between these vectors was significantly more concentrated around 90°

than the distribution of angles between two random direction vectors, and also significantly

larger than angle distributions between the same classification vectors (Supplementary Fig. 6).

To visualize the dynamic encoding of the stimuli by the neuronal population, we projected

the neural states in the high-dimensional neural space into a 3-D neural subspace formed by the

direction vectors for HV, OI, and CA (see Methods). Figure 2B shows that, prior to stimulus

onset, neural states for the stimuli were closely clustered and inseparable. Following the onset,

these states gradually spread and became completely separable along the HV axis. They then

remained in a steady phase for the duration of stimulus presentation before returning to their

original locations after stimulus offset (see Supplementary Movie. 2 and Supplementary Fig. 11).

Similar dynamic patterns were observed for the OI (Fig. 2C) and CA (Fig. 2D) axes as well. To

further illustrate the neural geometry constructed by the neural states at the steady phase, we

used the activity magnitude of neurons from 200ms to 500ms post-stimulus onset as the neural

states, which were then projected to this 3-D subspace (see Methods). Figure 2E shows that the

neural states were located at eight vertexes of a slightly distorted cube, corresponding to the

geometric relation among stimuli in the original stimulus space (Fig. 1D). This neural manifold

embedded in the high-dimensional neural space is referred to as the "sensory manifold" because

it directly responded to the stimulus space without involving interpretation, as contour

orientations remain linearly inseparable in this manifold. To further demonstrate that this

manifold was associated with sensory processing, we examined the relationship between its

geometry and the intensity of sensory signals. We found that the sensory manifold was sensitive

to variations in the coherence of moving dots in the stimuli, giving rise to a series of concentric

cubic sensory manifolds, with higher coherence levels eliciting larger cubic manifolds

(Supplementary Fig. 8). Taken together, the sensory manifold faithfully represented the stimulus

space, with HV, OI, and CA serving as the axes of the neural subspace that embedded this

manifold.

Based on previous studies showing that individual neurons that are sensitive to contour

orientation (Marcar et al., 2000; Ma et al., 2021), we used the SVM analysis to explore axes in

this high-dimensional neural space that could linearly decode contour orientations. We identified

an axis that can differentiate left-tilted orientation from the right-tilted orientation, referred to as

the LR axis, with an accuracy comparable to that of decoding the stimuli's features (i.e., HV, OI,

and CA) (Fig. 2A, orange line). Figure 2F illustrates the neural states along the LR axis, where

contour orientations became linearly separable (for dynamic trajectories see Supplementary Fig.

11 & Supplementary Movie 2), consistent with the finding from studies on single neurons

(Marcar et al., 2000; Ma et al., 2021). Critically, this LR axis was orthogonal to the three

stimulus feature axes of the sensory manifold (Supplementary Fig. 6A), suggesting that the LR

axis emerged not directly from the stimuli but from the interpretation of the sensory data.

Evidence supporting this conjecture comes from the analysis on the latency of the emergence of

the LR axis, which occurred about 30ms after the emergence of the axes encoding the stimuli's

features (i.e., HV, OI, and CA) (Fig. 3F). This observation aligns with previous findings on

visual motion segregation (Braddick, 1993; Lamme, 1995; Marcar et al., 2000; Chen et al., 2014;

Hu et al., 2018), implying that extra time may be needed to form this new axis. This new neural

manifold, embedded in the high-dimensional neural space including the LR axis for representing

contour orientations and the axes for stimulus features (i.e., LH, OI, and CA), is therefore

referred as the perceptual manifold, where the linearly inseparable problem was addressed. Next,

we explored how this LR axis was formed through geometric transformation.

Figure 2. Neural geometry of sensory and perceptual manifolds. (A) Accuracies over time by linear SVM

classifiers. The SVMs were trained on neural data within the time interval [-200ms, 1000ms] relative to

stimulus onset. Shaded regions denote the mean SVM accuracy (±3 standard deviations) of the baselines by

shuffling stimulus labels 1000 times. Individual monkey's results are shown in Supplementary Fig. 9 E & F.

(B-D) Dynamic trajectories of neural states. Changes in neural states from -200ms to 1000ms were projected

onto a neural subspace defined by the HV, OI, and CA axes. Identical trajectories are presented from various

perspectives to optimally illustrate the separation by these three stimulus feature axes. Blue and red colors

indicate categorizations along the HV, OI, and CA axes for (B), (C), and (D), respectively. Arrows on the

trajectories correspond to the progression of the neural states over time. The neural states prior to stimulus

onset are indicated in gray. The motion coherence level is 7. Individual monkey's results are shown in

Supplementary Fig. 10. The time courses of neural states (-200–1000ms) projected to each axis are shown in

Supplementary Fig. 11. (E) Sensory manifold. The centers of the point clouds for eight stimuli in the steady

phase (200ms–500ms after stimuli onset) are connected with dashed lines. Cool and warm colors indicate the

two contour orientations, respectively. All motion coherence levels were used. Individual monkey's results are

shown in Supplementary Fig. 9 A & B. (F) Dynamic trajectories of neural states along the LR axis. The point

clouds follow the same color code as in panel E, with their centers marked with solid circles. All motion

212 coherence levels were used. Note that cool and warm colors are separated along the LR axis. Motion strength

213 (r), which is the Euclidean distance between the neural states and the origin in panel E, is included for display

214 purposes only.

Nonlinear mixed selectivity neurons and twist operations

Traditional solutions to linearly inseparable problems such as the XOR problem involve

expanding dimensions of the original representational space (Minsky & Papert 1969; Fusi et al.,

2016). Previous studies have shown that neurons with nonlinear mixed selectivity (NMS) can

expand dimensions by responding to combinations of input features (Rigotti et al., 2013; Fusi et

al., 2016; Kaufman et al., 2022; Tye et al., 2024) and using nonlinear activation functions

(Cybenko 1989; LeCun et al., 2015) to capture higher-order interactions. In fact, all V2 neurons

used in this study showed interactive responsiveness to three stimulus features (HV, OI and CA)

(significant three-way interactions: minimum $F(1, 2200) = 18.25$, $p < 0.001$), as our formal

proof shows that this interactive responsiveness is a unique characteristic of NMS neurons

(Supplementary Notes N.16). Therefore, these NMS neurons in the V2 area may that play a

critical role in generating the LR axis through dimension expansion.

To reveal how NMS neurons expand the dimensions of representational spaces, here we

examined the relationship between neurons' response profiles and their ability to expand

dimensions using a one-layer network consisting of three neurons, s_1, s_2 and s_3. These

neurons receive inputs consisting of two continuous features, a and b, that form a 2-D feature

sheet (Fig. 3A, top). In this context, the XOR problem is defined as categorizing points located at

diagonally opposite corners (i.e., red versus blue points). The neurons in this network receive (1)

either pure (either a or b) or mixed (the combination of a and b) inputs, and (2) possess

either linear or nonlinear (e.g., ReLU) activation functions, leading to four distinct output

patterns (Fig. 3A, bottom).

Neurons with pure selectivity and the linear activation function (i.e., linear pure selectivity)

afford only a simple affine transformation, including rotation and shifting, of the original feature

sheet (Fig. 3B). Because the rotation axis is aligned with the orange and black edges, the edges

remain parallel after the transformation. For neurons with nonlinear pure selectivity, the feature

sheet undergoes bending due to the nonlinear activation function (Fig. 3C). This bending occurs

along an axis parallel to the orange and black edges, so the edges remain parallel after bending,

and the four corner points still lie on the same plane. For neurons with linear mixed selectivity

(Fig. 3D), the feature sheet experiences a complex affine transformation, with the rotation axis

not aligning with the three main axes. However, even after this rotation, the edges remain

parallel. In these three scenarios, neither bending nor rotation alone suffices to make the red and

blue points linearly separable.

In contrast, NMS neurons perform both bending and rotation operations on the feature

sheet, which make the orange and black edges no longer parallel (Fig. 3E) and thus create a new

axis perpendicular to the original orange and black edges. In this newly constructed

representational space, the XOR problem becomes linearly separable. The combined effects of

bending and rotation operations on the 2-D feature sheet can be conceptualized as a "twist"

operation. Accordingly, we refer to this unique characteristic of NMS neurons acting on the

geometry of input features as the twist operation (for a similar idea, see Nogueira et al, 2023).

Figure 3: NMS neurons and twist operations. (A) Top: The 2-D feature sheet represents all possible combinations of stimulus features a and b. Two edges of this sheet are highlighted as orange and black, and four corners are colored red and blue to indicate different categories. Bottom: Four types of neurons' response profiles derived from the combination of input (pure versus mixed) and activation functions (linear versus nonlinear). ReLU is used for the illustration of nonlinear activation functions. The neuron marked in light purple denotes an NMS neuron. (B-E) The geometries in the neural space constructed by (B) three linear pure selectivity neurons, (C) three nonlinear pure selectivity neurons, (D) two linear pure selectivity neurons and one linear mixed selectivity neuron, or (E) two nonlinear pure selectivity neurons and one NMS neuron.

With this unique characteristic of NMS neurons, we further explored how the LR axis was formed from three feature axes (HV, OI, and CA) theoretically. For simplicity, we used x, y, and z to denote the three feature axes of HV, OI, and CA, respectively. The coordinates of the points on the cylindrical manifold were denoted as (x, y, z) (Fig. 4A, left). In the x-y-z coordinate system, the four vertices {1,3,5,7} of the sensory manifold in the z-x plane exemplify a

standard planar XOR problem (Fig. 4A, left). With a twist operation around the x axis (Fig. 4A,

middle), the 2-D plane is transformed into a curved surface in a 3-D space (Fig. 4A, right),

creating a new coordinate axis, denoted as $v = zx$. Thus, the points on this curved surface have

coordinates (z, x, zx). Further, when letting the two levels on one axis represent the true and

false values of a Boolean variable, the axes are equivalent to Boolean variables (see

Supplementary Methods, M.1). Accordingly, the Boolean variable V of the new v-axis is equal

to the XOR operation of the Boolean variables Z of the original z-axis and X of the original x-

axis, expressed as $V = Z \oplus X$. Therefore, the twist operation in neural geometry equals the

XOR operator in logic.

To examine whether this theoretically derived v axis was actually present in the high-

dimensional neural space, we trained linear SVMs to classify three sets of vertex pairs among the

four vertices shown in Fig. 4A. As expected, the vertex pair of {1,5} versus {3,7} and that of

{1,7} versus {3,5} were linearly separable along the x and z axes, respectively, with accuracies

greater than 75%. Critically, the vertex pair of {1,3} versus {5,7}, a standard planar XOR

problem, was also linearly separable along the v axis with accuracy greater than 75%. That is,

the v axis, theoretically derived from the twist operation, was indeed present in the high-

dimensional neural space (Fig. 4B).

To examine whether this twist operation can generalize from the planar XOR problem to

address the cubic XOR problem (i.e., {1, 2, 3, 4} versus {5, 6, 7, 8}, Fig. 4C, left), in addition to

one twist operation equivalent to $V = Z \oplus X$ (Fig. 4C, middle), we incorporate a second twist

of the manifold's y-v projection around the y axis to make the vertex pair of {1, 2, 3, 4} versus

{5, 6, 7, 8} linearly separable (Fig. 3C, right). In this second twist, a new axis, denoted as $p =$

$vy = zxy$, is constructed. Logically, this axis is equivalent to $P = V \oplus Y = Z \oplus X \oplus Y$,

meaning the true and false values of P is obtained by concatenating Z, X, Y through two XOR

operators.

Figure 4: Twist operations on the classification of contour orientations. (A) Twist operations on planar

XOR problems. Left: Coplanar vertices $\{1,3,5,7\}$ are colored based on contour orientations, forming a

standard XOR problem on the $z\text{-}x$ plane. Middle: A twist operation around the x-axis resolves the XOR

problem by rotating two parallel edges in opposite directions. Right: This twist operation generates the v axis

orthogonal to the $z\text{-}x$ plane. (B) SVM classification accuracies over time. Shaded regions denote the mean

SVM accuracy (±3 standard deviations) of the baselines by shuffling stimulus labels 1000 times. (C) Double

twist operations on a cubic XOR problem. Two consecutive twists are required to correctly classify the 8

vertices according to their contour orientations. Left: Theoretical sensory manifold in the x-y-z space;

Middle: Intermediate manifold achieved after one twist operation on the z-x plane, with the emergence of the

new v axis. Right: Task-relevant p axis emerges after the second twist operation on the y-v plane. (D)

Neural manifolds corresponding to the theoretical manifolds achieved through twist operations. The axes of x,

y, z, v and p in the neural space were determined by corresponding SVM classifiers. Eight point clouds of

neural states corresponded to the 8 stimuli, and the centers of the clouds were used to depict the geometry of

neural manifolds through linear fitting. (E) Angle distribution between x, y, z, v and p axes. The

distribution of the subtended angles between the optimal separation direction vectors as determined by SVM

was concentrated around 90°. (F) Latency of axis emergence. Left: Classification accuracies of the axes over

time. The latencies of the emergence of the z, y, x, v, and p axes (against their corresponding baselines) at

43ms, 53ms, 57ms, 65ms, and 87ms, respectively. Shaded regions denote the mean SVM accuracy ($\pm$3

standard deviations) of the baselines by shuffling stimulus labels 1000 times. Right: Latencies of the sensory

axes (0-twist, blue), the intermediate axes (1-twist, green), and the task-relevant axis (2-twist, red). **: $p <$

0.001. Also see Supplementary Fig. 14 C & D. For the single monkey results, see Supplementary Fig. 15.

To examine whether the theoretically-derived intermediate v axis through one twist

operation was indeed present in the high-dimensional neural space when considering the

complete sensory manifold, we searched the z-x-v subspace (Fig. 4C, middle) in the high-

dimensional neural space, where the vertices {1, 3, 6, 8} was linearly separable from the vertices

{2, 4, 5, 7}. The SVM analysis showed that these two sets of vertices were indeed linearly

separable (Fig. 4D, middle). This finding confirms the existence of the v axis in the high

dimensional neural space. In addition, the theoretically-derived p axis through double twist

operations on the given sensory manifold is indeed the LR axis, as the p axis was approximately

parallel to the LR axis (Supplementary Fig. 13). Finally, the theoretically-derived manifolds from

twist operations (Fig. 4C) closely matched the neural manifolds derived from actual neural states

(Fig. 4D) (all $R^2 \geq 0.8$, for details see Methods). Note that the empirical v and p axes, as well

as the z, x, and y axes, were mutually orthogonal, as prescribed by twist operations (Fig. 4E).

Therefore, the perceptual manifold observed in the macaques' V2 may undergo geometric

transformations equivalent to the twist operations from the sensory manifold.

Evidence supporting this conjecture comes from the analysis on the latency of the

emergence of the intermediate v axis, which should emerge after the sensory axes of z and x,

upon which the first twist operation acts, and before the task-relevant p axis, which relies on the

v axis for the second twist. Consistent with this prediction, the empirical v axis emerged

(against the baseline) at 65ms post-stimulus onset, significantly later than the emergence of the

empirical z, x, and y axes (at 43ms, 57ms, and 53ms, respectively; bootstrap t-test, ps < 0.001),

and yet earlier than that of the empirical p axis (at 87ms; bootstrap t-test, p < 0.001) (Fig. 4F,

left; for the time courses of all intermediate axes, see Supplementary Fig. 14 C & D).

Taken together, the presence of the intermediate v axis predicted by twist operations, not by

the classification task itself, suggests that the perceptual manifold is the product of mentally

processing sensory data with the involvement of NMS neurons. Next, we examined the neural

geometry of the perceptual manifold and its functionality.

Dimensionality of perceptual manifold

Given the commutative nature of the equivalent logical computation, that is $P = Z \oplus X \oplus Y =$

$X \oplus Y \oplus Z = Y \oplus Z \oplus X$, we predicted the existence of two additional intermediate axes of

u and v, which correspond to $U = X \oplus Y$ and $W = Y \oplus Z$, respectively. Specifically, the u

axis can differentiate vertices {1,4,5,8} from vertices {2,3,6,7}, and the w axis can differentiate

vertices {1,2,7,8} from vertices {3,4,5,6} (Supplementary Fig. 12A&C). Consistent with this

prediction, the SVM analysis showed significantly higher classification accuracies for these

vertex sets compared to the baseline, confirming the existence of these two intermediate u and

w axes in the high-dimensional neural space (Supplementary Fig. 14A). The characteristics of

the u and w axes were the same as those of the v axis: first, the u and w axes were

orthogonal to each other and to other axes (Supplementary Fig. 14B); second, they emerged

subsequent to the sensory axes (i.e., z, x, and y axes) yet prior to the p axis ($F(2, 697) =$

1015.6, $p < 0.001$; for pairwise comparisons, all $ps < 0.001$, Bonferroni corrected) (Fig. 3F,

right; also see Supplementary Fig. 14C); third, the cubic XOR problem (i.e., the classification of

contour orientations) can be addressed using either the u axis or the w axis as the intermediate

axis (Supplementary Fig. 12). In addition, these 7 axes were present in each of three cytochrome

oxidase stripes (i.e., thin, thick, and pale) in the V2 area, suggesting that the twist operation is

likely a general property of V2 neurons (Supplementary Fig. 16). Taken together, the

dimensionality of the perceptual manifold was at least 7, much higher than that of the sensory

manifold (i.e., 3).

An intriguing question arises: why was the perceptual manifold embedded in a 7-D space

when a 4-D space, constructed by x, y, z, and p axes, is sufficient to satisfy the task demand of

classifying contour orientations? One possibility is that the availability of multiple alternative

pathways to construct the task-relevant p axis enhances the robustness for the classification.

Alternatively, the perceptual manifold may not be task-specific; rather, the classification of

contour orientations could be just one of its many possible applications. In fact, for the stimulus

space with 8 vertices, there are $2^8 = 256$ possible classifications. Some are linearly separable in

the stimulus space, such as vertex {1} versus {2,3,4,5,6,7,8} or vertices {1,5} versus

{2,3,4,6,7,8} (Fig. 5A), while others are not, such as {1,3} versus {2,4,5,6,7,8} (Fig. 5B). In

total, in the stimulus space, 104 classifications are linearly separable, and 152 are not (for a full

list, see Supplementary Fig. 17 and Supplementary Table. 1). Critically, all linearly inseparable

classifications in the stimulus space become linearly separable in the 7-D space. For example, the

vertex pair of {1,3} versus {2,4,5,6,7,8} becomes linearly separable in the y-z-p subspace (Fig.

5C). In total, there are $C_3^7 = 35$ 3-D subspaces embedded in the 7-D perceptual space

(Supplementary Fig. 18), and each of the 152 linearly inseparable classifications becomes

linearly separable in at least one of these 35 subspaces (Supplementary Table. 2). That is, every

possible classification in the stimulus space is linearly separable in this 7-D perceptual manifold.

Therefore, the perceptual manifold is unlikely for decision-making or action; rather, it may

provide a reservoir of all possible candidates (in our case, solutions for all possible

classifications) for higher-order cognitive processes. Consistent with this conjecture, after

excluding task-relevant neurons that showed high sensitivity to contour orientations from the V2

neuron population, the remaining neurons retained the ability to classify contour orientations at

the population level (Supplementary Fig. 7).

Figure 5: Linearly separable and inseparable classifications in the stimulus space. (A) Examples of

linearly separable but non-axial classifications in the stimulus space. The classification separates a subset of

vertices (with the set size of 0, 1, 2, 3, and 4, red) from the rest (blue). (B) Examples of linearly inseparable

classifications in the stimulus space, including the classification of contour orientations (right). (C) The

classifications in panel B become linearly separable in new subspaces through twist operations.

The necessity and sufficiency of NMS neurons in dimension expansion

The aforementioned analyses showed the important role of NMS neurons in expanding

dimensions of representational spaces through twist operations. Here, we further examined the

necessity and sufficiency of NMS neurons in dimension expansion. To do this, we first compared

NMS neurons with pure selectivity neurons in carrying out all possible classifications in the

stimulus space. We generated synthetic neurons exclusively tuned to one of the three stimulus

features (Supplementary Fig. 21) based on real recorded data in V2 to simulate neurons with

pure selectivity (Rigotti et al., 2013). For example, Fig. 6 A & B show a typical NMS neuron in

the V2 area responding differently to HV and CA and showing no sensitivity to OI (top), and a

typical synthetic neuron with pure selectivity to OI (bottom).

Figure 6: Necessity of NMS neurons and heterogeneous connectivity structure. (A) Time courses of an NMS neuron (top) and a synthetic neuron with pure selectivity (bottom). Colors and numbers denote different stimuli and their associated neural responses. The time course of the synthetic neuron was generated by modifying the time course of the NMS neuron shown above. (B) Average activity of the NMS neuron (top) and the synthetic neuron (bottom) from 200ms to 750ms after stimulus onset. Colors denote different conditions of a feature, and error bars denote the standard error of mean. (C) The number of successful linear classifications increased as a function of neuron population size for both pure selectivity neurons (gray) and NMS neurons (dark). The gray curve plateaus at 104, the total number of linearly separable classifications in the stimulus

space, whereas the dark curve converges to 256, including both 152 linearly inseparable classifications and 104 linearly separable ones. Real neuron: neurons recorded in the V2; Pure neuron: synthetic neuron with pure selectivity; error bar: standard deviation. (D) Schematic illustration of a two-layer feedforward neural network. Each output neuron of the network receives the inputs encoding three stimulus features (HV, OI and CA), indexed by x, y, and z, respectively, from the input neurons. The connectivity weights are randomly sampled from a multivariate Gaussian distribution, with the thickness of lines indicting the magnitudes of the weights. Connectivity patterns from feature x to the output neurons are highlighted by colors for display purposes. The response of output neurons is achieved through linear summation and ReLU activation. Networks with three levels of diversities in connectivity patterns are shown from left to right. (E) Visualization of neural manifolds in 3-D subspaces when $d = 1$ from a typical simulation. Left: Sensory manifold that corresponds to the stimulus space; Middle: Intermediate manifold after one twist operation; Right: The subspace where linearly classification of contour orientations is achieved. Each point denotes the neural state of a stimulus, with red and blue colors representing the two contour orientations, respectively. (F) Visualization of the neural manifold in a 3-D subspace when $d = 0$ from a typical simulation. The subspace is constructed by the first three PCs of neurons' activation. (G) Variance explained by PCs of neurons' activation with different level of diversity in connectivity patterns from a typical simulation for each d value. When $d = 0$, indexed by the dashed line with the lightest blue, the variance is nearly explained by the first PC alone. When $d = 1$, indexed by the dashed line with the darkest blue, the curve of variance explained by each PC is flattened. (H) The dimensionality and the number of successful classifications as a function of heterogeneity in response profiles from 100 simulations for each d value. Left axis (blue): the number of successful classifications. Right axis (red): inferred dimensionality of neural manifolds constructed by the network (for details, see Methods). Error bar: standard deviation.

To evaluate the classification performance for 152 linearly inseparable problems (Supplementary Table. 1) and 104 linearly separable problems (Supplementary Table. 2), we used a population-increment procedure (Rigotti et al., 2013), where the population size was

progressively increased from a single neuron to the entire set of 93 neurons, adding one

randomly selected neuron each time. During each iteration, we trained SVMs with neural

activities for all possible classifications, and a classification accuracy threshold of 75% was set

as the criterion for successful classification (for details, see Methods). Figure 6C shows the

number of successful linear classifications as a function of neuron population size. With NMS

neurons, we succeeded in all possible classifications (256 in total), for both linearly separable

and inseparable problems (Fig. 6C, black curve), when the number of NMS neurons exceeded

81. In contrast, using the synthetic neurons with pure selectivity, the total number of successful

classifications plateaued at 104 (Fig. 6C, gray curve) when the population size exceeded 49. That

is, additional increase in neuron population size did not further improve classification

performance.

Critically, close examination of the problems successfully classified by pure selectivity

neurons revealed that they were all linearly separable in the stimulus space (Supplementary

Table. 1), and none came from the set of linear inseparable problems (Supplementary Table. 2).

That is, neurons with pure selectivity can only address linearly separable problems, as they alone

cannot expand the sensory manifold to a higher dimensionality. Taken together, this finding

suggests that regardless of neuron population size, NMS neurons are necessary in expanding the

dimensionality of neural manifolds, hereby transforming the sensory manifold into the perceptual

manifold.

The finding that at least 81 neurons were needed for forming the 7-D perceptual manifold,

as shown in Fig. 6C, highlights the importance of population-level activity in dimension

expansion. Indeed, previous studies have shown that neurons' diverse response play an important

role in computational capacity (Rigotti et al., 2010; Kriegeskorte et al., 2021; Gast et al., 2024).

To quantify how diversity in response profiles of NMS neurons influences dimension expansion

of the representational space, we built a two-layer feedforward neural network tasked with

processing the stimuli used in the macaques' experiment (for details on the network, see

Methods). In this network, each output neuron receives the combination of all three stimulus

features (i.e., HV, OI and CA) from the input neurons and employs a nonlinear activation

function (i.e., ReLU), with connectivity weights independently sampled from a multivariate

Gaussian distribution. As a result, all output neurons in this neural network demonstrate a

response profile of nonlinear mixed selectivity.

In this network, the response profiles of NMS neurons are controlled by a parameter d,

which denotes the degree of diversity in connection patterns between the two layers (Fig. 6D).

This diversity ranges from identical patterns ($d = 0$) to completely uncorrelated patterns ($d = 1$)

(see Methods). When $d = 1$, each NMS neuron generates a distinct response because the

connection pattern from the input neurons is unique (Fig. 6D, right), and therefore the matrix of

connectivity weights is full rank. SVM analysis, similar to that performed on the macaques' data,

was carried out to identify the 7-D perceptual manifold. For visualization, neurons' activations

are projected into 3-D subspaces (Fig. 6E), where each dot denotes the neural state of a stimulus,

with red and blue colors representing the two contour orientations, respectively. Within this 7-D

perceptual manifold, we can identify the sensory manifold embedded in a 3-D subspace

constructed by axes corresponding to the three stimulus features (Fig. 6E, left), the intermediate

manifold in a 3-D subspace with a new axis v after one twist operation (Fig. 6E, middle), and

the subspace achieved after the second twist operation where linearly separating contour

orientations becomes possible (Fig. 6E, right). In addition, continuous stimuli that spanned the

entire sheared configuration ring (Fig. 1C, right) produced similar results (Supplementary Fig.

22). In sum, the 7-D perceptual manifold constructed by the network of NMS neurons with

random connectivity patterns (i.e., $d = 1$) is comparable to the 7-D perceptual manifold

identified in the macaque's V2 (Fig. 4D).

In contrast, when $d = 0$, all NMS neurons have the same inputs and thus generate

identical responses. Accordingly, the matrix of connectivity weights in the network is rank 1 (or

0 if all weights are 0), resulting in low dimensionality of the neural manifold (inferred dimension

= 1.3, std. = 0.70, see Methods). This low dimensionality is also revealed is demonstrated by

PCA analysis of the variance in neuron activation (Fig. 6G). When $d = 0$, the first PC explained

99.84% of the total variance, leaving nearly no variance for the remaining PCs. As a result, the

neural states of the stimuli were confined to an approximately 1-D space (Fig. 6F). In contrast,

when $d = 1$, the first 6 PCs (99.78%) were required to explain the same amount of variance as

the first PC when $d = 0$. Thus, when $d = 1$, the neural states of the stimuli were dispersed into

a higher dimensional neural space. Therefore, the neural manifold constructed by the network

with no diversity (i.e., $d = 0$) suffers a severe deficit in performing either linear or nonlinear

classification (the number of linearly separable problems successful addressed: 9.16, or 8.8% of

the whole set, std. = 2.89; the number of linearly inseparable problems successful addressed:

2.74, or 1.8%, std. = 2.23). These findings suggest that networks consisting of NMS neurons

with an identical response profile have limited computational capacity and thus hardly encodes

sufficient information, even when the response profile exhibits nonlinear mixed selectivity.

To systematically investigate how diversity in the response profiles of NMS neurons

influences the dimensionality of representational spaces, we constructed a series of neural

networks with different parameters d, and then measured the dimensionality and the

classification performances (see Methods). We found that as the diversity in response profiles

increased, the dimensionality increased monotonically (Fig. 6H, red curve). Interestingly, the

network did not need to possess completely diversity to form the perceptual manifold. With $d >$

0.5, the dimensionality reliably expanded to 7 (see Methods and Supplementary Methods M.5).

In parallel, the number of successful classifications increased monotonically, finally capable of

successfully carrying out all possible classifications (i.e., 256) once the dimensionality reliably

reached 7 (Fig. 6H, blue curve). Note that the linearly inseparable problems were resolved in

parallel with the linearly separable ones (Supplementary Fig. 23).

On the other hand, heterogeneity in response profiles alone seems insufficient, as neural

networks consisting of pure selectivity neurons with identical parameter d were only capable of

addressing linearly separable problems (Supplementary Fig. 24). Taken together, the synergy

between twist operations on input feature vectors by NMS neurons and the heterogeneous

response profiles among NMS neurons is critical, which optimally leverages neural networks to

construct a more complex, higher-dimensional neural space.

Discussion

In this study, we investigated how macaques' V2 neurons solve linearly inseparable problems

present in the physical world through the lens of neural geometry. By analyzing the neural

geometry embedded in the high-dimensional neural space formed by V2 neurons' collective

activities, we identified two related but distinct neural manifolds: the sensory and perceptual

manifolds. The sensory manifold, embedded in a 3-D subspace defined by the stimulus features,

faithfully represented the raw sensory input where contour orientations remained linearly

inseparable. However, through a series of geometric transformation equivalent to twist

operations, this 3-D sensory manifold evolved into a 7-D perceptual manifold with four

additional axes, allowing for the linear separability of contour orientations. Critically, this

geometric transformation was achieved through the synergy between twist operations on input

feature vectors by NMS neurons at the individual neuron level and the heterogeneous response

profiles among NMS neurons at the population level. In summary, our study offers mechanistic

insights into how biological neural networks expand the dimensions of representational space,

transitioning from the sensory to the perceptual manifold, thereby advancing our understanding

of how information progresses from sensation to perception.

Previous studies on neural geometry have shown that neural manifolds can faithfully

represent both stimulus (Xie et al., 2022; Gardner et al., 2022; Bao et al., 2020) and action spaces

(Churchland et al., 2012; Gallego et al., 2017; Perich et al., 2020). In line with these findings, our

study identified a neural manifold embedded in a 3-D subspace defined by three mutually

orthogonal axes corresponding to the HV, OI, and CA features of the MIC stimuli. Along with

the finding that the size of this manifold was found to correlate with the intensity of motion

coherence, this manifold reflects the raw sensory input (i.e., the stimulus space) and is therefore

termed the sensory manifold. Importantly, our theoretical predictions, derived from the geometric

transformation of input feature vectors by NMS neurons, led to the identification of four

additional axes that encode features absent from the physical stimuli. Specifically, one of these

axes, resulting from double twist operations on the three feature axes of the sensory manifold,

encoded the perceived orientations of illusory contours, allowing for linear separability of

contour orientations that were not linearly separable in the sensory manifold. Interestingly, this

manifold was not specific to the task at hand, as it potentially accomplishes all 256 possible

classifications present in the stimulus space. Therefore, this manifold likely functions as an

intermediary between the sensory manifold and those associated with decision-making or action,

hence its designation as the perceptual manifold. Note that the perceptual manifold observed in

the V2 does not necessarily originate and terminate within the V2. It likely inherits

characteristics from feedforward inputs from the V1 and is further shaped by feedback from

downstream cortical regions such as the V3 and V4. Future research employing simultaneous

recordings across multiple areas is essential to elucidate the transformation from the sensory to

the perceptual manifold.

The creation of these perception-related axes was attributed to NMS neurons, which have

the unique ability to geometrically transform input feature vectors. This transformation is

equivalent to twist operations, thus expanding the dimensions of representational spaces (Fusi et

al., 2016; Rigotti et al., 2013). In contrast, neurons exclusively selective for a single feature or

those exhibiting a linear combination of selectivity for multiple features are unable to change

dimensionality. Therefore, NMS neurons appear to be necessary for interpreting sensory inputs

into perceptual experiences by generating latent variables from intermediate axes without direct

semantic descriptions (Johnston et al., 2020; Jazayeri & Ostojic, 2021). However, the mere

presence of NMS neurons is not sufficient; their functional efficacy depends on the heterogeneity

of their response profiles at the population level (Langdon et al., 2023; Kriegeskorte et al., 2021).

Through simulations of neural networks consisting of NMS neurons, we found that

homogeneous response profiles among NMS neurons limited their capacity of expanding

dimensions, thereby constraining the network's computational power in addressing both linearly

separable and inseparable problems. Conversely, increasing the heterogeneity of the response

profiles significantly enhanced dimension expansion, effectively transforming linearly

inseparable problems into linearly separable ones. In summary, our study reveals the symbiotic

relationship between the geometric transformation capability of individual NMS neurons and the

heterogeneity in the response profiles at the population level, underscoring the importance of

both individual neuron properties and population dynamics in achieving dimension expansion.

The high dimensionality of the perceptual manifold functions as a reservoir of

computational solutions, enabling flexible classifications according to downstream task

demands. That is, one key function of dimension expansion is apparently to facilitate parallel

processing, allowing multiple computations (such as classifications in this study) to occur

simultaneously across different dimensions. As these computations are distributed across

multiple dimensions in parallel, they become less reliant on conscious control and more

automatic. However, this parallel processing comes with a cost, as the number of potential

solutions increases exponentially with the number of dimensions. In our study, downstream

cortical regions involved in decision-making, which is usually sequential processing, must select

the appropriate classification from 256 possibilities to meet the task demands. While the

mechanism for effectively navigating these potential solutions based on task demands remains

largely unknown, the modulation of NMS neurons' response profiles through Hebbian ("fire

together wire together") and anti-Hebbian ("out of sync, lose the link") rules (Caporale & Dan,

2008) might offer insights into reducing dimensionality and thus narrowing the range of potential

solutions. In networks governed by Hebbian plasticity, neurons frequently co-activated by

similar tasks or stimuli develop more homogeneous response profiles, leading to the formation of

specialized modules with relative lower dimensionality (Bullinaria, 2007; Lindsay et al., 2017;

Weigand et al., 2017). This idea is supported by recent findings showing that sequences of

contextually related images (e.g., natural video) are represented in a neural space with lower

dimensionality, evidenced by straighter neural population trajectories, compared to sequences of

contextually unrelated stimuli (Hénaff et al., 2021).

Conversely, under anti-Hebbian rule, task-relevant features are disentangled from task-irrelevant ones, which may result in the compression of axes representing these task-irrelevant features, thereby reducing effective dimensionality (Rajan et al., 2010; Ganguli et al., 2012; Farrell et al., 2022). This type of geometric transformation reshapes the representational space to focus on task-relevant features (Bernardi et al., 2020). This conjecture is supported by our findings that although the perceptual manifold can accomplish all 256 classifications, the accuracy along some dimensions (such as CA axis) was lower than others, suggesting that not all features are equally represented in the neural space. Taken together, along the hierarchy of the ventral visual stream, the amount of information encoded in each dimension varies significantly (Stringer et al., 2019), and the relational structure between representations evolves from relatively simple and straightforward to more abstract and complex, reflecting the integration of multiple features and the emergence of high-level perceptual categories (Lin & Kriegeskorte, 2023). This dynamic transformation further orchestrates the progression from perceptual to decision-making manifolds and ultimately to action-oriented manifolds, through intensive interplay of top-down and bottom-up processing, enabling us to act upon the physical world in response to stimuli that have acted upon us.

Supplemental Information

Supplemental Materials includes 25 figures, 2 tables and 2 videos.

Acknowledgments

We thank Dr. Xingyu Liu for her valuable discussion and comments, and Dr. Haidong Lu for his supervision on conducting the experiments. This study was funded by Beijing Municipal Science

Author contributions

H.M., L.J., T.L. and J.L. developed the theoretical framework. H.M. performed the experiments,

collected the data, and compiled the data. H.M., L.J., T.L., and J.L. conceived the data analyses.

H.M. and L.J. performed the data analyses. L.J. developed the double-twist model. T.L.

performed the network simulation. H.M., L.J., and J.L. wrote the paper.

Competing interests: Authors declare no competing interests.

Reference

Bao, P., She, L., McGill, M. & Tsao, D. Y. A map of object space in primate inferotemporal

cortex. *Nature* **583**, 103–108 (2020).

Bassett, D. S. & Sporns, O. Network neuroscience. *Nat Neurosci* **20**, 353–364 (2017).

Bernardi, S. *et al.* The Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. *Cell*

183, 954-967.e21 (2020).

Biederman, I. Recognition-by-Components: A Theory of Human Image Understanding. *Psychol*

Rev **94**, (1987).

Braddick, O. Segmentation versus integration in visual motion processing. *Trends Neurosci.* **16**,

263–268 (1993).

B. Schölkopf and A. J. Smola, *Learning with Kernels: Support Vector Machines Regularization*

Optimization and Beyond. (MIT Press, Cambridge, 2002).

Bullinaria, J. A. Understanding the emergence of modularity in neural systems. *Cogn. Sci.* **31**,

673–695 (2007).

Caporale, N. & Dan, Y. Spike Timing – Dependent Plasticity : A Hebbian Learning Rule. (2008)

doi:10.1146/annurev.neuro.31.060407.125639.

Chen, M. *et al.* An Orientation Map for Motion Boundaries in Macaque V2. *Cereb. Cortex*

(2014) doi:10.1093/cercor/bhu235.

Chung, S. & Abbott, L. F. Neural population geometry: An approach for understanding

biological and artificial neural networks. *Curr. Opin. Neurobiol.* **70**, 137–144 (2021).

Chung, S., Lee, D. D. & Sompolinsky, H. Classification and Geometry of General Perceptual

Manifolds. *Phys. Rev. X* **8**, 31003 (2018).

Churchland, M. M. *et al.* Neural population dynamics during reaching. *Nature* **487**, 51–56
(2012).

C. K. Williams and C. E. Rasmussen, *Gaussian Processes for Machine Learning.* (MIT Press,
Cambridge, 2006).

Cybenko, G. Approximation by superpositions of a sigmoidal function. *Mathematics of Control,*
Signals, and Systems **2**, (1989).

DiCarlo, J. J. & Cox, D. D. Untangling invariant object recognition. *Trends Cogn. Sci.* **11**, 333–
341 (2007).

DiCarlo, J. J., Zoccolan, D. & Rust, N. C. How does the brain solve visual object recognition?
Neuron **73**, 415–434 (2012).

Dyballa, L. *et al.* Population encoding of stimulus features along the visual hierarchy. Preprint at
bioRxiv https://doi.org/10.1101/2023.06.27.545450 (2023).

Farrell, M., Recanatesi, S., Moore, T., Lajoie, G. & Shea-Brown, E. Gradient-based learning
drives robust representations in recurrent neural networks by balancing compression and
expansion. *Nat. Mach. Intell.* **4**, 564–573 (2022).

Flesch, T., Juechems, K., Dumbalska, T., Saxe, A. & Summerfield, C. Orthogonal
representations for robust context-dependent task performance in brains and neural
networks. *Neuron* **110**, 1258-1270.e11 (2022).

Froudarakis, E. *et al.* Object manifold geometry across the mouse cortical visual hierarchy.
Preprint at *bioRxiv* https://doi.org/10.1101/2020.08.20.258798 (2020).

Fusi, S., Miller, E. K. & Rigotti, M. Why neurons mix: High dimensionality for higher cognition.
Curr. Opin. Neurobiol. **37**, 66–74 (2016).

Gallego, J. A., Perich, M. G., Miller, L. E. & Solla, S. A. Neural Manifolds for the Control of

Movement. *Neuron* **94**, 978–984 (2017).

Gallego, J. A. *et al.* Cortical population activity within a preserved neural manifold underlies

multiple motor behaviors. *Nat. Commun.* **9**, 1–13 (2018).

Ganguli, S. & Sompolinsky, H. Compressed sensing, sparsity, and dimensionality in neuronal

information processing and data analysis. *Annu. Rev. Neurosci.* **35**, 485–508 (2012).

Gardner, R. J. *et al.* Toroidal topology of population activity in grid cells. *Nature* **602**, 123–128

(2022).

Gast, R., Solla, S. A. & Kennedy, A. Neural heterogeneity controls computations in spiking

neural networks. *Proc Natl Acad Sci U S A* **121**, (2024).

Genkin, M., Shenoy, K. V, Chandrasekaran, C. & Engel, T. A. The dynamics and geometry of

choice in premotor cortex. Preprint at *bioRxiv*

https://www.biorxiv.org/content/10.1101/2023.07.22.550183v1 (2023).

Hénaff, O. J. *et al.* Primary visual cortex straightens natural video trajectories. *Nat. Commun.* **12**,

(2021).

Honey, C. J., Kötter, R., Breakspear, M. & Sporns, O. Network structure of cerebral cortex

shapes functional connectivity on multiple time scales. *Proceedings of the National*

Academy of Sciences **104**, 10240–10245 (2007).

Hu, J. *et al.* Visual Motion Processing in Macaque V2. *Cell Rep.* **25**, 157-167.e5 (2018).

Jazayeri, M. & Ostojic, S. Interpreting neural computations by examining intrinsic and

embedding dimensionality of neural activity. *Curr. Opin. Neurobiol.* **70**, 113–120 (2021).

Johnston, W. J., Palmer, S. E. & Freedman, D. J. Nonlinear mixed selectivity supports reliable

neural computation. *PLOS Comput. Biol.* **16**, e1007544 (2020).

Kaufman, M. T. *et al.* The implications of categorical and category-free mixed selectivity on

representational geometries. *Curr. Opin. Neurobiol.* **77**, 102644 (2022).

Kriegeskorte, N. & Wei, X. X. Neural tuning and representational geometry. *Nat. Rev. Neurosci.*

22, 703–718 (2021).

Lamme, V. A. F. The neurophysiology of figure-ground segregation in primary visual cortex. *J.*

Neurosci. **15**, 1605–1615 (1995).

Langdon, C., Genkin, M. & Engel, T. A. A unifying perspective on neural manifolds and circuits

for cognition. *Nat. Rev. Neurosci.* **24**, 363–377 (2023).

Lin, B. & Kriegeskorte, N. The Topology and Geometry of Neural Representations. *arxiv*

(2023).

Lindsay, G. W., Rigotti, M., Warden, M. R., Miller, E. K. & Fusi, S. Hebbian learning in a

random network captures selectivity properties of the prefrontal cortex. *J. Neurosci.* **37**,

11021–11036 (2017).

Low, I. I. C., Giocomo, L. M. & Williams, A. H. Remapping in a recurrent neural network model

of navigation and context inference. Preprint at *bioRxiv*

https://doi.org/10.1101/2023.01.25.525596 (2023).

Lu, H. D., Chen, G., Tanigawa, H. & Roe, A. W. A Motion Direction Map in Macaque V2.

Neuron **68**, 1002–1013 (2010).

Ma, H. *et al.* Processing of motion-boundary orientation in Macaque V2. *Elife* **10**, 1–24 (2021).

Mante, V., Sussillo, D., Shenoy, K. V. & Newsome, W. T. Context-dependent computation by

recurrent dynamics in prefrontal cortex. *Nature* **503**, 78–84 (2013).

Marcar, V. L., Raiguel, S. E., Xiao, D. & Orban, G. a. Processing of kinetically defined

boundaries in areas V1 and V2 of the macaque monkey. *J. Neurophysiol.* **84**, 2786–2798

(2000).

Minsky, M. L. & Papert, S. *Perceptrons, Expanded Edition An Introduction to Computational*

Geometry. (MIT Press, Cambridge, 1969).

Mysore, S. G., Vogels, R., Raiguel, S. E. & Orban, G. a. Processing of kinetic boundaries in

macaque V4. *J. Neurophysiol.* **95**, 1864–1880 (2006).

Nogueira, R., Rodgers, C. C., Bruno, R. M. & Fusi, S. The geometry of cortical representations

of touch in rodents. *Nat. Neurosci.* **26**, 239–250 (2023).

Okazawa, G., Hatch, C. E., Mancoo, A., Machens, C. K. & Kiani, R. Representational geometry

of perceptual decisions in the monkey parietal cortex. *Cell* **184**, 3748-3761.e18 (2021).

Perich, M. G. *et al.* Motor cortical dynamics are shaped by multiple distinct subspaces during

naturalistic behavior. Preprint at

https://www.biorxiv.org/content/10.1101/2020.07.30.228767v2 (2020).

Rajan, K., Abbott, L. F. & Sompolinsky, H. Stimulus-dependent suppression of chaos in

recurrent neural networks. *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.* **82**, (2010).

Rigotti, M. *et al.* The importance of mixed selectivity in complex cognitive tasks. *Nature* **497**,

585–590 (2013).

Rigotti, M., Rubin, D. B. D., Wang, X. J. & Fusi, S. Internal representation of task rules by

recurrent dynamics: The importance of the diversity of neural responses. *Front Comput*

Neurosci **4**, (2010).

Russo, A. A. *et al.* Neural Trajectories in the Supplementary Motor Area and Motor Cortex

Exhibit Distinct Geometries, Compatible with Different Classes of Computation. *Neuron*

107, 745-758.e6 (2020).

Seung HS & Lee DD. The manifold ways of perception. *Science* **290**, 2268–2269. (2000)

She, L., Benna, M. K., Shi, Y., Fusi, S. & Tsao, D. Y. Temporal multiplexing of perception and

memory codes in IT cortex. *Nature* **629**, 861–868 (2024).

Stringer, C., Pachitariu, M., Steinmetz, N., Carandini, M. & Harris, K. D. High-dimensional

geometry of population responses in visual cortex. *Nature* **571**, 361–365 (2019).

Tye, K. M. *et al.* Mixed selectivity: Cellular computations for complexity. *Neuron* (2024)

doi:10.1016/j.neuron.2024.04.017.

Weigand, M., Sartori, F. & Cuntz, H. Universal transition from unstructured to structured neural

maps. *Proc. Natl. Acad. Sci. U. S. A.* **114**, E4057–E4064 (2017).

Xie, Y. *et al.* Geometry of sequence working memory in macaque prefrontal cortex. *Science.*

375, 632–639 (2022).

STAR★METHODS

KEY RESOURCES TABLE

REAGENT or RESOURCE	SOURCE	IDENTIFIER
Experimental Models: Organisms/Strains		
Rhesus macaque (Macaca mulatta)	Suzhou Xishan Zhongke animal Company, Ltd;	http://xsdw.bioon.com.cn/
Deposited data and code		
Codes and dataset	This paper	https://data.mendeley.com/datasets/ vrj3645vgz/2
Software and Algorithms		
MATLAB	MathWorks	R2017b & R2022b
Jupyter	Project Jupyter	
Other		
32channel-Array	Blackrock Microsystems, LLC;	https://www.blackrockmicro.com/
64channel Multichannel Neural Recording (AlphaLab SNR)	Alpha Omega;	https://www.alphaomega-eng.com/
ViSaGe	Cambridge Research System Ltd;	https://www.crsltd.com/

RESOURCE AVAILABILITY

Data and materials availability

The data and analysis code are available at Mendeley Data,

https://doi.org/10.17632/vrj3645vgz.2. All data information that supports the findings of this

study are available from the corresponding author on reasonable request.

Materials and Methods

Four hemispheres from two adult male macaque monkeys (Macaca mulatta) were used in this study. All

procedures were performed in accordance with the National Institutes of Health Guidelines and were approved

by the Institutional Animal Care and Use Committee of the Beijing Normal University (protocol number:

IACUC(BNU)-NKCNL2013-13).

Visual stimuli, behavioral tasks, and recordings

The data used in this study was from our previous work, and for more details on stimuli, tasks, and

recordings, see Ma et al, 2021.

Stimuli were generated with ViSaGe using MATLAB scripts and presented on a 21-inch CRT display.

MIC stimuli had seven levels of dot motion coherence. The size of the MIC was a 4˚-diameter circular and the

position of MIC was consistent with array population RF.

Two monkeys performed an MIC orientation-discrimination task after headpost and optical imaging

guided 32-channel Utah array implant. This task was a two-alternative forced-choice discrimination task and

the monkeys were trained to make an eye saccade choice based on MIC orientations. The monkeys made a

saccade to the right target if the orientation was tilted to the right of the vertical axis, and vice versa. The

monkeys received water reward for correct choices.

The electrophysiological recording system is AlphaLab SnR 64-channel system. Neural signals were

sampled at 22 kHz and with an 800 – 7500 Hz bandpass filter. Recordings were performed on multiple days.

In this study, we only used single neurons in the unique-unit dataset (Ma et al., 2021). This dataset was

generated by excluding potential duplicated units (i.e., similar waveforms or tunings) that were recorded from

the same electrodes on different days. Therefore, the neurons in this dataset were either from different

electrodes or from the same electrode but had different waveforms or tunings. Additionally, we further refined

our selection to include only single neurons from this dataset.

Data analysis

Data preprocessing. For all single neurons selected as previously described, they passed the receptive field (RF) test. Briefly, we used two types of RF mapping stimuli. One is grid-like RF mapping, where a 0.8° square-wave grating is presented at different positions on the grid. We fit the neuronal response in two dimensions using a 2-D Gaussian function; the other is 4° long, 0.2° wide bars presented at different horizontal and vertical positions, for which we use a one-dimensional Gaussian for fitting. A goodness of fit greater than 0.7 is considered as passing the RF test, see Ma et al, 2021. Then, to build a high-dimensional neural space, we identified all V2 neurons that participated in the MIC orientation-discrimination task. In total, we obtained 93 V2 single neurons, with 47 neurons from Monkey S and 46 neurons from Monkey W.

We sorted all trials into 112 conditions to analyze each neuron's response (2 motion-axis orientation conditions, 4 sheared configuration conditions, 7 coherence levels, and 2 performance outcomes). Subsequently, we calculated each neuron's trial-averaged response (from -200ms before stimulus onset to 200ms after stimulus offset) with a Gaussian window (a 10ms sliding window with a 2ms step size). We then combined all neuron responses after z-scoring each neuron's trial average response (Okazawa et al., 2021; Mante et al., 2013). Additionally, we excluded conditions with fewer than 3 trials for some neurons, so we totally got 61 useful conditions. Following these steps, we constructed a data matrix of dimensions 61 (useful conditions) x T (trial time) x 93 (neuron number) from the MIC orientation discrimination task.

Support vector machine (SVM). We used SVM for two purposes: first, to decode categorical information from the neural data, and second, to provide a well-defined vector, which represents a distinct dimension in the neural space. In the analysis, we used the *fitcsvm* function with a linear kernel in MATLAB. We retained the default hyper-parameter values of the function, except for customizing the box constraint. In the neural geometry part, the box constraint was set at 0.001, whereas for the binary classification part, it was set at 1 (for an explanation of box constraints, see Supplementary Methods M.2). Then, the SVMs were trained and tested using data points in the neural space.

Since our population data is composed of multiple sessions with varying trial numbers, we followed previous methods (Mante et al., 2013; Okazawa et al., 2021) and used trial-averaged data (as described in Data

Preprocessing). So here we divided the data at different time points into training and testing sets. First, we

partitioned the complete time range from -200ms to 1000ms relative to stimulus onset into tiled 12ms-wide

time bins. Within each time bin, we randomly selected half of the time steps for training and the other half for

testing. To train a single SVM classifier, the selected training data from time bins were pooled together. To

generate time courses of classifier accuracy, the classifier was tested within each time bin using the testing

data. We also tried another method where, instead of using tiled 12ms-time window, we randomly selected half

of the time points from the entire time span as training data and the other half as test data. The classification

accuracies were consistent. However, in this way we could not obtain time courses of classification accuracy,

so we did not use it in this text.

Angle analysis. To calculate the angle subtended between two n-dimensional unit vectors $\boldsymbol{\beta}_i$ and $\boldsymbol{\beta}_j$, we

used the following formula:

$$\theta = \mathrm{acos}(\boldsymbol{\beta}_i^{\mathrm{T}} \boldsymbol{\beta}_j).$$

The vectors were from SVM classifications. For the neural geometry and twist model parts, we

performed SVM analysis once for each classification. For control analyses, we ran SVM analysis 200 times for

each classification (see Supplementary Notes N.6 and Supplementary Fig. 6 A & B). The orthogonality of the

angle was tested by examining whether it significantly differed from the angle distribution constructed by

randomly selecting two vectors in a 93-dimensional space (see Supplementary Notes N.6 and Supplementary

Fig. 6C).

Low-pass filter. To smooth the temporal profiles of the neuron activities, we applied customized simple

discrete-time RC low-pass filters. Let the temporal profile of a neuron be $x(t)$. The filtering is applied using a

sliding window starting from N time-steps before the current moment. In this time window, the filtered

temporal profile $\bar{x}(t)$ is

$$\bar{x}(t) = \alpha\, x(t) + (1 - \alpha)\, \bar{x}(t - 1).$$

where α is the smoothing factor. The factor α is computed from the sampling time interval Δt and the

required cutoff frequency f_c as

$$\alpha = \frac{2\pi\, \Delta t\, f_c}{2\pi\, \Delta t\, f_c + 1}$$

Essentially, the low-pass filter computes the exponentially weighted moving average of the original temporal

profile. In our study, $\Delta t = 0.002$s, $f_c = 2$Hz and $N = 5$.

Three-D visualization. The main axes identified by SVM must be perfectly mutually orthogonal for creating

Cartesian coordinate systems. So here we first created an arbitrary full rank matrix $\boldsymbol{A}$. Its first few columns

were replaced by the identified main axes by SVM. We then applied QR decomposition on matrix $\boldsymbol{A}$ to obtain

an orthogonal matrix $\boldsymbol{Q}$. The transformation matrix was $\boldsymbol{T} = \boldsymbol{Q}^{\mathrm{T}}$ (see Supplementary Methods M.3 for details).

Then, we used this transformation matrix to linearly transform the original neural space to a new coordinate

system where the identified main axes by SVM were the first several axes.

To neatly visualize the neural states in a 3-D subspace, we first applied low-pass filter to the data in the

original neural space. We chose cutoff frequency $f_c = 2$Hz, since we wanted to smooth the curve for better

visualization and clearer depiction of the dynamic process. Lowpass filtering was not used in other quantitative

calculation. We then used matrix $\boldsymbol{T}$ to transform the filtered data into a new high-dimensional coordinate

system. Finally, the transformed data were projected into a 3-D subspace constructed by the main axes

identified for visualization.

Double-twist model. The double-twist model transformed the continuous cylindrical stimulus manifold

depicted in Fig. 4C (left) to a continuous perceptual manifold embedded in a 7-D space. Its projections into 3-

D subspaces were shown in gray in Fig. 4C (middle & right). The perceptual manifold arose from the

correspondence between the XOR operator and the arithmetic product. Let the true value be represented by -1,

and the false value by 1. The truth table of the XOR operator aligns with that of the arithmetic product (see

Supplementary Fig. 25). That is,

876
$$X \oplus Y \Leftrightarrow xy,$$

where X and Y are Boolean variables and x and y are the coordinates on the x and y axes, respectively.

Therefore, after two twist operation, the 7-D coordinates of a point in the perceptual manifold corresponding to

a point $[x, y, z]$ in the stimulus manifold are $[x, y, z, xy, yz, xz, xyz]$.

The derived perceptual manifold was fit to the neural data using affine transformation for visualization.

Because the neural data contained noise, we first applied a low-pass filter (cutoff frequency: 2Hz), and then

calculated the steady-state averages (from 300ms to 500ms relative to stimulus onset) of neural activities for

the 8 stimuli to determine 8 centers. These centers were then projected into various 3-D subspaces (Fig. 4). In

each subspace, we located the neural states for the 8 stimuli based on the derived perceptual manifold. Using

the least-square method, we obtained the transformation matrix $\boldsymbol{F}$. The mean of the residuals was represented

as a vector $\boldsymbol{e}$. For any point $\boldsymbol{x}$ on the 3-D projections of the derived perceptual manifold, we applied the

transformation

$$\hat{\boldsymbol{y}} = \boldsymbol{F}\boldsymbol{x} + \boldsymbol{e}$$

to fit the model to the data (see Supplementary Methods M.4 for detailed formulation). The goodness of fit was

measured by R^2.

Binary classification. Binary classification entailed sorting stimulus conditions into two classes based on all

possible classification rules. With 8 stimulus conditions, we had a total of 256 classification rules. For each

classification, the criterion for linear separability was set at 75% accuracy within each stimulus condition. Each

neuron pool was randomly selected from the entire set of 93 neurons, one at a time, and we then conducted

SVM analysis 10 times for each neuron pool (see Supplementary Methods M.5).

To infer the dimensionality from binary classifications, we employed the approach developed by Rigotti

et al, 2013. Briefly, we calculated the ratio of the actual number of linearly separable classifications and the

theoretical number of binary classifications for each condition number n ($n \in \{2, ..., 8\}$). The last n whose

ratio > 0.8 was selected as the dimensionality (see Supplementary Methods M.6).

Connectivity patterns of neural networks. We created a simple two-layer feedforward neural network; the

first layer contained 3 units representing the three feature dimensions, respectively, and the second layer

contained 93 nonlinear mixed selectivity neurons. Each neuron received the input signals of all the three

feature dimensions (mixed): x(HV), y(OI) and z(CA), and employed a ReLU activation function

(nonlinearity). The input signals represented the eight corners of the cube in the x-y-z stimulus space, each

corresponding to a specific stimulus. The activity r_i of the ith neuron was defined as:

908
$$r_i = \text{ReLU}\left(\sum_j w_{ij}\gamma_j + b_i\right) + \epsilon,$$

where $\gamma_j \in \{x, y, z\}$ is the input signal of the jth stimulus feature with w_{ij} as the weight, b_i is a random

bias sampled from the uniform distribution $\mathcal{U}(0,1)$, and ϵ is a noise term drawn from the Gaussian

distribution $\mathcal{N}(0, 1/3)$.

The weights w_{ij} were randomly sampled from standard Gaussian distributions. The covariance

between the weights controlled the structure of the network and thus determined the heterogeneity of the

output activities. Hence, we used a diversity parameter $d \in [0,1]$ to define the 93×93-D covariance matrix K

for sampling the weights of feature x:

916
$$K = \begin{bmatrix} 1 & 1-d & \cdots & 1-d \\ 1-d & 1 & \cdots & 1-d \\ \vdots & \vdots & \ddots & 1-d \\ 1-d & 1-d & \cdots & 1 \end{bmatrix}.$$

The covariance matrix K was fed into the *multivariate_normal* function in Python's *numpy.random*

package to generate the weights. The procedure for generating weights of features y and z was identical.

We ran multiple simulations on the network. In each simulation, input stimuli were repeated 100 times

to allow the added random noise for generating point clusters. We applied the same analyses for the network's

output activities as we did for the neural data. One hundred simulations were conducted for calculating the

dimensionality of the neural geometry.