Title: From Sensory to Perceptual Manifolds: The Twist of Neural Geometry

Running title: Geometric twist of neural manifolds

Authors: Heng Ma[1,3], Longsheng Jiang[2,3], Tao Liu[1,3], Jia Liu[1*]

Affiliation: [1]Department of Psychology & Tsinghua Laboratory of Brain and Intelligence,

Tsinghua University, Beijing 100084, China; [2]Beijing Academy of Artificial Intelligence (BAAI),

Beijing 100085, China

[3]These authors contributed equally: Heng Ma, Longsheng Jiang, Tao Liu

[*]**Correspondence**: liujiathu@tsinghua.edu.cn

Abstract

To humans, nearly everything is classifiable: whether as big or small, edible or poisonous,

righteous or unjust. Similarly, classification is a central task in many machine learning

applications, yet the problem of linear inseparability has long posed challenges for artificial

neural networks since their inception. Here we asked how biological neural networks tackle this

problem by investigating the geometric embedding of neural manifolds in neural spaces of

macaques'V2 during orientation discrimination of motion-induced illusory contours. Specifically,

we constructed a three-dimensional stimulus space that inherently made the orientation

classification of these contours a linearly inseparable problem. As expected, we identified a

sensory manifold, formed by activities of the V2 neuron population, that faithfully corresponded

to this stimulus space. Crucially, this sensory manifold underwent a series of twist operations,

resulting in new axes orthogonal to the original ones. Within this expanded, high-dimensional

perceptual manifold, the problem of linear inseparability became linearly separable.

Computational models further revealed that the geometric twist operation was achieved by

neurons exhibiting nonlinear mixed selectivity in networks with heterogeneous connectivity

patterns. Taken together, our findings provide an example of how perception arises from

sensation through the lens of neural geometry, enriching our understanding of how cognitive

functions are derived from neuronal response profiles and their connectivity structure.

Keywords: motion-induced illusory contour; linearly inseparable problem; neural geometry;

sensory manifold; perceptual manifold; nonlinear mixed selectivity; connectivity structure.

Introduction

Classification constitutes a core cognitive challenge for both biological and artificial intelligence

systems, with many tasks potentially reducible to classification problems[1-4]. The primary

challenge in classification lies in the prevalence of linearly inseparable problems, where

perfectly segregating data points into their respective classes using a linear boundary is

infeasible[5,6]. Therefore, machine learning often resorts to complex, nonlinear decision boundaries

to address this issue[7,8]. Here we asked how biological systems address linearly inseparable

problems, which may provide insights for developing new machine learning algorithms.

Here we employed an orientation discrimination task involving motion-induced contours

(MIC), wherein moving dots generated an illusory contour at the center of a circular viewing

area (Fig. 1A). Specifically, dots in one hemisphere of the viewing area moved coherently in a

single direction, whereas those in the opposing hemisphere moved contrarily[9,10,11]. This

symmetrical motion led the dots to either converge or diverge at the center of the viewing area,

thus instantaneously forming a left- or right-tilted illusory contour (Fig. 1B). Further, we

constructed a three-dimensional stimulus space based on three orthogonal stimulus axes[9,12,13]: (1)

horizontal versus vertical, (2) outward versus inward, and (3) clockwise or anti-clockwise (Fig.

1C). This resulted in a three-dimensional Euclidean space that embedded the stimulus space

within a cylindrical surface (Fig. 1D). Crucially, stimuli sharing the same MIC orientation (e.g.,

right-titled, red) were interspersed among those with the opposing orientation (i.e., left-tilted,

blue), indicating that the classification of MIC orientations presents a linearly inseparable

problem within this stimulus space.

Previous neurophysiological studies have revealed that neurons in macaques' V2 show

selectivity for cue-invariant MIC orientations[10,13], suggesting that the linearly inseparable

problem in the stimulus space becomes linearly separable when processed by V2 neurons. Here

in this study, we analyzed neuronal activity data previously recorded in the V2 area[13], aiming to

elucidate how the sensory manifold, where MIC orientations remains linearly inseparable akin to

the stimulus space, transforms into the perceptual manifold that affords linear separability. To do

this, we utilized the population coding doctrine to characterize neural manifolds constituted by

neuron population[14,15,16], an approach recently applied to various domains such as vision[17,18],

memory[19,20], decision[21,22,23], navigation[24,25] and motor execution[26-29]. Specifically, we first

established the correspondence between the sensory manifold and the stimulus space. Then, we

illustrated how twist operations transformed the low-dimensional sensory manifold into the

high-dimensional perceptual manifold by generating new dimensions, where the originally

linearly inseparable problem became linearly separable. Furthermore, the expansion of the neural

manifold's embedding dimensions required neurons exhibiting nonlinear mixed selectivity in

networks with heterogeneous connectivity patterns, thereby echoing the longstanding dictum that

structure determines function.

Results

Stimulus space and linearly inseparable problems

Two macaque monkeys were trained to perform an MIC orientation classification task by

executing a saccade towards the corresponding side based on the MIC orientation (Fig. 1A). To

make the classification a linearly inseparable problem, we designed a three-dimensional stimulus

space. For dots in opposing halves, they moved in the opposite directions within a range of $[0, \pi]$

(e.g., dot I and dot II in Fig. 1B, left), and here we used the horizontal direction (i.e., 0) and the

vertical direction (i.e., $\pi/2$) as the motion axis of HV (i.e., horizontal versus vertical, Fig. 1C,

left). For dots within the same half, one dot (e.g., dot III) either led or trailed another dot (e.g.,

dot IV) (Fig. 1B, right), quantifiable as the angular location of dot IV with respect to dot III,

known as sheared configuration. The sheared configuration operates within a range of $[0, 2\pi]$

and possesses two independent axes: outward versus inward (OI) and clockwise versus

anti-clockwise (CA). Here we chose the sheared directions of $\pi/4$ (inward and clockwise),

$3\pi/4$ (inward and anti-clockwise), $5\pi/4$ (outward and anti-clockwise) and $7\pi/4$ (outward and

clockwise), which are orthogonally constructed by these two axes (Fig. 1C, right).

Using these three axes of HV, OI, and CA, we constructed a three-dimensional (3-D)

Euclidean space within which the stimulus space of a cylindrical surface was embedded, with the

stimuli utilized in this study positioned at the vertices of the inner tangent cube of the cylinder

(Fig. 1D). Thus, there were eight global patterns formed by local dot motion, with four patterns

exhibiting a right-tilted contour (No. 1 – No.4, red) and the remaining four left-tilted (No. 5 –

No.8, blue). Crucially, in the stimulus space, stimuli sharing the same MIC orientation (e.g.,

right-titled, red) were always interspersed with stimuli exhibiting the opposite orientation (i.e.,

left-tilted, blue) (Fig. 1D, for the whole set of stimulus parameters, see Supplementary Fig. 1,

also see Supplementary Movie. 1 for the 8 stimuli). In essence, this setup created a classification

task that was linearly inseparable. Despite this challenge, both monkeys adeptly performed the

task with an accuracy exceeding 90% at 100% motion coherence[13].

Figure 1. Overview of Stimulus Space.

(A) Left: the MIC orientation discrimination task; right: A right-titled MIC defined by surrounding moving

dots. Monkeys were trained to make saccades according to MIC orientations. This figure is modified from Ma

et al[13]. RF: array population receptive field.

(B) Sample stimulus. The intrinsic dimensions of the stimulus consist of a motion axis (left) and sheared

configuration (right). The motion axis represents the direction of dots' symmetric movement, for example, dot

I and II move horizontally. Right: the sheared configuration reveals the relative positioning of adjacent dots

moving in the same direction, for example, dot III and IV is 5 /4 in sheared configuration, and we define this

as outward and anti-clockwise (see panel C).

(C) Axes of stimulus space. Left: the parameter for the motion axis ranging from $[0, \pi]$; Right: the parameter

for the sheared configuration ranging from $[0, 2\pi]$. From these parameters, three orthogonal axes were

extracted: HV (Horizontal vs. Vertical), OI (Outward vs. Inward), and CA (Clockwise vs. Anti-clockwise).

Binary values along each axis were used to generate eight stimuli. Within these three axes, the sample stimulus

(red) is termed as HOA (Horizontal, Outward, and Anti-clockwise).

(D) Stimulus space. The eight stimuli used in the study, each labeled numerically and color-coded based on

their axis locations and MIC orientations (red: right-tilted; blue: left-tilted). Note that the classification of MIC

orientations poses a linearly inseparable problem in this stimulus space. For a comprehensive view of the full

stimulus space, see Supplementary Fig. 3.

Sensory and Perceptual manifolds

To investigate how the brain addressed this linearly inseparable problem, we analyzed neural

activity data from V2 neurons of two monkeys[13] to construct a high-dimension neural space (see

Methods; for neurons' receptive fields and selectivity, see Supplementary Fig. 4). Specifically,

we selected single neurons from the unique-unit dataset, which were previously recorded in the

MIC orientation-discrimination task with varying levels of motion coherences. First, we

investigated how the stimulus space was encoded at the level of neuron population. To do this,

we utilized linear support vector machines (SVM) to analyze the time course of the 93 neurons in

response to all the 8 stimuli to determine whether the three axes of the stimulus space (Fig. 1D),

HV ({1,2,5,6} versus {3,4,7,8}), OI ({1,3,5,7} versus {2,4,6,8}), and CA ({2,3,5,8} versus

{1,4,6,7}), could be decoded. We found that classifications along all three axes were linearly

separable, with accuracies above 75% and significantly higher than the shuffled baseline

(bootstrap t-tests, all ps < 0.001) (Fig. 2A). This finding was replicated with other methods such

as the analysis on population average responses and the principal component analysis

(Supplementary Fig. 5). Crucially, the optimal separation direction vectors (determined by SVM,

see Methods) for HV, OI, and CA, were mutually orthogonal, as the distribution of the subtended

angles between these vectors was significantly more concentrated around 90° than the

distribution of angles between two random direction vectors, and also significantly larger than

angle distributions between the same classification vectors (Supplementary Fig. 6).

To visualize the dynamic encoding of the stimuli by the neuronal population, we projected

the neural states into a 3-D neural subspace formed by the direction vectors for HV, OI, and CA

(see Methods). Figure 2B shows that, prior to stimulus onset, neural states for the stimuli were

closely clustered and inseparable. Following the onset, these states gradually spread and became

completely separable along the HV axis; then, they remained in a steady phase for the duration of

stimulus presentation before returning to their original locations after stimulus offset (see

Supplementary Movie. 2 and Supplementary Fig. 11). Similar dynamic patterns were observed

for the OI (Fig. 2C) and CA (Fig. 2D) axes as well. To further illustrate neural geometry, we

projected the neural states corresponding to all stimuli onto neural subspaces formed by specific

axes of interest (see Methods). The neural states were characterized by the magnitude of neurons'

activation in response to the stimuli during the steady phase, ranging from 200ms to 500ms

post-stimulus onset. Fig. 2E shows that each stimulus-associated neural state was located at a

vertex of a slightly distorted cube. Crucially, the geometric relation among these neural states

corresponded to the geometric relation among stimuli in the original stimulus space (Fig. 1D);

accordingly, we refer to the neural states embedded in this 3-D subspace as the "sensory

manifold". Since the function of sensation is to convert external sensory stimuli into neural

signals, the sensory manifold was sensitive to variations in the coherence of moving dots in the

stimuli, which gave rise to a series of concentric cubic sensory manifolds with higher coherence

levels eliciting larger cubic manifolds (Supplementary Fig. 8). Taken together, the sensory

manifold faithfully represented the stimulus space, with HV, OI, and CA serving as the axes of

the neural subspace that embedded this manifold. Consequently, the linearly inseparable problem

cannot be solved within the sensory manifold.

Consistent with previous studies on individual neurons[10,13], our SVM analysis at the

population level was able to linearly decode MIC orientations (i.e., left- versus right-titled, LR)

(Fig. 2A, orange line), and the accuracy was comparable to that of decoding the stimuli's features

(i.e., HV, OI, and CA). Fig. 2F illustrates the neural states along the optimal separation vector for

LR, where the linearly inseparable problem became linearly separable along this axis (for

dynamic trajectories see Supplementary Fig. 11 & Supplementary Movie 2). Critically, this LR

axis was orthogonal to the three existing axes for the sensory manifold (Supplementary Fig. 6A),

suggesting that the LR axis emerged not directly from the stimuli but from the processing of

sensory information. Evidence supporting this conjecture comes from the analysis on the latency

of the emergence of the LR axis, which occurred about 30ms after the emergence of the axes

encoding the stimuli's features (i.e., HV, OI, and CA) (Fig. 3F). This observation is in line with

previous findings on visual motion segregation[9,10,30,31,32], echoing the idea that perception is a

result of operations on sensory information[33]. Accordingly, we refer to the manifold embedded in

this dimension-expanded neural subspace, which now incorporated the new LR axis in addition

to the existing axes for the sensory manifold, as the "perceptual manifold". Next, we explored

the potential operation that transforms the sensory manifold into the perceptual manifold.

Figure 2. Neural geometry of sensory and perceptual manifolds.

(A) Time-course accuracies by linear SVM classifiers. The SVMs were trained on neural data from 93 neurons

within the time interval [-200ms, 1000ms] relative to stimulus onset. Shaded regions denote the mean SVM

accuracy (±3 standard deviations) of the baselines by shuffling stimulus labels 1000 times. Individual

monkey's results are shown in Supplementary Fig. 9 E & F.

(B-D) Dynamic trajectories of neural states. Changes in neural states from -200ms to 1000ms were projected

onto a neural subspace defined by the HV, OI, and CA axes. Identical trajectories are presented from various

perspectives to optimally illustrate the separation by these three stimulus feature axes. Blue and red colors

indicate categorizations along the HV, OI, and CA axes for (B), (C), and (D), respectively. Arrows on the

trajectories correspond to the progression of the neural states over time. The neural states prior to stimulus

onset are indicated in gray. Motion coherence level is 7. Individual monkey's results are shown in

Supplementary Fig. 10. The time courses of neural states (-200-1000ms) projected to each axis are shown in

Supplementary Fig. 11.

(E) Sensory manifold. Eight clusters of neural states in the steady phase (200ms-500ms after stimuli onset)

corresponded to the 8 stimuli. The centers of these clusters are connected with dashed lines. Cool and warm

colors indicate the two MIC orientations, respectively, all motion coherence levels were used. Individual

monkey's results are in Supplementary Fig. 9 A & B.

(F) Dynamic trajectories of neural states along the LR axis. The clusters follow the same color code as in panel

E, with the centers of the clusters marked with solid circles, all motion coherence levels were used. Note that

cool and warm colors are separated along the LR axis. Motion strength (r), which is the Euclidean distance

between the neural states and the origin in the sensory manifold in panel E, is included for display purposes

only.

Twist operations on neural geometry

For simplicity, here we use x, y, and z to denote the axes of HV, OI, and CA, respectively. In the

z-x plane, the four vertices $\{1,3,5,7\}$ exemplify the standard planar XOR problem (Fig. 3A, left).

Traditional solutions to the XOR problem often involve expanding dimensionality[5,6]. For example,

twisting two parallel edges along the z-axis in opposite directions around the x-axis can resolve

the issue (Fig. 3A, middle), thus termed as twist operation (for a similar idea, see Nogueira et al[34]).

Accordingly, this twist operation transforms the 2-D plane into a curved surface in a 3-D space

(Fig. 3A, right). In this new 3-D space, a new axis, denoted as v, is constructed through twisting

along the z and x axes, expressed as $v = z \oplus x$. At the phenomenal level, this twist operation

might appear akin to performing a cross-product between the z and x axes. However, it is

important to note that this resemblance is superficial (for a detailed mathematic definition of the

twist operation and its relation with the cross-product, see M.4 in Supplementary Methods). Along

this new v axis, the four vertices become linearly separable.

To examine whether this theoretically derived v axis was present in the actual neural space,

we trained linear SVMs to classify three sets of vertex pairs among four vertices. As expected, the

vertex pair of $\{1,5\}$ versus $\{3,7\}$ and that of $\{1,7\}$ versus $\{3,5\}$ were linearly separable along

the x and z axes, respectively, with accuracies greater than 75%. Critically, the vertex pair of

{1,3} versus {5,7} was also linearly separable along the v axis, suggesting that the v axis was

indeed present in the neural space (Fig. 3B). Next, we generalized this twist operation from the

planar XOR problem to the cubic XOR problem (i.e., {1, 2, 3, 4} versus {5, 6, 7, 8}, Fig. 3C, left).

Apparently, a single twist operation with $v = z \oplus x$ proves insufficient to resolve the cubic

XOR problem (Fig 3C, middle). However, incorporating a second twist in a plane parallel to the v

axis around the y axis makes the vertex pair of {1, 2, 3, 4} versus {5, 6, 7, 8} linearly separable

(Fig 3C, right). In this second twist, a new axis, denoted as p, is constructed: $p = v \oplus y = z \oplus$

$x \oplus y$. Accordingly, this model is thus termed as the double-twist model. Interestingly, this

newly constructed p axis is the axis that differentiates between the left- and right-titled MIC

orientations. Indeed, the p axis is the LR axis illustrated in Fig. 2F.

Figure 3: The double-twist model.

(A) One twist operation on a planar XOR problem. Left: the coplanar vertices　　　　are colored based on

MIC orientations, forming a standard XOR problem on the　-　plane. Middle: a twist operation along

the　-axis resolves the XOR problem by rotating two parallel edges in opposite directions around the　-axis.

Right: this twist operation generates the　　axis orthogonal to the　-　plane.

(B) Time courses of SVM classification accuracies. Shaded regions denote the mean SVM accuracy (±3

standard deviations) of the baselines by shuffling stimulus labels 1000 times.

(C) Double twist operations on a cubic XOR problem. Two consecutive twists are required to correctly classify

the 8 vertices according to their MIC orientations. Left: the theoretical sensory manifold in the y-z-x space;

Middle: the intermediate manifold achieved after one twist operation on the z-x plane, with the emergence of

the new v axis. Right: the task-relevant p axis emerges after the second twist operation on the y-v plane.

(D) Neural manifolds corresponding to the theoretical manifolds achieved through twist operations. The axes

of x, y, z, v and p in the neural space were determined by corresponding SVM classifiers. Eight clusters

of neural states corresponded to the 8 stimuli, and the centers of these clusters were used to depict the

geometry of neural manifolds through linear fitting.

(E) Angle distribution between x, y, z, v and p axes. The distribution of the subtended angles between the

optimal separation direction vectors as determined by SVM was concentrated around 90°.

(F) Latency of axis emergence. Left: time courses of classification accuracies of the axes. The enlarged inset

shows the latencies of the emergence of the z, x, v, and p axes (against their corresponding baselines) at 43ms,

57ms, 65ms, and 87ms, respectively. Shaded regions denote the mean SVM accuracy (±3 standard deviations)

of the baselines by shuffling stimulus labels 1000 times. Right: The latencies of the sensory axes (0-twist, blue),

the intermediate axes (1-twist, green), and the task-relevant axis (2-twist, red). **: $p < 0.001$.

To visualize the perceptual manifold embedded in the neural subspace constructed by the z,

x, y, v, and p axes, we projected the neural states during the steady phase (i.e., 300ms–500ms)

onto a 3-D subspace constructed by three axes selected. Figure 3D shows the geometric

transformation of the sensory manifold (left) into the perceptual manifold (right), which are

equivalent to two successive twist operations (see also Supplementary Fig. 12A). After the first

twist operation, two planar XOR problems were resolved: the vertex pair of {1, 3} versus {5, 7}

and that of {2, 4} versus {6, 8} became linearly separable along the intermediate v axis (Fig. 3D,

middle). After the second twist, the cubic XOR problem was resolved along the task-relevant p

axis, and the perceptual manifold emerged accordingly (Fig. 3D, right). In addition, the v and p

axis, as well as the z, x, and y axes, were mutually orthogonal (Fig. 3E). Note that the neural

manifolds derived from actual neural states (Fig 3D) closely matched the theoretical manifolds

generated through twist operations (Fig 3C) (all $R^2 \geq 0.8$, for details see Methods) and the

theoretical p axis from the double-twist model was approximately parallel to the empirical p axis

from the neural data (Supplementary Fig. 13), suggesting that the neural manifolds observed in the

macaques' V2 may indeed undergo geometric transformations equivalent to the twist operations.

More direct evidence supporting this conjecture comes from the analysis on the latency of

the emergence of the intermediate v axis. Our double-twist model predicts that the v axis

should emerge after the sensory axes of z and x, upon which the first twist operation acts, and

before the task-relevant p axis, which relies on the v axis for the second twist. Consistent with

this prediction, the v axis emerged (against the baseline) at 65ms post-stimulus onset,

significantly later than the emergence of the z and x axes (at 43ms and 57ms respectively;

bootstrap t-test, $p < 0.001$), yet earlier than that of the p axis (at 87ms; bootstrap t-test, $p < 0.001$)

(Fig. 3F, left; for the time courses of all intermediate axes, see Supplementary Fig. 14 C & D).

Taken together, the presence of the MIC-unrelated v axis, along with the observed temporal

sequence among the different axes, suggests that the perceptual manifold did not directly derive

from physical stimuli; instead, it appears to transition through a sequence of intermediate

transformations from the sensory manifold, each adhering to essential geometric procedures

required for evolving from one manifold to another. Next, we explored the possible existence of

other intermediate axes similar to the v axis.

Dimensionality of perceptual manifold

Given the commutative nature of the twist operation, $p = z \oplus x \oplus y$ can alternatively be

expressed as $p = x \oplus y \oplus z$ or $p = y \oplus z \oplus x$. Thus, our double-twist model predicts the

existence of two additional intermediate axes: $u = x \oplus y$, which classifies vertices $\{1,4,5,8\}$

from vertices $\{2,3,6,7\}$, and $w = y \oplus z$, which classifies vertices $\{1,2,7,8\}$ from vertices

$\{3,4,5,6\}$. Consistent with this prediction, the SVM analysis showed significantly higher

classification accuracies for these vertex pairs compared to the baseline, confirming the existence

of these two intermediate u and w axes in the neural space (Supplementary Fig. 14A). The

characteristics of the u and w axes were the same as those of the v axis: first, the u and w axes

were orthogonal to each other and to the other axes (Supplementary Fig. 14B); second, they

emerged subsequent to the sensory axes (i.e., z, x, and y axes) yet prior to the p axis

$(F(2,697) = 1015.6$, $p < 0.001$; for all pair-wise comparisons, $ps < 0.001$, Bonferroni

corrected) (Fig. 3F, right; also see Supplementary Fig. 14C); third, the cubic XOR problem can be

addressed using either the u axis or the w axis as the intermediate axis (Supplementary Fig. 12).

Note that these 7 axes were present in each of three cytochrome oxidase stripes (i.e., thin, thick,

and pale) in the V2 area, suggesting the twist operation likely a general property of V2 neurons

(Supplementary Fig. 15). In sum, seven axes, the x, y, z, u, v, w and p axes, were identified in

the neural space of the neuron population in the V2, suggesting that the perceptual manifold was

embedded in a 7-D neural subspace, a dimensionality much higher than that of the sensory

manifold (i.e., 3-D).

An intriguing question arises: why was the perceptual manifold embedded in a 7-D space

when a 4-D space, constructed by x, y, z, and p axes, would suffice for the LR classification in

the MIC task? One possibility is that the availability of multiple alternative pathways to construct

the task-relevant p axis enhances the robustness for the LR classification. Alternatively, the

perceptual manifold may not be task-specific; rather, the LR classification could be just one of its

many possible applications. That is, for the stimulus space with 8 vertices, there are $2^8=256$

possible classifications. Some of these are linearly separable, like vertex $\{1\}$ versus

$\{2,3,4,5,6,7,8\}$ or vertices $\{1,5\}$ versus $\{2,3,4,6,7,8\}$ (Fig. 4A), while others are not, such as

$\{1,3\}$ versus $\{2,4,5,6,7,8\}$ (Fig. 4B). Consider a classification task defined as X versus X^c with

$\|X\|$ ranging from 0 to 8. There are 104 types of linear classifications that can be formed under

these conditions, while the remaining 152 classifications are linearly inseparable (for a full list, see

Supplementary Fig. 16 and Supplementary Table. 1). Critically, these linearly inseparable

classifications in the stimulus space become linearly separable in the 7-D space. For example, the

vertex pair of $\{1,3\}$ versus $\{2,4,5,6,7,8\}$ becomes linearly separable in the y-z-p subspace (Fig.

4C). In total, there are $C_3^7 = 35$ 3-D subspaces (Supplementary Fig. 17), and each of the 152

linearly inseparable classifications becomes linearly separable in at least one of these 35 subspaces

(Supplementary Table. 2). That is, within the 7-D space, every conceivable classification in the

stimulus space becomes linearly separable.

Therefore, the perceptual manifold is not the manifold for decision-making or action; rather,

it provides a reservoir of all possible candidates (in our case, solutions for all conceivable

classifications), awaiting selection by higher-order cognitive processes. In support of this idea, we

found that after excluding neurons highly sensitive to MIC orientations (i.e., task-relevant neurons)

from the V2 neuron population, the remaining neurons, characterized by response profiles driven

by multiple features (i.e., mixed selectivity[6,35,37]), retained the ability to decode MIC orientations

at the population level. This decoding was just as effectively as that achieved by the original

neuron population (Supplementary Fig. 7). This finding suggests that neurons with mixed

selectivity to various features[35,36] may play a critical role in transforming the sensory manifold into

the perceptual manifold.

Figure 4: Linearly separable and inseparable classifications in the stimulus space.

(A) Examples of linearly separable but non-axial classifications in the stimulus space. The classification

separates a subset of vertices from the rest with 0, 1, 2, 3, and 4 (left to right, red vertices). The

classifications with 5, 6, 7, and 8 are complementary (blue vertices). In total, there are 104 linearly

separable classifications in the stimulus space when the axial classifications are included.

(B) Examples of linearly inseparable classifications in the stimulus space, including the LR classification

(right). In total, there are 152 linearly inseparable classifications in the stimulus space.

(C) The classifications in panel B become linearly separable in new subspaces obtained through twist

operations (see Supplementary Table. 1).

Nonlinear mixed selectivity neurons and their heterogeneous connectivity patterns

To exemplify the role of neurons with different response profiles in expanding dimensionality of

neural manifolds, we examined a one-layer network consisting of three neurons, , and .

These neurons receive inputs consisting of two continuous features, and , that form a 2-D

feature sheet (Fig. 5A, top). The XOR problem, in this context, is defined as categorizing points

located at diagonally opposite corners (i.e., red versus blue points). The neurons receive either

pure (either a or b) or mixed (the combination of a and b) inputs, and possess either linear or

nonlinear (e.g., ReLU) activation functions, leading to four distinct output patterns (Fig. 5A,

bottom).

Neurons with pure selectivity and the linear activation function (i.e., linear pure selectivity)

afford only a simple affine transformation of the original feature sheet (Fig. 5B). Because the

rotation axis is aligned with the orange and black edges, the edges remain parallel after

transformation. For neurons with nonlinear pure selectivity, the feature sheet undergoes bending

because of the nonlinear activation function (Fig. 5C). Because the bending occurs along an axis

parallel to the orange and black edges, the edges remain parallel after bending, and therefore the

four corner points still lie on a same plane. For neurons with linear mixed selectivity (Fig. 5D),

the feature sheet endures a complex affine rotation, with the rotation axis not aligning with the

three main axes. However, even after this rotation, the edges remain parallel. In these three

scenarios, neither bending nor rotation alone suffices to make the red and blue points linearly

separable.

In contrast, neurons with nonlinear mixed selectivity[6,35,37] (NMS) perform a twist operation

on the feature sheet, which derives from the combination of affine rotation and the bending. After

the twist operation, the orange and black edges are no longer parallel (Fig. 5E), making the XOR

problem linearly separable. In sum, this theoretical analysis suggests that NMS neurons likely

play a critical role in addressing the XOR problem.

Figure 5: Neurons with different response profiles in realizing twist operations.

(A) Top: The 2-D feature sheet represents all possible combinations of stimulus features   and   . Two edges

of this sheet are highlighted as orange and black, and four corners are colored red and blue to indicate different

categories. Bottom: Four types of neurons' response profiles derive from the combination of input (pure versus

mixed) with activation function (linear versus nonlinear) activation functions. ReLU is used for the illustration

of nonlinear activation functions. The neuron marked in light purple denotes the NMS neuron.

(B-E) The representations in the neural space constructed by (B) three linear pure selectivity neurons, (C) three

nonlinear pure selectivity neurons, (D) two linear pure selectivity neurons and one linear mixed selectivity

neuron, or (E) two nonlinear pure selectivity neurons and one NMS neuron.

Further formal proof shows that the unique characteristic of NMS neurons lies in their

interactive responsiveness to stimulus features (see Supplementary Notes N.16). For example,

the time course and average activity of a typical V2 neuron shows that this neuron responded

differently to HV and CA while showing no sensitivity to OI (Fig. 6 A & B, top). Thus, we used

the significance of a three-way interaction among the stimulus features (HV, OI and CA) as an

index to quantify whether a neuron exhibits nonlinear mixed selectivity (Three-way ANOVA

analysis was performed based on the response of each neuron to 8 different stimuli during the

period from 200 to 750 ms after stimulus onset.). We found that all V2 neurons recorded showed

significant interactions (with a minimum   ,   ), indicating that they

were all NMS neurons. To simulate neurons with pure selectivity[35], we generated synthetic

neurons exclusively tuned to one of the three features (Supplementary Fig. 20). For example, Fig.

6 A & B (bottom) shows a typical synthetic neuron with pure selectivity to OI. Next, we

examined the performance of both NMS and pure selectivity neurons in addressing problems that

are either linearly separable or inseparable.

Figure 6: Classification performance of NMS and pure selectivity neurons.

(A) Time courses of an NMS neuron (top) and a synthetic neuron with pure selectivity (bottom). Colors and

numbers denote different stimuli and their associated neural responses. The time course of the synthetic neuron

was generated by modifying the time course of the NMS neuron shown above.

(B) Average activity of the NMS neuron (top) and the synthetic neuron (bottom). Activity magnitude

represents the average activity from 200ms to 750ms after stimulus onset. Colors denote different conditions of

a feature, and error bars denote the standard error of mean.

(C) The number of successful linear classifications increases as a function of neuron population size for both

pure selectivity neurons (gray) and NMS neurons (dark). The gray curve plateaus at 104, the total number of

linearly separable problems in the stimulus space, whereas the dark curve converges to 256, which includes

152 linearly inseparable problems in addition to 104 linear separable ones. Real neuron: neurons recorded in

the V2; Pure neuron: synthetic neuron with pure selectivity; error bar: standard deviation.

To evaluate the classification efficacy for 152 linearly inseparable problems

(Supplementary Table. 1) and 104 linear separable problems (Supplementary Table. 2) in the

stimulus space, we used a population-increment procedure, where the population size was

progressively increased from a single neuron to the entire set of 93 neurons, adding one

randomly selected neuron each time. During each iteration, we trained SVMs with neural

activities for all possible classifications, and a classification accuracy threshold of 75% was set

as the criterion for successful classification (for details, see Methods). Fig. 6C shows the number

of successful linear classifications (i.e., binary classification) as a function of neuron population

size. With NMS neurons, we achieved the full range of possible classifications (256 in total) for

both linearly separable and inseparable problems (Fig. 6C, black curve) once the number of

NMS neurons exceeded 81. In contrast, using the synthetic neurons with pure selectivity, the

total number of successful classifications plateaued at 104 (Fig. 4C, gray curve) once the

population size exceeded 49. That is, additional increases in population size did not improve

classification performance. Critically, close examination of the problems successfully classified

by pure selectivity neurons revealed that they were all linearly separable in the stimulus space

(Supplementary Table. 1), and none came from the set of linear inseparable problems

(Supplementary Table. 2). That is, regardless of population size, neurons with pure selectivity

can only address linearly separable problems. Taken together, our finding suggests that pure

selectivity neurons alone cannot expand the sensory manifold to a higher dimensionality; instead,

NMS neurons are necessary in expanding the dimensionality of neural manifolds, hereby

transforming the sensory manifold into the perceptual manifold.

While necessary, NMS neurons alone seem insufficient for dimension expansion, as it has

been suggested that the dimensionality of neural manifolds is also dictated by the structure of

neural networks[38]. Here we further investigated the connectivity structure of NMS neurons that

may underpin dimension expansion. To easily quantify the connectivity structure, we built a

two-layer feedforward neural network tasked with processing the stimuli used in the macaques'

experiment (for details on the network, see Methods). In this network, each output neuron

receives the combination of all three stimulus features from the input neurons (i.e., HV, OI and

CA) and employs a nonlinear activation function, with connectivity weights independently

sampled from a Gaussian distribution. As a result, all output neurons in the neural network

demonstrate a response profile of nonlinear mixed selectivity.

In this network, the connectivity structure is controlled by parameter d, which signifies the

degree of diversity in connection patterns between the two layers (Fig. 7A). This diversity ranges

from identical patterns ($d = 0$) to completely uncorrelated patterns ($d = 1$) (see Methods). That

is, when $d = 1$, each NMS neuron generates a distinct response because the connection pattern

from the input neurons is unique (Fig. 7A, right). Therefore, the matrix of connectivity weights is

full rank, and after passing through the nonlinear activation function this connectivity structure

allows the neural manifold to carry out all possible linear and nonlinear classifications composed

by the stimulus features. Indeed, the SVM analysis, similar to that on the macaques' data, was

performed, and a 7-D perceptual manifold was identified. For visualization, neurons' activations

are projected into 3-D subspaces (Fig. 7B), where each dot denotes the neural state of a stimulus,

with red and blue colors representing the two MIC orientations. Within this 7-D perceptual

manifold, we can identify the sensory manifold embedded in a 3-D subspace constructed by axes

corresponding to the three stimulus features (Fig. 7B, left), the intermediate manifold in a 3-D

subspace with a new axis of $v = z \oplus x$ after one twist operation (Fig. 7B, middle), and the

subspace achieved after the second twist operation where linearly separating MIC orientations

becomes possible (Fig. 7B, right). In addition, we also used continuous stimuli that spanned the

entire sheared configuration rings (Fig. 1C, right) and found similar results (Supplementary Fig.

21). In sum, this 7-D perceptual manifold constructed by the network of NMS neurons with a

random connectivity (i.e., $d = 1$) is similar to the 7-D perceptual space identified in the

macaque's V2 (Fig. 3D).

In contrast, when $d = 0$, all NMS neurons have the same inputs and thus generate

identical responses, similar to neurons in a theoretical functional module that have the same

response profile. Accordingly, the matrix of connectivity weights of the network is rank 1 (or 0 if

all weights are 0), and thus the dimensionality of the neural manifold generated by this network

is low (dimensionality = 1.3, std. = 0.70). This can be clearly demonstrated with PCA analysis on

the variance of neurons' activation of the network (Fig. 7D). When $d = 0$, the first PC explained

99.84% of total variance, leaving nearly no variance for the rest of PCs. Thus, the neural states of

the stimuli were confined into an approximately 1-D space (Fig. 7C). In contrast, when $d = 1$,

to explain the same amount of variance of first PC when $d = 0$, the first 6 PCs (99.78%) were

required. In other words, when $d = 1$, the neural states of the stimuli were dispersed into a

higher dimensional space. Therefore, unlike the network with high diversity in connectivity (i.e.,

$d = 1$), the neural manifold constructed by the network with no diversity (i.e., $d = 0$) suffers a

severe deficit in performing either linear or nonlinear classification (number of linearly separable

problems successful addressed = 9.16 or 8.8% of the whole set, std. = 2.89; number of linearly

inseparable problems successful addressed = 2.74 or 1.8%, std. = 2.23). That is, networks with

identical connection patterns hardly encode much information, even with all neurons showed a

response profile of nonlinear mixed selectivity.

To systematically investigate how connectivity structure influences neural manifolds, we

constructed a series of neural networks with different parameter d, and then measured the

dimensionality of the neural manifolds and the classification performances on both linearly

separable and inseparable problems (see Methods). We found that as the diversity of connectivity

patterns increased, the dimensionality of the neural manifolds also increased monotonically (Fig.

7E, red curve). Interestingly, the network did not need to possess a completely diverse structure

to support a high-dimensional neural manifold. With $d > 0.5$, the dimensionality was reliably

expanded to 7 (see Methods and Supplementary Methods M.6). Accordingly, the number of

successful classifications increased monotonically, finally capable of successfully classifying all

possible problems (i.e., 256) after the dimensionality reliably reached 7 (Fig. 7E, blue curve).

Note that the linearly inseparable problems were resolved in parallel with the linearly separable

classifications (Supplementary Fig. 22).

On the other hand, the heterogeneity of the connectivity structure alone seems not

sufficient, as neural networks with identical heterogeneity of connectivity patterns but consisting

of pure selectivity neurons were only capable of classifying linearly separable problems

(Supplementary Fig. 23). Taken together, the synergy between NMS neurons and their

heterogeneous connectivity is critical, which optimally leverages neural networks to construct a

more complex, higher-dimensional neural space.

Figure 7. Connectivity structure on dimensionality.

(A) Schematic illustration of a two-layer feedforward neural network. Each output neuron of the network

receives the inputs encoding three stimulus features (HV, OI and CA), indexed by   ,   , and   , respectively,

from the input neurons. The connectivity weights are randomly sampled from a multivariate Gaussian

distribution, with the thickness of lines indicting the magnitudes of weights. The connectivity pattern from

feature   to the output neurons is highlighted by color for display purpose. Output neurons' response is

achieved through linear summation and ReLU activation. Networks with three levels of diversities in

connectivity patterns are shown here.

(B) Visualization of neural manifolds in 3-D subspaces when   = 1. Left: the sensory manifold that

corresponds to the stimulus space; Middle: the intermediate manifold after one twist operation (   );

Right: the subspace where linearly separating MIC orientations is achieved. Each point denotes the neural state

of a stimulus, with red and blue colors representing the two MIC orientations (LR), respectively.

(C) Visualization of the neural manifold in a 3-D subspace when   = 0. The subspace is constructed by the

first three PCs of neurons' activation.

(D) Variance explained by PCs of neurons' activation with different connectivity structures. When   = 0,

indexed by the dashed line with the lightest blue, the variance is nearly explained by the first PC alone. When

$d = 1$, indexed by the dashed line with the darkest blue, the curve of variance explained by each PC is

flattened.

(E) The dimensionality and the number of successful classifications as the function of connectivity

heterogeneity (diversity) of networks. Left axis (blue): the number of successful binary classifications. Right

axis (red): the inferred dimensionality of the neural manifolds constructed by the network (for details, see

Methods). Error bar: standard deviation.

Discussion

Sensation is typically defined as the conversion of external sensory stimuli into neural signals,

which are subsequently interpreted and give rise to perception. However, the lack of conceptual

clarity often leads to debates on whether the dichotomy between sensation and perception is real

and necessary[39], and if real, where and why the line of demarcation shall be drawn. Here we

investigate how linearly inseparable problems in the physical world become linearly separable

through the lens of the population doctrine by assembling neurons recorded at different times and

from different monkeys[21,22,26,40,41,42]. By analyzing neural geometry constructed by neuron

populational activities in macaques' V2, we found that the stimuli were faithfully represented in

a 3-D sensory manifold. Critically, to linearly decode the orientation of the illusory contours, an

inherently linearly inseparable problem in the stimulus space, we identified four additional axes,

along with the three axes for the sensory manifold, that constructed a 7-D perceptual manifold

through geometric transformations equivalent to twist operations. Further, the geometric

transformation from the sensory manifold to the perceptual manifold was realized through

collaborative work combining specialized neuronal properties of nonlinear mixed selectivity at

neuron level with heterogeneity in response profiles at population level. In summary, our study

offers a perspective from neural geometry to probe the distinction between sensation and

perception, advocating for future research that integrates more processing (e.g., top-down and

bottom-up processing) and embraces more doctrines (populational and neuronal doctrines).

Previous studies on neural geometry have shown that neural manifolds can faithfully

represent both stimulus space[19,24,43] and action space[26,27,44]. In line with these findings, our study

revealed a cubic-shaped neural manifold embedded in a subspace constructed by three mutually

orthogonal axes, each of which corresponded to the HV, OI, and CA feature of stimuli,

respectively. In addition, the manifold's size was monotonically increased as a function of the

motion coherence of local dots. This manifold, generated by stimuli acting upon the eyes, is

therefore termed the sensory manifold. Further, we identified four additional axes encoding

features absent from the physical stimuli. Specifically, one such axis, geometrically equivalent to

the double twist operations on three stimulus features, encoded perceived orientations of the

illusory contours. Consequently, the neural geometry transformed from the 3-D sensory manifold

into the 7-D perceptual manifold within a delay of about 30ms. This analysis may provide a

formal account of the dynamics involved in the hierarchical abstraction of categories[45]. Note that

the twist operation is just one of numerous algorithms for dimension expansion, and future

studies are essential to explore other biologically plausible algorithms capable of addressing

linearly inseparable problems by expanding dimensionality. Further, the perceptual manifold was

task irrelevant, because in addition to differentiating the MIC orientations, it was equipped to

accomplish the remaining 255 possible classifications, irrespective of linear separability.

Therefore, the task irrelevance characteristics of the perceptual manifold also draws a line of

demarcation between the perceptual manifold and manifolds associated with decision-making or

action. However, the manifold transformation observed in V2 does not necessarily imply that this

transformation originates and concludes in V2. It is possible that the perceptual manifold

partially inherits from feedforward inputs from V1 and is further shaped by feedback from

downstream cortical regions. Future research employing simultaneous recordings across multiple

regions is essential to elucidate the implementation of the transformation from the sensory

manifold to the perceptual manifold.

The creation of these perception-related axes was attributed to NMS neurons. On one hand,

the populational responses of NMS neurons are able to change the geometry of neural manifolds

equivalent to twist operations, thus expanding dimensionality of neural manifolds[6,35]. Both

neurons exclusively selective for a single feature and those exhibiting a linear combination of

selectivity for multiple features were found to be limited to addressing only linearly separable

problems, suggesting the necessity of NMS neurons in bridging sensory inputs to perceptual

experiences. Our study, therefore, advocates the significance of NMS neurons in mediating

geometric transformations from the sensory manifold to the perceptual manifold by generating

latent variables from intermediate axes without direct semantic descriptions[46]. While NMS

neurons apparently lie at the core of the population doctrine, the origins of nonlinear mixed

selectivity remain unclear. Future research is needed to investigate the sources of nonlinear

mixed selectivity, such as heterogeneity in neurons' receptive fields, both in subregions and their

surrounding areas[32,47-50], thus revealing the interplay of spatial heterogeneity in receptive fields

with diverse stimulus features. On the other hand, the distinction between NMS neurons and

neurons with explicit semantic meanings (e.g., neurons with pure selectivity), especially in

higher visual areas, remains vague. In fact, many neurons in these areas integrate multiple

features from earlier stages, qualifying them as NMS neurons, even as they possess semantic

meanings[51-54]. Future studies are needed to explore the interplay between different types of

neurons in the process of geometric transformation.

However, the mere presence of NMS neurons is not sufficient, and their functional efficacy

is intrinsically tied to the heterogeneity at population level[38,55]. With the simulation of networks

with NMS neurons, we found that when the connectivity patterns to NMS neurons were in a

homogenous fashion, the expansion of neural dimensionality was limited, thus constraining the

network's computational power in classifying either linearly separable or inseparable problems.

Conversely, when the heterogeneity in the connectivity patterns was increased, a significant

expansion in the dimensionality of neural manifolds was observed, effectively transforming

linearly inseparable problems into linearly separable ones. Taken together, our study revealed the

symbiotic relationship between the response properties of nonlinear mixed selectivity at neuron

level and the heterogeneity of NMS neurons at population level. In this framework, NMS

neurons serves the "building blocks" that enable the construction of high-dimensional neural

manifolds, whereas the specific architectural configuration of them provides the "blueprint" to

actualizes this potential. That is, both specialized neuronal properties and the intricate

configuration are critical in sculpting the landscape of neural computation.

The high dimensionality of the perceptual manifold provides a reservoir of all

computational solutions, enabling flexible classifications according to downstream task rules.

However, this flexibility comes with a cost as the potential solutions rise exponentially with the

number of dimensions. For example, in our study, downstream cortical regions must identify one

proper classification required by the task from 256 possibilities. While the mechanism for

effectively searching solutions based on task demands remains largely unknown, the

strengthening or weakening of the homogeneity of connectivity patterns through Hebbian ("fire

together wire together") and anti-Hebbian ("out of sync, lose the link") rules might hint at a

possible mechanism of reducing dimensionality[56]. In networks with Hebbian plasticity, neurons

that are frequently co-activated by similar tasks or stimuli often develop stronger and more

homogeneous connectivity patterns, and thus increase the selectivity to specific features and lead

to the formation of specialized modules. Within these modules, neurons tend to exhibit

heightened pure selectivity, thus reduced mixed selectivity at neuron level and decreased

heterogeneity at population level[57,58,59]. This idea is supported by a recent study, where a

sequence of contextually related images (i.e., natural video) is represented in a neural space with

lower dimensionality, evidenced by straighter neural population trajectories, compared to a

sequence of contextually unrelated stimuli[60]. On the other hand, with the anti-Hebbian rule,

task-relevant features are disentangled from task-irrelevant ones. Accordingly, axes associated

with less pertinent features can be compressed, thereby reducing effective dimensionality[61,62,63],

and reshaping the manifold to focus on task-relevant features[4]. Taken together, along the

hierarchy of the ventral visual stream, while the representational dimensionality is high and the

geometry transformation is homeomorphous, the amount of information in each dimension[64] and

the relational structure varies[65]. Thus, specialized neuronal modules gradually emerge, within

which neurons become increasingly selective and attuned to task demands. This dynamic

transformation orchestrates the progression from perceptual to decision-making manifolds, and

ultimately to action-oriented manifolds, through intensive interplay of top-down and bottom-up

processing, enabling us to act upon the physical world, in response to stimuli that have acted

upon us.

Supplemental Information

Supplemental Materials includes 24 figures, 2 tables and 2 videos.

627 **Acknowledgments:** This study was funded by Beijing Municipal Science & Technology

628 Commission, Administrative Commission of Zhongguancun Science Park (Z221100002722012),

629 Tsinghua University Guoqiang Institute (2020GQG1016), and Beijing Academy of Artificial

630 Intelligence (BAAI). We thank Dr. Xingyu Liu for her valuable discussion and comments, and Dr.

631 Haidong Lu for his supervision on conducting the experiments.

633 **Author contributions:** H.M., L.J., T.L. and J.L. developed the theoretical framework. H.M.

634 performed the experiments, collected the data, and compiled the data. H.M., L.J., T.L., and J.L.

635 conceived the data analyses. H.M. and L.J. performed the data analyses. L.J. developed the

636 double-twist model. T.L. performed the network simulation. H.M., L.J., and J.L. wrote the paper.

638 **Competing interests:** Authors declare no competing interests.

Reference

1. Cover, T. M. Geometrical and Statistical Properties of Systems of Linear Inequalities with Applications in Pattern Recognition. *IEEE Trans. Electron. Comput.* **EC**-**14**, 326–334 (1965).

2. DiCarlo, J. J., Zoccolan, D. & Rust, N. C. How does the brain solve visual object recognition? *Neuron* **73**, 415–434 (2012).

3. Chung, S., Lee, D. D. & Sompolinsky, H. Classification and Geometry of General Perceptual Manifolds. *Phys. Rev. X* **8**, 31003 (2018).

4. Bernardi, S. *et al.* The Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. *Cell* **183**, 954-967.e21 (2020).

5. Minsky, M. L. & Papert, S. *Perceptrons, Expanded Edition An Introduction to Computational Geometry*. (MIT Press, Cambridge, 1969).

6. Fusi, S., Miller, E. K. & Rigotti, M. Why neurons mix: High dimensionality for higher cognition. *Curr. Opin. Neurobiol.* **37**, 66–74 (2016).

7. B. Schölkopf and A. J. Smola, *Learning with Kernels: Support Vector Machines Regularization Optimization and Beyond*. (MIT Press, Cambridge, 2002).

8. C. K. Williams and C. E. Rasmussen, *Gaussian Processes for Machine Learning*. (MIT Press, Cambridge, 2006).

9. Chen, M. *et al.* An Orientation Map for Motion Boundaries in Macaque V2. *Cereb. Cortex* (2014) doi:10.1093/cercor/bhu235.

10. Marcar, V. L., Raiguel, S. E., Xiao, D. & Orban, G. a. Processing of kinetically defined boundaries in areas V1 and V2 of the macaque monkey. *J. Neurophysiol.* **84**, 2786–2798 (2000).

11. Mysore, S. G., Vogels, R., Raiguel, S. E. & Orban, G. a. Processing of kinetic boundaries in

macaque V4. *J. Neurophysiol.* **95**, 1864–1880 (2006).

12. Lu, H. D., Chen, G., Tanigawa, H. & Roe, A. W. A Motion Direction Map in Macaque V2.

Neuron **68**, 1002–1013 (2010).

13. Ma, H. *et al.* Processing of motion-boundary orientation in Macaque V2. *Elife* **10**, 1–24

(2021).

14. Seung HS & Lee DD. The manifold ways of perception. *Science* **290**, 2268–2269. (2000)

15. DiCarlo, J. J. & Cox, D. D. Untangling invariant object recognition. *Trends Cogn. Sci.* **11**,

333–341 (2007).

16. Chung, S. & Abbott, L. F. Neural population geometry: An approach for understanding

biological and artificial neural networks. *Curr. Opin. Neurobiol.* **70**, 137–144 (2021).

17. Froudarakis, E. *et al.* Object manifold geometry across the mouse cortical visual hierarchy.

Preprint at *bioRxiv* https://doi.org/10.1101/2020.08.20.258798 (2020).

18. Dyballa, L. *et al.* Population encoding of stimulus features along the visual hierarchy.

Preprint at *bioRxiv* https://doi.org/10.1101/2023.06.27.545450 (2023).

19. Xie, Y. *et al.* Geometry of sequence working memory in macaque prefrontal cortex. *Science.*

375, 632–639 (2022).

20. She, L. *et al.* The geometry of face memory. Preprint at *bioRxiv*

https://doi.org/10.1101/2021.03.12.435023 (2021).

21. Okazawa, G., Hatch, C. E., Mancoo, A., Machens, C. K. & Kiani, R. Representational

geometry of perceptual decisions in the monkey parietal cortex. *Cell* **184**, 3748-3761.e18

(2021).

22. Flesch, T., Juechems, K., Dumbalska, T., Saxe, A. & Summerfield, C. Orthogonal

representations for robust context-dependent task performance in brains and neural

networks. *Neuron* **110**, 1258-1270.e11 (2022).

23. Genkin, M., Shenoy, K. V, Chandrasekaran, C. & Engel, T. A. The dynamics and geometry

of choice in premotor cortex. Preprint at *bioRxiv*

https://www.biorxiv.org/content/10.1101/2023.07.22.550183v1 (2023).

24. Gardner, R. J. *et al.* Toroidal topology of population activity in grid cells. *Nature* **602**,

123–128 (2022).

25. Low, I. I. C., Giocomo, L. M. & Williams, A. H. Remapping in a recurrent neural network

model of navigation and context inference. Preprint at *bioRxiv*

https://doi.org/10.1101/2023.01.25.525596 (2023).

26. Churchland, M. M. *et al.* Neural population dynamics during reaching. *Nature* **487**, 51–56

(2012).

27. Gallego, J. A., Perich, M. G., Miller, L. E. & Solla, S. A. Neural Manifolds for the Control of

Movement. *Neuron* **94**, 978–984 (2017).

28. Gallego, J. A. *et al.* Cortical population activity within a preserved neural manifold underlies

multiple motor behaviors. *Nat. Commun.* **9**, 1–13 (2018).

29. Russo, A. A. *et al.* Neural Trajectories in the Supplementary Motor Area and Motor Cortex

Exhibit Distinct Geometries, Compatible with Different Classes of Computation. *Neuron*

107, 745-758.e6 (2020).

30. Braddick, O. Segmentation versus integration in visual motion processing. *Trends Neurosci.*

16, 263–268 (1993).

31. Lamme, V. A. F. The neurophysiology of figure-ground segregation in primary visual cortex.

J. Neurosci. **15**, 1605–1615 (1995).

32. Hu, J. *et al.* Visual Motion Processing in Macaque V2. *Cell Rep.* **25**, 157-167.e5 (2018).

33. Goldstein, E. B., & Cacciamani, L. *Sensation and perception*. (Cengage Learning, Boston,

2021).

34. Nogueira, R., Rodgers, C. C., Bruno, R. M. & Fusi, S. The geometry of cortical

representations of touch in rodents. *Nat. Neurosci.* **26**, 239–250 (2023).

35. Rigotti, M. *et al.* The importance of mixed selectivity in complex cognitive tasks. *Nature* **497**,

585–590 (2013).

36. Kaufman, M. T. *et al.* The implications of categorical and category-free mixed selectivity on

representational geometries. *Curr. Opin. Neurobiol.* **77**, 102644 (2022).

37. Johnston, W. J., Palmer, S. E. & Freedman, D. J. Nonlinear mixed selectivity supports

reliable neural computation. *PLOS Comput. Biol.* **16**, e1007544 (2020).

38. Langdon, C., Genkin, M. & Engel, T. A. A unifying perspective on neural manifolds and

circuits for cognition. *Nat. Rev. Neurosci.* **24**, 363–377 (2023).

39. Gibson, J. J. *The ecological approach to visual perception: classic edition.* (Houghton

Mifflin., Boston, MA, 1979).

40. Mante, V., Sussillo, D., Shenoy, K. V. & Newsome, W. T. Context-dependent computation

by recurrent dynamics in prefrontal cortex. *Nature* **503**, 78–84 (2013).

41. Yamada, H., Imaizumi, Y. & Matsumoto, M. Neural population dynamics underlying

expected value computation. *J. Neurosci.* **41**, 1684–1698 (2021).

42. Fine, J. M. *et al.* Abstract Value Encoding in Neural Populations But Not Single Neurons. *J.*

Neurosci. **43**, 4650–4663 (2023).

43. Bao, P., She, L., McGill, M. & Tsao, D. Y. A map of object space in primate inferotemporal

cortex. *Nature* **583**, 103–108 (2020).

44. Perich, M. G. *et al.* Motor cortical dynamics are shaped by multiple distinct subspaces during

naturalistic behavior. Preprint at

https://www.biorxiv.org/content/10.1101/2020.07.30.228767v2 (2020).

45. Dehaqani, M. R. A. *et al.* Temporal dynamics of visual category representation in the

macaque inferior temporal cortex. *J. Neurophysiol.* **116**, 587–601 (2016).

46. Jazayeri, M. & Ostojic, S. Interpreting neural computations by examining intrinsic and

embedding dimensionality of neural activity. *Curr. Opin. Neurobiol.* **70**, 113–120 (2021).

47. Xiao, D. The spatial distribution of the antagonistic surround of MT/V5 neurons. *Cereb.*

Cortex **7**, 662–677 (1997).

48. Xiao, D. K., Raiguel, S., Marcar, V., Koenderink, J. & Orban, G. A. Spatial heterogeneity of

inhibitory surrounds in the middle temporal visual area. *Proc. Natl. Acad. Sci. U. S. A.* **92**,

11303–11306 (1995).

49. Xiao, D.-K., Raiguel, S., Marcar, V. & Orban, G. A. Influence of stimulus speed upon the

antagonistic surrounds of area MT/V5 neurons. *Neuroreport* **9**, 1321–1326 (1998).

50. Anzai, A., Peng, X. & Van Essen, D. C. Neurons in monkey visual area V2 encode

combinations of orientations. *Nat. Neurosci.* **10**, 1313–1321 (2007).

51. Zeiler, M. D. & Fergus, R. Visualizing and Understanding Convolutional Networks. *Eur.*

Conf. Comput. Vis. **8689**, 818-833 (2014).

52. Simonyan, K. & Zisserman, A. Very Deep Convolutional Networks for Large-Scale Image

Recognition. *3rd Int. Conf. Learn. Represent. ICLR 2015 - Conf. Track Proc.* 1–14 (2014).

53. Ponce, C. R. *et al.* Evolving Images for Visual Neurons Using a Deep Generative Network

Reveals Coding Principles and Neuronal Preferences. *Cell* **177**, 999-1009.e10 (2019).

54. Bashivan, P., Kar, K. & DiCarlo, J. J. Neural population control via deep image synthesis.

Science **364**, (2019).

55. Kriegeskorte, N. & Wei, X. X. Neural tuning and representational geometry. *Nat. Rev.*

Neurosci. **22**, 703–718 (2021).

56. Caporale, N. & Dan, Y. Spike Timing – Dependent Plasticity□: A Hebbian Learning Rule.

(2008) doi:10.1146/annurev.neuro.31.060407.125639.

57. Bullinaria, J. A. Understanding the emergence of modularity in neural systems. *Cogn. Sci.* **31**,

673–695 (2007).

58. Lindsay, G. W., Rigotti, M., Warden, M. R., Miller, E. K. & Fusi, S. Hebbian learning in a

random network captures selectivity properties of the prefrontal cortex. *J. Neurosci.* **37**,

11021–11036 (2017).

59. Weigand, M., Sartori, F. & Cuntz, H. Universal transition from unstructured to structured

neural maps. *Proc. Natl. Acad. Sci. U. S. A.* **114**, E4057–E4064 (2017).

60. Hénaff, O. J. *et al.* Primary visual cortex straightens natural video trajectories. *Nat. Commun.*

12, (2021).

61. Ganguli, S. & Sompolinsky, H. Compressed sensing, sparsity, and dimensionality in

neuronal information processing and data analysis. *Annu. Rev. Neurosci.* **35**, 485–508

(2012).

62. Rajan, K., Abbott, L. F. & Sompolinsky, H. Stimulus-dependent suppression of chaos in

recurrent neural networks. *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.* **82**, (2010).

63. Farrell, M., Recanatesi, S., Moore, T., Lajoie, G. & Shea-Brown, E. Gradient-based learning

drives robust representations in recurrent neural networks by balancing compression and

expansion. *Nat. Mach. Intell.* **4**, 564–573 (2022).

64. Stringer, C., Pachitariu, M., Steinmetz, N., Carandini, M. & Harris, K. D. High-dimensional

geometry of population responses in visual cortex. *Nature* **571**, 361–365 (2019).

65. Lin, B. & Kriegeskorte, N. The Topology and Geometry of Neural Representations. *arxiv*

(2023).

STAR★METHODS

KEY RESOURCES TABLE

REAGENT or RESOURCE	SOURCE	IDENTIFIER
Experimental Models: Organisms/Strains		
Rhesus macaque (Macaca mulatta)	Suzhou Xishan Zhongke animal Company, Ltd;	http://xsdw.bioon.com.cn/
Deposited data and code		
Codes and dataset	This paper	https://data.mendeley.com/datasets/vrj3645vgz/2
Software and Algorithms		
MATLAB	MathWorks	R2017b & R2022b
Jupyter	Project Jupyter	
Other		
32channel-Array	Blackrock Microsystems, LLC;	https://www.blackrockmicro.com/
64channel Multichannel Neural Recording (AlphaLab SNR)	Alpha Omega;	https://www.alphaomega-eng.com/
ViSaGe	Cambridge Research System Ltd;	https://www.crsltd.com/

RESOURCE AVAILABILITY

Data and materials availability

The data and analysis code are available at Mendeley Data,

https://doi.org/10.17632/vrj3645vgz.2. All data information that supports the findings of this

study are available from the corresponding author on reasonable request.

Materials and Methods

Four hemispheres from two adult male macaque monkeys (Macaca mulatta) were used in this study. All

procedures were performed in accordance with the National Institutes of Health Guidelines and were approved

by the Institutional Animal Care and Use Committee of the Beijing Normal University (protocol number:

IACUC(BNU)-NKCNL2013-13).

Visual stimuli, behavioral tasks, and recordings

The data used in this study was from our previous work, and for details on stimuli, tasks, and recordings,

please see Ma et al[13].

Stimuli were generated with ViSaGe using MATLAB scripts and presented on a 21-inch CRT display.

MIC stimuli had seven levels of dot motion coherence. The size of the MIC was a 4˚-diameter circular and the

position of MIC was consistent with array population RF.

Two monkeys performed an MIC orientation-discrimination task after headpost and optical imaging

guided 32-channel Utah array implant. This task was a two-alternative forced-choice discrimination task and

the monkeys were trained to make an eye saccade choice based on MIC orientations. The monkeys made a

saccade to the right target if the orientation was tilted to the right of the vertical axis, and vice versa. The

monkeys received water reward for correct choices.

The electrophysiological recording system is AlphaLab SnR 64-channel system. Neural signals were

sampled at 22 kHz and with an 800 – 7500 Hz bandpass filter. In this study, we only used single neurons in the

unique-unit dataset[13].

Data analysis

Data preprocessing. To build a high-dimensional neural space, we identified all V2 neurons that participated

in the MIC orientation-discrimination task which only required pass receptive field test. In total, we obtained

93 V2 single neurons, with 47 neurons from Monkey S and 46 neurons from Monkey W.

We sorted all trials into 112 conditions to analyze each neuron's response (2 motion-axis orientation

conditions, 4 sheared configuration conditions, 7 coherence levels, and 2 performance outcomes).

Subsequently, we calculated each neuron's trial-averaged response (from -200ms before stimulus onset to

200ms after stimulus offset) with a Gaussian window (a 10ms sliding window with a 2ms step size). We then

combined all neuron responses after z-scoring each neuron's trial average response[21,40]. Additionally, we

excluded conditions with fewer than 3 trials for some neurons. Following these steps, we constructed a data

matrix of dimensions 61 (useful conditions) x T (trial time) x 93 (neuron number) to represent the data from

the MIC orientation discrimination task.

Support vector machine (SVM). We used SVM for two purposes: first, to decode categorical information

from the neural data, and second, to provide a well-defined vector known as the direction of interest (DoI),

which represents a distinct dimension in the neural space. In the analysis, we used the *fitcsvm* function with a

linear kernel in MATLAB. We retained the default hyper-parameter values of the function, except for

customizing the box constraint. In the neural geometry part, the box constraint was set at 0.001, whereas for

the binary classification part, it was set at 1 (for an explanation of box constraints, see Supplementary Methods

M.1). Then, the SVMs were trained and tested using data points in the neural space.

We divided the data points into training and testing sets. First, we partitioned the complete time range

from -200ms to 1000ms relative to stimulus onset into tiled 12ms-wide time bins. Within each time bin, we

randomly selected half of the time steps for training and the other half for testing. To train a single SVM

classifier, the selected training data from time bins were pooled together. To generate time courses of classifier

accuracy, the classifier was tested within each time bin using the testing data.

Angle analysis. To calculate the angle subtended between two n-dimensional unit vectors $\boldsymbol{\beta}_i$ and $\boldsymbol{\beta}_j$, we

used the following formula:

$$\theta = \text{acos}\left(\boldsymbol{\beta}_i^{\text{T}} \boldsymbol{\beta}_j\right).$$

The vectors were the DoI from SVM classification. For the neural geometry and twist model parts, we

performed SVM analysis once for each classification. For control analyses, we ran SVM analysis 200 times for

each classification (see Supplementary Notes N.6 and Supplementary Fig. 6 A & B). The orthogonality of the

angle was tested by examining whether it significantly differed from the angle distribution constructed by

randomly selecting two vectors in a 93-dimensional space (see Supplementary Notes N.6 and Supplementary

Fig. 6C).

Three-D visualization. The main axes identified by SVM were mutually orthogonal, resulting in Cartesian

coordinate systems. Then, we linearly transformed the original neural space to a new coordinate system where

its first several axes aligned with the main axes identified by SVM. To obtain the transformation matrix $\boldsymbol{T}$, we

first created an arbitrary full rank matrix $\boldsymbol{A}$, where its first few columns were the identified main axes. We then

applied QR decomposition on matrix $\boldsymbol{A}$ to obtain an orthogonal matrix $\boldsymbol{Q}$. The transformation matrix was

$\boldsymbol{T} = \boldsymbol{Q}^{\text{T}}$ (see Supplementary Methods M.2 for details).

To visualize the neural states in a 3-D subspace, we first applied low-pass filter (cutoff frequency: 2Hz)

to the data in the original neural space. We then used matrix $\boldsymbol{T}$ to transform the filtered data into a new

high-dimensional coordinate system. Finally, the transformed data were projected into a 3-D subspace

constructed by the main axes identified for visualization.

Double-twist model. The double-twist model transformed the continuous cylindrical stimulus manifold

depicted in Fig. 3C (left) to a continuous perceptual manifold embedded in a 7-D space. Its projections into

3-D subspaces were shown in gray in Fig. 3C (middle & right). The perceptual manifold arose from the

correspondence between the XOR operation and the arithmetic product. Let the true value be represented by

-1.0, and the false value by 1.0. The truth table of the XOR operation aligns with that of the arithmetic product

(see Supplementary Fig. 24). That is,

$$x \oplus y \Leftrightarrow xy.$$

Therefore, in the double-twist model, the 7-D coordinates of a point in the perceptual manifold

corresponding to a point $[x, y, z]$ in the stimulus manifold were $[x, y, z, xy, yz, xz, xyz]$.

The double-twist model was fit to the neural data using affine transformation. Because the neural data

contained noise, we first applied a low-pass filter (cutoff frequency: 2Hz), and then calculated the steady-state

averages (from 300ms to 500ms relative to stimulus onset) of neural activities for the 8 stimuli to determine 8

centers. These centers were then projected into various 3-D subspaces (Fig. 3). In each subspace, we located

the neural states for the 8 stimuli based on the ideal double-twist model. Using the least-square method, we

derived the transformation matrix $\boldsymbol{F}$. The mean of the residuals was represented as a vector $\boldsymbol{e}$. For any point

$\boldsymbol{x}$ on the ideal double-twist model, we applied the transformation

$$\hat{\boldsymbol{y}} = \boldsymbol{F}\boldsymbol{x} + \boldsymbol{e}$$

to fit the model to the data (see Supplementary Methods M.5 for detailed formulation). The goodness of fit was

measured by R^2.

Binary classification. Binary classification entailed sorting stimulus conditions into two classes based on all

possible classification rules. With 8 stimulus conditions, we had a total of 256 classification rules. For each

classification, the criterion for linear separability was set at 75% accuracy within each stimulus cluster. Each

neuron pool was randomly selected from the entire set of 93 neurons, one at a time, and we then conducted

SVM analysis 10 times for each neuron pool (see Supplementary Methods M.6).

To infer the dimensionality from binary classification, we employed the approach developed by Rigotti

et al[35]. Briefly, we calculated the ratio of the actual number of linearly separable classifications and the

theoretical number of binary classifications for each condition number n ($n \in \{2, \dots, 8\}$). The last n whose

ratio > 0.8 was selected as the dimensionality (see Supplementary Methods M.6).

Connectivity patterns of neural networks. We created a simple two-layer feedforward neural network; the

first layer contained 3 units representing the three feature dimensions, respectively, and the second layer

contained 93 nonlinear mixed selectivity neurons. Each neuron received the input signals of all the three

feature dimensions (mixed): x(HV), y(OI) and z(CA), and employed a ReLU activation function

(nonlinearity). The input signals represented the eight corners of the cube in the x-y-z stimulus space, each

corresponding to a specific stimulus. The activity r_i of the ith neuron was defined as:

$$r_i = \text{ReLU}\left(\sum_j w_{ij}\gamma_j + b_i\right) + \epsilon,$$

where $\gamma_j \in \{x, y, z\}$ is the input signal of the jth stimulus feature with w_{ij} as the weight, b_i is a random

bias sampled from the uniform distribution $\mathcal{U}(0,1)$, and ϵ is a noise term drawn from the Gaussian

distribution $\mathcal{N}(0, 1/3)$.

The weights w_{ij} were randomly sampled from standard Gaussian distributions. The covariance

between the weights controlled the structure of the network and thus determined the heterogeneity of the

output activities. Hence, we used a diversity parameter $d \in [0,1]$ to define the 93×93-D covariance matrix K

for sampling the weights of feature x:

$$K = \begin{bmatrix} 1 & 1-d & \cdots & 1-d \\ 1-d & 1 & \cdots & 1-d \\ \vdots & \vdots & \ddots & 1-d \\ 1-d & 1-d & \cdots & 1 \end{bmatrix}.$$

The covariance matrix K was fed into the *multivariate_normal* function in Python's *numpy.random*

package to generate the weights. The procedure for generating weights of features y and z was identical.

We ran multiple simulations on the network. In each simulation, input stimuli were repeated 100 times

to allow the added random noise for generating point clusters. We applied the same analyses for the network's

output activities as we did for the neural data. One hundred simulations were conducted for calculating the

dimensionality of the neural geometry.