Predictions enable top-down pattern separation in the macaque face-processing hierarchy

Tarana Nigam[1,2,3,4], Caspar M. Schwiedrzik[1,2,3*†]

[1.] Neural Circuits and Cognition Lab, European Neuroscience Institute Göttingen – A Joint Initiative of the University Medical Center Göttingen and the Max Planck Society, Grisebachstraße 5, 37077 Göttingen, Germany

[2.] Perception and Plasticity Group, German Primate Center – Leibniz Institute for Primate Research, Kellnerweg 4, 37077 Göttingen, Germany

[3.] Leibniz ScienceCampus 'Primate Cognition', Göttingen, Germany

[4.] International Max Planck Research School 'Neurosciences', Georg August University Göttingen, Grisebachstraße 5, 37077 Göttingen, Germany

* Correspondence: C.M.S. (c.schwiedrzik@eni-g.de)

† Lead contact

1 Summary

Distinguishing faces requires well distinguishable neural activity patterns. Contextual
information may separate neural representations, leading to enhanced identity recognition.
Here, we investigate how predictions derived from contextual information affect the
separability of neural activity patterns in the macaque face-processing system, a 3-level
processing hierarchy in ventral visual cortex. We find that in the presence of predictions,
early stages of this hierarchy exhibit well separable and high-dimensional neural
geometries otherwise characteristic only of the top of the hierarchy. This is accompanied
by a systematic shift of tuning properties from higher to lower areas, endowing lower areas
with higher-order, invariant representations instead of their feedforward tuning properties.
Thus, top-down signals dynamically transform neural representations of faces into
separable and high-dimensional neural geometries. Our results provide evidence how
predictive context transforms flexible representational spaces to optimally use the
computational resources provided by cortical processing hierarchies for better and faster
distinction of facial identities.

Highlights

- Predictions increase pattern-separation and dimensionality in early face-processing areas.
- Early face-processing areas dynamically inherit tuning properties from higher areas.
- Predictions enable top-down separability and invariance for identity recognition.

Keywords

pattern separation, predictive coding, statistical learning, feedback, plasticity, face-processing, inferotemporal cortex, macaque monkey, functional magnetic resonance imaging

Introduction

We have all mistaken someone or been mistaken for somebody else. Indeed, recognizing people by their face is a significant computational challenge both for humans and machines, especially in light of variations in appearance, e.g., with a different hairstyle or pose. This is particularly evident when distinguishing lookalikes (or "doppelgänger") like the actresses Natalie Portman and Keira Knightley in a movie (Fig. 1A)[1]. To do so, we need additional *contextual* information, e.g., information from previous scenes, which we use to make predictions[2]. Predictions render recognition better and faster, yet the computations and neural implementation mediating those effects remain poorly understood. In particular, it is unknown how contextual predictions optimize sensory neural representations, especially for distinguishing individuals by their face.

The reason why we struggle to distinguish Natalie from Keira is that similar stimuli lead to correlated neural activity patterns. To distinguish stimuli like faces, neural representations should have minimal overlap and hence be "separable". Separability is largely determined by stimulus properties, i.e., how physically similar faces are, and only achieved at hierarchically higher areas in the ventral visual stream, where neural representations are also robust against variations like pose change[3]. How can incorporating predictive information enable distinguishing identities? Predictive processing theories suggest that higher-order areas generate predictions that are communicated to lower areas via feedback pathways[4]. We hypothesized that incorporating higher-order predictive information leads to more separable (Fig. 1A) and invariant (Fig. 1B right) representations already in lower areas of the hierarchy.

To investigate how predictability optimizes neural representations for distinguishing identities, we turned to the macaque face-processing system (Fig. 1B left). This information processing hierarchy in inferotemporal (IT) cortex is highly specialized for faces, and the neural representations and transformations across successive stages of processing are well understood. In the ventral part of this system, representations become successively invariant to face view while the system extracts facial identity: the lowest area, ML, represents face shape and possesses view-specificity; the intermediate area AL has mirror-symmetric representations; at the apex of the hierarchy, in AM, representations are view-invariant and contains facial appearance information for identity recognition[5,6]. We used functional magnetic resonance imaging (fMRI) to access these qualitatively distinct representations in all three face-areas simultaneously. By training animals to expect specific faces based on temporally preceding information[7] (Fig. 1C), we could test how predictions affect neural representations, and whether feedback pathways are involved.

We find a gradient of pattern-separability along the face-processing hierarchy with the
highest separability at the top, in AM, even when no predictive context exists. Once
predictions come into play, pattern-separability increases in lower stages of the hierarchy.
This is accompanied by the emergence of abstract, view-invariant representations at these
lower processing stages: rather than the view-specific tuning properties they show in the
absence of predictions, we find that lower face-areas express representations characteristic
of higher stages of processing when stimuli are predictable. This suggests that high-level
prediction signals cascading-down the face-processing system dynamically transform
neural representational spaces, endowing them with increased pattern-separability and
invariance. This may enable lower areas to abstract from irrelevant features for enhanced
distinction of identities. Our findings provide a new take on the flexibility of neural
representations in IT and suggest a specific mechanism, top-down pattern-separability, by
which predictions exert their effects.

Figure 1: Increasing pattern separability through top-down predictions. ***A.*** Similar faces, like those of the lookalikes
Natalie Portman and Keira Knightley, are hard to distinguish because they lead to poorly separable neural activity patterns.
Contextual predictions, derived, e.g., from a previous scene, can aid distinguishing similar stimuli. We hypothesize that
predictive context facilitates recognition by increasing separability between neural activity patterns. ***B.*** In the face processing
system, the lowest area ML has view-specific shape representations, the intermediate area AL has mirror-symmetric
representations, and the top of the hierarchy, AM, has view-invariant appearance representations. All stages are directly and

Results

As a first step in investigating whether and how predictions alter neural coding in the face-

processing system, we localized three face-areas - ML, AL, and AM – in two macaque

monkeys using a standard face localizer for whole-brain fMRI. We then trained the monkeys

to associate temporally contiguous faces into pairs using statistical learning[7] (Fig. 1C). Once

learned, the first face in a pair (the "predictor") fully predicts the second face (the

"successor"). We exposed the monkeys to nine face-pairs for a minimum of three weeks,

providing ample time to elicit effects of predictability in IT cortex[8]. To assess the acquisition

of face-pair associations, we evaluated pupil dynamics, an established marker of statistical

learning[9]. Indeed, we found pupil entrainment to the frequency of the face-pairs after

training (Supplementary Fig. S1). Once we established face-pair learning in the monkeys,

we investigated if and how coding spaces changed as a function of contextual predictions

across the face-processing system using a rapid event-related design for fMRI (Fig. 1C). In

the *expected* condition (60% of trials), we presented learned face-pairs, such that

predictions were elicited once the predictor had been shown and thus took effect when the

successor appeared. On violation trials, predictions went unfulfilled as we presented an

unexpected identity in the expected view or an unexpected view of the expected identity as

the successor[7]. Since our focus was on investigating how predictability contributes to the

identity recognition, one of the main computational goals of face-processing, we mostly

concentrate on conditions involving facial identity.

Before evaluating how predictive context optimizes neural representations for face

individuation, we first established how neural separability for identity increases across the

face-processing hierarchy in the absence of predictive context (the *context-free* condition).

In each of the three face-areas we measured cosine distances between activity patterns

elicited by different faces (Fig. 2Ai). We report average results because these distances

were highly correlated across monkeys (Spearman's rho=0.95, p=3.5e-04). Pattern-

separability increased along the hierarchy (ML<AL<AM, paired Hotelling test, all p<1.462e-

11, corrected for multiple-comparisons). This corroborates previous electrophysiological

studies in IT cortex outside the face-processing system[10] and indicates that, in the absence

of predictability, high levels of pattern-separability for facial identities are only achieved in
AM, the top of the face-processing hierarchy.

After determining baseline pattern-separability across the face-processing system, we
evaluated whether predictability aids face identification by increasing pattern-separability in
lower areas. We compared separability across face identities between the expected and
context-free conditions (Fig. 2Aii): when faces were expected, we found that lower areas in
the face-processing hierarchy, ML and AL, increased pattern-separability for identities by
~10° from 52.1° to 61° in ML and 67.7° to 77.2° in AL (Fig. 2B; William-Watson test, ML:
$F_{(1,70)}=79.74$, p=1.067e-12; AL: $F_{(1,70)}=34.49$; p=2.619e-07, corrected for multiple
comparisons). In contrast, pattern-separability in the higher area AM remained unchanged
(84.7° vs. 87.5°; $F_{(1,70)}=3.53$; p=0.0644, corrected for multiple comparisons). This
suggests that high separability otherwise characteristic of the top of the processing
hierarchy can already be attained in lower areas if predictive information exists - potentially
facilitating readout of information from well decorrelated representations.

Predictive processing theories suggest that predictions serve to compute prediction errors
(PE) as a deviation between the prediction and the sensory input to reduce redundancy in
information transmission[11]: redundant information is removed, optimizing the dynamic
range of neurons and allowing them to efficiently signal decorrelated or unpredicted
information[12]. In terms of pattern separation, this may entail higher pattern-separability
when PEs (to unexpected faces) occur. To evaluate this possibility, we compared pattern
separation between the violation and context-free conditions in the three face areas.
Prediction violations increased pattern-separability in the entire face-processing hierarchy
(Fig. 2B; William-Watson test, ML: 77.7° vs. 52.1°, $F_{(1,70)}=485.84$, p<0.0001; AL: 82.8° vs.
67.7°, $F_{(1,70)}=115.65$, p=4.44e-16; AM: 89.6° vs. 84.7°, $F_{(1,70)}=14.00$, p=0.0003,
corrected for multiple comparisons). AM patterns were, in fact, almost orthogonal in this
condition (mean 89.6°, one-sample test for mean angle vs. 90°, p>0.05). Interestingly,
prediction violations increased pattern-separability even beyond the separability achieved
in predictable conditions, but only in lower stages of the hierarchy (paired Hotelling test,
ML: 77.1° vs. 61°, $F_{(2,34)}=97.0819$, p=2.631e-14; AL: 82.8° vs. 77.2°, $F_{(2,34)}=9.9190$,
p=8.084e-04; AM: 89.6° vs. 87.5°, $F_{(2,34)}=1.7520$, p=0.1887, corrected for multiple-
comparisons). PEs thus appear to enhance pattern-separability in lower processing stages
by optimizing the available dynamic range, while the top maintains a stable prior. Taken
together, our results suggest that pattern separation may be the mechanism underlying the
beneficial effects of predictability in IT cortex, decreasing interference between
representations of identities. By increasing pattern-separability at lower stages of
processing, predictions may thus help in achieving one of the core computations for
face/object recognition earlier than in the absence of predictive context.

Figure 2: Predictions increase separability in the face-processing hierarchy. A.i) Pattern-separability was computed as pair-wise cosine distances between activity patterns elicited by all faces presented in each context. Faces were computer generated in Facegen. **A.ii)** Neural activity patterns are well separable when there is minimal overlap between population vectors. Separability between the same faces can depend on context. The angle θ between population vectors denotes separability. Faces were computer generated in Facegen. **A.iii)** Activity patterns may not be well-separable in low-dimensional spaces. Expanding dimensionality, e.g., by adding feature dimensions, can increase separability. **B)** Pattern-separability increases along the face-processing hierarchy from ML (52.1°) to AL (67.1°) to AM (84.7°) in the context-free condition (green). Lower areas in the hierarchy increase pattern-separability when faces are expected (gray; ML 52.1° to 61°; p=1.067e-12; AL: 67.7° to 77.2°, p=2.619e-07), whereas AM shows no difference in separability (84.7° vs. 87.5°, p=0.0644). Prediction violations (red) increase separability in all areas even further (ML: 77.7° vs. 52.1°, p<0.0001; AL: 82.8° vs. 67.7°, p=4.44e-16; AM: 89.6° vs. 84.7°, p=0.0003). Only lower areas have higher separability in the unexpected than in the expected condition (ML: 77.1° vs. 61°, p=2.631e-14; AL: 82.8° vs. 77.2°, p=8.084e-04; AM: 89.6° vs. 87.5°, p=0.1887). Lines depict mean angles, squares and circles pair-wise angles between identities per monkey. **C)** Estimated dimensionality in all areas and conditions is lower than that of the noise ceiling (light grey boxplots, all p<9.99e-04). In the context-free condition (green), dimensionality is higher in AM than in lower areas (all p<9.9e-04 for both monkeys). Dimensionality increases when faces are expected

How do predictions give rise to increased separability in the hierarchy? We hypothesized that contextual information provided by predictions could add feature dimensions for separability – implying that predictive cues improve separability by increasing dimensionality of neural representational space (Fig. 2Aiii). To evaluate this hypothesis, we quantified dimensionality using the Participation Ratio (PR)[13,14] which describes how evenly the variance of neural activity is spread (i.e., dimensionality is high if variance is spread across all dimensions). PR was computed per face-area and condition across all voxels and stimuli. We first established that PR was interpretable, i.e., well differentiated from noise, in all conditions and face-areas (Fig. 2C; comparison to noise-ceiling for each monkey, all $p<9.99e-04$, corrected for multiple comparisons). Next, we investigated PR as a function of hierarchy. In the context-free condition, we found higher dimensionality in AM than in lower stages ML and AL (comparison of difference to noise ceiling between areas for each monkey, all $p<9.9e-04$, corrected for multiple comparisons). For expected faces, dimensionality increased in lower areas AL and ML (that had shown increases in pattern separability) compared to the context-free condition (Monkey L – ML: p=0.0189, AL: p=0.004; Monkey P – ML: p=0.045, AL: p<0.0001, corrected for multiple comparisons). When expectations were violated, dimensionality increased even further compared to the expected condition in ML (Monkey L: p<0.0001; Monkey P: p<0.0001, corrected for multiple comparisons) and AL (Monkey L: p<0.0001; Monkey P: p=0.0001, corrected for multiple comparisons), and slightly less consistently in AM (Monkey P: p<0.0001; Monkey L: p=0.055, corrected for multiple comparisons). Increases in dimensionality and separability across conditions and hierarchy were highly correlated (Spearman's rho=0.95, p=3.5273e-04), suggesting that contextual signals (like predictions and/or PEs) increase pattern-separability through an expansion of representational dimensionality.

Previous studies have shown that deviance between predictions and sensory inputs is signaled as a difference in the magnitude of neural activity between unexpected and expected stimuli[7,16,17]. Indeed, we also found stronger responses in the unexpected than in the expected condition in all three face-areas (Supplementary Fig. S2; all $p<3.5e-04$). However, this difference in magnitude did not explain the increase in pattern-separability (Spearman's rho=0.0167, p=0.9816) nor dimensionality (rho=0.2667, p=0.4933) with contextual information across the hierarchy. This is in line with previous findings indicating that population magnitude and separability in IT cortex convey different information[18].

A Representational similarity analysis

i) Representational geometry (1st level RDM) in Context-Free and Expected condition

Pattern of activity across voxels

Pair-wise distances

ii) Prediction error representational geometry

Unexpected   Expected

Pair-wise distances

iii) Model representational dissimilarity matrix

Shape/ Appearance feature vectors

Pair-wise distances

B High-level representations in lower areas of the face processing hierarchy

Face Area ML   Face Area AL   Face Area AM

lower hierarchy   higher hierarchy

Context-Free

Expected — Representational Similarity (Z-Spearman Correlation)

Prediction Error

Shape **M**irror **S**ymmetry **A**ppearance **V**iew-independent **a**ppearance

Figure 3: High-level predictions cascade down the face-processing hierarchy. Ai.) Representational Similarity Analysis
(RSA) was performed for each face area1st level representational dissimilarity matrices (RDMs) were computed for the
context-free (green) and expected (gray) condition as cosine distances between the stimulus-evoked activity patterns to the
different faces shown within each condition. **A.ii)** Prediction error (PE) geometry was calculated on the relative activity
difference of the same faces in the expected vs. unexpected condition. **A.iii)** 1st level RDMs were compared to model RDMs
derived from known tuning properties of the face areas (**s**hape, **m**irror-symmetry, **a**ppearance, **v**iew-independent

How can predictive signals increase separability in lower stages of the hierarchy? One possibility is that lower areas inherit (more separable) representations from higher areas via feedback pathways conveying predictions. Higher areas in the ventral stream contain representations that are not only highly separable, but also invariant, e.g., for view. A consequence of predictions being passed from higher to lower areas is that lower areas should inherit the invariant tuning properties of the areas where the predictions originate. To evaluate this hypothesis, we determined the representational geometry across the face-processing hierarchy using Representational Similarity Analysis (RSA)[19] (Fig. 3Ai). We computed cosine distances between the activity patterns for different face stimuli and compared 1st level RDMs to model RDMs based on known electrophysiological tuning properties of each face area (Fig. 3Aiii, see below). Results were highly correlated across monkeys (Spearman's rho=0.5524; p=2.3830e-04), hence, we report results from averaged 1st level RDMs.

First, in the context-free condition, we established that our approach recapitulated the known electrophysiological tuning properties of face-processing areas[5,6]. As expected, the known tuning properties best explained the representational geometry in all three face areas: view-specific representation of facial shape in ML, mirror-symmetric representation in AL, and view-invariant representation of facial appearance in AM (Fig. 3B; bootstrapped test comparing 2nd level correlation coefficients, one-sided; ML: shape vs. 3 others, difference=0.3153; p=0.0417; AL: mirror symmetry vs. 3 others, difference=0.8364, p<0.0001; AM: 2 appearance-based models vs. 2 others, difference=0.4712, p=0.0019). Next, we tested the hypothesis that under predictable conditions, lower areas exhibit higher-order tuning properties. To this end, we compared representational geometry between the expected and context-free conditions in ML and AL. These lower areas indeed expressed higher-order, abstract representations: ML showed an increase in mirror-symmetric tuning, characteristic of AL (Raghunathan's test, p=0.0460), while AL showed increased tuning for appearance (p=0.0072) and view-independent appearance (p=8.941e-6), characteristics of

AM. Moreover, in the predictable condition we observed a decrease in the classical, feedforward tuning properties in the entire face-processing network, i.e., decreased shape tuning in ML (p=0.0323), decreased mirror-symmetric tuning in AL (p=0.0073), and decreased appearance (p=0.0091) and view-independent appearance tuning (p=0.0043) in AM. Thus, rather than expressing their own feedforward tuning properties, lower areas ML and AL exhibited representations characteristic of higher face-areas when stimuli were predictable. This suggests that high-level predictions cascade-down the entire face-processing hierarchy along feedback pathways, carrying with them a representational format that enables better pattern separation.

Finally, we investigated the representational format of PEs in the unexpected conditions. Predictive processing theory and our results so far suggest that lower areas inherit tuning properties from higher areas, which implies that PEs in lower areas should also express higher-level tuning properties[7]. To test this, we isolated PEs by computing the relative difference between the expected and the unexpected conditions and then applied RSA (Fig. 3Aii). For identity PEs, we found that the pattern of tuning properties was highly correlated with the expected condition (Fig. 3B; Spearman's rho=0.7273, p=0.01), suggesting that the representational geometry evident in the expected condition indeed forms the basis of the computation of PEs when unexpected identities occur. Further mirroring the expected condition, there was an increase in appearance (Raghunathan's test, p=0.0086) and view-independent appearance tuning (p=0.0079) in AL compared to the context-free condition, concomitant to a decrease in mirror-symmetric tuning (p=0.0022). Similarly, appearance (p=0.0178) and view-independent appearance tuning (p=0.0049) again decreased in AM. This suggests that identity PEs in the unexpected identity condition are computed in AL on the basis of appearance tuning originating in AM, i.e., one stage earlier than identity information in the context-free condition. Similarly, and in accordance with our previous electrophysiological results from ML[7], we found significant mirror-symmetric tuning in ML (bootstrapped test, p=0.039) in the unexpected view condition (although this form of tuning did not exhibit a statistically significant increase over the context-free condition; Fisher test, p=0.188). This was accompanied by a decrease of mirror-symmetric tuning in AL (p=0.0003). Overall, this suggests that PEs are computed on the basis of high-level prediction signals in lower areas of the face-processing hierarchy.

Discussion

Taken together, our results reveal that incorporating predictive cues optimizes neural representations for distinguishing facial identities by increasing separability of neural activity

patterns already early in the face-processing hierarchy. The improved separability with
contextual information comes with an expansion of dimensionality of neural
representational space. These effects can be achieved by cascading-down prediction
signals via feedback pathways - such that well separated, invariant representations
characteristic of higher face-areas are passed down to lower areas. Our work thus proposes
a distinct mechanism, i.e., top-down pattern-separability, through which predictions exert
their effects.

Well separated neural representations are beneficial for processing because they allow for
linear readout of information[20,21] and learning new associations[22]. Pattern separation is a
well-established computational mechanism, originally attributed to hippocampal and
cerebellar circuits[23–25]. Recent proposals assign this computation also to cortex[26] - albeit
with different implementations owing to the distinct architectures. We find that predictive
information enables high separability in lower areas of the ventral visual stream, which is
otherwise only characteristic of the top of this cortical processing hierarchy. Highly
separated representations early on in the hierarchy may be beneficial since they facilitate
early readout of high-level information like object identity.

Theory suggests that highly separable representations can arise from dimensionality
expansion[20,21] - providing a larger neural activity space for linear separability. We find that
AM at the top of the face-processing hierarchy, which is thought to directly contribute to
face individuation, has high dimensionality, similar to the human face-processing
hierarchy[15]. This may be related to the inherently high dimensionality of face space required
to differentiate individuals[27]. Increases in separability in AL and ML brought about by
predictability are accompanied by an expansion of dimensionality. This suggests that the
dimensionality of IT cortex activity is in principle flexible and not hardwired. Our findings
thus resonate with studies in other species and brain areas which have shown that the
dimensionality of neural activity can change on short timescales, e.g., from spontaneous to
stimulus-evoked activity[28], or with task engagement[29].

Furthermore, we find that in the presence of expectations, lower areas in the face-
processing hierarchy express higher-order representations. This suggests that predictions
originating from high-level face-processing areas are propagated down to lower areas via
feedback connections, in line with predictive processing theories[30]. Predictions lead to a
complete transformation of representational geometry, suggesting that they impose the
high-level representational format characteristic of the stage of processing at which they
are generated, at the expense of the feedforward tuning properties of the respective lower
area. This transformation spans the entire face-processing hierarchy: ML inherits tuning
properties of AL, and AL inherits tuning properties of AM. This results in the processing of
facial appearance, a dimension most closely related to face identification[31], at earlier stages

of processing than when no context is available. AM itself no longer shows image-bound
properties expressed in the ventral face-processing network, but may inherit yet more
abstract, perhaps conceptual representations from the frontal or medial temporal lobe
(MTL) with which it is intricately connected[32,33]. This radical transformation between
predicted and context-free representations underscores IT's capacity to flexibly and
dynamically switch coding regimes on very short timescales, i.e., trial-by-trial, and refutes
the notion that tuning properties are hard-wired after years of learning and development.

Signaling predictions and deviations from them not only improves sensory encoding but
also refines internal models by means of PEs. We find that unexpected stimuli boost
pattern-separation in lower face-processing areas beyond the separability found in the
expected condition, while not modulating separability at the top of the hierarchy. PEs may
refine internal models by increasing separability, in line with memory updating in the MTL[34]
and episodic memory enhancement[35,36]. The concomitant increase in dimensionality that
we find in the unexpected condition suggests that contextual information provided by
predictions introduces additional dimensions into the representational geometry for
separability. This would be in line with conjunctive representations between stimulus
features and context[18,37], specifically between stimulus features and PEs[7] observed
electrophysiologically in IT cortex. Such mixed selectivity could boost pattern-separability
and enable more effective readout from high dimensional representational spaces[20].

Previous accounts have explained predictions by dampening, i.e., gain modulation[38], or
sharpening of highly selective neurons[39]. Dampening predicts amplitude differences
between expected and unexpected stimuli; while we find such differences in amplitudes in
line with previous studies (Supplementary Fig. S2), they do not explain the differences in
separability that we find across the face-processing hierarchy and between conditions,
which arise from the multivariate spatial pattern of activity. Sharpening would also predict
better discriminability of facial identities as a function of the underlying selectivity; however,
sharpening accounts would suggest increased separability solely in AM because only those
neurons are highly identity-selective[5]. Furthermore, sharpening may be specific to early
visual cortex and/or low dimensional stimuli such as gratings[40,41]. To what extent previously
reported sharpening and dampening effects are related to pattern separation remains an
important target for future research.

Overall, our results suggest a new account of how the ventral stream implements
predictions: top-down signals that dynamically transform neural representations into
separable and high-dimensional neural geometries. Passing tuning properties down to
earlier processing stages allows extraction of high-level, abstract information earlier than
what is possible in the absence of predictions, when feedforward computation dominates
and signals need to ascend the entire hierarchy to provide information about facial identity.

Predictions thus also free resources for the processing of yet more abstract, less image-
bound information in the areas whose feedforward tuning properties are now shifted
upstream. Predicting on the basis of invariant tuning properties that abstract over irrelevant
features circumvents overfitting to individual images and has an extended temporal horizon
compared to pixel-level predictions which are prone to fail in noisy conditions. Our results
thus exemplify how feedback connections enable flexible representational spaces that
optimally use the computational resources provided by cortical processing hierarchies.

Acknowledgements

We thank W. Freiwald for generously allowing us to collect part of the data in his lab; I.
Kagan for support; R. Auksztulewicz for insightful discussions; L. Melloni for comments on
the manuscript; A. Gonzalez, L. Burchardt, R. Mielsch, and S. Plewe for help with animal
training and care; T. Becker, O. Batura, and A. Schrod for veterinary care; S. Karmacharya,
W. Zarco, and R. Ludwig for help with the respective setups; and L. Yin for administrative
support. This research was supported by the Deutsche Forschungsgemeinschaft (DFG,
German Research Foundation) through an Emmy Noether grant (SCHW1683/2-1) and SFB
1528 - 'Cognition of Interaction' (Project-ID 454648639, project A04) to C.M.S.; additional
support was provided by an Outgoing Grant from the Leibniz ScienceCampus 'Primate
Cognition', Göttingen, Germany to T.N.
381

Author contributions

T.N.: Conceptualization; Methodology; Software; Validation; Formal analysis; Investigation;
Writing - Original Draft; Writing - Review & Editing; Visualization.
C.M.S.: Conceptualization; Methodology; Writing - Original Draft; Writing - Review &
Editing; Supervision; Project administration; Funding acquisition.

Declaration of Interest

The funders had no role in study design, data collection and interpretation, decision to
publish, or preparation of the manuscript. The authors declare no competing financial or
non-financial interests.

Methods

Resource Availability

Lead Contact

Further information and requests for resources should be directed and will be fulfilled by the lead contact, Caspar M. Schwiedrzik (c.schwiedzik@eni-g.de) upon reasonable request.

Material Availability

This study did not generate new or unique reagents.

Data and Code Availability

Data will be made openly available in a repository after publication.

Experimental Model and Study Participant Details

Monkey Subjects and Surgical Procedures

Data for this study were acquired in two adult macaque monkeys (*Macaca mulatta*): one male (Monkey P, 6.5-7 kg, 9 years) and one female (Monkey L, 8.5-9 kg, 10 years). No power calculation was performed to determine the sample size, but was chosen to be in accordance with previous studies[52,53]. We did not have sufficient sample size to investigate differences between female and male macaque monkeys. All procedures with Monkey P were conducted at the German Primate Center, Göttingen and approved by the responsible regional government office (Niedersächsisches Landesamt für Verbraucherschutz und Lebensmittelsicherheit - LAVES). The animal was either housed in pairs or groups, adhering to German and European regulations. The facility provided a stimulating environment for the animals, including various toys and structures, natural and artificial lighting, and access to outdoor spaces, surpassing the space requirements outlined in European regulations. All procedures with Monkey L complied with the National Institutes of Health Guide for Care and Use of Laboratory Animals and were approved by the local Institutional Animal Care and Use Committees of The Rockefeller University (protocol number 21104-H USDA) and Weill Cornell Medicine (protocol number 2010-0029, where

magnetic resonance imaging (MRI) was performed. The animal was housed with other
macaque monkeys and had access to a stimulating environment including various toys for
enrichment. The well-being of both the animals, both psychologically and medically, was
closely monitored on a daily basis by veterinarians, animal facility personnel, and scientists.
Both animals were subjected to surgical procedures where MRI-compatible cranial head-
posts were implanted, embedded within bone cement, anchored with MR-compatible
ceramic screws under general anesthesia and sterile conditions[7]. The animals underwent
extensive training using positive reinforcement[54] to become accustomed to entering and
remaining seated in a horizontal primate chair. Their head position was stabilized using the
implanted head-posts, allowing for cleaning of the implants, accurate recording of
gaze/pupil diameter, and minimizing motion artifacts during MRI experiments.

Method Details

MRI Data Acquisition

MRI data were acquired on 3T scanners (Monkey P: MAGNETOM-Prisma; Monkey L:
MAGNETOM-Prisma_fit, Siemens Healthineers, Erlangen, Germany). Anatomical images
were obtained for each animal in a separate session using a T1-weighted magnetization-
prepared rapid gradient echo (MPRAGE) sequence (Monkey P: field of view [FOV] 128 mm,
voxel size = 0.5 × 0.5 × 0.5 mm, repetition time [TR] = 2.7 s, echo time [TE] = 2.96 ms,
inversion time [TI] = 850 ms, bandwidth [BW] = 220 Hz/Px, flip angle [FA] = 8 degrees, 240
slices, 11 cm loop coil, Siemens Healthineers; Monkey L: FOV = 128 mm, voxel size = 0.5
× 0.5 × 0.5 mm, TR = 2.7 s, TE = 2.99 ms, TI = 868 ms, BW = 230 Hz/Px, FA = 9 degrees,
240 slices, custom 1-channel receive coil L. Wald, MGH Martinos Center for Biomedical
Imaging) while the monkeys were anesthetized (isoflurane 1.5%–2%) and positioned in an
MR-compatible stereotactic frame (Kopf Instruments). Functional images were acquired
using custom 4 or 8 channel phased-array receive surface coils with a horizontally oriented
single loop transmit coil (H. Kolster, Windmiller Kolster Scientific, and L. Wald, MGH
Martinos Center for Biomedical Imaging) while the monkeys were in a sphinx position. Each
functional time series consisted of whole-brain gradient-echo planar images (EPI; FOV =
96 mm, voxel size = 1.2 × 1.2 × 1.2 mm, TR = 2 s, TE = 27 ms, BW = 1302 Hz/Px, echo
spacing [ESP]= 0.93 ms, FA = 76 degrees, 43 slices) acquired in interleaved order with two
times generalized autocalibrating partially parallel acquisitions (GRAPPA) acceleration. All
functional images in the Statistical Learning Paradigm (see below) for both monkeys and
Face Localizer (see below) in Monkey P were acquired with the above sequence
parameters. Functional images for Face Localizer in Monkey L were acquired with the

contrast agent ferumoxytol (Molday ION, BioPAL, Worcester, USA), and hence slightly
different sequence parameters (FOV = 96 mm, voxel size = 1.2 × 1.2 × 1.2 mm, TR = 2.25
s, TE = 17 ms, BW = 1525 Hz/Px, FA = 79 degrees, 45 slices). Right before every scanning
session, ferumoxytol was injected into the saphenous vein. The amount administered
ranged from 9 mg of Fe per kg of the animal's body weight during the first scan to 6 mg on
following days to account for the functional half-life of the contrast agent. On every session,
field maps (FOV = 96 mm, voxel size = 1.2 × 1.2 × 2.4 mm, TR = 0.7 s, TE1 = 5 ms, TE2 =
7.46 ms, FA = 60 degrees, 22 slices) were also acquired which were later used for EPI
undistortion[55].

Face Localizer

We use a standard face localizer to localize the face patches ML, AL, and AM[56]. Subjects
fixated on a central white dot while we displayed images of human/monkey faces, body
parts/headless bodies, man-made objects, and fruits, alternating with baseline periods in a
block design (FOB). Each block lasted 24-30 s. Fluid reward was given after variable 2-4 s
periods, contingent on gaze staying within 2 degrees of the fixation dot. Analysis included
runs where subjects achieved ≥80-85% fixation stability. Visual stimulation and reward were
controlled using Psychtoolbox[48] for Monkey P and Presentation (v19, Neurobehavioral
Systems) for Monkey L. Stimuli were projected on a back-projection screen using a video
projector (Monkey P: Epson EB-G5600, refresh rate 60 Hz, resolution 1920 × 1080 px;
Monkey L: NEC NP3250, refresh rate 60 Hz, resolution 1024 × 768 px) with a custom lens.
Eye position was measured using a video-based eye tracking system (Monkey P: SR
Research Eyelink 1000 NHP Long Range Optics at 1000 Hz, Monkey L: ISCAN at 120 Hz).

Statistical Learning Paradigm

For the statistical learning experiment, we generated 30 three-dimensional faces with
neutral expression and no hair using FaceGen Modeller Pro 3.27 (Singular Inversions).
Seven views (0°, 30°, 45°, 60°, 300°, 315°, 330°) were extracted for each face. The faces
were counterbalanced for their gender and skin texture was added such that the right profile
image was not a simple mirror-version of the left-profile image. The images were converted
to grayscale and then luminance normalized using the SHINE toolbox[49]. The training set for
the statistical learning experiment consisted of 18 facial identities with 6 images of frontal,
right and left profile-view each. These were split into 9 predictor-successor pairs such that
the head orientations were balanced within predictors and successors, respectively[7].
Prior to the training phase, monkeys were familiarized with the entire set of 30 faces in all
the 7 views in randomized order such that no image was novel to the monkey. The monkeys

were then exposed to the face-pairs to establish associations between the predictor and the successor images. Pairs were arranged such that one identity-view combination would uniquely predict one other identity-view combination (Supplementary Fig. S3). Training was conducted with sequentially presented face-pairs for at least 3 weeks for both monkeys. The sequence of pairs was designed such that the transitional probability within a pair was 100% and the transitional probability between pairs was kept at a minimum.

In the early phase of training, each image was presented foveally (8 dva in size) for 500 ms with an inter-stimulus interval of 500 ms. Longer baselines (up to 9.5 s) and spatial jittering (~1 dva) from the foveal position were gradually introduced over the training period. This was done to accustom the animals to the task design to be used during the fMRI experiments. The monkey was rewarded with water/juice every 2.5-3.8 s for maintaining fixation within a 2-3 dva window around the fixation dot presented at the center of the screen. To control visual stimulation and reward delivery, we used mWorks (https://mworks.github.io/) and a custom-built input-output device (R. Brockhausen) using Teensy 3.6 (PJRC: Electronic Projects) for Monkey P, and Presentation (v20.2, Neurobehavioral Systems) with a commercially available data acquisition device (Measurement Computing USB 1208FS) for Monkey L. Stimuli were presented using a video projector for Monkey P (Barco F22 WUXGA; refresh rate, 60 Hz; resolution, 1920 × 1080 px) and displayed on a monitor for Monkey L (Dell E2011H, refresh rate 60 Hz, resolution 1920 × 1080 px). Eye position was measured using video-based eye tracking (Monkey P: SR Research Eyelink 1000 at 1000 Hz, Monkey L: ISCAN at 120 Hz).

The testing phase of the statistical learning paradigm took place while fMRI data were acquired (Monkey L: 81 runs; Monkey P: 56 runs). In this phase, learned face-pairs were presented such that one face predicted the next; violations of the predictions (40% of all trials) were introduced in the second image of a face-pair. The violations entailed a successor image with a different identity (but with the expected view) or a different view (but with the expected identity) than during the training phase. To create the identity violation conditions, we systematically recombined the trained predictor image of a pair with that of another successor image to generate unexpected pairs. To create the view violation conditions, we presented the predicted identity but with a different head orientation than during training. The experimenter was not blinded to the experimental conditions. A fixation dot was continuously presented at the center of the screen and the monkey was rewarded for maintaining fixation within a 2-3 dva fixation window every 2.2-3.6 s. Reward was thus not contingent upon image presentation but entirely on fixation performance. We used a rapid-event related design: each face image was presented for 500 ms, aligned to the onset of volume acquisition. To facilitate single-trial deconvolution of the blood oxygenation level

dependent (BOLD) response, baseline durations were jittered between 1.5, 3.5 and 5.5 s for intra-pair and 5.5, 7.5 and 9.5 s for inter-pair intervals. The face images were spatially jittered within ~1 dva around the fixation dot to avoid low-level adaptation effects.

Quantification and Statistical Analyses

MRI processing

Anatomical images were intensity normalized, skull-stripped, and segmented using Freesurfer (v5.3, https://surfer.nmr.mgh.harvard.edu/)[47]. Preprocessing of fMRI data was done using Freesurfer's functional analysis stream, FS FAST, AFNI (https://afni.nimh.nih.gov)[42] and the JIP toolkit (https://www.nitrc.org/projects/jip). Slice-wise motion-correction was done within each run using AFNI's 3dAllineate with terms for cubic warping in the phase encoding direction, as well as shifts, rotations, scaling, and skewing, followed by slice-time correction using FS FAST. Geometric distortions of the functional volumes were corrected by means of the field maps, followed by mutual information-based non-linear alignment to the high-resolution anatomical scans as implemented in JIP.

Statistical modeling was done using a General Linear Model (GLM) in FS FAST. Predictors of interest were convolved with the canonical hemodynamic response function (HRF) for BOLD for all experiments except for Monkey L's Face Localizer data where HRF parameters were appropriate for ferumuxytol[57]. Motion parameters, fixation stability, and reward were included as nuisance regressors. The first five volumes of each functional run were excluded to prevent T1 saturation artifacts, and detrending (up to 2nd degree polynomials) was applied within the GLM. To identify the face-areas from the FOB data, we contrasted faces vs. all other visual categories[58]. Regions of interest (ROIs) in each hemisphere were defined as the intersection of a sphere around the peak voxel identified by this contrast and the gray matter, resulting in ROIs of ~100 voxels. Since face-processing is not lateralized in macaque monkeys[59], we combined the voxels in each of the face-areas from the two hemispheres for all our analyses (Monkey P: ML 204, AL 185, AM 187; Monkey L: ML 198, AL 190, AM 204 voxels).

For the testing phase of the statistical learning experiment, we resolved trial-specific activation using the least squares-single approach[60]. In this approach, a separate GLM is calculated for each trial and the design matrix contains two main task-related regressors: the trial-of-interest was defined as the first regressor and all other trials in a run, irrespective of the experimental conditions, were simultaneously defined as the second (nuisance) regressor. This was done iteratively for every stimulus within a run. The regression

559   coefficient for the trial of interest was contrasted with the baseline and the t-statistic

560   obtained for each trial was used for further analyses[61].

Pattern separability

Pattern-separability was computed across facial identities using cosine distances, a

measure commonly used in the pattern separation literature[62,63]. Cosine distances indicate

the vector direction of a population response irrespective of amplitude or sample size

differences in the experimental conditions[64,65] and have thus been argued to be particularly

sensitive to the tuning of neural populations in the context of fMRI[66]. To compute cosine

distances, we extracted t-statistics from all trials and conducted multivariate noise-

normalization using the covariance matrix of the residuals from the GLM done on every

trial[61]. Cosine distances were then converted to angles by computing the inverse cosine.

This was done for each stimulus in all ROIs and conditions, respectively. All nine facial

identities that were presented as the first stimulus in a pair were used to estimate the

separability in the 'Context-Free' condition. The first image in a pair cannot be anticipated

on the basis of the preceding image and is thus processed in the absence of contextual

predictions. All nine trained successor stimuli were used for the 'Expected' condition. The

distances between the same nine stimuli when presented as an expectation violation were

used to quantify the separability in the 'Unexpected' condition. Due to the circular nature of

angles, circular statistics[44] were used to compare conditions and ROIs, respectively. We

used the Hotelling paired sample test for equal angular means[67] for paired comparisons,

and the William-Watson test for independent samples comparisons[68]. All p-values were

corrected for multiple comparisons using the Bonferroni-Holm method[69]. All the above

analyses were done using The Decoding Toolbox[50] in MATLAB (The MathWorks, Inc.,

R2018B) and custom MATLAB scripts.

Dimensionality

To estimate dimensionality of neural representational space in a given ROI in the different

experimental conditions, we computed the Participation Ratio (PR)[13,14,45]. PR is the ratio of

the square of the first moment and the second moment of the eigenvalue probability density

function and quantifies how evenly variance of activity is spread across stimuli; i.e., if

variance is widely spread, PR is high. We estimated PR using whitened t-statistics across

voxels and stimuli in each condition and ROI. Hence, our measure of dimensionality is

constrained by the number of stimuli. To determine whether the dimensionality estimates

are interpretable, we compared the estimated dimensionality to that of noise. Noise ceilings

were estimated by synchronized permutation (1000) of the stimuli and voxels for each

condition and ROI. We then tested whether the estimated dimensionality is lower than the

95% confidence interval (CI) of the noise distribution. Similarly, pairwise differences

between the dimensionality across ROIs or conditions were assessed by comparing

whether the increase in estimated dimensionality was higher than the 95% CI of the noise

distribution. All p-values were corrected for multiple comparisons using the Bonferroni-Holm

method[69]. PR was quantified using publicly available[45] Python scripts and statistically

analyzed using custom MATLAB scripts.

Population response magnitude

Population response magnitudes[18] were quantified as the Euclidean (L2) norm across all

voxels in a given ROI for each stimulus separately and then averaged. This served to

disentangle differences in the magnitude of the IT population response from angular

differences in stimulus identity as it has been shown that population response magnitude

and population response vector direction can contain differential information[70]. We

computed the Euclidean (L2) norm from the t-statistics per stimulus without further

normalization so as not to discard any relevant magnitude differences, as recommended

in[18]. Paired t-tests were used to assess differences in population response magnitude

across expected and unexpected conditions, and corrected for multiple comparisons using

the Bonferroni-Holm method[69].

Representational Similarity Analysis

Representational Similarity Analysis (RSA)[19] was conducted to assess tuning properties of

face-areas and how they change with experimental conditions. We first determined whether

we could replicate the well-known tuning properties of the face-areas using BOLD signals,

relative to the electrophysiological "gold standard"[5,6]. To this end, we computed 1st level

representational dissimilarity matrices (RDMs) using cosine distances (as described in the

separability section above) on the pattern of BOLD responses across voxels in each of the

ROIs. We then compared these 1st level RDMs to representations predicted by previous

electrophysiology studies (Model/Hypothetical RDMs).

The choice of model RDMs was based on previous studies that show that ML has a view-

specific representation of facial shape, AL has mirror-symmetric representation, and AM

has view-invariant representation of the facial appearance[5,6]. To compute hypothetical

RDMs for shape and appearance, the Active Appearance Model[51,71]

(https://www.menpo.org/) was trained using 871 pre-annotated images and used to fit each

of our face stimuli to obtain 68 shape landmarks[72]. We then computed Spearman rank
correlation distances between the feature vector of landmark positions for all the stimuli to
compute a hypothetical shape RDM. We used 45° and 135° faces to extract all 68 shape
landmarks to ascertain a full set of shape landmarks for all the facial views such that
similarity between the faces could be computed considering all views. Next, to compute an
appearance representational space, each face was smoothly warped to the average shape
template made from the training set, using spline interpolation. This warped image was then
normalized for the mean and reshaped to obtain an appearance feature vector. We then
computed Spearman rank correlation distances between the feature vector of the
appearance feature vector for all the stimuli to obtain a hypothetical appearance RDM. Note
that this appearance model RDM contains a component of facial view and is different from
the shape-free appearance model referred to in[6] where the authors computed appearance
representations on each view separately. Therefore, we additionally computed a model
RDM using only the frontal-view versions of the same nine facial identities and performed
the same procedure as above to obtain the hypothetical appearance RDM. Although this
hypothetical RDM is made with only frontal faces, correlating it with an empirical RDM
based on three different views is what makes this a view-independent/invariant appearance
model. Lastly, we designed a hypothetical mirror-symmetry RDM by assigning the distance
within each view and between left and right profile faces to be zero[5].
Comparisons of model RDMs with empirical, 1st level RDMs were carried out using
Spearman rank correlation[19], partialling out low-level similarities[73] using a Gabor wavelet
pyramid as a model of early visual cortex[74,75]
(https://github.com/daseibert/image_similarity_toolbox). To test whether the known
electrophysiological properties of each face-area best explain the representations in each
of the three face-areas, we compared the model fit of the candidate RDM (e.g., Fisher z-
transformed Spearman rank correlation between Mirror-symmetry model RDM and the 1st
level RDM in AL) to the average model fits of the three other models (e.g., shape,
appearance, and view-independent appearance). This was done using bootstrapping
(10000 samples, one-sided) in the context-free condition when no predictability exists, and
which corresponds most closely to the electrophysiological studies that established the
tuning properties of the face-areas. To test whether tuning properties changed as a function
of experimental condition, i.e., whether there is an increase in higher-order tuning properties
in lower areas and a decrease in feedforward tuning properties in higher areas, respectively,
we compared the model fit of the candidate RDM in the condition with no context to that of
its model fit in the expected/unexpected identity conditions. This was done by using
Raghunathan's test[76] (one-sided) for dependent, non-overlapping correlation coefficients
which also takes intercorrelations between the model and experimental RDMs into account.

To study the representational geometry of PEs, we first computed the relative difference between the expected and the respective unexpected condition (view, identity). This effectively isolates PEs, which are thought to signal the difference between expected and unexpected stimuli with increases in neural activity[7]. Following this, we computed pairwise cosine distances between the change in activity pattern and determined 2nd level similarity by means of RSA. For the unexpected identity condition, cosine distances were computed across the different identities before the 2nd level RSA was conducted. For the unexpected view condition, we calculated the difference between the expected identity and the view violations of the corresponding identity (both unexpected views of a given identity separately). Then, the 1st level RDM was computed across the different face images, followed by 2nd level RSA (the Gabor wavelet pyramid was not partialled out for this analysis). Since PEs are thought to be computed on the representational format of expectations, we hypothesized that PEs also lead to an increase in high-level properties in lower areas of the hierarchy. We assessed increases in high-level tuning properties and decrease in feedforward tuning properties between unexpected identity and context-free conditions using Raghunathan's test for dependent, non-overlapping correlations[76]. To compare the context-free with the unexpected view condition, we used Fisher's test for independent, non-overlapping correlations[77]. These analyses were carried out in R (v3.6.2) using the 'cocor' toolbox[43].

Pupil entrainment

Pupil entrainment was used to determine whether the face-pair structure was learned, in accordance with previous studies establishing neural[78,79] and pupillary entrainment[9] as a signature of statistical learning. During training, face images were presented at a rate of 1 Hz (the image frequency), resulting in a pair frequency of 0.5 Hz. To determine pupil entrainment to face pairs, we computed inter-trial phase coherence[80] (ITC). Only runs in which fixation stability was >85 % for Monkey P and >80% for Monkey L were selected. Preprocessing of pupil area data was done in accordance with previously published work on pupil entrainment to face-pairs[9]: blinks and missing data were linearly interpolated; outliers in pupil area were detected using median absolute deviation (cutoff 3.5 for Monkey P and 1.5 for Monkey L) and linearly interpolated. This was followed by low-pass filtering at 5 Hz using a onepass-zerophase Kaiser-windowed sinc finite impulse response (FIR) filter (filter order 1812, transition width 2.0 Hz, pass band 0-4.0 Hz, stop band 6.0-500 Hz, maximal pass band deviation 0.0010 (0.10%), stop band attenuation -60 dB)[81]. Subsequently, data were detrended per run and per block; the average pupil area over the baseline of 2 s before the beginning of stimulation in each block was subtracted. Data from

Monkey P were then downsampled to 500 Hz and Monkey L was retained at the acquisition
frequency (120 Hz). Pseudo-trials of 32 seconds were made from continuous data, time-
locked to the first stimulus in a face-pair. The pseudo trials had 30 second overlap for
Monkey P and 26 second overlap for Monkey L. An additional baseline correction was
performed per pseudo-trial by subtracting an average of the pupil area over the 2 s pre-
block baseline. Data for Monkey L which was acquired at a low sampling rate was
additionally detrended per pseudo-trial. We then computed a trial-by-trial Fourier transform
using discrete prolate spheroidal sequences (DPSS) as tapers with a spectral resolution of
0.0625 Hz, using the Matlab toolbox Fieldtrip (v20190329;
http://www.fieldtriptoolbox.org/)[46]. The resulting complex spectra were used to calculate
ITC. ITC at the pair-frequency was normalized by dividing the mean ITC of 4 surrounding
frequency bins (2 above, 2 below). Normalized ITC values above 1 thus indicate
entrainment at the respective frequency. Statistical significance of ITC at the pair-frequency
was determined using a one-sided t-test against 1 in both monkeys. In addition, to assess
whether ITC at the pair frequency increased from early to late phases of training, we
compared the first and second half of training sessions, respectively, in monkey P
(unpaired, one-sided t-test). Due to technical issues and time constraints, pupil data for
monkey L was only available from the late training phase.

References

1. H. Lamba, A. Sarkar, M. Vatsa, R. Singh, and A. Noore (2011). Face recognition for look-alikes: A preliminary study. In 2011 International Joint Conference on Biometrics (IJCB), pp. 1–6. 10.1109/IJCB.2011.6117520.

2. Summerfield, C., and de Lange, F.P. (2014). Expectation in perceptual decision making: neural and computational mechanisms. Nat. Rev. Neurosci. *15*, 745–756. 10.1038/nrn3838.

3. DiCarlo, J.J., and Cox, D.D. (2007). Untangling invariant object recognition. Trends Cogn. Sci. *11*, 333–341. 10.1016/j.tics.2007.06.010.

4. Spratling, M.W. (2017). A review of predictive coding algorithms. Brain Cogn. *112*, 92–97. 10.1016/j.bandc.2015.11.003.

5. Freiwald, W.A., and Tsao, D.Y. (2010). Functional Compartmentalization and Viewpoint Generalization Within the Macaque Face-Processing System. Science *330*, 845–851. 10.1126/science.1194908.

6. Chang, L., and Tsao, D.Y. (2017). The code for facial identity in the primate brain. Cell *169*, 1013–1028. 10.1016/j.cell.2017.05.011

7. Schwiedrzik, C.M., and Freiwald, W.A. (2017). High-Level Prediction Signals in a Low-Level Area of the Macaque Face-Processing Hierarchy. Neuron *96*, 89-97.e4. 10.1016/j.neuron.2017.09.007.

8. Meyer, T., and Olson, C.R. (2011). Statistical learning of visual transitions in monkey inferotemporal cortex. Proc. Natl. Acad. Sci. *108*, 19401–19406. 10.1073/pnas.1112895108

9. Schwiedrzik, C.M. and Sudmann, S.S. (2020). Pupil diameter tracks statistical structure in the environment to increase visual sensitivity. J. Neurosci. 40, 4565. 10.1523/JNEUROSCI.0216-20.2020.

10. Rust, N. C. and DiCarlo, J.J. (2010). Selectivity and Tolerance ("Invariance") Both Increase as Visual Information Propagates from Cortical Area V4 to IT. J. Neurosci. *30*, 12978. 10.1523/JNEUROSCI.0179-10.2010.

11. Huang, Y., and Rao, R.P.N. (2011). Predictive coding. WIREs Cogn. Sci. *2*, 580–593. 10.1002/wcs.142.

12. Srinivasan, M.V., Laughlin, S.B., and Dubs, A. (1982). Predictive Coding: A Fresh View of Inhibition in the Retina. Proc. R. Soc. Lond. B Biol. Sci. *216*, 427–459.

13. Gao, P., Trautmann, E., Yu,B., Santhanam,G., Ryu,S., Shenoy,K., and Ganguli,S. (2017). A theory of multineuronal dimensionality, dynamics and measurement. bioRxiv, 214262. 10.1101/214262.

14. Recanatesi, S., Bradde, S., Balasubramanian, V., Steinmetz, N.A., and Shea-Brown,
E. (2022). A scale-dependent measure of system dimensionality. Patterns *3*, 100555.
10.1016/j.patter.2022.100555.

15. Sheng, J., Zhang, L., Liu, C., Liu, J., Feng, J., Zhou, Y., Hu, H., and Xue, G. Higher-
dimensional neural representations predict better episodic memory. Sci. Adv. *8*,
eabm3829. 10.1126/sciadv.abm3829.

16. Alink, A., Schwiedrzik, C.M., Kohler, A., Singer, W., and Muckli, L. (2010). Stimulus
Predictability Reduces Responses in Primary Visual Cortex. J. Neurosci. *30*, 2960.
10.1523/JNEUROSCI.3730-10.2010.

17. Kaposvari, P., Kumar, S., and Vogels, R. (2018). Statistical Learning Signals in
Macaque Inferior Temporal Cortex. Cereb. Cortex *28*, 250–266. 10.1093/cercor/bhw374.

18. Jaegle, A., Mehrpour, V., Mohsenzadeh, Y., Meyer, T., Oliva, A., and Rust, N. (2019).
Population response magnitude variation in inferotemporal cortex predicts image
memorability. eLife *8*, e47596. 10.7554/eLife.47596.

19. Kriegeskorte, N., Mur, M., and Bandettini, P. (2008). Representational similarity analysis
- connecting the branches of systems neuroscience. Front. Syst. Neurosci. *2*, 4.
10.3389/neuro.06.004.2008.

20. Fusi, S., Miller, E.K., and Rigotti, M. (2016). Why neurons mix: high dimensionality for
higher cognition. Neurobiol. Cogn. Behav. *37*, 66–74. 10.1016/j.conb.2016.01.010.

21. Cayco-Gajic, N.A., and Silver, R.A. (2019). Re-evaluating Circuit Mechanisms
Underlying Pattern Separation. Neuron *101*, 584–602. 10.1016/j.neuron.2019.01.044.

22. Barlow, H., and Foldiak, P. (1989). Adaptation and decorrelation in the cortex. In The
Computing Neuron, C. Miall, R. Durbin, and G. Mitchison, eds. (Addison Wesley), pp.
54–72.

23. Marr, D. (1969). A theory of cerebellar cortex. J. Physiol. *202*, 437–470.
10.1113/jphysiol.1969.sp008820.

24. Marr, D., and Brindley, G.S. (1997). Simple memory: a theory for archicortex. Philos.
Trans. R. Soc. Lond. B Biol. Sci. *262*, 23–81. 10.1098/rstb.1971.0078.

25. Albus, J.S. (1971). A theory of cerebellar function. Math. Biosci. *10*, 25–61.
10.1016/0025-5564(71)90051-4.

26. Amer, T., and Davachi, L. (2023). Extra-hippocampal contributions to pattern
separation. eLife *12*, e82250. 10.7554/eLife.82250.

27. M. Meytlis, and L. Sirovich (2007). On the Dimensionality of Face Space. IEEE Trans.
Pattern Anal. Mach. Intell. *29*, 1262–1267. 10.1109/TPAMI.2007.1033.

28. Mazzucato, L., Fontanini, A., and La Camera, G. (2016). Stimuli Reduce the
Dimensionality of Cortical Activity. Front. Syst. Neurosci. *10*. 10.3389/fnsys.2016.00011

29. Yao, J.D., Zemlianova, K.O., Hocker, D.L., Savin, C., Constantinople, C.M., Chung, S.,

and Sanes, D.H. (2023). Transformation of acoustic information to sensory decision
variables in the parietal cortex. Proc. Natl. Acad. Sci. *120*, e2212120120.

30. Rao, R.P.N., and Ballard, D.H. (1999). Predictive coding in the visual cortex: a functional
interpretation of some extra-classical receptive-field effects. Nat. Neurosci. *2*, 79–87.
10.1038/4580.

31. Andrews, T.J., Rogers, D., Mileva, M., Watson, D.M., Wang, A., and Burton, A.M.
(2023). A narrow band of image dimensions is critical for face recognition. Vision Res.
212, 108297. 10.1016/j.visres.2023.108297.

32. Schwiedrzik, C.M., Zarco, W., Everling, S., and Freiwald, W.A. (2015). Face patch
resting state networks link face processing to social cognition. PLoS Biol. *13*, e1002245.
10.1371/journal.pbio.1002245

33. Grimaldi, P., Saleem, K.S., and Tsao, D. (2016). Anatomical Connections of the
Functionally Defined "Face Patches" in the Macaque Monkey. Neuron *90*, 1325–1342.
10.1016/j.neuron.2016.05.009.

34. Bein, O., Duncan, K., and Davachi, L. (2020). Mnemonic prediction errors bias
hippocampal states. Nat. Commun. *11*, 3451. 10.1038/s41467-020-17287-1.

35. Frank,D., Montemurro,M.A., and Montaldi, D. (2020). Pattern Separation Underpins
Expectation-Modulated Memory. J. Neurosci. *40*, 3455. 10.1523/JNEUROSCI.2047-
19.2020.

36. Barron, H.C., Auksztulewicz, R., and Friston, K. (2020). Prediction and memory: A
predictive coding account. Prog. Neurobiol. *192*, 101821.
10.1016/j.pneurobio.2020.101821.

37. She,L., Benna,M.K., Shi,Y., Fusi,S., and Tsao, D.Y. (2021). The neural code for face
memory. bioRxiv, 2021.03.12.435023. 10.1101/2021.03.12.435023.

38. Kumar, S., Kaposvari, P., and Vogels, R. (2017). Encoding of Predictable and
Unpredictable Stimuli by Inferior Temporal Cortical Neurons. J. Cogn. Neurosci. *29*,
1445–1454. 10.1162/jocn_a_01135.

39. Kok, P., Jehee, J.F.M., and de Lange, F.P. (2012). Less Is More: Expectation Sharpens
Representations in the Primary Visual Cortex. Neuron *75*, 265–270.
10.1016/j.neuron.2012.04.034.

40. Richter, D., Ekman, M. and de Lange, F.P. (2018). Suppressed Sensory Response to
Predictable Object Stimuli throughout the Ventral Visual Stream. J. Neurosci. *38*, 7452.
10.1523/JNEUROSCI.3421-17.2018.

41. Richter, D., Heilbron, M., and de Lange, F.P. (2022). Dampened sensory
representations for expected input across the ventral visual stream. Oxf. Open Neurosci.
1, kvac013. 10.1093/oons/kvac013.

42. Cox, R.W. (1996). AFNI: Software for Analysis and Visualization of Functional Magnetic

Resonance Neuroimages. Comput. Biomed. Res. *29*, 162–173.
10.1006/cbmr.1996.0014.

43. Diedenhofen, B., and Musch, J. (2015). cocor: A comprehensive solution for the
statistical comparison of correlations. PloS One *10*, e0121945.
10.1371/journal.pone.0121945

44. Berens, P. (2009). CircStat: A MATLAB Toolbox for Circular Statistics. J. Stat. Softw.
31, 1–21. 10.18637/jss.v031.i10.

45. Stephenson, C., Feather, J., Padhy, S., Elibol, O., Tang, H., McDermott, J., and Chung,
S. (2019). Untangling in invariant speech recognition. Adv. Neural Inf. Process. Syst. *32*.
arXiv:2003.01787v1

46. Oostenveld, R., Fries, P., Maris, E., and Schoffelen, J.-M. (2010). FieldTrip: Open
Source Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological
Data. Comput. Intell. Neurosci. *2011*, 156869. 10.1155/2011/156869.

47. Fischl, B. (2012). FreeSurfer. 20 YEARS FMRI *62*, 774–781.
10.1016/j.neuroimage.2012.01.021.

48. Brainard, D.H. (1997). The Psychophysics Toolbox. Spat. Vis. *10*, 433–436.
10.1163/156856897X00357.

49. Willenbockel, V., Sadr, J., Fiset, D., Horne, G.O., Gosselin, F., and Tanaka, J.W. (2010).
Controlling low-level image properties: The SHINE toolbox. Behav. Res. Methods *42*,
671–684. 10.3758/BRM.42.3.671.

50. Hebart, M.N., Görgen, K., and Haynes, J.-D. (2015). The Decoding Toolbox (TDT): a
versatile software package for multivariate analyses of functional imaging data. Front.
Neuroinformatics *8*. 10.3389/fninf.2014.00088

51. Alabort-i-Medina, J., Antonakos, E., Booth, J., Snape, P., and Zafeiriou, S. (2016). The
Menpo Project. SIGMultimedia Rec *8*, 4–9. 10.1145/2982857.2982858.

52. Klink, P.C., Chen, X., Vanduffel, W., and Roelfsema, P.R. (2021). Population receptive
fields in nonhuman primates from whole-brain fMRI and large-scale neurophysiology in
visual cortex. eLife *10*, e67304. 10.7554/eLife.67304.

53. Cui, D., Sypré, L., Vissers, M., Sharma, S., Vogels, R., and Nelissen, K. (2023).
Categorization learning induced changes in action representations in the macaque STS.
NeuroImage *265*, 119780. 10.1016/j.neuroimage.2022.119780.

54. Prescott, M.J., and Buchanan-Smith, H.M. (2003). Training Nonhuman Primates Using
Positive Reinforcement Techniques. J. Appl. Anim. Welf. Sci. *6*, 157–161.
10.1207/S15327604JAWS0603_01.

55. Jezzard, P., and Balaban, R.S. (1995). Correction for geometric distortion in echo planar
images from B0 field variations. Magn. Reson. Med. *34*, 65–73.
10.1002/mrm.1910340111.

56. Fisher, C., and Freiwald, W.A. (2015). Contrasting Specializations for Facial Motion
within the Macaque Face-Processing System. Curr. Biol. *25*, 261–266.
10.1016/j.cub.2014.11.038.

57. Leite, F.P., Tsao, D., Vanduffel, W., Fize, D., Sasaki, Y., Wald, L.L., Dale, A.M., Kwong,
K.K., Orban, G.A., Rosen, B.R., et al. (2002). Repeated fMRI Using Iron Oxide Contrast
Agent in Awake, Behaving Macaques at 3 Tesla. NeuroImage *16*, 283–294.
10.1006/nimg.2002.1110.

58. Moeller, S., Freiwald, W.A., and Tsao, D.Y. (2008). Patches with Links: A Unified
System for Processing Faces in the Macaque Temporal Lobe. Science *320*, 1355–1359.
10.1126/science.1157436.

59. Tsao, D.Y., Moeller, S., and Freiwald, W.A. (2008). Comparing face patch systems in
macaques and humans. Proc. Natl. Acad. Sci. *105*, 19514–19519.
10.1073/pnas.0809662105.

60. Mumford, J.A., Turner, B.O., Ashby, F.G., and Poldrack, R.A. (2012). Deconvolving
BOLD activation in event-related designs for multivoxel pattern classification analyses.
NeuroImage *59*, 2636–2643. 10.1016/j.neuroimage.2011.08.076.

61. Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., and Diedrichsen, J. (2016).
Reliability of dissimilarity measures for multi-voxel pattern analysis. NeuroImage *137*,
188–200. 10.1016/j.neuroimage.2015.12.012.

62. Madar, A.D., Ewell, L.A., and Jones, M.V. (2019). Pattern separation of spiketrains in
hippocampal neurons. Sci. Rep. *9*, 5282. 10.1038/s41598-019-41503-8.

63. Bird, A.D., Cuntz, H., and Jedlicka, P. (2023). Robust and consistent measures of
pattern separation based on information theory and demonstrated in the dentate gyrus.
bioRxiv, 2022.11.04.515143. 10.1101/2022.11.04.515143.

64. Chou, E.P., and Hsu, S.-M. (2018). Cosine similarity as a sample size-free measure to
quantify phase clustering within a single neurophysiological signal. J. Neurosci. Methods
295, 111–120. 10.1016/j.jneumeth.2017.12.007.

65. Diedrichsen, J., Berlot, E., Mur, M., Schütt, H., Shahbazi, M., and Kriegeskorte, N.
(2021). Comparing representational geometries using whitened unbiased-distance-
matrix similarity. Neurons Behav. Data Anal. Theory *5*. 10.51628/001c.27664.

66. Ramírez, F.M. (2018). Orientation Encoding and Viewpoint Invariance in Face
Recognition: Inferring Neural Properties from Large-Scale Signals. The Neuroscientist
24, 582–608. 10.1177/1073858418769554.

67. Zar, J.H. (1999). Biostatistical Analysis (Prentice Hall).

68. Watson, G.S., And Williams, E.J. (1956). On The Construction Of Significance Tests
On The Circle And The Sphere. Biometrika *43*, 344–352. 10.1093/Biomet/43.3-4.344.

69. Holm, S. (1979). A Simple Sequentially Rejective Multiple Test Procedure. Scand. J.

Stat. *6*, 65–70.

70. Rust, N.C., and Cohen, M.R. (2022). Priority coding in the visual system. Nat. Rev.
Neurosci. *23*, 376–388. 10.1038/s41583-022-00582-9.

71. Cootes, T.F., Edwards, G.J., and Taylor, C.J. (1998). Active appearance models. In
Computer Vision — ECCV'98, H. Burkhardt and B. Neumann, eds. (Springer Berlin
Heidelberg), pp. 484–498.

72. Chang, L., Egger, B., Vetter, T., and Tsao, D.Y. (2021). Explaining face representation
in the primate brain using different computational models. Curr. Biol. *31*, 2785-2795.e4.
10.1016/j.cub.2021.04.014.

73. Kietzmann, T.C., Swisher,J.D., König, P., and Tong, F. (2012). Prevalence of Selectivity
for Mirror-Symmetric Views of Faces in the Ventral and Dorsal Visual Pathways. J.
Neurosci. *32*, 11763. 10.1523/JNEUROSCI.0126-12.2012.

74. Tai Sing Lee (1996). Image representation using 2D Gabor wavelets. IEEE Trans.
Pattern Anal. Mach. Intell. *18*, 959–971. 10.1109/34.541406.

75. Kay, K.N., Naselaris, T., Prenger, R.J., and Gallant, J.L. (2008). Identifying natural
images from human brain activity. Nature *452*, 352–355. 10.1038/nature06713.

76. Raghunathan, T.E., Rosenthal, R., and Rubin, D.B. (1996). Comparing correlated but
nonoverlapping correlations. Psychol. Methods *1*, 178. 10.1037/1082-989X.1.2.178

77. Fisher, R.A. (1970). Statistical methods for research workers. In Breakthroughs in
statistics: Methodology and distribution (Springer), pp. 66–70. 10.1007/978-1-4612-
4380-9_6

78. Henin, S., Turk-Browne, N.B., Friedman, D., Liu, A., Dugan, P., Flinker, A., Doyle, W.,
Devinsky, O., and Melloni, L. Learning hierarchical sequence representations across
human cortex and hippocampus. Sci. Adv. *7*, eabc4530. 10.1126/sciadv.abc4530.

79. Sherman, B.E., Graves, K.N., Huberdeau, D.M., Quraishi, I.H., Damisah, E.C., and
Turk-Browne, N.B. (2022). Temporal Dynamics of Competition between Statistical
Learning and Episodic Memory in Intracranial Recordings of Human Visual Cortex. J.
Neurosci. *42*, 9053. 10.1523/JNEUROSCI.0708-22.2022.

80. Tallon-Baudry, C., Bertrand, O., Delpuech, C., and Pernier, J. (1996). Stimulus
Specificity of Phase-Locked and Non-Phase-Locked 40 Hz Visual Responses in Human.
J. Neurosci. *16*, 4240. 10.1523/JNEUROSCI.16-13-04240.1996.

81. Widmann, A., Schröger, E., and Maess, B. (2015). Digital filter design for
electrophysiological data – a practical approach. Cut.-Edge EEG Methods *250*, 34–46.
10.1016/j.jneumeth.2014.08.002.

934