# Convergent neural signatures of speech prediction error are a biological marker for spoken word recognition

**Ediz Sohoglu[1], Loes Beckers[2,3,4] and Matthew H. Davis[2]**

1) School of Psychology, University of Sussex, Brighton, UK
2) MRC Cognition and Brain Sciences Unit, Cambridge, UK
3) Department of Otorhinolaryngology, Donders Institute for Brain, Cognition and Behaviour, Radboud University Medical Center, Nijmegen, Netherlands
4) Cochlear Ltd., Mechelen, Belgium

Keywords: Predictive coding, Speech perception, MEG, fMRI

**Acknowledgements:** This research was supported by intermural funding from the Medical Research Council to the Cognition and Brain Sciences Unit (MC_UU_0005/5 and MC_UU_00030/6 to M.H.D.). We thank Sander Van Bree and Clare Cook for assistance with MEG data collection and Steve Eldridge and Karen Kabakulu for assistance with radiography.

**Address correspondence to:**

Ediz Sohoglu (E.Sohoglu@sussex.ac.uk) or Matthew Davis (matt.davis@mrc-cbu.cam.ac.uk)

# Abstract

We used MEG and fMRI to determine how predictions are combined with speech input in superior temporal cortex. We compared neural responses to bisyllabic spoken words in which the first syllable strongly or weakly predicts the form of the second syllable (e.g. "bingo" versus "tango"). We further compared neural responses to the same second syllables when heard in an unfamiliar pseudoword and therefore in a situation in which predictions mismatch with sensory input (e.g. "snigo" and "meago"). Across multiple imaging modalities and analysis approaches (including information-based pattern analysis methods), we show that neural representations of second syllables are suppressed by strong predictions when predictions match sensory input. However, neural representations of the same second syllables show the opposite effect (i.e. enhanced representations following strongly than weakly-predicting syllables) when predictions mismatch with sensory input. Computational simulations show that this interaction between prediction strength and (mis)match is consistent with prediction error but not alternative (sharpened signal) computations. Neural signatures of prediction error are observed early (beginning 200 ms after the onset of the second syllable), localise to early auditory regions (in fMRI, bilateral Heschl's gyrus and STG) and are expressed as changes in low-frequency (theta and alpha) power. Our study therefore provides convergent neural evidence that speech perception is supported by the computation of prediction errors in auditory brain regions. These prediction error computations play a central role in the identification of familiar spoken words and perception of unfamiliar pseudowords.

# Introduction

The information reaching our senses is incomplete and ambiguous such that

perception requires active computations for successful interpretation. Nowhere is this

more evident than with speech perception. To paraphrase Heraclitus, "No listener

ever hears the same speech twice, for it's not the same sounds and they're not the

same listener". No two productions of the same word are ever acoustically identical;

each will be differently realised due to the ubiquitous variability of natural speech

produced by different talkers, and in different contexts. No listener is ever the same

as they will have different expectations or prior knowledge for the speech they will

hear at different times. Consider for example, hearing a word starting with the

syllable "tan". It can be unclear whether this is the start of the word "tangle", "tango"

or another word that starts with the same initial sounds. This ambiguity can be

present even if speech is clearly heard in a quiet background. Yet when listening

during everyday conversation, our subjective impression is that spoken word

recognition is immediate, clear and accurate. How do listeners achieve such reliable

perception despite transient sensory ambiguity?

In answering this question, the notion of Bayesian inference is commonly

invoked. That is, listeners combine sensory evidence with prior knowledge about

which speech sounds they will hear [1]. This proposal is appealing because it can

explain how listeners process speech both rapidly and accurately [2,3]. However,

despite widely held agreement that listeners use prior knowledge during speech

processing, it remains unclear how this is implemented neurally. One possibility is

that neural representations of speech are enhanced by prior knowledge [4]. This has

been termed the sharpened signal account [5–7] because in this proposal, neural

responses to expected stimuli come to resemble a sharpened (i.e. less ambiguous or

less noisy) version of the sensory input. However, it is also the case that expected

speech sounds carry relatively little information. Therefore, an alternative and

potentially more efficient strategy would be to compute prediction errors i.e. the

difference between heard and predicted sounds [8–11]. In this prediction error

account, neural representations are suppressed by prior knowledge and unexpected

(and therefore novel and unexplained) sensory information is prioritised for

processing.

Sharpened signal and prediction error accounts have been difficult to
distinguish experimentally. This is because in both accounts, prior knowledge has a
similar effect on the overall strength of neural responses [5,6]. In the case of the
prediction error account, brain responses tuned to the heard stimulus features are
suppressed when those stimulus features are expected, resulting in an overall
reduction in brain activity. With the sharpened signal account, although brain
responses tuned to the heard stimulus features are enhanced, this is accompanied
by the suppression of responses tuned away from the stimulus input features i.e.
competing interpretations. This suppression of brain responses tuned away from the
input features also leads to overall weaker activity. Therefore, previous findings that
neural responses correlate with moment-by-moment phoneme and word
predictability during story comprehension [12–16] do not provide unambiguous
support for prediction error over sharpened signal accounts. Some accounts have
proposed that sharpened signal and prediction error computations operate in parallel
[8], and localise to different cortical layers [17]. Nonetheless, we focus on contrasting
sharpened signal and prediction error mechanisms since single mechanism
accounts have been proposed in speech perception [4,18,19] and remain to be
distinguished [20].
Multivariate pattern analysis methods that permit measurement of the
information conveyed by neural responses can distinguish between sharpened
signal and prediction error computations. Indeed, previous work using fMRI [18] and
MEG [21] has demonstrated a distinctive neural marker of prediction errors which is
that neural representations of sensory features of speech show an interaction
between signal quality and prior knowledge. This interaction arises because sensory
signals that match strong prior expectations are explained away more effectively as
signal quality increases and hence neural representations are suppressed even as
perceptual outcomes improve. Whereas for sensory signals that follow less
informative prior knowledge, increased signal quality leads to a corresponding
increase in sensory information that remains unexplained. By contrast, under a
sharpened signal account, computational simulations show that neural
representations (like perceptual outcomes) are similarly enhanced by increased
signal quality and prior knowledge [18,21]. Therefore, by experimentally manipulating
both signal quality and prior knowledge, and observing the consequences on
pattern-based neural measures, it is possible to distinguish between accounts.

However, in the aforementioned studies [18,21], listeners heard highly

distorted (and unnatural sounding) spoken words while prior knowledge was

manipulated by presenting matching or nonmatching written words before speech

was heard. This is far removed from real-world conditions in which speech is clearly

heard (non-distorted) and predictions are not derived from external written cues but

from linguistic knowledge e.g. word probabilities vary based on usage frequency and

preceding sentence context. Indeed, some investigators have argued that previously

documented effects of prior knowledge or prediction on language processing are the

consequence of "prediction encouraging" paradigms and fail to generalise to settings

more representative of real-world perception [22].

In the current study, we return to this issue by presenting listeners with clearly

spoken words. We experimentally manipulated the strength and accuracy of

listeners' prior knowledge with the goal of adjudicating between sharpened signal

and prediction error accounts. Here our manipulation of prior knowledge is based on

information intrinsic to the speech signal and arises from listeners' long-term

linguistic knowledge of the sounds of familiar spoken words. We compare neural

responses to bisyllabic spoken words (e.g. "bingo", "tango") in which the first syllable

strongly (in "bingo") or weakly (in "tango") predicts the form of the second syllable

(Figure 1A). In addition, we compare neural responses to the same second syllables

when heard in a pseudoword context (e.g. "snigo", "meago"). Pseudowords, by

definition, are unfamiliar to participants and therefore the second syllable of these

items mismatches with listeners' predictions. This creates a listening situation in

which strong predictions entirely mismatch with sensory input. This cannot be

observed in other experimental situations that forego manipulation of speech content

(e.g. story comprehension) and creates a further opportunity for adjudicating

between sharpened signal and prediction error computations.

We first performed computational simulations (using model architectures and

representations schematised in Figure 1B, C and Figure S6) to show that, as

intended, our experimental manipulations of prediction strength and match/mismatch

result in dissociable effects for sharpened signal and prediction error computations

(Figure 1E). While prediction strength and prediction congruency act to enhance

sharpened signal representations, prediction error computations show an interaction

between prediction strength and congruency. This interaction is driven by a reduction

of prediction errors when strong predictions match the sensory input compared with

weak predictions. When predictions mismatch with sensory input, however, the

opposite occurs with prediction errors slightly increasing with prediction strength. We

then measured neural responses using 204-channel MEG and 3T fMRI in separate

groups of listeners while they performed an incidental (pause detection) listening

task to maintain attention (Figure S1A). Across multiple imaging modalities (MEG,

fMRI), analysis approaches (univariate signal magnitude and multivariate pattern),

and signal domains (time and time-frequency), we provide convergent neural

evidence that speech perception is supported by the computation of prediction errors

in auditory brain regions.

*Figure 1- (A) Our stimuli consisted of multiple sets of bi-syllabic spoken words ("bingo", "bongo", etc. transcribed*

*phonetically as /b I N – g @U/, /b Q N – g @U/) and pseudowords ("bingger", "bongger", etc. transcribed /b I N –*

*g @ r*/, /b Q N – g @ r*/). Purple numbers indicate the strength of predictions for the second syllable of each*

*item, operationalized as p(Syl2|Syl1): the probability of hearing the second syllable, conditioned on the first*

*syllable (the negative log of this probability is equivalent to syllable surprisal; see [23]). Brown numbers indicate the entropy of predictions over all possible syllables (equivalent to the weighted average of syllable surprisal over syllables [23]). Thickness of arrows depicts the overall higher p(Syl2|Syl1) and lower entropy for Strong vs Weak Prediction items. By cross-splicing the syllables in our word items, we created a set of pseudowords in which predictions mismatched with Syl2. The earliest speech segment when the words diverged from the pseudowords (the divergence point) is indicated in bold and always occurred at the second segment of Syl2. (B) Model representations for the example word "bingo", visualized using word and segment clouds with larger text indicating higher probabilities (for a more complete illustration of these computations, see Figure S6). Both sharpened signal and prediction error computations are derived from conditional (posterior) word probabilities, as estimated using Bayes theorem by combining prior word probabilities (frequency of occurrence) and the sensory evidence. Here the sensory evidence is derived from the acoustic similarity between individual speech segments and expresses the degree to which the sensory input matches internal representations of spoken words. Word level representations show posterior probabilities for each word as each segment in the input word is heard prior to the divergence point (only the ten words with the highest probabilities at any one timepoint are shown for illustration purposes). Word posteriors provide predictions for which segment will be heard next (segment predictions shown as green colored phonetic transcriptions). Segment predictions are then combined with the sensory evidence for individual segments ('Input'; shown as brown colored phonetic transcriptions) through sharpened signal (multiplication) or prediction error (subtraction) computations with outcomes depicted on the right as purple and orange segment clouds, respectively (shown only for the divergence point). Note that the segment probabilities in these simulations are not directly related to the stimulus probabilities in panel A as the simulations are based on segment representations and assume some uncertainty in the sensory input (using acoustic similarity). In contrast the stimulus probabilities in Figure 1A, which were used to select the stimuli, are based on syllable representations and assume ideal observer behavior (i.e. no sensory uncertainty). (C) Example model representations for all four experimental conditions at the divergence point for Strong + Match ("bingo"), Weak + Match ("tango"), Strong + Mismatch ("snigo"), Weak + Mismatch ("meago") items. Due to differential predictions (top-line, green), identical speech input (/@U/, second line, brown), elicits different neural representations for sharpened signal (third line, purple) and prediction error (fourth line, orange) representations. (D) Results from sharpened signals and prediction error simulations at the divergence point, used to predict the magnitude of neural responses (univariate signal magnitude analysis). Sharpened signals were summarised as the sum of log activity over segment units while prediction errors were summarised as the sum of absolute activity. Dots indicate the model signals for each individual item (32 items in each condition) with bars and error bars indicating the mean and standard error across the full item set). (E) Results from simulations used to predict neural pattern distances, shown in the same way as panel D except the individual datapoints and bars depict the dissimilarity between model representations for all pairs of items (496 item pairs, i.e. 32x31/2) within each condition (multivariate pattern analysis).*

# Results

## Stimulus properties and behavioural responses

      To manipulate listeners' predictions, we chose a set of 64 bisyllabic words in which the first syllable (Syl1) either strongly or weakly predicts the same second

syllable (Syl2; see Figure 1A which depicts some example items). Here we

operationalise prediction strength as the probability of hearing Syl2, conditioned on

Syl1 (p(Syl2|Syl1); see Methods section for details and refs. [2,11,12,23]). For

example, after hearing the first syllable /b I N/, there is only one potential word

candidate (*bingo*). Therefore, based on their experience of spoken English, listeners

will predict that the second syllable /g @U/ is most likely after hearing /b I N/

(p(Syl2|Syl1) = 1). In contrast, after hearing the first syllable "tan", there are more

potential word candidates (e.g. *tango, tangle, tanker, tankard, tang*) and of these

words, *tango* is less frequently used than the competitors *tangle* and *tang*. As a

result, listeners can only make a weak prediction for /g @U/ after hearing /t { N/

(p(Syl2|Syl1) = .052). Note that p(Syl2|Syl1) can also be expressed as syllable

surprisal [see 23], which is equivalent to the negative log of p(Syl2|Syl1).

We validated our experimental manipulation of prediction strength by asking a

separate group of listeners to perform a free report gating task [see ref 24 and SI

Methods and Results]. This confirmed that listeners were more likely to predict the

second syllables of our Strong items than for Weak items. Further validation of our

experimental manipulation is provided when assessing listeners' memory for the

pseudowords in a cued recall task (see SI Results).

In addition to manipulating the strength of listeners' predictions, we

manipulated whether Syl2 matched or mismatched with listeners' predictions. This

was achieved by cross-splicing Syl1 and Syl2 between words to create a set of

corresponding pseudowords sharing the same set of syllables as the word items. For

real word items, Syl2 always matches predictions, at least to some degree. For

pseudowords, p(Syl2|Syl1) approaches zero. This is by definition, since these Syl1

and Syl2 combinations will never previously have been heard by participants as

English spoken words prior to the experiment. Therefore, for these items, Syl2

entirely mismatches with listeners' predictions.

It is important to note that even though p(Syl2|Syl1) approaches zero for all

Mismatch items, we can still expect a difference in prediction strength between

Strong+Mismatch and Weak+Mismatch items since Strong and Weak items differ not

only in terms of p(Syl2|Syl1), but also in entropy over all possible second syllables

i.e. the overall uncertainty of predictions (see SI Results and Figure S4A). Indeed in

natural speech, conditional probabilities for upcoming speech sounds are negatively

correlated with entropy [12,14,23]. Going back to the example above, after hearing

the first syllable /b I N/, entropy is relatively low because only one word (*bingo*) can

be predicted. In this case, the unexpected second syllable (/g @ r*/) follows a state

of precise predictions (low uncertainty/entropy). For *tango* on the other hand, entropy

is relatively high after hearing the first syllable because predictions are made for

multiple second syllables each arising from different word candidates. Here the

unexpected second syllable follows a state of imprecise predictions (high

uncertainty/entropy). Thus, while we constructed our stimuli based on p(Syl2|Syl1),

our manipulation of prediction strength reflects differences in both p(Syl2|Syl1) and

syllable entropy. Both aspects of predictability may contribute to perceptual and

neural responses in the Match (real word) condition. In the Mismatch condition

however, effects of prediction strength can only reflect differences in entropy (as

explained above).

To assess neural responses to these stimuli, we recorded MEG (N=19) and

fMRI (N=21) data in two separate groups of listeners (Figure S1A). To maintain

listeners' attention, participants were asked to detect brief (200 ms) pauses inserted

between Syl1 and Syl2 in occasional target items. As shown in Figure S1B and S1C,

participants could perform this task quickly and accurately (d-prime higher than 3

and with response times on target-present trials less than 1100 ms).

**Computational simulations**

We performed simulations of sharpened signal and prediction error

computations supporting spoken word and pseudoword recognition (model

architectures and representations schematised in Figure 1B, C with further

illustration of model computations provided in Figure S6). The underlying

mechanisms were  derived from established Bayesian models of spoken word

recognition [e.g. 2] guided by observations of functionally equivalent but neurally

distinct implementations of these. We focus on the timepoint at which the words and

pseudowords in our stimuli diverge (the divergence point; highlighted as bold speech

segments in Figure 1A). This is the time at which our experimental manipulation of

prediction congruency can affect brain responses: in phonemes, this is at the onset

of the second speech segment during Syl2 (98 ms after Syl2 onset on average, with

a standard deviation of 46 ms).

Both sharpened signal and prediction error computations are derived from
conditional (posterior) word probabilities, as estimated using Bayes theorem (for
details, see Methods). As with previous work [e.g. 2,11,12], predictions for the next
speech segment are estimated from the relative frequencies of the words matching
the preceding speech signal, which is appropriate for spoken words heard in
isolation (see Methods for details). Our estimates of the sensory evidence are
derived from the acoustic similarity between individual speech segments and
expresses the degree to which the sensory input matches internal representations of
spoken words [2,25]. Because our stimuli consisted of clear speech recordings, we
simulated conditions in which the sensory evidence was high (i.e. there was minimal
sensory uncertainty; see Methods) but dissociable sharpened signal and prediction
error computations are observed when simulating a range of sensory uncertainty
levels (Figure S3).

To relate these simulations to observed neural responses, we apply signal
magnitude (univariate) and pattern (multivariate) analysis procedures used in our MEG
and fMRI analyses (described in a subsequent section) to simulated representations
of speech segments at the divergence point (results shown in Figure 1D, E). This is
performed for each of the four experimental conditions (the 2-by-2 crossing of
prediction strength and congruency).

The signal magnitude analysis (Figure 1D) focusses on the overall strength
(rather than pattern) of neural responses. For this magnitude analysis of prediction
error representations, we summed model signals (absolute prediction error) over all
possible segment representations (48 in total). However, this approach is ill-suited for
the sharpened signal simulation since here the model representations correspond to
posterior probability distributions and hence all simulated signals are normalized to
sum to one (and will hence never differ between conditions). Therefore, to relate
sharpened signals to univariate neural responses, we summarised model responses
as the normalized sum of log-transformed probabilities over the 48 segment
representations (see Methods). This choice of linking function between the model and
neural responses was motivated by the proposal that neural responses encode log
rather than linear probabilities [26]. We also considered an alternative linking function
based on entropy, which was motivated by the observation that increased uncertainty
in neural responses can be accompanied by an increase in the mean and therefore
overall strength of neural responses [9]. The two linking functions produced equivalent

results (this is unsurprising given that entropy is defined as a weighted sum of log
probabilities). In the following section we report only the results of using the first linking
function (the normalised sum of log-transformed sharpened signals).

This univariate signal magnitude analysis shows a broadly similar pattern for
sharpened signal and prediction error computations. For familiar words (Match items),
both sharpened signal and prediction error simulations show a reduced univariate
response to strongly versus weakly predicted second syllables (Figure 1D). In addition,
univariate responses are overall larger for pseudowords (Mismatch items) versus
words (Match items). Within the Mismatch condition, sharpened signal and prediction
error simulations diverge somewhat with the former showing a reduced response to
strongly versus weakly predicted second syllables and the latter showing a larger
response. For both models, prediction strength and congruency have interactive
effects on univariate responses as the effect of prediction strength is largest for familiar
words (Match items) and reduced for pseudowords (Mismatch items).

The multivariate pattern analysis (Figure 1E), on the other hand, shows clearer
differences between sharpened signal and prediction error computations. This
multivariate analysis quantifies how strongly phonetic content in the speech input is
represented in simulated patterns at the segment level. This is achieved by quantifying
the dissimilarity between model representations (pattern distances) for all pairs of
items within each condition.

The results of this multivariate pattern analysis show that while sharpened
signal representations are enhanced for Match items, prediction strength and
congruency show a cross-over interaction which only occurs for prediction error
representations. Specifically, for signals that match prior predictions (during word
processing), prediction errors decrease in magnitude and pattern distance for stronger
predictions. However, the opposite effect occurs when predictions mismatch with
predictions during pseudoword processing; that is prediction error is increased, and
more informative for syllables that mismatch with stronger predictions. In addition,
prediction errors are overall larger for Mismatch compared with Match items, reflecting
the absence of accurate predictions following the divergence point of the pseudoword
(Mismatch) stimuli.

These simulations, particularly when analyzed using multivariate pattern
analysis, confirm that our experimental manipulations can distinguish between
sharpened signal and prediction error computations. We can therefore evaluate the

extent to which observed brain responses are more consistent with sharpened signal
or prediction error computations.
346

## MEG signal magnitude

As shown in Figure 2A, we assessed MEG responses timelocked to the onset
of Syl2, with respect to a baseline period prior to Syl1 (i.e. speech onset; see
Methods). Note that as a result, the MEG responses at negative latencies shown in
Figure 2A are non-zero (coinciding with sensory input from the Syl1 portion of our
spoken stimuli).
Before assessing the neural timecourse of between-condition differences, we
selected 20 (planar gradiometer) sensors with the strongest responses (signal power
averaged over conditions, separately for each hemisphere and participant). Sensor
selections (i.e. those sensors with the strongest responses) were distributed over
temporal and frontal sites bilaterally (shown inset within Figure 2A), consistent with
neural generators in superior temporal cortex. We then summarised MEG responses
in these "speech responsive" sensors in a univariate fashion by taking the RMS
amplitude across sensor selections for each timepoint. Reported effects are all FWE
(family-wise error) rate corrected for multiple comparisons across timepoints using
cluster permutation methods and a clusterwise threshold of $p < 0.05$.
Following Syl2 onset, prediction strength (Strong vs Weak) and congruency
(Match vs Mismatch) had interactive influences on MEG responses from around 200
to 600 ms (results for left hemisphere sensors are shown in Figure 2A; similar results
are seen for right hemisphere sensors, depicted in Figure S2A). Stronger predictions
resulted in weaker MEG responses but only when speech matched with predictions
(significant timepoints for the interaction between prediction strength and congruency
are indicated as horizontal cyan bars; the simple effect of Strong vs Weak for
Matching items is shown as the grey shaded area between MEG traces). MEG
responses also showed a main effect of prediction congruency with overall larger
responses for Mismatch vs Match items (significant timepoints shown as red
horizontal line). These two patterns – interaction between prediction strength and
congruency, together with a main effect of Mismatch > Match –are broadly consistent
with both sharpened signal and prediction error computations (compare with Figure
1D). Note that although MEG responses do not increase with prediction strength for

mismatching items in this particular analysis (a pattern present only in the prediction

error simulations; see Figure 1D), they do so for other analyses that will be reported

below.

Prior to Syl2 onset, a different pattern of results was observed. Here MEG

responses increased with prediction strength (indicated as horizontal purple bars in

Figure 2A). While the timing of this effect (before Syl2 onset) suggests a neural

signal reflecting predictions rather than prediction errors, we cannot rule out that this

pre-Syl2 effect reflects acoustic differences since the Syl1 portion of Strong items is

longer in duration than for Weak items (see SI Results and Figure S4A). This

duration difference could potentially lead to larger MEG signal when timelocking to

Syl2 onset as neural responses would be shifted later in time for Strong versus

Weak items. Indeed, when timelocking to Syl1 onset to control for this difference in

timing, the increased MEG response for Strong versus Weak items is no longer

apparent (Figure S2C). Note that these or other acoustic confounds can only affect

pre-Syl2 neural responses since our cross-splicing procedure ensures that post-

Syl2, there are no acoustic differences between our four conditions (see Figure 1A

and Figure S4A). Since representations of Syl2 are critical for distinguishing

sharpened signal from prediction error computations (Figure 1E), we subsequently

focus on post-Syl2 effects.

To test whether Syl2 responses are modulated by prediction strength for

single items, we correlated p(Syl2|Syl1) with MEG responses across items

separately for Match and Mismatch items. We show group-averaged Spearman

correlations between prediction strength and MEG responses in left hemisphere

sensors in Figure 2B (right hemisphere correlations shown in Figure S2B).

Consistent with the previous analysis averaged over items (Figure 2A), following

Syl2, there was an interaction between prediction strength and congruency from 168

to 300 ms and from 356 to 460 ms: Stronger predictions that matched with speech

were associated with weaker MEG responses and this correlation differed from that

observed when predictions mismatched (significant timepoints indicated as

horizontal cyan bars). Individually, the correlations within the Matching condition

were significantly negative (indicated as the grey shaded area). Within the

Mismatching condition, correlations were weakly positive and significant in the right

hemisphere at a later latency (Figure S2B, 500-600 ms). This pattern of results is

more consistent with prediction error than with sharpened signal computations as a

positive effect of prediction strength for Mismatch items is only apparent in prediction
error simulations (see Figure 1D). Thus, this analysis demonstrates that the item-
averaged effects depicted previously in Figure 2A extend to single items. That is, the
strength of lexical level predictions modulates neural responses to heard speech with
the magnitude and direction of this effect depending on whether subsequent
segments match or mismatch with predictions. The significant interaction shown in
both factorial and graded analyses is broadly consistent with both sharpened signal
and prediction error accounts although the positive effect of prediction strength for
Mismatch items (observed in graded analysis) favours the prediction error account.

To probe time-frequency correlates of prediction strength and congruency, we
also assessed changes in spectral power in the 2-48 Hz range. This time-frequency
analysis also showed a significant interaction between prediction strength and
congruency in the theta band, with a peak frequency at 3 Hz and a peak latency 120
ms after Syl2 onset (left hemisphere results shown in Figure 2D; a similar pattern
was observed in right hemisphere sensors). Similar to the time-domain analyses
above, stronger predictions resulted in weaker MEG power but only when speech
matched with predictions (see summary in Figure 2C). We also analysed high-
frequency gamma activity (52-90 Hz) but did not observe reliable condition-wise
differences.
430

# Figure 2

431
*Figure 2- MEG univariate signal magnitude results. (A) Traces indicate the RMS of the MEG signal across*
*"speech-responsive" sensors in the left hemisphere, timelocked to the onset of the second syllable (Syl2). Sensor*
*selections are indicated in the topography as the percentage of participants for which a sensor was selected.*
*Thick horizontal bars at the bottom of the graph indicate timepoints when statistical contrasts were significant at a*
*clusterwise threshold of p < .05 FWE corrected (thin horizontal bars show significance at an uncorrected p < .05*
*threshold). Grey shaded area indicates timepoints when the effect of Strong vs Weak in the Match condition was*
*significant at p < .05 (FWE cluster corrected). M = Match. MM = Mismatch. (B) Group-averaged correlations in*
*left hemisphere sensors between p(Syl2|Syl1) and the RMS of the MEG signal. Gray shaded area indicates*
*timepoints when the correlations within Match or Mismatch conditions were significant at p < .05 (FWE cluster*
*corrected). Error bars (transparent area around traces) indicate within-subject errors [28]. (C) Bar graph indicates*
*group means and within-subject standard errors [28] for the four experimental conditions after averaging MEG*
*power over the temporal and frequency extent of the interaction cluster reported in panel D. (D) Image depicts*
*changes in MEG power (between condition differences) across time and frequency in left hemisphere sensors for*
*the interaction (left panel) and simple effect of Weak > Strong in Match trials (right panel) . Nontransparent colors*

## fMRI signal magnitude

In a separate group of listeners, we recorded BOLD functional MRI responses

to the same stimuli, using a sparse fMRI sequence so that speech was presented in

the silent periods between scans (Figure S1A). The procedure (task and number of

stimulus repetitions) was otherwise identical to that used in the MEG experiment.

This allowed us to localize the neural generators of the MEG effects reported above.

Reported effects are all FWE rate corrected using a clusterwise threshold of $p <$

$0.05$.

As shown in Figure 3A, which presents the univariate fMRI results, the main

effect of Mismatch > Match (that was observed following Syl2 onset with MEG)

localized to middle/anterior STG bilaterally (see Table 1 for MNI space coordinates).

The main effect of Strong>Weak (observed with MEG prior to Syl2 onset) localized

to Heschl's gyrus (HG), extending into STG. Despite observing an interaction

between prediction and congruency on MEG responses following Syl2 onset, there

was no equivalent effect in this fMRI analysis. We suggest this is because of the

reduced temporal resolution of fMRI, which makes it more difficult to resolve

individual responses to Syl2 and Syl1.

A potentially more sensitive analysis is to correlate prediction strength i.e.

p(Syl2|Syl1) with the magnitude of the BOLD signal across individual items

(equivalent to the MEG analysis shown in Figure 2B). Employing this approach, fMRI

responses in bilateral HG and middle STG again increased with prediction strength

(positive correlation) for both Match and Mismatch items (shown in Figure 3B with

MNI space coordinates listed in Table 1), demonstrating that the effect depicted

previously for items that differ in averaged prediction strength in Figure 3A is also

observed for single items which encompass a range of prediction strengths. Because

this effect of prediction strength is positive and equally apparent for Match and

Mismatch items, we suggest it corresponds to the pre-Syl2 effect observed in MEG

i.e. reflecting processing prior to the critical Syl2 event. We therefore will not discuss

this effect further because our focus is post-Syl2 processing (as explained above),

which can distinguish different computational accounts.

Importantly, we also observed an interaction between p(Syl2|Syl1) and

prediction congruency in right anterior STG (shown in Figure 3B), revealing a

potential neural generator of the interaction effects previously observed with MEG

after Syl2 onset (Figure 2B and Figure S2B). Although this fMRI effect appears

driven by a positive correlation in the Mismatch condition (rather than a negative

correlation for Match items), the correlation is numerically negative for Match items,

which is consistent with earlier MEG analysis (Figure 2B and Figure S2B). We also

note that like the present fMRI analysis, right-hemisphere MEG sensors show a

positive correlation in the Mismatch condition at later latencies (Figure S2B). As

noted earlier for the univariate MEG analysis, this positive effect of prediction

strength for Mismatch items is only apparent in prediction error simulations (Figure

1D).

# Figure 3

Figure 3 fMRI univariate signal magnitude results. (A) Repeated measures ANOVA showed main effects of prediction strength (left panel) and congruency (right panel). Statistical maps (p < .05 FWE cluster corrected) are shown overlaid onto a template brain in MNI space. White outlines indicate the search volume which included superior and middle temporal regions bilaterally. (B) Statistical maps (p < .05 FWE cluster corrected) for correlations between p(Syl2|Syl1) and BOLD magnitude. In HG extending into middle STG (left panel), correlations are significantly positive and do not differ between Match and Mismatch items (equivalent to a main effect of prediction strength). In anterior STG (right panel), correlations are significantly larger for Mismatch than for Match items. Bar graphs show group-averaged correlations (Fisher-transformed r-values) between conditional probability and BOLD magnitude averaged across voxels in the clusters indicated (arrows). Error bars show within-subject standard errors suitable for statistical comparison between conditions.

## Table 1

| Location | Extent | Z-stat | x | y | z |
|---|---|---|---|---|---|
| **Univariate Strong > Weak** | | | | | |
| Right Heschl's Gyrus | 551 | 5.74 | 54 | -16 | 2 |
|   Right mid-STG | | 4.84 | 64 | -14 | 0 |
|   Right mid-STG | | 4.05 | 66 | -26 | 4 |
| Left mid-STG | 551 | 5.41 | -58 | -22 | 4 |
|   Left Heschl's Gyrus | | 4.55 | -44 | -24 | 2 |
|   Left mid-STG | | 4.55 | -46 | -32 | 4 |
| | | | | | |
| **Univariate Mismatch > Match** | | | | | |
| Left mid-STG | 569 | 6.00 | -64 | -24 | 6 |
|   Left mid-STG | | 5.81 | -60 | -16 | 2 |
|   Left anterior-STG | | 5.62 | -58 | -4 | -4 |
| Right anterior-STG | 205 | 5.25 | 58 | -4 | -4 |
|   Right mid-STG | | 4.51 | 64 | -16 | 0 |
|   Right mid-STG | | 3.54 | 56 | -14 | -2 |
| | | | | | |
| **Univariate Strong+Noise > Weak+Noise** | | | | | |
| Left anterior-STG | 245 | 4.42 | -54 | -12 | 2 |
|   Left Heschl's Gyrus | | 4.21 | -44 | -22 | -2 |
|   Left mid-STG | | 3.31 | -60 | -24 | 2 |
| Right posterior-STG | 56 | 4.25 | 64 | -44 | 10 |
|   Right posterior-MTG | | 3.58 | 60 | -54 | 6 |
| Right mid-STG | 115 | 4.00 | 54 | -20 | 0 |
|   Right Heschl's Gyrus | | 3.30 | 48 | -14 | 0 |
|   Right anterior-STG | | 3.10 | 58 | -12 | -4 |
| | | | | | |
| **Univariate correlations with p(Syl2\|Syl1) Mismatch+Match** | | | | | |
| Left Heschl's Gyrus | 467 | 5.01 | -52 | -22 | 2 |
|   Left Heschl's Gyrus | | 4.85 | -42 | -28 | 4 |
|   Left mid-STG | | 4.62 | -62 | -18 | 6 |
| Right mid-STG | 105 | 4.04 | 66 | -24 | 6 |
|   Right mid-STG | | 3.96 | 64 | -32 | 6 |
|   Right mid-STG | | 3.56 | 54 | -26 | 0 |
| | | | | | |
| **Univariate correlations with p(Syl2\|Syl1) Mismatch>Match** | | | | | |
| Right anterior-STG | 71 | 4.58 | 58 | -2 | -4 |
|   Right anterior-STG | | 3.81 | 50 | -4 | -2 |
|   Right anterior-STG | | 3.59 | 58 | -10 | 2 |
| | | | | | |
| **Multivariate Syl2 phonetic distance** | | | | | |
| Right Heschl's Gyrus | 148 | 4.49 | 56 | -6 | 2 |
| Left Heschl's Gyrus | 146 | 4.01 | -44 | -20 | 0 |

*Table 1- MNI coordinates for fMRI analyses. Also shown are the spatial extent (number of voxels) and peak statistic for each cluster.*

## MEG pattern analysis

The univariate signal magnitude analyses above shows that the magnitude of neural responses in superior temporal regions is modulated by syllable prediction strength in different directions depending on whether heard speech matches or mismatches with predictions. While the direction of these neural effects is in line with the magnitude of prediction error in our computational simulations, as mentioned above, our computational simulations indicate that multivariate pattern analysis more clearly distinguishes sharpened signal and prediction error accounts. Simulations of prediction error computations show that representational patterns show a specific cross-over interaction between prediction strength and congruency (Figure 1E) which is clearly absent for sharpened signal computations.

To examine how predictability modulates neural representational patterns in
our MEG data, we computed the Euclidean distance between sensor patterns (over
the entire 204 array of planar gradiometers) evoked by pairs of items. Taking this
approach, we first asked whether the MEG signal contained phonetic information
about the syllables by correlating neural pattern distances with the phonetic
dissimilarity between the syllables of item pairs (based on a representational
dissimilarity matrix derived from the Levenshtein distance between phonetic
transcriptions for different syllables, as illustrated in Figure 4A for Syl2 and Figure S5
for Syl1). As shown in Figure 4B, MEG patterns correlated with Syl2 phonetic
dissimilarities only after Syl2 onset (reliable effects were observed in two clusters
between 168 and 928 ms post-DP, with the peak effect observed at 332 ms;
indicated by horizontal red bars). In contrast the peak correlation with Syl1 phonetic
dissimilarities was largely confined to periods in which Syl1 was heard, with a cluster
from -200 to +188 ms, and peak effects occurring at -112 ms (indicated by horizontal
beige bars). This confirms that MEG response patterns represent the phonetic
content of the syllables as listeners are hearing them, in line with other, similar
demonstrations [29]. Qualitatively similar albeit weaker results are obtained when
using cross-validated Mahalanobis distances [30].
We next assessed how neural pattern distances were modulated by syllable
predictability by averaging pattern distances over item pairs within each condition
and comparing averaged distances between conditions [for a similar approach
applied to visual processing, see ref 31]. As shown in Figure 4C, following Syl2
onset, prediction strength and congruency interacted to influence MEG pattern
distances: stronger predictions resulted in larger MEG pattern distances but only
when speech mismatched with predictions (simple effect of Strong - Weak
[Mismatch] is shown as shaded grey area in Figure 4C, and the first interaction
cluster peak at 236 ms, is plotted as an inset). This interaction revealed for MEG
patterns after Syl2 onset is more consistent with prediction error than with sharpened
signal computations (compare with Figure 1E).
Complementing the analysis above, we also examined the correlation
between neural pattern distances and Syl2 phonetic dissimilarities, separately for
each condition (i.e. the same dissimilarities indicated in Figure 4A but within
condition). This provides a second measure of neural representations, one that is
potentially more specific to Syl2 phonetic content as opposed to other properties that

could differ between items e.g. acoustic, lexical, semantic etc. However, we did not

find any timepoints showing an interaction between prediction strength and

congruency nor any main effects (Figure S2D). Given that our simulations provide an

apriori hypothesis that the effect of Strong vs Weak predictions should differ for

Match and Mismatch conditions (see Figure 1E), we also tested for simple effects of

Strong versus Weak prediction within each congruency condition. This revealed

greater correlation between MEG pattern and Syl2 phonetic distances for Strong

versus Weak items in the Mismatch condition only. This occurred in two clusters,

from 44 to 116 ms and from 148 to 220 ms. These results remain broadly consistent

with the earlier analysis shown in Figure 4C. While here we did not observe an

interaction between prediction strength and congruency, as before we did observe a

positive effect of prediction strength within the Mismatch condition. This result

favours the prediction error account (see Figure 1E).

Correlating pattern distances with a graded measure of syllable prediction

strength (i.e. p(Syl2|Sy1)) revealed further, convergent evidence for prediction error

computations (Figure 4D). Stronger predictions for upcoming speech sounds during

Syl2 were associated with opposite effects on MEG pattern distances from 360 to

468 ms, depending on prediction congruency (significant timepoints indicated as

horizontal cyan bars). During this time period, correlations between prediction

strength and pattern distances were positive when predictions mismatched with

heard speech (i.e. neural representations were more informative for speech that

mismatched with stronger predictions), and negative when predictions matched

heard speech (i.e. less informative representations for speech that matched stronger

predictions). These findings are as expected for representations that signal

prediction error (Figure 1E right). Individually, correlations within the Matching

condition were not significantly different from zero. But within the Mismatching

condition, correlations were significantly positive from 320 to 544 ms (shown as

shaded grey area in Figure 4D).

We also applied our pattern analysis procedure to MEG sensor-space

patterns after the data was transformed into a time-frequency representation of

signal power (Figure 4E). Here there was again an interaction between prediction

strength and congruency with a peak at 560 ms in the theta band (peak at 4 Hz,

extending to higher alpha frequencies). This interaction was driven by smaller MEG

pattern distances (i.e. less informative neural representations) for Matching syllables

that follow Strong rather than Weak predictions (Figure S2E). Again, this effect is in

line with neural responses that signal prediction errors in heard speech. We also

applied the same pattern analysis approach to high-frequency gamma activity (52-90

Hz) but did not observe condition-wise differences.

*Figure 4 MEG multivariate pattern analysis results. (A) Phonetic dissimilarity matrix expressing the normalized*

*Levenshtein distance between phonetic transcriptions of Syl2 for different item pairs. Right panel inset highlights*

*predicted dissimilarity used in representational analyses. (B) Group-averaged correlation between MEG pattern*

*distances and phonetic dissimilarities for Syl2 (in red) and Syl1 (in beige). Horizontal bars indicate timepoints*

*when correlations were significantly different from zero (thick lines show corrected significance at p < .05*

*clusterwise; thin lines show uncorrected significance at p < .05). Error bars (transparent area around traces)*

*indicate standard error of the mean. (C) Group-averaged MEG pattern distances with larger values indicating*

*more dissimilar MEG response patterns between items. Thick horizontal bars at the bottom of the graph indicate*

*timepoints when statistical contrasts were significant at a clusterwise threshold of p < .05 FWE corrected (thin*

*horizontal bars show significance at an uncorrected p < .05 threshold). Grey shaded area indicates timepoints*

*when there was a significant difference between Strong and Weak items in the Mismatch condition (p < .05 FWE*

*clusterwise corrected). The inset bar plot shows group means for each condition (and within-subject standard*

*errors as before) after averaging over the temporal extent of the cluster for the interaction contrast. (D) Group-*

*averaged correlations between p(Syl2|Syl1) and MEG pattern distances. Grey shaded area indicates timepoints*

*when there was a significant positive correlation for Mismatch items (p < .05 FWE clusterwise corrected). Error*

*bars (transparent area around traces) indicate within-subject errors [28]. (E) Group-averaged MEG pattern*

*distances after transforming the MEG signal into time-frequency power. Image depicts the interaction contrast:*

*(Strong-Weak [Mismatch)]) – (Strong-Weak[Match]). Nontransparent colors indicate significance at p < .05 (FWE*

*cluster corrected) while transparent colors indicate p < .05 (uncorrected). Bar graph indicates group means (and*

*within-subject standard errors) after averaging over the temporal and frequency extent of the interaction cluster*

*(black broken outline on the time-frequency image).*

### fMRI pattern analysis

To localize the neural generators of the MEG pattern analysis effects reported

above, we applied a similar multivariate pattern analysis approach to spatial

searchlights in auditory brain areas in our fMRI data. As with our MEG pattern

analysis, we first asked whether fMRI responses contained phonetic information

about Syl2 by correlating neural pattern distances with the phonetic dissimilarity

between the second syllables of item pairs. As shown in Figure 5A, multivoxel

patterns correlated with Syl2 phonetic dissimilarities in HG bilaterally (see Table 1 for

MNI space locations).

We next proceeded to examine between-condition differences in neural

representations. Rather than directly analysing pattern distances (as with the

equivalent MEG analysis shown in Figure 4C), we opted to analyse a more specific

measure of the correlation between neural patterns and Syl2 phonetic dissimilarities.

This approach is more optimally suited to measure fMRI responses that are specific

to Syl2 as opposed to representing both syllables. This is because while the

temporally precise MEG signal can easily resolve neural responses to Syl1 and Syl2,

this is not the case for fMRI which integrates sensory information over both syllables.

However, by analysing the strength of correlation between fMRI pattern distances

and Syl2 phonetic dissimilarities, we can more specifically examine the neural

representations of Syl2. Within the left and right HG clusters previously shown in

Figure 5A, prediction strength and congruency showed interactive effects on the

correlation between multivoxel pattern distances and Syl2 phonetic dissimilarities

(shown in Figure 5B; $F(1,20) = 10.00$, $p = .005$). This effect did not reliably differ in

magnitude between the two hemispheres (the three-way interaction between

prediction strength, congruency and hemisphere was non-significant: $F(1,20) =$

$0.170$, $p = .684$). Though the interaction effect failed to reach significance in the left

hemisphere ($F(1,20) = 3.304$, $p = .084$), the interaction effect was significant in the

right hemisphere ($F(1,20) = 7.831$, $p = .011$). While tests of simple effects within

each hemisphere were not reliable, the numerical trends are entirely consistent with

previous analyses and in line with computational predictions: increasing prediction

strength resulted in a numerically weaker correlation for a matching Syl2 ($F(1,20) =$

$2.85$, $p = .107$) while the opposite numerical difference (i.e. a stronger correlation for

stronger predictions) was observed for mismatching Syl2 items ($F(1,20) = 2.70$, $p =$

$.116$).

We also examined whether fMRI responses contained phonetic information

about Syl1 by correlating neural pattern distances with the phonetic dissimilarity

between the first syllables of item pairs. However, we did not find significant

correlations (all clusters $p > .6$ uncorrected).

# Figure 5

*Figure 5* fMRI multivariate pattern analysis results. (A) Statistical maps showing voxels in which there was a significant correlation between fMRI pattern distances and phonetic dissimilarities for Syl2 (p < .05 FWE corrected clusterwise). White outline shows search volumes as in Figure 3. (B) Group-averaged correlations (and within-subject standard errors) after averaging over voxels in the left and right hemisphere clusters shown in (A).

## Discussion

Across multiple imaging modalities (MEG, fMRI), analysis approaches (univariate signal magnitude and multivariate pattern), and signal domains (phase-locked, evoked activity and induced, time-frequency MEG responses), we show that neural responses to second syllables in spoken words are modulated by the strength and content of prior knowledge (i.e. predictions for expected speech sounds). We further show that these neural influences of prior knowledge begin around 200 ms after the onset of the second syllable, localise to early auditory regions (in fMRI, bilateral Heschl's gyrus and STG) and are also expressed as changes in low-frequency (theta and alpha) power.

**Neural patterns distinguish prediction error from sharpened signal computations**

In the current study, the critical analyses used multivariate pattern analysis procedures that previous work has shown can unambiguously distinguish between sharpened signal and prediction error accounts [18,21]. By examining the pattern and not just the overall strength of neural signals, responses tuned to the stimulus input features as well as those tuned away from the heard stimulus can be jointly modelled. In this analysis framework, if neural response patterns reflect prediction errors they should contain less information about strongly versus weakly predicted speech sounds (see computational simulations in Figure 1E), and this is indeed what we observed for MEG and fMRI responses to familiar words.

While neural representations of second syllables are suppressed for stronger predictions that match heard speech, neural representations of exactly the same syllables show the opposite modulation for second syllables of pseudowords. That is, when predictions mismatch with sensory input, neural representations are enhanced after more strongly- than more weakly-predicting syllables. Our computational simulations and multivariate analysis confirm that the interaction between prediction strength and match/mismatch is entirely consistent with the operation of prediction error computations [8–11] but cannot be explained by sharpened signal accounts in which representations of speech are enhanced by prior knowledge [5–7]. Our study therefore provides convergent neural evidence – from different imaging modalities and multiple analysis approaches – that speech perception is supported by the computation of prediction error representations in auditory brain regions.

It should be noted that in prediction error accounts, computation of prediction errors is not the end goal of the system [as discussed in ref 21]. Rather, they are used to update – and thereby enhance or sharpen – future predictions. In some formulations of predictive coding [8,17], these sharpened predictions are represented in separate neural populations. However, we saw little evidence of sharpened representations in our study; perhaps because these sharpened predictions reside in deeper cortical layers [17] to which MEG [32] and BOLD [33] signals are less sensitive. It has also been proposed that prediction errors and predictions are communicated via distinct oscillatory channels [34,35], although our time-frequency analysis did not provide support for this (discussed below). In future, methodological advances e.g. in layer-specific imaging [36], or more invasive methods [37] may help

to resolve this issue. Insights may also come from studies that simultaneously probe
multiple levels of processing (e.g. to observe prediction updating in higher-level
semantic stages of processing).

Why are prediction error representations enhanced by prediction strength
when predictions mismatch with speech input i.e. for pseudowords? Because the
combinations of syllables in these items will never previously have been heard by
listeners as English spoken words, the expected probabilities for the second
syllables should always approach zero [in information theory terms, surprisal should
be maximal; see ref 3]. Therefore, if neural representations were only sensitive to
predictions for the heard syllables (and not alternative syllables), we would not
expect any neural differences between Strong+Mismatch and Weak+Mismatch
items. However, our manipulation of prediction strength reflects not only differences
in predictions for the heard second syllables, but also in the uncertainty of
predictions over all possible syllables: In information theory, this uncertainty is
formulated as entropy [23]. Indeed in natural speech, predictions for specific speech
sounds are negatively correlated with entropy [12,14,23].

We suggest our results reflect both aspects of prediction i.e. for the heard
syllables as well as the uncertainty of predictions over all possible syllables. In the
Strong+Mismatch condition, a focal (low entropy) prediction is misaligned with
sensory input. As a result, there is increased information in neural prediction errors
because the sensory signal remains "unexplained". By contrast, weak and more
distributed (lower entropy) predictions will tend to align more with speech input
representations. This illustrated by the pseudoword *tanger*. After hearing the first
syllable /t { N/, predictions are spread weakly over multiple word candidates including
the word *tanker* in which the penultimate sound is shared with *tanger*. This overlap
results in reduced prediction errors in the Weak+Mismatch condition.

Our findings are consistent with neurophysiological findings showing that in
addition to the informativeness of heard speech sounds, brain responses are also
sensitive to the uncertainty of predictions made in parallel for alternative sounds
[12,14,29,38]. Going beyond this previous work however, our current findings
suggest that neural sensitivity to prediction uncertainty reflects the specific neural
computation of prediction error. Prediction uncertainty is a parsimonious explanation
of the prediction strength effect on pseudoword representations. However, it is also
possible that the strong violations of predictions that occur for pseudoword items

may engage additional or qualitatively different mechanisms to those that support

processing of familiar words. Bayesian inference for unfamiliar words is ill-defined

because a pseudoword by definition has never previously been heard and therefore

has a prior probability of zero [2,3]. In this situation, prediction error is maximal [3]

and may function as a signal to indicate that the listener's existing internal model is

no longer applicable [3,39], triggering the encoding of a new word that may later

enter into the lexicon [see below for further discussion and refs 3,40] or perceptual

learning if the speaker systematically produces certain speech sounds with an

unusual pronunciation [41]. By this view, opposite neural effects of prediction

strength during perception of matching and mismatching second syllables arise

because distinct neural processes are engaged during perception of words and

pseudowords.

**Prediction error computations during natural listening**

Our findings replicate and extend the findings of previous studies that

manipulated prior knowledge by presenting matching or nonmatching written words

before highly degraded spoken words [18,21,42]. In this previous work, neural

representations showed interactive influences of prior knowledge and signal quality,

consistent with a prediction error account. We go beyond this previous work by

demonstrating prediction error computations in a more natural listening situation. The

present experiments are more naturalistic in two respects: Firstly, we presented clear

speech rather than the highly degraded (and hence less natural sounding) noise-

vocoded words used previously. Secondly, we used an intrinsic manipulation of prior

knowledge based on listeners' long-term linguistic knowledge of familiar spoken

words rather than an extrinsic manipulation of predictions based on written text. This

demonstration of prediction errors during more natural listening situations is

important because it directly addresses the concern that previous results reflect a

"prediction encouraging" paradigm [22] that would not generalise to other listening

situations. Instead, our findings are consistent with the idea that lexical identification

operates through prediction error computations and that these are integral to

perceptual processing of speech irrespective of the listening situation [3,43–46].

One might argue that our findings fall short of demonstrating prediction error

computation in a fully naturalistic listening situation as our stimuli comprised

individual spoken words as opposed to connected speech. In other work

investigating speech processing during perception of connected speech (e.g.

stories), neurophysiological responses (measured by MEG, EEG or

electrocorticography) are shown to correlate with various measures of time-varying

predictability, including phoneme surprisal [12–15,27], phoneme entropy [14,27] and

lexical entropy [12,15,27]. While these findings clearly demonstrate that speech

processing is strongly modulated by prior knowledge, consistent with the notion that

speech perception is fundamentally a process of Bayesian inference [2], they do not

indicate whether the underlying neural computations involve sharpened signals or

prediction errors. Consider for example, the common observation of reduced

responses to predictable speech sounds. This response reduction is compatible with

either a prediction error account (through the suppression of responses tuned to

input features that are predicted) or a sharpened signal mechanism (through the

suppression of responses tuned away from the input features; for a more detailed

explanation, see Introduction and refs. [5,6,20]). Indeed, this pattern is evident in our

simulations as univariate responses are reduced for strongly versus weakly

predicted second syllables of words for both sharpened signal and prediction error

simulations.

More recently, studies employing connected speech paradigms have shown

that neural representations of speech segments and acoustic features are

themselves modulated by predictability [16,29,47]. These studies use an approach

analogous to the present pattern analysis since they specifically link neural effects of

surprisal and entropy to neural representations of specific segments or acoustic

features. However, previous findings appear inconsistent with respect to sharpened

signal and prediction error accounts since some studies show that neural

representations are enhanced when predictions are strong [47] while others show

the opposite [16] or even effects in both directions at different latencies [29].

These inconsistent results from story listening paradigms therefore suggest

that alternative experimental manipulations of listeners' predictions are needed to

distinguish between accounts. Our pseudoword condition creates a second situation

in which prediction error and sharpened signal computations can be teased apart.

Pseudowords are previously unfamiliar to participants, and hence create a unique

listening situation in which predictions entirely mismatch with sensory input. Under a

sharpened signal account, the pattern of neural representations of speech sounds

forming a pseudoword (as compared with a word) should be suppressed, reflecting

the low prior probability of hearing these speech sounds. In contrast, under a prediction error account, the exact opposite should occur i.e. enhanced representations for pseudowords, particularly following strongly-predicting first syllables. Neural responses to pseudowords are consistent with this latter pattern and hence are likely to reflect prediction error computations. In our signal magnitude analyses, we observed larger MEG and fMRI responses for pseudowords versus words. For pattern analyses, although we did not observe a reliable main effect of prediction congruency, neural representations of speech for pseudoword items were enhanced following strongly- versus weakly-predicting first syllables. Overall, these pseudoword results again favour a prediction error account.

    We have previously argued that larger prediction error responses for pseudowords compared to real words provide a potential signal for novelty detection and pseudoword learning [3,interpreting results from 11,48]. Our demonstration of more informative prediction errors for syllables that mismatch with more strongly-predicting first syllables suggests that such pseudowords might be more readily learned. We note that memory studies using visual stimuli have similarly argued for enhanced learning of face-scene associations that generate larger prediction errors at encoding [49]. Consistent with this proposal, are the present behavioural results from the cued memory recall test conducted after the fMRI scans. This showed that listeners' recall for pseudowords is more accurate for items that strongly mismatched with predictions in the scanner.

**Spatiotemporal and spectral profile of prediction error computations**

    Our results also establish the timing and location of prediction error computations in response to speech. Previous studies using EEG [13], MEG [12–14,29], fMRI [18,50–53] and electrocorticography [15,54] disagree about when and where prediction errors are computed in the cortical hierarchy. Each of these techniques has their strengths but none combines spatiotemporal resolution with wide coverage of the cortex. Perhaps because of this, it remains unclear whether predictive neural computations emerge only once sensory information has been transformed into non-acoustic (e.g. phonetic) representations [12] or whether acoustic representations themselves can support predictive computations [21]. In the present study, we obtained MEG and fMRI responses to the same stimuli, while participants performed the same incidental (pause detection) task to maintain

attention. This feature of our study enabled us to map out prediction error

computations precisely in both time and space.

In our MEG results, effects of prediction strength and congruency occurred

around 200 ms following the onset of the critical second syllable. Note however that

our word and pseudoword stimuli are identical until approximately 100 ms after the

onset of the second syllable (corresponding to the onset of the subsequent

segment). Therefore, relative to when the critical acoustic information became

available to listeners, the interaction between prediction strength and congruency

occurred with a latency of approximately 100 ms. This latency is compatible with a

low-level acoustic locus of prediction error computation but perhaps not early enough

to definitively rule out a higher-level (non-acoustic) locus, if word identification is

supported by rapid (< 50 ms) cortical mechanisms [55].

However, our fMRI results enable more definitive conclusions, since

searchlight pattern results show prediction effects in primary auditory cortex

(Heschl's Gyrus).  This localisation to Heschl's Gyrus is striking as it suggests that

predictive computations for speech can operate even at the lowest levels of the

cortical processing hierarchy, which leaves open the possibility that top-down

predictive influences may even extend subcortically [56]. Future work manipulating

prediction at different linguistic levels (e.g. sublexical, lexical and supralexical) would

be valuable to establish the generality of this finding, and to determine whether these

effects are uniquely or differentially localised to specific cortical regions.

In both signal magnitude and pattern analysis of MEG responses, the

interaction between prediction strength and congruency occurred in low-frequency

neural responses, with a peak in the theta range (3-4 Hz). An influential proposal

claims that bottom-up prediction errors are conveyed by high-frequency (gamma)

activity while top-down predictions are conveyed by low-frequency (alpha/beta)

signals [17,34,57]. This is consistent with the idea that neural representations

integrate sensory information over longer timescales at higher cortical levels (where

top-down predictions are proposed to originate; see [50,51,58–60]). If the current

findings reflect prediction errors as we have argued, then we might have expected

modulation in the gamma range, which we did not observe. Instead, our findings are

consistent with other work suggesting that prediction errors for speech are conveyed

in low-frequency neural signals [14,61]. This does not rule out an additional role for

gamma responses. It may be for example that theta and gamma responses are

coupled [62,63] and that gamma effects are not observed in the present study due to

the generally lower signal-to-noise ratio of MEG responses at higher frequencies

[64].

**878    Integrating computational models and brain responses to reveal the neural**

**879    computations supporting speech processing**

The current study follows previous work that also combined computational

models and neuroimaging to test sharpened signal and prediction error accounts

[18,21]. As has been commented on elsewhere [65], computational models provide

the most reliable way to establish the predictions of a particular theory. This

observation also applies to the goal of distinguishing sharpened signal and prediction

error theories. For example, opposite outcomes are observed in simulated prediction

error representations depending on the level of sensory degradation [see refs 18,21

and also computational simulations in Figure S3 and Methods section]. While this

result is clearly apparent in simulations, it was not previously obvious from verbal

descriptions of prediction error theories. In the current study, we also see opposite

outcomes in simulated prediction errors depending on whether predictions match or

mismatch sensory input during word and pseudoword processing, respectively.

Through computational simulations, we could establish that this is a unique signature

of prediction error representations during perception of words and pseudowords and

furthermore show that this signature is observed in neural responses.

Importantly, our simulations also provide an explanation for why prediction

strength and match/mismatch combine interactively to influence prediction error

representations (see discussion above on why prediction error representations are

enhanced by prediction strength when predictions mismatch speech input).

However, future work is needed to develop a more complete model of prediction

error processing [for examples of other ongoing efforts, see refs 66–68]. For

example, in the present model implementation, predictions for upcoming speech

sounds are subtracted from the input to compute prediction errors but these

segmental predictions are never used to update higher-level lexical predictions.

Rather, lexical-level predictions are computed afresh as each new segment is

presented (by combining word priors and likelihoods using Bayesian inference). A

more complete model would update predictions via prediction errors. It would also

operate on real (i.e. acoustic) speech input or connected speech without explicitly

requiring word onset locations. We note with interest the success of recent
computational models which operate on acoustic speech inputs and are used to
predict neural data [69,70]. We hope that the present results can constrain future
iterations of these models.
912

# Methods

## Participants

40 participants (19 in the MEG experiment, 21 in the fMRI experiment) were
tested after being informed of the study's procedure, which was approved by the
Cambridge Psychology Research Ethics Committee. All were right-handed, native
speakers of English, aged between 18 and 40 years and had no self-reported history
of hearing impairment or neurological disease. The mean age in the MEG
experiment was 25 years (SD = 4.63; 12 female, 7 male) and 23 years in the fMRI
experiment (SD = 3.14; 13 female, 8 male).

## Stimuli

923    Spoken stimuli were 16-bit, 44.1 kHz recordings of a male speaker of
924 southern British English and their duration ranged from 388 to 967 ms (mean = 621,
925 SD = 107). A set of 64 bisyllabic words (Match items) were first selected from the
926 CELEX database [71] based on the probability of the second syllable (Syl2)
927 conditioned on the first syllable (Syl1):
928

$$p(Syl2|Syl1) = \frac{\sum freq(words\ matching\ both\ syllables)}{\sum freq(words\ matching\ first\ syllable)} \qquad Eq.\ 1$$

For this we used syllabified phonetic transcriptions in CELEX such that the
first syllable /t { N/, for example, in words such as *tango* and *tangle* were considered
to match the speech signal since all these words share the same first syllable /t { N/.
However, words such as "tank" were not considered as matching since this word
consists of the single syllable /t { N k/. Words were selected as sets of eight items
(one example item set is shown in Figure 1A). Within a set of eight items, each word
had a unique Syl1 that strongly or weakly predicted one of two Syl2 syllables. By

cross-splicing the first and second syllables of these words, we were able to create a

set of pseudowords (Mismatch items) that contained the same Syl2 syllables as the

real words.

To ensure that Syl2 syllables shared between items were acoustically

identical, all four recorded syllables were combined using audio morphing using

STRAIGHT software [72] implemented in Matlab (The Mathworks Inc). This software

decomposes speech signals into source information and spectral information, and

permits high quality speech resynthesis based on modified versions of these

representations. This enables flexible averaging and interpolation of parameter

values that can generate acoustically intermediate speech tokens [48,for application

see 73]. Exploiting this capability of STRAIGHT, all words and pseudowords sharing

the same Syl2 were constructed to be acoustically identical following Syl1 (by

averaging STRAIGHT parameters across the four instances of the same Syl2

syllable within a set and splicing the resulting syllable onto Syl1). To ensure that all

syllables sounded natural in these contexts, we constrained word selection such that

all Syl2 syllables within a set started with the same speech segment. In this way, we

could cross-splice syllables without conflicting co-articulatory information at the onset

of Syl2. As a result, the point at which words and pseudowords diverged (the

divergence point) occurred not at the onset of Syl2 but one speech segment later

(post divergence point speech segments highlighted as bold in Figure 1A). Additional

stimuli were derived by replacing the Syl1, Syl2, or both syllables, with spectrally and

intensity (RMS) matched noise (data for these stimuli are not reported here). In total

there were eight sets of items and therefore 240 stimuli (32 items in each of the

following conditions: Strong+Match, Weak+Match, Strong+Mismatch,

Weak+Mismatch; 32 each of Strong+Noise, Weak+Noise; 32 of Noise+Syl2; 16 of

Noise+Noise). For analysis of stimulus properties, see supplementary Results.

Before the experiment, participants completed a brief practice session lasting

approximately three minutes that contained examples of all the stimulus types

included (spoken words, pseudowords with and without noise) but using different

items to the main experiment. Stimulus delivery was controlled with Psychtoolbox

[74] scripts in Matlab.

## Procedure

Stimulus presentation and task procedure was nearly identical for MEG and fMRI listeners. On each trial, listeners heard one of the spoken items separated by a stimulus onset asynchrony (SOA) of 2.5 sec (see Figure S1A). For the MEG experiment, this SOA was jittered by adding a random time interval of $\pm100$ ms. For the fMRI experiment, a constant SOA was used, and stimuli were presented at the offset of the scans (sparse imaging sequence). Participants were asked to look at a fixation cross in the centre of the screen and respond as quickly and accurately as possible whenever they heard a brief pause in the speech stimuli. Pauses consisted of an additional 200 ms silence inserted between Syl1 and Syl2. Pilot testing revealed that pause detection was more difficult when one or both syllables were replaced by noise.

Trials were randomly ordered during each of five presentation blocks of 288 trials. Each block consisted of a single presentation of all stimuli plus 'Pause' stimuli. Across all five blocks, the order of 'Pause' and 'No Pause' items was completely randomised; in total there was one 'Pause' item for every six 'No Pause' items, with this ratio constant across stimulus type (Strong+Match, Weak+Match etc.). Participants received feedback on performance (% correct) at the end of each block.

### *Computational simulations*

Both sharpened signal and prediction error computations have the goal of implementing Bayes perceptual inference for spoken words [2,9]:

$$p(Word_i|Evidence) = \frac{p(Word_i) \times p(Evidence|Word_i)}{\sum_{j=1}^{j=n} p(Word_j) \times p(Evidence|Word_j)} \qquad Eq.\ 2$$

This equation computes the conditional (posterior) probability of each word, given their prior probabilities (frequency of occurrence) and the available sensory evidence. We modelled uncertainty in the sensory evidence based on the acoustic similarity between individual speech segments. Acoustic representations were obtained from a large set of 1024 words spoken by the same speaker as for the present stimuli. These stimuli comprised recordings from previous studies [75–77] as well as the 32 Strong Match items and 32 Weak Match items from the current study.

From these stimuli, we computed acoustic energy for individual speech segments

(phonemes): 48 unique segments in total, averaged over 3659 repeated tokens

(median token count = 52). Acoustic energy was expressed as a function of time,

frequency and spectrotemporal modulations [78], as computed by the nsltools

toolbox in Matlab [http://nsl.isr.umd.edu/downloads.html; for details see 21].

Segment onset times were obtained using a forced-alignment algorithm included as

part of BAS software [79; https://clarin.phonetik.uni-

muenchen.de/BASWebServices/interface/WebMAUSGeneral]. Acoustic

representations were vectorized and averaged over multiple productions of the same

segment. We then obtained a between-segment similarity matrix using negative

Euclidean distances and normalized each row of this matrix using the softmax

function (combined with a temperature parameter *T*) such that each row could be

interpreted as segment probabilities:

$$p(Segment_i) = \frac{\exp(-dT)}{\sum_{i=1}^{i=n} \exp(-dT)} \qquad \textit{Eq. 3}$$

where *d* denotes the Euclidean distance. From these segment probabilities,

we could compute the sensory evidence for a word by applying the product rule over

word segments [see 2]. The sensory evidence for an unfolding word will be strong if

its constituent segments match internal representations that are acoustically

dissimilar to other speech sounds in the language. It will also be strong if there are

few word competitors sharing the same speech segments. Given that our stimulus

set consisted of clear speech recordings, a reasonable assumption is that individual

segment probabilities are close to one (indicating high certainty). Nonetheless, even

clear speech segments will be perceived with momentary ambiguities as sub-

phonemic information unfolds over the duration of a segment. In the absence of

human sub-phonemic confusion data [80] for the British accent of the present stimuli,

we scaled acoustic similarities to simulate a range of overall sensory uncertainty

levels by varying the Softmax temperature parameter. The same qualitative patterns

were present over a range of sensory uncertainty levels (Figure S3). The one

exception to this is apparent for simulations with the highest degree of sensory

uncertainty for which prediction error representations in the Match condition are

enhanced relative to simulations with reduced sensory uncertainty (compare the

height of the first bar in each of the bottom row of plots in Figure S3B). The effect of

this is that – under high uncertainty – results show a reverse pattern with enhanced

neural representations for Strong versus Weak items. This is consistent with

previous modelling and experimental data [18,21] and is explained by an increase in

the informativeness of prediction errors that occurs when strong predictions match

noisy or ambiguous sensory input: Even though speech segments are accurately

predicted, their *acoustic form* is not as expected (deviating from clear speech).

Note that our stimuli were selected based on syllable conditional probabilities

p(Syl2|Syl1), which used the syllabified phonetic transcriptions in CELEX. For

consistency, we therefore incorporated the syllable boundaries from CELEX into our

model simulations. We achieved this by adding a separate segment to the model's

inventory of segments, representing the boundary between syllables. Thus, an item

like "bingo" was represented by six segments in total (five speech sounds plus the

boundary between the two component syllables). In Figure 1B and 1C, we omit the

syllable boundary segment for display purposes.

To simulate speech processing as each speech segment in our stimuli was

heard, we used Bayes theorem to compute the posterior probability distribution over

all words in the lexicon. Then to compute predictions for each upcoming speech

segment, we summed posterior probabilities over words sharing the same segment.

These segment predictions were then multiplied by individual segment probabilities

(derived from acoustic similarity as explained above), to simulate the sharpened signal

computation (normalizing to sum to one). For simulating the prediction error

computation, segment predictions were instead subtracted from segment probabilities.

For analysis of the simulated representations, pattern distances were computed as the

Euclidean distance between model signals for pairs of items at the divergence point.

For the signal magnitude analysis, we analysed model representations specifically for

the speech segment that was heard at the divergence point.

### MEG acquisition and analysis

Magnetic fields were recorded with a VectorView system (Elekta Neuromag,

Helsinki, Finland) containing two orthogonal planar gradiometers at each of 102

positions within a hemispheric array. Data were also acquired by magnetometer and

EEG sensors. However, only data from the planar gradiometers were analysed as

these sensors have maximum sensitivity to cortical sources directly under them and

are therefore less sensitive to noise artifacts [81]. To monitor eye and heart activity,

EOG and ECG signals were recorded with bipolar electrodes.

MEG data were processed using the temporal extension of Signal Source Separation [82] in Maxfilter software to suppress noise sources, compensate for motion, and reconstruct any bad sensors. Also using MaxFilter, the data were transformed to a common coordinate frame for each participant separately (to compensate for changes in head position between blocks). Subsequent processing was done in SPM12 (Wellcome Trust Centre for Neuroimaging, London, UK), FieldTrip (Donders Institute for Brain, Cognition and Behaviour, Radboud University Nijmegen, the Netherlands) and The Decoding Toolbox [83] implemented in Matlab.

MEG data were downsampled to 250 Hz and ICA used to remove eye and heart artefacts (based on an automatic procedure correlating the component time-series with EOG and ECG signals). When epoching, we retained only "no pause" trials. MEG recordings were epoched from -1700 ms to 2000 ms relative to the onset of Syl2 and epochs with large amplitude signals were discarded (time- and channel-averaged power larger than 2 standard deviations from the condition-specific mean for signal magnitude analysis; power larger than 3 standard deviations from the pooled mean for pattern analysis). For signal magnitude (evoked response) analyses only, the data were baseline-corrected from -750 to -500 ms relative to Syl2 onset; this corresponds to the silence period before speech onset (since the duration of Syl1 ranged from 130 to 479 ms; see Figure S4C for distribution of Syl1 duration).

For time-frequency analysis, we computed the power between 2 and 48 Hz (in 1 Hz steps) by convolving the data from each trial with Morlet wavelets of 7 cycles. To analyse high frequency activity (52-90 Hz), we used multi-taper estimation ($\pm 10$ Hz smoothing, 200 ms time-windows with a step size of 20 ms). We analysed differences in power attributable to our experimental manipulations without baseline normalization. For time-domain analyses, the data were additionally low-pass filtered below 30 Hz prior to trial averaging. Note that in the case of signal magnitude analyses, MEG responses reflect the average of 160 trials before outlier removal (5 repetitions × 32 items per stimulus type) while for pattern analyses, MEG responses reflect the average of 5 repetitions (since here we analyze item-specific responses). Subsequent analysis was based on the period immediately before and after Syl2 onset (-200 to 1000 ms).

For signal magnitude (evoked response) analysis, the MEG data across the sensor array were summarized as the root mean square (RMS) over the 20 sensors

with the largest evoked response (separately in each participant and hemisphere). Essentially the same results are obtained when selecting 10 or 40 sensors. The same sensor selections used for the signal magnitude (evoked response) analysis were also used when analysing time-frequency power. For pattern analyses, neural pattern distances were computed by taking the Euclidean distance between sensor patterns (over the entire 204 sensor-array) evoked by each pair of items in the relevant stimulus set. To assess whether MEG responses reflected the phonetic information about the syllables, neural pattern distances were correlated with the phonetic dissimilarities between the syllables of item pairs using Fisher-transformed Spearman's correlations. To compute the phonetic dissimilarities we used the Levenshtein distance between the phonetic transcriptions for each syllable, normalized by the maximum number of segments within the two syllables being compared; shown in Figure 4A for Syl2 and Figure S5 for Syl1 [see 77 for a similar method applied to scoring phonetic responses]. To maximize statistical power for this particular analysis, correlations were computed both across- and within-condition (see Figure 4A). As shown in Figure 4A, we also excluded dissimilarity of item pairs such as "cargar" and "cougo" since similar but opposite prediction errors are evoked during Syl2 of these items. For example, for "cargar", listeners predict /g @U/ but hear /g @ r*/. For "cougo", listeners predict /g @ r*/ but hear /g @U/. The pattern of prediction error in these two cases is identical, albeit opposite in polarity. Given uncertainty on how the polarity of prediction errors is encoded in neural responses [84], we exclude these pseudoword item pairs from pattern analysis of our neural data and model simulations. We also exclude the corresponding word item pairs (e.g. "cougar" and "cargo"; shown as NaNs in Figure 4A).

When correlating syllable conditional probabilities with MEG responses (either magnitude-based or pattern-based measures), we also used Fisher-transformed Spearman's correlations. For pattern analysis, in which the dependent measures reflect pattern distances for pairs of items, we averaged syllable conditional probabilities for the items in each pair of words (after log transformation).

For both signal magnitude (RMS signals, time-frequency power or Spearman correlations) and pattern analyses (pattern distances or Spearman correlations), group-level one-sample t-tests were performed for each timepoint (and frequency bin when relevant) while controlling the family-wise error (FWE) rate using a non-parametric cluster-based permutation procedure based on 5000 iterations [85].

1130 These tests were performed on contrasts of the data, testing for the main effects and
1131 interactions in our experimental design, as well as any simple effects. Reported
1132 effects were obtained by using a cluster defining height threshold of p < .05 with a
1133 cluster t-sum threshold of p < .05 (FWE corrected), unless otherwise stated.

## fMRI acquisition and analysis

Imaging data were collected on a Siemens 3 Tesla Prisma MRI scanner
(http://www.siemens.com). A total of 291 echo planar imaging (EPI) volumes were
acquired in each of 5 scanning runs, using a 32-channel head coil and a multiband
sparse imaging sequence (TR = 2.50 sec; TA = 1.135 sec; TE = 30 ms; 48 slices
covering the whole brain; flip angle = 78 deg; in-plane resolution = 3 × 3 mm; matrix
size = 64 × 64; echo spacing = 0.5 ms; inter-slice gap = 25%). After the third run,
field maps were acquired (short TE = 10 ms; long TE = 12.46 ms). The experimental
session commenced with the acquisition of a high-resolution T1-weighted structural
MRI scan (TR = 2250 ms; TE = 2.99 ms; flip angle = 9°; 1 mm isotropic resolution;
matrix size: 256 × 240 × 192 mm; GRAPPA acceleration factor PE = 2; Reference
lines PE = 24).

fMRI pre-processing was performed in SPM12. After discarding the first four
volumes to allow for magnetic saturation effects, the remaining images were
realigned and unwarped to the first volume to correct for movement of participants
during scanning. Also at the unwarping stage, the acquired field maps were used to
correct for geometric distortions in the EPI due to magnetic field variations.
Realigned images were co-registered to the mean functional image and then
subjected to statistical analysis. For signal magnitude analysis, prior to further
processing, images were also normalized to the Montreal Neurological Institute
(MNI) template image using the parameters from the segmentation of the structural
image (resampled resolution: 2 × 2 × 2 mm) and smoothed with a Gaussian kernel of
6 mm full-width at half-maximum. For pattern analysis, normalization and smoothing
were performed only after computing pattern distances.

Statistical analysis was based on the general linear model (GLM) of each
participant's fMRI time series, using a 1/128 second highpass filter and AR1
correction for auto-correlation. The design matrix comprised the auditory stimulus

events (onset of the spoken words), each modeled as a stick (delta) function and

convolved with the canonical haemodynamic response function specified in SPM

software. For signal magnitude analysis, separate columns were specified for each

of the stimulus types in addition to a column for button presses (replicated for each

of the five experimental blocks). For pattern analysis, the design matrix was identical

but separate columns were specified for each individual item.

Pattern analysis was performed using searchlight analysis [86] as

implemented in the Decoding toolbox, using spheres with a radius of 8 mm and

constrained to voxels within the whole-brain mask generated by SPM during model

estimation. Pattern distances were computed using the cross-validated Mahalanobis

distance [30]. This 'Crossnobis' distance is equivalent to the (cross-validated)

Euclidean distance, normalized by the noise covariance between voxels (estimated

from the GLM residuals). Cross-validation ensures that the expected pattern

distance is zero if two voxel patterns are not statistically different from each other,

making it a readily interpretable distance measure. Note that because of this cross-

validation, the Crossnobis distance can sometimes be negative if it's true value is

close to zero in the presence of noise. The Crossnobis distance has been

demonstrated to be a more reliable and accurate metric for characterizing multivoxel

patterns than the correlation or Euclidean distance [30]. To assess whether fMRI

responses reflected the phonetic information about Syl2, neural pattern distances

were Spearman correlated with the phonetic dissimilarities between Syl2 portions of

item pairs using the same Levenshtein distance measure as the MEG analysis

(shown in Figure 4A).

For both signal magnitude (contrast images from first-level models or

Spearman correlations) and pattern analyses (Spearman correlations), group-level

one-sample t-tests were performed for each voxel within a mask covering superior

and middle temporal regions (shown in Figure 3A). Inference was conducted

parametrically, controlling the family-wise error (FWE) rate using random field theory.

Reported effects were obtained by using a cluster defining height threshold of $p <$

.001 with a cluster extent threshold of $p < .05$ (FWE corrected), unless otherwise

stated.

1192

## *Data availability statement*

1193

1194
1195 Stimuli, data and analysis scripts will be made available on OSF upon
1196 publication of this manuscript.
1197

## *Code availability statement*

1198

1199
1200 Matlab code for the computational simulations will be made available on OSF
1201 upon publication of this manuscript.
1202
1203

# References

1204

1.    Norris D, McQueen JM, Cutler A. Prediction, Bayesian inference and feedback in
speech recognition. Language, Cognition and Neuroscience. 2015;3798: 1–15.
doi:10.1080/23273798.2015.1081703

2.    Norris D, McQueen JM. Shortlist B: a Bayesian model of continuous speech
recognition. Psychological review. 2008;115: 357–95. doi:10.1037/0033-
295X.115.2.357

3.    Davis MH, Sohoglu E. Three functions of prediction error for Bayesian inference in
speech perception. Cog Neuro. MIT Press; 2020. pp. 177–192.

4.    McClelland JL, Elman JL. The TRACE model of speech perception. Cognitive
Psychology. 1986;18: 1–86. doi:10.1016/0010-0285(86)90015-0

5.    Lange FP de, Heilbron M, Kok P. How Do Expectations Shape Perception? Trends in
Cognitive Sciences. 2018;22: 764–779. doi:10.1016/j.tics.2018.06.002

6.    Murray SO, Schrater P, Kersten D. Perceptual grouping and the interactions between
visual cortical areas. Neural networks : the official journal of the International Neural
Network Society. 2004;17: 695–705. doi:10.1016/j.neunet.2004.03.010

7.    Aitken F, Turner G, Kok P. Prior Expectations of Motion Direction Modulate Early
Sensory Processing. The Journal of Neuroscience. 2020;40: 6389–6397.
doi:10.1523/JNEUROSCI.0537-20.2020

8.    Rao RP, Ballard DH. Predictive coding in the visual cortex: a functional interpretation
of some extra-classical receptive-field effects. Nature neuroscience. 1999;2: 79–87.
doi:10.1038/4580

9.    Aitchison L, Lengyel M. With or without you: predictive coding and Bayesian inference
in the brain. Current Opinion in Neurobiology. 2017;46: 219–227.
doi:10.1016/j.conb.2017.08.010

10.   Friston K. A theory of cortical responses. Philosophical transactions of the Royal
Society of London Series B, Biological sciences. 2005;360: 815–36.
doi:10.1098/rstb.2005.1622

11.   Gagnepain P, Henson RN, Davis MH. Temporal Predictive Codes for Spoken Words in
Auditory Cortex. Current biology : CB. 2012;22: 1–7. doi:10.1016/j.cub.2012.02.015

12.   Brodbeck C, Hong LE, Simon JZ. Rapid Transformation from Auditory to Linguistic
Representations of Continuous Speech. Current biology : CB. 2018;28: 3976-3983.e5.
doi:10.1016/j.cub.2018.10.042

13.   Heilbron M, Armeni K, Schoffelen J-M, Hagoort P, de Lange FP. A hierarchy of
linguistic predictions during natural language comprehension. Proc Natl Acad Sci USA.
2022;119: e2201968119. doi:10.1073/pnas.2201968119

14.  Donhauser PW, Baillet S. Two Distinct Neural Timescales. Neuron. 2020; 1–9.
doi:10.1016/j.neuron.2019.10.019

15.  Keshishian M, Akkol S, Herrero J, Bickel S, Mehta AD, Mesgarani N. Joint, distributed
and hierarchically organized encoding of linguistic features in the human auditory
cortex. Nat Hum Behav. 2023; 1–14. doi:10.1038/s41562-023-01520-0

16.  Tezcan F, Weissbart H, Martin AE. A tradeoff between acoustic and linguistic feature
encoding in spoken language comprehension. Peelle JE, King AJ, editors. eLife.
2023;12: e82386. doi:10.7554/eLife.82386

17.  Bastos AMM, Usrey WMM, Adams RAA, Mangun GRR, Fries P, Friston KJJ.
Canonical Microcircuits for Predictive Coding. Neuron. 2012;76: 695–711.
doi:10.1016/j.neuron.2012.10.038

18.  Blank H, Davis MH. Prediction Errors but Not Sharpened Signals Simulate Multivoxel
fMRI Patterns during Speech Perception. PLoS biology. 2016;14: e1002577.
doi:10.1371/journal.pbio.1002577

19.  de Lange FP, Schmitt L-M, Heilbron M. Reconstructing the predictive architecture of
the mind and brain. Trends in Cognitive Sciences. 2022;26: 1018–1019.
doi:10.1016/j.tics.2022.08.007

20.  Luthra S, Li MYC, You H, Brodbeck C, Magnuson JS. Does signal reduction imply
predictive coding in models of spoken word recognition? Psychonomic bulletin &
review. 2021. doi:10.3758/s13423-021-01924-x

21.  Sohoglu E, Davis MH. Rapid computations of spectrotemporal prediction error support
perception of degraded speech. eLife. 2020;9: 1–25. doi:10.7554/eLife.58077

22.  Huettig F, Mani N. Is prediction necessary to understand language? Probably not.
Language, Cognition and Neuroscience. 2016;31: 19–31.
doi:10.1080/23273798.2015.1072223

23.  Gwilliams L, Davis M. Extracting language content from speech sounds: An
information theoretic approach. Springer Handbook of Auditory Research. Springer;
2022. pp. 113–139.

24.  Grosjean F. Spoken word recognition processes and the gating paradigm. Perception &
Psychophysics. 1980;28: 267–283. doi:10.3758/BF03204386

25.  Luce PA, Pisoni DB. Recognizing spoken words: the neighborhood activation model.
Ear and hearing. 1998;19: 1–36. doi:10.1097/00003446-199802000-00001

26.  Pouget A, Beck JM, Ma WJ, Latham PE. Probabilistic brains: knowns and unknowns.
Nature Neuroscience. 2013;16: 1170–1178. doi:10.1038/nn.3495

27.  Brodbeck C, Bhattasali S, Cruz Heredia AA, Resnik P, Simon JZ, Lau E. Parallel
processing in speech perception with local and global representations of linguistic
context. eLife. 2022;11: e72056. doi:10.7554/eLife.72056

28.   Loftus GR, Masson MEJ. Using confidence intervals in within-subject designs.
Psychonomic Bulletin & Review. 1994;1: 476–490. doi:10.3758/BF03210951

29.   Gwilliams L, King J-R, Marantz A, Poeppel D. Neural dynamics of phoneme sequences
reveal position-invariant code for content and order. Nat Commun. 2022;13: 6606.
doi:10.1038/s41467-022-34326-1

30.   Walther A, Nili H, Ejaz N, Alink A, Kriegeskorte N, Diedrichsen J. Reliability of
dissimilarity measures for multi-voxel pattern analysis. NeuroImage. 2016;137: 188–
200. doi:10.1016/j.neuroimage.2015.12.012

31.   Hebart MN, Bankson BB, Harel A, Baker CI, Cichy RM. The representational dynamics
of task and object processing in humans. eLife. 2018;7: 1–21. doi:10.7554/eLife.32816

32.   Hämäläinen M, Hari R, Ilmoniemi RJ, Knuutila J, Lounasmaa OV.
Magnetoencephalography—theory, instrumentation, and applications to noninvasive
studies of the working human brain. Reviews of Modern Physics. 1993;65: 413–497.
doi:10.1103/RevModPhys.65.413

33.   Lankinen K, Ahlfors SP, Mamashli F, Blazejewska AI, Raij T, Turpin T, et al. Cortical
depth profiles of auditory and visual 7 T functional MRI responses in human superior
temporal areas. Human Brain Mapping. 2023;44: 362–372. doi:10.1002/hbm.26046

34.   Arnal LH, Wyart V, Giraud A-L. Transitions in neural oscillations reflect prediction
errors generated in audiovisual speech. Nature neuroscience. 2011;14: 797–801.
doi:10.1038/nn.2810

35.   Bastos AM, Lundqvist M, Waite AS, Kopell N, Miller EK. Layer and rhythm specificity
for predictive routing. Proceedings of the National Academy of Sciences of the United
States of America. 2020;117: 31459–31469. doi:10.1073/pnas.2014868117

36.   Kok P, Bains LJ, van Mourik T, Norris DG, de Lange FP. Selective Activation of the
Deep Layers of the Human Primary Visual Cortex by Top-Down Feedback. Current
Biology. 2016;26: 371–376. doi:10.1016/j.cub.2015.12.038

37.   Leonard MK, Gwilliams L, Sellers KK, Chung JE, Xu D, Mischler G, et al. Large-scale
single-neuron speech sound encoding across the depth of human cortex. Nature. 2023
[cited 1 Feb 2024]. doi:10.1038/s41586-023-06839-2

38.   Zhuang J, Tyler LK, Randall B, Stamatakis EA, Marslen-Wilson WD. Optimally
efficient neural systems for processing spoken language. Cerebral Cortex. 2014;24:
908–918. doi:10.1093/cercor/bhs366

39.   Yu AJ, Dayan P. Uncertainty, neuromodulation, and attention. Neuron. 2005;46: 681–
92. doi:10.1016/j.neuron.2005.04.026

40.   Davis MH, Gaskell MG. A complementary systems account of word learning: neural
and behavioural evidence. Philosophical transactions of the Royal Society of London
Series B, Biological sciences. 2009;364: 3773–800. doi:10.1098/rstb.2009.0111

41.  Blanco-Elorrieta E, Gwilliams L, Marantz A, Pylkkänen L. Adaptation to mis-
pronounced speech: evidence for a prefrontal-cortex repair mechanism. Sci Rep.
2021;11: 97. doi:10.1038/s41598-020-79640-0

42.  Blank H, Spangenberg M, Davis MH. Neural Prediction Errors Distinguish Perception
and Misperception of Speech. The Journal of neuroscience : the official journal of the
Society for Neuroscience. 2018;38: 6076–6089. doi:10.1523/jneurosci.3258-17.2018

43.  Clark A. Whatever next? Predictive brains, situated agents, and the future of cognitive
science. Behavioral and Brain Sciences. 2013;36: 1–24.
doi:10.1017/S0140525X12000477

44.  Barascud N, Pearce MT, Griffiths TD, Friston KJ, Chait M. Brain responses in humans
reveal ideal observer-like sensitivity to complex acoustic patterns. Proceedings of the
National Academy of Sciences of the United States of America. 2016;113: E616-25.
doi:10.1073/pnas.1508523113

45.  Friston K. Does predictive coding have a future? Nature Neuroscience. 2018;21: 1019–
1021. doi:10.1038/s41593-018-0200-7

46.  Kuperberg GR, Jaeger TF. What do we mean by prediction in language comprehension?
Language Cognition & Neuroscience. 2016;31: 32–59.
doi:10.1080/23273798.2015.1102299

47.  Broderick MP, Anderson AJ, Lalor EC. Semantic Context Enhances the Early Auditory
Encoding of Natural Speech. The Journal of Neuroscience. 2019;39: 7564–7575.
doi:10.1523/JNEUROSCI.0584-19.2019

48.  Wang YC, Sohoglu E, Gilbert RA, Henson RN, Davis MH. Predictive Neural
Computations Support Spoken Word Recognition: Evidence from MEG and Competitor
Priming. The Journal of neuroscience : the official journal of the Society for
Neuroscience. 2021;41: 6919–6932. doi:10.1523/JNEUROSCI.1685-20.2021

49.  Greve A, Cooper E, Kaula A, Anderson MC, Henson R. Does prediction error drive
one-shot declarative learning? Journal of Memory and Language. 2017;94: 149–165.
doi:10.1016/j.jml.2016.11.001

50.  Schmitt L-M, Erb J, Tune S, Rysop AU, Hartwigsen G, Obleser J. Predicting speech
from a cortical hierarchy of event-based time scales. Science Advances. 2021;7:
2020.12.19.423616. doi:10.1126/sciadv.abi6070

51.  Caucheteux C, Gramfort A, King J-R. Evidence of a predictive coding hierarchy in the
human brain listening to speech. Nat Hum Behav. 2023; 1–12. doi:10.1038/s41562-022-
01516-2

52.  Schrimpf M, Blank IA, Tuckute G, Kauf C, Hosseini EA, Kanwisher N, et al. The
neural architecture of language: Integrative modeling converges on predictive
processing. Proc Natl Acad Sci USA. 2021;118: e2105646118.
doi:10.1073/pnas.2105646118

53.   Frank SL, Willems RM. Word predictability and semantic similarity show distinct
patterns of brain activity during language comprehension. Language, Cognition and
Neuroscience. 2017;32: 1192–1203. doi:10.1080/23273798.2017.1323109

54.   Goldstein A, Zada Z, Buchnik E, Schain M, Price A, Aubrey B, et al. Shared
computational principles for language processing in humans and deep language models.
Nat Neurosci. 2022;25: 369–380. doi:10.1038/s41593-022-01026-4

55.   MacGregor LJ, Pulvermüller F, van Casteren M, Shtyrov Y. Ultra-rapid access to words
in the brain. Nature communications. 2012;3: 711. doi:10.1038/ncomms1715

56.   Tabas A, Mihai G, Kiebel S, Trampel R, von Kriegstein K. Abstract rules drive
adaptation in the subcortical sensory pathway. Shinn-Cunningham BG, Griffiths TD,
Malmierca MS, editors. eLife. 2020;9: e64501. doi:10.7554/eLife.64501

57.   Sedley W, Gander PE, Kumar S, Kovach CK, Oya H, Kawasaki H, et al. Neural
signatures of perceptual inference. eLife. 2016;5: 1–13. doi:10.7554/eLife.11476

58.   Lerner Y, Honey CJ, Silbert LJ, Hasson U. Topographic mapping of a hierarchy of
temporal receptive windows using a narrated story. The Journal of neuroscience : the
official journal of the Society for Neuroscience. 2011;31: 2906–15.
doi:10.1523/JNEUROSCI.3684-10.2011

59.   Honey CJ, Thesen T, Donner TH, Silbert LJ, Carlson CE, Devinsky O, et al. Slow
cortical dynamics and the accumulation of information over long timescales. Neuron.
2012;76: 423–34. doi:10.1016/j.neuron.2012.08.011

60.   Norman-Haignere SV, Long LK, Devinsky O, Doyle W, Irobunda I, Merricks EM, et al.
Multiscale temporal integration organizes hierarchical computation in human auditory
cortex. Nature Human Behaviour. 2022. doi:10.1038/s41562-021-01261-y

61.   Di Liberto GM, Crosse MJ, Lalor EC. Cortical Measures of Phoneme-Level Speech
Encoding Correlate with the Perceived Clarity of Natural Speech. eNeuro. 2018;5:
ENEURO.0084-18.2018. doi:10.1523/ENEURO.0084-18.2018

62.   Giraud A-L, Poeppel D. Cortical oscillations and speech processing: emerging
computational principles and operations. Nature Neuroscience. 2012 [cited 19 Mar
2012]. doi:10.1038/nn.3063

63.   Canolty RT, Edwards E, Dalal SS, Soltani M, Nagarajan SS, Berger MS, et al. High
gamma power is phase-locked to theta oscillations in human neocortex. Science (New
York, NY). 2006;313: 1626–8. doi:10.1126/science.1128115

64.   Sedley W, Teki S, Kumar S, Overath T, Barnes GR, Griffiths TD. Gamma band pitch
responses in human auditory cortex measured with magnetoencephalography.
Neuroimage. 2012;59: 1904–1911. doi:10.1016/j.neuroimage.2011.08.098

65.   Norris D. How do Computational Models Help us Develop Better Theories? Twenty-
first century psycholinguistics: Four cornerstones. Mahwah,  NJ,  US: Lawrence
Erlbaum Associates Publishers; 2005. pp. 331–346.

66.   Nour Eddine S, Brothers T, Wang L, Spratling M, Kuperberg GR. A predictive coding
1391           model of the N400. Cognition. 2024;246: 105755. doi:10.1016/j.cognition.2024.105755

1392    67.   Hovsepyan S, Olasagasti I, Giraud A. Combining predictive coding and neural
1393           oscillations enables online syllable recognition in natural speech. Nature
1394           Communications. 2020;11: 3117. doi:10.1038/s41467-020-16956-5

1395    68.   Yildiz IB, von Kriegstein K, Kiebel SJ. From Birdsong to Human Speech Recognition:
1396           Bayesian Inference on a Hierarchy of Nonlinear Dynamical Systems. PLoS
1397           Computational Biology. 2013;9. doi:10.1371/journal.pcbi.1003219

1398    69.   Magnuson JS, You H, Luthra S, Li M, Nam H, Escabí M, et al. EARSHOT: A Minimal
1399           Neural Network Model of Incremental Human Speech Recognition. Cognitive science.
1400           2020;44: e12823. doi:10.1111/cogs.12823

1401    70.   Kell AJE, Yamins DLK, Shook EN, Norman-haignere SV, Mcdermott JH, Kell AJE, et
1402           al. A Task-Optimized Neural Network Replicates Human Auditory Behavior, Predicts
1403           Brain Responses, and Reveals a Cortical Processing Hierarchy. Neuron. 2018;98: 1–15.
1404           doi:10.1016/j.neuron.2018.03.044

1405    71.   Baayen RH, Piepenbrock R, Van Rijn H. The CELEX lexical database (CD-ROM).
1406           Philadelphia Linguistics Data Consortium University of Pennsylvania. 1993.

1407    72.   Kawahara H. STRAIGHT, exploitation of the other aspect of VOCODER: Perceptually
1408           isomorphic decomposition of speech sounds. Acoust Sci & Tech. 2006;27: 349–353.
1409           doi:10.1250/ast.27.349

1410    73.   Rogers JC, Davis MH. Inferior Frontal Cortex Contributions to the Recognition of
1411           Spoken Words and Their Constituent Speech Sounds. Journal of cognitive neuroscience.
1412           2017;25: 1–18. doi:10.1162/jocn_a_01096

1413    74.   Brainard DH. The Psychophysics Toolbox. Spatial Vision. 1997;10: 433–436.
1414           doi:10.1163/156856897X00357

1415    75.   Sohoglu E, Peelle JE, Carlyon RP, Davis MH. Predictive Top-Down Integration of Prior
1416           Knowledge during Speech Perception. The Journal of neuroscience : the official journal
1417           of the Society for Neuroscience. 2012;32: 8443–8453. doi:10.1523/JNEUROSCI.5069-
1418           11.2012

1419    76.   Sohoglu E, Peelle JE, Carlyon RP, Davis MH. Top-down influences of written text on
1420           perceived clarity of degraded speech. Journal of Experimental Psychology: Human
1421           Perception and Performance. 2014;40: 186–199. doi:10.1037/a0033206

1422    77.   Sohoglu E, Davis MH. Perceptual learning of degraded speech by minimizing prediction
1423           error. Proceedings of the National Academy of Sciences. 2016;113: E1747–E1756.
1424           doi:10.1073/pnas.1523266113

1425    78.   Chi T, Ru P, Shamma SA. Multiresolution spectrotemporal analysis of complex sounds.
1426           The Journal of the Acoustical Society of America. 2005;118: 887–906.
1427           doi:10.1121/1.1945807

1428    79.   Kisler T, Reichel U, Schiel F. Multilingual processing of speech via web services.
1429           Computer Speech & Language. 2017;45: 326–347. doi:10.1016/j.csl.2017.01.005

1430    80.   Warner N, McQueen JM, Cutler A. Tracking perception of the sounds of English. The
1431           Journal of the Acoustical Society of America. 2014;135: 2995–3006.
1432           doi:10.1121/1.4870486

1433    81.   Hämäläinen MS. Functional localization based on measurements with a whole-head
1434           magnetometer system. Brain topography. 1995;7: 283–9. doi:10.1007/BF01195254

1435    82.   Taulu S, Simola J, Kajola M. Applications of the signal space separation method. IEEE
1436           Transactions on Signal Processing. 2005;53: 3359–3372. doi:10.1109/TSP.2005.853302

1437    83.   Hebart MN, Görgen K, Haynes J-D. The Decoding Toolbox (TDT): a versatile software
1438           package for multivariate analyses of functional imaging data. Frontiers in
1439           Neuroinformatics. 2015;8. Available:
1440           https://www.frontiersin.org/articles/10.3389/fninf.2014.00088

1441    84.   Keller GB, Mrsic-Flogel TD. Predictive Processing: A Canonical Cortical Computation.
1442           Neuron. 2018;100: 424–435. doi:10.1016/j.neuron.2018.10.003

1443    85.   Maris E, Oostenveld R. Nonparametric statistical testing of EEG- and MEG-data.
1444           Journal of neuroscience methods. 2007;164: 177–90.
1445           doi:10.1016/j.jneumeth.2007.03.024

1446    86.   Kriegeskorte N, Goebel R, Bandettini P. Information-based functional brain mapping.
1447           Proceedings of the National Academy of Sciences of the United States of America.
1448           2006;103: 3863–3868. doi:10.1073/pnas.0600244103

1449

1450

# SI Methods

## Cued recall task

After the fMRI scans, listeners completed a cued recall test assessing memory for the pseudowords. Data were not available for this task for four participants either because of technical issues or because the participant did not understand the task instructions. The final sample size consisted of 17 participants for this test. We cued participants with the first syllable of each pseudoword item by presenting the same stimuli as the MEG and fMRI experiments but replacing the second syllables with spectrally and intensity (RMS) matched noise. We refer to these as Strong+Noise and Weak+Noise items. Participants were told that the nonsense (pseudo) words were "partly hidden by noise" and were asked to recall the nonsense word by saying it aloud. Responses were scored for accuracy based on counting the percentage of trials in which participants generated the correct Syl2 used in the Mismatch items. The order of stimulus presentation was randomised for each participant.

## Web-based gating study

Our measure of p(Syl2|Syl1) is derived from frequency counts and phonological transcriptions in the CELEX database. To validate this measure, we conducted a web-based gating task using the Strong+Noise and Weak+Noise stimuli (each item presented once in a random order). Participants were British English speakers (N=110, recruited via https://www.prolific.co and non-overlapping with participants in the MEG/fMRI studies), aged 18 to 40 years and self-reported as having no hearing difficulties or language-related disorders. They were told that they would hear real English words "partly hidden by noise" and asked to report the identity of the word by typing it out. For each item, we calculated the proportion of participants reporting the source word i.e. the matching word prior to replacing Syl2 with noise.

# SI Results

## Stimulus properties

A summary of stimulus properties is shown in Figure S4A and S4B. Based on frequency counts, and phonological transcriptions in CELEX, the average conditional probability of syllable 2 given syllable 1 (p(Syl2|Syl1)) for Strong prediction items was 0.574 (SD = 0.332) while for Weak items it was 0.019 (SD = 0.029). Strong items were also associated with smaller syllable entropy (calculated as the negative sum of log-transformed p(Syl2|Syl1) over all possible syllables; mean = 1.34, SD = 1.11) than Weak items (mean = 2.99, SD = 0.99). Strong and Weak items had similar log frequencies (Strong: mean = 4.90, SD = 1.56; Weak: mean = 3.89, SD = 1.62) although the difference was significant (independent samples $t(62) = 2.53$, p = 0.014). However, all reported MEG and fMRI effects involving correlations with conditional probabilities (Figures 2B, 3B and 4D) survive when controlling for differences in word frequency (using partial Spearman correlations). Moreover, p(Syl2|Syl1) is the strongest predictor of listeners' behaviour in a free report gating task (conducted in a separate group of listeners; see Figure S1E and SI Methods for more details), as compared with either word frequency or syllable entropy (see web-based gating study results reported below). Thus, we are confident that our effects of prediction strength after Syl2 onset stem from differences in conditional probability rather than differences in word frequency.

For the fMRI experiment (Figure S4A), the Syl1 portion of Strong items was lower in acoustic intensity ($t(62) = -2.14$, p = 0.036) and longer in duration ($t(62) = 3.47$, p < .001) than Weak items. The RMS intensity for Syl1 and Syl2 was separately normalised over items for the MEG experiment (which was conducted after the fMRI experiment) and did not differ between conditions (Figure S4B). All other stimulus properties did not differ between the fMRI and MEG experiments. Importantly, there were no acoustic differences between conditions for the Syl2 portion of our stimuli which were acoustically identical in all conditions. Neural responses to Syl2 are the key focus of this study since it is representations of Syl2 that distinguish sharpened signal and prediction error accounts.

## Cued recall task

After the fMRI scans, we assessed listeners' memory for the pseudowords in a cued recall task (see SI Methods). Recall accuracy (percentage correct) was around 10% on average over participants, with most participants achieving 5% or higher (see Figure S1D). These data indicate the recall task was difficult. Importantly however, they also suggest that participants could perform the task to some degree and hence were attentively processing the pseudoword stimuli. Recall accuracy was better for pseudowords formed with Strongly- versus Weakly-predicting first syllables (one-tailed $t(16) = 1.768$, $p = .048$), consistent with the proposal that items evoking strong prediction errors are learned more readily than items evoking weak prediction errors [see Discussion].

## Web-based gating study

Listeners' reports of the identity of spoken words with second syllables replaced by noise (Strong+Noise and Weak+Noise stimuli, see SI Methods) were combined over participants (N=110) to generate the proportion of responses that correspond to the target words. For these items, p(Syl2|Syl1) was strongly correlated with the proportion of listeners' responses matching the target word ($r = .636$, $p < .001$, N = 64 items; see Figure S1E) and this effect remains significant when other lexical predictors (entropy and word frequency) are factored out ($r = 0.341$, $p < 0.01$, N = 64 items). This finding shows that more strongly predicted second syllables were more likely to be reported by listeners than weakly predicted syllables when replaced with noise. Moreover, while both entropy and word frequency also correlate with gating responses ($r = -0.513$, $p < .001$ N = 64 items; and $r = 0.259$, $p < .05$, N = 64 items), neither of these factors predict gating responses when p(Syl2|Syl1) is factored out (both $p > .05$, see Figure S1E). These findings confirm that our experimental manipulation of prediction strength was successful, and that measures of prediction strength based on conditional probability computed from lexical statistics are an accurate predictor of listening behaviour.

# Supplementary figures

## Figure S1

*1549   Figure S1- Method and behavioural results. (A) Participants listened to the spoken stimuli and detected a brief*

*1550   pause that appeared occasionally between Syl1 and Syl2 by responding with a button press. MEG and fMRI*

*1551   were recorded in two separate groups of participants (N = sample size for each group). Two example trials are*

*1552   indicated with stimulus and scan timings. TA = time of fMRI scan acquisition. TR = repetition time for fMRI scans.*

*1553   SOA = Stimulus Onset Asynchrony. s = seconds. ms = milliseconds. (B) Bar graph showing group-averaged d-*

*1554   primes and response times (target-present trials) for the pause detection task in the MEG experiment (with*

*1555   within-subject standard errors). Individual lines represent individual participants. (C) Same as panel B but for*

*1556   pause detection responses in the fMRI experiment. (D) Percentage correct accuracy of pseudoword memory in a*

*1557   cued recall test conducted after the fMRI scans. For this recall test, participants were presented with the stimuli*

*1558   after the second syllables were replaced with noise ('Strong+Noise' and 'Weak+Noise' items) and asked to recall*

*1559   previously heard pseudowords that started with the same first syllable. (E) Scatter plots of the proportion of*

*1560   participants identifying target items in a web-based gating pre-test study plotted against lexical statistics for*

*1561   p(Syl2|Syl1), entropy and word frequency (each circle representing one of the 64 word items used in the*

*experiment). Correlation coefficients (and p values) for each relationship are shown above each graph with*

*further partial correlations reported within brackets.*

# Figure S2

*Figure S2- Supplementary MEG analyses. (A) Same as Figure 2A but for right hemisphere sensors. (B) Same as*

*Figure 2B but for right hemisphere sensors. (C) Same as Figure 2A for MEG signal timelocked to Syl1 onset. (D)*

*Group-averaged correlation between MEG pattern distances and Syl2 phonetic dissimilarities in each condition.*

*Thin horizontal bars at the bottom of the graph indicate timepoints when main effects and the interaction were*

*significant at an uncorrected p < .05 threshold (no timepoints survived correction for multiple comparisons). Grey*

*shaded areas indicate the two clusters during which there was a significant difference between Strong and Weak*

1572   *items in the Mismatch condition (p < .05 FWE clusterwise corrected). The inset bar plot shows group means for*

1573   *each condition (and within-subject standard errors as before) after averaging over the temporal extent of the first*

1574   *cluster (peaking at 76 ms). (E) Pattern analysis showing simple effect of Weak > Strong (Match) on MEG pattern*

1575   *distances.*

1576

# Figure S3

1577

1578   *Figure S3- Same as Figure 1D and 1E but showing the impact of varying sensory uncertainty levels (using the*

1579   *Softmax Temperature parameter) for Sharpened Signal (upper panels) simulations and Prediction Error (lower*

# Figure S4

1589 *Figure S4- (A) Stimulus properties for the fMRI experiment (means and standard errors of the mean). (B) The*
1590 *RMS intensity of the stimuli for the MEG experiment, which were slightly different to those for the fMRI*
1591 *experiment (all other stimulus properties did not differ) (C) Histograms showing the distribution of item durations*
1592 *in our stimuli as well as Syl1 and Syl2 durations.*
1593

# Figure S5

1595 *Figure S5- Same as Figure 4A. Phonetic dissimilarity matrix expressing the normalized Levenshtein distance*
1596 *between phonetic transcriptions of Syl1 in different items.*

# Figure S6

**A** Compute word posteriors (input segments: b I N – g)

*Figure S6- Illustration of each step in simulations for the example sequence of segments /b I N – g/ (i.e. after the first segment in the second syllable of "bingo"). A) The first step in the simulations is to compute the posterior probability of each word (shown in green for three selected words), by multiplying word priors (frequency of usage as shown, each of which is divided by the total word count for the corpus, 18585424) with word likelihoods (shown in brown) and normalising the result to sum to one. We compute word likelihoods as the product of segment probabilities, which are based on the acoustic similarity between segments. Selected segment probabilities are shown in the probability matrix in top right of figure. Each row in this matrix can be interpreted as the sensory evidence for different segments given an input segment (with yellow indicating strong evidence and blue indicating weak evidence). For example, given the input segment /b/, the sensory evidence for /b/ is high (P=0.8894), but also to some degree, there is evidence for acoustically similar segments /g/ (P=0.0442) and /f/ (P=0.0062). The non-zero probability of segment confusions is sufficient to make the likelihood of other, similar-sounding words non-zero (e.g. "finger"). B) In the second step, we compute predictions for each upcoming speech segment by summing posterior probabilities over words sharing the same next segment. Here we show posterior probabilities for two example segments /@U/ in "bingo", "bongo", etc, and /@/ in "finger", "bungalow", etc. Probabilities are similarly computed for each possible subsequent segment. C) In the final step, segment predictions (green distribution) are multiplied by individual segment probabilities (brown distribution) and normalized to sum to one to simulate the sharpened signal computation. To simulate the prediction error computation, segment predictions are instead subtracted from segment probabilities. The resulting distributions show how representations of expected segments (/@U/) are enhanced in sharpened signal computations (purple),and suppressed in prediction error computations (orange).*

# Figure 1

**A** Example items
(in total, 64 Match 64 Mismatch)

Second Syllable
Match    Mismatch

**Strong Prediction**

bingo b I N —0——1→ g @U / g @ r*
bongo b Q N —0.95——.625→ g @U / g@ r*    post deviation point
snigger s n I —2.63——.371→ g @ r* / g @U
swagger s w { —1.36——.493→ g @ r* / g @U

**Weak Prediction**

tango t { N —1.14——.052→ g @U / g @ r*
cargo k A: —4.39——.032→ g @U / g @ r*
meagre m i: —2.64——.014→ g @ r* / g @U
cougar k u: —2.49——.014→ g @ r* / g @U

entropy    p(Syl2|Syl1)

**B** Words ⇅ Segments

Input × Prediction = Sharpened Signal

Input − Prediction = Prediction Error

**C**
Strong+M "bingo" | Weak+M "tango" | Strong+MM "snigo" | Weak+MM "meago"

Prediction
Input
Sharpened Signal
Prediction Error

**D** Model results (univariate)

Sharpened Signal — Signal magnitude (at divergence point)

Prediction Error

Strong+M   Weak+M   Strong+MM   Weak+MM

**E** Model results (multivariate)

Sharpened Signal — Pattern distance (at divergence point)

Prediction Error

Strong+M   Weak+M   Strong+MM   Weak+MM

# Figure 2

**A** Left hemisphere sensors

Strong+M
Weak+M
Strong+MM
Weak+MM

RMS

% participants

Strong-Weak
Interaction
MM-M

Syl2 onset
Time (ms)

**B** Left hemisphere sensors correlation with p(Syl2|Syl1)

M
MM

Fisher r

M+MM
MM-M

Time (ms)

**C** Peak: 3 Hz, 120 ms

Power

M
MM

Strong
Weak

**D** Left hemisphere sensors

Interaction
Weak>Strong (M)

Freq (Hz)

Change in power

Time (ms)

# Figure 3

**A**

Strong>Weak

MM>M

F-stat
30

x=-58    z=4          x=-58    z=-4

**B**

Mismatch + Match > 0

Correlation with p(Syl2|Syl1)

Mismatch > Match

t-stat
5.5

3.6

x=-52    z=4          x=58    z=-4

Left HG/mid-STG

Right mid-STG

Right anterior STG

Fisher r

Match  Mismatch     Match  Mismatch     Match  Mismatch

# Figure 4

**A** Testing for Syl2 representation

**B** Correlation with Syl RDMs

**C** Strong+M, Weak+M, Strong+MM, Weak+MM

**D** Correlation with prob (Syl2|Syl1)

**E** Interaction

# Figure 5

**A** Regions that represent Syl2

x=55

Search volume

L   R

z=2

t-stat
5.5
3.6

**B**

p = .084

p = .011

Fisher r

0.03
0.02
0.01
0

Match   Mismatch

Strong
Weak

Match   Mismatch

Interaction (both hemispheres): p = .005

# Figure S1

# Figure S2

# Figure S3

A. Model signal magnitude at divergence point

B. Model pattern distance at divergence point

# Figure S4

# Figure S5

## Testing for Syl1 representation

# Figure S6

## A  Compute word posteriors (input segments: b I N – g)

**Word posteriors**
normalized (prior X likelihood)

**Word priors**
from word frequency

**Word likelihoods**
from segment probabilities

**Segment probabilities**
from acoustic similarity

| | bingo | | bingo | | | | P(b\|b) (I\|I) (N\|N) (g\|g) |
|---|---|---|---|---|---|---|---|
| | **0.7270** | ∝ | **113** | X | **0.5080** = Π | | 0.8894  0.7496  0.9619  0.7921 |

| | bongo | | bongo | | | | P(b\|b) (Q\|I) (N\|N) (g\|g) |
|---|---|---|---|---|---|---|---|
| | **0.0023** | ∝ | **36** | X | **0.0181** = Π | | 0.8894  0.0267  0.9619  0.7921 |

| | finger | | finger | | | | P(f\|b) (I\|I) (N\|N) (g\|g) |
|---|---|---|---|---|---|---|---|
| | **0.1037** | ∝ | **22** | X | **0.0036** = Π | | 0.0062  0.7496  0.9619  0.7921 |

...          ...          ...

38713 words total          38713 words total          38713 words total

| | b | g | N | f | I | Q |
|---|---|---|---|---|---|---|
| **b** | 0.8894 | 0.0442 | 0.0000 | 0.0062 | 0.0000 | 0.0000 |
| **g** | 0.0393 | 0.7921 | 0.0000 | 0.0105 | 0.0000 | 0.0000 |
| **N** | 0.0000 | 0.0000 | 0.9619 | 0.0000 | 0.0001 | 0.0003 |
| **f** | 0.0052 | 0.0098 | 0.0000 | 0.7408 | 0.0000 | 0.0000 |
| **I** | 0.0000 | 0.0000 | 0.0001 | 0.0000 | 0.7496 | 0.0267 |
| **Q** | 0.0000 | 0.0000 | 0.0002 | 0.0000 | 0.0272 | 0.7624 |

...
48 segments total

Low probablity ■■■ High probablity

## B  Sum predictions for words sharing next segment

| **Word posteriors** | | **Word posteriors** | |
|---|---|---|---|
| bIN-g**@U** | 0.7270 | fIN-g**@**r* | 0.1037 |
| bQN-g**@U** | 0.0023 | bVN-g**@**-l@U | 0.0452 |
| dIN-g**@U** | 0.0001 | fIN-g**@**-neIl | 0.0057 |
| kQN-g**@U** | 0.0001 | fIN-g**@**-tIp | 0.0043 |
| m{N-g**@U** | 0.0000 | fIN-g**@**-prInt | 0.0035 |
| · · · | | · · · | |

$$\sum_{j=1}^{j=n} = P(@U) = 0.7296$$

$$\sum_{j=1}^{j=n} = P(@) = 0.1746$$

## C  Combine segment predictions and input

Input    X    Prediction    =    Sharpened Signal

Input    −    Prediction    =    Prediction Error

# Table 1

| Location | Extent | Z-stat | x | y | z |
|---|---|---|---|---|---|
| **Univariate Strong > Weak** | | | | | |
| Right Heschl's Gyrus | 551 | 5.74 | 54 | -16 | 2 |
|   Right mid-STG | | 4.84 | 64 | -14 | 0 |
|   Right mid-STG | | 4.05 | 66 | -26 | 4 |
| Left mid-STG | 551 | 5.41 | -58 | -22 | 4 |
|   Left Heschl's Gyrus | | 4.55 | -44 | -24 | 2 |
|   Left mid-STG | | 4.55 | -46 | -32 | 4 |
| | | | | | |
| **Univariate Mismatch > Match** | | | | | |
| Left mid-STG | 569 | 6.00 | -64 | -24 | 6 |
|   Left mid-STG | | 5.81 | -60 | -16 | 2 |
|   Left anterior-STG | | 5.62 | -58 | -4 | -4 |
| Right anterior-STG | 205 | 5.25 | 58 | -4 | -4 |
|   Right mid-STG | | 4.51 | 64 | -16 | 0 |
|   Right mid-STG | | 3.54 | 56 | -14 | -2 |
| | | | | | |
| **Univariate Strong+Noise > Weak+Noise** | | | | | |
| Left anterior-STG | 245 | 4.42 | -54 | -12 | 2 |
|   Left Heschl's Gyrus | | 4.21 | -44 | -22 | -2 |
|   Left mid-STG | | 3.31 | -60 | -24 | 2 |
| Right posterior-STG | 56 | 4.25 | 64 | -44 | 10 |
|   Right posterior-MTG | | 3.58 | 60 | -54 | 6 |
| Right mid-STG | 115 | 4.00 | 54 | -20 | 0 |
|   Right Heschl's Gyrus | | 3.30 | 48 | -14 | 0 |
|   Right anterior-STG | | 3.10 | 58 | -12 | -4 |
| | | | | | |
| **Univariate correlations with p(Syl2\|Syl1) Mismatch+Match** | | | | | |
| Left Heschl's Gyrus | 467 | 5.01 | -52 | -22 | 2 |
|   Left Heschl's Gyrus | | 4.85 | -42 | -28 | 4 |
|   Left mid-STG | | 4.62 | -62 | -18 | 6 |
| Right mid-STG | 105 | 4.04 | 66 | -24 | 6 |
|   Right mid-STG | | 3.96 | 64 | -32 | 6 |
|   Right mid-STG | | 3.56 | 54 | -26 | 0 |
| | | | | | |
| **Univariate correlations with p(Syl2\|Syl1) Mismatch>Match** | | | | | |
| Right anterior-STG | 71 | 4.58 | 58 | -2 | -4 |
|   Right anterior-STG | | 3.81 | 50 | -4 | -2 |
|   Right anterior-STG | | 3.59 | 58 | -10 | 2 |
| | | | | | |
| **Multivariate Syl2 phonetic distance** | | | | | |
| Right Heschl's Gyrus | 148 | 4.49 | 56 | -6 | 2 |
| Left Heschl's Gyrus | 146 | 4.01 | -44 | -20 | 0 |