Sensorimotor mechanisms selective to numerosity: evidence from individual differences

Giovanni Anobile[1*], Irene Petrizzo[1], Daisy Paiardini[1], David C. Burr[1,3] & Guido Marco Cicchini[2]

[1]Department of Neuroscience, Psychology, Pharmacology and Child Health, University of Florence, Florence, Italy

[2]Institute of Neuroscience, CNR, via Moruzzi, 1, 56124, Pisa, Italy

[3]School of Psychology, University of Sydney, Camperdown NSW, Australia

* Correspondence:

Giovanni Anobile; giovanni.anobile@unifi.it

Keywords: Visuomotor numerosity, Numerosity perception, Motor system, Approximate number system

Abstract

We have previously shown that after few seconds of adaptation by finger-tapping, the perceived numerosity of spatial arrays and temporal sequences of visual objects displayed near the tapping region is increased or decreased, implying the existence of a *sensorimotor numerosity system* (Anobile et al., 2016). To date, this mechanism has been evidenced only by adaptation. Here we extend our finding by leveraging on a well-established covariance technique, used to unveil and characterize "channels" for basic visual features such as colour, motion, contrast, and spatial frequency. Participants were required to press rapidly a key a specific number of times, without counting. We then correlated the precision of reproduction for various target number presses between participants. The results showed high positive correlations for nearby target numbers, scaling down with numerical distance, implying tuning selectivity. Factor analysis identified two factors, one for low and the other for higher numbers. Principal component analysis revealed two bell-shaped covariance channels, peaking at different numerical values. Two control experiments ruled out the role of non-numerical strategies based on tapping frequency and response duration. These results reinforce our previous reports based on adaptation, and further suggest the existence of at

least two sensorimotor number channels responsible for translating symbolic numbers into

action sequences.

Introduction

Humans share with many animals a primitive non-verbal number system encoding the

number of objects in space and events in time (Dehaene, 2011). The capacity to estimate

number rapidly but imperfectly is thought to be a primary perceptual attribute, often termed

the *number sense* (Burr & Ross, 2008). The past few decades have accumulated much

evidence for the existence of the number sense. Many studies show that the sense of number

is truly general, transcending space and time, as well as modality and format (Arrighi et al.,

2014; Burr et al., 2018; Togoli et al., 2021). More recently, numerosity has been shown to

interact strongly with action, leading to the idea of a *sensorimotor number system*,

incorporating action, and its interaction with sensory systems (Anobile et al., 2016, 2021).

Both physiological and psychophysical studies support the existence of a sensorimotor

number system. Adaptation studies provide strong evidence: participants first tap

continuously with their index finger for a few seconds, either rapidly or slowly, then estimate

the numerosity of a dot array presented near the adapted region: adaptation to fast tapping

causes underestimation and slow tapping overestimation (Anobile et al., 2016, 2020;

Maldonado Moscoso et al., 2020). Motor adaptation induces similar effects on sequential

visual and auditory stimuli (Anobile et al., 2016; Togoli et al., 2020), consistent with the

existence of a generalized system linking motor and sensory signals to encode numerosity

(Anobile et al., 2021; Burr et al., 2021).

Electrophysiological studies in primates also point to the existence of a specific neural

substrate for counting a small set of actions. In a seminal paper Sawamura at al. (2002)

trained monkeys to repetitively make five identical movements, then switch to a different

movement, in a cyclical fashion: neurons in the posterior parietal cortex showed selectivity to

the number of self-generated actions, whatever the action. Kirshhock and Nieder (2022)

trained crows to peck a specific number of times (1 to 5). Neurons in the telencephalon were

shown to be tuned to the impending number of self-generated actions, during the phase

between the disappearance of the target to the onset of motor reproduction. The activity of

these neurons predicted the behavioural performance and was independent of both stimulus

format (dots or digits) and of the temporal characteristics of the motor responses. Each tuning

function peaked at a given preferred numerosity, with activity scaling down with numerical

distance. Overall, these cells in the crow brain could constitute the neural substrate

subserving the transformation of sensory inputs into a given quantity of numerical actions,

possibly a similar mechanism to that driving the motor number adaptation effects in humans

(Anobile et al., 2016).

Although motor adaptation has revealed a clear link between action and numerosity

perception, this is the only technique used so far to investigate the interaction in humans. The

aim of the current study is therefore to expand and generalize our previous findings, using a

different psychophysical technique that exploits individual differences in reproduction

precision (Peterzell & Kennedy, 2016). This technique has been widely used to reveal visual

channels for motion (Morrone et al., 1999), spatial frequency (Reynaud & Hess, 2017;

Simpson & McFadden, 2005), contrast sensitivity (Peterzell et al., 1995; Peterzell & Teller,

1996), color (Peterzell et al., 2000; Peterzell & Teller, 2000) and duration (Rammsayer &

Troche, 2014).

The rationale behind this technique is that performance measures of stimuli detected by the

same mechanism should correlate more between individuals than stimuli detected by

different mechanisms. Figure 1 illustrates the technique by simulation of results in a

numerosity reproduction task if the task were mediated for 1, 2 or 4 numerosity-selective

channels. It assumes intrinsic variability in reproduction precision across participants,

perturbed by additive random noise. The top row simulates results if reproduction of all

numerosities were governed by a single mechanism, rather than a range of numerosity-tuned

mechanisms. The correlation matrix for all pairs of stimuli (Figure 1B) shows no systematic

pattern, only random variations in correlations due to the general noisiness of the channel.

Figure 1C plots the average correlation plotted as a function of numerosity ratio, showing no

dependence on number ratio. Increasing or decreasing the added noise will change the

average correlation, but not create any dependency on numerosity ratio. However, if there

exist mechanisms selective for numerosity, the results are quite different. Assuming just two

mechanisms tuned to low and high numbers (Figure 1D) yields a correlation matrix with

higher correlations between similar numbers (near the diagonal) than dissimilar numbers.

This leads to the clear dependency on numerosity ratio shown in Figure 1E. Similarly, for a

range of numerosity-selective mechanisms like the four shown in Figure 1G, there will be a

strong dependency on numerical distance (Figure 1I). The cases of two and four channels are

difficult to distinguish if the amount of added noise is free to vary. Techniques such as cluster

 analysis and principal component analysis (PCA) can be also applied to study further the

 tuning of the channels.

Figure 1. Simulation of behaviour with 1, 2 or 4 channels mediating numerosity judgments. A: 1-channel model shown as a flat tuning function. (B) Predicted correlation matrix between all pairs of numerosities. There is no systematic variability, only random variations induced by the noise. (C) Average correlation as function of numerical ratio of dot pairs, showing no dependency. (D) 2-channel model centred at numerosities 8 and 32, with full bandwidth of 1.45 octaves. (E) Correlation matrix, showing higher correlations near the identity line. (F) Correlation as function of numerical ratio, showing a systematic falloff with numerical ratio. (G-I) Same as D-F for a 4-channel model with channels equally spaced in the range between 8 and 32 with full bandwidth of 1.10 octaves.

Here we applied the interindividual covariance technique to study sensorimotor tuning in humans, using a number matching task similar to that used by Kirschhock & Nieder (2022). We measured the precision with which 30 participants could press a key a given number of times (8-32) without counting, and then correlated performance across all pairs of numbers

(like the simulation of Figure 1). The results clearly demonstrate the existence of
sensorimotor mechanisms converting symbolic numbers into actions, with correlations
decreasing with numerical distance, like Figures 1F & I.

Methods

Participants

An a priori power analysis for a correlation test (r) with a medium effect size of $r^2 = 0.5$, and
$\alpha=0.05$ (one tailed, as positive correlations are expected) and power of 0.9 indicated a
required sample size of 28 participants. 30 participants took part in the fast-tapping condition
(age: average= 25.75, SD=4.5, min=18, max=39) and 29 in the slow tapping condition (age:
average= 25.43, SD=4.04, min=18, max=39). Of these, 18 completed both conditions. The
experimental procedures were approved by the local ethics committee (*Commissione per*
l'Etica della Ricerca, University of Florence, July 7, 2020, n. 111). The research was in
accordance with the Declaration of Helsinki and informed consent were obtained from all
participants prior to the experiment.

Stimuli and procedures

Stimuli were generated and presented with PsychToolbox routines for Matlab (ver. R2021a).
Stimuli were white visual digit numbers (8, 10, 11, 13, 14, 16, 19, 21, 24, 28, 32) presented in
the centre of a grey screen (iMac Retina display 27–inch) for 1 s and subtending 5° of visual
angle. Soon after the disappearance of the target digit, participants were asked to repeatedly
press a key as many times the target. In separate sessions, participants were asked to tap as
fast as they could or at a comfortable rate. Participants were all right-handed and performed
the tapping's with their right hand on a spacebar positioned about 30 cm to the right of the
monitor, to guarantee a comfortable arm position. Following previous studies (Cordes et al.,
2001; Whalen et al., 1999), serial counting was prevented by vocal suppression, repeating
aloud the syllable 'ba' (as fast as possible). For each participant, each target number was
presented from 25 to 30 times (for a total of 17183 trials: 8259 and 8924 trials in the fast and
slow tapping conditions), in separate blocks (usually 5) interspaced by pauses of a few
minutes. For those participants who completed both the fast and slow tapping condition, the
two were measured on different days (on average within 3-4 days). Each condition took about

1.5 hours of testing (3 hours for those who completed both). Before the experiment,
participants were familiarized with the task performing one single block of trials with
feedback (a digit displaying the number of tappings performed). In this phase 11 trials were
presented, one for each tested number (randomly selected trial by trial). No feedback was
provided during the rest of the experiment.

Control duration task

A randomly selected sub-sample of 9 participants from the slow tapping condition was
engaged in a duration control task. On each trial, a tone (500 Hz, ramped on and off with 20
ms raised-cosine ramps) was played though headphones, and participants asked to reproduce
its duration by repeatedly tapping on a key while pronouncing the syllable 'ba' as fast as
possible (to suppress counting). The between average tapping frequency rate in the number
task was 3.1 Hz (SD 1.1 Hz) and 3.5 Hz (SD 1.3 Hz) in the duration task ($t_{(8)}$=1.03, p= 0.33).
Target durations were customised for each participant to perfectly match those previously
produced in the number task: for each target number tested in the number matching task, we
extracted the average response duration (across trials) and these eleven durations were re-
presented as duration targets (Table 1). Before the experiment, participants were familiarized
with the task by performing one single block of trials with feedback (2 numbers, one
displaying the target duration and the second displaying the reproduced duration, in seconds).
In this phase 11 trials were presented, one for each tested duration (randomly selected trial by
trial). No feedbacks were provided during the rest of the experiment. As for the number task,
for each participant, each duration was presented from 25 to 30 times (for a total of 2455
trials), in separate blocks.

Table 1. Responses duration (in seconds) tested in in the control duration task for each one of the nine participants (S1-S9)								
S1	S2	S3	S4	S5	S6	S7	S8	S9
3	4.1	7.3	3.5	2.2	5	2.4	2.6	2.3
4	6.3	9.2	4.9	3.8	6.3	3.3	2.8	2.9
4.4	7	10.5	5.4	4.2	6.5	3.5	3	3.2
5.1	7.9	11.3	6.2	5	8.3	4.2	3.8	4
5.7	9.3	12.5	7	5.4	8.6	4.3	4	4.4

6.8	10	15.3	8.2	6	9.5	5.4	4.4	5
7.8	11.7	17	9.9	6.9	11.5	6.4	5.3	5.8
8.8	13.7	17.4	10.6	7	13.2	7.4	5.7	6
10.2	15.8	21	12.2	8.6	15.3	8.1	6	7.4
12	17.8	23.3	13.3	9.2	17.7	9.6	7.2	8.8
12.9	21.7	29.2	16	10.8	20.6	11.1	8.2	9.4

Data analyses

All the analyses were performed with Matlab software (ver. R2021a) with the exception of the repeated measures ANOVA comparing Weber fractions for the number and duration task and the t-test comparing frequency rates for the number and duration task (performed with JASP software, ver. 0.16.3).

Data processing

As a first step we detected and eliminated outlier responses. For each experimental condition, and separately for each participant and stimulus intensity, responses were converted into z−scores and eliminated from the analyses if falling above or below 3 STD. In the number matching task, this procedure resulted in the elimination of 0.5% of the trials in the fast-tapping condition and 0.6% in the slow tapping condition. In the control duration task, the same procedure led to the elimination of 0.4% trials in the duration matching condition and 0.6% in the number matching condition.

As a second step we measured responses accuracy and precision, on non-standardized data. For each task, and separately for each participant and stimulus intensity (numbers or durations), accuracy was indexed as the mean reproduction value across trials and precision as Weber fraction, computed as responses standard deviation divided by the average reproduction (a standard index of normalized precision).

Correlation matrices and numerical distance

As a third step we computed Weber fraction correlation matrices. We first measured the precision in translating digit numbers into action sequences, for different target numbers (8,

195 10, 11, 13, 14, 16, 19, 21, 24, 28, 32), for all N participants. For each target number, and

196 independently for each participant, we calculated the normalized reproduction precision

197 (Weber Fraction). The dataset comprised a matrix where each column represents a

198 participant, each row a target number, and each cell the corresponding Weber Fraction. This

199 dataset was then analysed with a pairwise correlation, across participants. For example, the

200 WFs provided by the N participants when tested at the target number "8" were correlated

201 with those obtained with the target number 10, 11, 13...32. If channels exist, the correlation

202 between "8 and 10" (low numerical distance) should be higher compared to that between "8

203 with 32" (higher numerical distance). We therefore analysed the correlation strength as a

204 function of numerical distance. This last analysis (Figure 2, panels B&D) was performed on

205 binned data. Bins were created to have an approximately equal number of observations for

206 each bin (13, 13, 14, 15). For each target, the numerical distance was calculated as the base

207 ten logarithm ratio between itself and the remaining target numbers. The correlation

208 coefficients were then averaged within the following numerical distance bins (log10 ratios):

209 <0.08; 0.08–0.14; 0.14–0.21; 0.21–0.29, 0.29–0.39, >0.39).

210 As a sanity check, this analysis was also performed on randomized correlation matrices. For

211 this analysis we applied a bootstrap approach. On each of 10000 iterations, separately for

212 each subject, the Weber fractions were randomized between numerosities and a new

213 correlation matrix computed. Then (as before) the correlation coefficients were averaged

214 within the reported bins. The results of this analysis are reported in Figure 3 (panels B&D) as

215 the "random" curve.

217 *Hierarchical clustering and Principal component analysis*

218 The hierarchical clustering was performed on normalised (z-scores) Weber fractions using

219 the linkage method. The distances were calculated with the Euclidean metric and the "ward"

220 algorithm was used to compute the distance between clusters. The number of clusters was

221 determined by the inconsistency index (computed by the build in *inconsistent* function in

222 Matlab 2021a) and results reported as a dendrogram. As for the PCA, to check the validity of

223 this analysis, we tested it with randomized correlation matrices, with a bootstrap approach.

224 On each of 10,000 iterations, separately for each participant, the Weber fractions were

225 randomized between numerosities, and a new clustering was computed. Then at each

226 iteration we looked at the structure of the clusters, counting the time on which the clusters

(separately for the fast and slow tapping conditions) contained contiguous numbers (as in

Figure 4 A&B).

The principal component analysis was performed on normalised (z-scores) and centred

Weber fractions and factors rotated with the non-orthogonal promax method (but orthogonal

varimax provides similar results). The number of components was determined as those

exceeding an eigenvalue of 1 and from visual inspection of the scree plots.

Modelling

As a preliminary analysis, we modelled the behaviour of a system with 1, 2 or 4 channels,

assuming that each channel would process stimuli with a gaussian tuning (like the illustration

of Figure 1). The 1-channel model had infinitely broad tuning, and the tuning of the 2- and 4-

channel models was allowed to vary between 0.5 and 2 octaves. The peak of the tuning was

equally spaced in log coordinates to be 8 and 32 for the 2-channel model and 8, 12.7, 20.1

and 32 for the 4-channel model. The behaviour for numerosities handled by more than one

channel was determined by a weighted average of the various channels. The average WF of

the channels taken from the actual dataset (i.e. 0.176 for the slow and fast tapping) however

the specific values for each observers could vary following a gaussian distribution whose

standard deviation was varied to achieve best fit. We then calculated predicted correlations

simulating 25 repetitions for each numerosity and observer. Without any noise correlations

between the same channel would approximate 1. Hence to achieve reasonable levels of

correlation we assumed that the actual measured WF was corrupted by some noise which we

manipulated to mimic the average correlation between observed in the actual experiment.

Correlation matrices were obtained by simulating 1000 experiments with cohorts of 29-30

observers to yield the best fit (R^2).

Results

Participants pressed a key a specific number of times (visually displayed as a digit) while

repeatedly pronouncing the syllable 'ba' as fast as possible, to prevent counting. To gauge the

generalizability across different motor actions, in separate sessions, participants were

required to tap concurrently as fast as they could (fast tapping) or at a comfortable rate (slow

tapping). As expected, the rate of tapping was higher in the fast tapping (average= 6.8 Hz,

SD = 1) compared with the slow tapping condition (average = 3.3 Hz, SD = 1.6). In both

conditions participants were able to correctly perform the numerical matching task, with
average number of reproduced actions scaling linearly with visual targets (both r = 0.99,
Figure 2A&C). Figure 2 B&D shows precision (Weber fractions, Wfs) in matching target and
reproduced numerosity as a function of target number. Average Wfs (across target number)
in the fast and slow conditions were virtually identical (average= 0.17, SD= 0.01 and
average= 0.17, SD= 0.007 for fast and slow tapping respectively) and within each condition,
Wfs were roughly constant across targets, following Weber's Law.

Figure 2. Matched number (A&B) and Weber Fractions (B&C) as a function of target
number, separated for the fast (circles) and slow (squares) tapping conditions. Lines through
the data in panel A&C show best linear fits. Thin lines in panel B&D show individual data.
Error bars are ±1 s.e.m., across participants.

We then computed the correlations of Wfs across participants, for all target values (see
methods for details). Figures 3 A&C show correlation matrices across all participants (like
the simulations of Figure 1), with each cell representing the Pearson correlation coefficient
between the two target numbers. The correlations were all positive, ranging from 0.1 to 0.75
in the fast condition and 0.3 to 0.88 in the slow condition. Importantly, the correlations were
clearly not randomly distributed, but most of the higher correlations (reddish) lie near the
diagonal, indicating that the motor matching performance was more similar for neighbouring
numbers, compared to higher numerical distance.

Figure 3 B&D show average correlation coefficients, averaged into six bins as a function of

numerical distance. There is a systematic decreasing trend in both fast and slow tapping

conditions (linear fit on unbinned data shown by dashed lines in Figure 3 B&D: slopes= –

0.58 ±0.11, –0.57 ±0.07 for fast and slow respectively, both p<0.001), clearly different to

that predicted by a random pattern of matching precision levels (curves with black filled

symbols in Figure 3 B&D, see methods). Overall, these analyses confirm that the degree of

performance similarity was systematically modulated by the numerical difference between

targets, in line with the existence of underlying tuning functions.

As a preliminary analysis we modelled the data with simulations like that of Figure 1,

assuming one, two or four numerosity-selective channels. The average WFs for the

participants was taken from the data, and channel width, variability, and measurement noise

free parameters. The fits with a single channel were very poor, with R^2 = 0.003 and 0.002

(essentially no better than the mean) for the fast and slow tapping respectively. However, the

two-channel model gave much better fits, with R^2 = 0.54 and 0.29. The four-channel model

had similarly good fits, with R^2 = 0.52 and 0.28. The parameters to yield best fits seemed

reasonable, with channel width of 1.2 and 1.8 octaves, and channel variability between 0.051

and 0.106.

Figure 3. Inter-participant correlations. A. Correlation matrices of Wfs for all pairs of target numbers for the slow-tapping condition. B. Correlation strength as a function of numerical ratio, for the slow-tapping condition. Small black filled symbols show bootstrapped average correlation strengths of randomized Wfs matrices. Dashed lines are the best linear fit on unbinned data and error bars are ±1s.e.m. C & D. Like A & B, for the slow-tapping condition.

We then investigated the structure underlying the number sensorimotor translation system with a hierarchical clustering analysis (see methods for details). Figure 4 (A&C) shows the resulting dendrograms. In both the fast and slow tapping conditions, the analyses returned a two-cluster solution with one cluster aggregating low numbers (N8-13 and N8-14 in the fast and slow conditions) and the other aggregating high numbers (N>13 and N>14 respectively). This analysis corroborates the results obtained from the correlation analysis and add on this suggests the existence (at least) of two channels dealing with relatively different numerical targets. A control analysis on randomised data (see methods) yielded clusters containing contiguous numbers only in 0.005% of cases (for both the fast and slow tapping conditions), suggesting that the results with the original dataset likely represent a structure genuinely organised as a function of the highest similarity between neighbouring numbers.

To study the tuning of these two hypothetical channels, we then performed a factor analysis
on Wfs. In both fast and slow tapping conditions, two factors emerged (see methods),
explaining a total of 68% and 81% of the total variance (for the fast and slow tapping
conditions respectively). Figure 4 shows the rotated component strength as a function of
target number. The results revealed two bell-shaped tuning functions for both fast (panel B)
and slow (panel D) tapping conditions, with factor strength distributions reasonably described
by logGaussian functions (fast tapping: $R^2 = 0.6$ and $R^2 = 0.65$; slow tapping: $R^2 = 0.97$, $R^2 =$
0.94 for 1st and 2nd components). In the fast-tapping condition, the first component peaked at
lower target numbers (N 11) and the second component at higher numbers (N 29). In the slow
motor condition, the first component packed at higher target numbers (N 26) and the second
component at lower numbers (N 8).

Figure 4. Dendrograms from hierarchical clustering on Wfs in the fast (A) and slow (C)
tapping conditions. Panels B and D show the strength of the first two principal components
from a PCA on the Wfs measured in the fast (B) and slow (D) tapping conditions. The
strength of these components is shown as a function of the different numerical target levels.
The smooth curves are logGaussian fits to the component strengths.

That fast and slow tapping conditions provided similar results despite the very different
tapping rates suggests that temporal frequency of the tapping did not play a major role.

However, as total response duration was positively correlated with target numbers (r = 0.95,

r = 0.36, for fast and slow tapping, both p<0.001), participants might have used response

duration instead of number of taps as a stop criterion. To test this possibility, a sub−sample of

9 participants were given a control task to match the duration of a tone (see methods). If the

number task was performed through duration, this latter must have an equal or lower

precision level compared to that measured in the number task. Figure 5 A&B shows that this

was not the case with the precision level (Wfs) in the number task being clearly lower (higher

precision) than the duration task, making the use of duration strategies during the number

task unlikely (number: average=0.16, SD= 0.03; duration: average= 0.24, SD= 0.04). A RM

ANOVA with task (duration, number) and stimuli intensity (11 levels) confirmed the

difference (F(1, 80)= 19.97, p= 0.002).

Figure 5. A) Average (across participant) Weber fraction for the number (filled squares) and
duration (empty squares) matching tasks, as a function of ranked target stimulus (visual digits
for the number task, and the corresponding auditory tones durations for the duration task, see
methods for details). B) Individual Weber fractions for the number task plotted against those
for the duration task, averaged across stimulus intensity. The star symbol reports average
across participants. Error bars are ±1 s.e.m.

Discussion

357 Using a motor reproduction task, we measured the precision with which number digits were

358 translated into sequences of actions. Replicating previous evidence from both human and

359 animal studies (Cordes et al., 2001; Kirschhock & Nieder, 2022; Whalen et al., 1999),

360 precision followed Weber's law, a well-established signature of the Approximate Number

361 System (Anobile et al., 2014; Dehaene, 2011; Feigenson et al., 2004; Ross, 2003). As the

focus of the current study was on the individual differences in the number-to-action transformation process, we used digits as sensory stimuli. Digits encoding, at least with educated adults, is noiseless, eliminating this source of variability but leaving that associated with the sensorimotor transformation process.

Importantly, by looking at the covariance structure of the motor reproduction precision index (Weber fraction) across participants, we found evidence for sensorimotor channels tuned to number. Precision for reproducing numerically similar targets was positively correlated ($r\sim0.8$) but for larger numerical distances, correlations decreased ($r\sim0.1$), suggesting the action of sensorimotor channels sharing the encoding of neighbouring numbers. In line with this, cluster analyses identified two main clusters, one aggregating low numbers (from 8 to ~13) and the other higher numbers (from ~13 to 32), pointing to (at least) two mechanisms encoding low and higher numbers. Finally, Principal Component Analyses on Weber fractions confirmed this and went to describe two bell-shaped components, one peaking at relatively low numbers (~10) and the second at higher numbers (~27).

The covariance technique used here has been widely employed to reveal visual channels in several basic perceptual dimensions such as colour, motion, contrast and spatial frequency (Morrone et al., 1999; Peterzell et al., 1995, 2000; Peterzell & Kennedy, 2016; Peterzell & Teller, 1996, 2000; Rammsayer & Troche, 2014). The technique is based on the idea that interindividual variability conveys information that can reveal common sensory processes (Peterzell & Kennedy, 2016), as illustrated in Figure 0. In practice, this approach requires multiple and densely sampled measurements of different stimuli intensity, in the same sample. Regions of high intercorrelation between neighbouring stimuli intensity can be interpreted to imply that sets of stimuli are processed by the same (shared) underlying channel. This channel, while responding relatively more to its preferred stimulus, will also be activated by neighbouring stimuli that although slightly different from the preferred intensity, are nevertheless included in the same response distribution. Following this rationale, relatively lower correlations among more distant stimuli would indicate that these are processed by different, or at least partially independent, channels (Peterzell & Teller, 1996). The results obtained in this study are in line with those predicted by this technique, implying the existence of sensorimotor channels tuned to different numerical targets, with a rather wide response distribution. These channels probably reflect the activity of noisy neurons responsible for translating sensory information into the corresponding numerical motor output, such as those observed in crows (Kirschhock & Nieder, 2022).

The results reinforce adaptation studies showing number-selective adaptation between actions
and perceived numerosity (Anobile et al., 2016; Maldonado Moscoso et al., 2020). Those
studies provided strong evidence for the existence of at least two (but possibly more)
sensorimotor mechanisms, tuned to high and low numbers. The results are also broadly in
line with recent evidence from animal physiology showing number selective sensorimotor
neurons in the crow brain, translating visual inputs (digits and dot arrays) into number of
pecks (Kirschhock & Nieder, 2022). While the crow study found as many channels as the
number tested (N1–5), we found evidence for only two channels (clusters and factors) over
the range of 8–32. However, it is important to note that PCA aims to summarize the dataset
with the minimal number of components (channels). We can therefore not exclude the
possible existence of more than two (perhaps not fully independent) channels. The results
should be not interpreted as evidence for only two sensorimotor channels, but rather as
evidence that tuned mechanisms exist in the human brain, with at least two different tunings.
This is also apparent from the simulations of Figure 1, showing that the predictions of two or
multiple channels are very similar, difficult to distinguish with the current technique. Indeed,
the fits to the data using two or four channels were very similar, but both almost infinitely
better than the one-channel fit. In other words, the channels described here likely represent a
coarse summary representation of several (probably sharper) underlying channels.

The results reported here are unlikely to be contaminated by strategies capitalizing on
duration of motor responses and/or temporal frequency. Despite the very different tapping
rates in the slow (~3 Hz) and fast motor conditions (~7 Hz), the overall pattern of results
remained almost unchanged. The only difference was an inversion of the order of the
principal components and factors, with the first component peaking at lower numbers for the
fast-tapping condition and higher numbers for the slow tapping condition (and vice versa for
the second component). This result suggests that for fast actions lower number targets show
more variance than higher numbers, and vice versa for slower actions. Although we have no
definitive explanation for this pattern of results, it could arise from different effects of the
matching motor noise associated with different tapping rates across the number ranges. In
any event, the results showed two covariance channels for both conditions, similarly
distributed along the numerical targets, supporting the existence of at least two mechanisms,
one tuned to the lower numbers and one to the higher (at least within this numerical range).

Even if total duration of responses were positively correlated with target number, and
although participants were free to use duration as a viable stopping criterion, the exploitation

of this non-numerical strategy seems unlikely. Duration could conceivably be useful proxy
for numerosity, but only if the thresholds for duration were lower than those for numerosity:
but the results show they are in fact higher. Once again, these results are in line with previous
studies showing lower sensitivities for motor matching duration tasks compared with motor
number matching tasks. The electrophysiological study on crows also found similar neural
response curves across very different motor response timing conditions (Kirschhock &
Nieder, 2022). In summary, the results seem to suggest that the channels found here, like
those in crows, reflect a genuine number selective sensorimotor transformation processes.

What may be the adaptive value of this mechanism? The spontaneous use of the number of
actions in the animal kingdom is now well-established. For example, desert ants rely on the
number of steps to return to the nest (Wittlinger et al., 2006), some species of male frogs
match or exceed the chucks of competitors to attract female partner (Rose, 2017), and some
songbirds modulate the numbers of syllables in their calls to signal dangerousness of
predators (Suzuki, 2016; Templeton et al., 2005). In all cases, the use of number-related
motor strategies by animals has a clear ecological value for survival and species preservation.

This system may have been preserved in humans and repurposed for our species-specific
needs. Some hints come from the literature on the role of visual numerosity perception (dot
arrays). Although most animal species are capable of some form of numerosity estimation
(Butterworth, 2022), it appears that in humans numerosity estimation may act as a non-
symbolic precursor for the development of symbolic mathematical skills (Chen & Li, 2014;
Decarli et al., 2023; Halberda et al., 2008; Mazzocco et al., 2011; Piazza, 2010; Piazza et al.,
2010; Schneider et al., 2017). The sensorimotor system could act as an early tool to
constantly update and calibrate motor and sensory systems for the encoding and active
manipulation of quantities and objects, with a potential impact on the quality of formal
mathematical skills in later development. In line with this idea, there are reports of a possible
co-occurrence of motor impairments in children with mathematical learning disorders such as
dyscalculia (Westendorp et al., 2011), and children with developmental coordination
disorders (which impair gross and fine motor function) perform poorly on math and
numerosity tasks (Gomez et al., 2015, 2017). This is in line with the suggestive idea proposed
by Walsh (2003) of a sensory magnitude system, encoding abstract quantities such as space,
time and number, to guide planning and execution of actions. It is also in line with more
recent proposal suggesting that the acquisition of number meaning is deeply grounded in
sensorimotor experiences (Ranzini et al., 2022; Sixtus et al., 2023). This is the first study

showing sensorimotor channels for the transformation of numbers into action sequences in
humans, and many questions remain open. Among these: is the channel preference (the peak)
fixed on the absolute numerical value, or does actively recalibrate according to the numerical
context (range)? Do these channels also integrate non-symbolic numerical information such
as the numerosity of sets of elements and/or sequences of visual/acoustic events? Are these
channels active during motor programming, or do they require action execution? Do these
channels integrate non-numerical motor parameters, such as the associated effort? Are these
channels motor effector-specific? These (and probably other) questions are waiting to be
explored using this technique, which has the advantage of being sufficiently generalisable to
be expanded to investigate most stimulus features.

Funding

This research was funded by the European Union (EU) and Horizon 2020—Grant Agreement
no. 832813—ERC Advanced "Spatio-temporal mechanisms of generative perception —
GenPercept"; and from the Italian Ministry of Education, University, and Research under the
PRIN2017 program (Grant no. 2017XBJN4F— "EnvironMag").

References

Anobile, G., Arrighi, R., Castaldi, E., & Burr, D. C. (2021). A Sensorimotor Numerosity
System. *Trends in Cognitive Sciences*, *25*(1), 24–36.
https://doi.org/10.1016/j.tics.2020.10.009
Anobile, G., Arrighi, R., Togoli, I., & Burr, D. C. (2016). A shared numerical representation
for action and perception. *ELife*, *5*, e16161. https://doi.org/10.7554/eLife.16161
Anobile, G., Cicchini, G. M., & Burr, D. C. (2014). Separate mechanisms for perception of
numerosity and density. *Psychological Science*, *25*(1), 265–270.
https://doi.org/10.1177/0956797613501520
Anobile, G., Domenici, N., Togoli, I., Burr, D., & Arrighi, R. (2020). Distortions of visual
time induced by motor adaptation. *Journal of Experimental Psychology. General*,
149(7), 1333–1343. https://doi.org/10.1037/xge0000709

Arrighi, R., Togoli, I., & Burr, D. C. (2014). A generalized sense of number. *Proceedings of*
the Royal Society B: Biological Sciences, *281*(1797), 20141791.
https://doi.org/10.1098/rspb.2014.1791

Burr, D. C., Anobile, G., & Arrighi, R. (2018). Psychophysical evidence for the number
sense. *Philosophical Transactions of the Royal Society B: Biological Sciences*,
373(1740), 20170045. https://doi.org/10.1098/rstb.2017.0045

Burr, D. C., Anobile, G., Castaldi, E., & Arrighi, R. (2021). Numbers in action. *The*
Behavioral and Brain Sciences, *44*, e185.
https://doi.org/10.1017/S0140525X21000996

Burr, D. C., & Ross, J. (2008). A Visual Sense of Number. *Current Biology*, *18*(6), 425–428.
https://doi.org/10.1016/j.cub.2008.02.052

Butterworth, B. (2022). *Can Fish Count?: What Animals Reveal About Our Uniquely*
Mathematical Minds (New edition). Basic Books.

Chen, Q., & Li, J. (2014). Association between individual differences in non-symbolic
number acuity and math performance: A meta-analysis. *Acta Psychologica*, *148*, 163–
172. https://doi.org/10.1016/j.actpsy.2014.01.016

Cordes, S., Gelman, R., Gallistel, C. R., & Whalen, J. (2001). Variability signatures
distinguish verbal from nonverbal counting for both large and small numbers.
Psychonomic Bulletin & Review, *8*(4), 698–707. https://doi.org/10.3758/bf03196206

Decarli, G., Sella, F., Lanfranchi, S., Gerotto, G., Gerola, S., Cossu, G., & Zorzi, M. (2023).
Severe Developmental Dyscalculia Is Characterized by Core Deficits in Both
Symbolic and Nonsymbolic Number Sense. *Psychological Science*, *34*(1), 8–21.
https://doi.org/10.1177/09567976221097947

Dehaene, S. (2011). *The Number Sense: How the Mind Creates Mathematics, Revised and*
Updated Edition (Updated edizione). Oxford University Press, USA.

Feigenson, L., Dehaene, S., & Spelke, E. (2004). Core systems of number. *Trends in*
Cognitive Sciences, *8*(7), 307–314. https://doi.org/10.1016/j.tics.2004.05.002

Gomez, A., Piazza, M., Jobert, A., Dehaene-Lambertz, G., Dehaene, S., & Huron, C. (2015).
Mathematical difficulties in developmental coordination disorder: Symbolic and
nonsymbolic number processing. *Research in Developmental Disabilities*, *43–44*,
167–178. https://doi.org/10.1016/j.ridd.2015.06.011

Gomez, A., Piazza, M., Jobert, A., Dehaene-Lambertz, G., & Huron, C. (2017). Numerical
abilities of school-age children with Developmental Coordination Disorder (DCD): A

behavioral and eye-tracking study. *Human Movement Science*, *55*, 315–326.

https://doi.org/10.1016/j.humov.2016.08.008

Halberda, J., Mazzocco, M. M. M., & Feigenson, L. (2008). Individual differences in non-

verbal number acuity correlate with maths achievement. *Nature*, *455*(7213), 665–668.

https://doi.org/10.1038/nature07246

Kirschhock, M. E., & Nieder, A. (2022). Number selective sensorimotor neurons in the crow

translate perceived numerosity into number of actions. *Nature Communications*,

13(1), 6913. https://doi.org/10.1038/s41467-022-34457-5

Maldonado Moscoso, P. A., Cicchini, G. M., Arrighi, R., & Burr, D. C. (2020). Adaptation to

hand-tapping affects sensory processing of numerosity directly: Evidence from

reaction times and confidence. *Proceedings. Biological Sciences*, *287*(1927),

20200801. https://doi.org/10.1098/rspb.2020.0801

Mazzocco, M. M. M., Feigenson, L., & Halberda, J. (2011). Impaired acuity of the

approximate number system underlies mathematical learning disability (dyscalculia).

Child Development, *82*(4), 1224–1237. https://doi.org/10.1111/j.1467-

8624.2011.01608.x

Morrone, M. C., Burr, D. C., Di Pietro, S., & Stefanelli, M. A. (1999). Cardinal directions for

visual optic flow. *Current Biology: CB*, *9*(14), 763–766.

https://doi.org/10.1016/s0960-9822(99)80338-8

Peterzell, D. H., Chang, S. K., & Teller, D. Y. (2000). Spatial frequency tuned covariance

channels for red-green and luminance-modulated gratings: Psychophysical data from

human infants. *Vision Research*, *40*(4), 431–444. https://doi.org/10.1016/s0042-

6989(99)00188-1

Peterzell, D. H., & Kennedy, J. F. (2016). Discovering Sensory Processes Using Individual

Differences: A Review and Factor Analytic Manifesto. *Electronic Imaging*, *28*(16),

1–11. https://doi.org/10.2352/ISSN.2470-1173.2016.16.HVEI-112

Peterzell, D. H., & Teller, D. Y. (1996). Individual differences in contrast sensitivity

functions: The lowest spatial frequency channels. *Vision Research*, *36*(19), 3077–

3085. https://doi.org/10.1016/0042-6989(96)00061-2

Peterzell, D. H., & Teller, D. Y. (2000). Spatial frequency tuned covariance channels for red-

green and luminance-modulated gratings: Psychophysical data from human adults.

Vision Research, *40*(4), 417–430. https://doi.org/10.1016/s0042-6989(99)00187-x

Peterzell, D. H., Werner, J. S., & Kaplan, P. S. (1995). Individual differences in contrast

557   sensitivity functions: Longitudinal study of 4-, 6- and 8-month-old human infants.

558   *Vision Research*, *35*(7), 961–979. https://doi.org/10.1016/0042-6989(94)00117-5

559   Piazza, M. (2010). Neurocognitive start-up tools for symbolic number representations.

560   *Trends in Cognitive Sciences*, *14*(12), 542–551.

561   https://doi.org/10.1016/j.tics.2010.09.008

562   Piazza, M., Facoetti, A., Trussardi, A. N., Berteletti, I., Conte, S., Lucangeli, D., Dehaene, S.,

563   & Zorzi, M. (2010). Developmental trajectory of number acuity reveals a severe

564   impairment in developmental dyscalculia. *Cognition*, *116*(1), 33–41.

565   https://doi.org/10.1016/j.cognition.2010.03.012

566   Rammsayer, T. H., & Troche, S. J. (2014). In search of the internal structure of the processes

567   underlying interval timing in the sub-second and the second range: A confirmatory

568   factor analysis approach. *Acta Psychologica*, *147*, 68–74.

569   https://doi.org/10.1016/j.actpsy.2013.05.004

570   Ranzini, M., Semenza, S., Zorzi, M., & Cutini, S. (2022). Influences of hand action on the

571   processing of symbolic numbers: A special role of pointing? *PloS One*, *17*(6).

572   https://doi.org/10.1371/journal.pone.0269557

573   Reynaud, A., & Hess, R. F. (2017). Characterization of Spatial Frequency Channels

574   Underlying Disparity Sensitivity by Factor Analysis of Population Data. *Frontiers in*

575   *Computational Neuroscience*, *11*.

576   https://www.frontiersin.org/articles/10.3389/fncom.2017.00063

577   Rose, G. J. (2017). The numerical abilities of anurans and their neural correlates: Insights

578   from neuroethological studies of acoustic communication. *Philosophical Transactions*

579   *of the Royal Society of London. Series B, Biological Sciences*, *373*(1740), 20160512.

580   https://doi.org/10.1098/rstb.2016.0512

581   Ross, J. (2003). Visual discrimination of number without counting. *Perception*, *32*(7), 867–

582   870. https://doi.org/10.1068/p5029

583   Sawamura, H., Shima, K., & Tanji, J. (2002). Numerical representation for action in the

584   parietal cortex of the monkey. *Nature*, *415*(6874), Article 6874.

585   https://doi.org/10.1038/415918a

586   Schneider, M., Beeres, K., Coban, L., Merz, S., Susan Schmidt, S., Stricker, J., & De Smedt,

587   B. (2017). Associations of non-symbolic and symbolic numerical magnitude

588   processing with mathematical competence: A meta-analysis. *Developmental Science*,

589   *20*(3). https://doi.org/10.1111/desc.12372

Simpson, W. A., & McFadden, S. M. (2005). Spatial frequency channels derived from

individual differences. *Vision Research*, *45*(21), 2723–2727.

https://doi.org/10.1016/j.visres.2005.01.015

Sixtus, E., Krause, F., Lindemann, O., & Fischer, M. H. (2023). A sensorimotor perspective

on numerical cognition. *Trends in Cognitive Sciences*, *27*(4), 367–378.

https://doi.org/10.1016/j.tics.2023.01.002

Suzuki, T. N. (2016). Semantic communication in birds: Evidence from field research over

the past two decades. *Ecological Research*, *31*(3), 307–319.

https://doi.org/10.1007/s11284-016-1339-x

Templeton, C. N., Greene, E., & Davis, K. (2005). Allometry of alarm calls: Black-capped

chickadees encode information about predator size. *Science (New York, N.Y.)*,

308(5730), 1934–1937. https://doi.org/10.1126/science.1108841

Togoli, I., Crollen, V., Arrighi, R., & Collignon, O. (2020). The shared numerical

representation for action and perception develops independently from vision. *Cortex;*

a Journal Devoted to the Study of the Nervous System and Behavior, *129*, 436–445.

https://doi.org/10.1016/j.cortex.2020.05.004

Togoli, I., Marlair, C., Collignon, O., Arrighi, R., & Crollen, V. (2021). Tactile numerosity is

coded in external space. *Cortex*, *134*, 43–51.

https://doi.org/10.1016/j.cortex.2020.10.008

Walsh, V. (2003). A theory of magnitude: Common cortical metrics of time, space and

quantity. *Trends in Cognitive Sciences*, *7*(11), 483–488.

https://doi.org/10.1016/j.tics.2003.09.002

Westendorp, M., Hartman, E., Houwen, S., Smith, J., & Visscher, C. (2011). The relationship

between gross motor skills and academic achievement in children with learning

disabilities. *Research in Developmental Disabilities*, *32*(6), 2773–2779.

https://doi.org/10.1016/j.ridd.2011.05.032

Whalen, J., Gallistel, C. R., & Gelman, R. (1999). Nonverbal Counting in Humans: The

Psychophysics of Number Representation. *Psychological Science*, *10*(2), 130–137.

https://doi.org/10.1111/1467-9280.00120

Wittlinger, M., Wehner, R., & Wolf, H. (2006). The ant odometer: Stepping on stilts and

stumps. *Science (New York, N.Y.)*, *312*(5782), 1965–1967.

https://doi.org/10.1126/science.1126912