Sensorimotor mechanisms selective to numerosity derived from individual differences

Giovanni Anobile[1*], Irene Petrizzo[1], Daisy Paiardini[1], David C. Burr[1,3] & Guido Marco Cicchini[2]

[1]Department of Neuroscience, Psychology, Pharmacology and Child Health, University of Florence, Florence, Italy

[2]Institute of Neuroscience, CNR, via Moruzzi, 1, 56124, Pisa, Italy

[3]School of Psychology, University of Sydney, Camperdown NSW, Australia

* Correspondence:

Giovanni Anobile; giovanni.anobile@unifi.it

Keywords: Visuomotor numerosity, Numerosity perception, Motor system, Approximate number system

Abstract

We have previously shown that after few seconds of adaptation by finger-tapping, the perceived numerosity of spatial arrays and temporal sequences of visual objects displayed near the tapping region is increased or decreased, implying the existence of a *sensorimotor numerosity system* (Anobile et al., 2016). To date, this mechanism has been evidenced only by adaptation. Here we extend our finding by leveraging on a well-established covariance technique, used to unveil and characterize "channels" for basic visual features such as colour, motion, contrast, and spatial frequency. Participants were required to press rapidly a key a specific number of times, without counting. We then correlated the precision of reproduction for various target number presses between participants. The results showed high positive correlations for nearby target numbers, scaling down with numerical distance, implying tuning selectivity. Factor analysis identified two factors, one for low and the other for higher numbers. Principal component analysis revealed two bell-shaped covariance channels, peaking at different numerical values. Two control experiments ruled out the role of non-numerical strategies based on tapping frequency and response duration. These results reinforce our previous reports based on adaptation, and further suggest the existence of at least two sensori-motor number channels responsible for translating symbolic numbers into action sequences.

Introduction

Humans share with many animals a primitive non-verbal number system encoding the number of objects in space and events in time (Dehaene, 2011). The capacity to estimate number rapidly but imperfectly is thought to be a primary perceptual attribute, often termed the *number sense* (Burr & Ross, 2008). The past few decades have accumulated much evidence for the existence of the number sense. Many studies show that the sense of number is truly general, transcending space and time, as well as modality and format (Arrighi et al., 2014; Burr et al., 2018; Togoli et al., 2021). More recently, numerosity has been shown to interact strongly with action, leading to the idea of a *sensorimotor number system*, incorporating action, and its interaction with sensory systems (Anobile et al., 2016, 2021).

Both physiological and psychophysical studies support the existence of a sensorimotor number system. Adaptation studies provide strong evidence: participants first tap continuously with their index finger for a few seconds, either rapidly or slowly, then estimate the numerosity of a dot array presented near the adapted region: adaptation to fast tapping causes underestimation and slow tapping overestimation (Anobile et al., 2016, 2020; Maldonado Moscoso et al., 2020). Motor adaptation induces similar effects on sequential visual and auditory stimuli (Anobile et al., 2016; Togoli et al., 2020), consistent with the existence of a generalized system linking motor and sensory signals to encode numerosity (Anobile et al., 2021; Burr et al., 2021).

Electrophysiological studies in primates also point to the existence of a specific neural substrate for counting a small set of actions. In a seminal paper Sawamura at al. (2002) trained monkeys to repetitively make five identical movements, then switch to a different movement, in a cyclical fashion: neurons in the posterior parietal cortex showed selectivity to the number of self-generated actions, whatever the action. Kirshhock and Nieder (2022) trained crows to peck a specific number of times (1 to 5). Neurons in the telencephalon were shown to be tuned to the impending number of self-generated actions, during the phase between the disappearance of the target to the onset of motor reproduction. The activity of these neurons predicted the behavioural performance and was independent of both stimulus format (dots or digits) and of the temporal characteristics of the motor responses. Each tuning function peaked at a given preferred numerosity, with activity scaling down with numerical distance. Overall, these cells in the crow brain could constitute the neural substrate subserving the transformation of sensory

inputs into a given quantity of numerical actions, possibly a similar mechanism to that driving

the motor number adaptation effects in humans (Anobile et al., 2016).

Although motor adaptation has revealed a clear link between action and numerosity perception,

this is the only technique used so far to investigate the interaction in humans. The aim of the

current study is therefore to expand and generalize our previous findings, using a different

psychophysical technique that exploits individual differences in reproduction precision

(Peterzell & Kennedy, 2016). This technique has been widely used to reveal visual channels

for motion (Morrone et al., 1999), spatial frequency (Reynaud & Hess, 2017; Simpson &

McFadden, 2005), contrast sensitivity (Peterzell et al., 1995; Peterzell & Teller, 1996), color

(Peterzell et al., 2000; Peterzell & Teller, 2000) and duration (Rammsayer & Troche, 2014).

The rationale behind this technique is that performance measures of stimuli detected by the

same mechanism should correlate more between individuals than stimuli detected by different

mechanisms. Figure 1 illustrates the technique by simulation of results in a numerosity

reproduction task if the task were mediated for 1, 2 or 4 numerosity-selective channels. It

assumes intrinsic variability in reproduction precision across participants, perturbed by

additive random noise. The top row simulates results if reproduction of all numerosities were

governed by a single mechanism, rather than a range of numerosity-tuned mechanisms. The

correlation matrix for all pairs of stimuli (Figure 1B) shows no systematic pattern, only random

variations in correlations due to the general noisiness of the channel. Figure 1C plots the

average correlation plotted as a function of numerosity ratio, showing no dependence on

number ratio. Increasing or decreasing the added noise will change the average correlation, but

not create any dependency on numerosity ratio. However, if there exist mechanisms selective

for numerosity, the results are quite different. Assuming just two mechanisms tuned to low and

high numbers (Figure 1D) yields a correlation matrix with higher correlations between similar

numbers (near the diagonal) than dissimilar numbers. This leads to the clear dependency on

numerosity ratio shown in Figure 1E. Similarly, for a range of numerosity-selective

mechanisms like the four shown in Figure 1G, there will be a strong dependency on numerical

distance (Figure 1I). The cases of two and four channels are difficult to distinguish if the

amount of added noise is free to vary. Techniques such as cluster analysis and principal

component analysis (PCA) can be also applied to study further the tuning of the channels.

Figure 1. Simulation of behaviour with 1, 2 or 4 channels mediating numerosity judgments. A: 1-channel model shown as a flat tuning function. (B) Predicted correlation matrix between all pairs of numerosities. There is no systematic variability, only random variations induced by the noise. (C) Average correlation as function of numerical ratio of dot pairs, showing no dependency. (D) 2-channel model centred at numerosities 8 and 32, with full bandwidth of 1.45 octaves. (E) Correlation matrix, showing higher correlations near the identity line. (F) Correlation as function of numerical ratio, showing a systematic falloff with numerical ratio. (G-I) Same as D-F for a 4-channel model with channels equally spaced in the range between 8 and 32 with full bandwidth of 1.10 octaves.

Here we applied the interindividual covariance technique to study sensorimotor tuning in humans, using a number matching task similar to that used by Kirschhock & Nieder (2022). We measured the precision with which 30 participants could press a key a given number of times (8-32) without counting, and then correlated performance across all pairs of numbers (like the simulation of Figure 1). The results clearly demonstrate the existence of sensorimotor mechanisms converting symbolic numbers into actions, with correlations decreasing with numerical distance, like Figures 1F & I.

Methods

Participants

An a priori power analysis for a correlation test (r) with a medium effect size of $r^2 = 0.5$, and $\alpha=0.05$ (one tailed, as positive correlations are expected) and power of 0.9 indicated a required sample size of 28 participants. 30 participants took part in the fast-tapping condition (age: average= 25.75, SD=4.5, min=18, max=39) and 29 in the slow tapping condition (age: average= 25.43, SD=4.04, min=18, max=39). Of these, 18 completed both conditions. The experimental procedures were approved by the local ethics committee (*Commissione per l'Etica della Ricerca*, University of Florence, July 7, 2020, n. 111). The research was in accordance with the Declaration of Helsinki and informed consent were obtained from all participants prior to the experiment.

Stimuli and procedures

Stimuli were generated and presented with PsychToolbox routines for Matlab (ver. R2021a). Stimuli were white visual digit numbers (8, 10, 11, 13, 14, 16, 19, 21, 24, 28, 32) presented in the centre of a grey screen (iMac Retina display 27–inch) for 1 s and subtending 5° of visual angle. Soon after the disappearance of the target digit, participants were asked to repeatedly press a key as many times the target. In separate sessions, participants were asked to tap as fast as they could or at a comfortable rate. Participants were all right-handed and performed the tapping's with their right hand on a spacebar positioned about 30 cm to the right of the monitor, to guarantee a comfortable arm position. Following previous studies (Cordes et al., 2001; Whalen et al., 1999), serial counting was prevented by vocal suppression, repeating aloud the syllable 'ba' (as fast as possible). For each participant, each target number was presented from 25 to 30 times (for a total of 17183 trials: 8259 and 8924 trials in the fast and slow tapping conditions), in separate blocks (usually 5) interspaced by pauses of a few minutes. For those participants who completed both the fast and slow tapping condition, the two were measured on different days (on average within 3-4 days). Each condition took about 1.5 hours of testing (3 hours for those who completed both). Before the experiment, participants were familiarized with the task performing one single block of trials with feedback (a digit displaying the number of tappings performed). In this phase 11 trials were presented, one for each tested number (randomly selected trial by trial). No feedback was provided during the rest of the experiment.

Control duration task

A randomly selected sub-sample of 9 participants from the slow tapping condition was engaged

in a duration control task. On each trial, a tone (500 Hz, ramped on and off with 20 ms raised-

cosine ramps) was played though headphones, and participants asked to reproduce its duration

by repeatedly tapping on a key while pronouncing the syllable 'ba' as fast as possible (to

suppress counting). The between average tapping frequency rate in the number task was 3.1

Hz (SD 1.1 Hz) and 3.5 Hz (SD 1.3 Hz) in the duration task ($t_{(8)}$=1.03, p= 0.33). Target

durations were customised for each participant to perfectly match those previously produced

in the number task: for each target number tested in the number matching task, we extracted

the average response duration (across trials) and these eleven durations were re-presented as

duration targets (Table 1). Before the experiment, participants were familiarized with the task

by performing one single block of trials with feedback (2 numbers, one displaying the target

duration and the second displaying the reproduced duration, in seconds). In this phase 11 trials

were presented, one for each tested duration (randomly selected trial by trial). No feedbacks

were provided during the rest of the experiment. As for the number task, for each participant,

each duration was presented from 25 to 30 times (for a total of 2455 trials), in separate blocks.

Table 1. Responses duration (in seconds) tested in in the control duration task for each one of the nine participants (S1-S9)								
S1	S2	S3	S4	S5	S6	S7	S8	S9
3	4.1	7.3	3.5	2.2	5	2.4	2.6	2.3
4	6.3	9.2	4.9	3.8	6.3	3.3	2.8	2.9
4.4	7	10.5	5.4	4.2	6.5	3.5	3	3.2
5.1	7.9	11.3	6.2	5	8.3	4.2	3.8	4
5.7	9.3	12.5	7	5.4	8.6	4.3	4	4.4
6.8	10	15.3	8.2	6	9.5	5.4	4.4	5
7.8	11.7	17	9.9	6.9	11.5	6.4	5.3	5.8
8.8	13.7	17.4	10.6	7	13.2	7.4	5.7	6
10.2	15.8	21	12.2	8.6	15.3	8.1	6	7.4
12	17.8	23.3	13.3	9.2	17.7	9.6	7.2	8.8
12.9	21.7	29.2	16	10.8	20.6	11.1	8.2	9.4

Data analyses

All the analyses were performed with Matlab software (ver. R2021a) with the exception of the
repeated measures ANOVA comparing Weber fractions for the number and duration task and
the t-test comparing frequency rates for the number and duration task (performed with JASP
software, ver. 0.16.3).

Data processing

As a first step we detected and eliminated outlier responses. For each experimental condition,
and separately for each participant and stimulus intensity, responses were converted into
z–scores and eliminated from the analyses if falling above or below 3 STD. In the number
matching task, this procedure resulted in the elimination of 0.5% of the trials in the fast-tapping
condition and 0.6% in the slow tapping condition. In the control duration task, the same
procedure led to the elimination of 0.4% trials in the duration matching condition and 0.6% in
the number matching condition.

As a second step we measured responses accuracy and precision, on non-standardized data.
For each task, and separately for each participant and stimulus intensity (numbers or durations),
accuracy was indexed as the mean reproduction value across trials and precision as Weber
fraction, computed as responses standard deviation divided by the average reproduction (a
standard index of normalized precision).

Correlation matrices and numerical distance

As a third step we computed Weber fraction correlation matrices. We first measured the
precision in translating digit numbers into action sequences, for different target numbers (8,
10, 11, 13, 14, 16, 19, 21, 24, 28, 32), for all N participants. For each target number, and
independently for each participant, we calculated the normalized reproduction precision
(Weber Fraction). The dataset comprised a matrix where each column represents a participant,
each row a target number, and each cell the corresponding Weber Fraction. This dataset was
then analysed with a pairwise correlation, across participants. For example, the WFs provided
by the N participants when tested at the target number "8" were correlated with those obtained
with the target number 10, 11, 13...32. If channels exist, the correlation between "8 and 10"
(low numerical distance) should be higher compared to that between "8 with 32" (higher

numerical distance). We therefore analysed the correlation strength as a function of numerical

distance. This last analysis (Figure 2, panels B&D) was performed on binned data. Bins were

created to have an approximately equal number of observations for each bin (13, 13, 14, 15).

For each target, the numerical distance was calculated as the base ten logarithm ratio between

itself and the remaining target numbers. The correlation coefficients were then averaged within

the following numerical distance bins (log10 ratios): <0.08; 0.08–0.14; 0.14–0.21; 0.21–0.29,

0.29–0.39, >0.39).

As a sanity check, this analysis was also performed on randomized correlation matrices. For

this analysis we applied a bootstrap approach. On each of 10000 iterations, separately for each

subject, the Weber fractions were randomized between numerosities and a new correlation

matrix computed. Then (as before) the correlation coefficients were averaged within the

reported bins. The results of this analysis are reported in Figure 3 (panels B&D) as the

"random" curve.

Hierarchical clustering and Principal component analysis

The hierarchical clustering was performed on normalised (z-scores) Weber fractions using the

linkage method. The distances were calculated with the Euclidean metric and the "ward"

algorithm was used to compute the distance between clusters. The number of clusters was

determined by the inconsistency index (computed by the build in *inconsistent* function in

Matlab 2021a) and results reported as a dendrogram. As for the PCA, to check the validity of

this analysis, we tested it with randomized correlation matrices, with a bootstrap approach. On

each of 10,000 iterations, separately for each participant, the Weber fractions were randomized

between numerosities, and a new clustering was computed. Then at each iteration we looked

at the structure of the clusters, counting the time on which the clusters (separately for the fast

and slow tapping conditions) contained contiguous numbers (as in Figure 4 A&B).

The principal component analysis was performed on normalised (z-scores) and centred Weber

fractions and factors rotated with the non-orthogonal promax method (but orthogonal varimax

provides similar results). The number of components was determined as those exceeding an

eigenvalue of 1 and from visual inspection of the scree plots.

Modelling

As a preliminary analysis, we modelled the behaviour of a system with 1, 2 or 4 channels,
assuming that each channel would process stimuli with a gaussian tuning (like the illustration
of Figure 1). The 1-channel model had infinitely broad tuning, and the tuning of the 2- and 4-
channel models was allowed to vary between 0.5 and 2 octaves. The peak of the tuning was
equally spaced in log coordinates to be 8 and 32 for the 2-channel model and 8, 12.7, 20.1 and
32 for the 4-channel model. The behaviour for numerosities handled by more than one channel
was determined by a weighted average of the various channels. The average WF of the channels
taken from the actual dataset (i.e. 0.176 for the slow and fast tapping) however the specific
values for each observers could vary following a gaussian distribution whose standard
deviation was varied to achieve best fit. We then calculated predicted correlations simulating
25 repetitions for each numerosity and observer. Without any noise correlations between the
same channel would approximate 1. Hence to achieve reasonable levels of correlation we
assumed that the actual measured WF was corrupted by some noise which we manipulated to
mimic the average correlation between observed in the actual experiment. Correlation matrices
were obtained by simulating 1000 experiments with cohorts of 29-30 observers to yield the
best fit (R^2).

Results

Participants pressed a key a specific number of times (visually displayed as a digit) while
repeatedly pronouncing the syllable 'ba' as fast as possible, to prevent counting. To gauge the
generalizability across different motor actions, in separate sessions, participants were required
to tap concurrently as fast as they could (fast tapping) or at a comfortable rate (slow tapping).
As expected, the rate of tapping was higher in the fast tapping (average= 6.8 Hz, SD = 1)
compared with the slow tapping condition (average = 3.3 Hz, SD = 1.6). In both conditions
participants were able to correctly perform the numerical matching task, with average number
of reproduced actions scaling linearly with visual targets (both r = 0.99, Figure 2A&C). Figure
2 B&D shows precision (Weber fractions, Wfs) in matching target and reproduced numerosity
as a function of target number. Average Wfs (across target number) in the fast and slow
conditions were virtually identical (average= 0.17, SD= 0.01 and average= 0.17, SD= 0.007
for fast and slow tapping respectively) and within each condition, Wfs were roughly constant
across targets, following Weber's Law.

Figure 2. Matched number (A&B) and Weber Fractions (B&C) as a function of target number, separated for the fast (circles) and slow (squares) tapping conditions. Lines through the data in panel A&C show best linear fits. Thin lines in panel B&D show individual data. Error bars are ±1 s.e.m., across participants.

We then computed the correlations of Wfs across participants, for all target values (see methods for details). Figures 3 A&C show correlation matrices across all participants (like the simulations of Figure 1), with each cell representing the Pearson correlation coefficient between the two target numbers. The correlations were all positive, ranging from 0.1 to 0.75 in the fast condition and 0.3 to 0.88 in the slow condition. Importantly, the correlations were clearly not randomly distributed, but most of the higher correlations (reddish) lie near the diagonal, indicating that the motor matching performance was more similar for neighbouring numbers, compared to higher numerical distance.

Figure 3 B&D show average correlation coefficients, averaged into six bins as a function of numerical distance. There is a systematic decreasing trend in both fast and slow tapping conditions (linear fit on unbinned data shown by dashed lines in Figure 3 B&D: slopes= –0.58 ±0.11, –0.57 ±0.07 for fast and slow respectively, both p<0.001), clearly different to that predicted by a random pattern of matching precision levels (curves with black filled symbols in Figure 3 B&D, see methods). Overall, these analyses confirm that the degree of performance

similarity was systematically modulated by the numerical difference between targets, in line with the existence of underlying tuning functions.

As a preliminary analysis we modelled the data with simulations like that of Figure 1, assuming one, two or four numerosity-selective channels. The average WFs for the participants was taken from the data, and channel width, variability, and measurement noise free parameters. The fits with a single channel were very poor, with $R^2 = 0.003$ and 0.002 (essentially no better than the mean) for the fast and slow tapping respectively. However, the two-channel model gave much better fits, with $R^2 = 0.54$ and 0.29. The four-channel model had similarly good fits, with $R^2 = 0.52$ and 0.28. The parameters to yield best fits seemed reasonable, with channel width of 1.2 and 1.8 octaves, and channel variability between 0.051 and 0.106.

Figure 3. Inter-participant correlations. A. Correlation matrices of Wfs for all pairs of target numbers for the slow-tapping condition. B. Correlation strength as a function of numerical ratio, for the slow-tapping condition. Small black filled symbols show bootstrapped average correlation strengths of randomized Wfs matrices. Dashed lines are the best linear fit on unbinned data and error bars are ±1s.e.m. C & D. Like A & B, for the slow-tapping condition.

We then investigated the structure underlying the number sensorimotor translation system with
a hierarchical clustering analysis (see methods for details). Figure 4 (A&C) shows the resulting
dendrograms. In both the fast and slow tapping conditions, the analyses returned a two-cluster
solution with one cluster aggregating low numbers (N8-13 and N8-14 in the fast and slow
conditions) and the other aggregating high numbers (N>13 and N>14 respectively). This
analysis corroborates the results obtained from the correlation analysis and add on this suggests
the existence (at least) of two channels dealing with relatively different numerical targets. A
control analysis on randomised data (see methods) yielded clusters containing contiguous
numbers only in 0.005% of cases (for both the fast and slow tapping conditions), suggesting
that the results with the original dataset likely represent a structure genuinely organised as a
function of the highest similarity between neighbouring numbers.

To study the tuning of these two hypothetical channels, we then performed a factor analysis on
Wfs. In both fast and slow tapping conditions, two factors emerged (see methods), explaining
a total of 68% and 81% of the total variance (for the fast and slow tapping conditions
respectively). Figure 4 shows the rotated component strength as a function of target number.
The results revealed two bell-shaped tuning functions for both fast (panel B) and slow (panel
D) tapping conditions, with factor strength distributions reasonably described by logGaussian
functions (fast tapping: $R^2 = 0.6$ and $R^2 = 0.65$; slow tapping: $R^2 = 0.97$, $R^2 = 0.94$ for 1st and
2nd components). In the fast-tapping condition, the first component peaked at lower target
numbers (N 11) and the second component at higher numbers (N 29). In the slow motor
condition, the first component packed at higher target numbers (N 26) and the second
component at lower numbers (N 8).

Figure 4. Dendrograms from hierarchical clustering on Wfs in the fast (A) and slow (C)
tapping conditions. Panels B and D show the strength of the first two principal components
from a PCA on the Wfs measured in the fast (B) and slow (D) tapping conditions. The strength
of these components is shown as a function of the different numerical target levels. The smooth
curves are logGaussian fits to the component strengths.

That fast and slow tapping conditions provided similar results despite the very different tapping

rates suggests that temporal frequency of the tapping did not play a major role. However, as

total response duration was positively correlated with target numbers ($r = 0.95$, $r = 0.36$, for

fast and slow tapping, both $p<0.001$), participants might have used response duration instead

of number of taps as a stop criterion. To test this possibility, a sub–sample of 9 participants

were given a control task to match the duration of a tone (see methods). If the number task was

performed through duration, this latter must have an equal or lower precision level compared

to that measured in the number task. Figure 5 A&B shows that this was not the case with the

precision level (Wfs) in the number task being clearly lower (higher precision) than the

duration task, making the use of duration strategies during the number task unlikely (number:

average=0.16, SD= 0.03; duration: average= 0.24, SD= 0.04). A RM ANOVA with task

(duration, number) and stimuli intensity (11 levels) confirmed the difference ($F_{(1, 80)}= 19.97$,

$p= 0.002$).

Figure 5. A) Average (across participant) Weber fraction for the number (filled squares) and duration (empty squares) matching tasks, as a function of ranked target stimulus (visual digits for the number task, and the corresponding auditory tones durations for the duration task, see methods for details). B) Individual Weber fractions for the number task plotted against those for the duration task, averaged across stimulus intensity. The star symbol reports average across participants. Error bars are ±1 s.e.m.

Discussion

Using a motor reproduction task, we measured the precision with which number digits were translated into sequences of actions. Replicating previous evidence from both human and animal studies (Cordes et al., 2001; Kirschhock & Nieder, 2022; Whalen et al., 1999), precision followed Weber's law, a well-established signature of the Approximate Number System (Anobile et al., 2014; Dehaene, 2011; Feigenson et al., 2004; Ross, 2003). As the focus of the current study was on the individual differences in the number-to-action transformation process, we used digits as sensory stimuli. Digits encoding, at least with educated adults, is noiseless, eliminating this source of variability but leaving that associated with the sensorimotor transformation process.

Importantly, by looking at the covariance structure of the motor reproduction precision index (Weber fraction) across participants, we found evidence for sensorimotor channels tuned to number. Precision for reproducing numerically similar targets was positively correlated (r~0.8) but for larger numerical distances, correlations decreased (r~0.1), suggesting the action of sensorimotor channels sharing the encoding of neighbouring numbers. In line with this, cluster analyses identified two main clusters, one aggregating low numbers (from 8 to ~13) and the other higher numbers (from ~13 to 32), pointing to (at least) two mechanisms encoding low

and higher numbers. Finally, Principal Component Analyses on Weber fractions confirmed
this and went to describe two bell-shaped components, one peaking at relatively low numbers
(~10) and the second at higher numbers (~27).

The covariance technique used here has been widely employed to reveal visual channels in
several basic perceptual dimensions such as colour, motion, contrast and spatial frequency
(Morrone et al., 1999; Peterzell et al., 1995, 2000; Peterzell & Kennedy, 2016; Peterzell &
Teller, 1996, 2000; Rammsayer & Troche, 2014). The technique is based on the idea that
interindividual variability conveys information that can reveal common sensory processes
(Peterzell & Kennedy, 2016), as illustrated in Figure 1. In practice, this approach requires
multiple and densely sampled measurements of different stimuli intensity, in the same sample.
Regions of high intercorrelation between neighbouring stimuli intensity can be interpreted to
imply that sets of stimuli are processed by the same (shared) underlying channel. This channel,
while responding relatively more to its preferred stimulus, will also be activated by
neighbouring stimuli that although slightly different from the preferred intensity, are
nevertheless included in the same response distribution. Following this rationale, relatively
lower correlations among more distant stimuli would indicate that these are processed by
different, or at least partially independent, channels (Peterzell & Teller, 1996). The results
obtained in this study are in line with those predicted by this technique, implying the existence
of sensorimotor channels tuned to different numerical targets, with a rather wide response
distribution. These channels probably reflect the activity of noisy neurons responsible for
translating sensory information into the corresponding numerical motor output, such as those
observed in crows (Kirschhock & Nieder, 2022).

The results reinforce adaptation studies showing number-selective adaptation between actions
and perceived numerosity (Anobile et al., 2016; Maldonado Moscoso et al., 2020). Those
studies provided strong evidence for the existence of at least two (but possibly more)
sensorimotor mechanisms, tuned to high and low numbers. The results are also broadly in line
with recent evidence from animal physiology showing number selective sensorimotor neurons
in the crow brain, translating visual inputs (digits and dot arrays) into number of pecks
(Kirschhock & Nieder, 2022). While the crow study found as many channels as the number
tested (N1–5), we found evidence for only two channels (clusters and factors) over the range
of 8–32. However, it is important to note that PCA aims to summarize the dataset with the
minimal number of components (channels). We can therefore not exclude the possible
existence of more than two (perhaps not fully independent) channels. The results should be not

interpreted as evidence for only two sensorimotor channels, but rather as evidence that tuned
mechanisms exist in the human brain, with at least two different tunings. This is also apparent
from the simulations of Figure 1, showing that the predictions of two or multiple channels are
very similar, difficult to distinguish with the current technique. Indeed, the fits to the data using
two or four channels were very similar, but both almost infinitely better than the one-channel
fit. In other words, the channels described here likely represent a coarse summary
representation of several (probably sharper) underlying channels.

The results reported here are unlikely to be contaminated by strategies capitalizing on duration
of motor responses and/or temporal frequency. Despite the very different tapping rates in the
slow (~3 Hz) and fast motor conditions (~7 Hz), the overall pattern of results remained almost
unchanged. The only difference was an inversion of the order of the principal components and
factors, with the first component peaking at lower numbers for the fast-tapping condition and
higher numbers for the slow tapping condition (and vice versa for the second component). This
result suggests that for fast actions lower number targets show more variance than higher
numbers, and vice versa for slower actions. Although we have no definitive explanation for
this pattern of results, it could arise from different effects of the matching motor noise
associated with different tapping rates across the number ranges. In any event, the results
showed two covariance channels for both conditions, similarly distributed along the numerical
targets, supporting the existence of at least two mechanisms, one tuned to the lower numbers
and one to the higher (at least within this numerical range).

Even if total duration of responses were positively correlated with target number, and although
participants were free to use duration as a viable stopping criterion, the exploitation of this non-
numerical strategy seems unlikely. Duration could conceivably be useful proxy for
numerosity, but only if the thresholds for duration were lower than those for numerosity: but
the results show they are in fact higher. Once again, these results are in line with previous
studies showing lower sensitivities for motor matching duration tasks compared with motor
number matching tasks. The electrophysiological study on crows also found similar neural
response curves across very different motor response timing conditions (Kirschhock & Nieder,
2022). In summary, the results seem to suggest that the channels found here, like those in
crows, reflect a genuine number selective sensorimotor transformation processes.

What may be the adaptive value of this mechanism? The spontaneous use of the number of
actions in the animal kingdom is now well-established. For example, desert ants rely on the
number of steps to return to the nest (Wittlinger et al., 2006), some species of male frogs match

or exceed the chucks of competitors to attract female partner (Rose, 2017), and some songbirds

modulate the numbers of syllables in their calls to signal dangerousness of predators (Suzuki,

2016; Templeton et al., 2005). In all cases, the use of number-related motor strategies by

animals has a clear ecological value for survival and species preservation.

This system may have been preserved in humans and repurposed for our species-specific needs.

Some hints come from the literature on the role of visual numerosity perception (dot arrays).

Although most animal species are capable of some form of numerosity estimation

(Butterworth, 2022), it appears that in humans numerosity estimation may act as a non-

symbolic precursor for the development of symbolic mathematical skills (Chen & Li, 2014;

Decarli et al., 2023; Halberda et al., 2008; Mazzocco et al., 2011; Piazza, 2010; Piazza et al.,

2010; Schneider et al., 2017). The sensorimotor system could act as an early tool to constantly

update and calibrate motor and sensory systems for the encoding and active manipulation of

quantities and objects, with a potential impact on the quality of formal mathematical skills in

later development. In line with this idea, there are reports of a possible co-occurrence of motor

impairments in children with mathematical learning disorders such as dyscalculia (Westendorp

et al., 2011), and children with developmental coordination disorders (which impair gross and

fine motor function) perform poorly on math and numerosity tasks (Gomez et al., 2015, 2017).

This is in line with the suggestive idea proposed by Walsh (2003) of a sensory magnitude

system, encoding abstract quantities such as space, time and number, to guide planning and

execution of actions. It is also in line with more recent proposal suggesting that the acquisition

of number meaning is deeply grounded in sensorimotor experiences (Ranzini et al., 2022;

Sixtus et al., 2023). This is the first study showing sensorimotor channels for the transformation

of numbers into action sequences in humans, and many questions remain open. Among these:

is the channel preference (the peak) fixed on the absolute numerical value, or does actively

recalibrate according to the numerical context (range)? Do these channels also integrate non-

symbolic numerical information such as the numerosity of sets of elements and/or sequences

of visual/acoustic events? Are these channels active during motor programming, or do they

require action execution? Do these channels integrate non-numerical motor parameters, such

as the associated effort? Are these channels motor effector-specific? These (and probably

other) questions are waiting to be explored using this technique, which has the advantage of

being sufficiently generalisable to be expanded to investigate most stimulus features.

Funding

This research was funded by the European Union (EU) and Horizon 2020—Grant Agreement no. 832813—ERC Advanced "Spatio-temporal mechanisms of generative perception — GenPercept"; and from the Italian Ministry of Education, University, and Research under the PRIN2017 program (Grant no. 2017XBJN4F— "EnvironMag").

Data availability statement

The datasets presented in this study can be found in online repositories. The names of the repository/repositories and accession number(s) can be found below: https://doi.org/10.5281/zenodo.8279069.

References

Anobile, G., Arrighi, R., Castaldi, E., & Burr, D. C. (2021). A Sensorimotor Numerosity System. *Trends in Cognitive Sciences*, *25*(1), 24–36. https://doi.org/10.1016/j.tics.2020.10.009

Anobile, G., Arrighi, R., Togoli, I., & Burr, D. C. (2016). A shared numerical representation for action and perception. *ELife*, *5*, e16161. https://doi.org/10.7554/eLife.16161

Anobile, G., Cicchini, G. M., & Burr, D. C. (2014). Separate mechanisms for perception of numerosity and density. *Psychological Science*, *25*(1), 265–270. https://doi.org/10.1177/0956797613501520

Anobile, G., Domenici, N., Togoli, I., Burr, D., & Arrighi, R. (2020). Distortions of visual time induced by motor adaptation. *Journal of Experimental Psychology. General*, *149*(7), 1333–1343. https://doi.org/10.1037/xge0000709

Arrighi, R., Togoli, I., & Burr, D. C. (2014). A generalized sense of number. *Proceedings of the Royal Society B: Biological Sciences*, *281*(1797), 20141791. https://doi.org/10.1098/rspb.2014.1791

Burr, D. C., Anobile, G., & Arrighi, R. (2018). Psychophysical evidence for the number sense. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *373*(1740), 20170045. https://doi.org/10.1098/rstb.2017.0045

Burr, D. C., Anobile, G., Castaldi, E., & Arrighi, R. (2021). Numbers in action. *The Behavioral and Brain Sciences*, *44*, e185. https://doi.org/10.1017/S0140525X21000996

Burr, D. C., & Ross, J. (2008). A Visual Sense of Number. *Current Biology*, *18*(6), 425–428.

https://doi.org/10.1016/j.cub.2008.02.052

Butterworth, B. (2022). *Can Fish Count?: What Animals Reveal About Our Uniquely*

Mathematical Minds (New edition). Basic Books.

Chen, Q., & Li, J. (2014). Association between individual differences in non-symbolic

number acuity and math performance: A meta-analysis. *Acta Psychologica*, *148*, 163–

172. https://doi.org/10.1016/j.actpsy.2014.01.016

Cordes, S., Gelman, R., Gallistel, C. R., & Whalen, J. (2001). Variability signatures

distinguish verbal from nonverbal counting for both large and small numbers.

Psychonomic Bulletin & Review, *8*(4), 698–707. https://doi.org/10.3758/bf03196206

Decarli, G., Sella, F., Lanfranchi, S., Gerotto, G., Gerola, S., Cossu, G., & Zorzi, M. (2023).

Severe Developmental Dyscalculia Is Characterized by Core Deficits in Both

Symbolic and Nonsymbolic Number Sense. *Psychological Science*, *34*(1), 8–21.

https://doi.org/10.1177/09567976221097947

Dehaene, S. (2011). *The Number Sense: How the Mind Creates Mathematics, Revised and*

Updated Edition (Updated edizione). Oxford University Press, USA.

Feigenson, L., Dehaene, S., & Spelke, E. (2004). Core systems of number. *Trends in*

Cognitive Sciences, *8*(7), 307–314. https://doi.org/10.1016/j.tics.2004.05.002

Gomez, A., Piazza, M., Jobert, A., Dehaene-Lambertz, G., Dehaene, S., & Huron, C. (2015).

Mathematical difficulties in developmental coordination disorder: Symbolic and

nonsymbolic number processing. *Research in Developmental Disabilities*, *43–44*,

167–178. https://doi.org/10.1016/j.ridd.2015.06.011

Gomez, A., Piazza, M., Jobert, A., Dehaene-Lambertz, G., & Huron, C. (2017). Numerical

abilities of school-age children with Developmental Coordination Disorder (DCD): A

behavioral and eye-tracking study. *Human Movement Science*, *55*, 315–326.

https://doi.org/10.1016/j.humov.2016.08.008

Halberda, J., Mazzocco, M. M. M., & Feigenson, L. (2008). Individual differences in non-

verbal number acuity correlate with maths achievement. *Nature*, *455*(7213), 665–668.

https://doi.org/10.1038/nature07246

Kirschhock, M. E., & Nieder, A. (2022). Number selective sensorimotor neurons in the crow

translate perceived numerosity into number of actions. *Nature Communications*,

13(1), 6913. https://doi.org/10.1038/s41467-022-34457-5

Maldonado Moscoso, P. A., Cicchini, G. M., Arrighi, R., & Burr, D. C. (2020). Adaptation to

hand-tapping affects sensory processing of numerosity directly: Evidence from

reaction times and confidence. *Proceedings. Biological Sciences*, *287*(1927),

20200801. https://doi.org/10.1098/rspb.2020.0801

Mazzocco, M. M. M., Feigenson, L., & Halberda, J. (2011). Impaired acuity of the

approximate number system underlies mathematical learning disability (dyscalculia).

Child Development, *82*(4), 1224–1237. https://doi.org/10.1111/j.1467-

8624.2011.01608.x

Morrone, M. C., Burr, D. C., Di Pietro, S., & Stefanelli, M. A. (1999). Cardinal directions for

visual optic flow. *Current Biology: CB*, *9*(14), 763–766.

https://doi.org/10.1016/s0960-9822(99)80338-8

Peterzell, D. H., Chang, S. K., & Teller, D. Y. (2000). Spatial frequency tuned covariance

channels for red-green and luminance-modulated gratings: Psychophysical data from

human infants. *Vision Research*, *40*(4), 431–444. https://doi.org/10.1016/s0042-

6989(99)00188-1

Peterzell, D. H., & Kennedy, J. F. (2016). Discovering Sensory Processes Using Individual

Differences: A Review and Factor Analytic Manifesto. *Electronic Imaging*, *28*(16),

1–11. https://doi.org/10.2352/ISSN.2470-1173.2016.16.HVEI-112

Peterzell, D. H., & Teller, D. Y. (1996). Individual differences in contrast sensitivity

functions: The lowest spatial frequency channels. *Vision Research*, *36*(19), 3077–

3085. https://doi.org/10.1016/0042-6989(96)00061-2

Peterzell, D. H., & Teller, D. Y. (2000). Spatial frequency tuned covariance channels for red-

green and luminance-modulated gratings: Psychophysical data from human adults.

Vision Research, *40*(4), 417–430. https://doi.org/10.1016/s0042-6989(99)00187-x

Peterzell, D. H., Werner, J. S., & Kaplan, P. S. (1995). Individual differences in contrast

sensitivity functions: Longitudinal study of 4-, 6- and 8-month-old human infants.

Vision Research, *35*(7), 961–979. https://doi.org/10.1016/0042-6989(94)00117-5

Piazza, M. (2010). Neurocognitive start-up tools for symbolic number representations.

Trends in Cognitive Sciences, *14*(12), 542–551.

https://doi.org/10.1016/j.tics.2010.09.008

Piazza, M., Facoetti, A., Trussardi, A. N., Berteletti, I., Conte, S., Lucangeli, D., Dehaene, S.,

& Zorzi, M. (2010). Developmental trajectory of number acuity reveals a severe

impairment in developmental dyscalculia. *Cognition*, *116*(1), 33–41.

https://doi.org/10.1016/j.cognition.2010.03.012

Rammsayer, T. H., & Troche, S. J. (2014). In search of the internal structure of the processes

underlying interval timing in the sub-second and the second range: A confirmatory

factor analysis approach. *Acta Psychologica*, *147*, 68–74.

https://doi.org/10.1016/j.actpsy.2013.05.004

Ranzini, M., Semenza, S., Zorzi, M., & Cutini, S. (2022). Influences of hand action on the

processing of symbolic numbers: A special role of pointing? *PloS One*, *17*(6).

https://doi.org/10.1371/journal.pone.0269557

Reynaud, A., & Hess, R. F. (2017). Characterization of Spatial Frequency Channels

Underlying Disparity Sensitivity by Factor Analysis of Population Data. *Frontiers in*

Computational Neuroscience, *11*.

https://www.frontiersin.org/articles/10.3389/fncom.2017.00063

Rose, G. J. (2017). The numerical abilities of anurans and their neural correlates: Insights

from neuroethological studies of acoustic communication. *Philosophical Transactions*

of the Royal Society of London. Series B, Biological Sciences, *373*(1740), 20160512.

https://doi.org/10.1098/rstb.2016.0512

Ross, J. (2003). Visual discrimination of number without counting. *Perception*, *32*(7), 867–

870. https://doi.org/10.1068/p5029

Sawamura, H., Shima, K., & Tanji, J. (2002). Numerical representation for action in the

parietal cortex of the monkey. *Nature*, *415*(6874), Article 6874.

https://doi.org/10.1038/415918a

Schneider, M., Beeres, K., Coban, L., Merz, S., Susan Schmidt, S., Stricker, J., & De Smedt,

B. (2017). Associations of non-symbolic and symbolic numerical magnitude

processing with mathematical competence: A meta-analysis. *Developmental Science*,

20(3). https://doi.org/10.1111/desc.12372

Simpson, W. A., & McFadden, S. M. (2005). Spatial frequency channels derived from

individual differences. *Vision Research*, *45*(21), 2723–2727.

https://doi.org/10.1016/j.visres.2005.01.015

Sixtus, E., Krause, F., Lindemann, O., & Fischer, M. H. (2023). A sensorimotor perspective

on numerical cognition. *Trends in Cognitive Sciences*, *27*(4), 367–378.

https://doi.org/10.1016/j.tics.2023.01.002

Suzuki, T. N. (2016). Semantic communication in birds: Evidence from field research over

the past two decades. *Ecological Research*, *31*(3), 307–319.

https://doi.org/10.1007/s11284-016-1339-x

Templeton, C. N., Greene, E., & Davis, K. (2005). Allometry of alarm calls: Black-capped

chickadees encode information about predator size. *Science (New York, N.Y.)*,

308(5730), 1934–1937. https://doi.org/10.1126/science.1108841

Togoli, I., Crollen, V., Arrighi, R., & Collignon, O. (2020). The shared numerical

representation for action and perception develops independently from vision. *Cortex;*

a Journal Devoted to the Study of the Nervous System and Behavior, *129*, 436–445.

https://doi.org/10.1016/j.cortex.2020.05.004

Togoli, I., Marlair, C., Collignon, O., Arrighi, R., & Crollen, V. (2021). Tactile numerosity is

coded in external space. *Cortex*, *134*, 43–51.

https://doi.org/10.1016/j.cortex.2020.10.008

Walsh, V. (2003). A theory of magnitude: Common cortical metrics of time, space and

quantity. *Trends in Cognitive Sciences*, *7*(11), 483–488.

https://doi.org/10.1016/j.tics.2003.09.002

Westendorp, M., Hartman, E., Houwen, S., Smith, J., & Visscher, C. (2011). The relationship

between gross motor skills and academic achievement in children with learning

disabilities. *Research in Developmental Disabilities*, *32*(6), 2773–2779.

https://doi.org/10.1016/j.ridd.2011.05.032

Whalen, J., Gallistel, C. R., & Gelman, R. (1999). Nonverbal Counting in Humans: The

Psychophysics of Number Representation. *Psychological Science*, *10*(2), 130–137.

https://doi.org/10.1111/1467-9280.00120

Wittlinger, M., Wehner, R., & Wolf, H. (2006). The ant odometer: Stepping on stilts and

stumps. *Science (New York, N.Y.)*, *312*(5782), 1965–1967.

https://doi.org/10.1126/science.1126912