1

Non-Negative Matrix Factorization for Analyzing State Dependent Neuronal Network Dynamics in Calcium Recordings

Daniel Carbonero[1,3,4¶], Jad Noueihed[1,3,4], Mark A. Kramer[2,3], John A. White[1,3,4*]

[1] Department of Biomedical Engineering, Boston University, Boston, Massachusetts, United
States of America

[2] Department of Mathematics and Statistics, Boston University, Boston, Massachusetts, United
States of America

[3] Center for Systems Neuroscience, Boston University, Boston, Massachusetts, United States of
America

[4] Neurophotonics Center, Boston University, Boston, Massachusetts, United States of America

* Corresponding Author

E-mail: dcarbo@bu.edu

Abstract

Calcium imaging allows recording from hundreds of neurons in vivo with the ability to resolve

single cell activity. Evaluating and analyzing neuronal responses, while also considering all

dimensions of the data set to make specific conclusions, is extremely difficult. Often, descriptive

statistics are used to analyze these forms of data. These analyses, however, remove variance by

averaging the responses of single neurons across recording sessions, or across combinations of

neurons to create single quantitative metrics, losing the temporal dynamics of neuronal activity,

and their responses relative to each other. Dimensionally Reduction (DR) methods serve as a

good foundation for these analyses because they reduce the dimensions of the data into

components, while still maintaining the variance. Non-negative Matrix Factorization (NMF) is an

especially promising DR analysis method for calcium imaging because of its mathematical

constraints, which include positivity and linearity. We adapt NMF for our analyses and compare

its performance to alternative dimensionality reduction methods on both artificial and in vivo data.

We find that NMF is well-suited for analyzing calcium imaging recordings, accurately capturing

the underlying dynamics of the data, and outperforming alternative methods in common use.

Author Summary

Calcium imaging has enabled the unprecedented recording of complex brain activity in novel

contexts. Recording activity from hundreds of single neurons within a specific brain region, it

allows study of local networks that was previously inaccessible. However, these recordings create

increasingly large data sets. Manually analyzing every neuron's activity, and meaningfully relating

it to every other neuron's is impossible in practice. Nearly all analyses use descriptive statistics

to simply summarize the activity found in these recordings, simplifying at the expense of

discounting the nuance found in such complicated data. Dimensionality Reduction (DR) provides

a machine learning alternative to comprehensively analyze the data, significantly reducing

complexity, while considering both each neuron's activity, and the relationships between them.

Non-Negative Matrix Factorization (NMF) is especially promising for analysis of these recordings

because of its mathematical constraints of linearity and positivity. We compare several DR

methods to NMF below, using simulated neuronal networks with statistically similar activity to our

recordings, before applying it to a series of awake baseline recordings as a proof of concept on

recorded data. We demonstrate NMF significantly outperforms every other method tested, proving

it a promisingly powerful tool for analyzing network dynamics to study unique neural contexts.

<u>Introduction</u>

Recent advances in neural recording methods have made it possible to collect large, complex

data sets that can be used to study context-dependent neural dynamics in great detail[1,2]. For

example, calcium imaging allows simultaneous recording from hundreds of neurons in a single

brain region in vivo, while maintaining single cell-resolution[3,4]. Other tools allow cell "tagging"

based on factors, including activity during a specified time window and molecular genotype [5–8].

The resultant data set consists of several hundred time series thousands of points long,

multiplicatively increasing per experimental condition added, in addition to any tagging data. The

process of characterizing such single-cells responses, relating them to those of other cells across

time, and accounting for the tagging information, all while considering changes in animal behavior,

is a difficult but essential task.

Basic descriptive statistics (mean, median, variance) are a common approach to analyze large

neural datasets. However, these approaches are limited because they average over the temporal

dynamics of neuronal activity and can obscure interactions among neurons at fine time

scales[9,10]. Dimensionality reduction (DR) is a more sophisticated approach that can help to

reveal low-dimensional dynamics by transforming high-dimensional data into interpretable, low-

dimensional components[11]. Compressing the data in this way can preserve temporal patterns

and correlations and focus subsequent analysis on the dynamical patterns of interest.

DR approaches have many applications in the analysis of neural data, including analysis of

electrophysiological recordings(9,12,13), automation of trace extraction of neuronal activity in

fluorescent recordings(1,14–18), and as a pre-processing step to more complex behavioral

decoding(19). To analyze network dynamics in calcium recordings, non-linear DR methods have

emerged to map dynamics to low dimensional manifolds(20–23). While excellent for very low

dimensional visualization(24,25), the dynamics are difficult to interpret beyond the manifold being

modeled, with manifolds being difficult to interpret beyond three dimensions. Linear DR methods

have likewise been employed to either statically cluster cells(18,26–28), or to abstractly analyze

activity in low-dimensional subspaces(29–32). As a result, for our data, we argue that linear

methods will provide a more interpretable low dimensional representation of the activity, using a

few more dimensions to describe the majority of the dynamics, at the cost of a difficult to interpret,

low dimensional manifold.

Non-negative Matrix Factorization (NMF) is an especially promising linear decomposition method

for analysis of activity recorded in calcium imaging. NMF operates under the constraint that every

element in the data, and the decomposition, be non-negative(33), as is naturally true for neuronal

calcium traces(18). Further, the positivity constraint, coupled with the linearity of the reduced

dimensions, ensures that each of the dimensions sum to form a low dimensional representation

of the data, simplifying the interpretation of the data(34). In neuroscience, NMF has been applied

to quantify single cell pairwise relationships (35) and statically cluster cells under a series of strict

assumptions(27). Here, we develop an application of NMF to analyze holistic network activity,

capturing how precise sub-networks of neuronal dynamics evolve in different experimental

contexts. To assess performance of the NMF approach, we generate artificial calcium imaging

data from ground-truth networks and assess how well our approach captures the underlying

network structures responsible for the emergent dynamics of the network compared to alternative

widely used approaches. We then apply the same NMF framework to characterize the dynamics

of a representative *in vivo* calcium imaging data set. We conclude that, compared to alternative

methods, NMF best captures the ground truth networks that underlie the observed calcium

dynamics and provides a useful low-dimensional description of complex physiological data.

Dimensionality Reduction (DR) Methods:

Non-Negative Matrix Factorization (NMF):

NMF is a linear, matrix-decomposition method requiring all elements be non-negative(33). Each

reduced dimension, or component, identified in NMF can be interpreted as a specific combination

of input features representing distinct sources of variance in the data(34). The components then

sum to represent the original data, rather than canceling variables (using negativity) to achieve a

geometrically strict representation(36). Mathematically, NMF decomposes an original matrix X

into two constituent, lower rank, matrices W and H, given by:

107
$$X = WH$$

(Eq. 1)

with the aim of iteratively updating W and H to minimize an objective function so that the product

of the two deconstructed matrices optimally reconstructs the original(33). Here, X is a column-

wise representation of the data (e.g., each column is the time-series fluorescent activity of a

neuron), that is decomposed into two lower rank matrices, W and H. For NMF, W can be

interpreted as a feature matrix, each vector representing a distinct pattern in the input data, and

H interpreted as a coefficient matrix, representing the contribution of each feature vector to each

point in the original matrix. When using DR for analyses, especially in the context of neural

recordings, the underlying assumption is that the original matrix can be decomposed into a lower

rank series of matrices. The rank, k, should be significantly smaller than n (k << n), the number

of neurons recorded, while still recapturing a majority of the variance present in the data(37).

Model performance can be assessed by the variance explained as represented by the coefficient

of determination (R^2)(38), given by:

$$R^2 = 1 - \frac{SS_{res}}{SS_{tot}},$$

where,

$$SS_{res} = \sum_{i,j} (X_{i,j} - (WH)_{i,j})^2 \, ,$$

$$SS_{tot} = \sum_{i,j} (X_{i,j} - \overline{X})^2 \, .$$

Thus, the model captures the original data perfectly in the limit as R^2 approaches one. R^2

increases as components are added, because the rank of the two constituent matrices are

increasing. Akaike Information Criterion (AIC) has been adapted for NMF to inform the rank to

which the dimensionality should be reduced(34,39), with the optimal model minimizing it(40); for

our implementation of NMF:

$$AIC = 2(\frac{R^2}{\sigma^2} + k(n + t))$$

Where R^2 is the reconstruction error defined in Eq. 2, σ^2 is the estimated variance of the data set,

k is the number of components the model is decomposing into, n is the number of neurons in the

recording, and t is the number of time points in each of the time series being decomposed. For

our analysis, we interpret each row of H as a sub-network, with each entry of that row as a

neuron's contribution of to that sub-network. Each column of W is then interpreted as the time-

series for that sub-network. We provide the pseudocode from an implementation of the NMF

analysis pipeline:

Input: X [time points x neurons]

Output: NMF_model

1:   normalize data between (0,1)*

2:   initialize list of AICs

3:   for i in range(1, num_neurons)

4:       W, H = init_WH(n_components = i)

5:       NMF_model = optimize(X, W, H)

6:       AIC_list.append(NMF_model.aic)

7:       if AIC[i-1] < AIC[i]:

8:               n_components = i-1

9:               break

10: W,H = init_WH(n_components = n_components)

11: NMF_model = optimize(X,W,H)

* we normalize using the global maximum and minimum of the trace set to preserve the relative difference

between them

The above pipeline describes the sequence of using AIC to find an optimal number of

components, and then fit a model to that number of components. Our implementation of NMF is

a modification of the implementation found in Python's Scikit-Learn package(41). We manually

initialize W and H, as opposed to the automated method found in the package, due to the wide

variety of initialization methods possible for NMF(42,43), and to maintain consistent, precise, and

easily reproduceable control over the initial conditions of our models. For the analyses found in

this paper, we apply non-negative dual singular value decomposition (nndsvd), a consistent and

efficient initialization method(44).

Principal Component Analysis (PCA):

We implement PCA because of its widespread use in neural data analysis(12,18,29–31,45–47).

PCA, efficiently calculated by a Singular Value Decomposition (SVD)(36):

$$X = U\Sigma V^T$$

where X is a column-wise representation of our data (i.e., each column is the time-series fluorescent activity of a neuron, assumed to have zero mean) decomposed into U, Σ, and V^T. V^T is the set of basis or singular vectors, also referred to as the principal components (PCs) of the original matrix, where each row of this matrix is a component of the data. Further, each of the PCs are necessarily orthogonal to each other by construction. U is the projection of the original matrix X onto the principal components in V^T, and Σ is a matrix containing the singular values of X describing the magnitude of the transformation, ordered by decreasing singular values(36). The variance explained by a PC is the proportion of its singular value compared to the sum of all singular values. For our analysis, we interpret each PC as a sub-network or prevalent pattern of activity, with each entry of the PC being a neuron's weight or contribution to that PC. We then interpret the projection of the data onto each PC as the activity or time series of that sub-network, attributing the dominance of that sub-network to the variance explained. Our implementation of PCA is a modification of the implementation found in Python's Scikit-Learn package(41). We provide the pseudocode from an implementation of the PCA pipeline below:

Input: X [time points x neurons]

Output: PCA_model

1: normalize data between (0,1)*

2: subtract mean of each time series

3: PCA_model = PCA(X) #data must be in column-format at this step.

* we normalize using the global maximum and minimum of the trace set to preserve the relative difference

between them

This is a modification of the implementation of PCA found in sklearn(41). PCA calls for every

variable, or trace in our case, to be centered about zero(36). However, we remove the uniform

normalization from sklearn's implementation to allow for finer tuning of data normalization before

decomposition with the model.

Independent Component Analysis (ICA):

We implement ICA because of its ability to extract independent sources from complex signals,

which could help separate overlapping patterns of neural activity in a single calcium recording.

While ICA has been used for automated trace extraction in calcium recordings(48), this

approach has seen limited application in the further analyses of neural signals estimated

calcium recordings. ICA is a statistical technique that aims to decompose a multivariate signal

into statistically independent components(49), rather than a set of orthogonal components, as

found in PCA. ICA operates under the assumption that k independent sources produce the data,

and that the data are a linear mixture of these underlying sources. ICA assumes the data to be

a linear mixture of sources:

206
$$x = As$$

(Eq. 8)

where x is the original data, s are the underlying independent sources, and A is a mixing matrix

that mixes the components of the sources(49).

In practice, the independent sources found in s, are decomposed using an unmixing matrix, W,

such that the linear transformation of the data by W, estimates the underlying independent

sources(49):

213
$$\hat{s} = Wx$$

Given that W transforms x to estimate the independent sources, we interpret the components of

W as the contribution of each neuron to the sub-network activities, which are the independent

sources in s. Here, we interpret the s independent sources as the underlying patterns of activity

of each sub-network that drive the observed dynamics. Like PCA, ICA assumes that inputs are

zero mean. While PCA is designed to maximize the variance of the data along the principal

components(36), ICA attempts to separate the data into k independent sources. We use the

fastICA implementation found in sklearn(41), and provide the pseudocode from an

implementation of the ICA analysis pipeline below:

Input: X [time points x neurons]

Output: ICA_model (contains A, s, amongst other information)

1: normalize data between (0,1)*

2: subtract mean of each time series

3: ICA_model = ICA(X)

* we normalize using the global maximum and minimum of the trace set to preserve the relative difference

between them

While ICA calls for unit variance for each of the features, which in this case would be the

calcium time series, we maintain the relative difference in variance between each neuronal time

series to maintain the relative difference in activity recorded as a function of the fluorescence.

Uniform Manifold-Approximation Projection (UMAP):

We implement UMAP because of its increasing use to analyze life science data(50,51) and its

ability to capture non-linear relationships. UMAP has been shown to capture complex patterns

to visualize and cluster data in very low dimensions(52), though the technique remains untested

on calcium recordings. Briefly, UMAP aims to optimize between preserving local and global

structures, where structure is local between neighboring points and global between data points

extending beyond the neighborhood. In neuronal calcium imaging, "neighborhood" refers to

local relationships among neurons with similar activity patterns at a time point, while global

relationships extend beyond those neighbors at the same point. UMAP subsequently directly

maps this structure to a lower dimension(52), resulting in the output being a single matrix (the

equivalent of H, V^T, and S), and not a product of matrices. Therefore, UMAP does not provide

temporal information about the activity of the lower dimensional patterns or sub-networks.

Further, there is no well-established way to quantify variance explained in UMAP as in the other

linear methods. We use the python package UMAP-learn to implement UMAP, and provide the

pseudocode from an implementation of the UMAP analysis pipeline below:

Input: X [neurons x time points] (NOTE TRANSPOSITION FOR THIS CASE, COMPARATIVELY)

Output: UMAP_model (contains low_d_projection, amongst other information)

1:   normalize data between (0,1)*

2:   UMAP_model = UMAP(X)

* we normalize using the global maximum and minimum of the trace set to preserve the relative difference

between them

In addition to the number of components, k, being a manually set hyperparameter, the number

of points in the neighborhood is also manually set, in addition to the other 37 tunable

parameters in the package(52). Because our main objective is to identify how neurons group to

form sub-networks and shift as a function of experimental contexts, we apply UMAP to

decompose the data X into a *k x n* matrix. k is the number of components or subnetworks we

determine to decompose into, while n is the number of neurons, aiming to give a similar

representation to H, V^T, and S in our other methods.

Model	Variance Explained	Information Criterion	Neuronal Weights	Decomposed Activity
NMF	✓	✓	✓	✓
UMAP	X	X	✓	X
PCA	✓	X	✓	✓
ICA	X	X	✓	✓

Table 1: Model Attributes

<u>**Network Simulation Methods:**</u>

To assess performance of the DR methods, we implement two simulation paradigms. In each

paradigm, we simulate the spiking activity in a network of interconnected neurons and estimate

calcium imaging traces for each neuron. We then apply each DR approach to the simulated

calcium fluorescence data. We describe each simulation paradigm below.

Perfectly Intraconnected, Independent Nodes:

We first consider a network of 100 neurons organized into 5 independent nodes, each

consisting of 20 neurons. Neurons within the same node are perfectly connected, such that a

spike by any neuron in one node produces a spike in all other neurons in that node. Neurons in

different nodes are disconnected, such that activity in two neurons of different nodes are

independent (Fig. 2A). The activity of a single neuron is governed by a basic Poisson spike

generator(53), given by:

277
$$spike[t] = x_{rand} < r * dt$$

278
(Eq. 10)

where a neuron spikes at time t if x$_{rand}$ (uniform [0, 1]) is less than the product of the set firing

rate, r, and the time step, dt. We update this generator to include additional network effects, and

a refractory period. We represent the connectivity between neurons as an adjacency matrix A.

Within any node of 20 neurons, A is 1, while between nodes A is 0; we exclude self-connections

by setting the diagonal of A to 0. We also include a refractory period of duration q time steps,

such that after a spike a neuron is temporarily unable to generate a subsequent spike.

We simulate the spiking activity of a single neuron in this network n = {1,2, … N} as:

286
$$spike[t]_n = x_{rand} < \left(\frac{rk}{N} dt + A_{n \times N} * spikes[t-1]_{N \times 1}^{T} \right) * RS[t]_n$$

287   *(Eq. 11)*

where r = 3 is the set nominal rate, N = 100 is the total number of neurons, k = 5 is the number

of nodes, and dt is the time step. A is the adjacency matrix of dimensions N x N, where each

row represents the incoming connections to a neuron, and each column represents the outgoing

connections of a neuron, and $RS[t]_n = \{0,1\}$ is the refractory state of neuron n at time t. A

neuron spikes at time t if the randomly generated number x_{rand} (uniform [0,1]) is less than the

product in Eq. 11. We note that any multiplication of an adjacency of 1 to neuron n, in

conjunction with a spike at time t-1 will result in a spike at time t in neuron n, given the neuron n

is not in a refractory state. After simulating the network we convolve each spike train with a

calcium kernel(27,54) as described below. The result is a series of 100 fluorescent neuronal

activities (Fig. 2B), of which there are five groups of twenty that are perfectly correlated (Fig.

2C).

Random Process Propagation:

We generate a second simulation paradigm to more closely represent a physiologically relevant

dynamic in calcium fluorescence data: a small number of independent random spiking patterns

simultaneously driving calcium events in all neurons. To do so, we first simulate k = 5 independent

spiking patterns as,

$$process\ spike[t]_n = x_{rand} < r\ dt\ .$$

We then consider a population of N = 150 neurons that receive inputs from each of the underlying

spiking patters (Fig. 3A) weighted as follow: 20% of the neurons have weights uniformly

distributed between 0.2 and 1.0, and 80% of the neurons have weights exponentially distributed

(rate parameter $\lambda = 8.0472$) with maximum value of 0.2 (Figure 3B). In this way, most neurons

are connected with weights following an exponential distribution(55), and the few neurons with

strong weights drive a majority of the activity. The resulting adjacency matrix A between the k

spiking patterns and N neurons has dimensions k x N, where each element describes the weight

of the kth underlying process input to neuron n = {1, 2, … N}. We simulate each neuron's spike

train as:

$$neuron\ spike[t]_n = x_{rand} < (A_{n\ x\ k} * process\ spike[t-1]_{k\ x\ 1}) * RS_n$$

where n indicates the nth neuron, k indicates the kth underlying spike processes, and we include

a refractory period for each neuron. Doing so results in N = 150 neuronal spike trains. We

convolve the spike train of each neuron with the calcium kernel(27,54), resulting in simulated

calcium data similar to our in vivo recordings, mirroring: activity rate, activity distribution,

underlying macroscopic drivers, and calcium neuronal time series characteristics.

Calcium Kernel:

We convolve the simulated spike trains with the following calcium kernel to represent the

fluorescence recorded from the genetically encoded calcium (GECI) kernel jGCaMP7f:

$$[Ca^{+2}]_t - [Ca^{+2}]_{t-1} = -\frac{dt}{\tau}([Ca^{+2}]_{t-1} - [Ca^{+2}]_b) + A * spike[t] + \sigma_c \sqrt{dt}\, \epsilon_t$$

(Eq. 14)

where $Ca^{+2}_{t,t-1,b}$ are the calcium concentrations at t, t-1, and the baseline, respectively. Here, dt is

the time step, τ is the time constant of the GECI, σ_c is the variance of the calcium noise, and ϵ_t is

a random variable following the standard gaussian distribution. We then calculate the

fluorescence as:

$$F_t = \alpha([Ca^{+2}]_t) + \beta + \sigma_F \epsilon_t \; ,$$

(Eq. 15)

where F_t is the fluorescence at time t, α is the intensity, β is the bias, σ_F is the variance of the

calcium noise, and ϵ_t is a random variable following the standard gaussian distribution. We set τ

to 0.265 and σ_c to 0.5 to match the kinetics of jGCaMP7f(56). We set the calcium baseline to 0.1,

A and α to 5, β to 10, and σ_F to 1(27).

Component Assignment Success

Perfectly Connected, Intraconnected Nodes:

To assess whether nodes were successfully assigned to components, we develop a framework

for each of our generated network architectures. For the nodal model, we begin by summing the

weights for each node, in each of the decomposed components, described by the pseudocode

below:

Input: H (matrix of neuronal weights), nodes (array detailing which neurons belong to each node)

Output: aggregated_weight_matrix

1: aggregated_weight_matrix = zeros(num_nodes, num_components)

2: for i in range(num_nodes)

3:        for j in range(num_compnents)

4:             aggregated_weight_matrix [i, j] = sum(H [nodes[i] , j)

The result is a five by five matrix, where the element [i , j] is the sum of the weights for neurons

in the ith node for the jth component. To then determine success of prediction, we establish two

conditions that must be met. First, within a particular component, the sum of weights for the

node with the highest value should exceed the sums of weights for all other nodes within the

same component. Second, this highest sum should also be the greatest for the node, across all

components. By applying these conditions, we can assess the assignment for each node

individually. In essence, once we obtain the aggregated weight matrix, an ideal model would

exhibit the same element as the maximum value for each row and column.

Random Process Propagation:

We calculate a 5 x 5 correlation matrix between the weights in each of the 5 components and

the connection probabilities from each of the 5 generated random processes sampled from the

defined exponential distribution. To assess assignment, we again consider two conditions. First,

for a chosen component, the highest correlation with the connection probabilities from one

random process should surpass the correlation to the other random processes in the same

component. Second, this highest correlation within each component should identify a different

random process; i.e., each component should identify a unique random process. We consider a

component successfully assigned to one of the five random processes if its highest correlation

is more correlated with that process than the other four processes.

Awake-State Data:

To investigate the application of each DR technique to *in vivo* recordings, we also consider

calcium imaging data recorded from 36 awake mice. Briefly, recordings in layer 2/3 of murine

S1(57) were collected during the awake, resting state(8). Traces representing calcium transients

were extracted from the recordings and processed using standard techniques (58).

Results

We test NMF against three existing DR approaches in common use: UMAP, PCA, and ICA. We

do so using two different simulated neuronal network architectures to assess the relative

performance of each DR approach, when the network structure is known. We first build a simple

network with five groups of independent neurons, each with 20 neurons, in which the neurons in

each independent node are perfectly connected (Fig. 2). In this architecture, a spike in one neuron

in a node will drive all other neurons in that node to spike. We use such an architecture to test if,

and how well, models can identify the five nodes given traces of simulated activity.

To further evaluate the performance between DR methods, we examine a more intricate network

architecture aligned with our spontaneous calcium recordings. In doing so, we create five distinct

random processes driving 150 neurons at varying degrees of strength (Fig. 3). This approach

better reflects the dynamics we aim to capture, encompassing underlying activity patterns in

diverse contexts driven by weighted sub-networks of neurons. Utilizing this surrogate architecture,

our objective is to assess how effectively the models can extract both the underlying activity

patterns, and the corresponding contributions by individual neurons, given a clear end target for

performance assessment. We present two different analyses for both simulated network

architectures. We both perform a qualitative analysis for a single generated network, and a more

scaled quantitative approach for a series of 256 random instantiations and simulations of the

networks. We find that NMF best captures the dynamics of the simulated networks, with

components summing to provide an accurate macroscopic low dimensional representation of the

data. We argue the parts-based representation provided inherently by NMF supports the

improved performance for these data and the goal of interpretably extracting low dimensional

neuronal network dynamics.

Perfectly Intraconnected, Independent Nodes:

We generate the nodal networks and fit each of the DR methods to the simulated calcium traces. Initially, we evaluate the average variance explained and the AIC across 256 networks to gauge how well the models capture the original data at different lower dimensionality levels. Both NMF and PCA exhibit similar variance explanation patterns across all components, with the average variance explained stabilizing at five components (Fig. 4A, left axis), as required to capture the dynamics of simulated activity in five nodes. This stabilization is influenced by the introduction of unique noise increments in each trace (Eq. 14 & Eq. 15). Additionally, the AIC for the NMF method consistently minimizes at five components across all 256 model instantiations, effectively optimizing for the correct number of nodes (Fig. 4A, right axis).

To evaluate how the different approaches capture the independent nodes of activity as components, we devised a discrete metric to determine success or failure of individual node assignment to components, detailed in the methods, for each architecture. We show the assignment success for a single model for each of the detailed DR methods (Fig. 4B). We find the best performance with the NMF method, which successfully maps each node to a component, followed by PCA, ICA, and UMAP. We repeat this process for 256 replicate models (Fig. 4E) and find that NMF always maps each node to a separate component, followed by PCA which performs with a mean accuracy of 0.8578, and then ICA and UMAP which perform with mean accuracies 0.6445 and 0.6242, respectively, and typically fail to successfully map the entire model.

We then visualize how each of the DR methods map the nodal patterns of activity to each of the components. We do so by showing the weight for each neuron, for each component, for each method, delimited by node (Fig. 4C), for a single instantiation of the simulated neural activity. In this example, we find a very clear separation of weights from each node for the NMF method; each component assigns weights to the neurons within a node. We argue this separation is a result of the parts-based representation that NMF inherently embodies(34). In a parts-based

representation, each component contributes an additive combination of components to faithfully

represent the original data. This means that NMF decomposes the overall activity into identifiable

parts, enabling a clear separation of weights for each node. Conversely, the PCA and ICA

methods produce distributions of node weights with less clear separations within a component.

While the first 5 components of the PCA method each identify neurons in each node, the

constraints of the method result in counterbalancing variables that obfuscate the underlying input

resulting in the data, hindering performance(36). UMAP poorly separates nodes into five

components because a strength of UMAP, and manifold learning in general (e.g., TSNE), is

visualization in very low dimensions (restricted to two or three dimensions)(24,25).

To provide a quantitative assessment of model performance, we calculate the average

displacement between neuronal weights assigned to a component and all other weights within

the same component, for all components of each of the 256 instantiations of the model (Fig. 4D).

We do so to provide a quantitative and continuous measurement of model performance

(separation between weights in node and not in node, at assigned component) beyond binary

success/failure, with the magnitude indicating the degree of separation between the neurons in

the assigned node and all other neurons within a given component. Normalized per model, a

positive value describes an assigned node whose average weight was higher than the weights of

the other node in that component. A negative value would then describe the opposite, with the

magnitude of the displacement describing the degree of difference between the weights. Our

findings reveal NMF best separates nodes into components, followed by PCA, UMAP, and ICA.

While this supports our finding that NMF specifically assigns patterns of nodal activity to

components, the other methods do tend to separate a majority of the nodes of neurons individually

in each component (the normalized distance tends to exceed 0), with the differing representations

being attributable to the different mathematical constraining during fitting (UMAP – very low

dimensional manifold, PCA – orthogonality, ICA – independence). However, as we show in our

next case, this structure breaks down on the introduction of more complicated data.

Random Process Propagation:

We simulate a network with a more complicated architecture to further evaluate model

performance. This architecture involves generating five underlying random processes to drive the

network activity. Each underlying random process provides input to each of 150 neurons, with a

weight randomly sampled from a generated exponential distribution (Fig. 3). By analyzing these

artificial networks, we aim to probe how well NMF maps the random process by observations from

the received neuronal inputs to components. We similarly aim to compare the performance and

low dimensional representation of NMF and the other methods we implement.

Analyzing the average variance explained for all 256 uniquely seeded networks of this

architecture, we find that NMF explains significantly more at all components (Fig. 5A, left axis).

We argue this is a function of the difference between optimizations. Rather than having a strict

orthogonality constraint between dimensions as in PCA, NMF aims to reconstruct the data with

as little error as possible into the specified number of dimensions, allowing for explaining more

variance with fewer components. The AIC shows a minimum at five components, the number of

random processes used to generate the network (Fig. 5A, right axis).

We quantify assignment success of this model differently from the nodal architecture, due to the

more continuous nature of the data, detailed in the methods. For or an example model

instantiation (Fig. 5B), only the NMF method successfully assigns each process to one

component. Assessing the performance over 256 realizations of the network (Fig 5F), we find that

NMF successfully assigns each random process to a component. Consistent with the results for

the nodal architecture, the other methods (PCA, ICA, and UMAP) have reduced performance. We

conclude that NMF reconstructs the latent network structure from the observed data, capturing

the five underlying random processes in a parts-based representation.

Beyond discrete prediction, we consider the correlation between the assigned connection

probabilities from the latent processes to the observed neurons, and the neuronal weights of the

predicted component. To start, we visualize the results for one instance of the NMF model, relating

the neuronal weights of each component to the assigned outgoing connection probability from the

assigned underlying random process to each neuron (Fig. 5C). We find that large neuronal

weights in each component tend to occur for large connection probabilities for the predicted

random process with a high correlation of 0.84 (Fig. 5D). Repeating this analysis for 256

realizations of the model, and regardless of prediction success, we find that NMF consistently

infers components with high correlations between the connection probabilities and weights (Fig.

5E). The other methods have reduced performance, consistent with the results for the nodal

architecture with PCA, ICA, and UMAP following in performance, respectively.

We finally analyze how the activity of each component correlates with the activity of the underlying

random process. Qualitatively, for a single realization of the model, the component activity

captures the underlying processes very well (Fig. 5G) with correlations between the activities

exceeding 0.85. Repeating this analysis across 256 realizations of the network, we once again

find that NMF best captures the activity of the latent input processes, followed by PCA and ICA

(Fig 5H); we note that UMAP does not estimate the times series of the latent processes.

We propose that the positivity and parts-based representation of the NMF method enable

accurate reconstruct of the high-dimensional activity through low dimensional inputs. We propose

that the constraints implemented by the PCA and ICA methods may obfuscate inputs to the

observed neural network in its low dimensional representations. Finally, we interpret the poor

performance of the UMAP method as indicating this method is better adapted for low dimensional

visualization of less variant data. We conclude that NMF accurately reconstructs the latent inputs

to a biophysically-motivated neuronal network that simulates calcium fluorescence recordings,

despite multiple barriers to accurate identification (e.g., the underlying process is unobserved,

with random connectivity to the observed neurons whose calcium signal is obfuscated with two

types of noise). These results demonstrate NMF outperforms existing methods in common use to

extract the underlying dynamics present in a series of neuronal activities recorded in calcium

imaging.

Awake-State Data:

As a final proof of concept, we analyze application of the DR methods to awake state calcium

imaging recordings from 36 mice. In doing so we apply the same analytical framework as for the

simulated data. Analysis of the variance explained for each model (Fig. 6A) shows similar

performance between the NMF and PCA methods, with a weak trend towards increased values

for the NMF method. This small advantage in increased variance explained may be due to the

NMF method acting to capture the original data as quickly as possible into a set number of

components (Eq. 2), rather than using a complex geometrical constraint to analyze the data(49).

We further find that NMF, using AIC, identifies an optimal number of components to describe the

data in each of the recordings (Fig. 6B), with number of neurons helping inform the number of

components at a correlation of 0.662. We qualitatively characterize an NMF model fit to a single

recording, using 18 components as determined by AIC. When characterizing the neuronal weights

estimated by the NMF method, we find behavior consistent with the simulated random process

network (Fig. 6C); the NMF method results in in the neuronal weights with an approximate

exponential distribution (Fig. 6D), with most neurons contributing little to the overall network

activity, and few neurons very significantly contributing. We further briefly characterize the

correlations between activity decomposed for each component (Fig. 6F). We find that correlations

are consistently low between the activity of the components. Given that the correlations are low,

and we capture a significant portion of the variance, we interpret these results to indicate that the

NMF, and the parts-based nature of the model, successfully extracts unique predominant patterns

of activity in the data. We conclude that, applied to these *in vivo* calcium imaging recordings, that

the NMF method identifies components with distinct (uncoupled) dynamics. While promising,

future work is required to relate these inferred components and dynamics to biological

mechanisms and behavior. We conclude that the NMF method is a promising tool to analyze

neuronal network dynamics and identify meaningly sub-network activity via a relatively simple and

interpretable approach.

<u>Discussion</u>

We have developed an analytical pipeline to more thoroughly model neuronal network dynamics

with NMF, considering all information provided by the model in its low dimensional representation.

We generate a series of calcium traces recorded from ground-truth artificial neuronal networks at

two degrees of complexity to assess how well our analyses extract the ground-truth responsible

for the simulated dynamics, and compare the performance of NMF to UMAP, PCA, and ICA. We

find the NMF significantly performs the best, followed by PCA, ICA, and UMAP, respectively. We

then apply our NMF pipeline to a series of in vivo baseline recordings and find that NMF confers

a similar, and easily interpretable representation to the underlying random process network.

We argue this performance is a result of the "parts-based representation" conferred by NMF(34).

Because every single element of the model is necessarily positive, and the decomposition is

aiming to recapture the original data, every component sums to give a low dimensional

macroscopic representation of the original data. Interpreting the decomposition as the sum of its

parts, rather than a complex cancelling of variables to achieve an algebraic constraint, as in

PCA(36), results in NMF being able to provide a better representation of the dynamics. Further,

the only fundamental assumption made in NMF is that the data can be represented exclusively

as positive values. Our other methods require more stringent assumptions. UMAP makes the

assumption that the data can be embedded on a low-dimensional manifold(52).   While very

advantageous in less variant data (large scale trial averaged electrophysiological recordings(51)),

we argue our data is far too variant with limited scalability (single trial, single recording) for this

method to be as effective. ICA assumes that components are both non-normal, and

independent(49). While the assumption of non-normality of traces, variables, is a positive feature

given that calcium traces are clearly non-normal data, we argue it is unfair to assume sub-network

dynamics are completely independent of each other. Finally, PCA assumes the data is best

described by the eigenvectors of the covariance matrix(36). We note that this algebraic constraint

does provide PCA the unique attribute of the model being the same for the first i components,

regardless of the number of components fit. NMF, UMAP, AND ICA will differ in their

representation of the data, dependent on the number of components fit too. As a result, PCA is

guaranteed to perfectly lossless in an inverse transformation of the data, given all components.

However, PCA is clearly less efficient than NMF in generating compact descriptions of data like

ours.

This pipeline was developed with the intent of analyzing state dependent neuronal network

dynamics, and future work will analyze differential network dynamics that arise from unique

experimental contexts. However, NMF, and other DR methods, require an underlying structure in

the data and can be especially sensitive to potential extremes in the number of components and

rates of activity in the network. An extreme sparsity or extreme saturation of events will lead to a

much noisier representation in the model. Further, a fundamental assumption of DR is that the

data can be represented with significantly fewer components than there are neurons(9). Data that

would carry hundreds of underlying drivers of activity (or any case where the number of patterns

approach the number of neurons) would be obfuscated in a model such as this. This analysis is

able to go beyond summary statistics, providing a low dimensional representation of dynamics

while still considering the activities of each neuron. Therefore, this approach will enable more

sophisticated and nuanced analysis of different states of neuronal networks, and how they shift

as a function of context.

In sum, NMF provides a superior method for the holistic analysis of network dynamics recorded

in calcium imaging. The mathematical constraints required by NMF, linearity and positivity,

complement the nature of fluorescent recording and neuronal activities well. Further, the parts-

based nature of NMF provides a simple and interpretable representation of sub-networks of

activity summing to drive macroscopic dynamics. As a result, we have developed an NMF pipeline

to be an exceptionally valuable tool for elegantly demystifying shifting neuronal network dynamics.

Acknowledgements

We thank Professor Chandramouli Chandrasekaran for providing a significant amount of the

motivation for this research. We further thank Dr. Jacob F. Norman and Dr. Fernando R.

Fernandez for their feedback and guidance in the development of this research. Research

reported in this publication was supported by the National Institute Of Mental Health of the

National Institutes of Health (F31MH133306 to DC, R01MH085074 to JW). The content is solely

the responsibility of the authors and does not necessarily represent the official views of the

National Institutes of Health. Further, this research was partially supported by NIH Translational

Research in Biomaterials Training Grant: T32 EB006359.

584
585 **Fig. 1. Representative Model Pipeline. A)** Recording Field of View (FOV) with detected

586 Regions of Interest (ROIs). **B)** Extracted fluorescent activity traces from ROIs. **C)** Same

587 recording FOV shown in A) with ROIs colored according to largest component contribution. **D)**

588 Decomposed activities of the components shown in C). **E)** Sample truncated heatmap showing

589 neuronal contribution or weight for each component.

590
591   **Fig. 2. Nodal Network Architecture. A)** Diagram showing perfect intraconnection between

592   neurons and independence between nodes. **B)** Randomly selected calcium traces generated by

593   the network. **C)** Same randomly selected calcium traces shown in B), but sorted according to

594   node.

595
Fig. 3. Artificial Random Propagating Process Network Architecture. A) Sample connection

diagram showing all random processes projecting to all neurons. **B)** Single histogram of

generated connections between processes and neurons from sampled distribution.

Fig. 4. Artificial Nodal Network Analysis. A) Variance Explained for NMF and PCA, left axis

(n = 256 networks) per component added to the model, and Akaike Information Criterion (AIC)

for NMF, right axis (n = 256 networks). **B)** Prediction visualization between nodes and

components for single network. **C)** Neuronal weights (y axis) for each model (panel) for each

node (color) for each component (x axis). **D)** Average between neurons inside and outside

predicted nodes for each component (n = 256 networks). **E)** Model assignment accuracy (n =

256 networks).

Fig. 5. Artificial Random Propagating Process Network Analysis. A) Variance Explained for

NMF and PCA, left axis (n = 256 networks) per component added to the model, and Akaike

Information Criterion (AIC) for NMF, right axis (n = 256 networks). **B)** Assignment visualization

between nodes and components for single network. **C)** Neuronal weights for NMF model (y

axis) for each component (x axis) compared to assigned connection probabilities (color scale)

for the predicted random process. **D)** Correlation between neuronal weights for NMF model (y

axis) and the respective assigned connection probability (x axis). **E)** Average Correlation

between neuronal weights for model and the respective assigned connection probabilities (n =

256 networks). **F)** Model assignment accuracy (n = 256 networks). **G)** Correlation between

component activity from NMF model and assigned random process activity. **H)** Correlations

between component activity from model and assigned random process activity (n = 256

networks).

Fig. 6. Baseline Awake State Network Analysis A) Variance Explained for NMF and PCA, left

axis (n = 36 mice) per component added to the model, and Akaike Information Criterion (AIC)

for NMF, right axis (n = 36 mice). **B)** Correlation between number of neurons (x axis) and

number of optimized components (y axis) (n = 36 mice). **C)** Neuronal weights for NMF model (y

axis) for each component (x axis) for a single mouse. **D)** Neuronal weight histogram from NMF

model for the same mouse as C). **E)** Component activity for NMF model of the same mouse as

in C) and D). **F)** Pairwise correlations between component activities shown in E).

References:

1. Pnevmatikakis EA. Analysis pipelines for calcium imaging data. Curr Opin Neurobiol. 2019 Apr;55:15–21.

2. Stevenson IH, Kording KP. How advances in neural recording affect data analysis. Nat Neurosci. 2011 Feb;14(2):139–42.

3. Stringer C, Pachitariu M. Computational processing of neural recordings from calcium imaging data. Curr Opin Neurobiol. 2019 Apr;55:22–31.

4. Birkner A, Tischbirek CH, Konnerth A. Improved deep two-photon calcium imaging in vivo. Cell Calcium. 2017 Jun;64:29–35.

5. Tonegawa S, Liu X, Ramirez S, Redondo R. Memory Engram Cells Have Come of Age. Neuron. 2015;87(5):918–31.

6. Josselyn SA, Tonegawa S. Memory engrams: Recalling the past and imagining the future. Science. 2020;367(6473).

7. Kitamura T, Ogawa SK, Roy DS, Okuyama T, Morrissey MD, Smith LM, et al. Engrams and circuits crucial for Systems Consolidation of a Memory. Science. 2017;78(April):73–8.

8. Norman JF, Rahsepar B, Noueihed J, White JA. Determining the optimal expression method for dual-color imaging. J Neurosci Methods. 2021 Mar;351:109064.

9. Cunningham JP, Yu BM. Dimensionality reduction for large-scale neural recordings. Nat Neurosci. 2014 Nov;17(11):1500–9.

10. Sanger TD, Kalaska JF. Crouching tiger, hidden dimensions. Nat Neurosci. 2014 Mar;17(3):338–40.

11. Géron A. Hands-on machine learning with Scikit-Learn, Keras, and TensorFlow: concepts, tools, and techniques to build intelligent systems. Second edition. Beijing [China] ; Sebastopol, CA: O'Reilly Media, Inc; 2019. 819 p.

12. Peyrache A, Benchenane K, Khamassi M, Wiener SI, Battaglia FP. Principal component analysis of ensemble recordings reveals cell assemblies at high temporal resolution. J Comput Neurosci. 2010 Aug;29(1–2):309–25.

13. Low RJ, Lewallen S, Aronov D, Nevers R, Tank DW. Probing variability in a cognitive map using manifold inference from neural dynamics [Internet]. Neuroscience; 2018 Sep [cited 2022 Oct 4]. Available from: http://biorxiv.org/lookup/doi/10.1101/418939

14. Giovannucci A, Friedrich J, Gunn P, Kalfon J, Brown BL, Koay SA, et al. CaImAn an open source tool for scalable calcium imaging data analysis. eLife. 2019 Jan 17;8:e38173.

15. Pnevmatikakis EA, Soudry D, Gao Y, Machado TA, Merel J, Pfau D, et al. Simultaneous Denoising, Deconvolution, and Demixing of Calcium Imaging Data. Neuron. 2016 Jan;89(2):285–99.

16. Pachitariu M, Stringer C, Dipoppa M, Schröder S, Rossi LF, Dalgleish H, et al. Suite2p: beyond 10,000
neurons with standard two-photon microscopy [Internet]. Neuroscience; 2016 Jun [cited 2022 Oct
4]. Available from: http://biorxiv.org/lookup/doi/10.1101/061507

17. Pnevmatikakis EA, Giovannucci A. NoRMCorre: An online algorithm for piecewise rigid motion
correction of calcium imaging data. J Neurosci Methods. 2017 Nov;291:83–94.

18. Romano SA, Pérez-Schuster V, Jouary A, Boulanger-Weill J, Candeo A, Pietri T, et al. An integrated
calcium imaging processing toolbox for the analysis of neuronal population dynamics. Graham LJ,
editor. PLOS Comput Biol. 2017 Jun 7;13(6):e1005526.

19. Batty E, Whiteway MR, Saxena S, Biderman D, Abe T, Musall S, et al. BehaveNet: nonlinear
embedding and Bayesian neural decoding of behavioral videos. :12.

20. Sotskov VP, Pospelov NA, Plusnin VV, Anokhin KV. Calcium Imaging Reveals Fast Tuning Dynamics of
Hippocampal Place Cells and CA1 Population Activity during Free Exploration Task in Mice. Int J Mol
Sci. 2022 Jan 7;23(2):638.

21. Rubin A, Sheintuch L, Brande-Eilat N, Pinchasof O, Rechavi Y, Geva N, et al. Revealing neural
correlates of behavior without behavioral measurements. Nat Commun. 2019 Dec;10(1):4745.

22. Driscoll LN, Pettit NL, Minderer M, Chettih SN, Harvey CD. Dynamic Reorganization of Neuronal
Activity Patterns in Parietal Cortex. Cell. 2017 Aug;170(5):986-999.e16.

23. Wenzel M, Han S, Smith EH, Hoel E, Greger B, House PA, et al. Reduced Repertoire of Cortical
Microstates and Neuronal Ensembles in Medically Induced Loss of Consciousness. Cell Syst. 2019
May;8(5):467-474.e4.

24. Anowar F, Sadaoui S, Selim B. Conceptual and empirical comparison of dimensionality reduction
algorithms (PCA, KPCA, LDA, MDS, SVD, LLE, ISOMAP, LE, ICA, t-SNE). Comput Sci Rev. 2021
May;40:100378.

25. Izenman AJ. Introduction to manifold learning: Introduction to manifold learning. Wiley Interdiscip
Rev Comput Stat. 2012 Sep;4(5):439–46.

26. Ghandour K, Ohkawa N, Fung CCA, Asai H, Saitoh Y, Takekawa T, et al. Orchestrated ensemble
activities constitute a hippocampal memory engram. Nat Commun. 2019 Dec;10(1):2637.

27. Nagayama M, Aritake T, Hino H, Kanda T, Miyazaki T, Yanagisawa M, et al. Detecting cell assemblies
by NMF-based clustering from calcium imaging data. Neural Netw. 2022 May;149:29–39.

28. Nagayama M, Aritake T, Hino H, Kanda T, Miyazaki T, Yanagisawa M, et al. Sleep State Analysis Using
Calcium Imaging Data by Non-negative Matrix Factorization. In: Tetko IV, Kůrková V, Karpov P, Theis
F, editors. Artificial Neural Networks and Machine Learning – ICANN 2019: Theoretical Neural
Computation [Internet]. Cham: Springer International Publishing; 2019 [cited 2022 Oct 4]. p. 102–
13. (Lecture Notes in Computer Science; vol. 11727). Available from:
http://link.springer.com/10.1007/978-3-030-30487-4_8

29. Briggman KL, Abarbanel HDI, Kristan WB. Optical Imaging of Neuronal Populations During Decision-
Making. Science. 2005 Feb 11;307(5711):896–901.

30. Ahrens MB, Li JM, Orger MB, Robson DN, Schier AF, Engert F, et al. Brain-wide neuronal dynamics
during motor adaptation in zebrafish. Nature. 2012 May;485(7399):471–7.

31. Morcos AS, Harvey CD. History-dependent variability in population dynamics during evidence
accumulation in cortex. Nat Neurosci. 2016 Dec;19(12):1672–81.

32. Makino H, Ren C, Liu H, Kim AN, Kondapaneni N, Liu X, et al. Transformation of Cortex-wide
Emergent Properties during Motor Learning. Neuron. 2017 May;94(4):880-890.e8.

33. Lee DD, Seung HS. Learning the parts of objects by non-negative matrix factorization. Nature. 1999
Oct;401(6755):788–91.

34. Devarajan K. Nonnegative Matrix Factorization: An Analytical and Interpretive Tool in
Computational Biology. PLoS Comput Biol. 2008;4(7):12.

35. Miyazaki T, Kanda T, Tsujino N, Ishii R, Nakatsuka D, Kizuka M, et al. Dynamics of Cortical Local
Connectivity during Sleep–Wake States and the Homeostatic Process. Cereb Cortex. 2020 Jun
1;30(7):3977–90.

36. Shlens J. A Tutorial on Principal Component Analysis [Internet]. arXiv; 2014 [cited 2022 Oct 4].
Available from: http://arxiv.org/abs/1404.1100

37. Cunningham JP, Ghahramani Z. Linear Dimensionality Reduction: Survey, Insights, and
Generalizations. :42.

38. Roh J, Cheung VCK, Bizzi E. Modules in the brain stem and spinal cord underlying motor behaviors. J
Neurophysiol. 2011 Sep;106(3):1363–78.

39. Cheung VCK, Devarajan K, Severini G, Turolla A, Bonato P. Decomposing time series data by a non-
negative matrix factorization algorithm with temporally constrained coefficients. In: 2015 37th
Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)
[Internet]. Milan: IEEE; 2015 [cited 2022 Oct 4]. p. 3496–9. Available from:
http://ieeexplore.ieee.org/document/7319146/

40. Akaike H. Information Theory and an Extension of the Maximum Likelihood Principle. In: Parzen E,
Tanabe K, Kitagawa G, editors. Selected Papers of Hirotugu Akaike [Internet]. New York, NY:
Springer New York; 1998 [cited 2023 Apr 20]. p. 199–213. (Springer Series in Statistics). Available
from: http://link.springer.com/10.1007/978-1-4612-1694-0_15

41. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine
Learning in Python. J Mach Learn Res. :6.

42. Esposito F. A Review on Initialization Methods for Nonnegative Matrix Factorization: Towards Omics
Data Experiments. Mathematics. 2021 Apr 29;9(9):1006.

43. Hafshejani SF, Moaberfard Z. Initialization for Nonnegative Matrix Factorization: a Comprehensive
Review [Internet]. arXiv; 2021 [cited 2022 Oct 4]. Available from: http://arxiv.org/abs/2109.03874

44. Boutsidis C, Gallopoulos E. SVD based initialization: A head start for nonnegative matrix
factorization. Pattern Recognit. 2008 Apr;41(4):1350–62.

45. Harvey CD, Coen P, Tank DW. Choice-specific sequences in parietal cortex during a virtual-navigation
decision task. Nature. 2012 Apr;484(7392):62–8.

46. Kato HK, Chu MW, Isaacson JS, Komiyama T. Dynamic Sensory Representations in the Olfactory
Bulb: Modulation by Wakefulness and Experience. Neuron. 2012 Dec;76(5):962–75.

47. Awal MR, Wirak GS, Gabel CV, Connor CW. Collapse of Global Neuronal States in *Caenorhabditis
elegans* under Isoflurane Anesthesia. Anesthesiology. 2020 Jul 1;133(1):133–44.

48. Mukamel EA, Nimmerjahn A, Schnitzer MJ. Automated Analysis of Cellular Signals from Large-Scale
Calcium Imaging Data. Neuron. 2009 Sep;63(6):747–60.

49. Shlens J. A Tutorial on Independent Component Analysis [Internet]. arXiv; 2014 [cited 2023 Feb 25].
Available from: http://arxiv.org/abs/1404.2986

50. Cid E, Marquez-Galera A, Valero M, Gal B, Medeiros DC, Navarron CM, et al. Sublayer- and cell-type-
specific neurodegenerative transcriptional trajectories in hippocampal sclerosis. Cell Rep. 2021
Jun;35(10):109229.

51. Lee EK, Balasubramanian H, Tsolias A, Anakwe SU, Medalla M, Shenoy KV, et al. Non-linear
dimensionality reduction on extracellular waveforms reveals cell type diversity in premotor cortex.
eLife. 2021 Aug 6;10:e67490.

52. McInnes L, Healy J, Melville J. UMAP: Uniform Manifold Approximation and Projection for
Dimension Reduction [Internet]. arXiv; 2020 [cited 2022 Nov 2]. Available from:
http://arxiv.org/abs/1802.03426

53. Dayan P, Abbott LF, Abbott LF. Theoretical neuroscience: computational and mathematical
modeling of neural systems. First paperback ed. Cambridge, Mass.: MIT Press; 2005. 460 p.
(Computational neuroscience).

54. Vogelstein JT, Watson BO, Packer AM, Yuste R, Jedynak B, Paninski L. Spike Inference from Calcium
Imaging Using Sequential Monte Carlo Methods. Biophys J. 2009 Jul;97(2):636–55.

55. Song S, Sjöström PJ, Reigl M, Nelson S, Chklovskii DB. Highly Nonrandom Features of Synaptic
Connectivity in Local Cortical Circuits. Friston KJ, editor. PLoS Biol. 2005 Mar 1;3(3):e68.

56. Dana H, Sun Y, Mohar B, Hulse BK, Kerlin AM, Hasseman JP, et al. High-performance calcium sensors
for imaging activity in neuronal populations and microcompartments. Nat Methods. 2019
Jul;16(7):649–57.

57. Noueihed J. Balance of Excitation and Inhibition in the Primary Somatosensory Cortex Layer 2/3
Under Isoflurane Anesthesia (Submitted).

58. Noueihed J. Multisession Processing of Multiphoton Calcium Imaging (Submitted).