vcfpp: a C++ API for rapid processing of the Variant Call Format

Zilong Li

Abstract

Given the widespread use of the variant call format (VCF/BCF) coupled with continuous surge in big data, there remains a perpetual demand for fast and flexible methods to manipulate these comprehensive formats across various programming languages. Many bioinformatic tools were developed in C++ to ensure high performance and modern C++ standards offer an ever expanding libraries to ease program development. This work presents `vcfpp`, a C++ API of `HTSlib` in a single file, providing an intuitive interface to manipulate VCF/BCF files rapidly and safely, in addition to being portable. Moreover, this work introduces the `vcfppR` package to demonstrate the development of a high performance R package with `vcfpp`, allowing for rapid and straightforward variants analyses. In the benchmarking, with the compressed VCF of 3202 samples and one million variants as input, the dynamic script using `vcfppR` is only $1.3\times$ slower than its compiled C++ counterpart `vcfpp`, whereas the Python API `cyvcf2` is $1.9\times$ slower when streaming a variant analysis with little memory. Lastly, in a two-step setting where the whole VCF content is loaded first, `vcfppR` demonstrates a $101\times$ speed improvement over `vcfR` and even more folds than `data.table` in processing genotypes.

Zilong Li: Section for Computational and RNA Biology, Department of Biology, University of Copenhagen. Email: zilong.dk@gamil.com.

Introduction

Computational biologists have made numerous efforts and contributions to facilitate analyses of genomic variants. The variant call format (VCF) has become the standard for storing genetic variant information consisting of detailed specifications (Danecek et al. 2011). With big data on the rise, the binary variant call format (BCF) was later designed to query and store large datasets efficiently. The C API of `HTSlib` (Bonfield et al. 2021) provides a full set of functionalities to manipulate the VCF/BCF for both compressed and uncompressed files. Given that the C API is challenging for less proficient programmers to use, APIs derived from other languages have been created to fill in the gap. Existing popular libraries include `vcfR` (Knaus et al. 2017) for R, `cyvcf2` (Pedersen et al. 2017) for Python, `hts-nim` (Pedersen et al. 2018) for Nim and `vcflib` (Garrison et al. 2022) for C++. All are valuable to each respective community, but not without their disadvantages. In particular, `vcflib` is both an API and a large collection of command line tools, with the primary pitfall being that it does not support the BCF format. It is noteworthy that many methods written in C++ designed for large sample size can not input the compressed VCF or BCF, as in the case of `Syllbable-PBWT` (Wang et al. 2023). The motivation behind `vcfpp` is to offer full functionalities as `HTSlib`, and provide a simple and safe API in a single header file, which can be easily integrated for programming in C++ as well as other languages that can call C/C++ codes, such as R and Python.

Methods

The VCF and HTSlib

A VCF file consists of a header section and a body section. The header contains lines with meta-information, each starting with characters "##" or "#", while the body consists of TAB-delimited lines. A VCF file differs from a typical TAB-delimited file in several ways. Firstly, the header is too important to be ignored. A VCF that contains a tag in the body without its declaration in the header violates the specification. Secondly, the VCF can be compressed and randomly accessed using `bgzip` and `tabix`, which were originally part of `SAMtools` library (Li et al. 2009) but were later separated into `HTSlib` (Bonfield et al. 2021). Additionally, the VCF standard is established and regularly updated by the `SAMtools` team. Therefore, it would be more advantageous to use a specialized library, namely `HTSlib`, to process the VCF rather than a customized parser. `HTSlib` offers full functionalities to interact with the VCF, including support for BCF, format

validation, compression, random access, identification of variant types, support for URL links as filenames, among others. Furthermore, `HTSlib` has demonstrated the best performance among many competitors (Bonfield et al. 2021). However, `HTSlib` was written in C language, which can be challenging for beginner programmers to use, especially when it comes to memory management.

A C++ API

As a C++ API of `HTSlib`, `vcfpp` inherits all functionalities from `HTSlib` and is implemented in a single header file that can be easily integrated and used safely. There are four core classes in `vcfpp`, as summarized in Table 1, all of which allocate and free memory automatically and safely, enabling users to program with ease.

TABLE 1. vcfpp capabilities and implemented C++ class

Class	Capability
BcfReader	read VCF/BCF, decompression, random access, subset samples
BcfWriter	output VCF/BCF, compression
BcfRecord	access the fields, modify the fields
BcfHeader	access the header, modify the header

To illustrate commonly used features and demonstrate the simplicity of `vcfpp`, here I showcase an example that will be used throughout the paper. In Listing 1, we count the number of heterozygous sites for each sample in a VCF file. The following code first includes a single `vcfpp.h` file (line 1), opens a compressed VCF file constrained to 3 samples and region "chr21" (line 2), and creates a variant record associated with the header information in the VCF file (line 3). Then it defines several types of objects to collect the results we want (line 4-5). Taking advantage of generic templates in C++, the genotype value can be of bool, char or int type so that users may control the memory consumed by their program. Then it iterates over the VCF file and processes each variant record in the loop (line 6). Here we ignore variants of other types (INDEL, SV), or if `FILTER` does not display "PASS", or if the `QUAL` value is smaller than 9 (line 8-9), though the API also allows us to do more complicated filtering should. Finally, we count the number of heterozygous variants for each diploid sample (line 10-11). The core is only 12 lines.

Listing 1. Counting the number of heterozygous genotypes for 3 samples on chr21

```cpp
#include <vcfpp.h>
vcfpp::BcfReader vcf("your.vcf.gz", "chr21", "id1,id2,id3");
vcfpp::BcfRecord var(vcf.header); // create a variant object
vector<int> gt; // genotype can be of bool, char or int type
vector<int> hets(vcf.nsamples, 0); // store the het counts
while(vcf.getNextVariant(var)){
  var.getGenotypes(gt);
  if(!var.isSNP()||var.QUAL()<9||var.FILTER()!="PASS")continue;
  assert(var.ploidy()==2); // make sure it is diploid
  for(int i=0; i<vcf.nsamples; i++)
    hets[i] += abs(gt[2*i+0] - gt[2*i+1])==1;
}
```

Results

To demonstrate the simplicity, portability and performance of `vcfpp`, the following sections include the benchmarking results and highlight the `vcfppR` package as an example of `vcfpp` working with R (R Core Team 2023).

Working with R

While `vcfpp` is very simple for writing a C++ program, a single C++ header file can be easily integrated into popular script languages like R and Python. Particularly, R is designed for statistical modeling and visualization, widely used for data analyses. Therefore, I developed the `vcfppR` package to demonstrate how `vcfpp` can seamlessly work with R using `Rcpp` (Eddelbuettel et al. 2011). For instance, with the basic familiarity of C++ and `Rcpp`, we can turn the C++ code in Listing 1 into an `Rcpp` function to return the heterozygosity counted per sample along with the sample's name (Listing 2), which can then be compiled and called dynamically in R using `sourceCpp` (Listing 3). As such, we can further process and visualize these results straightforwardly within the R ecosystem. For example, we can analyze the data by genomic region in parallel using the `parallel` package and then stratify the results by population, leveraging the external labels of each sample, to finally visualize them in R.

```
Listing 2. vcfpp-hets.cpp
#include <Rcpp.h>
#include <vcfpp.h>
using namespace Rcpp;
// [[Rcpp::export]]
List heterozygosity(std::string vcffile,
                    std::string region,
                    std::string samples) {
  vcfpp::BcfReader vcf(vcffile, region, samples);
  // here copy the lines 3-12 in listing 1.
  return List::create(Named("samples")=vcf.header.getSamples(),
                    Named("hets")=hets);
}
```

```
library(Rcpp)
sourceCpp("vcfpp-hets.cpp")
heterozygosity("bcf.gz", "chr21", "id1,id2,id3");
```

The vcfppR package

The `vcfppR` package is developed and powered by the `vcfpp` API. To parse the VCF with `vcfppR`, the `vcfreader` and `vcftable` functions can rapidly read contents of the VCF into the R data types with fine control over the region, samples, variant types, FORMAT column and filters. For instance, the code in Listing 4 parses the read depth per variant (DP) in the raw called VCF by the 1000 Genomes Project through the URL link. It restricts the analysis to 3 samples with variants in "chr21:1-10000000" region of SNP type, passing the FILTER, and discarding the INFO column in the returned list. Subsequently, the visual summary can be generated by using `boxplot()` in R (see Figure 1).

Listing 4. Example of vcfppR::vcftable

```
library(vcfppR)
vcffile <- "https://url-path"
vcf <- vcftable(vcffile, region="chr21:1-10000000", samples="
    NA12878,HG00118,HG00119", format="DP", vartype="snps", pass
    = TRUE, info = FALSE)
boxplot(vcf$DP, names=vcf$samples, ylab="Read␣Depth␣(DP)")
```

FIGURE 1. Analyzing variants discovered in the 1000 Genome Project with vcfppR (see code in supplementary).

Furthermore, as characterizing variants is an essential task in genomic analyses, I

showcase the `vcfsummary` function in Figure 1, which summarizes the variants found in the latest VCF released by the 1000 Genome Project (Byrska-Bishop et al. 2022).

Benchmarking

In addition to simplicity and portability, I showcase here the performance of `vcfpp` and `vcfppR`. For the benchmarking, I developed scripts (https://github.com/Zilong-Li/vcfpp/tree/main/scripts) to perform a common analysis of counting heterozygous genotypes per sample on a Linux server with AMD EPYC 7643 48-Core Processor. As shown in Table 2, when using the compressed (gzipped) VCF of 3202 samples and 1002753 variants, which includes only GT (genotype) in the FORMAT, the Rcpp function `vcfppR::heterozygosity` in Listing 2 demonstrates comparable performance to the compiled C++ code of `vcfpp` in Listing 1 with a minor overhead. This overhead is attributed to a list of sample names being returned to R. The dynamic script using `vcfppR::vcfreader` is only 1.3× slower than its compiled C++ counterpart, whereas the `cyvcf2::VCF` is 1.9× slower. With the streaming strategy, all scripts use little RAM, given that they only load one variant into memory at a time. However, R packages like `vcfR` and `data.table` usually load all VCF data into memory first and perform analyses later, which is referred here as the "two-step" strategy. To this end, I have also developed `vcftable` function in `vcfppR` to load the entire contents of the VCF into R for the two-step comparison. Notably, the `vcfppR::vcftable` is only 2.0× slower compared to the 19× slower `vcfR::read.vcfR` and the 119× slower `data.table::fread`. This discrepancy arises because the genotype values returned by both `vcfR` and `data.table` are characters, which are inefficient to further process in R. On the other hand, with `vcfppR`, an integer matrix of genotypes can be returned to R directly for fast computation. If we exclude the elapsed time of loading data, which means ignoring time marked by the *, then `vcfppR` demonstrates a 101× speed improvement over `vcfR`. Importantly, `vcfpp` and `vcfppR` offer users the full functionalities of `HTSlib`, including support for compressed VCF/BCF, selection of samples, regions, and variant types.

TABLE 2. Performance of counting heterozygous genotypes per sample with VCF of 3202 samples and 1002753 variants. * used by loading data in two-step strategy.

API/Function	Time (s)	Ratio	RAM (Gb)	Strategy
vcfpp	97	1.0	0.006	streaming
vcfppR::heterozygosity	109	1.1	0.074	streaming
vcfppR::vcfreader	150	1.3	0.136	streaming
cyvcf2::VCF	212	1.9	0.036	streaming
vcfppR::vcftable	206*+12	2.0	64.7	two-step
vcfR::read.vcfR	625*+1219	19.0	97.5	two-step
data.table::fread	313*+11243	119.1	77.3	two-step

Discussion

Here I have developed `vcfpp`, a fast and flexible C++ API for high-performance genetic variant analyses with the VCF/BCF input. Its simplicity and portability can be very valuable for both developing packages and writing in-house scripts. The `vcfppR` package is a great example of `vcfpp` working with R, and there are also examples of developing a Python API for `vcfpp` available on GitHub. In `vcfppR`, there are `vcfreader` and `vcftable` functions that can process the variants. The `vcftable` is specifically designed for reading the VCF into the tabular data structure in R, but it can only read a single FORMAT item in one pass over the VCF. In contrast, `vcfreader` serves as the full R-bindings of `vcfpp` and allows iterative parsing of variants, giving users the flexibility to decide the information to retrieve for each variant. As such, many packages written in C++ using a customized VCF parser can be simply replaced with `vcfpp` to offer more functionalities. For instance, `vcfpp` can be found successfully implemented in the imputation software programs STITCH (Davies, Flint, et al. 2016) and QUILT (Davies, Kucka, et al. 2021) to parse large reference panels in the compressed VCF/BCF.

Software and Code

The latest release of `vcfpp.h` and documentation can be found at https://github.com/Zilong-Li/vcfpp. The `vcfppR` package can be installed through CRAN for all platforms (https://CRAN.R-project.org/package=vcfppR). Scripts for the benchmarking are available at https://github.com/Zilong-Li/vcfpp/tree/main/scripts.

Acknowledgments

I would like to thank Anders Albrechtsen at Copenhagen University and Robert W Davies at Oxford University for their helpful comments. They are statisticians as well as R enthusiasts working on genetics, whom I work with and have learned a lot from. Also, I want to thank Cindy G. Santander and the reviewers for helping me to improve the quality of this article.

Funding

This work is supported by the Novo Nordisk 462 Foundation (NNF20OC0061343).

References

Bonfield, JK, J Marshall, P Danecek, H Li, V Ohan, A Whitwham, T Keane, and RM Davies (2021). "HTSlib: C library for reading/writing high-throughput sequencing data". In: *GigaScience* 10.2, giab007. DOI: 10.1093/gigascience/giab007.

Byrska-Bishop, M et al. (2022). "High-coverage whole-genome sequencing of the expanded 1000 Genomes Project cohort including 602 trios". In: *Cell* 185.18, 3426–3440.e19. DOI: 10.1016/j.cell.2022.08.004.

Danecek, P et al. (2011). "The variant call format and VCFtools". In: *Bioinformatics (Oxford, England)* 27.15, pp. 2156–2158. DOI: 10.1093/bioinformatics/btr330. pmid: 21653522.

Davies, RW, J Flint, S Myers, and R Mott (2016). "Rapid genotype imputation from sequence without reference panels". In: *Nature Genetics* 48.8, pp. 965–969. DOI: 10.1038/ng.3594. pmid: 27376236.

Davies, RW, M Kucka, D Su, S Shi, M Flanagan, CM Cunniff, YF Chan, and S Myers (2021). "Rapid genotype imputation from sequence with reference panels". In: *Nature Genetics* 53.7 (7), pp. 1104–1111. DOI: 10.1038/s41588-021-00877-0.

Eddelbuettel, D and R Francois (2011). "Rcpp: Seamless R and C++ Integration". In: *Journal of Statistical Software* 40, pp. 1–18. DOI: 10.18637/jss.v040.i08.

Garrison, E, ZN Kronenberg, ET Dawson, BS Pedersen, and P Prins (2022). "A spectrum of free software tools for processing the VCF variant call format: vcflib, bio-vcf, cyvcf2, hts-nim and slivar". In: *PLOS Computational Biology* 18.5, e1009123. DOI: 10.1371/journal.pcbi.1009123.

Knaus, BJ and NJ . Grünwald (2017). "vcfr: a package to manipulate and visualize variant call format data in R". In: *Molecular Ecology Resources* 17.1, pp. 44–53. DOI: 10.1111/1755-0998.12549.

Li, H, B Handsaker, A Wysoker, T Fennell, J Ruan, N Homer, G Marth, G Abecasis, R Durbin, and 1GPDP Subgroup (2009). "The Sequence Alignment/Map format and SAMtools". In: *Bioinformatics* 25.16, pp. 2078–2079. DOI: 10.1093/bioinformatics/btp352.

Pedersen, BS and AR Quinlan (2017). "cyvcf2: fast, flexible variant analysis with Python". In: *Bioinformatics* 33.12, pp. 1867–1869. DOI: 10.1093/bioinformatics/btx057.

Pedersen, BS and AR Quinlan (2018). "hts-nim: scripting high-performance genomic analyses". In: *Bioinformatics* 34.19, pp. 3387–3389. DOI: 10.1093/bioinformatics/bty358.

R Core Team (2023). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. Vienna, Austria.

Wang, V, A Naseri, S Zhang, and D Zhi (2023). "Syllable-PBWT for space-efficient haplotype long-match query". In: *Bioinformatics* 39.1. DOI: 10.1093/bioinformatics/btac734.

Supplementary

```r
library(vcfppR)
par(mfrow=c(1,3)) ## layout in plots
vcf <- vcftable(vcffile, region="chr21:1-10000000", samples="
    NA12878,HG00118,HG00119", format="DP", vartype="snps", pass
    = TRUE, info = FALSE)
boxplot(vcf$DP, names=vcf$samples, ylab="Read Depth (DP)")
svfile <- "https://ftp.1000genomes.ebi.ac.uk/vol1/ftp/data_
    collections/1000G_2504_high_coverage/working/20210124.SV_
    Illumina_Integration/1KGP_3202.gatksv_svtools_novelins.
    freeze_V3.wAF.vcf.gz"
sv <- vcfsummary(svfile, svtype = TRUE)
boxplot(sv[c("DEL","DUP", "CNV", "INS","INV","CPX","CTX")],
        main = "SVs per Genome stratified by SV types")
ped <- read.table("https://ftp.1000genomes.ebi.ac.uk/vol1/ftp/
    data_collections/1000G_2504_high_coverage/20130606_g1k_3202_
    samples_ped_population.txt", h=T)
ped <- ped[order(ped$Superpopulation),]
supers <- unique(ped$Superpopulation)
all <- parallel::mclapply(vcffiles, vcfsummary, pass = TRUE, mc
    .cores=23)
samples <- all[[1]]$samples
snps <- Reduce("+", lapply(all, "[[", "SNP"))
indels <- Reduce("+", lapply(all, "[[", "INDEL"))
o <- sapply(supers, function(pop) {
  id <- subset(ped, Superpopulation == pop)[,"SampleID"]
  ord <- match(id, samples)
  (snps[ord] + indels[ord]) / 1e6
})
boxplot(o, main = "SNP & INDEL with FILTER=PASS", ylab = "
    Number of variants per genome (in millions)")
```